



US011824042B2

(12) **United States Patent**  
**DeLaCruz et al.**

(10) **Patent No.:** **US 11,824,042 B2**  
(45) **Date of Patent:** **\*Nov. 21, 2023**

(54) **3D CHIP SHARING DATA BUS**

(56) **References Cited**

(71) Applicant: **Adeia Semiconductor Inc.**, San Jose, CA (US)

U.S. PATENT DOCUMENTS

5,016,138 A 5/1991 Woodman  
5,376,825 A 12/1994 Tukamoto et al.

(72) Inventors: **Javier A. DeLaCruz**, San Jose, CA (US); **Steven L. Teig**, Menlo Park, CA (US); **Ilyas Mohammed**, San Jose, CA (US)

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Xcelsis Corporation**, San Jose, CA (US)

CN 1175805 A 3/1998  
CN 101521194 A 9/2009

(Continued)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

This patent is subject to a terminal disclaimer.

He, Kaiming, Zhang, Xiangyu, Ren, Shaoqing, and Sun, Jian, "Delving deep into rectifiers: Surpassing human-level performance on imagenet classification," arXiv preprint arXiv: 1502.01852, 2015, pp. 1026-1034.

(Continued)

(21) Appl. No.: **17/105,272**

(22) Filed: **Nov. 25, 2020**

*Primary Examiner* — Brook Kebede

(74) *Attorney, Agent, or Firm* — HALEY GUILIANO LLP

(65) **Prior Publication Data**

US 2021/0202445 A1 Jul. 1, 2021

**Related U.S. Application Data**

(63) Continuation of application No. 16/806,854, filed on Mar. 2, 2020, now Pat. No. 10,892,252, which is a (Continued)

(57) **ABSTRACT**

Some embodiments of the invention provide a three-dimensional (3D) circuit that is formed by stacking two or more integrated circuit (IC) dies to at least partially overlap and to share one or more interconnect layers that distribute power, clock and/or data-bus signals. The shared interconnect layers include interconnect segments that carry power, clock and/or data-bus signals. In some embodiments, the shared interconnect layers are higher level interconnect layers (e.g., the top interconnect layer of each IC die). In some embodiments, the stacked IC dies of the 3D circuit include first and second IC dies. The first die includes a first semiconductor substrate and a first set of interconnect layers defined above the first semiconductor substrate. Similarly, the second IC die includes a second semiconductor substrate and a second set of interconnect layers defined above the second semiconductor substrate. As further described below, the first and second dies in some embodiments are placed in a face-to-

(Continued)

(51) **Int. Cl.**

**H01L 25/065** (2006.01)  
**H01L 23/00** (2006.01)

(Continued)

(52) **U.S. Cl.**


CPC ..... **H01L 25/0657** (2013.01); **H01L 21/8221** (2013.01); **H01L 23/49827** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC ..... H01L 21/8221; H01L 23/49827; H01L 23/50; H01L 23/5225; H01L 23/528;

(Continued)



face arrangement (e.g., a vertically stacked arrangement) that has the first and second set of interconnect layers facing each other. In some embodiments, a subset of one or more interconnect layers of the second set interconnect layers of the second die has interconnect wiring that carries power, clock and/or data-bus signals that are supplied to the first IC die.

**21 Claims, 25 Drawing Sheets**

**Related U.S. Application Data**

continuation of application No. 15/976,811, filed on May 10, 2018, now Pat. No. 10,580,757, and a continuation-in-part of application No. 15/725,030, filed on Oct. 4, 2017, now Pat. No. 10,522,352.

(60) Provisional application No. 62/619,910, filed on Jan. 21, 2018, provisional application No. 62/575,240, filed on Oct. 20, 2017, provisional application No. 62/575,184, filed on Oct. 20, 2017, provisional application No. 62/575,259, filed on Oct. 20, 2017, provisional application No. 62/405,833, filed on Oct. 7, 2016.

(51) **Int. Cl.**

*H01L 23/528* (2006.01)  
*H01L 21/822* (2006.01)  
*H01L 25/00* (2006.01)  
*H01L 23/498* (2006.01)  
*H01L 23/60* (2006.01)  
*H01L 23/522* (2006.01)  
*H01L 27/06* (2006.01)  
*H01L 23/50* (2006.01)

(52) **U.S. Cl.**

CPC ..... *H01L 23/528* (2013.01); *H01L 23/5225* (2013.01); *H01L 23/5286* (2013.01); *H01L 23/60* (2013.01); *H01L 24/32* (2013.01); *H01L 25/50* (2013.01); *H01L 27/0688* (2013.01); *H01L 23/50* (2013.01); *H01L 24/06* (2013.01); *H01L 24/08* (2013.01); *H01L 24/80* (2013.01); *H01L 2224/05571* (2013.01); *H01L 2224/08147* (2013.01); *H01L 2224/09181* (2013.01); *H01L 2224/80895* (2013.01); *H01L 2224/80896* (2013.01)

(58) **Field of Classification Search**

CPC ..... *H01L 23/5286*; *H01L 23/60*; *H01L 24/06*; *H01L 24/08*; *H01L 24/32*; *H01L 24/80*; *H01L 2224/05571*; *H01L 2224/08147*; *H01L 2224/09181*; *H01L 2224/80895*; *H01L 2224/80896*; *H01L 25/0657*; *H01L 25/50*; *H01L 27/0688*

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,579,207 A 11/1996 Hayden et al.  
 5,621,863 A 4/1997 Boulet et al.  
 5,673,478 A 10/1997 Beene et al.  
 5,717,832 A 2/1998 Steimle et al.  
 5,740,326 A 4/1998 Boulet et al.  
 5,793,115 A 8/1998 Zavracky  
 5,909,587 A 6/1999 Tran  
 6,320,255 B1 11/2001 Terrill

6,421,654 B1 7/2002 Gordon  
 6,707,124 B2 3/2004 Wachtler et al.  
 6,844,624 B1 1/2005 Kiritani  
 6,891,447 B2 5/2005 Song  
 6,909,194 B2 6/2005 Farnworth et al.  
 6,917,219 B2 7/2005 New  
 6,962,835 B2 11/2005 Tong et al.  
 7,046,522 B2 5/2006 Sung et al.  
 7,099,215 B1 8/2006 Rotenberg et al.  
 7,124,250 B2 10/2006 Kyung  
 7,202,566 B2 4/2007 Liaw  
 7,485,968 B2 2/2009 Enquist et al.  
 7,638,869 B2 12/2009 Irsigler et al.  
 7,692,946 B2 4/2010 Taufique et al.  
 7,863,918 B2 1/2011 Jenkins  
 7,977,962 B2 7/2011 Hargan et al.  
 8,032,711 B2 10/2011 Black et al.  
 8,042,082 B2 10/2011 Solomon  
 8,059,443 B2 11/2011 McLaren et al.  
 8,110,899 B2 2/2012 Reed et al.  
 8,148,814 B2 4/2012 Furuta et al.  
 8,223,523 B2 7/2012 Jin et al.  
 8,223,524 B2 7/2012 Chung  
 8,228,684 B2 7/2012 Losavio et al.  
 8,233,303 B2 7/2012 Best et al.  
 8,389,378 B2 3/2013 Enquist et al.  
 8,432,467 B2 4/2013 Jaworski et al.  
 8,441,831 B2 5/2013 Ku et al.  
 8,516,409 B2 8/2013 Coteus et al.  
 8,546,955 B1 10/2013 Wu  
 8,547,769 B2 10/2013 Saraswat et al.  
 8,552,569 B2 10/2013 Lee  
 8,704,384 B2 4/2014 Wu et al.  
 8,736,068 B2 5/2014 Bartley et al.  
 8,797,818 B2 8/2014 Jeddelloh  
 8,816,506 B2 8/2014 Kawashita et al.  
 8,860,199 B2 10/2014 Black et al.  
 8,885,380 B2 11/2014 Kang et al.  
 8,901,749 B2 12/2014 Kim et al.  
 8,907,439 B1 12/2014 Kay et al.  
 8,930,647 B1 1/2015 Smith  
 8,947,931 B1 2/2015 D'Abreu  
 8,987,066 B2 3/2015 Grobelny et al.  
 9,030,253 B1 5/2015 Ngai  
 9,067,272 B2 6/2015 Sutanto  
 9,076,700 B2 7/2015 Kawashita et al.  
 9,076,770 B2 7/2015 Foster, Sr. et al.  
 9,142,262 B2 9/2015 Ware  
 9,190,392 B1 11/2015 Shinde et al.  
 9,230,940 B2 1/2016 Goodnow et al.  
 9,300,298 B2 3/2016 Cordero  
 9,318,418 B2 4/2016 Kawashita et al.  
 9,418,964 B2 8/2016 Chang et al.  
 9,432,298 B1 8/2016 Smith  
 9,478,496 B1 10/2016 Lin  
 9,484,326 B2 11/2016 Keeth et al.  
 9,497,854 B2 11/2016 Giuliano  
 9,501,603 B2 11/2016 Barowski et al.  
 9,508,607 B2 11/2016 Chua-Eoan  
 9,640,233 B2 5/2017 Sohn  
 9,645,603 B1 5/2017 Chall et al.  
 9,647,187 B1 5/2017 Yap et al.  
 9,691,739 B2 6/2017 Kawashita et al.  
 9,726,691 B2 8/2017 Garibay  
 9,746,517 B2 8/2017 Whetsel  
 9,747,959 B2 8/2017 Seo  
 9,825,843 B2 11/2017 Thottethodi et al.  
 9,871,014 B2 1/2018 Haba  
 9,915,978 B2 3/2018 Dabby  
 9,934,832 B2 4/2018 Shibata et al.  
 10,121,743 B2 11/2018 Kamal  
 10,180,692 B2 1/2019 Kouchi  
 10,241,150 B2 3/2019 Woo et al.  
 10,255,969 B2 4/2019 Eom et al.  
 10,262,911 B1 4/2019 Gong  
 10,269,586 B2 4/2019 Chou et al.  
 10,289,604 B2 5/2019 Sankaralingam et al.  
 10,373,657 B2 8/2019 Kondo et al.  
 10,446,207 B2 10/2019 Kim et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

10,446,601 B2 10/2019 Otake et al.  
 10,522,352 B2 12/2019 Delacruz et al.  
 10,580,735 B2 3/2020 Mohammed et al.  
 10,580,757 B2 3/2020 Nequist et al.  
 10,580,817 B2 3/2020 Otake et al.  
 10,586,786 B2 3/2020 DeLaCruz et al.  
 10,593,667 B2 3/2020 DeLaCruz et al.  
 10,600,691 B2 3/2020 DeLaCruz et al.  
 10,600,735 B2 3/2020 DeLaCruz et al.  
 10,600,780 B2 3/2020 DeLaCruz et al.  
 10,607,136 B2 3/2020 Teig et al.  
 10,672,663 B2 6/2020 DeLaCruz et al.  
 10,672,743 B2 6/2020 Teig et al.  
 10,672,744 B2 6/2020 Teig et al.  
 10,672,745 B2 6/2020 Teig et al.  
 10,719,762 B2 7/2020 Teig et al.  
 10,762,420 B2 9/2020 Teig et al.  
 2001/0017418 A1 8/2001 Noguchi et al.  
 2002/0008309 A1 1/2002 Akiyama  
 2003/0102495 A1 6/2003 Huppenthal et al.  
 2005/0116331 A1 6/2005 Tsunozaki  
 2005/0127490 A1 6/2005 Black et al.  
 2006/0036559 A1 2/2006 Nugent  
 2006/0087013 A1 4/2006 Hsieh  
 2007/0220207 A1 9/2007 Black et al.  
 2008/0017971 A1 1/2008 Hollis  
 2008/0061373 A1 3/2008 Park  
 2008/0220565 A1\* 9/2008 Hsu ..... H01L 25/50  
 438/109  
 2009/0070727 A1 3/2009 Solomon  
 2010/0140750 A1 6/2010 Toms  
 2010/0261159 A1 10/2010 Hess et al.  
 2010/0283085 A1 11/2010 Bemanian et al.  
 2011/0026293 A1 2/2011 Riho  
 2011/0084365 A1 4/2011 Law et al.  
 2011/0131391 A1 6/2011 Barowski et al.  
 2011/0147949 A1 6/2011 Karp et al.  
 2012/0092062 A1 4/2012 Lee et al.  
 2012/0119357 A1 5/2012 Byeon et al.  
 2012/0136913 A1 5/2012 Duong et al.  
 2012/0170345 A1 7/2012 Choi et al.  
 2012/0201068 A1\* 8/2012 Ware ..... G11C 11/4096  
 438/109  
 2012/0242346 A1 9/2012 Wang  
 2012/0262196 A1 10/2012 Yokou  
 2012/0286431 A1 11/2012 Foster, Sr. et al.  
 2012/0313263 A1 12/2012 Barth  
 2013/0021866 A1 1/2013 Lee  
 2013/0032950 A1 2/2013 Ware et al.  
 2013/0051116 A1 2/2013 En et al.  
 2013/0144542 A1 6/2013 Ernst  
 2013/0187292 A1 7/2013 Semmelmeier  
 2013/0207268 A1 8/2013 Chapelon  
 2013/0242500 A1 9/2013 Lin et al.  
 2013/0275823 A1 10/2013 Cordero et al.  
 2013/0321074 A1 12/2013 Ko  
 2014/0022002 A1 1/2014 Chua-Eoan et al.  
 2014/0285253 A1 9/2014 Jeon et al.  
 2014/0323046 A1 10/2014 Asai  
 2014/0369148 A1 12/2014 Matsui et al.  
 2015/0061097 A1 3/2015 Pham et al.  
 2015/0199997 A1 7/2015 Ito et al.  
 2015/0228584 A1 8/2015 Huang et al.  
 2015/0262902 A1 9/2015 Shen et al.  
 2016/0093601 A1 3/2016 Ding et al.  
 2016/0111386 A1 4/2016 England et al.  
 2016/0218046 A1 7/2016 Or-Bach et al.  
 2016/0225431 A1 8/2016 Best et al.  
 2016/0233134 A1 8/2016 Lim et al.  
 2016/0329312 A1 11/2016 O'Mullan et al.  
 2016/0379115 A1 12/2016 Burger  
 2017/0092615 A1 3/2017 Oyamada  
 2017/0092616 A1 3/2017 Su et al.  
 2017/0148737 A1 5/2017 Fasano et al.  
 2017/0194309 A1 7/2017 Evans et al.

2017/0213787 A1 7/2017 Alfano et al.  
 2017/0227605 A1 8/2017 Kim et al.  
 2017/0278213 A1 9/2017 Eckert  
 2017/0278789 A1 9/2017 Chuang  
 2017/0285584 A1 10/2017 Nakagawa et al.  
 2017/0301625 A1 10/2017 Mahajan et al.  
 2018/0017614 A1 1/2018 Leedy  
 2018/0068218 A1 3/2018 Yoo et al.  
 2018/0286800 A1 10/2018 Kamal et al.  
 2018/0330992 A1 11/2018 Delacruz et al.  
 2018/0330993 A1 11/2018 Delacruz et al.  
 2018/0331037 A1 11/2018 Mohammed et al.  
 2018/0331038 A1 11/2018 Delacruz et al.  
 2018/0331072 A1 11/2018 Nequist et al.  
 2018/0331094 A1 11/2018 Delacruz et al.  
 2018/0331095 A1 11/2018 Delacruz et al.  
 2018/0350775 A1 12/2018 DeLaCruz  
 2018/0373975 A1 12/2018 Yu et al.  
 2018/0374788 A1 12/2018 Nakagawa et al.  
 2019/0006322 A1 1/2019 Park  
 2019/0042377 A1 2/2019 Teig et al.  
 2019/0042912 A1 2/2019 Teig et al.  
 2019/0042929 A1 2/2019 Teig et al.  
 2019/0043832 A1 2/2019 Teig et al.  
 2019/0051641 A1 2/2019 Lee et al.  
 2019/0109057 A1 4/2019 Hargan et al.  
 2019/0123022 A1 4/2019 Teig et al.  
 2019/0123023 A1 4/2019 Teig et al.  
 2019/0123024 A1 4/2019 Teig et al.  
 2019/0156215 A1 5/2019 Matveev et al.  
 2019/0180183 A1 6/2019 Diamant et al.  
 2019/0214991 A1 7/2019 Ngai  
 2019/0244933 A1 8/2019 Or-Bach  
 2020/0013699 A1 1/2020 Liu  
 2020/0143866 A1 5/2020 Biswas et al.  
 2020/0194052 A1 6/2020 Shaeffer et al.  
 2020/0203318 A1 6/2020 Nequist et al.  
 2020/0219771 A1 7/2020 DeLaCruz et al.  
 2020/0227389 A1 7/2020 Teig et al.  
 2020/0273798 A1 8/2020 Mohammed et al.  
 2020/0293872 A1 9/2020 Teig et al.  
 2020/0294858 A1 9/2020 DeLaCruz et al.  
 2020/0372345 A1 11/2020 Li

FOREIGN PATENT DOCUMENTS

CN 102598255 A 7/2012  
 CN 102856306 A 1/2013  
 CN 103219325 B 7/2013  
 CN 105529279 A 4/2016  
 CN 106611756 A 5/2017  
 EP 2466632 A2 6/2012  
 EP 3698401 A1 8/2020  
 EP 3698402 A1 8/2020  
 KR 20150137970 A 12/2015  
 WO 2017138121 A1 8/2017  
 WO 2019079625 A1 4/2019  
 WO 2019079631 A1 4/2019

OTHER PUBLICATIONS

International Search Report and Written Opinion of Commonly Owned International Patent Application PCT/US2018/056565, dated Apr. 2, 2019, 17 pages, International Searching Authority (European Patent Office).  
 Invitation to Pay Additional Fees for Commonly Owned International Patent Application PCT/US2018/056559, dated Feb. 7, 2019, 15 pages, International Searching Authority (EPO).  
 Invitation to Pay Additional Fees for Commonly Owned International Patent Application PCT/US2018/056565, dated Feb. 12, 2019, 13 pages, International Searching Authority (EPO).  
 Nair, Vinod and Hinton, Geoffrey E., "Rectified linear units improve restricted Boltzmann machines," ICML, pp. 807-814, 2010.  
 Non-Published Commonly Owned Related U.S. Appl. No. 16/806,854, filed Mar. 2, 2020, 75 pages, Xcelsis Corporation.

(56)

**References Cited**

## OTHER PUBLICATIONS

Author Unknown, "Fact Sheet: New Intel Architectures and Technologies Target Expanded Market Opportunities," Dec. 12, 2018, 9 pages, Intel Corporation, Santa Clara, California.

Author Unknown, "Vector Supercomputer SX Series: SX-Aurora TSUBASA," Oct. 2017, 2 pages, NEC Corporation.

Bansal, Samta, "3D-IC is Now Real: Wide-IO is Driving 3D-IC TSV," Cadence Flash Memory Summit, Aug. 2012, 14 pages. Cadence Design Systems, Inc.

Black, Bryan, "Die Stacking is Happening!," Dec. 9, 2013, 53 pages, Advanced Micro Devices, Inc., Santa Clara, California.

Black, Bryan, et al., "3D Processing Technology and its Impact on iA32 Microprocessors," Proceedings of 2004 IEEE International Conference on Computer Design: VLSI in Computers and Processors, Oct. 11-13, 2004, 3 pages, IEEE, San Jose, California.

Black, Bryan, et al., "Die Stacking (3D) Microarchitecture," Proceedings of the 39th Annual IEEE/ACM International Symposium on Microarchitecture, Dec. 9-13, 2006, 11 pages, IEEE, Orlando, Florida.

Hajkazemi, Mohammad Hossein, et al., "Wide I/O or LPDDR? Exploration and Analysis of Performance, Power and Temperature Trade-offs of Emerging DRAM Technologies in Embedded MPSoCs," Proceedings of 33rd IEEE International Conference on Computer Design (ICCD), Oct. 18-21, 2015, 8 pages, IEEE, New York City, New York.

International Search Report and Written Opinion of Commonly Owned International Patent Application PCT/US2018/056559, dated Mar. 29, 2019, 17 pages, International Searching Authority (European Patent Office).

Kim, Jung-Sik, et al., "A 1.2 V 12.8 GB/s 2 Gb Mobile Wide-I/O DRAM With 4x128 I/Os Using TSV Based Stacking," IEEE Journal of Solid-State Circuits, Jan. 2012, 10 pages, vol. 47, No. 1, IEEE.

Loh, Gabriel H., et al., "Processor Design in 3D Die-Stacking Technologies," IEEE Micro, May/Jun. 2007, 18 pages, vol. 27, Issue 3, IEEE Computer Society.

Nakamoto, Mark, et al., "Simulation Methodology and Flow Integration for 3D IC Stress Management," 2010 IEEE Custom Integrated Circuits Conference, Sep. 19-22, 2010, 4 pages, IEEE, San Jose, CA, USA.

Non-Published Commonly Owned Related U.S. Appl. No. 16/827,467, filed Mar. 23, 2020, 74 pages, Xcelsis Corporation.

Non-Published Commonly Owned Related U.S. Appl. No. 16/889,698, filed Jun. 1, 2020, 74 pages, Xcelsis Corporation.

Non-Published Commonly Owned Related U.S. Appl. No. 16/891,027, filed Jun. 2, 2020, 47 pages, Xcelsis Corporation.

Non-Published Commonly Owned U.S. Appl. No. 16/806,934, filed Mar. 2, 2020, 74 pages, Xcelsis Corporation.

Tran, Kevin, et al., "Start Your HBM/2.5D Design Today," High-Bandwidth Memory White Paper, Mar. 29, 2016, 6 pages, Amkor Technology, Inc., San Jose, CA, USA.

Wu, Xiaoxia, et al., "Electrical Characterization for Intertier Connections and Timing Analysis for 3-D ICs," IEEE Transactions on Very Large Scale Integration (VLSI) Systems, Dec. 6, 2010, 5 pages, IEEE.


"Sony IMX260 12 MP", "Sony IMX260 12 MP," TechInsights, <https://www.techinsights.com/products/ipr-1603-802> (Accessed Feb. 10, 2023).

"Sony IX260 in Samsung Galaxy S7: Stacked or Not?", "Sony IX260 in Samsung Galaxy S7: Stacked or Not?," Image Sensors World, <http://image-sensors-world.blogspot.com/2016/03/sony-imx260-in-samsung-galaxy-s7.html> (2016).


Garrou, Phil, "IFTLE 303 Sony Introduces Ziptronix DBI Technology in Samsung Galaxy S7", Garrou, Phil, "IFTLE 303 Sony Introduces Ziptronix DBI Technology in Samsung Galaxy S7," <http://image-sensors-world.blogspot.com/2016/03/sony-imx260-in-samsung-galaxy-s7.html> (2016).

Kagawa, Y., et al., "Novel Stacked CMOS Image Sensor with Advanced Cu2Cu Hybrid Bonding", Kagawa, Y., et al., "Novel Stacked CMOS Image Sensor with Advanced Cu2Cu Hybrid Bonding," 2016 IEEE, p. 8.4.1-8.4.4.


\* cited by examiner




*Figure 1*




*Figure 2*




*Figure 3*



*Figure 4*




*Figure 5*




*Figure 6*





*Figure 7*



**Figure 8**









Figure 11



(4)

(3)

(2)

(1)

**Figure 12**






Figure 13



*Figure 14*





*Figure 15*




Figure 16




Figure 17







Figure 18




*Figure 19*




*Figure 20A*



*Figure 20B*




*Figure 21*



*Figure 22*





**Figure 23**




Figure 24




Figure 25




Figure 26







Figure 27



*Figure 28*



*Figure 29*



*Figure 30*

**3D CHIP SHARING DATA BUS**CLAIM OF BENEFIT TO PRIOR  
APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 16/806,854, filed Mar. 2, 2020, now published as U.S. Patent Publication 2020/0203318. U.S. patent application Ser. No. 16/806,854 is a continuation application of U.S. patent application Ser. No. 15/976,811, filed May 10, 2018, now issued as U.S. Pat. No. 10,580,757. U.S. patent application Ser. No. 15/976,811 claims the benefit of U.S. Provisional Patent Application 62/619,910, filed Jan. 21, 2018, U.S. Provisional Patent Application 62/575,184, filed Oct. 20, 2017, U.S. Provisional Patent Application 62/575,259, filed Oct. 20, 2017, U.S. Provisional Patent Application 62/575,240, filed Oct. 20, 2017. U.S. patent application Ser. No. 15/976,811 is a continuation-in-part of U.S. patent application Ser. No. 15/725,030, filed Oct. 4, 2017, now issued as U.S. Pat. No. 10,522,352. U.S. patent application Ser. No. 15/725,030 claims the benefit of U.S. Provisional Patent Application 62/405,833, filed Oct. 7, 2016. U.S. patent application Ser. No. 16/806,854, now published as U.S. Patent Publication 2020/0203318, and U.S. patent application Ser. No. 15/976,811, now issued as U.S. Pat. No. 10,580,757, are incorporated herein by reference.

## BACKGROUND

Electronic circuits are commonly fabricated on a wafer of semiconductor material, such as silicon. A wafer with such electronic circuits is typically cut into numerous dies, with each die being referred to as an integrated circuit (IC). Each die is housed in an IC case and is commonly referred to as a microchip, “chip,” or IC chip. According to Moore’s law (first proposed by Gordon Moore), the number of transistors that can be defined on an IC die will double approximately every two years. With advances in semiconductor fabrication processes, this law has held true for much of the past fifty years. However, in recent years, the end of Moore’s law has been prognosticated as we are reaching the maximum number of transistors that can possibly be defined on a semiconductor substrate. Hence, there is a need in the art for other advances that would allow more transistors to be defined in an IC chip.

## BRIEF SUMMARY

Some embodiments of the invention provide a three-dimensional (3D) circuit that is formed by stacking two or more integrated circuit (IC) dies to at least partially overlap and to share one or more interconnect layers that distribute power, clock and/or data-bus signals. The shared interconnect layers include interconnect segments (also referred to as interconnect lines or wires) that carry power, clock and/or data-bus signals. In some embodiments, the shared interconnect layers are higher level interconnect layers (e.g., the top interconnect layer of each IC die).

In some embodiments, the stacked IC dies of the 3D circuit include first and second IC dies. The first die includes a first semiconductor substrate and a first set of interconnect layers defined above the first semiconductor substrate. Similarly, the second IC die includes a second semiconductor substrate and a second set of interconnect layers defined above the second semiconductor substrate. As further described below, the first and second dies in some embodi-

ments are placed in a face-to-face arrangement (e.g., a vertically stacked arrangement) that has the first and second set of interconnect layers facing each other. In some embodiments, a subset of one or more interconnect layers of the second set interconnect layers of the second die has interconnect wiring that carries power, clock and/or data-bus signals that are supplied to the first IC die. This subset is referred to below as the shared interconnect-layer subset.

In some embodiments, numerous electronic components (e.g., active components, like transistors and diodes, or passive components, like resistors and capacitors) are defined on the first semiconductor substrate, and these electronic components are connected to each other through interconnect wiring on the first set of interconnect layers to form numerous microcircuits (e.g., Boolean gates) and/or larger circuits (e.g., functional blocks). In some of these embodiments, the power, clock and/or data-bus signals from the shared interconnect-layer subset of the second die are supplied to several electronic components, microcircuits, and larger circuits of the first die. Also, in some of these embodiments, the power, clock and/or data-bus signals from the shared interconnect-layer subset are also supplied to electronic components, microcircuits, and larger circuits that are formed on the second substrate of the second die.

In some embodiments, the face-to-face arranged first and second dies have their top interconnect layers bonded to each other through a direct bonding process that establishes direct-contact metal-to-metal bonding, oxide bonding, or fusion bonding between these two sets of interconnect layers. An example of such bonding is copper-to-copper (Cu—Cu) metallic bonding between two copper conductors in direct contact. In some embodiments, the direct bonding is provided by a hybrid bonding technique such as DBI® (direct bond interconnect) technology, and other metal bonding techniques (such as those offered by Invensas Bonding Technologies, Inc., an Xperi Corporation company, San Jose, Calif.).

The direct bonding techniques of some embodiments allow a large number of direct connections (e.g., more than 1,000 connections/mm<sup>2</sup>, 10,000 connections/mm<sup>2</sup>, 100,000 connections/mm<sup>2</sup>, 1,000,000 connections/mm<sup>2</sup> or less, etc.) to be established between the top two interconnect layers of the first and second dies, in order to allow power, clock and/or data-bus signals to traverse between the first and second IC dies. These connections traverse the bonding layer between the two face-to-face mounted dies. When these connections provide signals from the top interconnect layer of the second die to the top interconnect layer of the first die, the first die in some embodiments uses other IC structures (e.g., vias) to carry these signals from its top interconnect layer to other layers and/or substrate of the first die.

These connections between the top interconnect layers of the first and second IC dies are very short in length, which, as further described below, allows the signals on these lines to reach their destinations quickly while experiencing minimal capacitive load from other nearby wiring. In some embodiments, the pitch between two neighboring direct-bonded connections (i.e., the distance between the centers of the two neighboring connections) that connect the top interconnect layers of the first and second dies can be extremely small, e.g., the pitch for two neighboring connections can be between 0.2 μm to 15 μm. This close proximity allows for the large number and high density of such connections between the top interconnect layers of the first and second dies. Moreover, the close proximity of these connections

does not introduce much capacitive load between two neighboring z-axis connections because of their short length and small interconnect pad size.

In some embodiments, the top interconnect layers of the first and second dies have preferred wiring directions that are orthogonal to each other. Specifically, the top interconnect layer of the first die has a first preferred routing direction, while the top interconnect layer of the second die has a second preferred routing direction. In some embodiments, the first and second preferred routing directions are orthogonal to each other, e.g., the top layer of one die has a horizontal preferred routing direction while the top layer of the other die has a vertical preferred routing direction. In other embodiments, the top layer of the first die has the same preferred routing direction as the top layer of the second die, but one of the two dies is rotated by 90 degrees before bonding the top two layers together through a direct bonding technique.

Having the wiring direction of the top interconnect layers of the first and second dies be orthogonal to each other has several advantages. It provides better signal routing between the IC dies and avoids capacitive coupling between long parallel segments on adjacent interconnect layers of the two dies. Also, it allows the top interconnect layers of the first and second dies to conjunctively define a power distribution network (referred to as power mesh below) or a clock distribution network (referred to below as clock tree) that requires orthogonal wire segments in two different interconnect layers.

Orthogonal wiring directions on the top layers of the first and second dies also increases the overlap between the wiring on these layers, which increases the number of candidate locations for bonding different pairs of wires on the top interconnect layers of the different dies to provide power signals and/or clock signals from one die to another die. For instance, in some embodiments, the first die has one set of alternating power and ground lines that traverses along one direction (e.g., the horizontal direction), while the second die has another set of alternating power and ground lines that traverses along another direction (e.g., the vertical direction). The power/ground lines on one die's interconnect layer can be directly bonded to corresponding power/ground lines on the other die's interconnect layer at each or some of the overlaps between corresponding pair of power lines.

This direct bonding creates a very robust power mesh for the first and second dies without using two different interconnect layers for each of these two dies. In other words, defining a power mesh by connecting orthogonal top interconnect layers of the first and second dies through a direct bonding scheme eliminates one or more of power layers in each die in some embodiments. Similarly, defining a clock tree by connecting orthogonal top interconnect layers of the first and second dies through a direct bonding scheme eliminates one or more of clock layers in each die in some embodiments. In other embodiments, the first die does not have a power mesh or clock tree, as it shares the power mesh or clock tree that is defined in the interconnect layer(s) of the second die.

The first and second dies in some embodiments are not face-to-face stacked. For instance, in some embodiments, these two dies are face-to-back stacked (i.e., the set of interconnect layers of one die is mounted next to the backside of the semiconductor substrate of the other die), or back-to-back stacked (i.e., the backside of the semiconductor substrate of one die is mounted next to the backside of the semiconductor substrate of the other die). In other embodiments, a third die is placed between the first and

second dies, which are face-to-face stacked, face-to-back stacked (with the third die between the backside of the substrate of one die and the set of interconnect layers of the other die), or back-to-back stacked (with the third die between the backsides of the substrates of the first and second dies). While some embodiments use a direct bonding technique to establish connections between the top interconnect layers of two face-to-face stacked dies, other embodiments use alternative connection schemes (such as through silicon vias, TSVs, through-oxide vias, TOVs, or through-glass vias, TGVs) to establish connections between face-to-back dies and between back-to-back dies.

Stacking IC dies to share power, clock and/or data-bus signals between two dies has several advantages. This stacking reduces the overall number of interconnect layers of the two dies because it allows the two dies to share some of the higher-level interconnect layers in order to distribute power, clock and/or data-bus signals. For example, as described above, each die does not need to devote two interconnect layers to create a power/ground mesh, because this mesh can be formed by direct bonding the power/ground top interconnect layer of one die with the power/ground top interconnect layer of the other die. Reducing the higher-level interconnect layers is beneficial as the wiring on these layers often consume more space due to their thicker, wider and coarser arrangements. In addition, the ability to share the use of these interconnect layers on multiple dies may reduce the congestion and route limitations that may be more constrained on one die than another.

Stacking the IC dies in many cases also allows the wiring for delivering the power, clock and/or data-bus signals to be much shorter, as the stacking provides more candidate locations for shorter connections between power, clock and/or data-bus signal interconnects and the circuit components that are to receive these signals. For instance, instead of routing data-bus signals on the first die about several functional blocks in order to reach a circuit or component within another block from that block's periphery, the data-bus signals can be provided directly to that circuit or component on the first die from data-bus interconnect on a shared interconnect layer of the second die. The data signal can be provided to its destination very quickly (e.g., within 1 or 2 clock cycles) as it does not need to be routed from the destination block's periphery, but rather is provided by a short interconnect from the shared interconnect layer above. Shorter connections for power, clock and/or data-bus signals reduce the capacitive load on the connections that carry these signals, which, in turn, reduces the signal skew on these lines and allows the 3D circuit to use no or less signal isolation schemes.

Stacking the IC dies also allows the dies to share power, clock and/or data-bus circuits. For instance, in some embodiments in which the first die shares power, clock and/or data-bus interconnects of the second die, the first die also relies on power, clock and/or data-bus circuits that are defined on the second die to provide the power, clock and/or data-bus signals. This frees up space on the first die to implement other circuits and functional blocks of the 3D circuit. The resulting savings can be quite significant because power, clock and/or data-bus circuits can often consume a significant portion of available space. For example, chip input/output (I/O) circuits (e.g., SERDES I/O circuits) and memory I/O circuits (e.g., DDR memory I/O circuits) can be larger than many other circuits on an IC.

Pushing off all or some of the power and clock circuits from the first die to the second die also frees up space on the first die because often power and clock circuits need to be

isolated from other circuits and/or signals that can affect the operation of the power and clock circuits. Also, having system level circuits on just one die allows for better isolation of such circuits (e.g., better isolation of voltage regulators and/or clock circuits).

In sum, stacking the IC dies optimizes the cost and performance of a chip stack system by combining certain functionalities into common interconnect layers and sharing these functions with multiple die in the stack. The functionalities provided by the higher-level interconnect layers can be shared with multiple dies in the stack. The higher-level interconnect layers require thicker and wider metal and coarser pitch. Removing them allows each chip to be connected with a few inner level interconnect layers with higher density vias to enable higher performance and lower cost. Examples of the high-level interconnect layers include system level circuitry layers, and RDL layers. The system circuits include power circuits, clock circuits, data bus circuits, ESD (electro-static discharge) circuits, test circuits, etc.

The preceding Summary is intended to serve as a brief introduction to some embodiments of the invention. It is not meant to be an introduction or overview of all inventive subject matter disclosed in this document. The Detailed Description that follows and the Drawings that are referred to in the Detailed Description will further describe the embodiments described in the Summary as well as other embodiments. Accordingly, to understand all the embodiments described by this document, a full review of the Summary, Detailed Description, the Drawings and the Claims is needed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the invention are set forth in the appended claims. However, for purposes of explanation, several embodiments of the invention are set forth in the following figures.

FIG. 1 illustrates a 3D circuit of some embodiments of the invention.

FIGS. 2-4 illustrate examples of a first die in some embodiments using power circuits, clock circuits, and/or data-bus circuits that are formed on a substrate of a second die.

FIG. 5 illustrates an example of the top interconnect layers of the first and second dies having preferred wiring directions that are orthogonal to each other.

FIGS. 6-8 illustrate examples of several techniques for ensuring that the preferred wiring directions of the top interconnect layers of the first and second dies are orthogonal to each other.

FIG. 9 presents an example that illustrates a power mesh that is formed by the top interconnect layers of two face-to-face mounted dies.

FIG. 10 presents another example for sharing a power mesh between two face-to-face mounted dies.

FIG. 11 illustrates a shared interconnect architecture in which the top two interconnect layers of two face-to-face mounted dies have power, ground and clock lines that form a shared power mesh and a shared clock tree.

FIGS. 12-15 presents other examples for sharing a power mesh and a clock tree between the two face-to-face mounted dies.

FIGS. 16-18 presents examples for sharing a clock tree between the two face-to-face mounted dies.

FIGS. 19 and 20A presents examples for sharing a data bus between the two face-to-face mounted dies.

FIG. 20B illustrates another example of two face-to-face mounted IC dies that form a 3D chip and that share data I/O circuits.

FIG. 21 illustrates a device that uses a 3D IC.

FIG. 22 provides an example of a 3D chip that is formed by two face-to-face mounted IC dies that are mounted on a ball grid array.

FIG. 23 illustrates a manufacturing process that some embodiments use to produce the 3D chip.

FIGS. 24-27 show two wafers at different stages of the fabrication process of FIG. 23.

FIG. 28 illustrates an example of a 3D chip with three stacked IC dies.

FIG. 29 illustrates an example of a 3D chip with four stacked IC dies.

FIG. 30 illustrates a 3D chip that is formed by face-to-face mounting three smaller dies on a larger die.

#### DETAILED DESCRIPTION

In the following detailed description of the invention, numerous details, examples, and embodiments of the invention are set forth and described. However, it will be clear and apparent to one skilled in the art that the invention is not limited to the embodiments set forth and that the invention may be practiced without some of the specific details and examples discussed.

Some embodiments of the invention provide a three-dimensional (3D) circuit that is formed by vertically stacking two or more integrated circuit (IC) dies to at least partially overlap and to share one or more interconnect layers that distribute power, clock and/or data-bus signals. The shared interconnect layers include interconnect segments (also referred to as interconnect lines or wires) that carry power, clock and/or data-bus signals. In some embodiments, the shared interconnect layers are higher level interconnect layers.

FIG. 1 illustrates a 3D circuit **100** of some embodiments of the invention. As shown, the circuit **100** includes two IC dies **105** and **110** that are in a vertically stacked, face-to-face arrangement. Although not shown in FIG. 1, the stacked first and second dies in some embodiments are encapsulated into one integrated circuit package by an encapsulating epoxy and/or a chip case. The first die **105** includes a first semiconductor substrate **120** and a first set of interconnect layers **125** defined above the first semiconductor substrate **120**. Similarly, the second IC die **110** includes a second semiconductor substrate **130** and a second set of interconnect layers **135** defined above the second semiconductor substrate **130**. In some embodiments, a subset **140** of one or more interconnect layers of the second set interconnect layers **135** of the second die has interconnect wiring that carries power, clock and/or data-bus signals that are supplied to the first IC die **105** (e.g., to the interconnect layers and/or substrate of the first die **105**). This subset **140** is referred to below as the shared interconnect-layer subset.

In some embodiments, numerous electronic components (e.g., active components, like transistors and diodes, or passive components, like resistors and capacitors) are defined on the first semiconductor substrate **120** and on the second semiconductor substrate **130**. The electronic components on the first substrate **120** are connected to each other through interconnect wiring on the first set of interconnect layers **125** to form numerous microcircuits (e.g., Boolean gates) and/or larger circuits (e.g., functional blocks). Similarly, the electronic components on the second substrate **130** are connected to each other through interconnect wiring on



the second set of interconnect layers **135** to form additional microcircuits (e.g., Boolean gates) and/or larger circuits (e.g., functional blocks).

In some embodiments, the electronic components on one die's substrate (e.g., the first substrate **120** of the first die **105**) are also connected to other electronic components on the same substrate (e.g., substrate **120**) through interconnect wiring on the other die's set of interconnect layers (e.g., the second set of interconnect layers **135** of the second die **110**) to form additional microcircuits and/or larger circuits.

In some embodiments, power, clock and/or data-bus signals from the shared interconnect-layer subset **140** of the second die **110** are supplied to several electronic components, microcircuits, and larger circuits of the first die **105**. Also, in some of these embodiments, the power, clock and/or data-bus signals from the shared interconnect-layer subset **140** are also supplied to electronic components, microcircuits, and larger circuits that are formed on the second substrate of the second die **110**.

To form the 3D circuit **100** of FIG. 1, the first and second dies are face-to-face stacked so that the first and second set of interconnect layers **125** and **135** are facing each other. The top interconnect layers **160** and **165** are bonded to each other through a direct bonding process that establishes direct-contact metal-to-metal bonding, oxide bonding, or fusion bonding between these two sets of interconnect layers. An example of such bonding is copper-to-copper (Cu—Cu) metallic bonding between two copper conductors in direct contact. In some embodiments, the direct bonding is provided by a hybrid bonding technique such as DBI® (direct bond interconnect) technology, and other metal bonding techniques (such as those offered by Invensas Bonding Technologies, Inc., an Xperi Corporation company, San Jose, Calif.). In some embodiments, DBI connects span across silicon oxide and silicon nitride surfaces.

The DBI process is further described in U.S. Pat. Nos. 6,962,835 and 7,485,968, both of which are incorporated herein by reference. This process is also described in U.S. patent application Ser. No. 15/725,030, which is also incorporated herein by reference. As described in U.S. patent application Ser. No. 15/725,030, the direct bonded connections between two face-to-face mounted IC dies are native interconnects that allow signals to span two different dies with no standard interfaces and no input/output protocols at the cross-die boundaries. In other words, the direct bonded interconnects allow native signals from one die to pass directly to the other die with no modification of the native signal or negligible modification of the native signal, thereby forgoing standard interfacing and consortium-imposed input/output protocols.

In this manner, the direct bonded interconnects allow circuits to be formed across and/or to be accessed through the cross-die boundary of two face-to-face mounted dies. Examples of such circuits are further described in U.S. patent application Ser. No. 15/725,030. The incorporated U.S. Pat. Nos. 6,962,835, 7,485,968, and U.S. patent application Ser. No. 15/725,030 also describe fabrication techniques for manufacturing two face-to-face mounted dies.

As shown in FIG. 1, the direct bonding techniques of some embodiments allow a large number of direct connections **150** to be established between the top interconnect layer **165** of the second die **110** and top interconnect layer **160** of the first die **105**. For these signals to traverse to other interconnect layers of the first die **105** or to the substrate **120** of the first die **105**, the first die in some embodiments uses other IC structures (e.g., vias) to carry these signals from its top interconnect layer to these other layers and/or substrate.

In some embodiments, more than 1,000 connections/mm<sup>2</sup>, 10,000 connections/mm<sup>2</sup>, 100,000 connections/mm<sup>2</sup>, 1,000,000 connections/mm<sup>2</sup> or less, etc. can be established between the top interconnect layers **160** and **165** of the first and second dies **105** and **110** in order to allow power, clock and/or data-bus signals to traverse between the first and second IC dies.

The direct-bonded connections **150** between the first and second dies are very short in length. For instance, based on current manufacturing technologies, the direct-bonded connections can range from a fraction of a micron to a single-digit or low double-digit microns (e.g., 2-10 microns). As further described below, the short length of these connections allows the signals traversing through these connections to reach their destinations quickly while experiencing no or minimal capacitive load from nearby planar wiring and nearby direct-bonded vertical connections. The planar wiring connections are referred to as x-y wiring or connections, as such wiring stays mostly within a plane define by an x-y axis of the 3D circuit. On the other hand, vertical connections between two dies or between two interconnect layers are referred to as z-axis wiring or connections, as such wiring mostly traverses in the z-axis of the 3D circuit. The use of "vertical" in expressing a z-axis connection should not be confused with horizontal or vertical preferred direction planar wiring that traverse an individual interconnect layer, as further described below.

In some embodiments, the pitch between two neighboring direct-bonded connections **150** can be extremely small, e.g., the pitch for two neighboring connections is between 0.2 μm to 15 μm. This close proximity allows for the large number and high density of such connections between the top interconnect layers **160** and **165** of the first and second dies **105** and **110**. Moreover, the close proximity of these connections does not introduce much capacitive load between two neighboring z-axis connections because of their short length and small interconnect pad size. For instance, in some embodiments, the direct bonded connections are less than 1 or 2 μm in length (e.g., 0.1 to 0.5 μm in length), and facilitate short z-axis connections (e.g., 1 to 10 μm in length) between two different locations on the two dies even after accounting for the length of vias on each of the dies. In sum, the direct vertical connections between two dies offer short, fast paths between different locations on these dies.

Stacking IC dies to share power, clock and/or data-bus signals between two dies reduces the overall number of interconnect layers of the two dies because it allows the two dies to share some of the higher-level interconnect layers in order to distribute power, clock and/or data-bus signals. For example, as further described below, this sharing of interconnect layers allows the two dies to share one power mesh between them. In some embodiments, this shared power mesh is formed by direct bonding a power/ground top interconnect layer of one die (e.g., layer **160** of the first die **105**) with a power/ground top interconnect layer of the other die (e.g., layer **165** of the second die **110**). In other embodiments, this shared power mesh is formed by two interconnect layers of one die (e.g., the top two interconnect layers of the second die **110**) that are shared with the other die (e.g., the first die **105**). Reducing the higher-level interconnect layers is beneficial as the wiring on these layers often consume more space due to their thicker, wider and coarser arrangements. In addition, the ability to share the use of these interconnect layers on multiple dies may reduce the congestion and route limitations that may be more constrained on one die than another.

Stacking the IC dies in many cases also allows the wiring for delivering the power, clock and/or data-bus signals to be much shorter, as the stacking provides more candidate locations for shorter connections between power, clock and/or data-bus signal interconnects and the circuit components that are to receive these signals. For instance, as further described below, some embodiments provide data-bus signals to circuits on the first die through short direct-bonded connections from a data bus on a shared interconnect layer of the second die. These direct-bonded connections are much shorter than connections that would route data-bus signals on the first die about several functional blocks in order to reach a circuit within another block from that block's periphery. The data signals that traverse the short direct-bonded connections reach their destination circuits on the first die very quickly (e.g., within 1 or 2 clock cycles) as they do not need to be routed from the periphery of the destination block. On a less-congested shared interconnect layer, a data-bus line can be positioned over or near a destination circuit on the first die to ensure that the data-bus signal on this line can be provided to the destination circuit through a short direct-bonded connection.

Stacking the IC dies also allows the dies to share power, clock and/or data-bus circuits. For instance, as shown in FIGS. 2-4, the first die **105** in some embodiments uses power circuits, clock circuits, and/or data-bus circuits that are formed on the substrate **130** of the second die **110**. In these figures, the examples of power, clock and data-bus circuits are respectively voltage regulators **205**, clock drivers **305**, and PHY (physical layer) interfaces **405** (e.g., chip I/O interface, memory I/O interface, etc.).

Having the first die share power, clock and/or data-bus circuits defined on the second die frees up space on the first die to implement other circuits and functional blocks of the 3D circuit. The resulting savings can be quite significant because power, clock and/or data-bus circuits can consume a significant portion of available space. For example, chip I/O circuits (e.g., SERDES I/O circuits) and memory I/O circuits (e.g., DDR memory I/O circuits) can be larger than many other circuits on an IC. Pushing off all or some of the power and clock circuits from the first die to the second die further frees up space on the first die because power and clock circuits often need to be isolated from other circuits and/or signals that can affect the operation of the power and clock circuits. Having system level circuits on just one die also allows for better isolation of such circuits (e.g., better isolation of voltage regulators and/or clock circuits).

In sum, stacking the IC dies optimizes the cost and performance of a chip stack system by combining certain functionalities into common interconnect layers and sharing these functions with multiple die in the stack. The functionalities provided by the higher-level interconnect layers can be shared with multiple dies in the stack. The higher-level interconnect layers require thicker and wider metal and coarser pitch. Removing them allows each chip to be connected with a few inner level interconnect layers with higher density vias to enable higher performance and lower cost. Examples of the high-level interconnect layers include system level circuitry layers, and RDL layers. The system circuits include power circuits, clock circuits, data bus circuits, ESD (electro-static discharge) circuits, test circuits, etc.

Each interconnect layer of an IC die typically has a preferred wiring direction (also called routing direction). Also, in some embodiments, the preferred wiring directions of successive interconnect layers of an IC die are orthogonal to each other. For example, the preferred wiring directions of

an IC die typically alternate between horizontal and vertical preferred wiring directions, although several wiring architectures have been introduced that employ 45 degree and 60 degree offset between the preferred wiring directions of successive interconnect layers. Alternating the wiring directions between successive interconnect layers of an IC die has several advantages, such as providing better signal routing and avoiding capacitive coupling between long parallel segments on adjacent interconnect layers.

When face-to-face mounting of first and second IC dies, some embodiments have the preferred wiring directions of the top interconnect layers of the first and second dies be orthogonal to each other in order to realize these same benefits as well as other unique benefits of orthogonal preferred wiring directions at the juncture of the face-to-face mounting. FIG. 5 illustrates an example of the top interconnect layers of the first and second dies **505** and **510** having preferred wiring directions that are orthogonal to each other. In this example, the top interconnect layer **502** of the first die **505** has a preferred horizontal direction, while the top interconnect layer **504** of the second die **510** has a preferred vertical direction. As shown, the first die's top layer **502** can have short vertical wire segments, and the second die's top layer **504** can have short horizontal wire segments. However, the majority of the segments on the top layers **502** and **504** are respectively horizontal and vertical.

Different embodiments employ different techniques to ensure that the preferred wiring directions of the top interconnect layers of the first and second dies are orthogonal to each other. FIGS. 6-8 illustrate examples of several such techniques. FIG. 6 illustrates that the two dies **605** and **610** are manufactured with different processes in some embodiments. The process for the first die **605** defines the first interconnect layer of the first die to have a horizontal preferred wiring direction, while the process for the second die **610** defines the first interconnect layer of the second die to have a vertical preferred wiring direction. As both these processes define seven interconnect layers above the IC substrate and alternate the preferred wiring directions between successive layers, the seventh layer of the first die has a horizontal preferred direction while the seventh layer of the second die has a vertical preferred direction.

FIG. 7 illustrates an example in which the first and second dies have different preferred wiring directions for their top interconnect layers because they have different number of interconnect layers. In this example, the preferred wiring direction of the first interconnect layer of both dies **705** and **710** has the same wiring direction (the horizontal in this example). However, the first die has seven interconnect layers while the second die has six interconnect layers. Hence, the top interconnect layer (the seventh layer) of the first die has a horizontal preferred wiring direction, while the top interconnect layer (the sixth layer) of the second die has a vertical preferred wiring direction.

FIG. 8 presents an example that illustrates achieving orthogonal preferred wiring directions between the top interconnect layers of the two face-to-face mounted dies **805** and **810** by rotating one of the two dies by 90 degrees. In this example, the preferred wiring directions of the interconnect layers of the first and second dies **805** and **810** are identical, i.e., they both start with a horizontal preferred wiring direction, alternate the preferred wiring directions for successive layers, and end with a vertical preferred wiring direction.

Also, in some embodiments, the first and second dies **805** and **810** are fabricated with several masks that are jointly defined as these two dies implement one IC design. The

jointly defined masks for the two dies **805** and **810** share one or more common masks in some embodiments. In other embodiments, the first and second dies **805** and **810** are from different manufacturing processes and/or different foundries.

However, before face-to-face stacking the two dies **805** and **810**, the second die is rotated by 90 degrees. This rotation in effect flips the preferred wiring direction of each interconnect layer of the second die to be orthogonal to the preferred wiring direction of the corresponding interconnect layer of the first die. Thus, the top layer of the rotated second die has effectively a vertical preferred wiring direction compared to the horizontal preferred wiring direction of the top layer of the first die.

In FIG. **8**, the effective preferred wiring directions of the second die are specified by placing these directions in quotes to indicate that these directions are not indicative of the manufactured preferred directions but are indicative of the wiring directions compared to the first die's wiring direction and are achieved by rotating the second die with respect to the first die. In some embodiments, the two dies **805** and **810** are produced from the same mono crystalline silicon wafer or are produced from two mono crystalline silicon wafers with the same crystalline direction. In some of these embodiments, the two dies **805** and **810** have orthogonal crystalline directions after they have been face-to-face mounted.

Having the preferred wiring direction of the top interconnect layers of the first and second dies be orthogonal to each other has several advantages. It provides better signal routing between the IC dies and avoids capacitive coupling between long parallel segments on adjacent interconnect layers of the two dies. Also, it allows the first and second dies to share the power lines on their top orthogonal layers, and thereby eliminating one or more of their power layers. Orthogonal wiring directions on the top layers of the first and second dies increases the overlap between the power wiring on these layers. This overlap increases the number of candidate locations for bonding different pairs of power wires on the top interconnect layers of the different dies to provide power signals from one die to another die.

FIG. **9** presents an example that illustrates a power mesh **950** that is formed by the top interconnect layers **902** and **904** of the first and second dies **905** and **910** in some embodiments. This mesh supplies power and ground signals to circuits defined on the first and second substrates **920** and **930** of the first and second dies **905** and **910**. As shown, the top interconnect layer **902** of the first die **905** has a set of alternating power lines **915** and ground lines **920** that traverse along the horizontal direction, while the top interconnect layer **904** of the second die **910** has a set of alternating power lines **925** and ground lines **930** that traverse along the vertical direction.

In some embodiments, the power/ground lines on one die's interconnect layer are directly bonded (e.g., through DBI interconnects) to corresponding power/ground lines on the other die's interconnect layer at each or some of the overlaps **955** between corresponding pairs of power lines and pairs of ground lines. This direct bonding creates a very robust power mesh **950** for the first and second dies without using two different interconnect layers for each of these two dies. This frees up at least one interconnect layer on each die and in total eliminates two interconnect layers from the 3D circuit (formed by the face-to-face bonded dies **905** and **910**) by having the two dies share one power mesh. Also, the face-to-face mounted top interconnect layers allow thicker and wider interconnect lines to be used for the power signals, which, in turn, allows these signals to face less resistance and suffer less signal degradation.

In some embodiments, the power and ground signals are supplied by power circuitry defined on the substrate of the second die **910** as described above by reference to FIG. **2**. In some of these embodiments, the power and ground signals from the power circuitry are supplied from the second die's substrate through vias to the power and ground lines on the top interconnect layer **904** of the second die **910**. From this interconnect layer **904**, these signals are supplied through direct bonded connections (e.g., DBI connections) to power and ground lines on the top interconnect layer **902** of the first die **905**, from where they are supplied to circuits and other interconnect layers of the first die **905**.

FIG. **10** presents another example for sharing a power mesh **1050** between the first and second dies **1005** and **1010** in some embodiments. In this example, the power mesh **1050** is formed by the top two interconnect layers **1002** and **1004** of the second die **1010**. Other than both of these interconnect layers belonging to the second die **1010**, these two interconnect layers **1002** and **1004** are similar to the interconnect layers **902** and **904**. Specifically, the interconnect layer **1002** has alternating power lines **1015** and ground lines **1020** while the interconnect layer **1004** has alternating power lines **1025** and ground lines **1030**, with vias defined at each or some of the overlaps **1055** between corresponding pairs of power lines and pairs of ground lines.

The power mesh architecture of FIG. **10** consumes two interconnect layers of the second die **1010** but does not use any interconnect layers of the first die. Hence, like the power mesh **950**, the power mesh **1050** eliminates in total two interconnect layers from the 3D circuit by having the two dies share one power mesh. Also, defining the power mesh with the top two interconnect layers of the die **1010** allows thicker and wider interconnect lines to be used for the power signals, which, in turn, allows these signals to face less resistance and suffer less signal degradation.

In some embodiments, the power and ground signals are supplied by power circuitry defined on the substrate of the second die **1010** to the power and ground lines **1015-1030** on the top-two interconnect layers **1002** and **1004** of the second die **1010**. From these interconnect layers **1002** and **1004**, these signals are supplied to power and ground interconnect lines and/or pads on the top interconnect layer of the first die **1005** through direct-bonded connections (e.g., DBI connections) between the first and second dies **1005** and **1010**. From the top interconnect layer of the first die **1005**, the power and ground signals are then supplied through vias to other interconnect layers of the first die **1005** and to circuits defined on the substrate of the first die.

In power mesh architectures of FIGS. **9** and **10**, as well as some of the other figures described below, the direct connections or vias that establish the electrical connections between two power lines on two different layers, or two ground lines on two different layers, electrically shield signals that traverse vertically in between these connections/vias through their own vertical connections or vias that traverse different interconnect layers on the same die or different dies. Also, in these examples, the power lines distribute power and ground signals. One of ordinary skill will realize that in other embodiments, the shared power distribution networks between two or more vertically stacked dies distribute other types of power signals, such as reference voltages ( $V_{REF}$ ) and low power state voltages.

Also, in some embodiments, a first power mesh is defined on the top two interconnect layers of a first die, while a second power mesh is defined on the top two interconnect layers of a second die that is face to face mounted with the first die through a direct bonding process. In some of these

embodiments, the direction of the power/ground interconnects on the top interconnect layer of the first die is orthogonal to the direction of the power/ground interconnects on the top interconnect layer of the second die.

In other embodiments, two dies that are face-to-face mounted through a direct bonding process (e.g., a DBI process) have power/ground lines on the top two interconnect layers of a first die (like layers **1002** and **1004** of FIG. **10**), but power/ground lines only on the top interconnect layer of the second die. In some of these embodiments, the direction of the power/ground interconnects on the top interconnect layer of the first die is orthogonal to the direction of the power/ground interconnects on the top interconnect layer of the second die. In this face-to-face mounted 3D chip arrangement, one power sub-mesh is formed by the top two interconnect layers of the first die, while another power sub-mesh is formed by the top interconnect layers of the first and second dies. These two sub-meshes form a three-layer shared power mesh on the two dies.

The shared power meshes that are formed by the top interconnect layers of one or both dies are used in some embodiments to shield other types of interconnect lines on these layers or between these layers. Specifically, some embodiments not only share a power mesh between two face-to-face mounted dies, but also share a clock tree that is formed on one or two interconnect layers that are shared between the two dies. In some embodiments, the clock tree is formed on the same shared interconnect layers that form the power mesh, while in other embodiments the interconnect layer or layers that contain the clock mesh are in between the interconnect layers that form the power mesh. The power mesh in some embodiments shields the clock lines from capacitive coupling of the other clock and data interconnect lines.

FIG. **11** illustrates a shared interconnect architecture of some embodiments. In this architecture, the top two interconnect layers **1115** and **1120** of two face-to-face mounted dies **1105** and **1110** (that form a 3D stacked chip **1100**) have power, ground and clock lines that form a power mesh **1150** and a clock tree **1160**. FIG. **11** has four sets of schematics. The first set shows the two face-to-face mounted dies **1105** and **1110**. The second set shows dies **1105** and **1110**, and expanded views of the top two interconnect layers **1115** and **1120** of these two dies. The top half of the third set of schematics shows just the power and ground lines on the top two interconnect layers **1115** and **1120**, while the bottom half of the third set shows just the clock lines on these two layers. Lastly, top half of the fourth set of schematics shows the power mesh formed by the power and ground lines of the top two interconnect layers **1115** and **1120**, while the bottom half of this set shows the clock tree **1160** formed by the clock lines on these two layers.

As shown in the second and third sets of schematics of FIG. **11**, the top interconnect layer **1115** of the first die **1105** includes horizontal power lines **1130**, ground lines **1135** and clock lines **1140**, while the top interconnect layer **1120** of the second die **1110** includes vertical power lines **1130**, ground lines **1135** and clock lines **1140**. In these schematics, the power/ground lines **1130** and **1135** are thinner, long solid lines, while the clock lines **1140** are thicker, shorter line segments.

The power and ground lines **1130** and **1135** on each interconnect layer alternate in their order (i.e., a power line is followed by a ground line, which is followed by a power line, and so on). Also, one set of clock line segments are placed between each neighboring pair of power and ground

lines **1130** and **1135**. Thus, each clock line segment **1140** on each interconnect layer is between two power/ground lines **1130** and **1135** that shield the clock line segment from nearby clock and data lines and thereby reduce the capacitive coupling between the clock line segment and the nearby clock and data lines. Also, by virtue of being in the top interconnect layers, the clock line segments are thicker and wider, which, in turn, reduces their resistance and allows the clock signals that they carry to be driven longer distances.

The horizontal and vertical clock line segments on the interconnect layers **1115** and **1120** form a shared H-tree clock structure **1160** that distributes a clock signal to the circuits on the first and second dies **1105** and **1110**. The H-tree clock structure will be further described below. To form the clock tree **1160**, each horizontal clock line segment on the interconnect layer **1115** is connected through at least one direct bonded connection (e.g., DBI connection) to at least one vertical clock line segment on the interconnect layer **1120**. Some of clock line segments on one top interconnect layer (e.g., layer **1115**) connect to three clock line segments on the other interconnect layer (e.g., layer **1120**) through three direct bonded connections (e.g., DBI connections). Similarly, to form the power mesh **1150**, (1) each power line on one interconnect layer (e.g., layer **1115**) connects through one or more direct bonded connections (e.g., DBI connections) to one or more power lines on the other interconnect layer (e.g., layer **1120**), and (2) each ground line on one interconnect layer (e.g., layer **1115**) connects through one or more direct bonded connections (e.g., DBI connections) to one or more ground lines on the other interconnect layer (e.g., layer **1120**).

The power mesh **1150** and clock tree **1160** eliminate two or more interconnect layers from the 3D circuit by having the two dies share two interconnect layers **1105** and **1110** that together form the power mesh **1150** and the clock tree **1160**. On each die **1105** or **1110**, the power, ground and clock signals are distributed among the interconnect layers of that die through vias between the interconnect layers. In some embodiments, power and clock circuits are defined on the substrate of only one of the dies (e.g., on the substrate of the second die **1110**). In other embodiments, the power circuits are defined on the substrate of one die (e.g., the substrate of the first die **1105**), while the clock circuits are defined on the substrate of the other die (e.g., the substrate of the second die **1110**). In other embodiments, power and/or clock circuits are defined on the substrate of both dies **1105** and **1110**.

The H-tree clock structure includes a hierarchical series of H-structures, with each H-structure distributing the same clock signal from the center of the H-structure to the outer four corners of the H-structure, where the signal is passed to the center of another, smaller H-structure, until the clock signal reaches the outer corner of the smallest H-structures. The center of the largest H-structure receives the clock signal from a clock circuit that is defined on the second die's substrate in some embodiments. In other embodiments, this signal is supplied to other locations of the H-structure from the clock circuit on the second die's substrate, or to a location on the H-structure from a clock circuit on the first die's substrate. In some embodiments, the clock signal is distributed from H-tree structure **1160** to circuits and interconnects of the first and second dies through vias.

FIG. **12** presents another example for sharing a power mesh **1250** and a clock tree **1260** between the first and second dies **1205** and **1210** in some embodiments. In this example, the power mesh **1250** and the clock tree **1260** are formed by the top two interconnect layers **1215** and **1220** of a second die **1210** that is face-to-face mounted through

## 15

direct bonded connections with a first die **1205** to form a 3D chip **1200**. Other than both of these interconnect layers belonging to the second die **1210**, these two interconnect layers **1215** and **1220** are similar to the interconnect layers **1115** and **1120**.

Specifically, each interconnect layer **1215** or **1220** has alternating power lines **1225** and ground lines **1230** and clock line segments between neighboring pairs of power and ground lines. Vias are defined at each or some of the overlaps between corresponding pairs of power lines, corresponding pairs of ground lines and corresponding pairs of clock line segments, in order to create the power mesh **1250** and the clock tree **1260**. The shared interconnect architecture of FIG. **12** eliminates two or more interconnect layers from the 3D circuit by having the two dies share the two interconnect layers **1215** and **1220** that form the power mesh **1250** and the clock tree **1260**.

In some embodiments, the power, ground and clock signals are supplied by power and clock circuitry defined on the substrate of the second die **1210** to the power, ground and clock lines on the interconnect layers **1215** and **1220** of the second die **1210**. From these interconnect layers **1215** and **1220**, the power, ground and clock signals are supplied to power, ground and clock interconnect lines and/or pads on the top interconnect layer of the first die **1205** through direct-bonded connections (e.g., DBI connections) between the first and second dies **1205** and **1210**. From the top interconnect layer of the first die **1205**, the power, ground and clock signals are then supplied through vias to other interconnect layers of the first die **1205** and to circuits defined on the substrate of the first die. In some embodiments, power circuits and/or clock circuits are also defined on the substrate of the first die **1205**.

FIG. **13** illustrates another shared interconnect architecture of some embodiments. In this example, a power mesh **1350** and a clock tree **1360** are formed by the top interconnect layer **1315** of a first die **1305** and the top two interconnect layers **1320** and **1325** of a second die **1310**, which is face-to-face mounted to the first die **1305** through direct bonded connections to form a 3D chip **1300**. The shared architecture of this example is similar to the shared interconnect architecture of FIG. **9**, except that the top interconnect layer **1320** of the second die **1310** contains a shared H-tree clock structure **1350** for distributing a clock signal to the circuits on the first and second dies **1305** and **1310**, and this interconnect layer **1320** is between two power/ground interconnect layers **1315** and **1325** of the first and second dies **1305** and **1310**. This placement of the H-tree clock structure between the power/ground interconnect layers **1315** and **1325** shields the clock line segments in this structure from capacitively coupling to interconnect lines that carry data and other signals on other interconnect layers of the first and second dies **1305** and **1310**.

The power/ground lines in some embodiments alternate on each of the interconnect layers **1315** and **1325**. Also, in some embodiments, the power/ground lines on the interconnect layer **1325** of the second die connect to pads on this die's interconnect layer **1320**, and these pads are connected through direct bonded connections (e.g., DBI connections) to power lines on the interconnect layer **1315**. The power/ground signals in some embodiments are distributed to other interconnect and substrate layers on each die through vias.

Also, in some embodiments, the clock signal is distributed from H-tree structure **1360** to circuits and interconnects of the second die through vias, while it is distributed from this structure **1360** to circuits and interconnects of the first die through direct-bonded connections between this structure

## 16

and clock pads on layer **1315** of the first die. The direct-bonded connections in some embodiments emanate from the corners of some of the H-structures and travel along the z-axis. The center of the largest H-structure in this clock tree receives the clock signal from a clock circuit that is defined on the second die's substrate in some embodiments. In other embodiments, this signal is supplied to other locations of the H-structure from the clock circuit on the second die's substrate, or to a location on the H-structure from a clock circuit on the first die's substrate.

FIG. **14** illustrates yet another shared power/clock interconnect architecture of some embodiments. This architecture **1400** is similar to the power/clock interconnect architecture **1300** of FIG. **13**, except that the power and clock interconnect layers **1415**, **1420** and **1425** are all interconnect layers of the second die **1410**. In this example, the first die **1405** does not contain any interconnect layer that is dedicated to either the power or clock lines. Also, in this example, the H-tree clock structure **1460** is again between the power/ground interconnect layers **1415** and **1425** of the second die **1410**, and hence its clock line segments are shielded by these power/ground interconnect layers from capacitive couplings to other interconnect lines that carry data and other signals on other interconnect layers of the first and second dies **1405** and **1410**.

In the architecture **1400**, the power, ground and clock signals are supplied to circuits and interconnects of the first die by directly bonding these circuits and interconnects through direct-bonded connections from the power/ground lines and clock lines/pads on layer **1415** of the second die to lines/pads on the top layer **1412** of the first die **1405**. The power, ground and clock signals are supplied in some embodiments to circuits, interconnects, and pads of the second die through vias. Similarly, in some embodiments, the power, ground and clock signals are supplied from the top layer **1412** of the first die **1405** to circuits and interconnects of the first die **1405** through vias.

FIG. **15** illustrates yet another shared power/clock interconnect architecture of some embodiments. This architecture **1500** is similar to the power/clock interconnect architecture **1300** of FIG. **13**. However, in the architecture **1500**, the H-tree structure **1560** is implemented by the top interconnect layers **1515** and **1520** of two dies **1505** and **1510**, which are face-to-face mounted through direct bonded connections (e.g., DBI connections) to form a 3D chip **1500**. The clock interconnect layer **1515** is the top interconnect layer of the first IC die **1505** and has the horizontal segments of the H-tree structure **1560**. The clock interconnect layer **1510** is the top interconnect layer of the second IC die **1510**, and has the vertical segments of the H-tree structure **1560**.

The vertical and horizontal segments of the H-tree structure **1560** are connected to each other through direct-bonded connections (e.g. DBI connections). The center of the largest H-structure receives the clock signal from a clock circuit that is defined on the second die's substrate in some embodiments. In other embodiments, this signal is supplied to other locations of the H-structure from the clock circuit on the second die's substrate, or to a location on the H-structure from a clock circuit on the first die's substrate. In some embodiments, the clock signal is distributed from the clock lines of the interconnect layer **1515** of the first die **1505** to circuits and interconnects of the first die through vias defined in the first die. Similarly, the clock signal is distributed from the clock lines on the interconnect layer **1520** of the second die **1510** to circuits and interconnects of the second die through vias.

As shown, the H-tree clock structure **1560** is between the interconnect layer **1525** of the first die **1505** and the top interconnect layer **1530** of the second die **1510**. Like the position of the H-tree structure **1360**, the placement of the H-tree clock structure **1560** between the power/ground interconnect layers **1525** and **1530** shields the clock line segments in this structure from capacitively coupling to interconnect lines that carry data and other signals on other interconnect layers of the first and second dies **1505** and **1510**.

In this example, the power/ground layers **1525** and **1530** connect to power/ground pads on clock interconnect layers **1515** and **1520** through vias. The power/ground pads on one of these interconnect layers (e.g., layer **1515**) connect to corresponding power/ground pads on the other interconnect layer (e.g., layer **1520**) through direct-bonded connections (e.g., DBI connections). Through these vias and direct-bonded connections, corresponding pairs of power/ground lines are connected on the interconnect layers **1525** and **1530** to form the power mesh **1550**.

The power/ground signals in some embodiments are distributed to other interconnect and substrate layers on each die through vias. In some embodiments, the four power/clock interconnect layers **1515**, **1520**, **1525** and **1530** are the interconnect layers of one of the dies (e.g., the second die **1510**), and these four layers are shared by the first die **1505**. In other embodiments, three of these interconnect layers belong to one die and one of them belongs to another die.

In some embodiments, the 3D chip structure that is formed by two face-to-face mounted dies has one or more clock interconnect layers in between a full power mesh that is formed on the first die and a full/half power mesh that is formed on the second die. A full power mesh on a die in some embodiments includes at least two interconnect layers that contain power/ground interconnect lines. In some of these embodiments, a partial power mesh on a die includes one interconnect layer that contains power/ground interconnect lines, and that connects through z-axis vertical connections (e.g., via and DBI connections) to the power mesh of the other die. In some of these embodiments, the full or partial power mesh layer(s) on one die do not include the top interconnect layer of that die as the top layer is used to carry clock or data interconnect lines (like the top interconnect layers **1515** and **1520** of FIG. **15**, which carry clock lines).

In some embodiments, two vertically stacked IC dies do not share power-distributing interconnect layers but share interconnect layers for sharing clock signal or signals. FIGS. **16-18** illustrate examples of two such shared interconnect architectures. In FIG. **16**, two dies **1605** and **1610** are face-to-face mounted through direct bonded connections to form a 3D chip **1600**. The top interconnect layer **1620** of the die **1610** includes a clock tree **1660** that is used (1) to distribute a clock signal to other interconnect layers of the die **1610** through vias of this die, and (2) to distribute the clock signal to other interconnect layers of the die **1605** through direct-bonded connections (e.g., DBI connections) to the top interconnect layer **1615** of the die **1605** and then through vias of this die **1605**.

As in the examples illustrated in FIGS. **13** and **14**, the clock tree **1660** is an H-tree structure. One of ordinary skill will realize that other embodiments use other types of clock distribution structures. The center of the largest H-structure receives the clock signal from a clock circuit that is defined on the second die's substrate in some embodiments. In some of these embodiments, the first IC die **1605** does not include a clock circuit that generates a clock signal. In other embodiments, this signal is supplied to other locations of the

H-structure from the clock circuit on the second die's substrate, or to a location on the H-structure from a clock circuit on the first die's substrate.

FIG. **17** illustrates two dies **1705** and **1710** are face-to-face mounted through direct bonded connections to form a 3D chip **1700**. In this example, the top interconnect layers **1715** and **1720** of these two dies **1705** and **1710** respectively include horizontal clock line segments **1735** and vertical clock line segments **1740** that together form a clock tree **1760** that is used to distribute a clock signal to other interconnect layers of the dies **1705** and **1710**. The horizontal and vertical line segments on the top interconnect layers **1715** and **1720** are connected through direct-bonded connections (e.g., DBI connections) in order to form the H-tree clock structure **1760**.

One or more clock line segments on the top layer **1720** of the second die **1710** in some embodiments receive the clock signal from a clock circuit that is defined on the second die's substrate. In some embodiments, the clock signal is distributed from the clock lines on the interconnect layer **1715** of the first die **1705** to circuits and interconnects of the first die through vias of the first die. Similarly, the clock signal is distributed from the clock lines on the interconnect layer **1720** of the second die **1710** to circuits and interconnects of the second die through vias.

FIG. **18** illustrate yet another shared interconnect structure for distributing clock signals between two face-to-face mounted IC dies. This architecture is similar to the architecture of FIG. **17**, except that in FIG. **18** the horizontal and vertical clock interconnect layers **1815** and **1820** both belong to a second die **1810** that is face-to-face mounted through direct bonded connections to a first die **1805** to form a 3D chip **1800**. In this architecture, vias between the interconnect layers **1815** and **1820** of the second die establish the connections between the clock lines on these layers in order to create the clock structure **1860** (i.e., the H-tree structure **1860**) in this example.

Direct bonded connections between the first and second dies **1805** and **1810** then supply the clock signal from this clock structure to clock lines/pads on the top interconnect layer of the first die **1805**. The clock signal is then passed to other interconnect and substrate layers of the first die **1805** through vias. The clock signal is also passed to other interconnect and substrate layers of the second die **1810** through vias. In some embodiments, a clock circuit on the second die's substrate supplies the clock signal to one or more clock line segments on interconnect layer **1815** and/or interconnect layer **1820** of the second die **1810**. In other embodiments, the clock signal is generated by a clock circuit defined on the substrate of the first die **1805**.

One of the unique features of the 3D chips illustrated in FIGS. **11-18** is that in these chips, the clock lines are moved to the top interconnect layers of a die, or next to the top interconnect layer of the die. Typically, clock lines are not in the top interconnect layers as such a placement would expose the clock signals/lines to interfering signals outside of the chip. However, the face-to-face mounted dies of FIGS. **11-18** can place the clock lines in their top interconnect layers as these layers are very well isolated from signals outside of their 3D chips because these interconnect layers are effectively in the middle of the die stack.

In addition to isolating the clock signals, the face-to-face mounted top interconnect layers allow thicker and wider interconnect lines to be used for the clock signals. These signals have less resistance and suffer less signal degradation. Hence, the clock signals can be driven longer distance with no clock signal regeneration (which would require the

## 19

clock signals to travel to the buffer circuits formed on a semiconductor substrate) or with less clock signal regeneration. This lower resistance advantage (i.e., less signal degradation advantage) of thicker and wider interconnects on upper interconnect layers is also enjoyed by power and data interconnect line segments that are defined on the upper interconnect layers and that are shared between two or more vertically stacked IC dies (e.g., two face-to-face mounted IC dies).

As mentioned above, stacking IC dies also allows two or more dies to share a data bus on one or more shared interconnect layers. FIG. 19 illustrates an example of one such shared interconnect layer architecture that allows two face-to-face mounted IC dies to share a data bus and a data storage that are defined on one of the dies. In this example, the data storage is an on-chip cache 1960. In other embodiments, the shared data storage is any other type of storage. In FIG. 19, the two face-to-face mounted IC dies 1905 and 1910 (that form a 3D chip 1900) share a data bus 1950 that is defined on a top interconnect layer 1920 of the second die 1910. As shown, this top interconnect layer 1920 connects to the top interconnect layer 1915 of the first die 1905 through direct bonded connections (e.g., DBI connections).

Although a data bus does not necessarily need to include parallel interconnect lines, the data bus 1950 in this example includes several parallel interconnect lines that connect to other interconnect lines on the first and second dies through vias and direct-bonded connections at one or more locations along each interconnect line. These lines are shown to be physically parallel, but in other cases, they are just topologically parallel (e.g., on one end, they connect to several adjacent locations at one position of a die or interconnect layer, while on another end, they connect to several other adjacent locations at another position in a die or interconnect layer). The data bus 1950 connects through interconnect lines and vias to an input/output interface 1955 of a cache storage 1960 that is defined on the substrate 1965 of the second die 1910. Through interconnect lines and vias, the data bus 1950 also connects to circuits defined on the second die 1910, so that through these connections and the I/O interface 1955 these circuits can receive output data read from the cache storage 1960, and provide input data for storing in the cache storage 1960.

Through the direct bonded connections, the data bus 1950 also connects to interconnect lines/pads on the top interconnect layer 1915 of the first die 1905. These interconnect lines/pads on the interconnect layer 1915 connect to circuits on the first die 1905 through interconnect lines and vias of the first die 1905. Through these connections (i.e., the interconnect lines, vias and direct-bonded connections) and the I/O interface 1955, the circuits defined on the first die 1905 can receive output data read from the cache storage 1960, and provide input data for storing in the cache storage 1960.

Stacking the IC dies so that they can share one or more data buses allows the wiring for delivering the data to be much shorter, as the stacking provides more candidate locations for shorter connections between data bus interconnects and the circuit components that are to receive these signals. For instance, instead of routing data signals on the second die about several functional blocks in order to reach a circuit or component within another block from that block's periphery, the data signals can be provided directly to that circuit or component on the second die from data-bus interconnect on the shared interconnect layer of the first die. The data signal can be provided to its destination very quickly (e.g., within 1 or 2 clock cycles) as it does not need

## 20

to be routed from the destination block's periphery, but rather is provided by a short interconnect from the shared interconnect layer above. Shorter connections for data signals reduce the capacitive load on the connections that carry these signals, which, in turn, reduces the signal skew on these lines and allows the 3D circuit to use no or less signal isolation schemes.

FIG. 20A illustrates another example of two face-to-face mounted IC dies sharing resources. In this example, the circuits of first and second dies 2005 and 2010 of the two dies share data I/O circuitry, which includes an I/O interface 2025, an external data I/O unit 2030 (e.g., level shifting drivers), and a data I/O bus 2022 formed by a number of data bus lines. The data I/O unit 2030 can be an external memory I/O unit or another data interface unit, such as a SerDes unit. In FIG. 20A, the two face-to-face mounted IC dies 2005 and 2010 form a 3D chip 2000. Through silicon vias (TSVs) are defined on the backside of the second die 2010. Through these TSVs and the I/O interface, data is received and supplied to the data I/O unit 2030 defined on the substrate of the second die 2010.

The data I/O unit 2030 connects through interconnect lines and vias of the second die to the data bus 2022 that is defined on a top interconnect layer 2020 of the second die 2010. As shown, this top interconnect layer 2020 connects to the top interconnect layer 2015 of the first die 2005 through direct bonded connections (e.g., DBI connections). In this example, the data bus 2022 is again shown to have several parallel interconnect lines that connect to other interconnect lines on the first and second dies through vias and direct-bonded connections at one or more locations along each interconnect line. However, as mentioned above, the interconnect lines of a data bus do not necessarily need to be parallel.

Through interconnect lines and vias, the data bus 2022 connects to circuits defined on the second die 2010, so that through these connections these circuits can receive data from and supply data to the data I/O unit 2030. Through the direct bonded connections, the data bus 2022 also connects to interconnect lines/pads on the top interconnect layer 2015 of the first die 2005. These interconnect lines/pads on the interconnect layer 2015 connect to circuits on the first die 2005 through interconnect lines and vias of the first die 2005. Through these connections (i.e., the interconnect lines, vias and direct-bonded connections), the circuits defined on the first die 2005 can receive data from and supply data to the data I/O unit 2030.

Some embodiments distribute an IO circuit between two or more vertically stacked IC dies. For instance, some embodiments distribute a SerDes circuit between two vertically stacked IC dies. A SerDes circuit includes digital (logic) portions and analog portions. In some embodiments, the digital portions of the SerDes circuit are implemented on a first IC die, while the analog portions are implemented on a second IC die that is face-to-face mounted or otherwise vertically stacked with the first die. This IO interface has to involve the interaction between these two layers before signals are passed to the core circuitry. Only the two layers together complete the IO circuitry.

FIG. 20B illustrates another example of two face-to-face mounted IC dies that form a 3D chip 2052 and that share data I/O circuits. In this example, the I/O circuitry is defined on both dies 2055 and 2060 in order to reduce the area that the I/O circuitry consumes on each die. The I/O circuitry in this example includes two sets of power and ground rails 2062-2068, ESD (electro-static discharge) circuits 2073, drivers 2074, and decoupling capacitors (not shown).

The power/ground rails include two power rails **2062** and **2066** on the top interconnect layer **2070** of the second die **2060** and two ground rails **2064** and **2068** on the top interconnect layer **2072** of the first die **2055**. The power and ground rails **2062** and **2064** are the I/O interface power and ground rails that carry the power and ground signals for the I/O circuitry (e.g., I/O drivers). The power and ground rails **2066** and **2068** are the core power and ground rails that carry the power and ground signals for the core circuits of the first and second dies. The core circuits of the dies are the circuits that perform the computation operations of the dies.

In some embodiments, each power or ground rail is a rectangular ring formed by four rectangular segments, with each segment spanning one of the four sides of the die and connecting to two other rectangular segments of the same rail. In other embodiments, each power rail is not a contiguous ring that spans the entire periphery of the die, as it has one or more discontinuities (e.g., at the corners of the interconnect layer on which it resides). Also, while showing power and ground rails on the top interconnect layers **2070** and **2072**, one of ordinary skill will realize that in some embodiments power and ground rails exist on other interconnect layers of the dies (e.g., power rails on several interconnect layers of one die, and ground rails on several interconnect layers of the other die).

Multiple drivers **2074** are formed on the substrate **2082** of the first die **2055**. When signals traverse from circuits outside of the dies to core circuits of the die, the drivers **2074** level shift these signals to convert them from their external voltage levels to internal voltage levels. Similarly, when signals traverse from the core circuits of the die to circuits outside of the dies, the drivers **2074** level shift these signals to convert them from their internal voltage levels to external voltage levels. The drivers **2074** also provide signal buffering. To perform their operations (e.g., level shifting operations), the drivers receive power and ground signals from the power and ground rails **2062-2068**.

In some embodiments, the substrate **2080** of the second die **2060** includes the signal pads that are connected through TSVs to signal pads on the backside of the second die **2060**. These backside signal pads are connected to external interconnects (e.g., micro bump arrays) that receive signals from and supply signals to external circuits outside of the 3D chip **2052**. Through these backside signal pads, the signals pads on the front side of the second die substrate **2080** receive signals from external circuits for the I/O circuitry, and supply signals from the I/O circuitry to external circuits. One of ordinary skill will realize that other embodiments use other structures (e.g., copper pillars connected through interposers) to supply signals to the dies.

As shown, the second die **2060** includes the ESD circuits **2073** that are defined on its substrate, while the first die **2055** includes the drivers **2074** that are defined on its substrate. The ESD circuits are for maintaining signal stability inside of the chip. The ESD circuits are designed in some embodiments to dissipate quickly external irregular signal surges, in order to maintain signal stability inside of the chip. Each die **2055** or **2060** also includes decoupling capacitors that are for maintaining signal stability inside of the chip by eliminating signal noise from affecting signal quality on the chip.

The power or ground rail (I/O or core) on the top interconnect layer of each die has to provide its power signal or ground signal to the other die through the top interconnect layer of the other die. In some embodiments, this is done by having the power signal or ground signal traverse down one layer on the same die with one or more vias, traverse along interconnect lines on that layer, and then traverse back up

along one or more vias to one or more pads on the top interconnect layer of its die. These pads have direct-bonded connections (e.g., DBI connections) to pads on the top interconnect layer of the other die. The pads on the other die then distribute to circuits on the other die the received power or ground signals through vias and interconnect lines. Also, between respective power and ground rails (e.g., I/O power and ground rails, or core power and ground rails), some embodiments define decoupling capacitors in the face-to-face mounted layer coupling the two dies, in order to suppress the effect of signal noise on the power supply.

In some embodiments, the core power and ground rails **2066** and **2068** respectively connect to interior power and ground lines on the same interconnect layers as the rails **2066** and **2068**. These interior power and ground lines in some embodiments form an interior power mesh, such as the power mesh shown in either FIG. **9** or **10**. Also, in some embodiments, the top interconnect layer of each die **2055** or **2060** has additional direct-bonded connections with the top interconnect layer of the other die in order to receive inputs for the I/O circuitry components (e.g., for the ESD circuits, drivers, etc.) from the other die, and to provide outputs from the I/O circuitry components (e.g., for the ESD circuits, drivers, etc.) to the other die.

In prior IC designs, the power/ground rails for the I/O circuitry and IC core are typically defined as four concentric rectangular rings that are placed on a single die along with the decoupling capacitors, drivers, and ESD circuits of the I/O circuitry. Placing these components on one die requires the I/O circuitry to consume a lot of area on the periphery of an IC die. This, in turn, leads to larger dies or leaves less space for the IC core. The 3D chip **2052**, on the other hand, does not suffer these shortcomings as its I/O circuitry is split on the two dies **2055** and **2060**. Also, by placing the power and ground rails (for the I/O and the core) on different dies, the 3D chip **2052** has far less area devoted to the power and ground rails, leaving more space to the circuits of the IC's core.

One of ordinary skill will understand that the 3D chip **2052** presents only one way by which the I/O circuits and power rails can be distributed among two vertically stacked (e.g., two face-to-face mounted dies). Other embodiments use other techniques to distribute the I/O circuits and power rails. For instance, in other embodiments, one I/O power rail is on the periphery of a top interconnect layer of a first die, while another I/O power rail is closer to the center of the top interconnect layer(s) of a second die vertically stacked (e.g., face-to-face mounted) with the first die. Still other embodiments define multiple stripes of I/O rails on the higher interconnect layers of two vertically stacked dies and then define multiple cores between different stripes. Accordingly, the architecture presented in FIG. **22B** is only illustrative of how some embodiments distribute the I/O circuit and power rails between two vertically stacked dies.

FIG. **21** illustrates a device **2102** that uses a 3D IC **2100** (like any of the 3D IC **100**, **900-2000**). In this example, the 3D IC **2100** is formed by two face-to-face mounted IC dies **2105** and **2110** that have numerous direct bonded connections **2115** between them. In other examples, the 3D IC **2100** includes three or more vertically stacked IC dies. As shown, the 3D IC die **2100** includes a cap **2150** that encapsulates the dies of this IC in a secure housing **2125**. On the back side of the die **2110** one or more TSVs and/or interconnect layers **2106** are defined to connect the 3D IC to a ball grid array **2120** (e.g., a micro bump array) that allows this to be mounted on a printed circuit board **2130** of the device **2102**. The device **2102** includes other components (not shown). In



some embodiments, examples of such components include one or more memory storages (e.g., semiconductor or disk storages), input/output interface circuit(s), one or more processors, etc.

In some embodiments, the first and second dies **2105** and **2110** are the first and second dies shown in any of the FIGS. **1-20**. In some of these embodiments, the second die **2110** receives power, clock and/or data bus signals through the ball grid array, and routes the received signals to shared power, clock and/or data bus lines on its shared interconnect layer(s), from where the received signals can be supplied to the interconnects/circuits of the first die through direct bonded connections between the first and second dies **2105** and **2110**.

FIG. **22** provides another example of a 3D chip **2200** that is formed by two face-to-face mounted IC dies **2205** and **2210** that are mounted on a ball grid array **2240**. In this example, the first and second dies **2205** and **2210** are face-to-face connected through direct bonded connections (e.g., DBI connections). As shown, several TSVs **2222** are defined through the second die **2210**. These TSVs electrically connect to interconnects/pads on the backside of the second die **2210**, on which multiple levels of interconnects are defined.

In some embodiments, the interconnects on the backside of the second die **2210** create the signal paths for defining one or more system level circuits for the 3D chip **2200** (i.e., for the circuits of the first and second dies **2205** and **2210**). Examples of system level circuits are power circuits, clock circuits, data I/O signals, test circuits, etc. In some embodiments, the circuit components that are part of the system level circuits (e.g., the power circuits, etc.) are defined on the front side of the second die **2210**. The circuit components can include active components (e.g., transistors, diodes, etc.), or passive/analog components (e.g., resistors, capacitors (e.g., decoupling capacitors), inductors, filters, etc.

In some embodiments, some or all of the wiring for interconnecting these circuit components to form the system level circuits are defined on interconnect layers on the backside of the second die **2210**. Using these backside interconnect layers to implement the system level circuits of the 3D chip **2200** frees up one or more interconnect layers on the front side of the second die **2210** to share other types of interconnect lines with the first die **2205**. The backside interconnect layers are also used to define some of the circuit components (e.g., decoupling capacitors, etc.) in some embodiments. As further described below, the backside of the second die **2210** in some embodiments can also connect to the front or back side of a third die.

In some embodiments, one or more of the layers on the backside of the second die **2210** are also used to mount this die to the ball grid array **2240**, which allows the 3D chip **2100** to mount on a printed circuit board. In some embodiments, the system circuitry receives some or all of the system level signals (e.g., power signals, clock signals, data I/O signals, test signals, etc.) through the ball grid array **2240** connected to the backside of the third die.

In some embodiments, the backside of the second die **2210** of chip **2200** is used to define one or more interconnect layers on which power/ground lines are defined. For instance, in some embodiments, a first interconnect layer on the backside of the second die provides a first set of alternating power and ground lines, while a second interconnect layer on this backside provides another set of alternating power and ground lines. These two sets of alternating power/ground lines form a power mesh (similar the meshes described above by reference to FIGS. **9** and **10**)

as vias connect power lines in each set to power lines in the other set and ground lines in each set to ground lines in the other set.

The power/ground lines on such backside interconnect layer(s) are thicker and wider lines in some embodiments than the lines on the top interconnect layers on the front side(s) of the first and second dies **2205** and **2210**. Gate stress is an undesirable side effect of having very thick power lines on the top interconnect layers on the front sides of the first and second dies. However, this is not an issue when placing thick (e.g., wide) power lines on the backside of IC dies. The thicker and wider power lines on the backside of the second die have less resistance (suffer less signal degradation) and are ideal for supplying additional power signals to the core circuits on the first and second dies. The circuits towards the center of a die can experience power signal degradation due to the power consumption of the circuits that are closer to the periphery of the die. Accordingly, in some embodiments, the power/ground lines on the backside of the second die is used in some embodiments to provide non-degraded power signals to the circuits that are closer to the middle of the first and second dies.

Alternatively to, or conjunctively with, defining the power/ground lines on the backside of the second die **2210**, clock lines and/or data-bus lines are defined in some embodiments on the backside of the second die. Such clock lines and data-bus lines can be used to achieve analogous interconnect architectures to those described above by reference to FIGS. **11-20B**. As the backside interconnects can be thicker and wider, the clock lines and data-bus lines can enjoy the same benefits as those described above for the power lines that are defined on the backside of the second die **2210**. In some embodiments, the interconnect line widths on the backside of the second die **2210** are in the range of 1-10 microns, while the interconnect line widths on the interconnect layers on the front side of the first and second dies **2205** and **2210** are in the range of 1 microns or less.

FIG. **23** illustrates a manufacturing process **2300** that some embodiments use to produce the 3D chip **2200** of FIG. **22**. This figure will be explained by reference to FIGS. **24-27**, which show two wafers **2405** and **2410** at different stages of the process. Once cut, the two wafers produce two stacked dies, such as dies **2205** and **2210**. Even though the process **2300** of FIG. **23** cuts the wafers into dies after the wafers have been mounted and processed, the manufacturing process of other embodiments performs the cutting operation at a different stage at least for one of the wafers. Specifically, some embodiments cut the first wafer **2405** into several first dies that are each mounted on the second wafer before the second wafer is cut into individual second dies.

As shown, the process **2300** starts (at **2305**) by defining components (e.g., transistors) on the substrates of the first and second wafers **2405** and **2410**, and defining multiple interconnect layers above each substrate to define interconnections that form micro-circuits (e.g., gates) on each die. To define these components and interconnects on each wafer, the process **2300** performs multiple IC fabrication operations (e.g., film deposition, patterning, doping, etc.) for each wafer in some embodiments. FIG. **24** illustrates the first and second wafers **2405** and **2410** after several fabrication operations that have defined components and interconnects on these wafers. As shown, the fabrication operations for the second wafer **2410** defines several TSVs **2412** that traverse the interconnect layers of the second wafer **2410** and penetrate a portion of this wafer's substrate **2416**.

After the first and second wafers have been processed to define their components and interconnects, the process **2300**

## 25

face-to-face mounts (at 2310) the first and second wafers 2205 and 2210 through a direct bonding process, such as a DBI process. FIG. 25 illustrates the first and second wafers 2405 and 2410 after they have been face-to-face mounted through a DBI process. As shown, this DBI process creates a number of direct bonded connections 2426 between the first and second wafers 2405 and 2410.

Next, at 2315, the process 2300 performs a thinning operation on the backside of the second wafer 2410 to remove a portion of this wafer's substrate layer. As shown in FIG. 26, this thinning operation exposes the TSVs 2412 on the backside of the second wafer 2410. After the thinning operation, the process 2300 defines (at 2320) one or more interconnect layers 2430 the second wafer's backside. FIG. 27 illustrates the first and second wafers 2405 and 2410 after interconnect layers have been defined on the second wafer's backside.

These interconnect layers 2430 include one or more layers that allow the 3D chip stack to electrically connect to the ball grid array. In some embodiments, the interconnect lines/pads on the backside of the third wafer also produce one or more redistribution layers (RDL layers) that allow signals to be redistributed to different locations on the backside. The interconnect layers 2430 on the backside of the second die in some embodiments also create the signal paths for defining one or more system level circuits (e.g., power circuits, clock circuits, data I/O signals, test circuits, etc.) for the circuits of the first and second dies. In some embodiments, the system level circuits are defined by circuit components (e.g., transistors, etc.) that are defined on the front side of the second die. The process 2300 in some embodiments does not define interconnect layers on the backside of the second wafer to create the signal paths for the system level circuits, as it uses only the first and second dies' interconnect layers between their two faces for establishing the system level signal paths.

After defining the interconnect layers on the backside of the second wafer 2410, the process cuts (at 2325) the stacked wafers into individual chip stacks, with each chip stack include two stacked IC dies 2205 and 2210. The process then mounts (at 2330) each chip stack on a ball grid array and encapsulates the chip stack within one chip housing (e.g., by using a chip case). The process then ends.

In some embodiments, three or more IC dies are stacked to form a 3D chip. FIG. 28 illustrates an example of a 3D chip 2800 with three stacked IC dies 2805, 2810 and 2815. In this example, the first and second dies 2805 and 2810 are face-to-face connected through direct bonded connections (e.g., DBI connections), while the third and second dies 2815 and 2810 are face-to-back connected (e.g., the face of the third die 2815 is mounted on the back of the second die 2810). In some embodiments, the first and second dies 2805 and 2810 are the first and second dies shown in any of the FIGS. 1-20.

In FIG. 28, several TSVs 2822 are defined through the second die 2810. These TSVs electrically connect to interconnects/pads on the backside of the second die 2810, which connect to interconnects/pads on the top interconnect layer of the third die 2815. The third die 2815 also has a number of TSVs that connect signals on the front side of this die to interconnects/pads on this die's backside. Through interconnects/pads, the third die's backside connects to a ball grid array 2840 that allows the 3D chip 2800 to mount on a printed circuit board.

In some embodiments, the third die 2815 includes system circuitry, such as power circuits, clock circuits, data I/O circuits, test circuits, etc. The system circuitry of the third

## 26

die 2815 in some embodiments supplies system level signals (e.g., power signals, clock signals, data I/O signals, test signals, etc.) to the circuits of the first and second dies 2805 and 2810. In some embodiments, the system circuitry receives some or all of the system level signals through the ball grid array 2840 connected to the backside of the third die.

FIG. 29 illustrates another example of a 3D chip 2900 with more than two stacked IC dies. In this example, the 3D chip 2900 has four IC dies 2905, 2910, 2915 and 2920. In this example, the first and second dies 2905 and 2910 are face-to-face connected through direct bonded connections (e.g., DBI connections), while the third and second dies 2915 and 2910 are face-to-back connected (e.g., the face of the third die 2915 is mounted on the back of the second die 2910) and the fourth and third dies 2920 and 2915 are face-to-back connected (e.g., the face of the fourth die 2920 is mounted on the back of the third die 2915). In some embodiments, the first and second dies 2905 and 2910 are the first and second dies shown in any of the FIGS. 1-20.

In FIG. 29, several TSVs 2922 are defined through the second, third and fourth die 2910, 2915 and 2920. These TSVs electrically connect to interconnects/pads on the backside of these dies, which connect to interconnects/pads on the top interconnect layer of the die below or the interconnect layer below. Through interconnects/pads and TSVs, the signals from outside of the chip are received from the ball grid array 2940.

Other embodiments use other 3D chip stacking architectures. For instance, instead of face-to-back mounting the fourth and third dies 2920 and 2915 in FIG. 29, the 3D chip stack of another embodiment has these two dies face-to-face mounted, and the second and third dies 2910 and 2915 back-to-back mounted. This arrangement would have the third and fourth dies 2915 and 2920 share a more tightly arranged set of interconnect layers on their front sides.

While the invention has been described with reference to numerous specific details, one of ordinary skill in the art will recognize that the invention can be embodied in other specific forms without departing from the spirit of the invention. For instance, one of ordinary skill will understand that even though several H-trees were described above as example of clock distribution networks, other embodiments use other types of clock distribution networks. Also, in some embodiments, the stacked dies in a 3D chip share multiple different clock trees on multiple shared interconnect layers in order to distribute multiple different clock signals (e.g., to distribute a different clock signal with each different shared clock tree).

In the examples illustrated in FIG. 1-20, a first IC die is shown to be face-to-face mounted with a second IC die. In other embodiments, the first IC die is face-to-face mounted with a passive interposer that electrically connects the die to circuits outside of the 3D chip or to other dies that are face-to-face mounted or back-to-face mounted on the interposer. In some of these embodiments, the passive interposer can include the power, clock, and/or data bus interconnect line architectures that were described in FIGS. 1-20 for the second dies in these examples. In other words, the interposer can provide the interconnect layers for establishing the power, clock and data-bus lines of the 3D chip.

In some embodiments, the preferred wiring directions of the top layer of the interposer is orthogonal to the preferred wiring directions of the top layer of the first die. This can be achieved by using similar techniques to those described above by reference to FIGS. 6-8. Some embodiments place

a passive interposer between two faces of two dies. Some embodiments use an interposer to allow a smaller die to connect to a bigger die.

Also, the 3D circuits and ICs of some embodiments have been described by reference to several 3D structures with vertically aligned IC dies. However, other embodiments are implemented with a myriad of other 3D structures. For example, in some embodiments, the 3D circuits are formed with multiple smaller dies placed on a larger die or wafer. FIG. 30 illustrates one such example. Specifically, it illustrates a 3D chip 3000 that is formed by face-to-face mounting three smaller dies 3010a-c on a larger die 3005. All four dies are housed in one chip 3000 by having one side of this chip encapsulated by a cap 3020, and the other side mounted on a micro-bump array 3025, which connects to a board 3030 of a device 3035. Some embodiments are implemented in a 3D structure that is formed by vertically stacking two sets of vertically stacked multi-die structures.

The invention claimed is:

1. A three-dimensional (3D) circuit comprising:
  - a first integrated circuit (IC) die comprising a first semiconductor substrate and a first set of interconnect layers defined on the first semiconductor substrate;
  - a second IC die comprising a second semiconductor substrate and a second set of interconnect layers defined on the second semiconductor substrate, wherein a second-set interconnect layer comprises a plurality of interconnect segments that form a data bus that traverses along the second-set interconnect layer to carry a set of data signals, the second IC die face-to-face mounted with the first IC die; and
  - a plurality of direct-bonded connections between the first and second sets of interconnect layers to allow the data bus on the second IC die to provide data to, and to receive data from, a set of circuits of the first IC die.
2. The 3D circuit of claim 1, wherein the plurality of interconnect segments forming the data bus are parallel lines.
3. The 3D circuit of claim 2, wherein the parallel lines are physically parallel lines.
4. The 3D circuit of claim 2, wherein the parallel lines are topologically parallel lines that traverse the second-set interconnect layer to connect (i) to a first plurality of adjacent locations on the second-set interconnect layer and (ii) to a second plurality of adjacent locations on the second-set interconnect layer.
5. The 3D circuit of claim 1, wherein a set of at least 1000 direct-bonded connections/mm<sup>2</sup> allow signals to traverse between the first and second IC dies, and a subset of the plurality of direct-bonded connections carries signals to and from the data bus.
6. The 3D circuit of claim 1, wherein a set of at least 10000 direct-bonded connections/mm<sup>2</sup> allow signals to traverse between the first and second IC dies, and a subset of the plurality of direct-bonded connections carries signals from the data bus.
7. The 3D circuit of claim 1, wherein a center-to-center pitch between two neighboring direct-bonded connections in each of a plurality of neighboring direct-bonded connections is 5 μm or less.

8. The 3D circuit of claim 1, wherein a center-to-center pitch between two neighboring connections in each of a plurality of neighboring connections is 0.5 μm or less.

9. The 3D circuit of claim 1, wherein the first and second IC dies are face-to-face directly bonded, wherein at least a subset of direct-bonded connections that exchange data-bus signals between the first and second IC dies are 10 microns or shorter.

10. The 3D circuit of claim 9, wherein the direct bond comprises a hybrid bond.

11. The 3D circuit of claim 1, wherein the set of data signals carried by the data bus are from a memory that is defined on the second semiconductor substrate of the second IC die.

12. The 3D circuit of claim 1, wherein the set of data signals carried by the data bus are from a circuit outside of the 3D circuit.

13. The 3D circuit of claim 12, further comprising a plurality of through silicon vias (TSVs) that pass through the second semiconductor substrate to receive data signals on a back side of the second IC die from the circuit outside of the 3D circuit and to supply the data signals to a front side of the second IC die for the data signals to be supplied through vias to the data bus on the second-set interconnect layer.

14. The 3D circuit of claim 12, further comprising a data input/output interface defined on the second semiconductor substrate of the second die, wherein the set of data signals from the circuit outside of the 3D circuit pass through the data input/output interface before being forwarded to the data bus.

15. The 3D circuit of claim 12, wherein the data bus receives signals from the first IC die that the second IC die has to output from the 3D circuit to a circuit outside of the 3D circuit.

16. The 3D circuit of claim 1, wherein, in addition to the second-set interconnect layer of the second IC die, the data bus is further defined on another interconnect layer of the second IC die.

17. The 3D circuit of claim 1, wherein each IC die of the first and second IC dies comprises a plurality of transistors and a plurality of circuit elements formed by interconnecting transistors of the plurality of transistors with interconnect segments on a respective set of interconnect layers of the IC die.

18. The 3D circuit of claim 1, wherein the direct-bonded connections are native connections that allow signals to span the first and second IC dies without any modifications.

19. The 3D circuit of claim 18, wherein the native connections allow the signals to span the first and second IC dies without traversing any intervening circuit.

20. The 3D circuit of claim 1, further comprising a third IC die that is vertically stacked with the first and second IC dies and that receives a data signal carried by the data bus on the second-set interconnect layer.

21. The 3D circuit of claim 1, wherein the plurality of direct-bonded connections is between the second-set interconnect layer of the second set of interconnect layers of the second IC die and a top interconnect layer of the first set of interconnect layers of the first IC die.