



US011839804B2

(12) **United States Patent**  
**Morin et al.**

(10) **Patent No.:** **US 11,839,804 B2**  
(45) **Date of Patent:** **Dec. 12, 2023**

(54) **INTERACTIVE EXERCISE AND TRAINING SYSTEM**

(71) Applicant: **Litebox Technologies, Inc.**, Hampton, NH (US)  
(72) Inventors: **Jeffrey W. Morin**, Exeter, NH (US); **Todd A. Dagues**, Boston, MA (US); **Arvin G. Abadilla**, Carlsbad, CA (US); **Matthew A. Froncillo**, San Diego, CA (US); **Adam V. Hickerson**, Oceanside, CA (US); **Donald I. Lambe**, Watertown, MA (US)

(73) Assignee: **Liteboxer Technologies, Inc.**, Hampton, NH (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/688,325**

(22) Filed: **Mar. 7, 2022**

(65) **Prior Publication Data**  
US 2022/0184480 A1 Jun. 16, 2022

**Related U.S. Application Data**  
(60) Division of application No. 16/188,128, filed on Nov. 12, 2018, now Pat. No. 11,266,894, and a (Continued)

(51) **Int. Cl.**  
*A63B 69/32* (2006.01)  
*A63B 71/06* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *A63B 69/32* (2013.01); *A63B 71/0622* (2013.01); *A63B 2220/833* (2013.01); *A63B 2225/50* (2013.01)

(58) **Field of Classification Search**  
CPC ..... *A63B 1/00*; *A63B 24/0075*; *A63B 69/32*; *A63B 71/0622*; *A63B 2024/0068*; (Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,974,833 A \* 12/1990 Hartman ..... A63B 69/0053 482/84  
8,011,222 B2 \* 9/2011 Wiber ..... A63B 69/322 482/84

(Continued)


*Primary Examiner* — Joshua Lee

(74) *Attorney, Agent, or Firm* — David H. Judson

(57) **ABSTRACT**

A punching bag training comprises a flexible housing adapted to be wrapped around a punching bag. The housing supports a strike pad array. Each strike pad in the array comprises a force sensor to detect strikes, together with a plurality of light emitting diodes (LEDs) that are positioned around the force sensor and that are lit when the user strikes the pad accurately (e.g., within a predetermined strike zone, and within a predetermined time). In addition, each strike pad has associated therewith an extension (or connecting) portion that couples the strike pad to the center portion. The connecting portion advantageously includes a set of LEDs that are selectively lit to telegraph a hit point to the user, namely, the strike pad associated with the connecting portion. The LEDs arranged on the connecting portion serve as a runway with the LEDs being lit progressively from the center portion and outward toward the strike pad to be hit next in a programmed hit sequence. As the user interacts with the system, speed, timing and accuracy preferably are measured to determine a score. The lighting elements are controlled using a controller unit that may be integral with the housing, attached thereto, or coupled to the housing wirelessly. The controller unit outputs one or more programmed hit sequences (i.e., to provide the control signals that activate the LEDs), and to detect and record electrical signals generated by the force sensors as the user strikes the pads.

**10 Claims, 7 Drawing Sheets**



**Related U.S. Application Data**

continuation-in-part of application No. 16/016,639,  
filed on Jun. 24, 2018, now Pat. No. 10,124,227.

(58) **Field of Classification Search**

CPC ..... A63B 2071/0625; A63B 2207/02; A63B  
2209/10; A63B 2220/40; A63B 2220/51;  
A63B 2220/833; A63B 2225/50

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,931,539 B1 \* 4/2018 de Pablos ..... A63B 71/0616  
9,943,742 B2 \* 4/2018 Burt, Jr. .... A63B 69/322  
10,016,650 B2 \* 7/2018 Shaw ..... A63B 71/0622  
2002/0098946 A1 \* 7/2002 Clark ..... A63B 69/222  
482/1

2005/0288159 A1 \* 12/2005 Tackett ..... A63B 69/22  
482/84  
2006/0258515 A1 \* 11/2006 Kang ..... A63B 69/00  
482/83  
2008/0125293 A1 \* 5/2008 Ng ..... A63B 69/32  
482/84  
2009/0048069 A1 \* 2/2009 Sheedy ..... A63B 24/0006  
482/8  
2011/0172060 A1 \* 7/2011 Morales ..... A63B 69/0053  
482/8  
2014/0366645 A1 \* 12/2014 Tsai ..... G01L 5/0052  
73/862.041  
2016/0367856 A1 \* 12/2016 DePompe ..... A63B 71/0622  
2017/0021258 A1 \* 1/2017 Hoggatt ..... A63B 69/305  
2017/0036087 A1 \* 2/2017 Codrington ..... A63B 69/32  
2017/0312614 A1 \* 11/2017 Tran ..... G06F 3/00  
2018/0178103 A1 \* 6/2018 Zhang ..... A63B 69/32

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7

# INTERACTIVE EXERCISE AND TRAINING SYSTEM

## TECHNICAL FIELD

The subject disclosure relates generally to punching systems and methods with automated interactive components providing feedback for training and exercise.

## BACKGROUND OF THE RELATED ART

Recreational punching bags have been in use for many years. More recently, manufacturers have been including sensors and electronic devices to detect and visually/audibly register strikes of particular targets on the punching bag. A typical boxing system of this type provides punching pads disposed on some structure for hand and/or foot punch by a user. Sensors are connected to the pads for detecting strikes, and a controller is coupled to each sensor. A display may also be provided to output video and audio, e.g., for strike training, or providing quantitative feedback of actual strike results to the pads. These systems may be integral to the punching bag or supported in other structures that are mounted on the bag. Control electronics in or associated with these systems also may suitably programmed or adapted to interact (e.g., via WiFi or Bluetooth) with connected computers or mobile devices, and training sessions may be gamified, e.g., by integrating music, lighting, and other interactive content.

## BRIEF SUMMARY

An interactive system for exercise and training comprises a set of components. A primary component is a flexible housing adapted to be wrapped around or otherwise secured to a punching or kicking bag, wherein the housing supports a strike pad array positioned about a center portion. Each strike pad in the array comprises a force sensor to detect strikes, together with a plurality of light emitting diodes (LEDs) that are positioned around the force sensor and that are selectively controlled to be lit when the user strikes the pad accurately (e.g., within a predetermined strike zone, and within a predetermined time). In addition, each strike pad has associated therewith an extension (or connecting) portion that couples the strike pad to the center portion. The connecting portion advantageously includes a set of LEDs that are selectively lit to telegraph a hit point to the user, namely, the strike pad associated with the connecting portion. In particular, preferably the LEDs arranged on the connecting portion serve as a runway with the LEDs being lit progressively from the center portion and outward toward the strike pad to be hit next in a programmed hit sequence. As the user interacts with the system, speed, timing and accuracy preferably are measured to determine a score. The lighting elements are controlled using a controller unit that may be integral with the housing, attached thereto, or coupled to the housing remotely (e.g., via WiFi or Bluetooth). The controller unit includes processor-based (or electronics) suitably programmed by software (or otherwise configured) to output the programmed hit sequence (i.e., to provide the control signals that activate the LEDs), and to detect and record electrical signals generated by the force sensors as the user strikes the pads.

The foregoing has outlined some of the more pertinent features of the subject disclosure. These features should be construed to be merely illustrative. Many other beneficial

results can be attained by applying the disclosed subject matter in a different manner or by modifying the subject matter as will be described.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts the interactive exercise and training system comprising a flexible body supporting a strike pad array mounted on a punching bag, together with an associated controller unit;

FIG. 2 depicts another view of the wrap as mounted on a punching bag;

FIG. 3 depicts a preferred configuration of the strike pad array with covering removed to expose the lighting structures;

FIG. 4 depicts a single strike pad of the array together with its associated connecting portion that supports the runway lighting;

FIG. 5 depicts a user interface of a programming tool that is used to create a custom training session that associates a music source with a set of configured strike pad hit point locations and timing;

FIG. 6 depicts a representative controller unit architecture; and

FIG. 7 depicts an exploded view of a preferred implementation of the wrap of this disclosure.

## DETAILED DESCRIPTION

FIG. 1 depicts an interactive exercise and training system **100** comprising a body or housing **102** (sometimes referred to herein as a “wrap”) supporting a strike pad array **104**, together with an associated controller unit **105**. A power button/indicator **106** is used to activate the controller. One or more fastening straps not shown are attached to or integral to the body **102** and are used to secure the flexible body to a punching or kicking bag **108**. Typically, the interactive system is provided as an aftermarket or add-on to an existing bag **108**, but this is not a limitation. The body **102** is made of a flexible material (cloth, elastomer, or the like) and, as such, is adapted to rolled up for ease of transport. When attached to the punching bag, the strike pad array **104** presents to a set of strike zones **110** to the user. Each strike zone **110** (one of which is shown) is defined by a strike pad that is selectively positioned to present a hit target. As will be described, each of the strike zones **110** includes an embedded force sensor, and a zone is lit by a set of embedded LEDs **112** that encircle the zone when the user strikes the zone with appropriate accuracy, force and timing. While a preferred body or housing is configured as a shield and designed to be wrapped around and supported on the bag as depicted, this is not a limitation, as the system may implement a different body configuration and one that is affixed to the punching bag with or without straps. The body configuration also may be integral or otherwise integrated with the bag or the bag covering.

FIG. 2 depicts another view of the wrap **200** that includes the strike pad array **204** with the set of strike pads **206**, and the controller unit **208**. As also depicted, a pair of Y-straps (one of which is shown at **210**) are used to secure the wrap around the bag. Respective end portions of the straps support a fastener mechanism (not shown) such as a buckle, hook/loop assembly, a clasp or string assembly, or the like.

FIG. 3 depicts a preferred configuration of the strike pad array **300** with strike pad covering removed to expose the lighting structures in more detail. As depicted, in one embodiment, the strike pad array comprises a starburst (or

hub and spoke) configuration comprising strike pads **302** selectively positioned about a center portion **304**. Each strike pad **302** has associated therewith an outwardly-extending connecting portion **305**. In an alternative embodiment, the strike pads and the center portion are integral. The connecting portion may be part of the strike pad, part of the center portion, or a standalone structure. As shown, each strike pad **302** comprises a force sensor **306** surrounded by a circular set of LEDs **308**, together with an internal set of LEDs **310** arranged linearly from a center point **312** of the strike pad. The internal set of LEDs **310** are arranged along a line **315** that bisects the center point of a strike pad **302** and a center point **314** of the center portion **304** of the array itself. Each connecting portion **304** likewise includes a set of LEDs **316** arranged linearly, and LEDs **316** preferably are also aligned on line **315**. FIG. 4 depicts this strike pad lighting arrangement in additional detail. As will be described, the LEDs **316** and **310** (from the center outward) are configured to provide an LED “runway” that is selectively activated to telegraph to the user that the associated strike pad should be hit. In other words, when the runway is activated, the LEDs light sequentially from the center out. Typically, this cueing occurs throughout a session (or portion thereof), with different strike pads thereby being selected identified (randomly, or in some programmed sequence) to the user. As the LED runway lights are activated, they cue (telegraph) to the user that the associated pad (at the end of the runway) should then be hit. More than one strike pad may be identified at the same time such that a pair of LED runways are lit concurrently to cue the user to hit two pads together with his or her left and right hands.

The starburst configuration of the strike pad array shown in FIGS. 3 and 4 is not intended to be limited. The number and orientation of the strike pads may be varied, and there may be more than one center, although preferably the LED runway lighting structures are utilized in association with the strike pads to provide for enhanced play.

Control over the lighting sequence is provided by the controller unit **105**, which as noted typically also receives signals generated by the force sensors **306**. As the user interacts with the system, speed, timing and accuracy preferably are measured by the force sensors and the associated controller unit to determine a score or to provide other information. As noted above, the controller unit **105** may be integral with the housing, attached thereto (such as shown in FIG. 1), or coupled to the housing remotely (e.g., via WiFi or Bluetooth). As will be described in more detailed below, the controller unit includes processor-based (or electronics) suitably programmed by software (or otherwise configured) to output the programmed hit sequence (i.e., to provide the control signals that activate the LEDs), and to detect and record electrical signals generated by the force sensors as the user strikes the pads.

The controller unit **105** may be integrated with the strike pad array, as opposed to being a separate unit.

In one embodiment, a punch detection and measurement algorithm implements a moving threshold that filters the pressure reading from a force sensor; on a punch, the pressure reading changes rapidly and passes a threshold, and the algorithm determines the force to record preferably by taking a maximum value before the pressure reading returns below the threshold or a timeout occurs.

To facilitate gamification, the system preferably includes programming tools (e.g., a mobile device app, a desktop application, hardwired controls, etc.) to enable the user or other content provider (or indeed the system itself in an automated manner) to create a customized training or exercise

session. Preferably, a custom session links together source audio (e.g., a music track), and a set of strike pad hit point locations and timing. FIG. 5 depicts a representative display interface **500** that may be used for this purpose. As shown, preferably the display **500** comprises a panel **502** that includes a representation **504** of the strike pad array as previously described. An audio file (whose waveform is depicted) **506** is imported into the interface and rendered along a timeline as depicted. Juxtaposed under the timeline is a grid **508** that includes a number of grid lines corresponding to a number of strike pads in the array. Using an input/output device, the user inputs strike pad cues on the grid lines, such that these cues are then selectively aligned (timed) to occur at various points in the audio. A navigation box (not shown) may be provided and includes a graphical representation of the entire selection, and the user can use a display tool within that box to navigate to particular portions of the audio selection, which are then represented above (by selectively expanding or compressing the audio file together with the underlying grid). An additional set of controls provide additional programming functionality. These include, for example, a dropdown field **512** by which the user can select one of a set of grids to display, an audio file import field **514**, and a tempo selection field **516**. A Spawn External Simulator button **518** can be selected to render a simulation of the programmed session, and a Save Punch Track button **520** can be selected to save the programmed session. Once saved, the user then recalls the session. The information comprising the session (typically the audio file and the set of programming) is then transmitted or otherwise provided (by hardwire connection) to the controller unit **105** and the session initiated. Display area **524** may be used to render a simulation of a programmed session. The audio file may be programmed to be rendered (output) in the user’s mobile device, although the controller unit may include its own integral audio output system such as a speaker.

Machine or other learning may be applied to the system to provide for enhanced or more complex training sessions as the user increases his or her proficiency.

FIG. 6 depicts a representative software-based controller unit architecture. In a typical implementation, a controller on which the software executes comprises commodity hardware, an operating system, an application runtime environment, and a set of applications or processes and associated data, that provide the functionality of a given system or subsystem. In this embodiment, controller unit **600** comprises a communications layer **602**, which provides communications between processor **604**, memory **606**, persistent storage **608**, communications unit **610**, input/output (I/O) unit **612**, and display **614**. Program code **616** is located on computer-readable media **618** that is selectively removable and may be loaded onto or transferred to the controller unit for execution by processor. Program code **616** and computer-readable media **618** form computer program product **620**. An alternative to program-based control, the controller unit may include logic circuitry and other analog devices that provide the desired functionality (lighting control and force detection).

The interactive system of this disclosure also may include or utilize a client device for interacting with the controller unit. A client device typically is a mobile device, such as a smartphone, tablet (e.g., an iPhone® or iPad®) or wearable computing device. Such a device comprises a CPU (central processing unit), computer memory, such as RAM, and a drive. The device software includes an operating system (e.g., Apple iOS, Google® Android™, or the like), and generic support applications and utilities. Connectivity to

## 5

the interactive system typically is via a management application (a mobile app) that may be downloaded via a mobile application storefront (e.g., the AppStore). The management application provides data management functions, connectivity to social networks, and interactivity. The display interface depicted in FIG. 5 may be implemented using the mobile app or a desktop application.

As an alternative to LEDs, other lighting devices (e.g., EL, LCD, incandescent, halogen, etc.) may be used.

There is no requirement that the wrap be used on a punching bag; the wrap may also be attached to a flat surface (e.g., a wall), or otherwise affixed to a support structure, or even a person (who would then in effect serve as the target).

The controller unit includes a power source, e.g., a battery, which may be removable for recharge or replacement.

Preferably, the wrap comprises a stacked construction such as depicted in the exploded view shown in FIG. 7. In particular, the wrap 700 comprises the following layers from back to front: a fabric backing 702, a rear puck housing typically formed of hard plastic (for each sensor) 704, a flexible printed circuit board (PCB) 706 (such as depicted in FIG. 3), an upper puck housing (for each sensor) 708, a compression-molded foam layer 710 that absorbs the impact, and an outward facing front fabric layer 712. Layers 710 and 712 comprise a compression-molded front shield.

In addition to or in lieu of the force sensor (which typically is a resistive device), an accelerometer may be used to generate the hit detection.

In use, and to facilitate multi-player interactivity, the controller may be selectively programmed to capture and upload (e.g., by wireless transfer) hit data, exercise/training session data, scores, and the like, to multi-player gaming sites, other social media sites and the like. Such interactivity may include an instructor providing instructions (to users) via real-time or recorded audio/video. The instruction may include cues for punch location, timing and other exercises (e.g., push-ups, knee bends, etc.) during an interactive workout session. Instruction of this type can be given to multiple users, and their session results may then be used for competition or social sharing.

Having described our invention, we claim:

1. A method carried out in association with first and second users each having associated therewith a training device, the training device comprising a body configured to be positioned on or in association with a support surface, the body comprising an array of strike pads selectively positioned to provide a set of hit targets, wherein each strike pad has associated therewith a set of indicator lights, and a force sensor, the method comprising:

outputting content to the second user, the content having been previously generated in a training session involv-

## 6

ing the first user interacting with the training device associated with the first user, the content having associated therewith a data set comprising a set of hit points in a timed sequence, wherein a hit point represents the first user interacting with a particular one of the strike pads; and

as the content is output to the second user, selectively triggering the set of indicator lights in the training device associated with the second user based at least in part on the data set recorded during the training session involving the first user.

2. The method as described in claim 1 wherein the content is a video.

3. The method as described in claim 1 wherein the content is a video having an audio track.

4. The method as described in claim 1 wherein the training device associated with the second user is located remotely from the training device associated with the first user.

5. The method as described in claim 1 wherein the set of indicator lights are triggered as a cue to identify to the second user a next strike pad that is to be hit in a training sequence corresponding to the timed sequence.

6. The method as described in claim 1 wherein the first user is a trainer.

7. A method carried out in association with first and second users each having associated therewith a training device, the training device comprising a body configured to be positioned on or in association with a support surface, the body comprising an array of strike pads selectively positioned to provide a set of hit targets, wherein each strike pad has associated therewith a set of indicator lights, and a force sensor, the method comprising:

recording a training session as the first user interacts with the training device associated with the first user to generate content, the content having associated therewith a data set comprising a set of hit points in a timed sequence, wherein a hit point represents the first user interacting with a particular one of the strike pads; and providing the content including the data set to the second user, wherein information associated with the data set is configured to selectively trigger the set of indicator lights in the training device associated with the second user to identify to the second user a set of strike pads in a training sequence corresponding to the timed sequence.

8. The method as described in claim 7 wherein the content is a video.

9. The method as described in claim 7 wherein the content is a video having an audio track.

10. The method as described in claim 7 wherein the first user is a trainer.

\* \* \* \* \*