



US011841441B2

(12) **United States Patent**
Barber et al.

(10) **Patent No.:** **US 11,841,441 B2**
(45) **Date of Patent:** **Dec. 12, 2023**

(54) **LIDAR SYSTEM**

(71) Applicant: **AURORA OPERATIONS, INC.**,
Mountain View, CA (US)

(72) Inventors: **Zeb William Barber**, Bozeman, MT (US); **Stephen C. Crouch**, Bozeman, MT (US); **Ryan Moore Galloway**, Bozeman, MT (US); **Edward Joseph Angus**, Bozeman, MT (US); **Emil Kadlec**, Bozeman, MT (US)

(73) Assignee: **AURORA OPERATIONS, INC.**,
Mountain View, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 40 days.

(21) Appl. No.: **17/584,169**

(22) Filed: **Jan. 25, 2022**

(65) **Prior Publication Data**

US 2022/0146643 A1 May 12, 2022

Related U.S. Application Data

(63) Continuation of application No. 17/319,709, filed on May 13, 2021, now Pat. No. 11,262,455, which is a continuation of application No. 16/915,045, filed on Jun. 29, 2020, now Pat. No. 11,016,197.

(51) **Int. Cl.**

G01S 13/93 (2020.01)
G01S 17/931 (2020.01)
G01S 7/48 (2006.01)
G01S 7/4865 (2020.01)
G01S 17/32 (2020.01)
G01S 7/481 (2006.01)
G02B 26/10 (2006.01)

(52) **U.S. Cl.**

CPC **G01S 17/931** (2020.01); **G01S 7/4804** (2013.01); **G01S 7/4817** (2013.01); **G01S 7/4865** (2013.01); **G01S 17/32** (2013.01); **G02B 26/105** (2013.01)

(58) **Field of Classification Search**

None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,483,511 A 12/1969 Rabinow
3,947,816 A 3/1976 Rabedeau
4,140,903 A 2/1979 Clark
5,646,765 A 7/1997 Laakmann et al.
5,892,575 A 4/1999 Marino
8,988,754 B2 3/2015 Sun et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 105026970 A 11/2015
EP 2 929 382 A1 10/2015

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion on PCT Appl. Ser. No. PCT/US2021/038093 dated Jul. 29, 2021 (6 pages).


Primary Examiner — Hovhannes Baghdasaryan

(74) *Attorney, Agent, or Firm* — FOLEY & LARDNER LLP

(57) **ABSTRACT**

A LIDAR system includes a laser source, a first scanner, and a second scanner. The first scanner receives a first beam from the laser source and applies a first angle modulation to the first beam to output a second beam at a first angle. The second scanner receives the second beam and applies a second angle modulation to the second beam to output a third beam at a second angle.

15 Claims, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,476,981	B2	10/2016	Yaacobi et al.
10,003,168	B1	6/2018	Villeneuve
10,042,159	B2	8/2018	Dussan et al.
10,338,321	B2	7/2019	Hosseini et al.
10,495,757	B2	12/2019	Dussan et al.
10,627,517	B2	4/2020	Yaacobi et al.
10,761,272	B2	9/2020	Hosseini et al.
11,150,411	B2	10/2021	Hosseini et al.
11,372,106	B2	6/2022	Yaacobi et al.
2005/0099637	A1	5/2005	Kacyra et al.
2005/0173770	A1	8/2005	Linden et al.
2010/0053715	A1	3/2010	O'Neill et al.
2011/0298820	A1	12/2011	Hajjar
2016/0047895	A1	2/2016	Dussan
2016/0191870	A1	6/2016	Hajjar et al.
2017/0299697	A1	10/2017	Swanson
2017/0346347	A1	11/2017	Abiri et al.
2019/0212419	A1	7/2019	Jeong et al.
2020/0256960	A1	8/2020	Lachapelle et al.
2022/0003937	A1	1/2022	Hosseini et al.

FOREIGN PATENT DOCUMENTS

JP	6363619	B2	7/2018
KR	102181537	B1	11/2020
KR	102350191	B1	1/2022
WO	WO-2018/107237	A1	6/2018




FIG. 1A




FIG. 1B




FIG. 1C

100D




FIG. 1D




FIG. 2A






FIG. 2B




FIG. 4




FIG. 5






FIG. 6




FIG. 7




FIG. 8

1**LIDAR SYSTEM****CROSS-REFERENCE TO RELATED APPLICATION**

This application is a continuation of U.S. patent application Ser. No. 17/319,709, filed May 13, 2021, which is a continuation of U.S. patent application Ser. No. 16/915,045, filed Jun. 29, 2020. The entire disclosures of U.S. patent application Ser. No. 16/915,045 and U.S. patent application Ser. No. 17/319,709 are hereby incorporated by reference as if fully set forth herein.

BACKGROUND

Optical detection of range using lasers, often referenced by a mnemonic, LIDAR, for light detection and ranging, also sometimes called laser RADAR, is used for a variety of applications, from altimetry, to imaging, to collision avoidance. LIDAR provides finer scale range resolution with smaller beam sizes than conventional microwave ranging systems, such as radio-wave detection and ranging (RADAR).

SUMMARY

At least one aspect relates to a light detection and ranging (LIDAR) system. The LIDAR system includes a laser source, a first scanner, and a second scanner. The first scanner receives a first beam from the laser source and applies a first angle modulation to the first beam to output a second beam at a first angle. The second scanner receives the second beam and applies a second angle modulation to the second beam to output a third beam at a second angle.

At least one aspect relates to an autonomous vehicle control system. The autonomous vehicle control system includes a first scanner, a second scanner, one or more detectors, and one or more processors. The first scanner receives a first beam from the laser source and applies a first angle modulation to the first beam to output a second beam at a first angle. The second scanner receives the second beam and applies a second angle modulation to the second beam to output a third beam at a second angle. The one or more detectors receive a return beam from an object responsive to the third beam and output a signal responsive to the return beam. The one or more processors are configured to determine at least one of a range to or a velocity of the object using the signal, and control operation of an autonomous vehicle responsive to the at least one of the range or the velocity.

At least one aspect relates to an autonomous vehicle. The autonomous vehicle includes a LIDAR system, at least one of a steering system or a braking system, and a vehicle controller. The LIDAR system includes a laser source, a first scanner that receives a first beam from the laser source and applies a first angle modulation to the first beam to output a second beam at a first angle, and a second scanner that receives the second beam and applies a second angle modulation to the second beam to output a third beam at a second angle. The vehicle controller includes one or more processors configured to determine at least one of a range to or a velocity of the object using the signal, and control operation of an autonomous vehicle responsive to the at least one of the range or the velocity.

Those skilled in the art will appreciate that the summary is illustrative only and is not intended to be in any way limiting. Any of the features described herein may be used

2

with any other features, and any subset of such features can be used in combination according to various embodiments. Other aspects, inventive features, and advantages of the devices and/or processes described herein, as defined solely by the claims, will become apparent in the detailed description set forth herein and taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Implementations are illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings in which like reference numerals refer to similar elements and in which:

FIG. 1A is a block diagram of an example of a system environment for autonomous vehicles;

FIG. 1B is a block diagram of an example of a system environment for autonomous commercial trucking vehicles;

FIG. 1C is a block diagram of an example of a system environment for autonomous commercial trucking vehicles;

FIG. 1D is a block diagram of an example of a system environment for autonomous commercial trucking vehicles;

FIG. 2A is a block diagram of an example of a LIDAR system;

FIG. 2B is a chart of an example of angle profiles of light beams achieved using a LIDAR system;

FIG. 3 is a block diagram of an example of a LIDAR system that includes an optical phased array;

FIG. 4 is a block diagram of an example of a LIDAR system that includes a micro-electromechanical system (MEMS) phased array;

FIG. 5 is a block diagram of an example of a LIDAR system that includes a MEMS mirror scanner;

FIG. 6 is a chart of an example of angle profiles of light beams achieved using the LIDAR system of FIG. 5;

FIG. 7 is a block diagram of an example of a LIDAR system that includes an electro-optic (EO) scanner; and

FIG. 8 is a chart of an example of angle profiles of light beams achieved using the LIDAR system of FIG. 7.

DETAILED DESCRIPTION

A LIDAR system can generate and transmit a light beam that an object can reflect or otherwise scatter as a return beam corresponding to the transmitted beam. The LIDAR system can receive the return beam, and process the return beam or characteristics thereof to determine parameters regarding the object such as range and velocity. The LIDAR system can apply various frequency or phase modulations to the transmitted beam, which can facilitate relating the return beam to the transmitted beam in order to determine the parameters regarding the object.

Due to factors such as the relative velocities of the LIDAR system—such as if the LIDAR system is implemented by an autonomous vehicle—and the object from which the return beam is received, the position of the LIDAR system may change between when the transmitted beam is outputted and the return beam is received. The position may change to an extent that it can become difficult to accurately determine the parameters regarding the object using the transmitted beam and the return beam. This may become notable in applications such as autonomous trucking, in which the LIDAR system may be expected to determine range and velocity of objects at relatively long range (e.g., on the order of 300 meters or further).

Systems and methods in accordance with the present disclosure can improve how the LIDAR system determines

parameters regarding the object by using at least two scanning devices to control characteristics of the transmitted beam, such as angle (e.g., azimuth angle in an azimuthal plane), to better relate the transmitted beam and the return beam with each other. For example, the scanning devices can be selected and controlled to generate a transmitted beam that can be backscanned, such as by having an angle as a function of time that approximates a step function. This can improve the ability of the LIDAR system to accurately determine parameters regarding the object using the transmitted beam and the return beam and thus improve characteristics of the LIDAR system such as signal to noise ratio, maximum range, and effective duty cycle.

1. System Environments for Autonomous Vehicles

FIG. 1A is a block diagram illustrating an example of a system environment for autonomous vehicles according to some implementations. FIG. 1A depicts an example autonomous vehicle **100** within which the various techniques disclosed herein may be implemented. The vehicle **100**, for example, may include a powertrain **102** including a prime mover **104** powered by an energy source **106** and capable of providing power to a drivetrain **108**, as well as a control system **110** including a direction control **112**, a powertrain control **114**, and a brake control **116**. The vehicle **100** may be implemented as any number of different types of vehicles, including vehicles capable of transporting people and/or cargo, and capable of traveling in various environments. The aforementioned components **102-116** can vary widely based upon the type of vehicle within which these components are utilized, such as a wheeled land vehicle such as a car, van, truck, or bus. The prime mover **104** may include one or more electric motors and/or an internal combustion engine (among others). The energy source may include, for example, a fuel system (e.g., providing gasoline, diesel, hydrogen, etc.), a battery system, solar panels or other renewable energy source, and/or a fuel cell system. The drivetrain **108** can include wheels and/or tires along with a transmission and/or any other mechanical drive components to convert the output of the prime mover **104** into vehicular motion, as well as one or more brakes configured to controllably stop or slow the vehicle **100** and direction or steering components suitable for controlling the trajectory of the vehicle **100** (e.g., a rack and pinion steering linkage enabling one or more wheels of the vehicle **100** to pivot about a generally vertical axis to vary an angle of the rotational planes of the wheels relative to the longitudinal axis of the vehicle). In some implementations, combinations of powertrains and energy sources may be used (e.g., in the case of electric/gas hybrid vehicles), and in some instances multiple electric motors (e.g., dedicated to individual wheels or axles) may be used as a prime mover.

The direction control **112** may include one or more actuators and/or sensors for controlling and receiving feedback from the direction or steering components to enable the vehicle **100** to follow a desired trajectory. The powertrain control **114** may be configured to control the output of the powertrain **102**, e.g., to control the output power of the prime mover **104**, to control a gear of a transmission in the drivetrain **108**, etc., thereby controlling a speed and/or direction of the vehicle **100**. The brake control **116** may be configured to control one or more brakes that slow or stop vehicle **100**, e.g., disk or drum brakes coupled to the wheels of the vehicle.

Other vehicle types, including but not limited to off-road vehicles, all-terrain or tracked vehicles, construction equipment, may utilize different powertrains, drivetrains, energy sources, direction controls, powertrain controls and brake

controls. Moreover, in some implementations, some of the components can be combined, e.g., where directional control of a vehicle is primarily handled by varying an output of one or more prime movers.

Various levels of autonomous control over the vehicle **100** can be implemented in a vehicle control system **120**, which may include one or more processors **122** and one or more memories **124**, with each processor **122** configured to execute program code instructions **126** stored in a memory **124**. The processor(s) can include, for example, graphics processing unit(s) (“GPU(s)”) and/or central processing unit(s) (“CPU(s)”).

Sensors **130** may include various sensors suitable for collecting information from a vehicle’s surrounding environment for use in controlling the operation of the vehicle. For example, sensors **130** can include radar sensor **134**, LIDAR (Light Detection and Ranging) sensor **136**, a 3D positioning sensors **138**, e.g., any of an accelerometer, a gyroscope, a magnetometer, or a satellite navigation system such as GPS (Global Positioning System), GLONASS (Globalnaya Navigazionnaya Sputnikovaya Sistema, or Global Navigation Satellite System), BeiDou Navigation Satellite System (BDS), Galileo, Compass, etc. The 3D positioning sensors **138** can be used to determine the location of the vehicle on the Earth using satellite signals. The sensors **130** can include a camera **140** and/or an IMU (inertial measurement unit) **142**. The camera **140** can be a monographic or stereographic camera and can record still and/or video images. The IMU **142** can include multiple gyroscopes and accelerometers capable of detecting linear and rotational motion of the vehicle in three directions. One or more encoders (not illustrated), such as wheel encoders may be used to monitor the rotation of one or more wheels of vehicle **100**. Each sensor **130** can output sensor data at various data rates, which may be different than the data rates of other sensors **130**.

The outputs of sensors **130** may be provided to a set of control subsystems **150**, including a localization subsystem **152**, a planning subsystem **156**, a perception subsystem **154**, and a control subsystem **158**. The localization subsystem **152** can perform functions such as precisely determining the location and orientation (also sometimes referred to as “pose”) of the vehicle **100** within its surrounding environment, and generally within some frame of reference. The location of an autonomous vehicle can be compared with the location of an additional vehicle in the same environment as part of generating labeled autonomous vehicle data. The perception subsystem **154** can perform functions such as detecting, tracking, determining, and/or identifying objects within the environment surrounding vehicle **100**. A machine learning model in accordance with some implementations can be utilized in tracking objects. The planning subsystem **156** can perform functions such as planning a trajectory for vehicle **100** over some timeframe given a desired destination as well as the static and moving objects within the environment. A machine learning model in accordance with some implementations can be utilized in planning a vehicle trajectory. The control subsystem **158** can perform functions such as generating suitable control signals for controlling the various controls in the vehicle control system **120** in order to implement the planned trajectory of the vehicle **100**. A machine learning model can be utilized to generate one or more signals to control an autonomous vehicle to implement the planned trajectory.

Multiple sensors of types illustrated in FIG. 1A can be used for redundancy and/or to cover different regions around a vehicle, and other types of sensors may be used. Various

types and/or combinations of control subsystems may be used. Some or all of the functionality of a subsystem **152-158** may be implemented with program code instructions **126** resident in one or more memories **124** and executed by one or more processors **122**, and these subsystems **152-158** may in some instances be implemented using the same processor(s) and/or memory. Subsystems may be implemented at least in part using various dedicated circuit logic, various processors, various field programmable gate arrays (“FPGA”), various application-specific integrated circuits (“ASIC”), various real time controllers, and the like, as noted above, multiple subsystems may utilize circuitry, processors, sensors, and/or other components. Further, the various components in the vehicle control system **120** may be networked in various manners.

In some implementations, the vehicle **100** may also include a secondary vehicle control system (not illustrated), which may be used as a redundant or backup control system for the vehicle **100**. In some implementations, the secondary vehicle control system may be capable of fully operating the autonomous vehicle **100** in the event of an adverse event in the vehicle control system **120**, while in other implementations, the secondary vehicle control system may only have limited functionality, e.g., to perform a controlled stop of the vehicle **100** in response to an adverse event detected in the primary vehicle control system **120**. In still other implementations, the secondary vehicle control system may be omitted.

Various architectures, including various combinations of software, hardware, circuit logic, sensors, and networks, may be used to implement the various components illustrated in FIG. **1A**. Each processor may be implemented, for example, as a microprocessor and each memory may represent the random access memory (“RAM”) devices comprising a main storage, as well as any supplemental levels of memory, e.g., cache memories, non-volatile or backup memories (e.g., programmable or flash memories), read-only memories, etc. In addition, each memory may be considered to include memory storage physically located elsewhere in the vehicle **100**, e.g., any cache memory in a processor, as well as any storage capacity used as a virtual memory, e.g., as stored on a mass storage device or another computer controller. One or more processors illustrated in FIG. **1A**, or entirely separate processors, may be used to implement additional functionality in the vehicle **100** outside of the purposes of autonomous control, e.g., to control entertainment systems, to operate doors, lights, convenience features, etc.

In addition, for additional storage, the vehicle **100** may include one or more mass storage devices, e.g., a removable disk drive, a hard disk drive, a direct access storage device (“DASD”), an optical drive (e.g., a CD drive, a DVD drive, etc.), a solid state storage drive (“SSD”), network attached storage, a storage area network, and/or a tape drive, among others.

Furthermore, the vehicle **100** may include a user interface **164** to enable vehicle **100** to receive a number of inputs from and generate outputs for a user or operator, e.g., one or more displays, touchscreens, voice and/or gesture interfaces, buttons and other tactile controls, etc. Otherwise, user input may be received via another computer or electronic device, e.g., via an app on a mobile device or via a web interface.

Moreover, the vehicle **100** may include one or more network interfaces, e.g., network interface **162**, suitable for communicating with one or more networks **170** (e.g., a Local Area Network (“LAN”), a wide area network (“WAN”), a wireless network, and/or the Internet, among

others) to permit the communication of information with other computers and electronic device, including, for example, a central service, such as a cloud service, from which the vehicle **100** receives environmental and other data for use in autonomous control thereof. Data collected by the one or more sensors **130** can be uploaded to a computing system **172** via the network **170** for additional processing. In some implementations, a time stamp can be added to each instance of vehicle data prior to uploading.

Each processor illustrated in FIG. **1A**, as well as various additional controllers and subsystems disclosed herein, generally operates under the control of an operating system and executes or otherwise relies upon various computer software applications, components, programs, objects, modules, data structures, etc., as will be described in greater detail below. Moreover, various applications, components, programs, objects, modules, etc. may also execute on one or more processors in another computer coupled to vehicle **100** via network **170**, e.g., in a distributed, cloud-based, or client-server computing environment, whereby the processing required to implement the functions of a computer program may be allocated to multiple computers and/or services over a network.

In general, the routines executed to implement the various implementations described herein, whether implemented as part of an operating system or a specific application, component, program, object, module or sequence of instructions, or even a subset thereof, will be referred to herein as “program code”. Program code can include one or more instructions that are resident at various times in various memory and storage devices, and that, when read and executed by one or more processors, perform the steps necessary to execute steps or elements embodying the various aspects of the present disclosure. Moreover, while implementations have and hereinafter will be described in the context of fully functioning computers and systems, it will be appreciated that the various implementations described herein are capable of being distributed as a program product in a variety of forms, and that implementations can be implemented regardless of the particular type of computer readable media used to actually carry out the distribution.

Examples of computer readable media include tangible, non-transitory media such as volatile and non-volatile memory devices, floppy and other removable disks, solid state drives, hard disk drives, magnetic tape, and optical disks (e.g., CD-ROMs, DVDs, etc.) among others.

In addition, various program code described hereinafter may be identified based upon the application within which it is implemented in a specific implementation. Any particular program nomenclature that follows is used merely for convenience, and thus the present disclosure should not be limited to use solely in any specific application identified and/or implied by such nomenclature. Furthermore, given the typically endless number of manners in which computer programs may be organized into routines, procedures, methods, modules, objects, and the like, as well as the various manners in which program functionality may be allocated among various software layers that are resident within a typical computer (e.g., operating systems, libraries, API’s, applications, applets, etc.), the present disclosure is not limited to the specific organization and allocation of program functionality described herein.

2. LIDAR for Automotive Applications

A truck can include a LIDAR system (e.g., vehicle control system **120** in FIG. **1A**, LIDAR system **200** in FIG. **2A**, among others described herein). In some implementations,

the LIDAR system can use frequency modulation to encode an optical signal and scatter the encoded optical signal into free-space using optics. By detecting the frequency differences between the encoded optical signal and a returned signal reflected back from an object, the frequency modulated (FM) LIDAR system can determine the location of the object and/or precisely measure the velocity of the object using the Doppler effect. In some implementations, an FM LIDAR system may use a continuous wave (referred to as, “FMCW LIDAR”) or a quasi-continuous wave (referred to as, “FMQW LIDAR”). In some implementations, the LIDAR system can use phase modulation (PM) to encode an optical signal and scatters the encoded optical signal into free-space using optics.

In some instances, an object (e.g., a pedestrian wearing dark clothing) may have a low reflectivity, in that it only reflects back to the sensors (e.g., sensors **130** in FIG. 1A) of the FM or PM LIDAR system a low amount (e.g., 10% or less) of the light that hit the object. In other instances, an object (e.g., a shiny road sign) may have a high reflectivity (e.g., above 10%), in that it reflects back to the sensors of the FM LIDAR system a high amount of the light that hit the object.

Regardless of the object’s reflectivity, an FM LIDAR system may be able to detect (e.g., classify, recognize, discover, etc.) the object at greater distances (e.g., 2×) than a conventional LIDAR system. For example, an FM LIDAR system may detect a low reflectively object beyond 300 meters, and a high reflectivity object beyond 400 meters.

To achieve such improvements in detection capability, the FM LIDAR system may use sensors (e.g., sensors **130** in FIG. 1A). In some implementations, these sensors can be single photon sensitive, meaning that they can detect the smallest amount of light possible. While an FM LIDAR system may, in some applications, use infrared wavelengths (e.g., 950 nm, 1550 nm, etc.), it is not limited to the infrared wavelength range (e.g., near infrared: 800 nm-1500 nm; middle infrared: 1500 nm-5600 nm; and far infrared: 5600 nm-1,000,000 nm). By operating the FM or PM LIDAR system in infrared wavelengths, the FM or PM LIDAR system can broadcast stronger light pulses or light beams while meeting eye safety standards. Conventional LIDAR systems are often not single photon sensitive and/or only operate in near infrared wavelengths, requiring them to limit their light output (and distance detection capability) for eye safety reasons.

Thus, by detecting an object at greater distances, an FM LIDAR system may have more time to react to unexpected obstacles. Indeed, even a few milliseconds of extra time could improve safety and comfort, especially with heavy vehicles (e.g., commercial trucking vehicles) that are driving at highway speeds.

The FM LIDAR system can provide accurate velocity for each data point instantaneously. In some implementations, a velocity measurement is accomplished using the Doppler effect which shifts frequency of the light received from the object based at least one of the velocity in the radial direction (e.g., the direction vector between the object detected and the sensor) or the frequency of the laser signal. For example, for velocities encountered in on-road situations where the velocity is less than 100 meters per second (m/s), this shift at a wavelength of 1550 nanometers (nm) amounts to the frequency shift that is less than 130 megahertz (MHz). This frequency shift is small such that it is difficult to detect directly in the optical domain. However, by using coherent detection in FMCW, PMCW, or FMQW LIDAR systems, the signal can be converted to the RF

domain such that the frequency shift can be calculated using various signal processing techniques. This enables the autonomous vehicle control system to process incoming data faster.

Instantaneous velocity calculation also makes it easier for the FM LIDAR system to determine distant or sparse data points as objects and/or track how those objects are moving over time. For example, an FM LIDAR sensor (e.g., sensors **130** in FIG. 1A) may only receive a few returns (e.g., hits) on an object that is 300 m away, but if those return give a velocity value of interest (e.g., moving towards the vehicle at >70 mph), then the FM LIDAR system and/or the autonomous vehicle control system may determine respective weights to probabilities associated with the objects.

Faster identification and/or tracking of the FM LIDAR system gives an autonomous vehicle control system more time to maneuver a vehicle. A better understanding of how fast objects are moving also allows the autonomous vehicle control system to plan a better reaction.

The FM LIDAR system can have less static compared to conventional LIDAR systems. That is, the conventional LIDAR systems that are designed to be more light-sensitive typically perform poorly in bright sunlight. These systems also tend to suffer from crosstalk (e.g., when sensors get confused by each other’s light pulses or light beams) and from self-interference (e.g., when a sensor gets confused by its own previous light pulse or light beam). To overcome these disadvantages, vehicles using the conventional LIDAR systems often need extra hardware, complex software, and/or more computational power to manage this “noise.”

In contrast, FM LIDAR systems do not suffer from these types of issues because each sensor is specially designed to respond only to its own light characteristics (e.g., light beams, light waves, light pulses). If the returning light does not match the timing, frequency, and/or wavelength of what was originally transmitted, then the FM sensor can filter (e.g., remove, ignore, etc.) out that data point. As such, FM LIDAR systems produce (e.g., generates, derives, etc.) more accurate data with less hardware or software requirements, enabling safer and smoother driving.

The FM LIDAR system can be easier to scale than conventional LIDAR systems. As more self-driving vehicles (e.g., cars, commercial trucks, etc.) show up on the road, those powered by an FM LIDAR system likely will not have to contend with interference issues from sensor crosstalk. Furthermore, an FM LIDAR system uses less optical peak power than conventional LIDAR sensors. As such, some or all of the optical components for an FM LIDAR can be produced on a single chip, which produces its own benefits, as discussed herein.

2.1 Commercial Trucking

FIG. 1B is a block diagram illustrating an example of a system environment for autonomous commercial trucking vehicles, according to some implementations. The environment **100B** includes a commercial truck **102B** for hauling cargo **106B**. In some implementations, the commercial truck **102B** may include vehicles configured to long-haul freight transport, regional freight transport, intermodal freight transport (i.e., in which a road-based vehicle is used as one of multiple modes of transportation to move freight), and/or any other road-based freight transport applications. In some implementations, the commercial truck **102B** may be a flatbed truck, a refrigerated truck (e.g., a reefer truck), a vented van (e.g., dry van), a moving truck, etc. In some implementations, the cargo **106B** may be goods and/or produce. In some implementations, the commercial truck **102B** may include a trailer to carry the cargo **106B**, such as

a flatbed trailer, a lowboy trailer, a step deck trailer, an extendable flatbed trailer, a sidekit trailer, etc.

The environment **100B** includes an object **110B** (shown in FIG. **1B** as another vehicle) that is within a distance range that is equal to or less than 30 meters from the truck.

The commercial truck **102B** may include a LIDAR system **104B** (e.g., an FM LIDAR system, vehicle control system **120** in FIG. **1A**, LIDAR system **200** in FIG. **2A**) for determining a distance to the object **110B** and/or measuring the velocity of the object **110B**. Although FIG. **1B** shows that one LIDAR system **104B** is mounted on the front of the commercial truck **102B**, the number of LIDAR system and the mounting area of the LIDAR system on the commercial truck are not limited to a particular number or a particular area. The commercial truck **102B** may include any number of LIDAR systems **104B** (or components thereof, such as sensors, modulators, coherent signal generators, etc.) that are mounted onto any area (e.g., front, back, side, top, bottom, underneath, and/or bottom) of the commercial truck **102B** to facilitate the detection of an object in any free-space relative to the commercial truck **102B**.

As shown, the LIDAR system **104B** in environment **100B** may be configured to detect an object (e.g., another vehicle, a bicycle, a tree, street signs, potholes, etc.) at short distances (e.g., 30 meters or less) from the commercial truck **102B**.

FIG. **1C** is a block diagram illustrating an example of a system environment for autonomous commercial trucking vehicles, according to some implementations. The environment **100C** includes the same components (e.g., commercial truck **102B**, cargo **106B**, LIDAR system **104B**, etc.) that are included in environment **100B**.

The environment **100C** includes an object **110C** (shown in FIG. **1C** as another vehicle) that is within a distance range that is (i) more than 30 meters and (ii) equal to or less than 150 meters from the commercial truck **102B**. As shown, the LIDAR system **104B** in environment **100C** may be configured to detect an object (e.g., another vehicle, a bicycle, a tree, street signs, potholes, etc.) at a distance (e.g., 100 meters) from the commercial truck **102B**.

FIG. **1D** is a block diagram illustrating an example of a system environment for autonomous commercial trucking vehicles, according to some implementations. The environment **100D** includes the same components (e.g., commercial truck **102B**, cargo **106B**, LIDAR system **104B**, etc.) that are included in environment **100B**.

The environment **100D** includes an object **110D** (shown in FIG. **1D** as another vehicle) that is within a distance range that is more than 150 meters from the commercial truck **102B**. As shown, the LIDAR system **104B** in environment **100D** may be configured to detect an object (e.g., another vehicle, a bicycle, a tree, street signs, potholes, etc.) at a distance (e.g., 300 meters) from the commercial truck **102B**.

In commercial trucking applications, it is important to effectively detect objects at all ranges due to the increased weight and, accordingly, longer stopping distance required for such vehicles. FM LIDAR systems (e.g., FMCW and/or FMQW systems) or PM LIDAR systems are well-suited for commercial trucking applications due to the advantages described above. As a result, commercial trucks equipped with such systems may have an enhanced ability to safely move both people and goods across short or long distances, improving the safety of not only the commercial truck but of the surrounding vehicles as well. In various implementations, such FM or PM LIDAR systems can be used in semi-autonomous applications, in which the commercial truck has a driver and some functions of the commercial

truck are autonomously operated using the FM or PM LIDAR system, or fully autonomous applications, in which the commercial truck is operated entirely by the FM or LIDAR system, alone or in combination with other vehicle systems.

3. Lidar Systems Using Multiple Scanners

FIG. **2A** depicts an example of a LIDAR system **200**. The LIDAR system **200** can be used to determine parameters regarding objects, such as range and velocity, and output the parameters to a remote system. For example, the LIDAR system **200** can output the parameters for use by a vehicle controller that can control operation of a vehicle responsive to the received parameters (e.g., vehicle controller **268**) or a display that can present a representation of the parameters. The LIDAR system **200** can be used to implement various features and systems described with reference to FIGS. **1A-1D**.

The LIDAR system **200** can include a laser source **204** that emits a beam **206**, such as a carrier wave light beam. A splitter **208** can split the beam **206** into a beam **210** and a reference beam **212**. A modulator **214** can apply modulation such as frequency modulation (e.g., up chirp, down chirp) or phase modulation to generate a beam **216** (e.g., target beam). As depicted in FIG. **2A**, the modulator **214** can apply the modulation to the beam **210** subsequent to splitting of the beam **206** by the splitter **208**, such that the reference beam **212** is unmodulated (and can be separately modulated in modulator **228**), or the modulator **214** can modulate the beam **206** and provide a modulated beam to the splitter **208** for the splitter **208** to split into a target beam and a reference beam.

The beam **216**, which is used for outputting a transmitted signal, can have most of the energy of the beam **206** outputted by the laser source **204**, while the reference beam **212** can have significantly less energy, yet sufficient energy to enable mixing with a return beam **280** (e.g., returned light) scattered from an object. The reference beam **212** passes through a reference path **232** and can be directed to a detector array **236**. The detector array **236** can include one or more detectors for detecting signals corresponding to the return beam **280** (e.g., with the light reflected or otherwise scattered by the object). The detector array **236** can be a single paired or unpaired detector or a 1 dimensional (1D) or 2 dimensional (2D) array of paired or unpaired detectors arranged in a plane roughly perpendicular to returned beams **280** from the object. The reference beam **212** and the return beam **280** can be combined in at least one optical mixer **240** to produce an optical signal of characteristics to be properly detected. The frequency, phase or amplitude of the interference pattern, or some combination, can be recorded by acquisition system **244** for each detector at multiple times during a signal duration of the beam **216**.

The reference path **232** can introduce a predetermined delay sufficient for the reference beam **212** to arrive at the detector array **236** with the return beam **280** within a spread of ranges of interest. The reference beam **212** can be a local oscillator (LO) signal. The reference beam **212** can be caused to arrive with the return beam **280** by at least one of: 1) putting a mirror in the scene to reflect a portion of the beam **226** back at the detector array **236** so that path lengths are well matched; 2) using a fiber delay to closely match the path length and broadcast the reference beam **212** with optics near the detector array **236**, with or without a path length adjustment to compensate for the phase or frequency difference observed or expected for a particular range; or, 3) using a frequency shifting device (acousto-optic modulator) or time delay of a local oscillator waveform modulation

11

(e.g., in modulator 228) to produce a separate modulation to compensate for path length mismatch. The object may be close enough and the transmitted duration long enough that the return beam 280 sufficiently overlaps the reference beam 212 without a delay.

The LIDAR system 200 can include a processing system 260, which can be implemented using features of the vehicle control system 120 of FIG. 1A. The processing system 260 can process data received regarding the return beam 280 to determine parameters regarding the object such as range and velocity. The processing system 260 can include a scanner controller 264 that can provide scanning signals to control operation of first scanner 220 and second scanner 224 as described further herein, such as to control angle modulation performed by at least one of first scanner 220 or second scanner 224. The processing system 260 can include a Doppler compensator (not shown) that can determine the sign and size of a Doppler shift associated with processing the return beam 280 and a corrected range based thereon along with any other corrections. The processing system 260 can include a modulator controller (not shown) that can send one or more electrical signals to drive modulators 214, 228.

The processing system 260 can include or be communicatively coupled with a vehicle controller 268 to control operation of a vehicle for which the LIDAR system 200 is installed (e.g., to provide complete or semi-autonomous control of the vehicle). For example, the vehicle controller 268 can be implemented by at least one of the LIDAR system 200 or control circuitry of the vehicle. The vehicle controller 268 can control operation of the vehicle responsive to at least one of a range to the object or a velocity of the object determined by the processing system 260. For example, the vehicle controller 268 can transmit a control signal to at least one of a steering system or a braking system of the vehicle to control at least one of speed or direction of the vehicle.

The LIDAR system 200 includes at least a first scanner 220 and a second scanner 224 (e.g., scanning optics). The first scanner 220 can receive the beam 216 and modify the beam 216, such as to adjust an angle of the beam 216, to output a beam 222. The second scanner 224 can receive the beam 222 and modify the beam 222, such as to adjust an angle of the beam 222, to output a beam 226. In some implementations, the first scanner 220 can perform relative small, rapid adjustments to the angle of the beam 216 to output the beam 222, as compared to adjustments performed by the second scanner 224.

FIG. 2B depicts an example of an angle profile 284 of angle modulation that the first scanner 220 applies to the beam 216 to output the beam 222, an angle profile 290 of angle modulation that the second scanner 224 applies to the beam 222 to output the beam 226, and a resulting angle profile 294 of the beam 226. While FIG. 2B depicts the angle profiles 284, 290, 294 as being continuous, the angle profiles 284, 290, 294 can be discrete points, such as if at least one of the first scanner 220 or the second scanner 224 is configured to discretely (e.g., randomly) modulate the angles of the respective beams 216, 222.

The first scanner 220 controls an angle θ (e.g., azimuth angle) of the received beam 216 in order to output the beam 222. The first scanner 220 can control the angle θ by applying a first angle modulation 286 to the beam 216 over a characteristic time τ of three microseconds. The first angle modulation 286 can be greater than 0.02 degrees and less than 0.32 degrees. The first angle modulation 286 can be greater than 0.04 degrees and less than 0.16 degrees. The first angle modulation 286 can be 0.08 degrees. As depicted

12

in FIG. 2B, the first scanner 220 can perform a sequence of first angle modulations 286, between which the first scanner 220 sets the angle θ (back) to a baseline 288.

The second scanner 224 controls an angle (e.g., azimuth angle) of the received beam 222 in order to output the beam 226. The second scanner 224 can have a relatively high slew rate (e.g., compared to the first scanner 220). The slew rate can represent a rate of electrical current or voltage change of input to the second scanner 224 (e.g., from processing system 260) responsive to which the second scanner 224 controls the angle of the received beam 222. As depicted in FIG. 2B, the second scanner 224 can adjust the angle θ over a time scale that is relatively long compared to the characteristic time τ , such as exceeding on the order of one thousand degrees per second. The second scanner 224 can adjust the angle θ of the received beam 222 at a rate 292 (of angle as a function of time) that is within a threshold value of equal to and opposite the first angle modulation 286 divided by the characteristic time τ , such that the angle θ of the beam 226 remains level (e.g., does not change more than a threshold value relative to an initial value) during the period in which the first scanner 220 is performing the first angle modulation 286.

The resulting angle profile 294 of the beam 226, as depicted in FIG. 2B, can be analogous to a step function over a plurality of cycles of modulations by the first scanner 220 and the second scanner 224. The angle profile 294 can define an angle θ of the beam 226 that remains level (e.g., remains within a threshold value of an initial value) during the characteristic time τ during which the first scanner 220 performs the first angle modulation 286. The angle θ of the beam 226 can increase between instances of the first angle modulation 286 in which the signs of the angle modulations performed by the first scanner 220 and the second scanner 224 are not opposite (e.g., the angles θ of the beams 216, 222 are both increasing at the same time). By back-scanning the beam 226 according to the angle profile 294, the LIDAR system 200 can more effectively relate the beam 226 with a return beam in order to determine parameters of the object from which the return beam is returned.

FIG. 3 depicts an example of scanning optics 300 including an optical phased array 304 (e.g., first scanning device) and a second scanner 224. The optical phased array 304 and second scanner 224 can be used to implement the first scanner 220 and second scanner 224, respectively, of the LIDAR system 200. For example, the scanning optics 300 can be used to transmit a beam having the angle profile 294 depicted in FIG. 2B.

The scanning optics 300 can include at least one lens 312 between the optical phased array 304 and the second scanner 224. The at least one lens 312 can be a telescope, such as an arrangement of a plurality of optical elements such as a lens, a mirror, or combinations thereof, such as to increase the size of the beam 222. The at least one lens 312 can receive the beam 222 from the optical phased array 304 and output the beam 222 to the second scanner 224. The at least one lens 312 can adjust a size of the beam 222, such as to increase the size of the beam 222, so that the optical phased array 304 can be sized smaller than the second scanner 224. The at least one lens 312 can include a cylindrical lens to facilitate steering of the beam 222.

The optical phased array 304 can include a plurality of emitters 316. Each emitter 316 can include a phase shifter 320 coupled with a radiating element 324. The emitter 316 can receive input light from a light source (e.g., receive beam 216 as described with reference to FIGS. 2A and 2B) through an optical fiber 332 of a plurality of optical fibers

332. For example, the optical fibers 332 can be coupled with the modulator 214 to receive the beam 216 from the modulator 214 and output the beam 216 to each of the emitters 316. The emitters 316 can be arranged as a one-dimensional or a two-dimensional array. As an example, the emitters 316 can be arranged as a two-dimensional array having sixteen emitters 316 in each row (which can be used to perform azimuthal angle scanning) and one thousand emitters 316 in each column (which can be used to perform vertical, elevation angle scanning).

The emitters 316 can emit light having a phase φ (e.g., respective phases ($\varphi_1, \varphi_2, \dots$) as depicted in FIG. 3). The light from one or more emitters 316 can combine (e.g., superimpose) to form the beam 222 outputted from the optical phased array 304. The phase shifter 320 can control the phase φ of the received beam 216. For example, the phase shifter 320 can control the phase φ responsive to a control signal (e.g., from processing system 160). By controlling the phase shifters 320, the optical phased array 304 can be controlled to randomly determine the angle θ of the outputted beam 222.

The angle θ of the outputted beam 222 can be based on a wavelength λ of the light of the beam 216, a spacing Λ between emitters 316, and a phase difference $d\varphi$ (e.g., ($\varphi_2 - \varphi_1$, etc.) between phases of light outputted by the emitters 316. For example, the angle θ can be defined as:

$$\theta = \frac{\lambda}{\Lambda} d\varphi.$$

By using the optical phased array 304, the angle θ can be achieved while having a relatively large spacing Λ , which can reduce the number of emitters 316 needed.

FIG. 4 depicts an example of scanning optics 400 including a micro-electromechanical system (MEMS) phased array 404 and the second scanner 224. The MEMS phased array 404 can receive the beam 216 and modulate the angle of the beam 216 to output the beam 222. The scanning optics 400 can include the lens(es) 312, which can direct the beam 222 to the second scanner 224.

The MEMS phased array 404 can include a plurality of emitters 408. Each emitter 408 can be controlled to adjust an angle of light outputted by the emitter 408, such that light emitted by the plurality of emitters 408 can combine (e.g., superimpose) to control the angle θ of the beam 222.

The emitter 408 can include an electrostatic plate actuator 412 coupled with a mirror 416. The mirror 416 can be defined by a surface of the electrostatic plate actuator 412, or can be a separate reflective material or component fixed to the electrostatic plate actuator 412. A voltage can be applied to the electrostatic plate actuator 412 to rotate the electrostatic plate actuator 412, which can modulate a pitch of the mirror 416. By controlling the pitch of the mirror 416, a path length of light (e.g., of the beam 216) that interacts with the emitter 408 can be changed, steering the light as it is outputted by the emitter 408. The electrostatic plate actuator 412 can be coupled with a mechanical biasing element 420 (e.g., spring) that biases the position of the electrostatic plate actuator 412 to a predetermined position.

FIG. 5 depicts an example of scanning optics 500 including a MEMS mirror scanner 504 and the second scanner 224. The MEMS mirror scanner 504 can receive the beam 216 and modulate the angle of the beam 216 to output the beam 222. The scanning optics 500 can include the at least

one lens 312 (see, e.g., FIG. 3), which can direct the beam 222 to the second scanner 224.

The MEMS mirror scanner 504 can include a MEMS mirror 508 and a driver 512 (e.g., an actuator). The MEMS mirror 508 can have a resonant frequency f_{MEMS} at which it can be driven by the driver 512 to cause the MEMS mirror 508 to rotate over an angle range 516 to modulate the angle of the beam 216 to output the beam 222. For example, the MEMS mirror 508 can have a resonant frequency of 50 kHz.

The MEMS mirror 508 can rotate over the angle range 516 to perform a first angle modulation 520 of the beam 222, which can be analogous to the first angle modulation 286 described with reference to FIG. 2B. The MEMS mirror 508 can be shaped or configured such that the angle range 516 corresponds to the first angle modulation 520. For example, the MEMS mirror 508 can be configured such that the angle range 516 is 0.5 degrees to achieve the first angle modulation 520 (e.g., to achieve a 0.08 degree modulation of the beam 222).

FIG. 6 depicts an angle profile 600 of angle modulation performed by the MEMS mirror 508, the angle profile 290 performed by the second scanner 224, and a resulting angle profile 620 of the beam 226. As depicted in FIG. 6, the angle profile 600 can be sinusoidal due to the pivoted rotation of the MEMS mirror 508. The angle profile 600 can define a first portion 604, a second portion 608, and a characteristic time T_c . The second portion 608 can correspond to a portion of output of the beam 226 over time based on which useful return data can be received (e.g., during which the resulting angle profile 620 is relatively level). The characteristic time T_c can be inversely proportional to the frequency f_{MEMS} at which the driver 512 causes the MEMS mirror 508 to rotate, such that as the frequency f_{MEMS} increases, the characteristic time τ_c decreases. The characteristic time τ_c can be greater than or equal to two microseconds and less than or equal to ten microseconds.

The characteristic time τ_c can be related to a range that can be achieved using the scanning optics 500:

$$\tau_c > \tau_{int} + \tau_{delay} > \frac{2R}{c}$$

where τ_{int} is an integration time corresponding to processing the return beam, such as for determining range or velocity of an object corresponding to the return beam, τ_{delay} is a delay time associated with overhead in the signal processing pathway, R is a design range of the scanning optics 500 (e.g., of a LIDAR system 200 that implements the scanning optics 500), and c is the speed of light. As such, the maximum range of the scanning optics 500 can increase as the frequency f_{MEMS} decreases (increasing the characteristic time τ_c), which can enable the scanning optics 500 to be used for scanning at long range (e.g., beyond 300 meters). Design parameters such as the maximum range, pulse repetition rate, and effective duty cycle can be determined based on selection of the frequency f_{MEMS} (e.g., based on material selection of the MEMS mirror 508).

FIG. 7 depicts an example of scanning optics 700 including an electro-optic (EO) scanner 704 and the second scanner 224. The EO scanner 704 can receive the beam 216 and modulate the angle of the beam 216 to output the beam 222. The scanning optics 700 can include the at least one lens 312 (see, e.g., FIG. 3), which can direct the beam 222 to the second scanner 224.

The EO scanner 704 can include an EO crystal 708 coupled with a voltage source 712. The EO crystal 708 can receive the beam 216 through a fiber array 716 (which may be coupled with a component of the LIDAR system 200, such as the modulator 214, to receive the beam 216). The scanning optics 700 can include a collimator 720 that receives the beam 222 from the EO crystal 708 and collimates the beam 222 for reception by the second scanner 224.

The EO crystal 708 can include a crystal material for which a refractive index changes based on a change in electric field. For example, responsive to the voltage source 712 applying a voltage to the EO crystal 708, a direction of light passing through the EO crystal 708 can be displaced by a displacement d , such that the EO scanner 704 can adjust the direction of the beam 216 to output the beam 222 at the angle θ based on the voltage applied by the voltage source 712. The displacement d can be proportional to the voltage applied by the voltage source 712, enabling the EO scanner 704 to control the angle θ of the beam 222.

FIG. 8 depicts an angle profile 800 of angle modulation performed by the EO scanner 704, the angle profile 290 performed by the second scanner 224, and a resulting angle profile 820 of the beam 226. As depicted in FIG. 8, an angle modulation 808 can be applied (by controlling the voltage applied by the voltage source 712) to control the angle θ of the beam 222. The angle modulation 808 can be greater than 0.02 degrees and less than 0.32 degrees. The angle modulation 808 can be greater than 0.04 degrees and less than 0.16 degrees. The angle modulation 808 can be 0.08 degrees.

Referring further to FIGS. 2A and 3, the second scanner 224 is depicted as a polygon scanner 308. The polygon scanner 308 can include a plurality of facets 328 that receive the beam 222 from the optical phased array 304 and output the beam 222 as the beam 226. For example, the facet 328 can include a reflective (or refractive) surface to reflect (or refract) the beam 222 as the beam 226. The optical phased array 304 can be positioned within the polygon scanner 308. Accordingly, the polygon scanner 308 can be used to perform angle modulation of the beam 222 to achieve the angle profile 294 depicted in FIG. 2B for the beam 226.

The scanning optics 300 can include a motor 310 that rotates the polygon scanner 308. The motor 310 can rotate the polygon scanner 308 at a rate of rotation corresponding to the angle modulation performed over the characteristic time by the optical phased array 304, such that the scanning optics 300 can achieve a backscanned profile for the angle of the beam 226.

The second scanner 224 can be a galvanometer (e.g., mirror galvanometer). The galvanometer can be controlled to reflect the beam 222 to output the beam 226 (e.g., responsive to a control signal from processing system 260). The second scanner 224 can be similar to the MEMS phased array 404 or the MEMS mirror 508, but having at least one of a size or configuration such that the second scanner 224 can achieve angle control of a relatively large magnitude (e.g., angle profile 290 described with reference to FIG. 2B).

Having now described some illustrative implementations, it is apparent that the foregoing is illustrative and not limiting, having been presented by way of example. In particular, although many of the examples presented herein involve specific combinations of method acts or system elements, those acts and those elements can be combined in other ways to accomplish the same objectives. Acts, elements and features discussed in connection with one implementation are not intended to be excluded from a similar role in other implementations or implementations.

The phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including” “comprising” “having” “containing” “involving” “characterized by” “characterized in that” and variations thereof herein, is meant to encompass the items listed thereafter, equivalents thereof, and additional items, as well as alternate implementations consisting of the items listed thereafter exclusively. In one implementation, the systems and methods described herein consist of one, each combination of more than one, or all of the described elements, acts, or components.

Any references to implementations or elements or acts of the systems and methods herein referred to in the singular can also embrace implementations including a plurality of these elements, and any references in plural to any implementation or element or act herein can also embrace implementations including only a single element. References in the singular or plural form are not intended to limit the presently disclosed systems or methods, their components, acts, or elements to single or plural configurations. References to any act or element being based on any information, act or element can include implementations where the act or element is based at least in part on any information, act, or element.

Any implementation disclosed herein can be combined with any other implementation or embodiment, and references to “an implementation,” “some implementations,” “one implementation” or the like are not necessarily mutually exclusive and are intended to indicate that a particular feature, structure, or characteristic described in connection with the implementation can be included in at least one implementation or embodiment. Such terms as used herein are not necessarily all referring to the same implementation. Any implementation can be combined with any other implementation, inclusively or exclusively, in any manner consistent with the aspects and implementations disclosed herein.

Where technical features in the drawings, detailed description or any claim are followed by reference signs, the reference signs have been included to increase the intelligibility of the drawings, detailed description, and claims. Accordingly, neither the reference signs nor their absence have any limiting effect on the scope of any claim elements.

Systems and methods described herein may be embodied in other specific forms without departing from the characteristics thereof. Further relative parallel, perpendicular, vertical or other positioning or orientation descriptions include variations within $\pm 10\%$ or ± 10 degrees of pure vertical, parallel or perpendicular positioning. References to “approximately,” “about” “substantially” or other terms of degree include variations of $\pm 10\%$ from the given measurement, unit, or range unless explicitly indicated otherwise. Coupled elements can be electrically, mechanically, or physically coupled with one another directly or with intervening elements. Scope of the systems and methods described herein is thus indicated by the appended claims, rather than the foregoing description, and changes that come within the meaning and range of equivalency of the claims are embraced therein.

The term “coupled” and variations thereof includes the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent or fixed) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members coupled directly with or to each other, with the two members coupled with each other using a separate intervening member and any additional intermediate members coupled with one another, or with the

two members coupled with each other using an intervening member that is integrally formed as a single unitary body with one of the two members. If “coupled” or variations thereof are modified by an additional term (e.g., directly coupled), the generic definition of “coupled” provided above is modified by the plain language meaning of the additional term (e.g., “directly coupled” means the joining of two members without any separate intervening member), resulting in a narrower definition than the generic definition of “coupled” provided above. Such coupling may be mechanical, electrical, or fluidic.

References to “or” can be construed as inclusive so that any terms described using “or” can indicate any of a single, more than one, and all of the described terms. A reference to “at least one of ‘A’ and ‘B’” can include only ‘A’, only ‘B’, as well as both ‘A’ and ‘B’. Such references used in conjunction with “comprising” or other open terminology can include additional items.

Modifications of described elements and acts such as variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations can occur without materially departing from the teachings and advantages of the subject matter disclosed herein. For example, elements shown as integrally formed can be constructed of multiple parts or elements, the position of elements can be reversed or otherwise varied, and the nature or number of discrete elements or positions can be altered or varied. Other substitutions, modifications, changes and omissions can also be made in the design, operating conditions and arrangement of the disclosed elements and operations without departing from the scope of the present disclosure.

References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below”) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

What is claimed is:

1. A light detection and ranging (LIDAR) system, comprising:

a laser source configured to generate a beam; and

a plurality of scanners comprising a first scanner configured to modulate an azimuth angle of the beam during one or more first portions of a scan and a second scanner configured to modulate the azimuth angle of the beam during the one or more first portions of the scan and the beam is outputted from second scanner such that the azimuth angle of the beam is level relative to a baseline angle during the one or more first portions of the scan and increases during one or more second portions of the scan, wherein at least one of the first scanner or the second scanner is configured to discretely modulate the azimuth angle of the beam.

2. The LIDAR system of claim **1**, wherein the first scanner is configured to receive the beam from the laser source and in response to receiving the beam, output the beam for the second scanner to receive.

3. The LIDAR system of claim **1**, further comprising a telescope between the first scanner and the second scanner.

4. The LIDAR system of claim **1**, wherein the plurality of scanners comprise at least one of an optical phased array, a micro-electromechanical system (MEMS) phased array, a MEMS mirror, or an electro-optical (EO) crystal.

5. The LIDAR system of claim **1**, further comprising a modulator configured to modulate at least one of a phase or a frequency of the beam.

6. An autonomous vehicle control system, comprising:

a laser source configured to output a beam;

a plurality of scanners comprising a first scanner configured to modulate an azimuth angle of the beam during one or more first portions of a scan and a second scanner configured to modulate the azimuth angle of the beam during the one or more first portions of the scan and the beam is outputted from second scanner such that the azimuth angle of the beam is level relative to a baseline angle during the one or more first portions of the scan and increases during one or more second portions of the scan, wherein at least one of the first scanner or the second scanner is configured to discretely modulate the azimuth angle of the beam;

one or more detectors, each detector of the one or more detectors configured to receive a return beam from at least one of reflection or scattering of the beam by an object and output a signal based on the return beam; and

one or more processors configured to:

determine at least one of a range to or a velocity of the object based on the signal; and

control operation of an autonomous vehicle based on the at least one of the range or the velocity.

7. The autonomous vehicle control system of claim **6**, wherein the first scanner is configured to receive the beam from the laser source, and the second scanner configured to receive the beam from the first scanner.

8. The autonomous vehicle control system of claim **6**, further comprising a telescope between the first scanner and the second scanner.

9. The autonomous vehicle control system of claim **6**, wherein the plurality of scanners comprise at least one of an optical phased array, a micro-electromechanical system (MEMS) phased array, a MEMS mirror, or an electro-optical (EO) crystal.

10. The autonomous vehicle control system of claim **6**, further comprising a modulator configured to modulate at least one of a phase or a frequency of the beam.

11. An autonomous vehicle, comprising:

a laser source configured to output a beam;

a plurality of scanners comprising a first scanner configured to modulate an azimuth angle of the beam during one or more first portions of a scan and a second scanner configured to modulate the azimuth angle of the beam during the one or more first portions of the scan and the beam is outputted from second scanner such that the azimuth angle of the beam is level relative to a baseline angle during the one or more first portions of the scan and increases during one or more second portions of the scan, wherein at least one of the first scanner or the second scanner is configured to discretely modulate the azimuth angle of the beam;

one or more detectors, each detector of the one or more detectors configured to receive a return beam from at least one of reflection or scattering of the beam by an object and output a signal based on the return beam;

a steering system;

a braking system; and

a vehicle controller configured to:

determine at least one of a range to or a velocity of the object based on the signal; and

control operation of at least one of the steering system
or the braking system based on the at least one of the
range or the velocity.

12. The autonomous vehicle of claim **11**, wherein the first
scanner is configured to receive the beam from the laser 5
source and in response to receiving the beam, output the
beam for the second scanner to receive.

13. The autonomous vehicle of claim **11**, wherein the
plurality of scanners comprise at least one of an optical
phased array, a micro-electromechanical system (MEMS) 10
phased array, a MEMS mirror, or an electro-optical (EO)
crystal.

14. The autonomous vehicle of claim **11**, further com-
prising a modulator configured to modulate at least one of a
phase or a frequency of the beam. 15

15. The LIDAR system of claim **1**, wherein the second
scanner is a polygon scanner.

* * * * *