



US011850910B2

(12) **United States Patent**
Ogawa et al.

(10) **Patent No.:** **US 11,850,910 B2**
(45) **Date of Patent:** **Dec. 26, 2023**

(54) **CONTROL DEVICE, VEHICLE, AND CONTROL METHOD**

(52) **U.S. Cl.**
CPC **B60H 1/00392** (2013.01); **B60H 1/04** (2013.01); **B60K 1/00** (2013.01); **B60K 11/02** (2013.01);

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota (JP)

(Continued)

(72) Inventors: **Toshinari Ogawa**, Nagoya (JP); **Kohta Tarao**, Nagoya (JP); **Shinya Kijima**, Nagoya (JP); **Osamu Fukawatase**, Miyoshi (JP); **Koji Yasui**, Toyota (JP); **Toshiyuki Kobayashi**, Miyoshi (JP); **Hitomi Nakatani**, Toyota (JP); **Kuniaki Jinnai**, Nagoya (JP); **Nobuki Hayashi**, Nisshin (JP); **Masahiro Nagano**, Toyota (JP); **Akihiro Ito**, Shinagawa-ku (JP)

(58) **Field of Classification Search**
CPC **B62D 33/077**; **B62D 59/04**; **B62D 63/025**; **B60H 1/00364**; **B60H 1/00378**;
(Continued)

(73) Assignee: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota (JP)

(56) **References Cited**
U.S. PATENT DOCUMENTS
6,516,925 B1 * 2/2003 Napier B60L 7/10 188/112 A
7,040,430 B2 * 5/2006 Nomura B60L 7/14 180/53.5
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 354 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **17/247,124**

JP 2003-317787 A 11/2003
JP 2019-26111 A 2/2019
WO WO 2018/230720 A1 12/2018
Primary Examiner — Jenna M Hopkins

(22) Filed: **Dec. 1, 2020**

(74) *Attorney, Agent, or Firm* — Oblon, McClelland, Maier & Neustadt, L.L.P.


(65) **Prior Publication Data**
US 2021/0188041 A1 Jun. 24, 2021

(57) **ABSTRACT**
A control device includes a controller that executes determining a connection between a first unit that has a boarding space which allows a user to board and is provided with a predetermined facility and that is provided with a first path through which a fluid used in the predetermined facility passes and a second unit that is configured to be separated from and connected to the first unit and that has a drive device of a vehicle that is formed by being connected to the first unit, and supplying the fluid in the first path to a second unit side to absorb heat generated from the drive device.

(30) **Foreign Application Priority Data**
Dec. 19, 2019 (JP) 2019-229276

13 Claims, 5 Drawing Sheets

(51) **Int. Cl.**
B60H 1/00 (2006.01)
B60K 11/02 (2006.01)
(Continued)



US 11,850,910 B2

Page 2

(51)	Int. Cl.		7,213,664 B2 *	5/2007	Nomura	B60L 58/33
	<i>B60R 16/08</i>	(2006.01)					180/53.5
	<i>B60H 1/04</i>	(2006.01)	9,758,010 B2 *	9/2017	Johnston	B60H 1/00385
	<i>B60K 1/00</i>	(2006.01)	2003/0155160 A1 *	8/2003	Nomura	H01M 8/04007
(52)	U.S. Cl.						180/65.1
	CPC <i>B60R 16/08</i>	(2013.01); <i>B60H 2001/00307</i>	2006/0144625 A1 *	7/2006	Nomura	B60L 58/40
		(2013.01); <i>B60K 2001/005</i>					180/65.1
		(2013.01)	2010/0096203 A1 *	4/2010	Freese V	B62D 15/0285
(58)	Field of Classification Search						701/37
	CPC ... <i>B60H 1/02</i> ; <i>B60D 1/36</i> ; <i>B60D 1/62</i> ; <i>B60D</i>		2012/0167929 A1 *	7/2012	Benfield	B60R 15/02
	<i>1/665</i> ; <i>B60R 15/02</i> ; <i>B60R 15/04</i> ; <i>B60P</i>						134/115 R
	<i>3/32</i>		2013/0241236 A1 *	9/2013	Vitale	B62D 47/003
	See application file for complete search history.						296/193.04
			2019/0241040 A1 *	8/2019	Errick	B60H 1/2218
(56)	References Cited		2020/0207419 A1 *	7/2020	Iwasaki	B60R 16/03
	U.S. PATENT DOCUMENTS		2021/0163083 A1 *	6/2021	Ogawa	G06Q 50/30
			2021/0261163 A1 *	8/2021	Ohno	B60R 15/04
			2021/0303000 A1 *	9/2021	Ogawa	G05D 1/0088
			2022/0055653 A1 *	2/2022	Ogawa	H04W 4/029
	7,109,601 B2 *	9/2006	Costello			B60T 13/74
							307/9.1

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5



1**CONTROL DEVICE, VEHICLE, AND
CONTROL METHOD**

INCORPORATION BY REFERENCE

The disclosure of Japanese Patent Application No. 2019-229276 filed on Dec. 19, 2019 including the specification, drawings and abstract is incorporated herein by reference in its entirety.

BACKGROUND

1. Technical Field

The present disclosure relates to a control device, a vehicle, and a control method.

2. Description of Related Art

An autonomous driving vehicle including a traveling unit having no vehicle cabin and a structure detachably attached to the upper portion of the traveling unit is disclosed (for example, WO 2018/230720).

SUMMARY

One aspect of the disclosure is to provide a technique to accelerate heat dissipation from heat generated by a drive device in a vehicle in which a vehicle cabin unit and a traveling unit equipped with drive wheels and the drive device that drives the drive wheels are separable and connectable.

A first aspect of the present disclosure relates to a control device. The control device includes a controller that executes determining a connection between a first unit that has a boarding space which allows a user to board and is provided with a predetermined facility and that is provided with a first path through which a fluid used in the predetermined facility passes and a second unit that is configured to be separated from and connected to the first unit and that has a drive device of a vehicle that is formed by being connected to the first unit, and supplying the fluid in the first path to a second unit side to absorb heat generated from the drive device.

A second aspect of the present disclosure relates to a vehicle. The vehicle includes a first unit that has a boarding space which allows a user to board and is provided with a predetermined facility and that is provided with a first path through which a fluid used in the predetermined facility passes, a second unit that is configured to be separated from and connected to the first unit and that has a drive device of a vehicle that is formed by being connected to the first unit, a connection member that connects the first unit and the second unit, and a first controller that executes supplying the fluid in the first path to a second unit side to absorb heat generated from the drive device in a case where the first unit and the second unit are connected by the connection member.

A third aspect of the present disclosure relates to a control method. The control method includes a determination step of determining a connection between a first unit that has a boarding space which allows a user to board and is provided with a predetermined facility and that is provided with a first path through which a fluid used in the predetermined facility passes and a second unit that is configured to be separated from and connected to the first unit and that has a drive device of a vehicle that is formed by being connected to the

2

first unit, and a supply step of supplying the fluid in the first path to a second unit side to absorb heat generated from the drive device.

According to the present disclosure, it is possible to provide the technique to accelerate the heat dissipation from the heat generated by the drive device in the vehicle in which the vehicle cabin unit and the traveling unit equipped with the drive wheels and the drive device that drives the drive wheels are separable and connectable.

BRIEF DESCRIPTION OF THE DRAWINGS

Features, advantages, and technical and industrial significance of exemplary embodiments of the disclosure will be described below with reference to the accompanying drawings, in which like signs denote like elements, and wherein:

FIG. 1 shows an example of an outline of a vehicle according to a first embodiment;

FIG. 2 shows an example of an outline of a functional configuration of a control device;

FIG. 3 shows an example of a flowchart of processing executed by the control device;

FIG. 4 shows an example of an outline of a vehicle structure according to a second embodiment; and

FIG. 5 shows an example of a flowchart of processing executed by a control device according to the second embodiment.

DETAILED DESCRIPTION OF EMBODIMENTS

A predetermined facility according to a first aspect of the present disclosure includes a water heater and an air conditioner. A fluid according to the first aspect of the present disclosure includes clean water used in the air conditioner, a heating medium that exchanges heat with air supplied from the air conditioner, and wastewater generated in a first unit. A drive device included in a second unit includes a motor that drives drive wheels of a vehicle formed by connecting the second unit and the first unit. The drive device includes a secondary battery that supplies electric power to the motor.

With the control device as described above, the fluid in the first unit is used without providing a heat dissipation device in the second unit, and thus it is possible to accelerate heat dissipation of the drive device provided in the second unit. That is, such a control device can accelerate the heat dissipation of the second unit while suppressing an unnecessary increase in size of the second unit that is separable and connectable with the first unit that allows a user to board.

First Embodiment

Configuration of Vehicle 1

FIG. 1 shows an example of an outline of a vehicle 1 according to a first embodiment. The vehicle 1 is, for example, an electric vehicle, and includes a vehicle cabin unit 10 that has a space allowing the user to board and a traveling unit 20 that is capable of autonomous traveling. The vehicle cabin unit 10 and the traveling unit 20 can be separated and connected vertically. The vehicle cabin unit 10 and the traveling unit 20 may be respectively provided with, for example, a mechanism that is separable and connectable to achieve the separation and the connection. The vehicle cabin unit 10 and the traveling unit 20 may be separated and connected by using the magnetic force of an electromagnet, for example. The vehicle cabin unit 10 is an example of the “first unit” of the present disclosure. The traveling unit 20 is

an example of the “second unit” of the present disclosure. In the following embodiments, various sensors provided in the vehicle **1** include communication modules capable of wireless communication and wirelessly transmit measurement data to a control device **21** (described below) provided in the traveling unit **20**. Each pump provided in the vehicle **1** includes a communication module capable of wireless communication, wirelessly receives an operation control signal from the control device **21**, and operates according to the received operation control signal. Each valve provided in the vehicle **1** includes a communication module capable of wireless communication, wirelessly receives an opening-degree control signal from the control device **21**, and is opened and closed according to the received opening-degree control signal.

Configuration of Vehicle Cabin Unit **10**

The vehicle cabin unit **10** has the space that allows the user to board, and a kitchen unit **101** is provided in the space. The kitchen unit **101** is provided with a water heater **102** and a clean water tank **103** that stores clean water. The kitchen unit **101** is provided with a pipe **104** that connects the clean water tank **103** and the water heater **102**. A pump **118** for pumping the clean water from the clean water tank **103** to the water heater **102** is provided in the middle of the pipe **104**. The pipe **104** is branched in the middle, and a branched pipe **105** is provided such that a tip opening of the branched pipe is connectable with a pipe provided in the traveling unit **20**. A valve **106** is provided in the middle of the pipe **105**. An opening degree of the valve **106** is controlled to adjust a flow rate of the clean water flowing from the pipe **104** to the pipe **105**. A pipe **104** near an outlet of the clean water tank **103** is provided with a temperature sensor **120** capable of measuring the temperature of the clean water passing through the pipe **104**. The pipe **104** is an example of a “first path” in the present disclosure.

The kitchen unit **101** includes a sink in which hot water generated in the water heater **102** is used, and a wastewater tank **107** below the sink. The hot water that is used for a predetermined purpose in the sink flows into the wastewater tank **107** as the wastewater and is stored.

The vehicle cabin unit **10** includes an air conditioner **108**, a circulation pipe that circulates between the wastewater tank **107** and the air conditioner **108**, and a pump **119** that pumps the wastewater from the wastewater tank **107** to the air conditioner **108**. When the wastewater stored in the wastewater tank **107** (an example of the heating medium of the present disclosure) passes through the circulation pipe and is supplied to the air conditioner **108**, the wastewater exchanges heat with the air passing through the outer surface of the circulation pipe and thus the air is heated in the air conditioner **108**. The air further exchanges the heat with a predetermined heating medium, is further heated, and is supplied to the inside of the vehicle cabin unit **10** as warm air.

The circulation pipe from the air conditioner **108** to the wastewater tank **107** is branched before the wastewater tank **107**, and water is discharged from the branched pipe to the outside of the system. A valve **111** is provided in the middle of the branched pipe. The opening degree of the valve **111** is controlled to adjust the flow rate of the water discharged to the system out of the water flowing through the circulation pipe connecting the wastewater tank **107** and the air conditioner **108**. The valve **111** may be opened, for example, while the vehicle **1** is stopped.

The vehicle cabin unit **10** includes a pipe **117**. The pipe **117** connects the pipe provided in the traveling unit **20** and the clean water tank **103**.

Configuration of Traveling Unit **20**

The traveling unit **20** includes the control device **21**. The control device **21** is provided with an electronic control unit (ECU) having a central processing unit (CPU) and a memory. The control device **21** includes a communication module capable of wireless communication with an external device, an external storage device, and a Global Positioning System (GPS) module.

The traveling unit **20** includes a drive motor **202**. The drive motor **202** rotates each wheel provided in the traveling unit **20**. Note that the drive motor **202** may drive any one pair of two pairs of front and rear wheels. The traveling unit **20** includes a steering motor. The steering motor outputs power for changing a direction along a rotation shaft of at least a pair of wheels to steer the vehicle **1**. The traveling unit **20** includes an encoder that can detect a rotation angle and a steering angle of the wheels. The traveling unit **20** includes an environment sensor that can detect the environment around the vehicle **1**. The environment sensor, for example, emits an ultrasonic wave, an electromagnetic wave, or the like in a detection target direction, and detects presence, position, relative speed, and the like of an obstacle in the detection target direction by using a difference between the emitted wave and the received reflected wave. Examples of the obstacles include a pedestrian, a bicycle, a structure, and a building. The environment sensor may include, for example, a microphone, and may detect presence of a surrounding person by analyzing a frequency spectrum of a signal output from the microphone, by voice recognition, or the like.

The control device **21** acquires information on a current point by the GPS module and generates a route to a target point. The drive motor **202** and the steering motor are controlled such that the vehicle **1** moves along the generated route. In a case where the drive motor **202** and the steering motor are controlled, the information on the wheel rotation angle and the steering angle detected by the encoder is used. The control device **21** acquires obstacle information by the environment sensor, and the initially generated route is modified to avoid the obstacle. Through such processing, the traveling unit **20** can autonomously travel from the current point to the target point.

The traveling unit **20** is provided with a jacket **203** that covers an outer surface of the drive motor **202**. The inside of the jacket **203** has a structure through which water can pass. The water passing through the inside of the jacket **203** absorbs heat generated from the drive motor **202** and cools the drive motor **202**. The traveling unit **20** is provided with a pipe **204** that is connected to an inlet of the jacket **203** and allows the water to flow into the jacket **203**. The pipe **204** is provided such that a tip opening of the pipe is connectable with the tip opening of the pipe **105** provided in the vehicle cabin unit **10**. The traveling unit **20** is provided with a pipe **206** that is connected to an outlet of the jacket **203** and through which the water passing through the jacket **203** passes. The pipe **206** is provided such that a tip opening of the pipe is connectable with a tip opening of the pipe **117** provided in the vehicle cabin unit **10**. The pipe **206** is provided with a pump **217** that pumps the water from the jacket **203** to the pipe **117** provided in the vehicle cabin unit **10**. The traveling unit **20** includes a temperature sensor **209** near the drive motor **202** that measures a temperature near the drive motor **202**. The traveling unit **20** includes a battery **208**. The battery **208** supplies the electric power to the drive motor **202**.

5

The traveling unit 20 includes a connection member 210A that connects the tip opening of the pipe 204 and the tip opening of the pipe 105 on the vehicle cabin unit 10 side. The connection member 210A is provided with a connection detection sensor 211A capable of detecting a connection state between the tip opening of the pipe 204 and the tip opening of the pipe 105. Similarly, the traveling unit 20 includes a connection member 210B that connects the tip opening of the pipe 206 and the tip opening of the pipe 117 on the vehicle cabin unit 10 side. The connection member 210B is provided with a connection detection sensor 211B capable of detecting the connection state between the tip opening of the pipe 206 and the tip opening of the pipe 117. The connection detection sensor 211A and the connection detection sensor 211B are exemplified to include a mechanical switch, an electric circuit for checking electrical conductivity, an optical waveguide for checking whether light arrives, and the like.

In the vehicle 1 as described above, when the valve 106 installed in the middle of the pipe 105 is closed, the supply of water from the clean water tank 103 to the traveling unit 20 side through the pipe 105 is suppressed. In such a case, the water is not supplied to the traveling unit 20 side. Therefore, it goes without saying that the water does not return to the vehicle cabin unit 10 side through the pipe 206 of the traveling unit 20. That is, the water stored in the clean water tank 103 is used solely on the vehicle cabin unit 10 side. More specifically, the water stored in the clean water tank 103 is pumped to the water heater 102 by the pump 118 and then heated by the water heater 102 to become the hot water. The hot water is used in the sink for a predetermined purpose and then stored in the wastewater tank 107. The warm water stored in the wastewater tank 107 is pumped to the air conditioner 108 by the pump 119 and used to generate the warm air.

Functional Configuration of Control Device 21

FIG. 2 shows an example of an outline of a functional configuration of the control device 21. Each function described below is realized by the CPU of the ECU executing a computer program developed in the memory in an executable manner. The control device 21 includes a communication unit 221. The communication unit 221 is formed including a communication module. The communication unit 221 wirelessly communicates, according to a predetermined communication standard, with control targets including various sensors (including the temperature sensor 120, the temperature sensor 209, the connection detection sensor 211A, and the connection detection sensor 211B), the valve 106, and the pumps 118, 119, 217 which are disposed in the vehicle 1.

The control device 21 includes a temperature determination unit 222. The temperature determination unit 222 determines whether or not the temperature measured by the temperature sensor 209 installed near the drive motor 202 exceeds a determination reference. The determination reference is set to a value that does not affect the driving of the drive motor 202 due to the heat, for example, a value such that internal windings inside the drive motor 202 are not burned. The temperature determination unit 222 also determines whether or not the temperature measured by the temperature sensor 120 installed in the pipe 104 of the vehicle cabin unit 10 is lower than the above determination reference.

The control device 21 includes a connection determination unit 223. The connection determination unit 223 determines whether or not the vehicle cabin unit 10 and the traveling unit 20 are connected. More specifically, in a case

6

where both signals of a signal, generated by the connection detection sensor 211A, indicating the connection state between the tip opening of the pipe 105 and the tip opening of the pipe 204 and a signal, generated by the connection detection sensor 211B, indicating the connection state between the tip opening of the pipe 117 and the tip opening of the pipe 206 indicate that the tip openings are connected, the connection determination unit 223 determines that the vehicle cabin unit 10 and the traveling unit 20 are connected.

The control device 21 includes a controller 224. The controller 224 generates the opening-degree control signal to control the opening degree of the valve 106 provided in the vehicle 1. The controller 224 also generates the opening-degree control signal to control the opening degree of the valves other than the valve 106 provided in the vehicle 1. The controller 224 generates an operation control signal to operate the pumps 118, 119, 217 provided in the vehicle 1. The controller 224 is an example of the “controller” in the present disclosure.

Processing Flow of Control Device 21

Next, a processing flow executed by the control device 21 will be described. FIG. 3 shows an example of a flowchart of processing executed by the control device 21. It is assumed that the pump 118 operates and that the clean water is supplied from the clean water tank 103 to the water heater 102. It is assumed that the pump 119 operates and the wastewater circulates between the wastewater tank 107 and the air conditioner 108. It is assumed that the connection detection sensor 211A and the connection detection sensor 211B periodically transmit signals indicating the connection state to the communication unit 221.

S1001

In step S1001, the connection determination unit 223 determines whether or not the vehicle cabin unit 10 and the traveling unit 20 are connected, using the signal, transmitted by the connection detection sensor 211A, indicating the connection state between the tip opening of the pipe 204 and the tip opening of the pipe 105 and the signal, transmitted by the connection detection sensor 211B, indicating the connection state between the tip opening of the pipe 206 and the tip opening of the pipe 117 (an example of a “determination step” in the present disclosure).

S1002

In step S1002, in a case where both signals of the signal indicating the connection state between the tip opening of the pipe 105 and the tip opening of the pipe 204 and the signal indicating the connection state between the tip opening of the pipe 117 and the tip opening of the pipe 206 indicate that the tip openings are connected and the vehicle cabin unit 10 and the traveling unit 20 are determined to be connected in step S1001, the communication unit 221 receives the temperature information near the drive motor 202 from the temperature sensor 209. The communication unit 221 receives the temperature information of the clean water passing through the pipe 104 from the temperature sensor 120.

S1003

In step S1003, the temperature determination unit 222 determines whether or not the temperature near the drive motor 202 received in step S1002 exceeds the determination reference. In a case where the temperature near the drive motor 202 is determined to exceed the determination reference, the temperature determination unit 222 further determines whether or not the temperature of the clean water passing through the pipe 104 measured by the temperature sensor 120 is lower than the determination reference. The determination reference to determine the temperature of the

clean water passing through the pipe 104 may be the same as the determination reference to determine the temperature near the drive motor 202 or may be a numerical value lower than the determination reference.

S1004

In step S1004, in a case where the temperature near the drive motor 202 is determined to be higher than the determination reference and further the temperature of the clean water passing through the pipe 104 is lower than the determination reference in step S1003, the controller 224 generates an opening-degree control signal to issue an instruction to open the valve 106. The controller 224 generates the operation control signal to operate the pump 217. The communication unit 221 transmits the opening-degree control signal for the valve 106 and the operation control signal of the pump 217 generated by the controller 224 to the respective devices (an example of a “supply step” in the present disclosure).

Description of Water Flow

Next, a water flow in the vehicle 1 will be described. It is assumed that the vehicle 1 is in traveling and the vehicle cabin unit 10 and the traveling unit 20 are determined to be connected in step S1001. In step S1003, it is assumed that the temperature determination unit 222 determines that the temperature near the drive motor 202 received in step S1002 is higher than the determination reference and further the temperature of the clean water passing through the pipe 104 measured by the temperature sensor 120 is lower than the determination reference.

In the above case, the valve 106 is opened by the control device 21 executing the processing of step S1004. Therefore, at least a part of the clean water flowing from the clean water tank 103 toward the water heater 102 passes through the pipe 105 and flows into the pipe 204 provided in the traveling unit 20. The clean water that passes through the pipe 204 flows into the jacket 203. The water flowing into the jacket 203 absorbs the heat generated from the drive motor 202. The warm water that absorbs the heat flows out to the pipe 206. The pump 217 provided in the middle of the pipe 206 is operated by the operation control signal received from the control device 21. Therefore, the warm water flowing out from the jacket 203 to the pipe 206 flows into the pipe 117 provided in the vehicle cabin unit 10. The warm water that passes through the pipe 117 flows into the clean water tank 103.

That is, the clean water supplied from the clean water tank 103 to the water heater 102 is mixed with the warm water that has absorbed the heat generated from the drive motor 202. The mixed water is heated by the water heater 102 to generate the hot water.

The generated hot water is used in the sink for a predetermined purpose and stored in the wastewater tank 107. The warm water stored in the wastewater tank 107 is pumped to the air conditioner 108 by the pump 119 and used to generate the warm air. That is, the warm water used to generate the warm air in the air conditioner 108 is also mixed with the warm water that has absorbed the heat generated from the drive motor 202. The pump 118 and the valve 106 are examples of a “first controller” in the present disclosure. The pump 217 is an example of a “second controller” in the present disclosure.

Effect of First Embodiment

In a case of the electric vehicle, the heat generated from the drive motor 202 while the vehicle travels is a problem. A cooling function corresponding to the heat generation may be generated. However, in a vehicle in which the traveling unit 20 and the vehicle cabin unit 10 are separable and

connectable, provision of a sufficient heat dissipation mechanism for the traveling unit 20 may be difficult due to a dimensional limitation of the traveling unit 20. However, in the vehicle 1 as described above, a part of the water stored in the clean water tank 103 in the vehicle cabin unit 10 and flowing toward the water heater 102 is supplied to the jacket 203 that covers the drive motor 202 installed in the traveling unit 20. Therefore, with the vehicle 1 as described above, the traveling unit 20 is provided with a simple heat dissipation structure (jacket 203) and the water stored in the vehicle cabin unit 10 is used, and thus it is possible to accelerate the heat dissipation of the drive motor 202. The heat dissipation of the drive motor 202 is accelerated in this manner, but the traveling unit 20 is not provided with a device for heat dissipation. Therefore, the traveling unit 20 suppresses the increase in size.

With the vehicle 1 as described above, the warm water that passes through the jacket 203 and has absorbed the heat generated from the drive motor 202 flows into the clean water tank 103 and is mixed with the clean water originally stored in the clean water tank 103. The mixed water is heated by the water heater 102. That is, the heat generation of the drive motor 202 is used to save the energy for heating the water in the water heater 102.

The warm water heated in the water heater 102 is used for a predetermined purpose in the sink installed in the kitchen unit 101. The warm water is stored in the wastewater tank 107 and then circulates between the tank and the air conditioner 108. That is, the heat generation of the drive motor 202 is used to save the energy for generating the warm air in the air conditioner 108.

With the vehicle 1 as described above, heat storage is realized in the wastewater tank 107. Therefore, even when the drive motor 202 does not generate the heat, the warm water stored in the wastewater tank 107 is sent to the air conditioner 108 to save the energy for generating the warm air in the air conditioner 108.

Modification Example

In the above first embodiment, the opening degree of the valve 106 may be adjusted according to the values of the temperature of the drive motor 202 and the temperature of the clean water passing through the pipe 104. With such a control device 21, it is possible to adjust the flow rate of the clean water flowing into the jacket 203 of the traveling unit 20 from the vehicle cabin unit 10 side according to the values of the temperature of the drive motor 202 and the temperature of the clean water passing through the pipe 104. The water flowing from the vehicle cabin unit 10 side to the traveling unit 20 side may be executed regardless of the value of the temperature measured by the temperature sensor 209 installed in the drive motor 202.

The vehicle cabin unit 10 may have a structure in which at least a part of the warm air generated in the air conditioner 108 is supplied to the inside of the wastewater tank 107. With such a vehicle cabin unit 10, at least a part of the wastewater stored in the wastewater tank 107 is evaporated by the warm air. Therefore, an amount of the wastewater discharged from the valve 111 is reduced and the wastewater is easily handled.

The vehicle cabin unit 10 may have a structure in which the warm water that passes through the jacket 203 is not returned to the vehicle cabin unit 10 side. The vehicle cabin unit 10 may have a structure in which a refrigerant used in

the air conditioner **108** provided in the vehicle cabin unit **10** flows into the jacket **203** of the traveling unit **20**.

Second Embodiment

Configuration of Vehicle Cabin Unit **10A**

FIG. **4** shows an example of an outline of a structure of a vehicle **1A** according to a second embodiment. A vehicle cabin unit **10A** of the vehicle **1A** according to the second embodiment includes a kitchen unit **101A**. The kitchen unit **101A** is provided with the clean water tank **103** as in the first embodiment. The clean water stored in the clean water tank **103** is used for a predetermined purpose and becomes the wastewater. The kitchen unit **101A** is provided with a wastewater tank **107A** that stores the wastewater. A pipe **115** for discharging the wastewater is connected to the wastewater tank **107A**. The pipe **115** is provided such that a tip opening of the pipe is connectable with a pipe provided in a traveling unit **20A**. A pump **112** is provided in the middle of the pipe **115**. The operation of the pump **112** is controlled to adjust the flow rate of the wastewater discharged from the wastewater tank **107A**. The pipe **115** is an example of the “first path” in the present disclosure.

Configuration of Traveling Unit **20A**

The traveling unit **20A** has the same component as the traveling unit **20** according to the first embodiment. In addition, the traveling unit **20A** includes a temperature sensor **209A**, near a battery **208A**, that measures the temperature near the battery **208A**. The traveling unit **20A** is provided with a cooling plate **215** so as to be in contact with a surface of the battery **208A**. A flow pipe that allows the water to pass through is laid so as to meander along a plate plane inside the cooling plate **215**. That is, the water flowing through the flow pipe can exchange heat with the surface of the battery **208A** through the cooling plate **215**.

The traveling unit **20A** includes a pipe **204A** that is connected to a flow pipe inlet of the cooling plate **215** and causes the water to flow into the flow pipe. The pipe **204A** is provided such that a tip opening of the pipe is connectable with the tip opening of the pipe **115** provided in the vehicle cabin unit **10A**. The traveling unit **20A** is provided with a wastewater tank **225** that stores the wastewater that passes through the flow pipe of the cooling plate **215** and a pump **227** that pumps the wastewater from the flow pipe of the cooling plate **215** to the wastewater tank **225**.

In the wastewater tank **225**, decomposition treatment using a microorganism is performed on a contaminant contained in the wastewater. A temperature sensor **226** capable of measuring the temperature of the stored wastewater is installed inside the wastewater tank **225**. The traveling unit **20** is provided with a pipe that connects the flow pipe of the cooling plate **215** and the wastewater tank **225**, and a branch pipe that branches from the pipe and joins the pipe **204A**. A valve **216** is provided in the branch pipe. The opening degree of the valve **216** is controlled to adjust the flow rate of the wastewater that joins the pipe **204A** and flows into the flow pipe inlet of the cooling plate **215** again out of the wastewater flowing from a flow pipe outlet of the cooling plate **215** toward the wastewater tank **225**.

The traveling unit **20A** includes a discharge pipe that is connected to the wastewater tank **225** and that allows the wastewater to discharge from the wastewater tank **225** to the outside of the system. A valve **207** is provided in the middle of the discharge pipe. The opening degree of the valve **207** is controlled to adjust the flow rate of the wastewater discharged from the wastewater tank **225** to the outside of the system is adjusted.

The traveling unit **20A** includes a connection member **210C** that connects the tip opening of the pipe **204A** and the tip opening of the pipe **115** on the vehicle cabin unit **10A** side. The connection member **210C** includes a connection detection sensor **211C** capable of detecting the connection state between the tip opening of the pipe **204A** and the tip opening of the pipe **115** on the vehicle cabin unit **10A** side.

Processing Flow of Control Device **21A**

Next, a processing flow executed by the control device **21A** will be described. FIG. **5** shows an example of a flowchart of processing executed by the control device **21A**. It is assumed that the pumps **112**, **227** are initially not operated and valve **216** is initially closed. Details of the processing executed in each step will be exemplified below.

S1001A

In step S1001A, a connection determination unit **223A** determines whether or not the vehicle cabin unit **10A** and the traveling unit **20A** are connected, using a signal, transmitted by the connection detection sensor **211C**, indicating the connection state between the tip opening of the pipe **115** and the tip opening of the pipe **204A** (an example of the “determination step” in the present disclosure).

S1002A

In step S1002A, in a case where the signal indicating the connection state between the tip opening of the pipe **115** and the tip opening of the pipe **204A** indicates that the tip openings are connected and the vehicle cabin unit **10A** and the traveling unit **20A** are determined to be connected in step S1001A, a communication unit **221A** receives the temperature information near the battery **208A** from the temperature sensor **209A**.

S1003A

In step S1003A, determination is made whether or not the temperature near the battery **208A** received in step S1002A is higher than a determination reference. The determination reference is a value that does not affect the battery **208A** due to the heat. For example, in a case where a threshold value of temperature at which a failure rate of the battery **208A** rapidly increases is known, the temperature is set as the determination reference.

S1004A

In step S1004A, in a case where the temperature near the battery **208A** is determined to be higher than the determination reference in step S1003A, a controller **224A** generates an operation control signal to issue an instruction to operate the pump **112**. The communication unit **221A** transmits the generated operation control signal to the pump **112**. The controller **224A** generates an operation control signal to issue an instruction to operate the pump **227**. The generated operation control signal is transmitted to the pump **227** by the communication unit **221A**. The pump **112** is an example of the “first controller” in the present disclosure. Step S1004A is an example of the “supply step” in the present disclosure.

S1005A

In step S1005A, the communication unit **221A** receives the temperature information of the wastewater stored in the wastewater tank **225** from the temperature sensor **226**. In a case where the temperature in the wastewater tank **225** received from the temperature sensor **226** is lower than the temperature near the battery **208A** received from the temperature sensor **209A** in step S1002A, the controller **224A** generates an opening-degree control signal to issue an instruction to open the valve **216**. The generated opening-degree control signal is transmitted to the valve **216** by the communication unit **221A**. The opening-degree control signal to open the valve **216** may be generated in a case where

11

the temperature of the wastewater stored in the wastewater tank 225 received from the temperature sensor 226 is lower than the temperature near the battery 208A by a predetermined value or more. The opening-degree control signal to open the valve 216 may be generated in a case where the temperature of the wastewater stored in the wastewater tank 225 is lower than the temperature near the battery 208A and lower than a temperature at which a decomposition reaction using the microorganism rapidly proceeds.

Description of Wastewater Flow

Next, a flow of the wastewater will be described. It is assumed that the vehicle 1A is stopped, the battery 208A is supplied with the electric power from an external power supply device, and the battery 208A is being charged. In step S1003A, it is assumed that a temperature determination unit 222A determines that the temperature near the battery 208A received in step S1002A is higher than the determination reference.

In such a case, the control device 21A executes the processing of step S1004A to operate the pump 112. Therefore, the wastewater stored in the wastewater tank 107A passes through the pipe 115 and is pumped to the pipe 204A provided in the traveling unit 20A. The wastewater that passes through the pipe 204A flows into the flow pipe of the cooling plate 215. The wastewater flowing into the flow pipe of the cooling plate 215 absorbs the heat generated from the battery 208A disposed so as to be in contact with the cooling plate 215 through the cooling plate 215. The wastewater that has absorbed the heat is pumped to the wastewater tank 225 by the pump 227.

In the wastewater tank 225, the decomposition treatment using the microorganism is performed on the contaminant contained in the wastewater. The wastewater stored in the wastewater tank 225 absorbs the heat generated from the battery 208A being charged. Therefore, the decomposition treatment may be accelerated. In a case where the temperature in the wastewater tank 225 is lower than the temperature near the battery 208A, the valve 216 is opened and a part of the wastewater that has absorbed the heat generated from the battery 208A flows into the flow pipe of the cooling plate 215 of the battery 208A again. Therefore, the temperature of the wastewater flowing out from the flow pipe of the cooling plate 215 rises. Therefore, the temperature of the wastewater flowing into the wastewater tank 225 rises. Therefore, the decomposition treatment in the wastewater tank 225 may be accelerated. Since the wastewater stored in the wastewater tank 225 absorbs the heat generated from the battery 208A being charged, a part thereof may be dried. Such wastewater stored in the wastewater tank 225 is discharged to the outside of the system in a case where the valve 207 is open.

As in the first embodiment, a pipe may be installed that allows the wastewater heated by absorbing the heat in the flow pipe of the cooling plate 215 to return to the wastewater tank 107A on the vehicle cabin unit 10A side. A valve may be provided in the middle of the pipe, and the opening degree of the valve may be controlled to adjust the flow rate of the wastewater returning to the vehicle cabin unit 10A side.

Effect of Second Embodiment

In a case of the electric vehicle, the battery 208A may generate heat when the battery 208A mounted therein is rapidly charged. A cooling function corresponding to the heat generation may be provided. However, in the vehicle 1A in which the traveling unit 20A and the vehicle cabin unit 10A are separable and connectable, provision of a sufficient heat dissipation mechanism for the traveling unit 20A may be difficult due to a dimensional limitation of the traveling

12

unit 20A. However, in the vehicle 1A as described above, the water stored in the wastewater tank 107A in the vehicle cabin unit 10A is supplied to the flow pipe of the cooling plate 215 provided so as to be in contact with the battery 208A installed in the traveling unit 20A. Therefore, with the vehicle 1A as described above, the traveling unit 20A is provided with a simple heat dissipation structure (cooling plate 215) and the water stored in the wastewater tank 107A of the vehicle cabin unit 10A is used, and thus it is possible to accelerate the heat dissipation of the battery 208A during charging. The heat dissipation of the battery 208A during charging is accelerated, but the traveling unit 20A is not provided with a device for heat dissipation. Therefore, the traveling unit 20A suppresses the increase in size.

In the vehicle 1A as described above, the contaminant contained in the wastewater is decomposed by the microorganism. Therefore, the wastewater is easily handled in a case where the wastewater is discharged from the vehicle 1A or the like. The wastewater stored in the wastewater tank 225 absorbs the heat generated from the battery 208A, and the contaminant is decomposed in a state where the temperature of the water is higher than that in the case where the water is stored in the wastewater tank 107A. Therefore, the decomposition reaction may be accelerated. As shown in step S1005A, in a case where the temperature in the wastewater tank 225 is lower than the temperature near the battery 208A, the valve 216 is opened and the wastewater that has absorbed the heat generated from the battery 208A flows into the flow pipe of the cooling plate 215 again to absorb the heat generated from the battery 208A. Therefore, the temperature of the wastewater flowing into the wastewater tank 225 rises, and the decomposition reaction of the contaminant contained in the wastewater is accelerated.

Since the wastewater stored in the wastewater tank 225 absorbs the heat generated from the battery 208A, at least a part of the wastewater may be dried. Therefore, an amount of the wastewater stored in the wastewater tank 107A may be reduced and discharged. From this point of view, the vehicle 1A may be a vehicle in which the wastewater is easily handled.

The heat generated by the driving of the drive motor 202 while the vehicle travels may be absorbed by the wastewater stored in the wastewater tank 107A. With such a structure, it is possible to accelerate the heat dissipation of the drive motor 202.

The above embodiments are merely examples, and the present disclosure may be modified and implemented as appropriate within a scope not departing from the gist thereof.

The configurations and processing described in the present disclosure can be freely combined and implemented as long as no technical contradiction occurs.

The processing described as being performed by one device may be shared and executed by a plurality of devices. Alternatively, the processing described as being performed by different devices may be executed by one device. In a computer system, it is possible to flexibly change the hardware configuration (server configuration) for realizing each function.

The present disclosure can also be realized by supplying a computer with a computer program that implements the functions described in the above embodiments, and one or more processors included in the computer read and execute the program. Such a computer program may be provided to the computer by a non-transitory computer readable storage medium connectable to a system bus of the computer, or may be provided to the computer through a network.

13

Examples of the non-transitory computer-readable storage medium include any type of disc such as a magnetic disc (floppy (registered trademark) disc, hard disk drive (HDD), or the like) and an optical disc (CD-ROM, DVD disc, Blu-ray disc, or the like), a read solely memory (ROM), a random access memory (RAM), an EPROM, an EEPROM, a magnetic card, a flash memory, an optical card, and any type of medium suitable for storing an electronic command.

What is claimed is:

1. A control device comprising a controller that executes determining a connection between a first unit that has a boarding space which allows a user to board and is provided with a predetermined facility and that is provided with a first path through which a fluid used in the predetermined facility passes and a second unit that includes a second path and is configured to be separated from and connected to the first unit and that has a drive device of a vehicle that is formed by being connected to the first unit by a connection member that connects a tip opening of the first path and a tip opening of the second path, wherein the connection member includes a connection detection sensor that detects a connection state between the tip opening of the first path and the tip opening of the second path and determining that the connection is based on a signal indicating the connection state transmitted by the connection detection sensor, and

supplying the fluid in the first path to a second unit side to absorb heat generated from the drive device.

2. The control device according to claim 1, wherein the controller further executes adjusting a supply amount of the fluid supplied from the first path to the second unit side based on a temperature of the drive device.

3. The control device according to claim 1, wherein the controller further executes recovering the fluid that has absorbed the heat generated from the drive device to a first unit side.

4. The control device according to claim 3, wherein:
the fluid includes water;
the predetermined facility includes a water heater; and
the controller executes recovering water that has absorbed the heat generated from the drive device for the first path that supplies the water to the water heater.

5. The control device according to claim 3, wherein:
the predetermined facility includes an air conditioner; and
the controller executes recovering the fluid that has absorbed the heat generated from the drive device for the first path through which a heating medium that exchanges heat with air supplied from the air conditioner passes.

6. The control device according to claim 3, wherein:
the fluid includes water; and
the controller executes recovering water that has absorbed the heat generated from the drive device such that heat exchange with wastewater after being used in the predetermined facility is possible.

7. The control device according to claim 1, wherein the drive device includes a motor that drives drive wheels of the vehicle.

8. The control device according to claim 7, wherein the controller executes supplying a part of the fluid to the second unit side when the motor exceeds a predetermined tempera-

14

ture and a temperature of the fluid in the first path is lower than the predetermined temperature.

9. The control device according to claim 1, wherein the drive device includes a secondary battery that supplies electric power to a motor that drives the drive wheels of the vehicle.

10. The control device according to claim 9, wherein the controller executes supplying the fluid in the first path to the second unit side when the secondary battery is charged.

11. A vehicle comprising:

a first unit that has a boarding space which allows a user to board and is provided with a predetermined facility and that is provided with a first path through which a fluid used in the predetermined facility passes;

a second unit that is configured to be separated from and connected to the first unit and that has a second path and a drive device of a vehicle that is formed by being connected to the first unit;

a connection member that connects the first unit and the second unit by connecting a tip opening of the first path and a tip opening of a second path; and

a first controller that executes supplying the fluid in the first path to a second unit side to absorb heat generated from the drive device in a case where the first unit and the second unit are connected by the connection member, wherein the connection member includes a connection detection sensor that detects a connection state between the tip opening of the first path and the tip opening of the second path and determining that the connection is based on a signal indicating the connection state transmitted by the connection detection sensor.

12. The vehicle according to claim 11, wherein:
the drive device includes a secondary battery that supplies electric power to a motor that drives the drive wheels of the vehicle; and

the first controller executes supplying the fluid in the first path to the second unit side when the secondary battery is charged.

13. A control method comprising:

a determination step of determining a connection between a first unit that has a boarding space which allows a user to board and is provided with a predetermined facility and that is provided with a first path through which a fluid used in the predetermined facility passes and a second unit that includes a second path and is configured to be separated from and connected to the first unit and that has a drive device of a vehicle that is formed by being connected to the first unit by a connection member that connects a tip opening of the first path and a tip opening of the second path, wherein the connection member includes a connection detection sensor that detects a connection state between the tip opening of the first path and the tip opening of the second path and determining that the connection is based on a signal indicating the connection state transmitted by the connection detection sensor; and

a supply step of supplying the fluid in the first path to a second unit side to absorb heat generated from the drive device.

* * * * *