

#### US011861795B1

### (12) United States Patent

Cowburn et al.

### (10) Patent No.: US 11,861,795 B1

(45) **Date of Patent:** \*Jan. 2, 2024

### (54) AUGMENTED REALITY ANAMORPHOSIS SYSTEM

(71) Applicant: Snap Inc., Santa Monica, CA (US)

(72) Inventors: Piers Cowburn, London (GB); Qi Pan,

London (GB); Eitan Pilipski, Los

Angeles, CA (US)

(73) Assignee: Snap Inc., Santa Monica, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 16/277,626

(22) Filed: Feb. 15, 2019

#### Related U.S. Application Data

- (63) Continuation of application No. 15/436,363, filed on Feb. 17, 2017, now Pat. No. 10,319,149.
- (51) Int. Cl.

  G06T 13/20 (2011.01)

  G06T 19/00 (2011.01)

(Continued)

(52) **U.S. Cl.** 

CPC ...... *G06T 19/006* (2013.01); *G06T 7/74* (2017.01); *G06T 13/20* (2013.01); *G06T 15/20* (2013.01); *G06T 2200/24* (2013.01)

(58) Field of Classification Search

CPC ....... G06T 19/006; G06T 7/74; G06T 13/20; G06T 15/20

(Continued)

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

4,581,634 A 4/1986 Williams 4,975,690 A 12/1990 Torres (Continued)

#### FOREIGN PATENT DOCUMENTS

CA 2887596 A1 7/2015 CN 113396443 A 9/2021 (Continued)

#### OTHER PUBLICATIONS

"A Whole New Story", Snap, Inc., [Online] Retrieved from the Internet: < URL: https://www.snap.com/en-US/news/>, (2017), 13 pgs.


#### (Continued)

Primary Examiner — Jin Ge (74) Attorney, Agent, or Firm — Schwegman Lundberg & Woessner, P.A.

#### (57) ABSTRACT

Systems, methods, devices, and media for anamorphosis systems to generate and cause display of anamorphic media are disclosed. In one embodiment, an anamorphosis system is configured to identify a set of features of a space, determine relative positions of the set of features, determine a perspective of the mobile device within the space based on the relative positions of the set of features, retrieve anamorphic media based on the location of the mobile device, and apply the anamorphic media to a presentation of the space at the mobile device. The anamorphic media may include media items such as images and videos, configured such that the media items are only visible from one or more specified perspectives. The anamorphic media may include a stylized text string projected onto surfaces of a space such that the stylized text string is correctly displayed when viewed through a user device from a specified perspective.

#### 14 Claims, 14 Drawing Sheets



(51)	Int. Cl.				7,085,571 B	2 8/2006	Kalhan et al.
(51)	G06T 15/20		(2011.01)		7,110,744 B		Freeny, Jr.
	G00T 7/73		(2017.01)		7,124,164 B	1 10/2006	Chemtob
(58)	Field of Clas	ssification			7,149,893 B		Leonard et al.
(50)				^	7,173,651 B 7,188,143 B		Knowles
			r complete search history.		7,188,143 B		Chiu et al.
	occ application	on me to	r complete search mistory.		7,206,568 B		
(56)		Referen	ces Cited		7,227,937 B		Yoakum et al.
					7,237,002 B 7,240,089 B		Estrada et al. Boudreau
	U.S.	PATENT	DOCUMENTS		7,240,089 B. 7,243,163 B.		Friend et al.
	5 072 412 A	12/1001	Handanaan In at al		7,269,426 B		Kokkonen et al.
	5,072,412 A 5,493,692 A		Henderson, Jr. et al. Theimer et al.		7,278,168 B		Chaudhury et al.
	5,699,444 A	12/1997			7,280,658 B2 7,315,823 B2		Amini et al. Brondrup
	5,713,073 A	1/1998	_		7,349,768 B		Bruce et al.
	5,754,939 A 5,855,008 A		Herz et al. Goldhaber et al.		7,356,564 B		Hartselle et al.
	/ /		Walton et al.		7,376,715 B2		Cunningham et al.
	5,999,932 A	12/1999	_		7,394,345 B. 7,411,493 B.		Ehlinger et al. Smith
	6,009,190 A		Szeliski et al.		7,423,580 B		Markhovsky et al.
	6,012,098 A 6,014,090 A		Bayeh et al. Rosen et al.		7,454,442 B		Cobleigh et al.
	6,029,141 A		Bezos et al.		7,478,402 B2 7,496,347 B2		Christensen et al. Puranik
	6,038,295 A		Mattes		7,508,419 B		Toyama et al.
	6,049,711 A		Yehezkel et al.		7,512,649 B		Faybishenko et al.
	6,154,764 A 6,158,044 A		Nitta et al. Tibbetts		7,519,670 B		Hagale et al.
	6,167,435 A		Druckenmiller et al.		7,535,890 B2 7,546,554 B2		Rojas Chiu et al.
	6,204,840 B1		Petelycky et al.		7,607,096 B		Oreizy et al.
	6,205,432 B1 6,216,141 B1		Gabbard et al. Straub et al.		7,639,943 B	1 12/2009	Kalajan
	6,285,381 B1		Sawano et al.		7,650,231 B2		Gadler
	6,285,987 B1		Roth et al.		7,668,537 B2 7,703,140 B2		DeVries Nath et al.
	6,310,694 B1		Okimoto et al.		7,720,554 B		Dibernardo et al.
	6,317,789 B1 6,334,149 B1		Rakavy et al. Davis, Jr. et al.		7,737,965 B		Alter et al.
	6,349,203 B1		Asaoka et al.		7,770,137 B2 7,778,973 B2		Forbes et al.
	6,353,170 B1		Eyzaguirre et al.		7,779,444 B		
	6,446,004 B1 6,449,657 B2		Cao et al. Stanbach et al.		7,787,886 B	2 8/2010	Markhovsky et al.
	6,456,852 B2		Bar et al.		7,796,946 B		Eisenbach
	6,484,196 B1		Maurille		7,801,954 B2 7,856,360 B2		Cadiz et al. Kramer et al.
	, ,		Ogilvie et al.		7,912,896 B		Wolovitz et al.
	6,487,601 B1 6,523,008 B1	2/2003	Hubacher et al.		8,001,204 B		Burtner et al.
	6,525,731 B1		Suits et al.		8,032,586 B2 8,082,255 B		Challenger et al. Carlson, Jr. et al.
	6,542,749 B2		Tanaka et al.		8,090,351 B		,
	6,549,768 B1 6,618,593 B1		Fraccaroli Drutman et al.		8,098,904 B		Ioffe et al.
	6,622,174 B1		Ukita et al.		8,099,109 B		Altman et al.
	6,631,463 B1		Floyd et al.		8,112,716 B2 8,131,597 B2		Kobayashi Hudetz
	6,636,247 B1		Hamzy et al.		8,135,166 B		Rhoads
	6,636,855 B2 6,643,684 B1		Holloway et al. Malkin et al.		8,136,028 B		Loeb et al.
	/ /		Yoakum et al.		8,146,001 B 8,161,115 B		Yamamoto
	, ,		Soderbacka et al.		8,161,417 B		
	, ,	12/2003 1/2004			8,170,957 B		Richard
	, ,		Camut et al.		8,183,997 B		Wong et al.
1	6,698,020 B1	2/2004	Zigmond et al.		8,195,203 B 8,199,747 B		Rojas et al.
	6,700,506 B1		Winkler		8,208,943 B		Petersen
	6,701,347 B1 6,711,608 B1		Ogilvie Ogilvie		8,214,443 B		Hamburg
	6,720,860 B1		Narayanaswami		8,234,350 B 8,238,947 B		Gu et al. Lottin et al.
	6,724,403 B1		Santoro et al.		8,244,593 B		Klinger et al.
	6,757,713 B1 6,832,222 B1		Ogilvie et al. Zimowski		8,276,092 B		Narayanan et al.
	6,834,195 B2		Brandenberg et al.		8,279,319 B		
1	6,836,792 B1	12/2004	Chen		8,280,406 B2 8,285,199 B2		Ziskind et al. Hsu et al.
	, ,	5/2005			8,287,380 B		Nguyen et al.
	6,959,324 B1 6,970,088 B2	10/2005	Kubik et al. Koyach		8,301,159 B		Hamynen et al.
	6,970,907 B1		Ullmann et al.		8,306,922 B		Kunal et al.
1	6,980,909 B2	12/2005	Root et al.		8,312,086 B2		Velusamy et al.
	6,981,040 B1		Konig et al.		8,312,097 B: 8,326,315 B:		Siegel et al. Phillips et al.
	7,020,494 B2 7,027,124 B2		Spriestersbach et al. Foote et al.		•		Hymel et al.
	, ,		Anderson et al.		8,332,475 B		•

(56)	Referen	ces Cited	9,258,459		2/2016	
U.S.	PATENT	DOCUMENTS	9,204,46. 9,276,886 9,294,425	6 B1		Rubinstein et al. Samaranayake Son
8,352,546 B1	1/2013	Dollard	9,317,133			Korah et al.
8,379,130 B2		Forutanpour et al.	9,317,92		4/2016	Chao et al.
8,385,950 B1		Wagner et al.	9,344,600			Hartley et al.
8,402,097 B2			9,355,123 9,361,283			Wnuk et al. Jones et al.
8,405,773 B2		Hayashi et al.	9,385,983		7/2016	
8,418,067 B2 8,423,409 B2		Cheng et al. Rao	9,396,354			Murphy et al.
8,471,914 B2		Sakiyama et al.	•		8/2016	
8,472,935 B1		•	9,407,816 9,430,783		8/2016 8/2016	
8,502,903 B2						Parvizi et al.
8,510,383 B2 8,525,825 B2		Hurley et al. Zhu et al.	9,443,22			Evans et al.
8,527,345 B2		Rothschild et al.	•			Pridmore et al.
8,554,627 B2		Svendsen et al.				Hogeg et al.
8,560,612 B2			•			Johnson et al. Filip et al.
8,564,710 B2 8,570,907 B2		Garcia, Jr. et al.				Hanover et al.
8,594,680 B2			· · · · · · · · · · · · · · · · · · ·			Meisenholder
8,601,380 B2	12/2013	Vaittinen et al.	•			Evans et al.
		Holloway et al.	·			Rosen et al. Samarasekera et al.
8,660,358 B1 8,660,369 B2		Bergboer et al. Llano et al.	9,498,720			Geisner et al.
8,660,793 B2		Ngo et al.				Allen et al.
8,676,623 B2		Gale et al.	9,537,81			Allen et al.
8,682,350 B2		Altman et al.	9,560,000 9,628,950		- 4	Prado et al. Noeth et al.
8,712,776 B2		Bellegarda et al.	9,652,896			Jurgenson et al.
8,718,333 B2 8,724,622 B2	5/2014	Wolf et al. Rojas	9,659,24			Anderton et al.
8,732,168 B2		Johnson	9,693,19		6/2017	
8,744,523 B2		Fan et al.	9,705,833			Spiegel
8,745,132 B2		Obradovich	9,710,821 9,742,713		7/2017 8/2017	Spiegel et al.
8,761,800 B2 8,761,811 B2	6/2014	Kuwahara Alonzo	9,761,04			Cote et al.
8,768,876 B2			9,785,796			Murphy et al.
8,775,972 B2		Spiegel	9,805,020			Gorman et al.
8,788,680 B1	7/2014				11/2017 12/2017	Jurgenson et al.
8,790,187 B2 8,797,415 B2		Walker et al. Arnold	9,854,219		12/2017	
8,798,646 B1		Wang et al.	9,961,520	0 B2	5/2018	Brooks et al.
8,856,349 B2		Jain et al.	9,965,893			Gray G06T 19/006
8,874,677 B2		Rosen et al.	9,984,499 10,074,383			Jurgenson et al. Cowburn
8,886,227 B2 8,909,679 B2			10,074,580			Jurgenson et al.
		Agarwal et al.	10,304,23	7 B2	5/2019	Sequeira et al.
8,909,725 B1	12/2014	$\mathbf{c}$	10,319,149			Cowburn et al.
	12/2014	<b>1</b> •	10,366,543 10,733,802			Jurgenson et al. Jurgenson et al.
8,933,966 B2 8,965,460 B1		Oi et al. Rao et al.	10,733,802			Corcoran et al.
8,972,357 B2		Shim et al.	11,315,33			Jurgenson et al.
8,995,433 B2	3/2015		2002/0047868			Miyazawa
9,015,285 B1		Ebsen et al.	2002/0078456 2002/0087633			Hudson et al. Sharma
9,020,745 B2 9,031,283 B2		Johnston et al. Arth et al.	2002/008703			Miller et al.
9,031,283 B2 9,040,574 B2		Wang et al.	2002/0122659	9 A1	9/2002	Mcgrath et al.
9,055,416 B2		Rosen et al.	2002/012804		9/2002	_
9,058,687 B2		Kruglick	2002/0144154 2003/0001846			Tomkow Davis et al.
9,083,770 B1 9,094,137 B1		Drose et al. Sehn et al.	2003/001644			Lai et al.
9,098,926 B2		Quan et al.	2003/0017823			Mager et al.
9,100,806 B2	8/2015	Rosen et al.	2003/0020623			Cao et al.
9,100,807 B2		Rosen et al.	2003/0023874 2003/0037124			Prokupets et al. Yamaura et al.
9,113,301 B1 9,119,027 B2		Spiegel et al. Sharon et al.	2003/0050785			Friedrich et al.
9,119,027 B2 9,123,074 B2		Jacobs et al.	2003/0052925	5 A1	3/2003	Daimon et al.
9,129,432 B2	9/2015	Quan et al.	2003/0101230			Benschoter et al.
9,143,382 B2		Bhogal et al.	2003/0110503		6/2003 7/2003	
9,143,681 B1 9,148,424 B1	9/2015 9/2015	Ebsen et al. Yang	2003/012621: 2003/014877:		7/2003 8/2003	Spriestersbach et al.
9,148,424 B1 9,152,477 B1		Campbell et al.	2003/01487/			Prager et al.
9,191,776 B2		-	2003/0217106			Adar et al.
9,204,252 B2	12/2015		2003/022960			Zellweger et al.
9,225,805 B2			2004/0027373		2/2004	•
9,225,897 B1 9,237,202 B1	12/2015		2004/0064429 2004/007836			Hirstius et al. Anderson et al.
, ,		Berkovich et al.	2004/00/836			Oh et al.
2,2 10,07 DZ	1,2010	LUINOTION VE GIA	200 1/00/333		5, 200 T	

(56)		Referen	ces Cited	2008/0189177			Anderton et al.
	U.S.	PATENT	DOCUMENTS	2008/0207176 2008/0208692			Brackbill et al. Garaventi et al.
	0.5.		DOCOMENTO	2008/0214210	<b>A</b> 1		Rasanen et al.
2004/0111467	' A1	6/2004	Willis	2008/0222545		9/2008	_
2004/0158739			Wakai et al.	2008/0255976 2008/0256446			Altberg et al. Yamamoto
2004/0189465			Capobianco et al.	2008/0230440			Funaki et al.
2004/0203959 2004/0215625			Coombes Svendsen et al.	2008/0266421			Takahata et al.
2004/0243531		12/2004		2008/0270938		10/2008	
2004/0243688			Wugofski	2008/0288338			Wiseman et al.
2005/0021444			Bauer et al.	2008/0306826 2008/0313329			Kramer et al. Wang et al.
2005/0022211 2005/0048989		1/2005 3/2005	Veselov et al.	2008/0313346			Kujawa et al.
2005/0048989			Yomoda	2008/0318616			Chipalkatti et al.
2005/0097176			Schatz et al.	2009/0006191			Arankalle et al.
2005/0102381			Jiang et al.	2009/0006565 2009/0015703			Velusamy et al. Kim et al.
2005/0104976 2005/0114783		5/2005 5/2005	Currans	2009/0013703			Kobayashi
2005/0114785			Buchanan et al.	2009/0030774			Rothschild et al.
2005/0122405			Voss et al.	2009/0030999			Gatzke et al.
2005/0162523			Darrell et al.	2009/0040324			Nonaka Lottin et al
2005/0193340			Amburgey et al.	2009/0042588 2009/0058822			Lottin et al. Chaudhri
2005/0193345 2005/0198128			Klassen et al. Anderson	2009/0079846		3/2009	
2005/0130120			Buchheit et al.	2009/0089678			Sacco et al.
2005/0288954	A1	12/2005	McCarthy et al.	2009/0089710			Wood et al.
2006/0001758			Nam et al.	2009/0093261 2009/0132341			Ziskind Klinger
2006/0026067 2006/0107297			Nicholas et al. Toyama et al.	2009/0132341			Hangartner et al.
2006/0107297			Rothschild	2009/0132665			Thomsen et al.
2006/0119882			Harris et al.	2009/0148045			Lee et al.
2006/0242239			Morishima et al.	2009/0153492 2009/0157450		6/2009	Popp Athsani et al.
2006/0252438			Ansamaa et al.	2009/0137430			Gonzalez
2006/0265417 2006/0270419			Amato et al. Crowley et al.	2009/0160970			Fredlund et al.
2006/0287878			Wadhwa et al.	2009/0163182			Gatti et al.
2007/0004426			Pfleging et al.	2009/0177299			Van De Sluis
2007/0038715			Collins et al.	2009/0192900 2009/0199242			Collision Johnson et al.
2007/0040931 2007/0064899		3/2007	Nishizawa Boss et al.	2009/0135212			Fisher et al.
2007/00073517		3/2007	_	2009/0232354	<b>A</b> 1	9/2009	Camp, Jr. et al.
2007/0073823			Cohen et al.	2009/0234815			Boerries et al.
2007/0075898			Markhovsky et al.	2009/0239552 2009/0249222			Churchill et al. Schmidt et al.
2007/0082707 2007/0136228			Flynt et al. Petersen	2009/0249222			Robinson et al.
2007/0130228			Celestini	2009/0265647			Martin et al.
2007/0198340			Lucovsky et al.	2009/0288022			Almstrand et al.
2007/0198495			Buron et al.	2009/0291672 2009/0292608		11/2009 11/2009	Treves et al. Polachek
2007/0208751			Cowan et al.	2009/0292008			Alter et al.
2007/0210936 2007/0214180			Nicholson Crawford	2009/0319607			Belz et al.
2007/0214216			Carrer et al.	2009/0327073			Li
2007/0233556		10/2007	Koningstein	2010/0062794		3/2010	
2007/0233801			Eren et al.	2010/0082427 2010/0082693			Burgener et al. Hugg et al.
2007/0233859 2007/0243887			Zhao et al. Bandhole et al.	2010/0100568			Papin et al.
2007/0244750			Grannan et al.	2010/0113065			Narayan et al.
2007/0255456			Funayama	2010/0130233		5/2010	
2007/0281690			Altman et al.	2010/0131880 2010/0131895			Lee et al. Wohlert
2008/0022329 2008/0025701		1/2008 1/2008		2010/0151055			Miller et al.
2008/0023701			Krumm et al.	2010/0159944	<b>A</b> 1	6/2010	Pascal et al.
2008/0033930		2/2008		2010/0161658			Hamynen et al.
2008/0043041			Hedenstroem et al.	2010/0161831 2010/0162149			Haas et al. Sheleheda et al.
2008/0049704 2008/0055269			Witteman et al. Lemay et al.	2010/0182149			Beauregard et al.
2008/0053203			Chandhri	2010/0185552	<b>A</b> 1		Deluca et al.
2008/0076505			Ngyen et al.	2010/0185665			Horn et al.
2008/0092233			Tian et al.	2010/0191631			Weidmann Poterson et al
2008/0094387 2008/0104503		4/2008 5/2008	Chen Beall et al.	2010/0197318 2010/0197319			Petersen et al. Petersen et al.
2008/0104303			Bean et al. Baldeschweiler et al.	2010/0197319		8/2010	
2008/0120409			Sun et al.	2010/0198694			Muthukrishnan
2008/0147730	A1*		Lee G06Q 30/0212	2010/0198826	<b>A</b> 1	8/2010	Petersen et al.
2008/0148150		6/2008		2010/0198828			Petersen et al.
2008/0158230			Sharma et al.	2010/0198862			Jennings et al.
2008/0168033 2008/0168489			Ott et al. Schraga	2010/0198870 2010/0198917			Petersen et al. Petersen et al.
2000/0100 <del>4</del> 09	A1	112008	Semaga	ZUIU/UIJOJI/ .	4 1 1	0/2010	receised et al.

(56)	Referer	nces Cited	2012/0124176 A1		Curtis et al.
TIG	DATENIT	DOCUMENTS	2012/0124458 A1 2012/0131507 A1		Cruzada Sparandara et al.
U.L	o. PATEINT	DOCUMENTS	2012/0131507 A1 2012/0131512 A1		Takeuchi et al.
2010/0201482 A1	8/2010	Robertson et al.	2012/0143760 A1		Abulafia et al.
2010/0201402 A1 2010/0201536 A1		Robertson et al.	2012/0146991 A1	6/2012	Bala et al.
2010/0214436 A1		Kim et al.	2012/0150978 A1		Monaco
2010/0223128 A1	9/2010	Dukellis et al.	2012/0165100 A1		Lalancette et al.
2010/0223343 A1		Bosan et al.	2012/0166971 A1		Sachson et al.
2010/0250109 A1		Johnston et al.	2012/0169855 A1 2012/0172062 A1	7/2012	Altman et al.
2010/0257196 A1		Waters et al.	2012/01/2002 A1 2012/0173991 A1		Roberts et al.
2010/0259386 A1 2010/0273509 A1		Holley et al. Sweeney et al.	2012/0176401 A1		Hayward et al.
2010/02/3303 A1 2010/0281045 A1		•	2012/0181330 A1	7/2012	•
2010/0287485 A1		Bertolami et al.	2012/0184248 A1		Speede
2010/0306669 A1	12/2010	Della Pasqua	2012/0197724 A1		Kendall
2011/0004071 A1		Faiola et al.	2012/0200743 A1		Blanchflower et al.
2011/0010205 A1		Richards	2012/0209921 A1 2012/0209924 A1		Adafin et al. Evans et al.
2011/0029512 A1		Folgner et al. Uemichi et al.	2012/0209924 A1		De Francisco Lopez et al.
2011/0040783 A1 2011/0040804 A1		Peirce et al.	2012/0212509 A1		Benko et al.
2011/0040004 A1		Ellenby et al.	2012/0212632 A1	8/2012	Mate et al.
2011/0050915 A1		Wang et al.	2012/0220264 A1		Kawabata
2011/0064388 A1		Brown et al.	2012/0226748 A1		Bosworth et al.
2011/0066743 A1		Hurley et al.	2012/0233000 A1 2012/0236162 A1		Fisher et al. Imamura
2011/0083101 A1		Sharon et al.	2012/0230102 A1 2012/0239761 A1		Linner et al.
2011/0096093 A1 2011/0099507 A1		Oi et al. Nesladek et al.	2012/0239701 A1*		Vaittinen G06F 3/04815
2011/0099307 A1 2011/0102630 A1		Rukes			715/781
2011/0102030 A1		Igelman et al.	2012/0250951 A1	10/2012	Chen
2011/0137881 A1		Cheng et al.			Kandekar et al.
2011/0145564 A1	6/2011	Moshir et al.	2012/0254325 A1		
2011/0159890 A1		Fortescue et al.			Garcia et al.
2011/0164163 A1		Bilbrey et al.		11/2012	Perantatos et al.
2011/0197194 A1 2011/0202598 A1		D'Angelo et al. Evans et al.			Wada et al.
2011/0202338 A1 2011/0202968 A1		Nurmi			Tanaka et al.
2011/0202533 A1		Schmidt et al.	2012/0304080 A1	11/2012	Wormald et al.
2011/0213845 A1		Logan et al.	2012/0307096 A1		Ford et al.
2011/0215966 A1		_	2012/0307112 A1		
2011/0225048 A1			2012/0314040 A1 2012/0319904 A1		Kopf et al. Lee et al.
2011/0238763 A1 2011/0255736 A1		Shin et al. Thompson et al.			He et al.
2011/0233730 A1 2011/0270584 A1		Thompson et al. Plocher et al.			Metcalf et al.
2011/0273575 A1			2013/0002649 A1		
		Murphy G06F 3/04842	2013/0006759 A1		Srivastava et al.
		345/419	2013/0024757 A1		Doll et al.
2011/0279446 A1	* 11/2011	Castro G01C 21/20	2013/0036364 A1 2013/0045753 A1		Johnson Obermeyer et al
2011/0250152 11	* 11/2011	345/419	2013/0043733 A1 2013/0050260 A1	2/2013	Obermeyer et al. Reitan
2011/02/9453 A1	* 11/2011	Murphy G06T 13/00	2013/0055083 A1	2/2013	_
2011/0282799 A1	11/2011	345/420 Huston	2013/0057587 A1		Leonard et al.
2011/0282799 A1 2011/0283188 A1			2013/0059607 A1		Herz et al.
2011/0286586 A1		±	2013/0060690 A1		Oskolkov et al.
2011/0314419 A1		Dunn et al.	2013/0063369 A1 2013/0067027 A1		Malhotra et al. Song et al.
2011/0320373 A1		Lee et al.	2013/0007027 A1 2013/0071093 A1		Hanks et al.
2012/0028659 A1		Whitney et al.	2013/0080254 A1		Thramann
2012/0033718 A1 2012/0036015 A1		Kauffman et al. Sheikh	2013/0085790 A1	4/2013	Palmer et al.
2012/0036013 A1 2012/0036443 A1		Ohmori et al.	2013/0086072 A1		Peng et al.
2012/0041722 A1		Quan et al.	2013/0090171 A1		Holton et al.
2012/0054797 A1		Skog et al.	2013/0095857 A1 2013/0104053 A1		Garcia et al. Thornton et al.
2012/0059722 A1			2013/0104033 A1 2013/0110885 A1		Brundrett, III
2012/0062805 A1		Candelore	2013/0110503 A1 2013/0111514 A1		Slavin et al.
2012/0069233 A1 2012/0084731 A1		Nonaka et al. Filman et al.	2013/0128059 A1	5/2013	Kristensson
2012/0084731 A1 2012/0084835 A1		Thomas et al.	2013/0129252 A1	5/2013	Lauper
2012/0086727 A1		Korah G06F 3/03	2013/0132477 A1		Bosworth et al.
		345/633	2013/0141419 A1		Mount et al.
2012/0099800 A1	4/2012	Llano et al.	2013/0145286 A1 2013/0159110 A1		Feng et al.
2012/0108293 A1		Law et al.	2013/0139110 A1 2013/0159919 A1		Rajaram et al. Leydon
2012/0110096 A1		Smarr et al.	2013/0159919 A1 2013/0169680 A1		Chien et al.
2012/0113143 A1 2012/0113272 A1		Adhikari et al. Hata	2013/0169822 A1		Zhu et al.
2012/0113272 A1 2012/0122570 A1		паца Baronoff	2013/0173729 A1		Starenky et al.
2012/0122370 A1 2012/0123830 A1		Svendsen et al.	2013/0181971 A1*		Mueller G06F 3/04815
2012/0123871 A1	5/2012	Svendsen et al.			345/419
2012/0123875 A1		Svendsen et al.	2013/0182133 A1		Tanabe
2012/0124126 A1	5/2012	Alcazar et al.	2013/0185131 A1	7/2013	Sinha et al.

(56)	Referer	ices Cited	2014/0306986 A1 2014/0317302 A1	10/2014 10/2014	Gottesman et al.
U.S.	PATENT	DOCUMENTS	2014/0324627 A1		Haver et al.
2013/0187952 A1*	7/2013	Berkovich G01S 5/16	2014/0325383 A1	10/2014	Brown et al.
2012/0121120	<b>5</b> /2012	345/633		12/2014 12/2014	Spiegel Spiegel et al.
2013/0191198 A1 2013/0194164 A1*		Carlson et al. Sugden G06F 3/167	2014/0339032 A1*		Saarimaki
2013/0194301 A1 2013/0198176 A1	8/2013 8/2013	Robbins et al.	2015/0020086 A1 2015/0040074 A1*		Chen et al. Hofmann G06F 3/04815
2013/01981/0 A1 2013/0215101 A1	8/2013			- (	715/852
2013/0218965 A1		Abrol et al.	2015/0046278 A1 2015/0071619 A1		Pei et al. Brough
2013/0218968 A1 2013/0222323 A1		Mcevilly et al. Mckenzie	2015/00/1019 A1 2015/0087263 A1		Branscomb et al.
2013/0227476 A1	8/2013		2015/0088622 A1		Ganschow et al.
2013/0232194 A1		Knapp et al.	2015/0095020 A1 2015/0096042 A1		Leydon Mizrachi
2013/0263031 A1 2013/0265450 A1		Oshiro et al. Barnes, Jr.	2015/0050512 AT		Wu et al.
2013/0267253 A1	10/2013	Case et al.	2015/0169827 A1		Laborde
2013/0275505 A1		Gauglitz et al.	2015/0172534 A1 2015/0178257 A1*		Miyakawa et al. Jones G06F 17/241
2013/0290443 A1 2013/0304646 A1		Collins et al. De Geer	2010,01.020. 111	0,2010	345/419
2013/0308822 A1	11/2013	Marimon et al.	2015/0178260 A1		Brunson
2013/0311255 A1 2013/0325964 A1		Cummins et al. Berberat	2015/0193982 A1 2015/0199082 A1		Mihelich et al. Scholler et al.
2013/0323904 A1 2013/0344896 A1		Kirmse et al.	2015/0222814 A1		Li et al.
2013/0346869 A1	12/2013	Asver et al.	2015/0227602 A1		Ramu et al.
2013/0346877 A1 2014/0006129 A1		Borovoy et al. Heath	2015/0261917 A1 2015/0312184 A1		
		Mulcahy et al.			Bare G06K 9/00671
2014/0019264 A1	1/2014	Wachman et al.	2015/0250126 4.1	10/0015	345/633
2014/0032682 A1 2014/0043204 A1		Prado et al. Basnayake et al.	2015/0350136 A1 2015/0365795 A1		
2014/0045204 A1		Gordon et al.			Hu et al.
2014/0047016 A1	2/2014		2016/0006927 A1	1/2016	
2014/0047045 A1 2014/0047335 A1		Baldwin et al. Lewis et al.	2016/0014063 A1 2016/0019270 A1*		Hogeg et al. Jones G06F 16/248
2014/0049652 A1		Moon et al.			700/98
2014/0052485 A1		Shidfar	2016/0085773 A1		Chang et al.
2014/0052633 A1 2014/0057660 A1		Gandhi Wager	2016/0085863 A1 2016/0086670 A1		Allen et al. Gross et al.
2014/0064624 A1	3/2014	Kim et al.	2016/0099901 A1		Allen et al.
2014/0081634 A1 2014/0082651 A1		Forutanpour Sharifi	2016/0180887 A1	6/2016	
2014/0082031 A1 2014/0086727 A1	3/2014		2016/0182422 A1 2016/0182875 A1	6/2016	Sehn et al.
2014/0092130 A1		Anderson et al.	2016/0102073 AT 2016/0225164 A1		Tomlin et al.
2014/0096029 A1 2014/0114565 A1		Schultz Aziz et al.	2016/0239248 A1	8/2016	
2014/0122658 A1		Haeger et al.	2016/0253710 A1		Publicover et al.
2014/0122787 A1		Shalvi et al.	2016/0266386 A1 2016/0277419 A1		Scott et al. Allen et al.
2014/0125668 A1 2014/0129207 A1		Steed et al. Bailey et al.	2016/0321708 A1	11/2016	
2014/0129953 A1		Spiegel	2016/0352791 A1		
2014/0143143 A1		Fasoli et al.			Laliberte Laliberte
2014/0149519 A1 2014/0155102 A1		Redfern et al. Cooper et al.			Benko et al.
2014/0173424 A1	6/2014	Hogeg et al.	2017/0006094 A1		Abou Mahmoud et al.
2014/0173457 A1 2014/0189592 A1		Wang et al. Benchenaa et al.	2017/0061308 A1 2017/0124713 A1*		Chen et al.  Jurgenson G06K 0/78
2014/0103332 A1		Krivorot	2017/0124713 A1 2017/0161382 A1		Jurgenson G06K 9/78 Ouimet et al.
2014/0207679 A1	7/2014		2017/0228878 A1*		Goldman G06T 7/344
2014/0214471 A1 2014/0222564 A1		Schreiner, III Kranendonk et al.	2017/0237789 A1		Harner et al.
		Na G09G 5/377	2017/0243371 A1 2017/0263029 A1		Jurgenson et al. Yan et al.
2014/0250405 4.1	0/2014	345/629			Azmoodeh et al.
2014/0258405 A1 2014/0265359 A1		Perkin Cheng et al.			Samaranayake et al.
2014/0266703 A1		Dalley, Jr. et al.			Allen et al. Davis et al.
2014/0277735 A1	9/2014	Breazeal	2017/0374308 A1 2018/0005450 A1		Davis et al.  Daniels et al.
2014/0279061 A1 2014/0279436 A1		Elimeliah et al. Dorsey et al.	2018/0061127 A1		Gullicksen
2014/0279540 A1	9/2014	Jackson	2018/0089904 A1		Jurgenson et al.
2014/0280537 A1 2014/0282096 A1		Pridmore et al. Rubinstein et al.	2018/0096502 A1 2018/0144524 A1*		Kansara Lotto G06F 3/167
2014/0282096 A1 2014/0287779 A1		O'Keefe et al.	2019/0073832 A1	3/2019	
2014/0289833 A1	9/2014	Briceno	2019/0156534 A1		Chen et al.
2014/0301645 A1*	10/2014	Mattila G06K 9/00476	2019/0295326 A1		Jurgenson et al.
		382/182	2020/0250889 A1	8/2020	LI

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

2020/0327738 A1 10/2020 Jurgenson et al. 2022/0245907 A1 8/2022 Jurgenson et al.

#### FOREIGN PATENT DOCUMENTS

EP	2051480 A1	4/2009
EP	2151797 A1	2/2010
GB	2399928 A	9/2004
KR	19990073076 A	10/1999
KR	20010078417 A	8/2001
KR	20110071210 A	6/2011
KR	20130137063 A	12/2013
KR	20150107063 A	9/2015
WO	WO-1996024213 A1	8/1996
WO	WO-1999063453 A1	12/1999
WO	WO-2000058882 A1	10/2000
WO	WO-2001029642 A1	4/2001
WO	WO-2001050703 A3	7/2001
WO	WO-2006118755 A2	11/2006
WO	WO-2007092668 A2	8/2007
WO	WO-2009043020 A2	4/2009
WO	WO-2011040821 A1	4/2011
WO	WO-2011119407 A1	9/2011
WO	WO-2012000107 A1	1/2012
WO	WO-2013008238 A1	1/2013
WO	WO-2013008251 A2	1/2013
WO	WO-2013045753 A1	4/2013
WO	WO-2014006129 A1	1/2014
WO	WO-2014068573 A1	5/2014
WO	WO-2014115136 A1	7/2014
WO	WO-2014194262 A2	12/2014
WO	WO-2015192026 A1	12/2015
WO	WO-2016044424 A1	3/2016
WO	WO-2016054562 A1	4/2016
WO	WO-2016065131 A1	4/2016
WO	WO-2016100318 A2	6/2016
WO	WO-2016100318 A3	6/2016
WO	WO-2016100342 A1	6/2016
WO	WO-2016/112299 A1	7/2016
WO	WO-2016149594 A1	9/2016
WO	WO-2016179166 A1	11/2016
WO	WO-2016179235 A1	11/2016
WO	WO-2017075476 A1	5/2017
WO	WO-2017176739 A1	10/2017
WO	WO-2017176992 A1	10/2017
WO	WO-2018005644 A1	1/2018
WO	WO-2020160261 A1	8/2020

#### OTHER PUBLICATIONS

- "Adding photos to your listing", eBay, [Online] Retrieved from the Internet: <URL: http://pages.ebay.com/help/sell/pictures.html>, (accessed May 24, 2017), 4 pgs.
- "U.S. Appl. No. 14/954,090, Corrected Notice of Allowance mailed Feb. 3, 17", 4 pgs.
- "U.S. Appl. No. 14/954,090, Corrected Notice of Allowance mailed Apr. 18, 17", 4 pgs.
- "U.S. Appl. No. 14/954,090, Notice of Allowance mailed Jan. 11, 17", 11 pgs.
- "U.S. Appl. No. 14/954,090, Preliminary Amendment filed Dec. 28, 2016", 10 pgs.
- "U.S. Appl. No. 15/436,363, Examiner Interview Summary dated Nov. 28, 2018", 3 pgs.
- "U.S. Appl. No. 15/436,363, Non Final Office Action dated Oct. 9, 2018", 15 pgs.
- "U.S. Appl. No. 15/436,363, Notice of Allowance dated Jan. 29, 2019", 8 pgs.
- "U.S. Appl. No. 15/436,363, Response filed Nov. 28, 2018 to Non Final Office Action dated Oct. 9, 2018", 15 pgs.
- "U.S. Appl. No. 15/591,887, Corrected Notice of Allowance dated Sep. 8, 2017", 4 pgs.

- "U.S. Appl. No. 15/591,887, Notice of Allowance dated Aug. 25, 2017", 10 pgs.
- "U.S. Appl. No. 15/591,887, Preliminary Amendment filed Jun. 12, 2017", 10 pgs.
- "U.S. Appl. No. 15/591,887, PTO Response to Rule 312 Communication dated Sep. 19, 2017", 2 pgs.
- "U.S. Appl. No. 15/830,965, Corrected Notice of Allowability dated Aug. 6, 2018", 4 pgs.
- "U.S. Appl. No. 15/830,965, Non Final Office Action dated Feb. 16, 2018", 7 pgs.
- "U.S. Appl. No. 15/830,965, Notice of Allowability dated Jul. 5, 2018", 5 pgs.
- "U.S. Appl. No. 15/830,965, Notice of Allowance dated Jun. 13, 2018", 8 pgs.
- "U.S. Appl. No. 15/830,965, Response filed May 16, 2018 to Non Final Office Action dated Feb. 16, 2018", 10 pgs.
- "U.S. Appl. No. 16/135,849, Preliminary Amendment filed Oct. 15, 2018", 10 pgs.
- "U.S. Appl. No. 16/136,849, Non Final Office Action dated Oct. 17, 2018", 4 pgs.
- "BlogStomp", StompSoftware, [Online] Retrieved from the Internet: <URL: http://stompsoftware.com/blogstomp>, (accessed May 24, 2017), 12 pgs.
- "Cup Magic Starbucks Holiday Red Cups come to life with AR app", Blast Radius, [Online] Retrieved from the Internet: <URL: http://www.blastradius.com/work/cup-magic>, (2016), 7 pgs.
- "Daily App: InstaPlace (IOS/Android): Give Pictures a Sense of Place", TechPP, [Online] Retrieved from the Internet: <URL: http://techpp.com/2013/02/15/instaplace-app-review>, (2013), 13 pgs.
- "InstaPlace Photo App Tell The Whole Story", [Online] Retrieved from the Internet: <URL: https://youtu.be/uF\_gFkg1hBM>, (Nov. 8, 2013), 113 pgs., 1:02 min.
- "International Application Serial No. PCT/US2015/037251, International Search Report dated Sep. 29, 2015", 2 pgs.
- "Introducing Snapchat Stories", [Online] Retrieved from the Internet: <URL: https://www.youtube.com/watch?v=88Cu3yN-LIM>, (Oct. 3, 2013), 92 pgs.
- "Macy's Believe-o-Magic", [Online] Retrieved from the Internet: < URL: https://www.youtube.com/watch?v=xvzRXy3J0ZO>, (Nov. 7, 2011), 102 pgs.
- "Macys Introduces Augmented Reality Experience in Stores across Country as Part of Its 2011 Believe Campaign", Business Wire, [Online] Retrieved from the Internet: <URL: https://www.businesswire.com/news/home/20111102006759/en/Macys-Introduces-Augmented-Reality-Experience-Stores-Country>, (Nov. 2, 2011), 6 pgs.
- "Starbucks Cup Magic", [Online] Retrieved from the Internet: <URL: https://www.youtube.com/watch?v=RWwQXi9RG0w>, (Nov. 8, 2011), 87 pgs.
- "Starbucks Cup Magic for Valentine's Day", [Online] Retrieved from the Internet: <URL: https://www.youtube.com/watch?v=8nvqOzjq10w>, (Feb. 6, 2012), 88 pgs.
- "Starbucks Holiday Red Cups Come to Life, Signaling the Return of the Merriest Season", Business Wire, [Online] Retrieved from the Internet: <URL: http://www.businesswire.com/news/home/20111115005744/en/2479513/Starbucks-Holiday-Red-Cups-Life-Signaling-Return>, (Nov. 15, 2011), 5 pgs.
- Carthy, Roi, "Dear All Photo Apps: Mobli Just Won Filters", TechCrunch, [Online] Retrieved from the Internet: <URL: https://techcrunch.com/2011/09/08/mobli-filters>, (Sep. 8, 2011), 10 pgs. Castelluccia, Claude, et al., "EphPub: Toward robust Ephemeral Publishing", 19TH IEEE International Conference on Network Protocols (ICNP), (Oct. 17, 2011), 18 pgs.
- Fajman, "An Extensible Message Format for Message Disposition Notifications", Request for Comments: 2298, National Institutes of Health, (Mar. 1998), 28 pgs.
- Janthong, Isaranu, "Instaplace ready on Android Google Play store", Android App Review Thailand, [Online] Retrieved from the Internet: <URL: http://www.android-free-app-review.com/2013/01/instaplace-android-google-play-store.html>, (Jan. 23, 2013), 9 pgs. Leyden, John, "This SMS will self-destruct in 40 seconds", [Online] Retrieved from the Internet: <URL: http://www.theregister.co.uk/2005/12/12/stealthtext/>, (Dec. 12, 2005), 1 pg.

#### (56) References Cited

#### OTHER PUBLICATIONS

Macleod, Duncan, "Macys Believe-o-Magic App", [Online] Retrieved from the Internet: <URL: http://theinspirationroom.com/daily/2011/macys-believe-o-magic-app>, (Nov. 14, 2011), 10 pgs.

Macleod, Duncan, "Starbucks Cup Magic Lets Merry", [Online] Retrieved from the Internet: <URL: http://theinspirationroom.com/daily/2011/starbucks-cup-magic>, (Nov. 12, 2011), 8 pgs.

Melanson, Mike, "This text message will self destruct in 60 seconds", [Online] Retrieved from the Internet: <URL: http://readwrite.com/2011/02/11/this\_text\_message\_will\_self\_destruct\_in\_60\_seconds>, (Feb. 18, 2015), 4 pgs.

Notopoulos, Katie, "A Guide To The New Snapchat Filters And Big Fonts", [Online] Retrieved from the Internet: <URL: https://www.buzzfeed.com/katienotopoulos/a-guide-to-the-new-snapchat-filters-and-big-fonts?utm\_term =.bkQ9qVZWe#.nv58YXpkV>, (Dec. 22, 2013), 13 pgs.

Panzarino, Matthew, "Snapchat Adds Filters, A Replay Function And For Whatever Reason, Time, Temperature And Speed Overlays", TechCrunch, [Online] Retrieved from the Internet: <URL: https://techcrunch.com/2013/12/20/snapchat-adds-filters-new-font-and-for-some-reason-time-temperature-and-speed-overlays/>, (Dec. 20, 2013), 12 pgs.

Sawers, Paul, "Snapchat for IOS Lets You Send Photos to Friends and Set How long They're Visible For", [Online] Retrieved from the Internet: <URL: https://thenextweb.com/apps/2012/05/07/snapchat-for-ios-lets-you-send-photos-to-friends-and-set-how-long-theyre-visible-for/>, (May 7, 2012), 5 pgs.

Shein, Esther, "Ephemeral Data", Communications of the ACM, vol. 56, No. 9, (Sep. 2013), 3 pgs.

Tripathi, Rohit, "Watermark Images in PHP And Save File on Server", [Online] Retrieved from the Internet: <URL: http://code.rohitink.com/2012/12/28/watermark-images-in-php-and-save-file-on-server>, (Dec. 28, 2012), 4 pgs.

Vaas, Lisa, "StealthText, Should You Choose to Accept It", [Online] Retrieved from the Internet: <URL: http://www.eweek.com/print/c/a/MessagingandCollaboration/StealthTextShouldYouChooseto Acceptit>, (Dec. 13, 2005), 2 pgs.

"U.S. Appl. No. 14/053,913, Response filed Nov. 13, 2017 to Non Final Office Action dated Jun. 12, 2017", 11 pgs.

"U.S. Appl. No. 14/953,913, Non Final Office Action dated Jun. 12, 2017", 35 pgs.

"U.S. Appl. No. 14/953,913, Notice of Allowance dated Jan. 30, 2018", 23 pgs.

"U.S. Appl. No. 15/437,018, Corrected Notice of Allowability dated Jul. 11, 2018", 2 pgs.

"U.S. Appl. No. 15/437,018, Corrected Notice of Allowance dated Jun. 6, 2018", 5 pgs.

"U.S. Appl. No. 15/437,018, Examiner Interview Summary dated Feb. 16, 2018", 3 pgs.

"U.S. Appl. No. 15/437,018, Non Final Office Action dated Jan. 26, 2018", 9 pgs.

"U.S. Appl. No. 15/437,018, Notice of Allowance dated May 18, 2018", 7 pgs.

"U.S. Appl. No. 15/437,018, Response Filed Mar. 21, 2018 to Non Final Office Action dated Jan. 26, 2018", 9 pgs.

"U.S. Appl. No. 15/492,089, Non Final Office Action dated Jan. 25, 2019", 7 pgs.

"U.S. Appl. No. 15/706,074, Non Final Office Action dated Nov. 7, 2018", 26 pgs.

"U.S. Appl. No. 15/971,566, Final Office Action dated Oct. 31, 2018", 38 pgs.

"U.S. Appl. No. 15/971,566, Non Final Office Action dated Feb. 12, 2019", 12 pgs.

"U.S. Appl. No. 15/971,566, Non Final Office Action dated Jun. 14, 2018", 7 pgs.

"U.S. Appl. No. 15/971,566, Resonse filed Jan. 31, 2019 to Final Office Action dated Oct. 31, 2018", 12 pgs.

"U.S. Appl. No. 15/971,566, Response filed Oct. 15, 2018 to Non Final Office Action dated Jun. 14, 2018", 11 pgs.

"U.S. Appl. No. 16/136,849, Corrected Notice of Allowability dated Apr. 25, 2019", 4 pgs.

"U.S. Appl. No. 16/136,849, Notice of Allowance dated Mar. 5, 2019", 7 pgs.

"U.S. Appl. No. 16/136,849, Response filed )Jan. 17, 2019 to Non Final Office Action dated Oct. 17, 2018", 9 pgs.

"deltatre and Vizrt expanding partnership for Magma Pro Football solution", Vizrt (Online), [Online] Retrieved from the Internet: <URL: http://www.vizrt.com/news/newsgrid/39609/deltatre\_and\_Vizrt\_expanding\_partnership\_for\_Magma-Pro\_Football-solution>, (2013), 5 pgs.

"European Application Serial No. 16795488.2, Response filed Dec. 7, 2018 to Communication Pursuant to Rules 161(1) and 162 EPC dated Jun. 7, 2018", w/ English Claims, 114 pgs.

"International Application Serial No. PCT/US2016/059503, International Preliminary Report on Patentability dated May 11, 2018", 7 pgs.

"International Application Serial No. PCT/US2016/059503, International Search Report dated Jan. 23, 2017", 4 pgs.

"International Application Serial No. PCT/US2016/059503, Written Opinion dated Jan. 23, 2017", 5 pgs.

"Korean Application Serial No. 10-2017-7035785, Notice of Preliminary Rejection dated Dec. 28, 2018", w/ English Translation, 10 pgs.

Klein, Georg, "Parallel Tracking and Mapping for Small AR Workspaces—Source Code", PTAM Blog, [Online] Retrieved from the Internet on Apr. 3, 2019: <URL: www.robots.ox.ac.uk/~gk/PTAM/>, (Feb. 2014), 2 pgs.

Maher, Mary Lou, et al., "Designworld: An Augmented 3D Virtual World for Multidisciplinary, Collaborative Design", University of Sydney, Key Centre for Design Computing and Cognition, (2006), 10 pgs.

Rosten, Edward, "Fast Comer Detection", Edwardrosten.com, [Online] Retrieved from the Internet on Apr. 3, 2019: <URL: https://www.edwardrosten.com/work/fast.html>, (Feb. 25, 2018), 5 pgs.

Wagner, Daniel, et al., "Pose Tracking from Natural Features on Mobile Phones", Proc. of the 7th IEEE/ACM Intl. Symposium on Mixed and Augmented Reality, IEEE Computer Society, (2008), 10 pgs.

"U.S. Appl. No. 16/438,226, Non Final Office Action dated Jul. 10, 2019", 6 pgs.

"U.S. Appl. No. 16/438,226, Response filed Oct. 8, 2019 to Non-Final Office Action dated Jul. 10, 2019", 11 pgs.

"U.S. Appl. No. 16/265,382, Non Final Office Action dated Mar. 3, 2020", 18 pgs.

"U.S. Appl. No. 16/438,226, Final Office Action dated Jan. 3, 2020", 10 pgs.

"U.S. Appl. No. 16/438,226, Notice of Allowance dated Mar. 26, 2020", 8 pgs.

"U.S. Appl. No. 16/438,226, Response filed Mar. 16, 2020 to Final Office Action dated Jan. 3, 2020", 11 pgs.

"U.S. Appl. No. 16/438,226, Corrected Notice of Allowability dated May 1, 2020", 4 pgs.

"International Application Serial No. PCT/US2020/015868, Invitation to Pay Additional Fees dated May 19, 2020", 14 pgs.

Park, Jungsik, et al., "Interactive deformation of real objects", IEEE International Symposium On Mixed and Augmented Reality (ISMAR), (Sep. 10, 2014), 295-296.

Raskar, R, et al., "Table-top spatially-augmented realty: bringing physical models to life with projected imagery", Augmented Reality, Proceedings. 2nd IEEE and ACM International Workshop On San Francisco, CA, (Oct. 20-21, 1999), 64-71.

Taejin, Ha, et al., "ARtalet: Tangible User Interface Based Immersive Augmented Reality Authoring Tool for Digilog Book", Ubiquitous Virtual Reality (ISUVR), International Symposium On, IEEE, Piscataway, NJ, USA, (Jul. 7, 10), 40-43.

"U.S. Appl. No. 16/265,382, Response filed Aug. 3, 2020 to Non Final Office Action dated Mar. 3, 2020", 10 pgs.

"International Application Serial No. PCT/US2020/015868, International Search Report dated Jul. 10, 2020", 6 pgs.


"International Application Serial No. PCT/US2020/015868, Written Opinion dated Jul. 10, 2020", 15 pgs.


#### (56) References Cited


#### OTHER PUBLICATIONS

- "U.S. Appl. No. 16/265,382, Final Office Action dated Oct. 13, 2020", 21 pgs.
- "U.S. Appl. No. 16/265,382, Response filed Feb. 12, 2021 to Final Office Action dated Oct. 13, 2020", 11 pgs.
- "U.S. Appl. No. 16/265,382, Non Final Office Action dated May 24, 2021", 23 pgs.
- "U.S. Appl. No. 16/265,382, Response filed Sep. 24, 2021 to Non Final Office Action dated May 24, 2021", 11 pgs.
- "International Application Serial No. PCT/US2020/015868, International Preliminary Report on Patentability dated Aug. 12, 2021", 17 pgs.
- "U.S. Appl. No. 16/265,382, Advisory Action dated Jan. 12, 2022", 4 pgs.
- "U.S. Appl. No. 16/265,382, Final Office Action dated Oct. 29, 2021", 22 pgs.
- "U.S. Appl. No. 16/265,382, Response filed Dec. 29, 2021 to Final Office Action dated Oct. 29, 2021", 11 pgs.
- "U.S. Appl. No. 16/913,503, 312 Amendment filed Mar. 23, 2022", 9 pgs.
- "U.S. Appl. No. 16/913,503, Notice of Allowance dated Dec. 23, 2021", 8 pgs.


- Wei, Guan, "Hybrid methods for robust image matching and its applications in augmented reality", PhD diss., University of Southern California, (2014), 131 pgs.
- "U.S. Appl. No. 16/265,382, Response filed Mar. 29, 2022 to Advisory Action dated Jan. 12, 2022", 11 pgs.
- "U.S. Appl. No. 16/913,503, PTO Response to Rule 312 Communication dated Apr. 1, 2022", 2 pgs.
- "U.S. Appl. No. 16/265,382, Non Final Office Action dated Jun. 3, 2022", 24 pgs.
- "Korean Application Serial No. 10-2021-7027590, Notice of Preliminary Rejection dated Jul. 11, 2022", W/English Translation, 11 pgs.
- "U.S. Appl. No. 16/265,382, Final Office Action dated Oct. 18, 2022", 24 pgs.
- "U.S. Appl. No. 16/265,382, Response filed Oct. 3, 2022 to Non Final Office Action dated Jun. 3, 2022", 11 pgs.
- "U.S. Appl. No. 17/728,553, Non Final Office Action dated Oct. 14, 2022", 5 pgs.
- "U.S. Appl. No. 16/277,626, Response filed Oct. 26, 2022 to Non Final Office Action dated Oct. 7, 2022", 11 pgs.
- "Korean Application Serial No. 10-2021-7027590, Response filed Oct. 11, 2022 to Notice of Preliminary Rejection dated Jul. 11, 2022", w/ English Claims, 17 pgs.
- \* cited by examiner










0000





food of Contract of State of S















Jooos Cook S




900


RECEIVING THE ANAMORPHIC MEDIA FROM A SECOND MOBILE DEVICE, THE SECOND MOBILE DEVICE ASSOCIATED WITH A SECOND USER PROFILE, WHEREIN THE SECOND USER PROFILE IS LINKED TO A USER PROFILE ASSOCIATED WITH THE MOBILE DEVICE 902

ASSIGNING THE ANAMORPHIC MEDIA TO THE LOCATION OF THE SPACE 904


DETECTING THE MOBILE DEVICE AT THE LOCATION 906


RETRIEVING THE ANAMORPHIC MEDIA AT THE MOBILE DEVICE IN RESPONSE TO THE DETECTING THE MOBILE DEVICE AT THE LOCATION 908






Food (C). 11





600x 600 13



### AUGMENTED REALITY ANAMORPHOSIS SYSTEM

#### PRIORITY CLAIM

This application is a continuation of and claims the benefit of priority of U.S. patent application Ser. No. 15/436,363, filed on Feb. 17, 2017, which is hereby incorporated by reference herein in its entirety

#### TECHNICAL FIELD

Embodiments of the present disclosure relate generally to mobile computing technology and, more particularly, but not by way of limitation, to the presentation of augmented and virtual reality displays.

#### BACKGROUND

Augmented reality (AR) is a live direct or indirect view of a physical, real-world environment whose elements are supplemented, or "augmented." by a computer-generated sensory input such as sound, video, graphics, or the like. As a result, the technology functions to enhance a user's perception of reality.

Anamorphosis is a distorted projection or perspective requiring the viewer to use a special device or occupy a special vantage point (or both) to reconstitute an image. Anamorphic media may be generated through a process of 30 greatly distorting an image only to have it revealed either from a single vantage point or from its reflection on a mirrored surface. For example, artists have created anamorphic art at physical locations, wherein the anamorphic art is only viewable from a single perspective, and appears dis-35 torted from all other vantage points.

### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.

- FIG. 1 is a block diagram showing an example messaging 45 system for exchanging data (e.g., messages and associated content) over a network in accordance with some embodiments, wherein the messaging system includes an augmented reality anamorphosis system.
- FIG. 2 is block diagram illustrating further details regarding a messaging system, according to example embodiments.
- FIG. 3 is a schematic diagram illustrating data that may be stored in the database of the messaging server system, according to certain example embodiments.
- FIG. 4 is a schematic diagram illustrating a structure of a message, according to some embodiments, generated by a messaging client application for communication.
- FIG. **5** is a schematic diagram illustrating an example access-limiting process, in terms of which access to content 60 (e.g., an ephemeral message, and associated multimedia payload of data) or a content collection (e.g., an ephemeral message story) may be time-limited (e.g., made ephemeral) in accordance with some embodiments.
- FIG. **6** is a block diagram illustrating various modules of 65 an anamorphosis system, according to certain example embodiments.

2

- FIG. 7 is a flowchart illustrating various operations of the anamorphosis system in generating and causing display of anamorphic media within a presentation of a space at a graphical user interface (GUI), according to certain example embodiments.
- FIG. 8 is a diagram illustrating various operations of the anamorphosis system in causing display of anamorphic media in a presentation of a space, according to certain example embodiments.
- FIG. 9 is a flowchart illustrating various operations of the anamorphosis system in retrieving anamorphic media to be displayed in a presentation of a space, according to certain example embodiments.
- FIG. **10** is an example of anamorphic media displayed in a presentation of a space, according to certain example embodiments.
  - FIG. 11 is an example of anamorphic media displayed in a presentation of a space, according to certain example embodiments.
  - FIG. 12 is an example of anamorphic media displayed in a presentation of a space, according to certain example embodiments.
  - FIG. 13 is a block diagram illustrating a representative software architecture, which may be used in conjunction with various hardware architectures herein described and used to implement various embodiments.
  - FIG. 14 is a block diagram illustrating components of a machine, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein.

#### DETAILED DESCRIPTION

Reference will now be made in detail to specific example embodiments for carrying out the inventive subject matter of the present disclosure. In the following description, specific details are set forth in order to provide a thorough understanding of the subject matter. It shall be appreciated that embodiments may be practiced without some or all of these specific details.

Disclosed are anamorphosis systems to generate and cause display of anamorphic media (e.g., distorted text or other anamorphically distorted images) within a presentation of a space (e.g., a room or a defined environment). The anamorphosis systems are configured to identify a set of features of a space (e.g., walls and objects), determine relative positions of the set of features, determine a perspective of the mobile device within the space based on the relative positions of the set of features in the space, retrieve anamorphic media based on the location of the mobile device, and apply the anamorphic media to a presentation of the space at the mobile device. For example, in a bare rectangular room, an example anamorphosis system on a 55 mobile device may use an image sensor to capture one or more images of the walls of the room, identify the walls and their relative positions, and then apply anamorphic text as an augmented reality addition to images output on a display of the mobile device. The anamorphic text may, for example, be presented clearly on the display when the mobile device is in one perspective (e.g., phone position) and displayed as distorted to the point of being unreadable from another perspective (e.g., position of the mobile device).

Anamorphic media may include media items such as images and videos, configured such that the media items are only visible from one or more specified perspectives. The anamorphic media may also include a stylized text string

projected onto surfaces of a space such that the stylized text string is correctly displayed when viewed through a user device from a specified perspective.

The anamorphic media may be generated through a process of distorting a media item by stretching, expanding, 5 splitting, projecting, or otherwise altering the media item such that the media item may be revealed to a user from a single vantage point or through a viewing apparatus or surface (e.g., a cylindrical, conical, or flat mirror). Thus, if the anamorphic media is viewed from a perspective other 10 than an intended perspective, the anamorphic media may appear distorted or unclear.

The anamorphosis system may include a video and image capture system to perform functionality that includes at least recording and presenting images of a space, and a graphical 15 interface configured to display a presentation of the space. In some example embodiments, to apply the anamorphic media to a presentation of a space, the anamorphosis system generates a surface model of a space. The surface model of the space is a topographical representation of the space that 20 includes three-dimensional depictions of features, surfaces, contours, and shapes that make up the space. For example, the surface model may include a wire-mesh representation of a three-dimensional view of the space. To generate the surface model, the anamorphosis system may apply various 25 computer vision techniques to digital images and videos of the space. For example, the anamorphosis system may acquire, process, and analyze a digital image and/or video of the space to generate the surface model.

In further embodiments, the anamorphosis system may 30 access a surface model database that includes surface models of spaces, organized based on geolocation coordinates of corresponding locations depicted by the surface models. The anamorphosis system determines a location of a mobile retrieves the corresponding surface model from the surface model database based on the location.

The anamorphosis system identifies a set of features of the space to determine a perspective of the mobile device. The set of features may include distinguishing points or features 40 such as contours in the space, markings, or other features that may be used as graphical markers. For example, the distinguishing points or features may include landmarks as well as identifiable objects such as windows and/or doors. Having identified the set of features of the space, the 45 anamorphosis system determines relative positions of each of the distinguishing points or features relative to one another. For example, the relative positions may indicate distances between the distinguishing points or features. The anamorphosis system thereby determines a perspective of 50 the mobile device based on the relative positions of the distinguishing points or features. The perspective indicates a representation of the space relative to the mobile device.

In some example embodiments, the anamorphosis system retrieves anamorphic media to be applied to the presentation 55 of the space, based on the location of the mobile device. In some example embodiments, the anamorphic media may only be available to one or more specified users (e.g., based on user identifiers). For example, upon detecting a mobile device at a location the anamorphosis system may retrieve 60 an anamorphic media assigned to the location based on location data coordinates.

Upon retrieving the anamorphic media to be displayed in the presentation of the space, the anamorphosis system applies transformations to the anamorphic media based on 65 the perspective of the mobile device, and displays the transformed anamorphic media in the presentation of the

space. In this way, the anamorphic media may appear differently based on the perspective of the mobile device.

Consider an illustrative example from a user perspective. A user of a mobile device causes display of a space corresponding to a current location of the mobile device (e.g., the user points a camera of the mobile device at a space adjacent to them). Based on location data retrieved from the mobile device, the anamorphosis system determines the location of the mobile device, and in response retrieves corresponding anamorphic media to be displayed in the presentation of the space. The anamorphosis system receives a set of features of the space and relative positions of the set of features within the space from the mobile device, and determines a perspective of the mobile device based on the set of features and the relative positions. The anamorphosis system thereby applies a transformation to the anamorphic media based on the perspective of the mobile device. The anamorphosis system displays the transformed anamorphic media in the presentation of the space, for viewing by the user. As the user moves within the space, the anamorphosis system recalculates the perspective of the user, and updates the display of the anamorphic media within the presentation of the space in real-time. Thus, as the user views the anamorphic media item within the presentation of the space, the user may adjust their perspective until the anamorphic media is correctly displayed.

In some example embodiments, users may generate and tag their own anamorphic media to locations. A user at a location may generate anamorphic media to be displayed in a space, and assign the anamorphic media to a position in the space. For example, the user may specify the position of the anamorphic media by selecting landmarks and/or distinguishing features of the space, and specifying a viewing device (e.g., based on geographic position sensors), and 35 perspective of the anamorphic media. The anamorphosis system may store the anamorphic media in a database to be retrieved at a later time.

> FIG. 1 is a block diagram showing an example messaging system 100 for exchanging data (e.g., messages and associated content) over a network. The messaging system 100 includes multiple client devices 102, each of which hosts a number of applications including a messaging client application 104. Each messaging client application 104 is communicatively coupled to other instances of the messaging client application 104 and a messaging server system 108 via a network **106** (e.g., the Internet).

> Accordingly, each messaging client application 104 is able to communicate and exchange data with another messaging client application 104 and with the messaging server system 108 via the network 106. The data exchanged between messaging client applications 104, and between a messaging client application 104 and the messaging server system 108, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data which may include or be used as anamorphic media).

> The messaging server system 108 provides server-side functionality via the network 106 to a particular messaging client application 104. While certain functions of the messaging system 100 are described herein as being performed by either a messaging client application 104 or by the messaging server system 108, it will be appreciated that the location of certain functionality either within the messaging client application 104 or the messaging server system 108 is a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system 108, but to later migrate

this technology and functionality to the messaging client application 104 where a client device 102 has a sufficient processing capacity.

The messaging server system 108 supports various services and operations that are provided to the messaging client application 104. Such operations include transmitting data to, receiving data from, and processing data generated by the messaging client application 104. In some embodiments, this data includes, message content, client device information, geolocation information, media annotation and overlays, message content persistence conditions, social network information, and live event information, as examples. In other embodiments, other data is used. Any such data may be used as part of or to generate anamorphic media in accordance with different embodiments described herein. Data exchanges within the messaging system 100 are invoked and controlled through functions available via user interfaces (UIs) of the messaging client application 104.

Turning now specifically to the messaging server system 20 tion of a space. 108, an Application Program Interface (API) server 110 is coupled to, and provides a programmatic interface to, an application server 112. The application server 112 is communicatively coupled to a database server(s) 118, which facilitates access to a database(s) 120 in which is stored data 25 114. associated with messages processed by the application server 112.

Dealing specifically with the Application Program Interface (API) server 110, this server receives and transmits message data (e.g., commands and message payloads) 30 between the client device 102 and the application server 112. Specifically, the Application Program Interface (API) server 110 provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the messaging client application server 112. The Application Program Interface (API) server 110 exposes various functions supported by the application server 112, including account registration, login functionality, the sending of messages, via the application server 112, from a particular messaging client application 40 104 to another messaging client application 104, the sending of media files (e.g., images or video) from a messaging client application 104 to the messaging server application 114, and for possible access by another messaging client application 104, the setting of a collection of media data 45 (e.g., story), the retrieval of a list of friends of a user of a client device 102, the retrieval of such collections, the retrieval of messages and content, the adding and deletion of friends to a social graph, the location of friends within a social graph, opening and application event (e.g., relating to 50 the messaging client application 104).

The application server 112 hosts a number of applications and subsystems, including a messaging server application 114, an image processing system 116, a social network system 122, and an anamorphosis system 124. The messag- 55 ing server application 114 implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the messaging client 60 application 104. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available, by the messaging server application 114, to the messaging client 65 application 104. Other processor and memory intensive processing of data may also be performed server-side by the

messaging server application 114, in view of the hardware requirements for such processing.

The application server 112 also includes an image processing system 116 that is dedicated to performing various image processing operations, typically with respect to images or video received within the payload of a message at the messaging server application 114.

The social network system 122 supports various social networking functions services, and makes these functions and services available to the messaging server application 114. To this end, the social network system 122 maintains and accesses an entity graph 304 within the database(s) 120. Examples of functions and services supported by the social network system 122 include the identification of other users of the messaging system 100 with which a particular user has relationships or is "following," and also the identification of other entities and interests of a particular user. The anamorphosis system 124 provides functionality to generate and cause display of anamorphic media within a presenta-

The application server 112 is communicatively coupled to one or more database server(s) 118, which facilitates access to a database(s) 120 in which is stored data associated with messages processed by the messaging server application

FIG. 2 is block diagram illustrating further details regarding the messaging system 100, according to example embodiments. Specifically, the messaging system 100 is shown to comprise the messaging client application 104 and the application server 112, which in turn embody a number of some subsystems, namely an ephemeral timer system 202, a collection management system 204 and an annotation system 206.

The ephemeral timer system **202** is responsible for enforcapplication 104 in order to invoke functionality of the 35 ing the temporary access to content permitted by the messaging client application 104 and the messaging server application 114. To this end, the ephemeral timer system 202 incorporates a number of timers that, based on duration and display parameters associated with a message, or collection of messages (e.g., a SNAPCHAT story), selectively display and enable access to messages and associated content such as anamorphic media via the messaging client application **104**. Further details regarding the operation of the ephemeral timer system 202 arc provided below.

> The collection management system **204** is responsible for managing collections of media (e.g., collections of text, image video and audio data). In some examples, a collection of content (e.g., messages, including anamorphic media, images, video, text and audio) may be organized into an "event gallery" or an "event story." Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content such as anamorphic media displayed at specific locations relating to a music concert may be made available as a "story" for the duration of that music concert. The collection management system 204 may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the messaging client application 104.

> The collection management system 204 furthermore includes a curation interface 208 that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface 208 enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system 204 employs machine vision (or image recognition

technology) and content rules to automatically curate a content collection. In certain embodiments, compensation may be paid to a user for inclusion of user generated content into a collection. In such cases, the curation interface 208 operates to automatically make payments to such users for 5 the use of their content.

The annotation system 206 provides various functions that enable a user to annotate or otherwise modify or edit media content associated with a message. For example, the annotation system 206 provides functions related to the 10 generation and publishing of media overlays for messages processed by the messaging system 100. The annotation system 206 operatively supplies a media overlay (e.g., a SNAPCHAT filter) to the messaging client application 104 based on a geolocation of the client device **102**. In another 15 example, the annotation system 206 operatively supplies a media overlay to the messaging client application 104 based on other information, such as, social network information of the user of the client device 102. A media overlay may include audio and visual content and visual effects. 20 Examples of audio and visual content include anamorphic media, pictures, texts, logos, animations, and sound effects. An example of a visual effect includes color overlaying, or projecting an anamorphic media item over a presentation depicting a space. The audio and visual content or the visual 25 effects can be applied to a media content item (e.g., a photo) at the client device **102**. For example, the media overlay including text that can be overlaid on top of a photograph or video stream generated taken by the client device 102. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the annotation system **206** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the 35 geolocation of the client device 102. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database(s) 120 and accessed through the database server(s) 118.

In one example embodiment, the annotation system **206** 40 provides a user-based publication platform that enables users to select a geolocation on a map, and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The annotation system 45 **206** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

In another example embodiment, the annotation system **206** provides a merchant-based publication platform that 50 enables merchants to select a particular media overlay associated with a geolocation via a bidding process. For example, the annotation system **206** associates the media overlay of a highest bidding merchant with a corresponding geolocation for a predefined amount of time 55

FIG. 3 is a schematic diagram 300 illustrating data which may be stored in the database(s) 120 of the messaging server system 108, according to certain example embodiments. While the content of the database(s) 120 is shown to comprise a number of tables, it will be appreciated that the 60 data could be stored in other types of data structures (e.g., as an object-oriented database).

The database(s) 120 includes message data stored within a message table 314. The entity table 302 stores entity data, including an entity graph 304. Entities for which records are maintained within the entity table 302 may include individuals, corporate entities, organizations, objects, places, application 104 to enable a send personal story. A collection of colle

8

events etc. Regardless of type, any entity regarding which the messaging server system 108 stores data may be a recognized entity. Each entity is provided with a unique identifier, as well as an entity type identifier (not shown).

The entity graph 304 furthermore stores information regarding relationships and associations between entities. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example.

The database(s) 120 also stores annotation data, in the example form of filters, in an annotation table 312. Filters for which data is stored within the annotation table 312 are associated with and applied to videos (for which data is stored in a video table 310) and/or images (for which data is stored in an image table 308). Filters, in one example, are overlays (e.g., anamorphic media items) that are displayed as overlaid on an image or video during presentation to a recipient user. For example, the overlay may include an anamorphic media item displayed within a presentation of a space, such that the anamorphic media item appears to be projected over a set of three dimensional surfaces of a space, following the contours of the surfaces of the space. Filters may be of varies types, including a user-selected filters from a gallery of filters presented to a sending user by the messaging client application 104 when the sending user is composing a message. Other types of filers include geolocation filters (also known as geo-filters) which may be presented to a sending user based on geographic location. For example, geolocation filters specific to a neighborhood or special location may be presented within a user interface by the messaging client application 104, based on geolocation information determined by a GPS unit of the client device 102. Another type of filer is a data filer, which may be selectively presented to a sending user by the messaging client application 104, based on other inputs or information gathered by the client device 102 during the message creation process. Example of data filters include current temperature at a specific location, a current speed at which a sending user is traveling, battery life for a client device 102 or the current time.

Other annotation data that may be stored within the image table 308 is so-called "lens" data. A "lens" may be a real-time special effect and sound that may be added to an image or a video.

As mentioned above, the video table 310 stores video data which, in one embodiment, is associated with messages for which records are maintained within the message table 314. Similarly, the image table 308 stores image data associated with messages for which message data is stored in the entity table 302. The entity table 302 may associate various annotations from the annotation table 312 with various images and videos stored in the image table 308 and the video table 310.

A story table **306** stores data regarding collections of messages and associated image, video or audio data, which are compiled into a collection (e.g., a SNAPCHAT story or a gallery). The creation of a particular collection may be initiated by a particular user (e.g., each user for which a record is maintained in the entity table **302**) A user may create a "personal story" in the form of a collection of content that has been created and sent/broadcast by that user. To this end, the user interface of the messaging client application **104** may include an icon that is user selectable to enable a sending user to add specific content to his or her personal story.

A collection may also constitute a "live story." which is a collection of content from multiple users that is created

manually, automatically or using a combination of manual and automatic techniques. For example, a "live story" may constitute a curated stream of user-submitted content from varies locations and events. Users, whose client devices have location services enabled and are at a common location 5 event at a particular time may, for example, be presented with an option, via a user interface of the messaging client application 104, to contribute content to a particular live story. The live story may be identified to the user by the messaging client application 104, based on his or her location. The end result is a "live story" told from a community perspective.

A further type of content collection is known as a "location story," which enables a user whose client device 102 is located within a specific geographic location (e.g., on a 15 college or university campus) to contribute to a particular collection. In some embodiments, a contribution to a location story may require a second degree of authentication to verify that the end user belongs to a specific organization or other entity (e.g., is a student on the university campus).

FIG. 4 is a schematic diagram illustrating a structure of a message 400, according to some in some embodiments, generated by a messaging client application 104 for communication to a further messaging client application 104 or the messaging server application 114. The content of a 25 particular message 400 is used to populate the message table 314 stored within the database(s) 120, accessible by the messaging server application 114. Similarly, the content of a message 400 is stored in memory as "in-transit" or "in-flight" data of the client device 102 or the application 30 server 112. The message 400 is shown to include the following components:

A message identifier 402: a unique identifier that identifies the message 400.

- user via a user interface of the client device 102 and that is included in the message 400.
- A message image payload 406: image data, captured by a camera component of a client device 102 or retrieved from memory of a client device 102, and that is 40 included in the message 400.
- A message video payload 408: video data, captured by a camera component or retrieved from a memory component of the client device 102 and that is included in the message 400.
- A message audio payload 410: audio data, captured by a microphone or retrieved from the memory component of the client device 102, and that is included in the message 400.
- A message annotations 412: annotation data (e.g., filters, 50 stickers or other enhancements) that represents annotations to be applied to message image payload 406, message video payload 408, or message audio payload **410** of the message **400**.
- A message duration parameter 414: parameter value indi- 55 cating, in seconds, the amount of time for which content of the message (e.g., the message image payload 406, message video payload 408, message audio payload 410) is to be presented or made accessible to a user via the messaging client application 104.
- A message geolocation parameter 416: geolocation data (e.g., latitudinal and longitudinal coordinates) associated with the content payload of the message. Multiple message geolocation parameter 416 values may be included in the payload, each of these parameter values 65 being associated with respect to content items included in the content (e.g., a specific image into within the

**10** 

message image payload 406, or a specific video in the message video payload 408).

- A message story identifier 418: identifier values identifying one or more content collections (e.g., "stories") with which a particular content item in the message image payload 406 of the message 400 is associated. For example, multiple images within the message image payload 406 may each be associated with multiple content collections using identifier values.
- A message tag 420: each message 400 may be tagged with multiple tags, each of which is indicative of the subject matter of content included in the message payload. For example, where a particular image included in the message image payload 406 depicts an animal (e.g., a lion), a tag value may be included within the message tag **420** that is indicative of the relevant animal. Tag values may be generated manually, based on user input, or may be automatically generated using, for example, image recognition.
- A message sender identifier 422: an identifier (e.g., a messaging system identifier, email address or device identifier) indicative of a user of the client device 102 on which the message 400 was generated and from which the message 400 was sent
- A message receiver identifier 424: an identifier (e.g., a messaging system identifier, email address or device identifier) indicative of a user of the client device 102 to which the message 400 is addressed.

The contents (e.g. values) of the various components of message 400 may be pointers to locations in tables within which content data values are stored. For example, an image value in the message image payload 406 may be a pointer to (or address of) a location within an image table 308. Similarly, values within the message video payload 408 may A message text payload 404: text, to be generated by a 35 point to data stored within a video table 310, values stored within the message annotations **412** may point to data stored in an annotation table 312, values stored within the message story identifier 418 may point to data stored in a story table **306**, and values stored within the message sender identifier 422 and the message receiver identifier 424 may point to user records stored within an entity table 302.

> FIG. 5 is a schematic diagram illustrating an accesslimiting process 500, in terms of which access to content (e.g., an ephemeral message 502, and associated multimedia 45 payload of data including anamorphic media) or a content collection (e.g., an ephemeral message story **504**) may be time-limited (e.g., made ephemeral). For example, an ephemeral message 502 may include an anamorphic media item which may be displayed for a period of time specified by the story timer **514**.

> An ephemeral message 502 is shown to be associated with a message duration parameter 506, the value of which determines an amount of time that the ephemeral message 502 will be displayed to a receiving user of the ephemeral message 502 by the messaging client application 104. In one embodiment, where the messaging client application 104 is a SNAPCHAT application client, an ephemeral message **502** is viewable by a receiving user for up to a maximum of 10 seconds, depending on the amount of time that the sending user specifies using the message duration parameter **506**.

The message duration parameter 506 and the message receiver identifier 424 are shown to be inputs to a message timer 512, which is responsible for determining the amount of time that the ephemeral message 502 is shown to a particular receiving user identified by the message receiver identifier 424. In particular, the ephemeral message 502 will only be shown to the relevant receiving user for a time

period determined by the value of the message duration parameter 506. The message timer 512 is shown to provide output to a more generalized ephemeral timer system 202, which is responsible for the overall timing of display of content (e.g., an ephemeral message 502) to a receiving user.

The ephemeral message 502 is shown in FIG. 5 to be included within an ephemeral message story 504 (e.g., a personal SNAPCHAT story, or an event story). The ephemeral message story 504 has an associated story duration parameter 508, a value of which determines a time-duration 10 for which the ephemeral message story 504 is presented and accessible to users of the messaging system 100. The story duration parameter 508, for example, may be the duration of a music concert, where the ephemeral message story 504 is a collection of content pertaining to that concert. Alternatively, a user (either the owning user or a curator user) may specify the value for the story duration parameter 508 when performing the setup and creation of the ephemeral message story 504.

Additionally, each ephemeral message **502** within the 20 ephemeral message story 504 has an associated story participation parameter 510, a value of which determines the duration of time for which the ephemeral message 502 will be accessible within the context of the ephemeral message story 504. Accordingly, a particular ephemeral message 25 story 504 may "expire" and become inaccessible within the context of the ephemeral message story 504, prior to the ephemeral message story 504 itself expiring in terms of the story duration parameter **508**. The story duration parameter **508**, story participation parameter **510**, and message receiver 30 identifier 424 each provide input to a story timer 514, which operationally determines, firstly, whether a particular ephemeral message 502 of the ephemeral message story 504 will be displayed to a particular receiving user and, if so, for how long. Note that the ephemeral message story **504** is also 35 aware of the identity of the particular receiving user as a result of the message receiver identifier 424.

Accordingly, the story timer 514 operationally controls the overall lifespan of an associated ephemeral message story **504**, as well as an individual ephemeral message **502** 40 included in the ephemeral message story 504. In one embodiment, each and every ephemeral message 502 within the ephemeral message story 504 remains viewable and accessible for a time-period specified by the story duration parameter **508**. In a further embodiment, a certain ephemeral 45 message 502 may expire, within the context of ephemeral message story **504**, based on a story participation parameter **510**. Note that a message duration parameter **506** may still determine the duration of time for which a particular ephemeral message 502 is displayed to a receiving user, even 50 within the context of the ephemeral message story 504. Accordingly, the message duration parameter 506 determines the duration of time that a particular ephemeral message 502 is displayed to a receiving user, regardless of whether the receiving user is viewing that ephemeral mes- 55 sage 502 inside or outside the context of an ephemeral message story 504.

The ephemeral timer system 202 may furthermore operationally remove a particular ephemeral message 502 from the ephemeral message story 504 based on a determination 60 that it has exceeded an associated story participation parameter 510. For example, when a sending user has established a story participation parameter 510 of 24 hours from posting, the ephemeral timer system 202 will remove the relevant ephemeral message 502 from the ephemeral message story 65 504 after the specified 24 hours. The ephemeral timer system 202 also operates to remove an ephemeral message story

12

504 either when the story participation parameter 510 for each and every ephemeral message 502 within the ephemeral message story 504 has expired, or when the ephemeral message story 504 itself has expired in terms of the story duration parameter 508.

In certain use cases, a creator of a particular ephemeral message story 504 may specify an indefinite story duration parameter 508. In this case, the expiration of the story participation parameter 510 for the last remaining ephemeral message 502 within the ephemeral message story 504 will determine when the ephemeral message story 504 itself expires. In this case, a new ephemeral message 502, added to the ephemeral message story 504, with a new story participation parameter 510, effectively extends the life of an ephemeral message story 504 to equal the value of the story participation parameter 510.

Responsive to the ephemeral timer system 202 determining that an ephemeral message story 504 has expired (e.g., is no longer accessible), the ephemeral timer system 202 communicates with the messaging system 100 (and, for example, specifically the messaging client application 104 to cause an indicium (e.g., an icon) associated with the relevant ephemeral message story 504 to no longer be displayed within a user interface of the messaging client application 104. Similarly, when the ephemeral timer system 202 determines that the message duration parameter 506 for a particular ephemeral message 502 has expired, the ephemeral timer system 202 causes the messaging client application 104 to no longer display an indicium (e.g., an icon or textual identification) associated with the ephemeral message 502.

FIG. 6 is a block diagram 600 illustrating components of the anamorphosis system 124, that configure the anamorphosis system 124 to cause display of anamorphic media in a presentation of a space, according to various example embodiments. The anamorphosis system 124 is shown as including a location module 602, a presentation module 604, an identification module 606, and an anamorphosis module 608, all, or some, configured to communicate with each other (e.g., via a bus, shared memory, or a switch). Any one or more of these modules may be implemented using one or more processors 610 (e.g., by configuring such one or more processors to perform functions described for that module) and hence may include one or more of the processors 610.

Any one or more of the modules described may be implemented using hardware alone (e.g., one or more of the processors 610 of a machine) or a combination of hardware and software. For example, any module described of the anamorphosis system 124 may physically include an arrangement of one or more of the processors 610 (e.g., a subset of or among the one or more processors of the machine) configured to perform the operations described herein for that module. As another example, any module of the engagement tracking system 610 may include software, hardware, or both, that configure an arrangement of one or more processors 610 (e.g., among the one or more processors of the machine) to perform the operations described herein for that module. Accordingly, different modules of the anamorphosis system 124 may include and configure different arrangements of such processors 610 or a single arrangement of such processors 610 at different points in time. Moreover, any two or more modules of the anamorphosis system 124 may be combined into a single module, and the functions described herein for a single module may be subdivided among multiple modules. Furthermore, according to various example embodiments, modules described herein as being implemented within a single

machine, database, or device may be distributed across multiple machines, databases, or devices.

FIG. 7 is a flowchart illustrating various operations of the anamorphosis system 124 in performing a method 700 for causing display of anamorphic media in a presentation of a space, according to certain example embodiments. Operations of the method 700 may be performed by the modules described above with respect to FIG. 6. As shown in FIG. 7, the method 700 includes one or more operations 702, 704, 706, 708, 710, 712, and 714.

Operation 702 may be performed by the presentation module 604. At operation 702, the presentation module 604 causes display of a presentation of a space within a graphical user interface (GUI) of a mobile device (e.g., client device 102). The mobile device may include a camera that captures images of a surrounding area. The images may thereby be displayed at within a GUI displayed on the mobile device.

Operation 704 may be performed by the location module 602. At operation 704, the location module 602 determines a location of the mobile device, wherein the location corresponds to the space displayed in the GUI. The location module 602 may determine the location based on GPS coordinates, or in some example embodiments, based on the images of the space captured by the camera of the mobile device. For example, the location module 602 may determine the location of the mobile device based on image recognition. The location module 602 may compare the images collected by the camera of the mobile device (e.g., client device 102) with a catalog of preloaded images depicting locations. Based on the comparison, the location ments.

Operation 704, the location corresponds to the space displayed in the GUI. The location of the mobile device causing of the mobile device.

Operation 706 may be performed by the identification module 606. At operation 706, the identification module 606 identifies a set of features of the space. The set of features may include landmarks or other distinguishing features, 35 such as windows, doors, wall outlets, identifying markings (e.g., a painted "X"), edges of walls, or the like. For example, the identification module 606 may employ computer vision and/or feature detection techniques known to persons of ordinary skill in the art, wherein the identification module 606 may collect image data that include visual images (e.g., through a camera element of the client device 102). In some example embodiments, the identification module 606 identifies at least three distinct features.

Operation 708 may be performed by the identification 45 module 606. At operation 708, the identification module 606 determines relative positions of each of the set of features identified, based on relative positions of the set of features. In some example embodiments, the identification module 606 may determine distances between each features, and a 50 position of each feature in the display. For example, the identification module 606 may apply triangulation techniques to determine relative positions of each of the set of features.

Operation 710 may be performed by the identification 55 module 606. At operation 710, the identification module determines a perspective of the mobile device based on the relative positions of each of the set of features. The perspective of the mobile device indicates a position and vantage point of the mobile device at the location.

Operation 712 may be performed by the anamorphosis module 608. At operation 712, the anamorphosis module 608 retrieves anamorphic media based on the location of the mobile device. The anamorphic media includes images and video that may be displayed in a presentation of a space, and 65 which appear distorted unless viewed from a specific viewing point in the location.

14

In some example embodiments, the anamorphosis module 608 may access a database of anamorphic media that includes anamorphic media categorized based on location, and wherein each anamorphic media item is to be viewed from a specific viewing point at a corresponding location.

The anamorphic media may include an image to be displayed at a location, wherein the image is only discernable if viewed from a specific position at the location. For example, the anamorphic media may include a stylized text string wherein the text string is not legible unless viewed from a specific viewing location (e.g., from a specified perspective), or in further embodiments, the anamorphic media may include a video or animation that plays once the user views the anamorphic media from a specific perspective.

Operation 714 may be performed by the presentation module 604. At operation 714, the presentation module 604 causes display of the anamorphic media in the presentation of the space based on the perspective of the mobile device.

FIG. 8 is a diagram illustrating various operations of the anamorphosis system 124 in performing a method 800 for causing display of the anamorphic media in the presentation of the space, according to certain example embodiments. Operations of the method 800 may be performed by the modules described above with respect to FIG. 6. As shown in FIG. 8, the method 800 includes one or more operations 802, 804, and 806 that may be performed as part (e.g., a precursor task, a subroutine, or a portion) of operation 714 of the method 700, according to some example embodiments

module **602** determines a location of the mobile device.

Operation **706** may be performed by the identification module **606**. At operation **706**, the identification module **606** identifies a set of features of the space. The set of features may include landmarks or other distinguishing features, such as windows, doors, wall outlets, identifying markings

Operation **802** may be performed by the anamorphosis module **608**. At operation **802**, the anamorphosis module **608** accesses a surface model of the space based on the location of the mobile device, wherein the surface model includes a three-dimensional representation of the space, such as a wire-mesh form.

In some example embodiments, the surface model may be generated by the anamorphosis module 608 based on computer vision. The surface model may be a geometric representation that includes a three-dimensional representation of a space based on a set of vertices and edges that together form polygons depicting the space. In further embodiments, the anamorphosis module 608 may access a surface model database that includes a set of pre-generated surface models categorized based on location data.

Operation 804 may be performed by the anamorphosis module 608. At operation 804, the anamorphosis module 608 causes display of the anamorphic media in the presentation of the space based on the three-dimensional representation of the space as depicted by the surface model and the perspective of the mobile device.

FIG. 9 is a flowchart illustrating various operations of the anamorphosis system 124 in performing a method 900 receiving anamorphic media, according to certain example embodiments. Operations of the method 900 may be performed by the modules described above with respect to FIG. 6. As shown in FIG. 9, the method 900 includes one or more operations 902, 904, and 906 that may be performed as part (e.g., a precursor task, a subroutine, or a portion) of the method 700, according to some example embodiments.

At operation 902, the anamorphosis system 124 receives anamorphic media from a client device 102 (e.g., a second mobile device of a second user). In some example embodiments, a second user may submit media data to be converted into anamorphic media by the anamorphosis system 124. For example, the user may provide the anamorphosis system 124 with media data (e.g., pictures, videos), as well as

location data indicating a location in which to assign the media data, and positioning data to indicate a position to display the media data in a presentation of a space corresponding to the location. The positioning data may include a perspective specified by the user, wherein the perspective may be defined by relative positions of a set of features in a space.

Consider an illustrative example from a user perspective. A user may provide the anamorphosis system 124 with media data that includes a media item such as a digital image 10 or video to be converted and displayed as anamorphic media at a specified location. The user may tag a media item with location data, and specify a display configuration of the media item in a presentation of the location. For example, the user may specify that the media item is to be displayed 15 so that it is viewable from a specific viewing location (e.g., based on location data and a specified perspective of the client device 102). Upon receiving the display configuration, the anamorphosis system 124 may apply a transformation to the media item in order to generate the anamorphic media. 20 The transformation may include stretching, distorting, or altering the media item, such that the media item may be projected onto a surface of the space, and be visible from a perspective specified by the user. For example, the anamorphosis system 124 may apply transformations to the media 25 item such that the media item is projected onto various surfaces on a space.

In some example embodiments, the second user may provide an input to the anamorphosis system 124 specifying that the anamorphic media is only visible/made available to "friends." or "connections" of the second user within a social media platform. In further embodiments, the second user may specify that the anamorphic media is only available/displayed to a first user (e.g., based on a user identifier of the first user).

At operation 904, the anamorphosis system 124 assigns the anamorphic media to the location based on location data such as GPS coordinates. For example, the user may provide the anamorphosis system 124 with GPS coordinates of the location and in response, the anamorphosis system 124 may 40 geo-tag the anamorphic media to the location.

At operation 906, the anamorphosis system 124 detects a client device 102 of a user at the location. For example, the anamorphosis system 124 may maintain a geofence around the location and detect a mobile device as the mobile device 45 transgresses a threshold of the geofence.

At operation 908, the anamorphosis system 124 retrieves the anamorphic media in response to detecting the user at the location, and causes display of the anamorphic media in a presentation of the space within the mobile device of the 50 user. The display of the anamorphic media may vary based on the perspective of the user.

FIG. 10 is an example of anamorphic media 1020 displayed in a presentation 1000 of a space 1010, according to certain example embodiments. The presentation 1000 may 55 be displayed within a GUI at a client device 102 according to the method 700 of FIG. 7. As shown in FIG. 10, the anamorphosis system 124 may display the anamorphic media 1020 in the presentation 1000 based on a perspective of a client device 102 displaying the presentation 1000. As 60 the perspective of the client device 102 changes (e.g., the user moves to a different viewing location), the anamorphosis system 124 may alter the display of the anamorphic media 124 based on the changes in the perspective.

FIG. 11 is an example of anamorphic media 1120 dis- 65 played in a presentation 1100 of a space 1110, from a first perspective, according to certain example embodiments. The

**16** 

presentation 1100 may be displayed within a GUI at a client device 102 according to the method 700 of FIG. 7. As shown in FIG. 11, the anamorphosis system 124 may display the anamorphic media 1120 in the presentation 1100 based on a perspective of a client device 102 displaying the presentation 1100. As the perspective of the client device 102 changes (e.g., the user moves to a different viewing location), the anamorphosis system 124 may alter the display of the anamorphic media 124 based on the changes in the perspective.

FIG. 12 is an example of anamorphic media 1120 displayed in a presentation 1200 of a space 1110, from a second perspective, according to certain example embodiments. The presentation 1200 may be displayed within a GUI at a client device 102 according to the method 700 of FIG. 7. As shown in FIG. 12, the anamorphosis system 124 may display the anamorphic media 1120 in the presentation 1200 based on a perspective of a client device 102 displaying the presentation 1200. As the perspective of the client device 102 changes (e.g., the user moves to a different viewing location), the anamorphosis system 124 may alter the display of the anamorphic media 124 based on the changes in the perspective.

Software Architecture

FIG. 13 is a block diagram illustrating an example software architecture 1306, which may be used in conjunction with various hardware architectures herein described. FIG. 13 is a non-limiting example of a software architecture and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture 1306 may execute on hardware such as machine 1300 of FIG. 13 that includes, among other things, processors 1304, memory 1314, and I/O components 1318. A representative hardware layer 1352 is illustrated and 35 can represent, for example, the machine 1300 of FIG. 13. The representative hardware layer 1352 includes a processing unit 1354 having associated executable instructions **1304**. Executable instructions **1304** represent the executable instructions of the software architecture 1306, including implementation of the methods, components and so forth described herein. The hardware layer 1352 also includes memory and/or storage modules memory/storage 1356, which also have executable instructions **1304**. The hardware layer 1352 may also comprise other hardware 1358.

In the example architecture of FIG. 13, the software architecture 1306 may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software architecture 1306 may include layers such as an operating system 1302, libraries 1320, applications 1316 and a presentation layer 1314. Operationally, the applications 1316 and/or other components within the layers may invoke application programming interface (API) API calls 1308 through the software stack and receive a response as in response to the API calls 1308. The layers illustrated are representative in nature and not all software architectures have all layers. For example, some mobile or special purpose operating systems may not provide a frameworks/ middleware 1318, while others may provide such a layer. Other software architectures may include additional or different layers.

The operating system 1302 may manage hardware resources and provide common services. The operating system 1302 may include, for example, a kernel 1322, services 1324 and drivers 1326. The kernel 1322 may act as an abstraction layer between the hardware and the other software layers. For example, the kernel 1322 may be responsible for memory management, processor manage-

ment (e.g., scheduling), component management, networking, security settings, and so on. The services 1324 may provide other common services for the other software layers. The drivers **1326** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers 5 **1326** include display drivers, camera drivers, Bluetooth® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), Wi-Fi® drivers, audio drivers, power management drivers, and so forth depending on the hardware configuration.

The libraries 1320 provide a common infrastructure that is used by the applications 1316 and/or other components and/or layers. The libraries 1320 provide functionality that allows other software components to perform tasks in an easier fashion than to interface directly with the underlying 15 operating system 1302 functionality (e.g., kernel 1322, services 1324 and/or drivers 1326). The libraries 1320 may include system libraries 1344 (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematical functions, and 20 the like. In addition, the libraries 1320 may include API libraries 1346 such as media libraries (e.g., libraries to support presentation and manipulation of various media format such as MPREG4, H.264, MP3, AAC, AMR, JPG, PNG), graphics libraries (e.g., an OpenGL framework that 25 may be used to render 2D and 3D in a graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebKit that may provide web browsing functionality), and the like. The libraries **1320** may also include a wide variety 30 of other libraries **1348** to provide many other APIs to the applications 1316 and other software components/modules.

The frameworks/middleware 1318 (also sometimes referred to as middleware) provide a higher-level common and/or other software components/modules. For example, the frameworks/middleware 1318 may provide various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks/middleware 1318 may provide a broad spec- 40 trum of other APIs that may be utilized by the applications **1316** and/or other software components/modules, some of which may be specific to a particular operating system 1302 or platform.

The applications **1316** include built-in applications **1338** 45 and/or third-party applications **1340**. Examples of representative built-in applications 1338 may include, but are not limited to, a contacts application, a browser application, a book reader application, a location application, a media application, a messaging application, and/or a game appli- 50 cation. Third-party applications 1340 may include an application developed using the ANDROID<sup>TM</sup> or IOS<sup>TM</sup> software development kit (SDK) by an entity other than the vendor of the particular platform, and may be mobile software running on a mobile operating system such as IOS<sup>TM</sup>, ANDROID<sup>TM</sup>, 55 WINDOWS® Phone, or other mobile operating systems. The third-party applications 1340 may invoke the API calls 1308 provided by the mobile operating system (such as operating system 1302) to facilitate functionality described herein.

The applications 1316 may use built in operating system functions (e.g., kernel 1322, services 1324 and/or drivers 1326), libraries 1320, and frameworks/middleware 1318 to create user interfaces to interact with users of the system. Alternatively, or additionally, in some systems interactions 65 with a user may occur through a presentation layer, such as presentation layer 1314. In these systems, the application/

**18** 

component "logic" can be separated from the aspects of the application/component that interact with a user.

FIG. 14 is a block diagram illustrating components of a machine 1400, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically. FIG. 14 shows a diagrammatic representation of the machine 1400 in the example form of a computer 10 system, within which instructions 1410 (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1400** to perform any one or more of the methodologies discussed herein may be executed. As such, the instructions 1410 may be used to implement modules or components described herein. The instructions 1410 transform the general, non-programmed machine 1400 into a particular machine 1400 programmed to carry out the described and illustrated functions in the manner described. In alternative embodiments, the machine 1400 operates as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine 1400 may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine 1400 may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch, head mounted device, VR goggles), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable infrastructure that may be used by the applications 1316 35 of executing the instructions 1410, sequentially or otherwise, that specify actions to be taken by machine 1400. Further, while only a single machine **1400** is illustrated, the term "machine" shall also be taken to include a collection of machines that individually or jointly execute the instructions **1410** to perform any one or more of the methodologies discussed herein.

> The machine 1400 may include processors 1404, memory memory/storage 1406, and I/O components 1418, which may be configured to communicate with each other such as via a bus 1402. The memory/storage 1406 may include a memory 1414, such as a main memory, or other memory storage, and a storage unit 1416, both accessible to the processors 1404 such as via the bus 1402. The storage unit **1416** and memory **1414** store the instructions **1410** embodying any one or more of the methodologies or functions described herein. The instructions 1410 may also reside, completely or partially, within the memory **1414**, within the storage unit 1416, within at least one of the processors 1404 (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine 1400. Accordingly, the memory 1414, the storage unit 1416, and the memory of processors 1404 are examples of machine-readable media.

The I/O components **1418** may include a wide variety of 60 components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components 1418 that are included in a particular machine 1400 will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input

device. It will be appreciated that the I/O components 1418 may include many other components that are not shown in FIG. 14. The I/O components 1418 are grouped according to functionality merely for simplifying the following discussion and the grouping is in no way limiting. In various 5 example embodiments, the I/O components 1418 may include output components 1426 and input components **1428**. The output components **1426** may include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal 10 display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components 1428 may include alphanumeric input components (e.g., a key- 15 board, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instrument), tactile input components (e.g., a physi- 20 cal button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

In further example embodiments, the I/O components 25 1418 may include biometric components 1430, motion components 1434, environmental environment components **1436**, or position components **1438** among a wide array of other components. For example, the biometric components **1430** may include components to detect expressions (e.g., 30) hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint iden- 35 tification, or electroencephalogram based identification), and the like. The motion components **1434** may include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environment components 40 **1436** may include, for example, illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometer that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., 45 one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other 50 components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components 1438 may include location sensor components (e.g., a Global Position system (GPS) receiver component), altitude sensor components (e.g., 55 altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

Communication may be implemented using a wide varicommunication components 1440 operable to couple the machine 1400 to a network 1432 or devices 1420 via coupling 1422 and coupling 1424 respectively. For example, the communication components 1440 may include a network interface component or other suitable device to inter- 65 face with the network 1432. In further examples, communication components 1440 may include wired

**20** 

communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices 1420 may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a Universal Serial Bus (USB)).

Moreover, the communication components 1440 may detect identifiers or include components operable to detect identifiers. For example, the communication components 1440 may include Radio Frequency Identification (RFID) tag reader components. NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components 1440, such as, location via Internet Protocol (IP) geo-location, location via Wi-Fi® signal triangulation, location via detecting a NFC beacon signal that may indicate a particular location, and so forth.

#### Glossary

"ANAMORPHOSIS" in this context refers to distortions and transformations applied to a media items such as images and videos, such that the media items appear normal when viewed from a particular point or through a suitable viewing device, mirror, or lens.

"PERSPECTIVE" in this context refers to a viewing angle of a user at a particular location.

"CARRIER SIGNAL" in this context refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible medium to facilitate communication of such instructions. Instructions may be transmitted or received over the network using a transmission medium via a network interface device and using any one of a number of wellknown transfer protocols.

"CLIENT DEVICE" in this context refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smart phones, tablets, ultra books, netbooks, laptops, multi-processor systems, microprocessorbased or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

"COMMUNICATIONS NETWORK" in this context refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless ety of technologies. The I/O components 1418 may include 60 LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include

a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other type of cellular or wireless coupling. In this example, the coupling may implement any of a variety of 5 types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology. General Packet Radio Service (GPRS) technology. Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership 10 Project (3GPP) including 3G, fourth generation wireless (4G) networks. Universal Mobile Telecommunications System (UMTS). High Speed Packet Access (HSPA). Worldwide Interoperability for Microwave Access (WiMAX). Long Term Evolution (LTE) standard, others defined by 15 various standard setting organizations, other long range protocols, or other data transfer technology.

"EMPHEMERAL MESSAGE" in this context refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

"MACHINE-READABLE MEDIUM" in this context refers to a component, device or other tangible media able to store instructions and data temporarily or permanently and may include, but is not be limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, 30 flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., Erasable Programmable Read-Only Memory (EEPROM)) and/or any suitable combination thereof. The term "machine-readable medium" should be taken to include a single medium or multiple 35 media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions. The term "machine-readable medium" shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., code) for execution 40 by a machine, such that the instructions, when executed by one or more processors of the machine, cause the machine to perform any one or more of the methodologies described herein. Accordingly, a "machine-readable medium" refers to a single storage apparatus or device, as well as "cloud- 45 based" storage systems or storage networks that include multiple storage apparatus or devices. The term "machinereadable medium" excludes signals per se.

"COMPONENT" in this context refers to a device, physical entity or logic having boundaries defined by function or 50 subroutine calls, branch points, application program interfaces (APIs), or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine 55 process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-read- 60 able medium) or hardware components. A "hardware component" is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, 65 a client computer system, or a server computer system) or one or more hardware components of a computer system

2.2

(e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a Field-Programmable Gate Array (FPGA) or an Application Specific Integrated Circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer generalpurpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations. Accordingly, the 25 phrase "hardware component" (or "hardware-implemented" component") should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently config-

ured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, "processor-implemented compo- 5 nent" refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a 10 method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a "cloud computing" environment or as a "software as a service" (SaaS). For example, at least 15 some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an Application Program Interface (API)). The performance 20 of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location 25 (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

"PROCESSOR" in this context refers to any circuit or 30 virtual circuit (a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., "commands". "op codes", "machine code", etc.) and which produces corresponding output signals that are applied to operate a machine. A 35 processor may, for example, be a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit 40 (ASIC), a Radio-Frequency Integrated Circuit (RFIC) or any combination thereof. A processor may further be a multicore processor having two or more independent processors (sometimes referred to as "cores") that may execute instructions contemporaneously.

"TIMESTAMP" in this context refers to a sequence of characters or encoded information identifying when a certain event occurred, for example giving date and time of day, sometimes accurate to a small fraction of a second.

What is claimed is:

- 1. A system comprising:
- a memory; and
- at least one hardware processor couple to the memory and comprising instructions that cause the system to perform operations comprising:
- causing display of a presentation of an environment at a client device, the client device associated with a user profile;
- identifying a set of features within the presentation of the environment, the set of features corresponding with a 60 landmark;
- determining a location of the client device based on the landmark that corresponds with the set of features;
- accessing a surface model from a surface model database based on the location of the client device, the surface 65 model comprising a wire-frame that comprises a topographical representation of the environment;

24

determining a perspective of the client device based on the location and the set of features;

accessing media content associated with the user profile of the client device, based on the location of the client device, the media content comprising an animation configured to execute responsive to a determination that the perspective of the client device associated with the user profile matches a specific perspective associated with the media content;

applying a transformation to the media content based on the topographical representation of the environment and the perspective of the client device;

causing display of the media content based on the transformation;

determining the perspective of the client device matches the specific perspective associated with the media content; and

causing the client device to execute the animation associated with the media content based on the determining that the perspective of the client device matches the specific perspective associated with the media content.

2. The system of claim 1, wherein the identifying the set of features depicted within the presentation of the environment includes:

receiving an input from the client device, the input comprising an identification of the set of features.

3. The system of claim 1, wherein the accessing the media content at the client device includes:

receiving an input that selects the media content from among a collection of media content from the client device.

4. The system of claim 1, wherein the instructions cause the system to perform operations further comprising:

receiving, from the client device, an input that specifies a display configuration of the media content;

wherein the applying the transformation to the image data of the media content is based on the perspective of the client device and the display configuration; and

generating anamorphic media based on the applying the transformation to the image data of the media content.

5. The system of claim 4, wherein the instructions cause the system to perform operations further comprising:

accessing location data of the client device, the location data identifying a location of the client device within the environment depicted in the presentation of the environment; and

associating the anamorphic media with the location identified by the location data.

**6**. A method including:

55

causing display of a presentation of an environment at a client device, the client device associated with a user profile;

identifying a set of features within the presentation of the environment, the set of features corresponding with a landmark;

determining a location of the client device based on the landmark that corresponds with the set of features;

accessing a surface model from a surface model database based on the location of the client device, the surface model comprising a wire-frame that comprises a topographical representation of the environment;

determining a perspective of the client device based on the location and the set of features;

accessing media content associated with the user profile of the client device, based on the location of the client device, the media content comprising an animation configured to execute responsive to a determination

that the perspective of the client device associated with the user profile matches a specific perspective associated with the media content;

applying a transformation to the media content based on the topographical representation of the environment 5 and the perspective of the client device;

causing display of the media content based on the transformation;

determining the perspective of the client device matches the specific perspective associated with the media con- 10 tent; and

causing the client device to execute the animation associated with the media content based on the determining that the perspective of the client device matches the specific perspective associated with the media content. 15

7. The method of claim 6, wherein the identifying the set of features depicted within the presentation of the environment includes:

receiving an input from the client device, the input comprising an identification of the set of features.

8. The method of claim 6, wherein the accessing the media content at the client device includes:

receiving an input that selects the media content from among a collection of media content from the client device.

9. The method of claim 6, wherein the method further comprises:

receiving, from the client device, an input that specifies a display configuration of the media content;

wherein the applying the transformation to the image data of the media content is based on the perspective of the client device and the display configuration; and

generating anamorphic media based on the applying the transformation to the image data of the media content.

10. The method of claim 9, wherein the method further 35 comprises:

accessing location data of the client device, the location data identifying a location of the client device within the environment depicted in the presentation of the environment; and

associating the anamorphic media with the location identified by the location data.

11. A non-transitory machine-readable storage medium comprising instructions that, when executed by one or more processors of a machine, cause the machine to perform 45 operations including:

causing display of a presentation of an environment at a client device, the client device associated with a user profile;

identifying a set of features within the presentation of the 50 environment, the set of features corresponding with a landmark;

**26** 

determining a location of the client device based on the landmark that corresponds with the set of features;

accessing a surface model from a surface model database based on the location of the client device, the surface model comprising a wire-frame that comprises a topographical representation of the environment;

determining a perspective of the client device based on the location and the set of features;

accessing media content associated with the user profile of the client device, based on the location of the client device, the media content comprising an animation configured to execute responsive to a determination that the perspective of the client device associated with the user profile matches a specific perspective associated with the media content;

applying a transformation to the media content based on the topographical representation of the environment and the perspective of the client device;

causing display of the media content based on the transformation;

determining the perspective of the client device matches the specific perspective associated with the media content; and

causing the client device to execute the animation associated with the media content based on the determining that the perspective of the client device matches the specific perspective associated with the media content.

12. The non-transitory machine-readable storage medium of claim 11, wherein the identifying the set of features depicted within the presentation of the environment includes:

receiving an input from the client device, the input comprising an identification of the set of features.

13. The non-transitory machine-readable storage medium of claim 11, wherein the accessing the media content at the client device includes:

receiving an input that selects the media content from among a collection of media content from the client device.

14. The non-transitory machine-readable storage medium of claim 11, wherein the instructions cause the machine to perform operations further comprising:

receiving, from the client device, an input that specifies a display configuration of the media content;

wherein the applying the transformation to the image data of the media content is based on the perspective of the client device and the display configuration; and

generating anamorphic media based on the applying the transformation to the image data of the media content.

\* \* \* \*