

US011909729B2

(12) **United States Patent**
Kaznocha et al.

(10) **Patent No.:** **US 11,909,729 B2**
(45) **Date of Patent:** **Feb. 20, 2024**

(54) **AUTO-FORM FILL BASED WEBSITE AUTHENTICATION**

(71) Applicant: **Google LLC**, Mountain View, CA (US)

(72) Inventors: **Clifton Kaznocha**, Mountain View, CA (US); **Erik Gustavson**, Los Angeles, CA (US); **Scott Kriz**, Manhattan Beach, CA (US)

(73) Assignee: **Google LLC**, Mountain View, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 630 days.

(21) Appl. No.: **17/049,126**

(22) PCT Filed: **Apr. 26, 2018**

(86) PCT No.: **PCT/US2018/029656**

§ 371 (c)(1),

(2) Date: **Oct. 20, 2020**

(87) PCT Pub. No.: **WO2019/209306**

PCT Pub. Date: **Oct. 31, 2019**

(65) **Prior Publication Data**

US 2021/0243174 A1 Aug. 5, 2021

(51) **Int. Cl.**

H04L 9/40 (2022.01)

G06F 16/955 (2019.01)

(52) **U.S. Cl.**

CPC **H04L 63/08** (2013.01); **G06F 16/955** (2019.01)

(58) **Field of Classification Search**

CPC ... H04L 63/08; H04L 63/0815; G06F 16/955; G06F 2221/2115; G06F 21/31; H04W 12/068

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,038,603 A * 3/2000 Joseph H04L 67/562
370/476
6,182,085 B1 * 1/2001 Eichstaedt G06F 16/951
707/999.102

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2003261124 A1 1/2004
CN 102968584 A 3/2013

(Continued)

OTHER PUBLICATIONS

International Search Report for the Application No. PCT/US2018/029656, dated Apr. 26, 2018, 13 pages.

(Continued)


Primary Examiner — Aravind K Moorthy

(74) *Attorney, Agent, or Firm* — Honigman LLP; Brett A. Krueger

(57) **ABSTRACT**

A method (400) for a website authentication is provided. The method includes receiving a reference uniform resource locator (URL) (130) at a browser (120) and determining whether the reference URL adheres to an authentication protocol (202) including a credential identifier (132c) and a web authentication host URL (132a). When the reference URL adheres to the authentication protocol, the method also includes extracting the credential identifier and the web authentication host URL from the reference URL. The method further includes obtaining credential data (160) from a remote service (150) using the credential identifier and sending web authentication instructions (170) to the browser. The web authentication instructions include the web authentication host URL and the credential data.

38 Claims, 14 Drawing Sheets



US 11,909,729 B2

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

6,557,038	B1 *	4/2003	Becker	H04L 67/14 709/227
6,587,880	B1 *	7/2003	Saigo	H04L 67/02 709/225
6,901,431	B1 *	5/2005	Dodrill	H04M 3/5307 704/E15.044
6,925,485	B1 *	8/2005	Wang	G06F 16/9574 709/202
6,996,718	B1 *	2/2006	Henry	G06F 21/41 713/184
7,003,576	B2 *	2/2006	Bjornestad	G09B 5/00 709/205
7,263,722	B1 *	8/2007	Luo	G06F 21/125 713/193
7,596,804	B2	9/2009	Toomey et al.	
7,603,320	B1 *	10/2009	Shu	G06Q 20/382 705/16
7,809,858	B1 *	10/2010	Brown	G06F 16/9566 709/245
8,438,631	B1 *	5/2013	Taylor	H04W 12/068 726/15
8,607,306	B1 *	12/2013	Bridge	H04L 67/02 726/1
8,677,115	B2	3/2014	Paris et al.	
8,954,004	B1 *	2/2015	Wang	G06F 21/41 455/410
9,001,370	B1 *	4/2015	Nuggehalli	G06F 21/31 358/1.15
9,053,297	B1 *	6/2015	Fitch	H04L 63/168
9,106,423	B1 *	8/2015	Salinas	G06F 21/41
9,111,074	B1 *	8/2015	Friedman	G06F 21/41
9,391,782	B1 *	7/2016	Mironenko	H04L 9/3247
9,473,380	B1 *	10/2016	Bermudez	G06F 16/80
9,703,802	B1 *	7/2017	Ward	G06F 16/182
9,961,070	B2 *	5/2018	Tang	H04L 63/123
9,967,236	B1 *	5/2018	Ashley	H04L 63/20
10,002,029	B1 *	6/2018	Bequet	G06F 16/9014
10,069,812	B1 *	9/2018	Moturu	H04L 67/02
10,454,897	B1 *	10/2019	Rajanna	H04L 63/0281
10,552,823	B1 *	2/2020	Woodward	G06Q 20/322
10,938,925	B1 *	3/2021	Fitzhugh	H04L 67/52
2002/0007460	A1 *	1/2002	Azuma	H04L 63/0884 709/229
2003/0056224	A1 *	3/2003	Stone	H04N 21/235 725/51
2003/0163691	A1 *	8/2003	Johnson	H04L 9/3297 713/168
2003/0204601	A1 *	10/2003	Takano	H04L 63/0281 709/227
2004/0019610	A1 *	1/2004	Burns	G06F 40/106
2004/0068584	A1 *	4/2004	Costa-Requena	H04L 65/1043 709/227
2004/0152448	A1 *	8/2004	Passi	H04L 63/08 455/411
2004/0158746	A1 *	8/2004	Hu	H04L 63/0815 726/8
2004/0230536	A1 *	11/2004	Fung	G06Q 20/382 705/64
2004/0250118	A1 *	12/2004	Andreev	H04L 63/0815 726/8
2005/0044380	A1 *	2/2005	Bostick	G06F 21/41 713/182
2005/0055398	A1 *	3/2005	Olson	H04L 9/40 709/200
2005/0108520	A1 *	5/2005	Yamamoto	G06F 21/35 726/4
2005/0188226	A1 *	8/2005	Kasatani	H04L 67/02 726/5
2005/0195446	A1 *	9/2005	Kasatani	H04N 1/00331 358/402
2005/0204173	A1 *	9/2005	Chang	H04L 9/3231 726/19
2005/0210031	A1 *	9/2005	Kasatani	H04N 1/0096
2005/0216582	A1	9/2005	Toomey et al.	
2006/0265279	A1 *	11/2006	Livingston	G06Q 30/02 705/14.63
2007/0038568	A1 *	2/2007	Greene	G06Q 40/08 705/50
2007/0104326	A1 *	5/2007	Feigenbaum	H04L 61/30 726/1
2007/0136413	A1 *	6/2007	Ishikawa	H04L 65/1104 709/200
2007/0180127	A1 *	8/2007	Vuori	H04L 67/303 709/227
2007/0226783	A1 *	9/2007	Mimlitsch	H04L 63/0815 726/4
2007/0244904	A1 *	10/2007	Durski	G06F 8/30
2008/0027914	A1 *	1/2008	Caputo	H04L 65/1069
2008/0031447	A1 *	2/2008	Geshwind	H04L 9/0822 713/168
2008/0127097	A1 *	5/2008	Zhao	G06F 11/3684 717/124
2008/0140861	A1 *	6/2008	Kothari	H04L 69/08 709/246
2008/0240490	A1 *	10/2008	Finkelstein	H04N 21/235 382/100
2008/0256087	A1 *	10/2008	Piironen	G06F 16/13
2008/0276098	A1 *	11/2008	Florencio	G06F 21/46 713/183
2009/0049533	A1 *	2/2009	Kim	H04L 63/08 726/7
2009/0144812	A1 *	6/2009	Sasamura	G06F 21/35 726/5
2009/0164447	A1 *	6/2009	Daya	G06F 21/6218 707/999.005
2009/0271371	A1 *	10/2009	Levin	G06F 16/29
2009/0328169	A1	12/2009	Hutchison et al.	
2010/0017616	A1 *	1/2010	Nichols	H04L 63/06 726/6
2010/0064355	A1	3/2010	Toomey et al.	
2010/0205053	A1 *	8/2010	Shuster	G06Q 20/385 705/40
2010/0223358	A1 *	9/2010	Schneider	G06F 21/83 709/219
2010/0241865	A1 *	9/2010	Chang	H04L 63/1483 713/184
2011/0055250	A1 *	3/2011	Nandy	G06F 16/248 715/810
2011/0161510	A1 *	6/2011	Arnold	H04L 63/10 709/229
2011/0207433	A1 *	8/2011	Miyamoto	G06F 21/41 455/411
2011/0276414	A1 *	11/2011	Subbarao	G06Q 20/102 705/40
2011/0314532	A1 *	12/2011	Austin	H04L 63/0892 726/8
2011/0321141	A1 *	12/2011	Zeng	H04L 63/0853 726/5
2012/0252405	A1 *	10/2012	Lortz	H04W 4/50 455/410
2012/0297190	A1 *	11/2012	Shen	H04L 9/0866 713/168
2013/0085906	A1 *	4/2013	Cottingham	G06Q 10/10 705/30
2013/0104202	A1 *	4/2013	Yin	G06F 21/42 726/5
2013/0124687	A1 *	5/2013	Nam	H04L 63/1483 709/218
2013/0132817	A1 *	5/2013	Sharad	G06F 40/186 715/234
2013/0159840	A1 *	6/2013	Nicolaescu	G06F 40/186 715/235
2013/0173964	A1 *	7/2013	Okano	G06F 11/079 714/48
2013/0179005	A1 *	7/2013	Nishimoto	B60R 25/1001 701/2

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0246528 A1 *

9/2013

Ogura

H04L 67/563

709/204

2014/0033273 A1 *

1/2014

Rathbun

H04L 63/08

726/3

2014/0165165 A1 *

6/2014

Story, Jr.

H04W 12/0431

726/6

2014/0259105 A1 *

9/2014

Alibakhsh

H04L 63/08

726/3

2014/0310808 A1 *

10/2014

Yao

G06F 21/57

726/22

2014/0333713 A1 *

11/2014

Shoemake

H04L 65/403

348/14.05

2015/0007278 A1 *

1/2015

Benezra

G06F 21/31

726/5

2015/0020178 A1 *

1/2015

Grunin

H04L 63/08

726/7

2015/0096001 A1 *

4/2015

Morikuni

H04L 63/123

726/7

2015/0113626 A1 *

4/2015

Bocanegra Alvarez

H04L 63/0815

726/8

2015/0121482 A1 *

4/2015

Berman

H04L 63/10

726/5

2015/0207660 A1 *

7/2015

Sundaram

H04L 67/02

709/203

2015/0281227 A1 *

10/2015

Fox Ivey

H04L 9/3226

713/168

2015/0281229 A1 *

10/2015

Kang

H04L 63/0869

713/185

2015/0350186 A1 *

12/2015

Chan

H04L 63/0815

726/9

2016/0124782 A1 *

5/2016

Gruby

G06F 9/546

719/313

2016/0156719 A1 *

6/2016

Mobarak

H04L 67/141

726/4

2016/0191564 A1 *

6/2016

Liu

H04L 63/0227

726/11

2016/0191970 A1 *

6/2016

Sheppard

H04N 21/252

725/14

2016/0212113 A1 *

7/2016

Banerjee

H04W 12/06

2017/0048245 A1 *

2/2017

Owen

G06F 16/951

2017/0118215 A1 *

4/2017

Varadarajan

H04L 63/10

2017/0147826 A1 *

5/2017

Farkash

H04L 9/3263

2017/0195319 A1 *

7/2017

Gerber

G06Q 20/34

2017/0199872 A1 *

7/2017

Krasadakis

G06F 16/787

2017/0213206 A1 *

7/2017

Shearer

G06Q 20/3278

2017/0237726 A1 *

8/2017

Wang

H04W 12/06

726/7

2017/0244672 A1 *

8/2017

Shulman

H04L 61/5007

2017/0250998 A1 *

8/2017

Miliefsky

H04L 63/02

2017/0251002 A1 *

8/2017

Rostamabadi

G06F 21/566

2017/0346830 A1 *

11/2017

Goldfarb

H04L 67/01

2017/0366547 A1 *

12/2017

Goldfarb

H04L 63/10

2018/0075231 A1 *

3/2018

Subramanian

H04L 63/0807

2018/0124068 A1 *

5/2018

Ruhlen

H04L 67/60

2018/0316510 A1 *

11/2018

Rai

H04L 9/3268

2018/0332042 A1 *

11/2018

Yu

H04L 51/02

2019/0026456 A1 *

1/2019

Hon

G06F 21/40

2019/0147178 A1 *

5/2019

Baldwin

H04L 51/52

726/28

2019/0197747 A1 *

6/2019

Garcia

G06V 20/20

2019/0213553 A1 *

7/2019

Ragsdale

H04L 51/00

2019/0215375 A1 *

7/2019

Ragsdale

H04L 9/0894

FOREIGN PATENT DOCUMENTS

CN

103646081 A

3/2014

CN

104270404 A

1/2015

CN

106961415 A

7/2017

TW

201206138 A

2/2012

WO

2004006499 A1

1/2004

WO

WO-2005022893 A2 *

3/2005

H04L 61/2015

OTHER PUBLICATIONS

Indian Examination Report for the related Application No. 202047046545, dated Sep. 16, 2021, 6 pages.

China National Intellectual Property Administration. Office Action relating to Application No. 201880092757.4, dated May 6, 2022.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B





FIG. 2C






FIG. 2E




FIG. 2F




FIG. 3A

300b




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4




FIG. 5




FIG. 6

1

**AUTO-FORM FILL BASED WEBSITE
AUTHENTICATION**

TECHNICAL FIELD

This disclosure relates to auto-form fill based website authentication.

BACKGROUND

With the vast amount of computing resources today, users, owners, and administrators of resources often limit or restrict resource access. For these restrictions, it is commonplace to use credentials to verify and authenticate identities of entities who are attempting to access the resources. Thus, credentials have become an integral part of resource access. This is especially true for larger computing environments (cloud service environments and distributed systems) that have shared resources among numerous users. With the ever-increasing use of credentials, entities having access rights to resources with credentials, spend time managing, organizing, and submitting credentials.

SUMMARY

One aspect of the disclosure provides a method for website authentication. The method includes receiving, at data processing hardware, a reference uniform resource locator (URL) at a browser and determining, by the data processing hardware, whether the reference URL adheres to an authentication protocol including a credential identifier and a web authentication host URL. When the reference URL adheres to the authentication protocol, the method also includes extracting, by the data processing hardware, the credential identifier and the web authentication host URL from the reference URL, obtaining, by the data processing hardware, credential data from a remote service using the credential identifier, and sending web authentication instructions to the browser. The web authentication instructions include the web authentication host URL and the credential data.

Implementations of the disclosure may include one or more of the following optional features. In some implementations, the reference URL adheres to either the authentication protocol or a Hypertext Transfer Protocol (HTTP). The credential data may include a username and a password. The authentication protocol may include a user identifier. When the authentication protocol includes a user identifier, the user identifier and the credential identifier may include object identifiers. The object identifiers are configured to publically obfuscate an identity of a user associated with the user identifier and a credential associated with the credential identifier. Additionally or alternatively, the authentication protocol may include a user identifier combined with the credential identifier as a single identifier.

In some examples, the web authentication instructions configure the browser to auto-populate a login form at the web authentication host URL using the credential data based on the web authentication instructions. The web authentication instructions may include a login URL and may configure the browser to: execute the login URL, the login URL navigating to a login page associated with the web authentication host URL; determine login fields by parsing a document object model of the login page; populate the login fields using the credential data based on the web authentication instructions, and redirect the browser to the web authentication host URL. The authentication protocol may

2

also include a custom protocol identifier. Optionally, the authentication protocol may include a format of web+credential://{Credential ID}/{Web Host}.

Another aspect of the disclosure provides a method for website authentication. The method includes receiving, at data processing hardware, references to web resources, a first reference having a first protocol formatting, the remaining references having a second protocol formatting. The method also includes identifying, by the data processing hardware, the first reference as having the first protocol formatting and executing, by the data processing hardware, an automated website login routine using the first reference. The automated website login routine is configured to extract a credential identifier and a web host identifier from the first reference and obtain credential data corresponding to the credential identifier. The credential data includes a user credential. The automated website login routine is also configured to obtain a uniform resource locator (URL) for a login page corresponding to the web host identifier and automatically log into the login page corresponding to the web host identifier using the user credential.

This aspect may include one or more of the following optional features. In some configurations, automatically logging into the login page includes parsing a document object model (DOM) of the login page to identify a username field and a password field, inserting a user name of the user credential into the username field, and inserting a password of the user credential into the password field. The first protocol formatting may include web+credential://{User OID}:{Credential OID}@{Web App Host}/.

In some implementations, the method includes receiving, at the data processing hardware, a format of web+credential://{Web App Host}/ as the first reference. Here, the method also includes identifying, by the data processing hardware, the format of web+credential://{Web App Host}/ as an incomplete first protocol formatting. In this implementation, the automated website login routine is configured to extract the web host identifier from the first reference, obtain the uniform resource locator (URL) for the login page corresponding to the web host identifier, and display the login page corresponding to the web host identifier in response to the received references including the format of web+credential://{Web App Host}/ as the first reference.

In some examples, receiving references to web resources includes a uniform resource locator (URL). The first protocol formatting may include a custom protocol identifier. The user credential identifier may include a user identifier and a credential identifier. Optionally, the method may include redirecting, by the data processing hardware, to the web resources of the received references. When the user credential identifier includes an object identifier, the object identifier may be configured to publically obfuscate an identity of a user associated with the user credential identifier. The user credential may include a username and a password.

Another aspect of the disclosure provides a system for website authentication. The system includes data processing hardware and memory hardware in communication with the data processing hardware. The memory hardware stores instructions that when executed by the data processing hardware cause the data processing hardware to perform operations. The operations include receiving a reference uniform resource locator (URL) at a browser and determining whether the reference URL adheres to an authentication protocol including a credential identifier and a web authentication host URL. When the reference URL adheres to the authentication protocol, the operations also include extracting the credential identifier and the web authentication host

URL from the reference URL, obtaining credential data from a remote service using the credential identifier, and sending web authentication instructions to the browser. The web authentication instructions include the web authentication host URL and the credential data.

Implementations of this system may include one or more of the following optional features. In some implementations, the reference URL adheres to either the authentication protocol or a Hypertext Transfer Protocol (HTTP). The credential data may include a username and a password. The authentication protocol may include a user identifier. When the authentication protocol includes a user identifier, the user identifier and the credential identifier may include object identifiers. The object identifiers are configured to publically obfuscate an identity of a user associated with the user identifier and a credential associated with the credential identifier. Additionally or alternatively, the authentication protocol may include a user identifier combined with the credential identifier as a single identifier.

In some examples, the web authentication instructions configure the browser to auto-populate a login form at the web authentication host URL using the credential data based on the web authentication instructions. The web authentication instructions may include a login URL and may configure the browser to: execute the login URL, the login URL navigating to a login page associated with the web authentication host URL, determine login fields by parsing a document object model of the login page; populate the login fields using the credential data based on the web authentication instructions; and redirect the browser to the web authentication host URL. The authentication protocol may also include a custom protocol identifier. Optionally, the authentication protocol may include a format of web+credential://{Credential ID}@{Web Host}.

Yet another aspect of the disclosure provides a system for website authentication. The system includes data processing hardware and memory hardware in communication with the data processing hardware. The memory hardware stores instructions that when executed by the data processing hardware cause the data processing hardware to perform operations. The operations include receiving references to web resources. A first reference has a first protocol formatting and the remaining references have a second protocol formatting. The operations also include identifying the first reference as having the first protocol formatting and executing an automated website login routine using the first reference. The automated website login routine is configured to extract a credential identifier and a web host identifier from the first reference and obtain credential data corresponding to the credential identifier. The credential data includes a user credential. The automated website login routine is also configured to obtain a uniform resource locator (URL) for a login page corresponding to the web host identifier and automatically log into the login page corresponding to the web host identifier using the user credential.

This aspect may include one or more of the following optional features. In some configurations, automatically logging into the login page includes parsing a document object model (DOM) of the login page to identify a username field and a password field, inserting a user name of the user credential into the username field, and inserting a password of the user credential into the password field. The first protocol formatting may include web+credential://{User OID}:{Credential OID}@{Web App Host}/.

In some implementations, the operations include receiving a format of web+credential://{Web App Host}/ as the

first reference. Here, the operations also include identifying the format of web+credential://{Web App Host}/ as an incomplete first protocol formatting. In this implementation, the automated website login routine is configured to extract the web host identifier from the first reference, obtain the uniform resource locator (URL) for the login page corresponding to the web host identifier, and display the login page corresponding to the web host identifier in response to the received references including the format of web+credential://{Web App Host}/ as the first reference.

In some examples, receiving references to web resources includes a uniform resource locator (URL). The first protocol formatting may include a custom protocol identifier. The user credential identifier may include a user identifier and a credential identifier. Optionally, the operations may include redirecting to the web resources of the received references. When the user credential identifier includes an object identifier, the object identifier may be configured to publically obfuscate an identity of a user associated with the user credential identifier. The user credential may include a username and a password.

The details of one or more implementations of the disclosure are set forth in the accompanying drawings and the description below. Other aspects, features, and advantages will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

FIG. 1 is a schematic view of an example authentication environment.

FIGS. 2A-2F are schematic views of example authentication managers interacting within the authentication environment.

FIG. 3A is a schematic view of an example authentication manager webpage for the authentication manager.

FIG. 3B is a schematic view of an example authentication manager as a browser extension.

FIGS. 3C and 3D are schematic views of example login routines of an authentication manager at a web browser.

FIG. 4 is a flowchart of an example method for providing website authentication.

FIG. 5 is a flowchart of an example method for providing website authentication.

FIG. 6 is a schematic view of an example computing device that may be used to implement the systems and methods described herein.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

An authentication manager is a tool to simplify credential management for a user and/or browser. For example, there are webpages that the user often visits that request a login for each visit. Each login requires a user time to complete the login process. As resources become more accessible via webpages and/or as resources increase security procedures requiring security credentials, more webpages that the user encounters request login credentials to authenticate the user. In these situations, the user may be left managing credentials across many webpages as well as spending time entering and submitting credentials to authenticate the user's permission to access each webpage. Therefore, in some capacity, the authentication manager provides an efficient and reliable

5

authentication process for the user as an intermediary between authentication credentials of the user and a resource such as a webpage.

Implementations herein further solve the technical problem of how to create a secure and a reliable credential management system to access resources with automated authentication by the technical solution that includes a browser extension and/or a central credential management webpage. Here, both the browser extension and the central credential management webpage allow for custom uniform resource locator (URL) protocols to access web resources requiring a user authentication via a login. The browser extension intercepts or otherwise observes the URL navigation at a browser. The custom URL includes a format that identifies the customer protocol, a host of the web resource, and a user credential for authenticating the user to access the web resource. The custom URL permits transparency such that the user knows authentication will occur when navigating to the custom URL, as well as security since the URL does not itself reveal or expose the actual credential or identity of the user. Based on the resource host and credential identifier information, the authentication manager (e.g. a password management system, which may or may not be remotely located) provides the user credential with data such that the browser extension or central webpage may initiate the automated authentication of the user. For example, the browser extension may pass the user credential data to a web browser (or other application through which the URL has been accessed, selected, or input) for auto-filling user login fields required for accessing the web resource of interest.

FIG. 1 is an example of an authentication environment 100. The authentication environment 100 generally includes a user device 110 associated with a user 10 communicating, via a browser 120 over a network 140, with remote services 150. The remote services 150 may be located within a distributed system (e.g., a cloud environment) having scalable/elastic resources 152. The resources 152 include computing resources 154 (e.g., data processing hardware) and/or storage resources 156 (e.g., memory hardware). In other examples, the remote services 150 communicate with a distributed system.

In some examples, the user 10 interfaces with the resources 152 (e.g., web resources) via the web browser 120. The web browser 120 is a program configured to access these resources 152 and display these resources 152 through a webpage 124. A webpage 124 generally refers to a presentation of resources 152 in a document with elements such as style sheets, scripts, images, etc. A webpage 124 may be static or dynamic such that it may include web hosted applications 155. A web hosted application 155 refers to a program hosted on a server that a web browser 120 may access via the network 140. For example, a webpage 124 corresponds to a web hosted application 155 located on a server of the distributed system (i.e., executing on computing resources 154) in communication with the web browser 120 over the network 140. These web hosted applications 155 may also execute on other computing resources separate from the remote service 150.

In some implementations, access to a resource 152 through a webpage 124 requires authentication of the user 10. In other words, the user 10 may only access the resource 152 once the user 10 is authenticated as having permission to access the resource 152. A common method of authentication for a web resource 152 is a login prompt on a webpage 124, such as a login page 124a. Once the user 10 logs into the webpage 124, the user 10 may proceed to a home page 124b. In some examples, to login to a webpage

6

124, a remote service 150 provides credential data 160 for the user 10 to access the web resource 152 via the browser 120. For example, the user 10 uses credential data 160 as a form of authentication to login to the webpage 124. In some examples, the authentication environment 100 includes an authentication manager 200 for managing the authentication process for the user 10 to login to webpages 124.

The user device 110 can be any computing devices or data processing hardware capable of communicating with remote services 150 via the browser 120. With continued reference to FIG. 1, the user device 110 includes data processing hardware 112 and memory hardware 114. The user device 110, includes, but is not limited to, desktop computing devices and mobile computing devices, such as laptops, tablets, smart phones, and wearable computing devices (e.g., headsets and/or watches). The user device 110 is configured such that the user 10 views webpages 124 using the browser 120 executing on the user device 110 (e.g., via a display of the user device 110).

The user device 110 may download a browser 120, such as CHROME®, FIREFOX®, OPERA®, EXPLORER®, etc. to the memory hardware 114 and execute the browser 120 on the data processing hardware 112 when the user 10 decides to use the web browser 120. The web browser (also referred to as “browser”) 120 includes an address field 122 for receiving references R to web resources 152. The reference R generally conveys to the browser 120 a destination, such as a webpage 124, that the user 10 wants to access. The browser 120 uses the reference R entered by the user 10 into the address field 122 to navigate to the destination webpage 124. The browser 120 may receive the reference R directly or indirectly from the user 10. For example, the browser 120 may receive the reference R directly from the user 10 via a user input, such as typing the reference R (e.g., URL 130) into the address field 122 of the web browser 120 or via a speech input. In other examples, the browser 120 receives the reference R indirectly from the user 10 when the user 10 selects a hyperlink associated with the reference R that auto-populates the address field 122. The user 10 may select the hyperlink of the reference R by selecting an object or an icon embedding the hyperlink.

To achieve standardization for referencing web resources 152, references R often include a format 132 that the browser 120 can interpret to understand how and/or where to navigate for the desired web resource(s) 152. In some examples, the reference R to the web resource(s) 152 is a uniform resource identifier (URI) such as a uniform resource locator (URL) 130. The URL 130 has a format 132 that indicates a name of a resource and a protocol used to fetch the resource. As a basic example, the URL 130, <http://patent.com>, has a protocol of “http” and a resource name of “patent.com.” The protocol of “http” indicates to the browser 120 to use the Hypertext Transfer Protocol (HTTP) to access the “patent.com” resource. Although HTTP and HTTPS (Hypertext Transfer Protocol Secure) are two commonly used protocols to navigate to web resources, other protocols exist (e.g., file transfer protocol (FTP), internet message access protocol (IMAP), internet printing protocol (IPP), etc.) or may be created (e.g., custom protocols) to configure how the browser 120 fetches the resource 152.

As with the browser 120, the authentication manager 200 is configured to interpret a reference R such as a URL 130. This interpretation determines whether the reference R refers to a resource 152 whose access requests some degree of authentication. To make this determination, the authentication manager 200 is configured to use the format 132 of the URL 130. Based on how the authentication manager 200

interprets the format **132**, the authentication manager **200** may authenticate the user **10** to access the requested resource **152**. In some examples, the authentication manager **200** authenticates the user **10** by providing authentication credentials (e.g., credential data **160**) to a webpage **124** requesting authentication. Additionally or alternatively, the authentication manager **200** authenticates the user **10** by submitting the authentication credentials **160** to a webpage **124**, such as a login webpage **124a**, associated with the reference URL **130** and redirecting the browser **120** to the reference URL **130**.

In some examples, the authentication manager **200** interprets the format **132** of a reference R such as a URL **130** by determining whether the format **132** of the reference URL **130** adheres to an authentication protocol **202**. The authentication protocol **202** generally refers to a reference format configured by the authentication manager **200**. The authentication protocol **202** may be pre-programmed by a developer or administrator of the authentication manager **200** or configured by the user **10**. In some implementations, updates or development of a browser **120** communicating with the authentication manager **200** also update or modify the authentication protocol **202**. In this respect the authentication protocol **202** may be static or dynamic.

The format **132** of a reference (e.g., URL **130**) may include identifiers recognizable by the browser **120** and/or the authentication manager **200**. The format **132** may refer to the identifiers. The identifiers may be any combination of syntax characters designated as an element of an authentication protocol **202** by the authentication manager **200**. For example, with respect to a reference URL **130**, these characters correspond to valid URL characters. The browser **120** and/or authentication manager **200** may be configured to recognize different combinations of identifiers to detect that the user **10** is navigating to a webpage **124** that requests authentication. The webpage **124** that requests authentication includes a web authentication host reference, such as a web authentication host URL **132**, **132a**. Some examples of identifiers within the format **132** include a protocol identifier **132**, **132b**, a credential identifier **132**, **132c**, and a user identifier **132**, **132d** (FIG. 2B). Depending on the configuration, the authentication protocol **202** may combine or include additional identifiers and still detect that the user **10** is navigating to a webpage **124** that requests authentication. In some examples, the authentication protocol **202** combines the credential identifier **132c** and the user identifier **132d** into a single identifier, such as a user credential identifier **132**, **132e** (e.g., FIG. 2C). In some implementations, identifiers are configured to publically obfuscate an identity of the user **10** navigating with a reference URL **130** having the authentication protocol **202**. For example, the user identifier **132d** and/or credential identifier **132c** include object identifiers (OIDs), such as a unique string of character or numbers.

In some implementations, the authentication protocol **202** refers to a format **132** that includes a web authentication host URL **132**, **132a** and a credential identifier **132**, **132c**. When the authentication manager **200** receives a reference URL **130** that adheres to the authentication protocol **202** with a respective web authentication host URL **132a** and a respective credential identifier **132**, **132c**, the authentication manager **200** is configured to extract the web authentication host URL **132**, **132a** and the credential identifier **132**, **132c** from the reference URL **130**. With the extracted credential identifier **132c**, the authentication manager **200** obtains credential data **160** based on the credential identifier **132c** from the remote service **150**. The authentication manager **200** incor-

porates the obtained credential data **160** along with the web authentication host URL **132a** into web authentication instructions **170**. The authentication manager **200** sends the web authentication instructions **170** to the browser **120** to authenticate the user **10** (e.g., at the web authentication host URL **132a**).

The credential data **160** refers to a type of digital verification to indicate an identity (e.g., the identity of the user **10**). In some configurations, the credential data **160** includes credentials **162** and data related to credentials **162**. Resources such as webpages **124** use credential data **160** to indicate that the identity has permission to access content of the webpage **124**. Yet the degree of complexity of the credential data **160** may vary. In other words, credential data **160** and/or credentials **162** may provide evidence as to an identity's authority, status, rights, privileges, etc with respect to the webpage **124**. For example, the credential data **160** includes credentials **162** such as a username **162a** (FIG. 2A) and a password **162b** (FIG. 2A) corresponding to the user **10**. Another example of a credential **162** is an access key such as a unique link (e.g., a unique URL) to reference the webpage **124**. Additionally or alternatively, the credential data **160** may be any data corresponding to the user **10** that may authenticate an identity of the user **10** such as personal questions (e.g., about banking, residencies, employers, education, etc.), digital certificates, digital signatures, or digital representations of user biometrics.

A credential identifier **132c** generally refers to a syntax of characters that may be interpreted (e.g., by the authentication manager **200**) to identify credentials **162** and/or credential data **160**. In some examples, credential identifiers **132c** are used in context with other identifiers (e.g., user identifiers **132d**) or other portions of a reference R to a resource (e.g., a web authentication host URL **132a**) to identify credentials **162** and/or credential data **160**. In some implementations, credential identifiers **132c** refer to a location that stores credential data **160**.

FIGS. 2A-2F are examples of the authentication manager **200**. The authentication manager **200** includes an observer **210**, an extractor **220**, and an obtainer **230**. The observer **210** is configured to identify the authentication protocol **202** of the authentication manager **200**. As the authentication manager **200** receives a reference URL **130**, the observer **210** inspects each reference URL **130** to determine whether the reference URL **130** has a respective format **132** that adheres to the authentication protocol **202**. For example, the observer **210** receives each reference URL **130** when the address field **122** of the browser **120** receives a URL **130** from the user **10**. When the observer **210** encounters a reference URL **130** with the authentication protocol **202**, the observer **210** communicates that reference URL **130** to the extractor **220**. Generally, the format **132** of the reference URL, **130** adheres to the authentication protocol **202** when the format **132** includes elements (e.g., identifiers) that correlate to elements of the authentication protocol **202**.

Additionally or alternatively, the observer **210** may be configured to identify part or all of the authentication protocol **202** within the reference URL **130**. For example, the observer **210**, instead of identifying each identifier within a received reference URL **130**, may be configured to identify whether a particular identifier **132** (e.g., protocol identifier **132b**, credential identifier **132c**, or user identifier **132d**) exists within the received reference URL **130**. Moreover, the observer **210** may communicate the reference URL **130** to the extractor **220** when the observer **210** identifies that a reference URL **130** includes the customer protocol identifier **132b**. By identifying a particular identifier **132**, the

authentication manager 200 reduces processing time at the obtainer 230 to allow the authentication manager 200 to more efficiently detect webpages 124 with authentication without compromising navigation speed of the browser 120.

In some implementations, the observer 210 is configured to identify when reference URLs 130 include web authentication host URLs 132a. In these implementations, when the observer 210 identifies a reference URL 130 with the web authentication host URL 132a, the observer 210 communicates the reference URL 130 to the extractor 220. In order to identify a web authentication host URL 132a, in some examples, the authentication manager 200 stores a list of web authentication host URLs 132a that the observer 210 references as the observer 210 receives reference URLs 130. As the user 10 acquires credential data 160 for various web pages 124, the user 10 may store the credential data 160 with the associated web authentication host URL 132a in a credential database (e.g., storage resource 156) accessible to the authentication manager 200. As the credential database (e.g., storage resource 156) is accessible to the authentication manager 200, the observer 210 may reference an up-to-date list of web authentication host URLs 132a.

The extractor 220 receives the reference URL 130 from the observer 210 and is configured to extract identifiers from the received reference URL 130. FIGS. 2A-2E depict examples of different representations of reference URLs 130 received by the extractor 220. Here, the braces within the examples of different reference URLs 130 may be replaced with actual data (e.g., various characters). Even though the extractor 220 may be configured to extract any combination of identifiers and to communicate the extracted identifier to the obtainer 230, the extractor 220 is generally configured to extract the credential identifier 132c from the received reference URL 130 to allow the authentication manager 200 to efficiently retrieve credential data 160 associated with the credential identifier 132c. FIGS. 2A-2F depict the extractor 220 parsing the received reference URL 130 for illustration to show the different identifiers included in the format 132 of a reference URL 130 received from the observer 210. In other words, the extractor 220 may simply extract the credential identifier 132c rather than parsing the format 132 into identifiers. As used herein, the format 132 may refer to a collection of one or more identifiers. With the extracted credential identifier 132c, the extractor 220 communicates the credential identifier 132c to the obtainer 230.

FIG. 2A is a generic example of the reference URL 130 with a representative format 132 of "ProtocolIdentifier://{Credential Identifier}@{Web App Host}/" having at least a protocol identifier 132b, a web authentication host URL 132a, and a credential identifier 132c. FIG. 2B is an example where the authentication protocol 202 corresponds to a custom protocol where a reference URL 130 has a representative format 132 of "web+credential://{User OID}:{Credential OID}@{Web App Host}/" Here, the representative format 132 has at least a custom protocol identifier 132b, a web authentication host URL 132a, a credential identifier 132c, and a user identifier 132d. As shown in FIG. 2B, the credential identifier 132c and the user identifier 132d may be object identifiers (OIDs). FIG. 2C is an example similar to FIG. 2B except that the representative format 132 of the reference URL 130 combines the credential identifier 132c and the user identifier 132d into a user credential identifier 132e.

FIG. 2D illustrates an example that the authentication protocol 202 may be associated with HTTP or HTTPS. In this example, the reference URL 130 has a format 132 of "https://www.patent.com/#auto_login={Credential OID}"

where "https" is the protocol identifier 132b, "www.patent.com" is the web authentication host URL 132a, and a hash character indicates {Credential OID} as the credential identifier 132c. With a format such as HTTP or HTTPS, the authentication protocol 202 uses existing protocols by appending login information to a hash portion of a respective URL 130. This may be advantageous with current URLs 130, but may cause the authentication manager 200 to parse through more portions of the URL 130 with less uniformity when compared to, for example, a custom protocol identifier 132b for the authentication protocol 202.

FIG. 2E is an example where the extractor 220 fails to receive the reference URL 130 from the observer 210 and thus does not perform extraction. In this example, the observer 210 recognizes that the reference URL 130 has a format 132 that does not adhere the authentication protocol 202 of "web+credential." Rather, the reference URL 130 as "https://www.google.com/search?q=fighting+illini+win+2008+ncaa" has a format 132 with a http protocol identifier 132b and no credential identifier 132c. Based on this recognition, the observer 210 does not communicate the reference URL 130 to the extractor 220.

With reference to FIGS. 2A-2D and 2F, the obtainer 230 is configured to use the credential identifier 132c from the extractor 220 to obtain credential data 160 for the reference URL 130. In other words, the obtainer 230 allows the authentication manager 200 to gather raw data requested by the webpage 124 to perform a login indicated by information within the reference URL 130. When the observer 210 identifies a reference URL 130 that adheres to a format 132 of the authentication protocol 202 and the extractor 220 extracts the credential identifier 132c within the reference URL 130, the obtainer 230 uses the credential identifier 132c to retrieve relevant credential data 160 from the remote service 150. In some examples, the credential identifier 132c indicates one or more locations from where the remote service 150 provides credential data 160 relating to the credential identifier 132c. For example, the credential identifier 132c refers a resource within the remote service 150 that stores the credential data 160. In some examples, the obtainer 230 calls on the remote service 150 to provide the related credential data 160. In other examples, the obtainer 230 retrieves the credential data 160 from the remote service 150 based on the credential identifier 132c. In the examples shown, the obtainer 230 receives a username 162a and a password 162b as credential data 160 based on the credential identifier 132c. Referring to FIG. 2F, the obtained credential data 160 may also include a login URL 162c associated with other credential data 160, such as the username 160a and password 162b. In some examples, the obtainer 230 determines the login URL 162c based on the web authentication host URL 132a. In other examples, when the user 10 or the authentication manager 200 creates authentication credentials associated with a web authentication host URL 132a, the authentication credentials generate and/or store the login URL 162c as credential data 160.

The example authentication manager 200 of FIGS. 2A-2F sends web authentication instructions 170 including the credential data 160 and the web authentication host URL 132a. In some examples, the authentication manager sends the web authentication instructions 170 to the browser 120. The web authentication instructions 170 when received by the browser 120, may cause the browser 120 to execute the instructions 170 to login to the web authentication host URL 132a with the credential data 160.

Referring to FIG. 2F, the authentication manager 200 may additionally include an auto-filler 240. The auto-filler 240

11

receives the web authentication instructions 170 and is configured to auto-populate a login form at the web authentication host URL 132a. For example, a webpage 124 such as a login page 124a or a home page 124b includes the login form 125. In some examples (as indicated by the dashed box in FIG. 2F), the auto-filler 240 accesses a document object model (DOM) 241 associated with the web authentication host URL 132a to perform auto-population of the login form 125. When the auto-filler 240 populates the login form 125, the auto-filler 240 uses the credential data 160 based on the web authentication instructions 170. In some examples, the login form 125 includes a username field U_F and a password field P_F , but may include other fields depending on a design of the login form 125 for the webpage 124. As depicted in the example FIG. 2F, the auto-filler 240 executes the web authentication instructions 170 to navigate to the browser 120 to the login URL 162c and populates the username field U_F and the password field P_F located on the login URL 162c with the username 162a and password 162b of the credential data 160 within the web authentication instructions 170. When the login form 125 includes other fields in addition to, or in lieu of, the username field U_F and the password field P_F , the auto-filler 240 is configured to communicate with the obtainer 230 to ensure the obtainer 230 provides relevant credential data 160 for the auto-filler 240 to populate the additional fields in login form 125.

In some implementations, the auto-filler 240 authenticates the user 10 by auto-filling the login URL 162c. In these implementations, when the auto-filler 240 fills in the login form 125 of the associated login URL 162c, the auto-filler 240 redirects the browser to the web authentication host URL 132a. To redirect the web authentication host URL 132a, the auto-filler 240 navigates the browser 120 from the login URL 162c provided within the instructions 170 to the web authentication host URL 132a provided by the authentication manager 200. By auto-filling the login page 124a of the login URL 162c and redirecting to the web authentication host URL 132a, the authentication manager 200 prevents the user 10 from having to spend time filling in each field of the login form 125 with credential data 160 or having to navigate back to the web authentication host URL 132a. In some examples, the authentication manager 200 recognizes that the user 10 originally attempted to navigate to a webpage 124 associated with the web authentication host URL 132a and instead redirects the browser 120 to the webpage 124 of the original navigation attempt. For example, the user 10 originally attempted to navigate to a webpage “www.patents.com/US4722098A,” and, in response to the attempt, the authentication manager 200 (1) logs the user 10 into the login URL 162c associated with the webpage “www.patents.com/US4722098A,” and (2) redirects the user 10 to the webpage 124 corresponding to the file “U.S. Pat. No. 4,722,098” within the web authentication host URL “www.patents.com.”

In some examples, the authentication manager 200 prompts the user 10 by asking whether the user 10 wants to auto-populate a respective web authentication host URL 132a. When the user 10 answers affirmatively, the authentication manager 200 activates the auto-filler 240 to fill-in login fields of the login form 125 associated with the respective web authentication host URL 132a. In some cases, the authentication manager 200 allows the user 10 to configure one or more settings. In these cases, the settings may include an option to toggle the auto-filler 240 on or off universally for all web authentication host URLs 132a or for a particular web authentication host URL 132a.

12

Referring back to FIG. 1, the dashed box associated with the authentication manager 200 indicates that the location of the authentication manager 200 within the authentication environment 100 may vary for different applications. For examples, schematic views 300a, 300b of FIGS. 3A and 3B show examples where the authentication manager 200 includes a web application 200a (FIG. 3A) or a browser extension 200b (FIG. 3B). Referring to FIG. 3A, the remote service 150 may host the web application 200, 200a such that the authentication manager 200 is accessible to, yet separate from, the user device 110. In other words, the web application 200, 200a is hosted on a remote server rather than on the user device 110. The web application 200, 200a includes an application manager webpage 250 with an authentication manager URL 252. The user 10 may navigate to the application manager webpage 250 via the authentication manager URL 252. The application manager webpage 250 functions as a central hub for the authentication manager 200. For example, the application manager webpage 250 displays a list 254 of stored web authentication host URLs 256, 256a-n. Each stored web authentication host URL 256 may include the credential data 160 associated with the stored web authentication host URL 256.

In some implementations, the application manager webpage 250 displays each stored web authentication host URL 256 as an icon with a hyperlink. When the user 10 selects the icon, the hyperlink may execute the web authentication instructions 170 and/or initiate the auto-filler 240 of the authentication manager 200 to execute the web authentication instructions 170 for the selected icon. In some implementations, the hyperlink associated with the stored web authentication host URL 256 allows the user 10 to conveniently share the hyperlink to permit another user to login to a webpage 124 related to the stored web authentication host URL 256. The user 10 may also bookmark the hyperlink to quickly access the webpage 124 at a later time. Another advantage of the web application 200, 200a of the authentication manager 200 is that the web application 200, 200a may be accessible across multiple user devices 110 as long as each user device 110 has web access.

FIG. 3B shows the authentication manager 200 as a browser extension 200, 200b, such as a plug-in. Generally, browser extensions customize the functionality of a web browser 120. These browser extensions are commonly built with web programming languages such as HTML, JavaScript, CSS or developed in conjunction with application programming interfaces (APIs). These extensions may be downloaded to hardware of the user device 110 (e.g., downloaded by data processing hardware 112 and stored in memory hardware 114) or hosted by a web provider. Some examples of known extensions include ad blockers, print shortcuts, download managers, translators, privacy features, and browser history organizers. In some implementations, the browser extension 200, 200b is configured to access a document object model (DOM) 241 (FIG. 2F) of a webpage 124 to modify the webpage 124. For example, by accessing the DOM 241, the authentication manager 200 logs into a webpage 124 requesting a login. In some examples, the browser extension 200b is automatically tied into the address field 122 of the browser 120. In other words, when the browser 120 receives a reference R, such as a URL 130 (e.g., at the address field), the reference R is also received by the browser extension 200b.

FIGS. 3C and 3D illustrate schematic views 300c, 300d depicting examples of the browser extension 200b. In these examples, the authentication manager 200 subdivides the format 132 of the reference R (e.g., a URL 130) into multiple

13

references (e.g., a first reference R_1 and a second reference R_2). Here, the authentication manager **200** identifies the first reference R_1 as a first protocol formatting F_1 and the remaining portion of the reference R , the second reference R_2 , as a second protocol formatting F_2 . Based on the first protocol formatting F_1 , the browser extension **200**, **200b** executes an automated website login routine **204**. In some examples, the first protocol formatting F_1 is similar to the authentication protocol **202** previously described such that the login routine **204** executes functions similar to the observer **210**, the extractor **220**, and the obtainer **230**. Here, the automated website login routine **204** extracts a credential identifier **132c** and a web host identifier (e.g., identifying a web authentication host URL **132a**) from the first reference R_1 . With the credential identifier **132c**, the automated website login routine **204** obtains credential data **160** corresponding to the credential identifier **132c** such that the automated website login routine **204** obtains user credentials **162a-n**. The user credentials **162** include a URL for a login page **124a** (e.g., a login URL **162c**) corresponding to the web host identifier. The automated website login routine **204** uses the user credentials **162** to automatically log into the login page **124a**.

In some examples, the automated website login routine **204** includes web authentication instructions **170** that insert user credentials **162** into the fields of the login form **125**. For example, the automated website login routine **204** executes the authentication instructions **170**, navigates to the login URL **162c**, and inserts the username **162a** and the password **162b** into the username field U_r and the password field P_F , respectfully. As shown in the example of FIG. 3C, the automated website login routine **204** may additionally or alternatively navigate to the web authentication host URL **132a** corresponding to the web host identifier after logging into the login page **124a** related to the web authentication host URL **132a**.

FIG. 3D is an example where the browser extension **200b** recognizes that elements of the first reference R_1 are incomplete. For example, the browser extension **200**, **200b** receives a reference of “web-credential://www.deletefakebook.fakebook.com/deletefakebook/myfakebook.” Here, the browser extension **200b** divides the reference into “web+credential://www.deletefakebook.fakebook.com” as the first reference R_1 and “deletefakebook/myfakebook” as the second reference R_2 . Although this reference resembles the first protocol formatting F_1 with a protocol identifier **132b**, “web+credential” and a web host identifier “www.deletefakebook.fakebook.com,” the reference actually fails to include a credential identifier **132c**. In this scenario, the automated website login routine **204** is configured to recognize the first reference R_1 as an incomplete first protocol formatting and extract the web authentication host URL **132a** via the web host identifier. Here, the automated website login routine **204** obtains the login page URL **162c** and displays the login page URL **162c** for the user **10** instead of automatically logging into the login page **124a** associated with the identified web authentication host URL **132a**. Additionally or alternatively, the automated website login routine **204** may prompt the user **10** by asking whether the user **10** would like to navigate to the login page URL **162c** prior to displaying the login page URL **162c**.

FIG. 4 is a flowchart of an example method **400** using the authentication manager **200** to provide website authentication. At block **402**, the method **400** receives a reference uniform resource locator (URL) **130** at a browser **120**. At block **404**, the method **400** determines whether the reference URL **130** adheres to an authentication protocol **202**. The

14

authentication protocol **202** includes a credential identifier **132c** and a web authentication host URL **132a**. At block **406**, when the reference URL **130** adheres to the authentication protocol **202**, the method **400** includes extracting the credential identifier **132c** and the web authentication host URL **132a** from the reference URL **130**, obtaining credential data **160** from a remote service **150** using the credential identifier **132c**, and sending web authentication instructions **170** to the browser **120**. The web authentication instructions **170** include the web authentication host URL **132a** and the credential data **160**.

FIG. 5 is a flowchart of an example method **500** using the authentication manager **200** to provide website authentication. At block **502**, the method **500** receives references R to web resources. A first reference R_1 has a first protocol formatting F_1 while the remaining references R_2 have a second protocol formatting F_2 . At block **504**, the method **500** identifies the first reference R_1 as having the first protocol formatting F_1 . At block **506**, the method **500** executes an automated website login routine **204** using the first reference R_1 . The automated website login routine **204** is configured to: extract a credential identifier **132c** and a web host identifier from the first reference R_1 ; obtain credential data **160** corresponding to the credential identifier **132c**; obtain a uniform resource locator (URL) **130** for a login page **124a** corresponding to the web host identifier, and automatically log into the login page **124a** corresponding to the web host identifier using the user credential **162**. The credential data **160** obtained when executing the automated website login routine **204** includes a user credential **162**.

A software application (i.e., a software resource) may refer to computer software that causes a computing device to perform a task. In some examples, a software application may be referred to as an “application,” an “app,” or a “program.” Example applications include, but are not limited to, system diagnostic applications, system management applications, system maintenance applications, word processing applications, spreadsheet applications, messaging applications, media streaming applications, social networking applications, and gaming applications.

FIG. 6 is schematic view of an example computing device **600** that may be used to implement the systems and methods described in this document. The computing device **600** is intended to represent various forms of digital computers, such as laptops, desktops, workstations, personal digital assistants, servers, blade servers, mainframes, and other appropriate computers. The components shown here, their connections and relationships, and their functions, are meant to be exemplary only, and are not meant to limit implementations of the inventions described and/or claimed in this document.

The computing device **600** includes a processor **610**, memory **620**, a storage device **630**, a high-speed interface/controller **640** connecting to the memory **620** and high-speed expansion ports **650**, and a low speed interface/controller **660** connecting to a low speed bus **670** and a storage device **630**. Each of the components **610**, **620**, **630**, **640**, **650**, and **660**, are interconnected using various busses, and may be mounted on a common motherboard or in other manners as appropriate. The processor **610** can process instructions for execution within the computing device **600**, including instructions stored in the memory **620** or on the storage device **630** to display graphical information for a graphical user interface (GUI) on an external input/output device, such as display **680** coupled to high speed interface **640**. In other implementations, multiple processors and/or multiple buses may be used, as appropriate, along with

15

multiple memories and types of memory. Also, multiple computing devices **600** may be connected, with each device providing portions of the necessary operations (e.g., as a server bank, a group of blade servers, or a multi-processor system).

The memory **620** stores information non-transitorily within the computing device **600**. The memory **620** may be a computer-readable medium, a volatile memory unit(s), or non-volatile memory unit(s). The non-transitory memory **620** may be physical devices used to store programs (e.g., sequences of instructions) or data (e.g., program state information) on a temporary or permanent basis for use by the computing device **600**. Examples of non-volatile memory include, but are not limited to, flash memory and read-only memory (ROM)/programmable read-only memory (PROM)/erasable programmable read-only memory (EPROM)/electronically erasable programmable read-only memory (EEPROM) (e.g., typically used for firmware, such as boot programs). Examples of volatile memory include, but are not limited to, random access memory (RAM), dynamic random access memory (DRAM), static random access memory (SRAM), phase change memory (PCM) as well as disks or tapes.

The storage device **630** is capable of providing mass storage for the computing device **600**. In some implementations, the storage device **630** is a computer-readable medium. In various different implementations, the storage device **630** may be a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. In additional implementations, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The information carrier is a computer- or machine-readable medium, such as the memory **620**, the storage device **630**, or memory on processor **610**.

The high speed controller **640** manages bandwidth-intensive operations for the computing device **600**, while the low speed controller **660** manages lower bandwidth-intensive operations. Such allocation of duties is exemplary only. In some implementations, the high-speed controller **640** is coupled to the memory **620**, the display **680** (e.g., through a graphics processor or accelerator), and to the high-speed expansion ports **650**, which may accept various expansion cards (not shown). In some implementations, the low-speed controller **660** is coupled to the storage device **630** and a low-speed expansion port **690**. The low-speed expansion port **690**, which may include various communication ports (e.g., USB, Bluetooth, Ethernet, wireless Ethernet), may be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

The computing device **600** may be implemented in a number of different forms, as shown in the figure. For example, it may be implemented as a standard server **600a** or multiple times in a group of such servers **600a**, as a laptop computer **600b**, or as part of a rack server system **600c**.

Various implementations of the systems and techniques described herein can be realized in digital electronic and/or optical circuitry, integrated circuitry, specially designed ASICs (application specific integrated circuits), computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable

16

and/or interpretable on a programmable system including at least one programmable processor, which may be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

These computer programs (also known as programs, software, software applications or code) include machine instructions for a programmable processor, and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms “machine-readable medium” and “computer-readable medium” refer to any computer program product, non-transitory computer readable medium, apparatus and/or device (e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term “machine-readable signal” refers to any signal used to provide machine instructions and/or data to a programmable processor.

The processes and logic flows described in this specification can be performed by one or more programmable processors, also referred to as data processing hardware, executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows can also be performed by special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit). Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read only memory or a random access memory or both. The essential elements of a computer are a processor for performing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto optical disks, or optical disks. However, a computer need not have such devices. Computer readable media suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks, magneto optical disks, and CD ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

To provide for interaction with a user, one or more aspects of the disclosure can be implemented on a computer having a display device, e.g., a CRT (cathode ray tube), LCD (liquid crystal display) monitor, or touch screen for displaying information to the user and optionally a keyboard and a pointing device, e.g., a mouse or a trackball, by which the user can provide input to the computer. Other kinds of devices can be used to provide interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, e.g., visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input. In addition, a computer can interact with a user by sending documents to and receiving documents from a device that is used by the user: for example, by sending web

17

pages to a web browser on a user's client device in response to requests received from the web browser.

A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the disclosure. Accordingly, other implementations are within the scope of the following claims.

What is claimed is:

1. A method for providing website authentication, the method comprising:

receiving, at data processing hardware, a reference uniform resource locator (URL) at a browser, the reference URL comprising a credential identifier and a web authentication host URL, the credential identifier identifying credential data;

determining, by the data processing hardware, that the reference URL adheres to an authentication protocol based on the credential identifier and the web authentication host URL; and

based on determining that the reference URL adheres to the authentication protocol:

extracting, by the data processing hardware, the credential identifier and the web authentication host URL from the reference URL;

obtaining, by the data processing hardware, credential data from a remote service using the credential identifier; and

sending web authentication instructions to the browser, the web authentication instructions comprising: the web authentication host URL; and the credential data.

2. The method of claim 1, wherein the reference URL adheres to either the authentication protocol or a Hypertext Transfer Protocol.

3. The method of claim 1, wherein the credential data comprises a username and a password.

4. The method of claim 1, wherein the authentication protocol comprises a user identifier.

5. The method of claim 4, wherein the user identifier and the credential identifier comprise object identifiers, the object identifiers configured to publically obfuscate an identity of a user associated with the user identifier and a credential associated with the credential identifier.

6. The method of claim 1, wherein the authentication protocol comprises a user identifier combined with the credential identifier as a single identifier.

7. The method of claim 1, wherein the web authentication instructions configure the browser to auto-populate a login form at the web authentication host URL using the credential data based on the web authentication instructions.

8. The method of claim 1, wherein the web authentication instructions further comprise a login URL and configure the browser to:

execute the login URL, the login URL navigating to a login page associated with the web authentication host URL;

determine login fields by parsing a document object model of the login page;

populate the login fields using the credential data based on the web authentication instructions; and

redirect the browser to the web authentication host URL.

9. The method of claim 1, wherein the authentication protocol further comprises a custom protocol identifier.

10. The method of claim 1, wherein the authentication protocol comprises a format of web+credential://{Credential ID}@{Web Host}.

18

11. A method for providing website authentication, the method comprising:

receiving, at data processing hardware, references to web resources, a first reference comprising a credential identifier and a web host identifier, the first reference having a first protocol formatting, the remaining references having a second protocol formatting;

identifying, by the data processing hardware, the first reference as having the first protocol formatting based on the credential identifier and the web host identifier; and

executing, by the data processing hardware, an automated website login routine using the first reference, wherein the automated website login routine is configured to:

extract the credential identifier and the web host identifier from the first reference;

obtain, using the credential identifier, credential data corresponding to the credential identifier, the credential data comprising a user credential;

obtain a uniform resource locator for a login page corresponding to the web host identifier; and

automatically log into the login page corresponding to the web host identifier using the user credential.

12. The method of claim 11, wherein automatically logging into the login page comprises:

parsing a document object model of the login page to identify a username field and a password field;

inserting a user name of the user credential into the username field; and

inserting a password of the user credential into the password field.

13. The method of claim 11, wherein the first protocol formatting comprises: web+credential://{User OID}:{Credential OID}@{Web App Host}/.

14. The method of claim 11, further comprising:

receiving, at the data processing hardware, a format of web+credential://{Web App Host}/ as the first reference; and

identifying, by the data processing hardware, the format of web+credential://{Web App Host}/ as an incomplete first protocol formatting,

wherein the automated website login routine is configured to:

extract the web host identifier from the first reference; obtain the uniform resource locator for the login page corresponding to the web host identifier; and

display the login page corresponding to the web host identifier in response to the received references comprising the format of web+credential://{Web App Host}/ as the first reference.

15. The method of claim 11, wherein the first protocol formatting comprises a custom protocol identifier.

16. The method of claim 11, wherein the credential identifier comprises a user identifier.

17. The method of claim 11, further comprising redirecting, by the data processing hardware, to the web resources of the received references.

18. The method of claim 11, wherein the credential identifier comprises an object identifier, the object identifier configured to publically obfuscate an identity of a user associated with the credential identifier.

19. The method of claim 11, wherein the user credential comprises a username and a password.

20. A system for providing website authentication, the system comprising:
data processing hardware; and

19

memory hardware in communication with the data processing hardware, the memory hardware storing instructions that when executed by the data processing hardware cause the data processing hardware to perform operations comprising: 5

receiving a reference uniform resource locator (URL) at a browser, the reference URL comprising a credential identifier and a web authentication host URL, the credential identifier identifying credential data; 10

determining that the reference URL adheres to an authentication protocol based on the credential identifier and the web authentication host URL; and based on determining that the reference URL adheres to the authentication protocol: 15

extracting, by the data processing hardware, the credential identifier and the web authentication host URL from the reference URL; 20

extracting the credential identifier and the web authentication host URL from the reference URL; obtaining credential data from a remote service using the credential identifier; and 25

sending web authentication instructions to the browser, the web authentication instructions comprising: the web authentication host URL; and the credential data.

21. The system of claim 20, wherein the reference URL adheres to either the authentication protocol or a Hypertext Transfer Protocol.

22. The system of claim 20, wherein the credential data comprises a username and a password. 30

23. The system of claim 20, wherein the authentication protocol comprises a user identifier.

24. The system of claim 23, wherein the user identifier and the credential identifier comprise object identifiers, the object identifiers configured to publically obfuscate an identity of a user associated with the user identifier and a credential associated with the credential identifier. 35

25. The system of claim 20, wherein the authentication protocol comprises a user identifier combined with the credential identifier as a single identifier. 40

26. The system of claim 20, wherein the web authentication instructions configure the browser to auto-populate a login form at the web authentication host URL using the credential data based on the web authentication instructions. 45

27. The system of claim 20, wherein the web authentication instructions further comprise a login URL and configure the browser to:

execute the login URL, the login URL navigating to a login page associated with the web authentication host URL; 50

determine login fields by parsing a document object model of the login page;

populate the login fields using the credential data based on the web authentication instructions; and 55

redirect the browser to the web authentication host URL.

28. The system of claim 20, wherein the authentication protocol further comprises a custom protocol identifier.

29. The system of claim 20, wherein the authentication protocol comprises a format of web+credential://{Credential ID}@{Web Host}. 60

30. A system for providing website authentication, the system comprising:

data processing hardware; and

memory hardware in communication with the data processing hardware, the memory hardware storing 65

20

instructions that when executed by the data processing hardware cause the data processing hardware to perform operations comprising:

receiving references to web resources, a first reference comprising a credential identifier and a web host identifier, the first reference having a first protocol formatting, the remaining references having a second protocol formatting;

identifying the first reference as having the first protocol formatting based on the credential identifier and the web host identifier; and

executing an automated website login routine using the first reference,

wherein the automated website login routine is configured to:

extract the credential identifier and the web host identifier from the first reference;

obtain, using the credential identifier, credential data corresponding to the credential identifier, the credential data comprising a user credential;

obtain a uniform resource locator for a login page corresponding to the web host identifier; and

automatically log into the login page corresponding to the web host identifier using the user credential.

31. The system of claim 30, wherein automatically logging into the login page comprises:

parsing a document object model of the login page to identify a username field and a password field;

inserting a user name of the user credential into the username field; and

inserting a password of the user credential into the password field.

32. The system of claim 30, wherein the first protocol formatting comprises: web+credential://{User OID}:{Credential OID}@{Web App Host}/.

33. The system of claim 30, wherein the operations further comprise:

receiving a format of web+credential://{Web App Host}/ as the first reference; and

identifying the format of web+credential://{Web App Host}/ as an incomplete first protocol formatting,

wherein the automated website login routine is configured to:

extract the web host identifier from the first reference;

obtain the uniform resource locator for the login page corresponding to the web host identifier; and

display the login page corresponding to the web host identifier in response to the received references comprising the format of web+credential://{Web App Host}/ as the first reference.

34. The system of claim 30, wherein the first protocol formatting comprises a custom protocol identifier.

35. The system of claim 30, wherein the credential identifier comprises a user identifier.

36. The system of claim 30, wherein the operations further comprise redirecting to the web resources of the received references.

37. The system of claim 30, wherein the credential identifier comprises an object identifier, the object identifier configured to publically obfuscate an identity of a user associated with the credential identifier.

38. The system of claim 30, wherein the user credential comprises a username and a password.

* * * * *