



US011916360B2

(12) **United States Patent**
Fowler, Jr. et al.

(10) **Patent No.:** **US 11,916,360 B2**
(45) **Date of Patent:** ***Feb. 27, 2024**

(54) **CONDUCTOR IDENTIFICATION**

(71) Applicant: **Southwire Company, LLC**, Carrollton, GA (US)

(72) Inventors: **Willie Franklin Fowler, Jr.**, Roopville, GA (US); **Jeremy Harris**, Villa Rica, GA (US); **Richard Mike Temblador**, Carrollton, GA (US); **Juan Alberto Galindo Gonzalez**, Powder Springs, GA (US)

(73) Assignee: **Southwire Company, LLC**, Carrollton, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/675,091**

(22) Filed: **Feb. 18, 2022**

(65) **Prior Publication Data**

US 2022/0173581 A1 Jun. 2, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/780,096, filed on Feb. 3, 2020, now Pat. No. 11,264,784, which is a continuation of application No. 15/254,051, filed on Sep. 1, 2016, now Pat. No. 10,554,025.

(60) Provisional application No. 62/212,624, filed on Sep. 1, 2015.

(51) **Int. Cl.**
H02G 1/08 (2006.01)

(52) **U.S. Cl.**
CPC **H02G 1/08** (2013.01); **H02G 2200/20** (2013.01)

(58) **Field of Classification Search**

CPC H02G 1/08; H02G 2200/20
USPC 254/134.3 R, 134.7, 2 R
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

83,341 A	10/1868	Towndrow
745,833 A	12/1903	Hanson
993,008 A	5/1911	West
1,403,404 A	1/1922	Grumpelt
1,553,963 A	9/1925	Swartsel

(Continued)

FOREIGN PATENT DOCUMENTS

EP	1693126 A1	6/2005
WO	2001/28906 A1	4/2001
WO	2006/037395 A1	4/2006

OTHER PUBLICATIONS

U.S. Appl. No. 13/464,168, filed May 4, 2012, Temblador, et al., entitled "Multiple Conductor Container" (abandoned).

(Continued)

Primary Examiner — Lee D Wilson



Assistant Examiner — Shantese L McDonald

(74) *Attorney, Agent, or Firm* — Merchant & Gould P.C.

(57) **ABSTRACT**

Conductor identification may be provided. A first sleeve may be placed around a first conductor and a second sleeve around a second conductor. Next, a first tag may be placed on the first conductor and a second tag on the second conductor. Then, the first conductor and the second conductor may be pulled together through a conduit. The first conductor may slideably move through the first sleeve and the second conductor may slideably move through the second sleeve as the first conductor and the second conductor are pulled together through the conduit.

20 Claims, 23 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

1,649,940 A	11/1927	Willmot	6,209,725 B1	4/2001	Chen
1,915,843 A	6/1933	Wright	6,499,284 B2	12/2002	Chern et al.
1,926,836 A	9/1933	Corlett	6,530,584 B1	3/2003	Lucy
1,974,862 A	9/1934	Cryan	6,662,963 B1	12/2003	Meike et al.
2,077,349 A	4/1937	Hobbis	6,683,555 B2	1/2004	Carlson
2,239,222 A	4/1941	Funke	6,702,077 B2	3/2004	Skowronski
2,249,051 A	7/1941	Schulse	6,857,521 B2	2/2005	Cantu-Gonzalez
2,620,997 A	12/1942	Lyon	6,882,898 B2	4/2005	Fore, Sr.
2,330,909 A	10/1943	Olson	6,889,835 B2	5/2005	Land
2,490,837 A	12/1949	Scott	6,966,701 B2	11/2005	Schelbert
2,497,440 A	2/1950	Denny	7,004,419 B2	2/2006	Hsu
2,580,900 A	1/1952	Epstein	7,025,300 B2	4/2006	Glassey
2,610,812 A	9/1952	Epstein	7,076,985 B2	7/2006	Rex
2,713,938 A	7/1955	Snyder	7,100,863 B2	9/2006	Hsu et al.
2,736,512 A	2/1956	Drummond	7,161,097 B1	1/2007	Gorgone
2,765,090 A	10/1956	Halls	7,185,838 B2	3/2007	Mullebrouck
2,803,337 A	8/1957	Lee	7,399,017 B1	7/2008	Lasseigne
2,826,322 A	2/1958	Posehn	7,520,120 B2	4/2009	Saito
2,854,245 A	9/1958	Manahan	7,798,180 B2	9/2010	Kazuaki
2,869,719 A	1/1959	Hubbard	7,798,326 B2	9/2010	Hsu
2,895,691 A	7/1959	Toler	7,866,586 B2	1/2011	Fabian
2,903,147 A	9/1959	Davis, Jr.	8,157,201 B2	4/2012	Galgano
2,912,763 A	11/1959	Loewe et al.	8,235,210 B2	8/2012	De Lacerda et al.
3,000,493 A	9/1961	Hirst	8,366,126 B2	2/2013	Galgano et al.
3,011,735 A	12/1961	Lachat	8,387,909 B2	3/2013	Galgano et al.
3,081,893 A	3/1963	Holsclaw	8,662,003 B1	3/2014	Cooper et al.
3,082,868 A	3/1963	Hubbard	8,746,607 B2	6/2014	LaForest
3,114,456 A	12/1963	Van Billiard	8,936,153 B1	1/2015	Temblador et al.
3,278,061 A	10/1966	Christensen	9,145,219 B1	9/2015	Temblador et al.
3,298,631 A	1/1967	Richardson, Jr.	9,796,494 B1	10/2017	Temblador et al.
3,369,687 A	2/1968	Walls	9,867,300 B1	1/2018	Fowler et al.
3,473,489 A	10/1969	Sargent	10,232,868 B1	3/2019	Gonzalez
3,485,458 A	12/1969	Evans	10,356,924 B1	7/2019	Fowler
3,491,876 A	1/1970	Zecchin	10,427,816 B1	10/2019	Temblador
3,602,455 A	8/1971	Lewis	10,554,025 B2	2/2020	Fowler
3,642,301 A	2/1972	Crawford	10,843,830 B1	11/2020	Temblador
3,674,164 A	7/1972	Kaufman	11,264,784 B2	3/2022	Temblador et al.
3,711,111 A	1/1973	Crawford	11,267,598 B1	8/2022	Temblador et al.
3,722,825 A	3/1973	Phillips	2001/0006184 A1	7/2001	Ohike
3,815,844 A	6/1974	Wright et al.	2001/0039464 A1	11/2001	Hackauf
3,819,847 A	6/1974	Charles	2002/0113162 A1	8/2002	Fournier
3,868,033 A	2/1975	Duff	2002/0168259 A1	11/2002	McConnell
3,902,679 A	9/1975	Bost et al.	2003/0089818 A1	5/2003	Reau
4,018,468 A	4/1977	Lundquist	2003/0230660 A1	12/2003	Vernam
4,202,509 A	5/1980	Horn	2003/0230667 A1	12/2003	Ganster
4,213,536 A	7/1980	Hafner	2004/0177642 A1	9/2004	Citrynell et al.
4,257,729 A	3/1981	Morissette	2005/0074317 A1	4/2005	Escorza
4,444,313 A	4/1984	Tyson	2005/0127233 A1	6/2005	Hsu et al.
4,509,702 A	4/1985	Reese	2005/0263640 A1	12/2005	Vanderslice
4,512,431 A	4/1985	Bloomfield	2006/0086527 A1*	4/2006	Sterkers G09F 3/205 174/112
4,582,198 A	4/1986	Ditton	2006/0102771 A1	5/2006	Kimura
4,588,318 A	5/1986	O'Brien	2006/0056947 A1	9/2006	Posly
4,664,260 A	5/1987	Stokes	2006/0196989 A1	9/2006	Bartley
4,680,068 A	7/1987	Hofstettler et al.	2006/0249611 A1	11/2006	Carroscia et al.
4,741,659 A	5/1988	Berg	2007/0045141 A1	3/2007	Gelmetti
4,981,412 A	1/1991	Hawkins	2007/0175786 A1	8/2007	Nicklas
5,022,603 A	6/1991	Maree et al.	2008/0023358 A1	1/2008	Otto
5,033,520 A	7/1991	Kuehmicel	2008/0236102 A1	10/2008	Murakami
5,129,593 A	7/1992	Smith	2010/0124476 A1	5/2010	Berlinger
D329,561 S	9/1992	Nyorkor	2010/0164191 A1	7/2010	Kinnen et al.
5,275,349 A	1/1994	Tussing	2010/0224328 A1*	9/2010	Utaka H01B 7/368 156/378
5,277,314 A	1/1994	Cooper et al.	2011/0174763 A1	7/2011	Kennedy
5,406,996 A	4/1995	Wagner	2011/0259467 A1	10/2011	Maness
5,499,775 A	3/1996	Vander Groef	2012/0168554 A1	7/2012	Blunt et al.
5,641,947 A	6/1997	Riddle, Jr.	2012/0234713 A1	9/2012	Nicklas
5,642,811 A	7/1997	Huebner et al.	2013/0032597 A1	2/2013	Anderson
5,707,021 A	1/1998	Bitts	2013/0119184 A1	5/2013	Ma et al.
5,738,209 A	4/1998	Burr et al.	2013/0313377 A1	11/2013	Struck, II
5,746,380 A	5/1998	Chung	2013/0334166 A1	12/2013	Garipalli et al.
5,758,834 A	6/1998	Dragoo et al.	2014/0145408 A1	5/2014	Midas
5,816,514 A	10/1998	Duclos et al.	2014/0319438 A1	10/2014	Carlson et al.
5,879,068 A	3/1999	Menashrov et al.	2015/0014468 A1*	1/2015	Carlson B65H 55/005 242/594
5,967,362 A	10/1999	Corbin	2015/0225205 A1	8/2015	Fleury et al.
6,016,911 A	1/2000	Chen	2017/0063057 A1	3/2017	Fowler, Jr. et al.
6,129,796 A	10/2000	Steinberg et al.			

(56)

References Cited

U.S. PATENT DOCUMENTS

2020/0176959 A1 6/2020 Fowler
2020/0365062 A1* 11/2020 Geens G09F 3/20

OTHER PUBLICATIONS

Copending U.S. Appl. No. 16/780,096, filed Feb. 3, 2020 entitled
"Conductor identification".

U.S. Office Action dated Jan. 17, 2023 co-pending U.S. Appl. No.
17/680,452; 29 pages.

Canadian Office Action dated Oct. 24, 2022 Application No. 2,941,006;
6 pages.

Co-Pending U.S. Appl. No. 17/680,452, filed Feb. 25, 2022 entitled
Method for Laying Multiple Conductors in a Container.

* cited by examiner




FIG. 1A




FIG. 1B





FIG. 1C






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17A

1700





FIG. 17B



1732

FIG. 17C




FIG. 17D




FIG. 18B

FIG. 18A




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23

CONDUCTOR IDENTIFICATION**CROSS-REFERENCE TO RELATED APPLICATION**

The current application is a Continuation Application of and claims priority to U.S. application Ser. No. 16/780,096 filed Feb. 3, 2020, now U.S. Pat. No. 11,264,784, which is a Continuation of U.S. application Ser. No. 15/254,051 filed on Sep. 1, 2016, now U.S. Pat. No. 10,554,025, which claims priority to and the benefit of U.S. Provisional Application No. 62/212,624, filed Sep. 1, 2015, which are incorporated herein by reference in their entirety.

COPYRIGHTS

All rights, including copyrights, in the material included herein are vested in and the property of the Applicants. The Applicants retain and reserve all rights in the material included herein, and grant permission to reproduce the material only in connection with reproduction of the granted patent and for no other purpose.

BACKGROUND

With conventional systems, at least three electricians may be needed to install wire. One would pull and feed the wire from a reel holder, one would feed the wire and possibly lubricate the wire into a conduit, and a third would pull the wire through the conduit. This method of installing wire is very labor intensive and strenuous as the electrician pulling wire from the reel holder may have to pull hard enough to overcome then stationary inertia of multiple reels hold 50 or more pounds of wire. For example, if there are seven reels with 50 pounds of wire on each reel, the electrician must pull with a force to overcome 3,500 pounds of stationary wire.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this disclosure, illustrate various embodiments of the present invention. In the drawings:

FIGS. 1A, 1B, and 1C show a multiple conductor container assembly;

FIG. 2 shows a top view of the multiple conductor container assembly;

FIG. 3 shows a side view of the multiple conductor container assembly;

FIG. 4 shows cross-section of the multiple conductor container assembly;

FIG. 5 shows a container tap wire guide;

FIG. 6 shows an insert;

FIG. 7 shows a container tap wire guide;

FIG. 8 shows a method and configuration for stacking multiple conductor container assemblies;

FIG. 9 shows a multiple conductor container having graduations;

FIG. 10 shows a label for a conductor container;

FIG. 11 shows a computer;

FIG. 12 shows a flowchart of a method for estimating a remaining amount of wire in a multiple conductor container;

FIG. 13 shows a flow chart of a method for packaging multiple conductors;

FIG. 14 shows a monitoring station;

FIG. 15 shows a guide;

FIG. 16 shows a tension equalization capstan;

FIGS. 17A and 17B show a variable speed drive system;

FIGS. 17C and 17D show a drive wheel and a pressure roller;

FIGS. 18A and 18B show a method and configuration for laying multiple conductors in a multiple conductor container assembly;

FIG. 19 shows a flow chart of a method of using a container including multiple conductors;

FIG. 20 shows a multiple conductor container assembly and a coupler;

FIG. 21 shows a multiple conductor container assembly and a coupler;

FIG. 22 is a block diagram of an operating environment for providing conductor identification; and

FIG. 23 is a flow chart setting forth the general stages involved in a method for providing conductor identification.

DESCRIPTION

The following detailed description refers to the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the following description to refer to the same or similar elements. While embodiments of the invention may be described, modifications, adaptations, and other implementations are possible. For example, substitutions, additions, or modifications may be made to the elements illustrated in the drawings, and the methods described herein may be modified by substituting, reordering, or adding stages to the disclosed methods. Accordingly, the following detailed description does not limit the invention.

Consistent with embodiments of the invention, a container may be provided. The container may comprise a first surface and a second surface concentric with the first surface. The first surface and the second surface may define a volume. The volume may house a concentric length of multiple single conductors arranged in parallel.

With embodiments of the invention, multiple conductors may be non-bound, paralleled, cabled, twisted, non-twisted or bundled (e.g., with a binder) together and laid in a circular pattern in the container. Paralleled conductors may be conductors arranged such that they are substantially parallel to one another. A conductor may be any material that may conduct electricity, light, or any signal. Examples of a conductor may include copper wire, a data cable, a fiber optic cable, and aluminum wire.

An example of the container may be a barrel for housing multiple conductors. The circular pattern may be helically distributed horizontally within the container assembly with a center core and an outside diameter that is larger than the circular pattern effectively forming a horizontal layer. Moreover, each horizontal layer may be layered or stacked vertically. If the container assembly is layered and stacked, then an end user may be able to easily payoff the multiple conductors from the center of the container assembly without having to set up a reel, thus eliminating the need to lift reels and issues associated with paying off on reels. Additionally, a cart may be adapted or modified to allow the container to be secured, moved, and located where needed. For example, the container may be located near or equipped with a container tap wire guide that may center the conductors over the container and allows it to be pulled where needed.

FIG. 1A shows a multiple conductor container assembly 100 (e.g., a container) that may be used to store, transport, and feed a cable. Multiple conductor container assembly 100 may comprise a first surface (e.g., an outer wall 102), a second surface (e.g., a middle wall 104), and a third surface

(e.g., an inner wall **106**). Outer wall **102** and middle wall **104** may form a first volume **108** (e.g., a first cavity) and middle wall **104** and inner wall **106** may form a second volume **110** (e.g., a second cavity). Inner wall **106** may form a third volume **112** (e.g., a third cavity). Multiple conductor container assembly **100** may further comprise a bottom plate **114**. While FIG. 1A shows middle wall **104** and inner wall **106** each having a cylindrical profile, as shown in FIG. 1B, an inner surface **116** may comprise a conical profile. In addition, as shown in FIG. 1C a multiple conductor assembly **100a** may comprise bottom plate **114** and inner surface **116**. The multiple conductors may be wrapped around inner surface **116**.

As will be describe in greater detail below, first volume **108**, second volume **110**, and third volume **112** may be used to house and feed cables.

Furthermore, items other than cables may be stored in the cavities. For instance, third volume **112** may include various materials such as an electrician's tools or other supplies (e.g., wire nuts, receptacle boxes, etc.). Moreover, any number of walls and any number of cavities may be used consistent with embodiments. Consistent with embodiments of the invention, any of the surfaces (e.g., first surface, a second surface, a third surface, etc.) may be solid, may contain holes, may have slots, may have spaces, and may form any structure (e.g., a frame structure). The surfaces are not limited to being solid.

The cable may comprise a single conductor (e.g., THHN) or may have multiple conductors (e.g., MC cable, parallel cables, parallel conductors, multiple sets of bound cables, insulated, un-insulated, etc.). The multiple conductors may be unbound or may be bound together. The multiple conductors may be bound together by twisting the multiple conductors together, placing a binding wire or tape around the multiple conductors, or a jacket may be placed around the multiple conductors. In addition, the multiple conducts may laid in the multiple conductor container assembly **100** simultaneously.

FIG. 2 shows top view of multiple conductor container assembly **100** having a first conductor **202** stored in first volume **108** and a second conductor **204** stored in second volume **110**. First conductor **202** and second conductor **204** may be placed in multiple conductor container assembly **100** such that they form concentric circles. For instance, FIG. 2 shows first conductor **202** having a lay that forms counter-clockwise concentric circles and second conductor **204** having a lay that forms counter-clockwise concentric circles. While FIG. 2 shows first conductor **202** and second conductor **204** having the same lay direction, first conductor **202** and second conductor **204** may have the opposite lay directions (i.e., first conductor **202** laying clockwise and second conductor **204** laying counter-clockwise). As will be described in greater detail below with regard to FIG. 4, each set of concentric circles may form a horizontal layer in multiple conductor container assembly **100**.

FIG. 3 shows a side view of multiple conductor container assembly **100**. As shown in FIG. 3, multiple conductor container assembly **100** may include a container tap wire guide **302** that may facilitate removal of first conductor **202** and second conductor **204** from multiple conductor container assembly **100**. Container tap wire guide **302** may comprise an opening **304** in at least one leg **306**. The at least one leg **306** may be flexible, ridged, and adjustable. The at least one leg **306** may be fixed to a top **308** or may be rotatably connected to top **308**. Top **308** may be fixed to or may be rotatably connected to multiple conductor container assembly **100**. While FIG. 3 shows container tap wire guide

302 having a curved dome type structure, container tap wire guide **302** may be any shape such as a pyramid, a conical structure, etc. Opening **304** may allow first conductor **202** and/or second conductor **204** to exit multiple conductor container assembly **100**. Container tap wire guide **302** may also include additional features not shown such as rollers, a twister and devices that may braid or bind first conductor **202** to second conductor **204**.

FIG. 4 shows a cross-section of multiple conductor container assembly **100** along section line **3** shown in FIG. 2. FIG. 4 shows first conductor **202** forming layers **1** through **n** and second conductor **204** forming layers **1** through **m**. As shown in FIG. 4, first conductor **202** and second conductor **204** may have different diameters and therefore there may be more or less layers formed by second conductor **204** than by first conductor **202**. During use, first conductor **202** and second conductor **204** may be pulled by a user through opening **304**. First conductor **202** and second conductor **204** may both be fed from multiple conductor container assembly **100** through opening **304**. Also, first conductor **202** may be fed from multiple conductor container assembly **100** through opening **304** independently from second conductor **204**. In addition, while FIG. 4 shows first conductor **202** and second conductor **204** being fed into independent sections, first conductor **202** and second conductor **204** may be fed into the same section (e.g., first volume **108** or second volume **110**). In other words, each volume may receive more than one conductor. Container tap wire guide **302** may have multiple openings for first conductor **202** and second conductor **204** separately.

Furthermore, while FIGS. 1 through 4 show multiple conductor container assembly **100** as being circular, embodiments may comprise other shapes. For example, multiple conductor container assembly **100** may be square, rectangular, spherical, or any other shape. For example, in various embodiments, outer wall **102** and middle wall **104** may be circular, and inner wall **106** may be rectangular. In addition, while FIGS. 1 through 4 show multiple conductor container assembly **100** having cavities of differing volumes, the cavities may have the same volume. Furthermore, first volume **108** may be sized to hold a first particular amount of a first conductor (e.g., 2,500 feet of 12 gauge wire) and second volume **110** may be sized to a second particular amount of a second conductor (e.g., 2,500 feet of a 18 gauge wire). The conductors housed in the different cavities may be of the same type. For instance, first volume **108** and second volume **110** may each house 5,000 feet of 12 gauge wire. Moreover, while FIGS. 1-4 show a single conductor housed in each cavity of multiple conductor container assembly **100**, each cavity may house multiple conductors. For example, first volume **108** may house two parallel conductors (e.g., a 12 gauge black wire and a 12 gauge white wire) and second volume **110** may house a single conductor (e.g., a 12 gauge green wire).

FIG. 5 shows another embodiment of container tap wire guide **302**.

Container tap wire guide **302** may comprise a plurality of legs (e.g., a first leg **502**, a second leg **504**, and a third leg **506**) that may be connected to a collar **510**. Collar **510** may receive an insert **512**. The connection points where the plurality of legs may connect to collar **510** may pivot. In addition, the plurality of legs may be adjustable in length. Furthermore, the plurality of legs may comprise clamps that may be used to connect container tap wire guide **302** to multiple conductor container assembly **100**. Set screws may be used to secure insert **512** into collar **510**.

5

FIG. 6 shows insert 512 in more detail. Insert 512 may comprise a male portion 602 that may mate with collar 510. Insert 512 also may comprise a neck 604 and a top portion 606. Top portion 606 may include a shaped surface 608 that may provide conductors a smooth transition away from container tap wire guide 302 as it passes up through neck 604 and out of top portion 606. Shaped surface 608 may be curved, arc-shaped, parabolic, or any other shape that may provide a smooth transition. Shaped surface 608 may allow conductors to be pulled from multiple conductor container assembly 100 without damage to the conductors. Neck 604 may also include a shaped surface (not shown) exposed to conductors entering insert 512 through the bottom of neck 604. Neck 604's shaped surface may be shaped similarly to shaped surface 608 and may allow the conductors to enter insert 512 without damage. In addition, the shaped surfaces may allow the conductors to be pulled in any direction without damage.

Insert 512 may act to hinder the conductors from falling back into multiple conductor container assembly 100 when not being pulled by a user. For instance, the conductors may have a natural twist imparted upon them as they are pulled from multiple conductor container assembly 100. This natural twist may cause portions of the conductors to rest against the inner surface of neck 604. The friction between the conductors and the inner surface may hinder the conductors from falling back into multiple conductor container assembly 100. Insert 512 may also include a lubricant applying member (not shown) that may apply a lubricant to the conductors as they pass through insert 512.

FIG. 7 shows yet another embodiment of container tap wire guide 302 that may be attached to the top of multiple conductor container assembly 100. Container tap wire guide 302 may comprise a plurality of legs (e.g., a first leg 702, a second leg 704, and a third leg 706) and a feeder ring 708. Conductors from each of cavities multiple conductor container assembly 100 may be pulled together through feeder ring 708. Feeder ring 708 may be manufactured such that portions that may contact the conductors do not rub against a sharp edge. In addition, feeder ring 708 may be configured to apply a lubricant to wires or cable being pulled through it. Container tap wire guide 302 may be permanently attached or removable.

Container tap wire guide 302 may include a cap structure 710 that may facilitate removal of conductors from multiple conductor container assembly 100. Cap structure 710 may comprise an opening 712. Cap structure 710 may be flexible or may be ridged. Cap structure 710 may be fixed or may be rotatably connected to multiple conductor container assembly 100. While FIG. 7 shows cap structure 710 having a curved structure, cap structure 710 may be any shape such as a pyramid, a conical structure, etc. Cap structure 710 may also include additional features not shown such as a twister and devices that may braid or bind conductors together.

Container tap wire guide 302 may comprise a locking mechanism (not shown) that may comprise a choking member located internal or external to container tap wire guide 302, cap structure 710, or opening 712. The choking member may hinder wires or cables from traveling back into multiple conductor container assembly 100. For instance, during operation an electrician may pull wires or cables through cap structure 710. The choking member may then prevent the wires and cables from slipping back into multiple conductor container assembly 100. This may prevent the electrician from having to feed the wires and cables through container tap wire guide 302 every time he cuts the conductors.

6

Conductors used in conjunction with multiple conductor container assembly 100, insert 512, and/or cap structure 710 may also comprise a cable having a jacket having a built-in lubricant (e.g., SIMPULL® cable) to lower the pulling force need to pull the wires or cables past surfaces they may contact.

FIG. 8 shows a method 800 and configuration that may allow a multiple conductor container assembly 802 to be stacked on top of another multiple conductor container assembly 804. As shown in FIG. 8, multiple conductor container assembly 802 and multiple conductor container assembly 804 may include complementary surfaces to facilitate stacking. For example, a male surface 806 and a female surface 808. During stacking, male surface 806 may mate with female surface 808 to create an interlocking effect that may help hinder the multiple conductor container assembly 802 from sliding off the multiple conductor container assembly 804. When multiple conductor container assembly 802 is located atop multiple conductor container assembly 804, the weight of multiple conductor container assembly 802, coupled with the interaction between male surface 806 and female surface 808, may keep multiple conductor container assembly 802 from sliding off the top of multiple conductor container assembly 804.

In addition, male surface 806 and female surface 808 may include locking members that may create an interlocking connection. For example, male surface 806 may include tenons (not shown) that fit within mortises (not shown) located in female surface 808. Upon the tenons being inserted into the mortise, multiple conductor container assembly 802 may be rotated about an axis 810 as indicated by arrow 812. This rotation may lock the multiple conductor container assembly 802 to multiple conductor container assembly 804.

FIG. 9 shows a multiple conductor container 900 comprising graduations 902. Multiple conductor container 900 may comprise an outer container 904 and an inner container 906. Inner container 906 may have an outer surface 908. Graduations 902 may be located on outer surface 908. In addition, outer container 904 may have an inner surface 910. Graduations 902 may be located on inner surface 910. The graduations may be placed on an external surface such as a yardstick.

During manufacturing, graduations 902 may be printed directly on inner surface 910 or outer surface 908. Embodiments may also include graduations 902 being printed on a sticker or other label (not shown) and applied to inner surface 910 or outer surface 908. Further embodiments may comprise multiple conductor container 900 being comprised of a transparent portion, or be manufactured entirely out of a transparent material, that may allow a user to view an amount of conductors located in multiple conductor container 900.

FIG. 10 shows a label 1000 that may be attached to multiple conductor container 900. Label 1000 may include a designation 1002. Designation 1002 may include text describing the type of cable in multiple conductor container 900. For instance, designation 1002, as shown in FIG. 10, may indicate that a cable stored in multiple conductor container 900 may comprise seven 14 gauge conductors in parallel. Other information that may be included on label 1000 includes the number of conductors within multiple conductor container 900 and the amount of each contained in multiple conductor container 900. For instance, multiple conductor container 900 may contain 1,000 feet of a AWG #14 white wire and 1,500 feet of a AWG #18 green wire.

Label **1000** may also include a scale **1004**. Scale **1004** may provide a user with information to estimate a remaining amount of cable in multiple conductor container **900**. For instance, scale **1004**, as shown in FIG. **10**, may indicate that for every one unit of graduation in graduations **902** there may be 650 feet of the seven 14 gauge conductors. For example, graduations **902**, as shown in FIG. **9**, include 12 units, so multiple conductor container **900**, when full, may contain 7,800 feet of cable (650 feet/unit X 12 units). During use an electrician may estimate he needs 3,500 feet of cable for a particular job. To determine if multiple conductor container **900** contains enough cable for the particular job, he may use label **1000** in conjunction with graduations **902** to determine that if multiple conductor container **900** contains less than 6 units (3,500 feet/650 ft/unit=5.38 units of conductors), he may not have enough cable for the particular job.

Graduations **902** may be conductor specific or standard sizes. For example, multiple conductor container **900** may be manufactured with graduations **902** spaced for a particular cable (e.g., a 14 gauge wire). Embodiments may also include using label **1000** to allow for multiple conductor container **900** to be manufactured with standard graduations. For instance, multiple conductor container **900** may be a standard container size that may be able to accept multiple types of conductor ranging from very small gauges to very large gauges and from a single conductor to multiple conductors of varying gauges. Having a standard container with standard graduations may make the manufacturing of multiple conductor container **900** more efficient than manufacturing containers having different graduations for different conductor sizes.

Label **1000** may also include other information. For instance, an estimated weight of multiple conductor container **900** may be included on label **1000**. For example, label **1000** may indicate that each unit of graduation is approximately 100 pounds of cable. Thus, when multiple conductor container **900** is full of conductor (i.e., has 12 units of conductor) it may weigh approximately 1,200 lbs. This information may be useful when estimating shipping weights. Other information that may be included on label **1000** may include, for example, a lot number, model number, serial number, manufacturing date, and manufacturing location. In addition, label **1000** may include a barcode **1006** that may allow a user to determine information about the contents of multiple conductor container **900**.

Furthermore, an application running on a computer **1100**, shown in FIG. **11**, (e.g., a smartphone) may receive information that allows the computer calculate an amount of wire remaining in multiple conductor container **900**. As shown in FIG. **11**, computer **1100** may include a processing unit **1112**, a memory unit **1114**, a display **1116**, and an input unit **1118**. Memory unit **1114** may include a software module **1120** and a database **1122**. While executing on processing unit **1112**, software module **1120** may perform processes for determining an amount of conductor remaining in multiple conductor container **900**, including, for example, one or more stages included in method **1200** described below with respect to FIG. **12**.

Computer **1100** ("the processor") may be implemented using a personal computer, a network computer, a mainframe, a smartphone, or other similar computer-based system. Computer **1100** may also be configured to transmit data to a supplier or manufacturer. For instance, if there is a problem with the wire in multiple conductor container **900** a user, using computer **1100**, may scan barcode **1006** located

on label **1000** and transit the information to the supplier of manufacturer of multiple conductor container **900**.

The processor may comprise any computer operating environment, such as hand-held devices, multiprocessor systems, microprocessor-based or programmable sender electronic devices, minicomputers, mainframe computers, and the like. The processor may also be practiced in distributed computing environments where tasks are performed by remote processing devices. Furthermore, the processor may comprise a mobile terminal, such as a smart phone, a cellular telephone, a cellular telephone utilizing wireless application protocol (WAP), personal digital assistant (PDA), intelligent pager, portable computer, a hand held computer, or a wireless fidelity (Wi-Fi) access point. The aforementioned systems and devices are examples and the processor may comprise other systems or devices.

FIG. **12** is a flow chart setting forth the general stages involved in method **1200** for determining an amount of wire remaining in multiple conductor container **900**. Method **1200** may be implemented using, for example, computer **1100** as described in more detail above. Ways to implement the stages of method **1200** will be described in greater detail below.

Method **1200** may begin at starting block **1205** and proceed to stage **1210** where computer **1100** may receive input. For example, after using some of the conductor in multiple conductor container **900**, an electrician may input information into computer **1100**. For instance, the electrician may input the graduation displayed on label **1000** and other information such as wire size, container size, etc. Some of the inputs may be received by computer **1100** reading barcode **1006** on label **1000**. In other words, the electrician may read and input the graduation reading into computer **1100**. The electrician may cause computer **1100** to read barcode **1006** to gather any other information needed to calculate the amount of wire remaining in multiple conductor container **900**. As an alternative or in addition to the graduation reading, the electrician may enter a weight of multiple conductor container **900** or a total resistance of the wire remaining in multiple conductor container **900**.

From stage **1210**, where computer **1100** received the input, method **1200** may advance to stage **1215** where computer **1100** may calculate an amount of conductor remaining in multiple conductor container **900**. For example, computer **1100** may use a formula stored in memory unit **1114** to calculate the remaining amount of wire. Barcode **1006**, for example, may provide computer **1100** with information needed to retrieve information about multiple conductor container **900** and/or about the contents of multiple conductor container **900** from a manufacturer via the internet, for example. After reading barcode **1006**, computer **1100** may obtain a calibration scale for graduations **902**. In addition, barcode **1006** may allow computer **1100** to retrieve information that may be combined with other data from the electrician to determine an amount of conductor in multiple conductor container **900**. For example, after reading barcode **1006**, the electrician may input a property such as, for example, the weight of multiple conductor container **900** or the overall resistance of the conductor remaining in multiple conductor container **900**. For this information, computer **1100** may calculate the amount of conductor remaining in multiple conductor container **900**.

From stage **1215**, where computer **1100** calculates the remaining amount of wire in multiple conductor container **900**, method **1200** may advance to stage **1220** where computer **1100** may display the remaining amount of wire in multiple conductor container **900**. In addition, computer

1100 may transmit the remaining amount of wire in multiple conductor container **900** to a supplier, manufacturer, or other entity. For example, computer **1100** may transmit the remaining amount of conductor to a supplier notifying the supplier that the electrician may need more wire. In addition, if there is some defect with multiple conductor container **900** or the conductor located therein, the supplier or manufacturer may be notified and the electrician given a credit, discount, or other monetary compensation. From stage **1220**, where computer **1100** may transmit data, method **1200** may end at stage **1225**.

FIG. **13** shows a flow chart for a process **1300** for packaging multiple conductors. First, in stage **1302**, the multiple conductors may be fed from a payoff reel. The payoff reel may be part of a production line. For example, as the multiple conductors are being manufactured they may be fed to a take-up reel. After the multiple conductors are manufactured, the take-up reel may be stored for use in process **1300** either immediately or at a later day. The take-up reel may be any container suitable for storing the multiple conductors. For example, the multiple conductors may be stored in stems, barrel, reels, or as coils.

After the multiple conductors are manufactured and fed to the take-up reel, process **1300** may proceed to stage **1304** where the multiple conductors may pass through a tension equalization fixture (shown in FIG. **14**). The tension equalization fixture may comprise a wire straightener **1406** (shown in FIG. **14**). The wire straightener may help remove memory or twist in the wire that may have developed while feeding the multiple conductors from a payoff reel or a production line. For example, wire straightener **1406** may comprise a set of rollers that the multiple conductors may pass through. The height of the rollers may be adjusted to increase or decrease the pressure on the conductors. The increase or decrease in pressure may act to further straighten the wires.

After the multiple conductors pass through the tension equalization fixture, process **1300** may proceed to stage **1306** where the multiple conductors may pass through a monitoring station **1400**, shown in FIG. **14**. Monitoring station **1400** may comprise a plurality of optical sensors **1402**. Plurality of optical sensors **1402** may utilize lasers and a Doppler Effect to measure a speed the conductors travel. In addition, the plurality of optical sensors **1402** may measure a length of the conductors. For example, the conductors may travel through a guide **1404** (shown in greater detail in FIG. **15**).

Monitoring station **1400** may allow a user to detect problems with laying the multiple conductors in multiple conductor container assembly **100**. For example, as shown in FIG. **15**, a first conductor **1502** and a second conductor **1506** may pass through one of a plurality of guide holes **1504** located in guide **1404**. Monitoring station **1400** may monitor the length of each of the conductors being fed into multiple conductor container assembly **100**. If the length or amount of each conductor being fed into multiple conductor container assembly **100** varies by a preset margin, process **1300** may terminate or an operator may be notified. After process **1300** terminates or the operator is notified, corrective measures may be taken. The preset margin may be measured as a percentage of total feet or a percentage of feet for a given feed rate. For example, first conductor **1502** may feed at a faster rate than second conductor **1506**. To ensure that roughly the same amount of first conductor **1502** and second conductor **1506** are laid in multiple conductor container assembly **100**, may alert the operator when the dif-

ference between the amount of first conductor **1502** and second conductor **1506** exceeds a certain amount.

After the multiple conductors pass through monitoring station **1400**, process **1300** may proceed to stage **1308** where the multiple conductors may be fed from monitoring station **1400** to a tension equalization capstan **1600** (shown in FIG. **16**). Tension equalization capstan **1600** may assist the conductors to flow smoothly. Tension equalization capstan **1600** may pull the conductors from the payoff reel through monitoring station **1400**. Tension equalization capstan **1600** may assist in minimizing and/or eliminating variables such as wire bends, issues with stiff wires, and tangles.

Tension equalization capstan **1600** may be a motor driven drum that may rotate at a constant speed. In addition, tension equalization capstan **1600** may comprise multiple motor driven drums. For example, each conductor may have its own motor driven drum that may operate at differing speeds than other motor driven drums. Tension equalization capstan **1600** may rotate at the constant speed regardless of a speed other capstans. The speed at which tension equalization capstan **1600** rotates may be set higher than a highest speed the multiple conductors may be fed at. The highest speed may be the actual speed the multiple conductors are fed to multiple conductor container assembly **100** or it may be an anticipated highest speed.

During operation, the multiple conductors may be in a loosely or tightly wrapped around drum **1602**. For example, if the multiple conductors are being pulled, they may be wrapped around drum **1602** tighter than if they were not being pulled. Drum **1602** may be rotating in the direction the multiple cables are traveling. If there is no tension on the multiple conductors, drum **1602** may rotate without moving the multiple conductors moving. This rotation without the multiple conductors moving may facilitate a smooth flow of wire between the tension equalization capstan and multiple conductor container assembly **100**.

Drum **1602** may have a finely machined finish. The finely machined finish may be located on the exterior of drum **1602** where the multiple conductors contact the drum **1602**. The finely machined finish may allow the drum to rotate freely when no or little tension is on the multiple conductors. The finely machined finish may also allow the drum to feed the multiple conductors. As shown in FIG. **16**, drum **1602** may also comprise a plurality of grooves **1604**. Grooves **1604** may assist in keeping the multiple conductors from becoming tangled or crossing one another.

Tension equalization capstan **1600** may also comprise a guide **1606**, which may be similar to guide **1404** shown in FIG. **15**, having a plurality of holes. Each hole may receive one of the multiple conductors. Guide **1606** may assist in keeping the multiple conductors separate and may help hinder the multiple conductors from drifting and becoming tangled.

From stage **1308** where the multiple conductors may be fed to tension equalization capstan **1600**, process **1300** may proceed to stage **1310** where a variable speed drive system **1700** (shown in FIGS. **17A** and **17B**) may package the multiple conductors.

During process **1300**, each of the multiple conductors may be fed from tension equalization capstan **1600** to variable speed drive system **1700**. Variable speed drive system **1700** may comprise a drive wheel **1702**, a pressure roller **1704**, a feed channel **1706**, and a feed tube **1708**. During operation, the multiple conductors may be fed through drive wheel **1702** and pressure roller **1704**. The rotation drive wheel **1702** may pull the multiple conductors and cause them to tighten around drum **1602** and may cause

the multiple conductors to move in unison. The pressure applied by pressure roller 1704 to drive wheel 1702 may assist drive wheel 1702 in gripping the multiple conductors. For example, if the multiple conductors have lubricated insulation, pressure may be applied via pressure roller 1704 to increase the friction between drive wheel 1702 and the lubricated insulation. This increased friction may assist in minimizing slippage between drive wheel and the multiple conductors.

Pressure roller 1704 may apply pressure via a hydraulic, pneumatic, or electric actuator. Pressure roller 1704 may comprise grooves or protrusions (1710 in FIG. 17B) that may mate with corresponding protrusion or grooves (1712 in FIG. 17B) in drive wheel 1702 to assist in increasing a contact surface area. The increased contact surface area may assist in minimizing slippage when a lubricated wire is used.

The multiple conductors may exit drive wheel 1702 and enter feed channel 1706. From feed channel 1706, the multiple conductors may enter feed tube 1708 where they may feed into multiple conductor container assembly 100. Feed channel 1706 may assist in orienting the multiple conductors. The orientation may allow the multiple conductors to be laid in a manner such that any memory or twist in the multiple conductors may enter multiple conductor container assembly 100 in coincide with one another. In other words the feed channel 1706 may cause the multiple conductors to have a singular memory. A singular memory may comprise any memory or twist in each of the conductors coinciding with any memory or twist of other conductors.

FIG. 17C shows an embodiment of drive wheel 1702 and pressure roller 1704. As shown in FIG. 17C, drive wheel 1702 may comprise multiple sections (e.g., a first section 1714, a second section 1716, a third section 1718, and a fourth section 1720). The multiple sections may be of equal diameter. Pressure roller 1704 may comprise multiple sections (e.g., a fifth section 1722, a sixth section 1724, a seventh section 1726, and an eighth section 1728). The sections of pressure roller 1704 may comprise tenons 1730. Drive wheel 1702 may comprise grooves 1732. During operation, tenons 1730 may nestle within grooves 1732. The tolerances between grooves 1732 and tenons 1730 may be such that during operation the conductors sandwiched between the pressure roller 1704 and drive wheel 1702 have very little room to move vertically or laterally. The tight tolerances may also help to prevent damage to the conductors and any sheathing that may cover the conductors. In addition, the tight tolerances help to ensure that a consistent length of conductor is being fed with each revolution of the drive wheel 1702.

Multiple conductors (e.g., a first conductor 1734, a second conductor 1736, a third conductor 1738, and a fourth conductor 1740) may pass between drive wheel 1702 and pressure roller 1704. During installation of the multiple conductors into multiple conductor container assembly 100, drive wheel 1702 may rotate at a predetermined speed. Depending on the diameter of drive wheel 1702, each revolution of drive wheel 1702 may advance a given amount to the multiple conductors. For example, the multiple sections of drive wheel 1702 may have a diameter of six-inches. For a six-inch diameter, the drive wheel may advance the multiple conductors approximately 19 inches per revolution. Grooves 1732 and tenons 1730 may be coated with a material (e.g., rubber) to help increase friction between drive wheel 1702 and the multiple conductors.

The multiple sections of drive wheel 1702 may rotate in unison or they may rotate independently of each other. For example, the multiple sections of drive wheel 1702 may

share a common axel 1742. One revolution of axel 1742 may cause each of the multiple sections to rotate one revolution. Each of the multiple sections may also rotate on respective independent axes (not shown). For example, first section 1714 may be connected to a first axis (not shown) that may be driven by a first motor (not shown), second sections 1716 may be connected to a second axis (not shown) that may be driven by a second motor (not shown), etc. Because the multiple sections are independent of each other, the speed of each may be increased or decreased without affecting the speed of others. In addition to a single drive wheel, embodiments may comprise multiple drive wheels and multiple pressure rollers.

FIG. 17D shows an embodiment of drive wheel 1702 and pressure roller 1704. As shown in FIG. 17D, drive wheel 1702 may comprise multiple sections (e.g., first section 1714, second section 1716, third section 1718, and fourth section 1720). The multiple sections may be of unequal diameter. For example, first section 1714 may be six-inches in diameter and fourth section 1720 may be three-inches in diameter. Pressure roller 1704 may comprise multiple sections (e.g., fifth section 1722, sixth section 1724, seventh section 1726, and eighth section 1728). The sections of pressure roller 1704 may comprise tenons 1730. Drive wheel 1702 may comprise grooves 1732. During operation the tenons 1730 may nestle within grooves 1732.

Multiple conductors (e.g., first conductor 1734, second conductor 1736, third conductor 1738, and fourth conductor 1740) may pass between drive wheel 1702 and pressure roller 1704. During installation of the multiple conductors into multiple conductor container assembly 100, drive wheel 1702 may rotate at a predetermined speed. Depending on the diameter of each section of drive wheel 1702, each revolution of drive wheel 1702 may advance a given amount to the multiple conductors. For example, first section 1714 of drive wheel 1702 may have a diameter of six-inches and fourth section of drive wheel 1702 may have a diameter of three-inches. For the six-inch diameter first section 1714 may advance first conductor 1734 approximately 19 inches per revolution and the three-inch diameter fourth section 1720 may advance fourth conductor 1740 approximately 9.5 inches per revolution. Grooves 1732 and tenons 1730 may be coated with a material (e.g., rubber) to help increase friction between drive wheel 1702 and the multiple conductors.

The multiple sections of drive wheel 1702 may rotate in unison or they may rotate independently of each other. For example, the multiple sections of drive wheel 1702 may share a common axel 1742. One revolution of axel 1742 may cause each of the multiple sections to rotate one revolution. Each of the multiple sections may also rotate on respective independent axes (not shown). For example, first section 1714 may be connected to a first axis (not shown) that may be driven by a first motor (not shown), second sections 1716 may be connected to a second axis (not shown) that may be driven by a second motor (not shown), etc. Because the multiple sections are independent of each other, the speed of each may be increased or decreased without affecting the speed of others. In addition to a single drive wheel, embodiments may comprise multiple drive wheels and multiple pressure rollers.

FIGS. 18A and 18B show a method and configuration that may be implemented to lay multiple conductors in multiple conductor container assembly 100 with first conductor 202 and second conductor 204. In the embodiment shown in FIG. 18A, multiple conductor container assembly 100 may be located proximate feed tube 1708. Feed tube 1708 may

feed first conductor **202** and second conductor **204** at a constant or variable speed as indicated by arrow **1804**. While first conductor **202** and second conductor **204** is being fed from feed tube **1708**, multiple conductor container assembly **100** may be rotated about an axis **1806** as indicated by arrow **1808**. During loading of multiple conductor container assembly **100** with first conductor **202** and second conductor **204**, the rotational speed of multiple conductor container assembly **100** may be constant or variable.

Consistent with embodiments of the invention, feed tube **1708** may feed first conductor **202** and second conductor **204** at a constant speed and multiple conductor container assembly **100** may rotate at a constant speed. In addition, feed tube **1708** may feed first conductor **202** and second conductor **204** at a variable speed and multiple conductor container assembly **100** may rotate at a constant speed. Furthermore, feed tube **1708** may feed first conductor **202** and second conductor **204** at a variable speed and multiple conductor container assembly **100** may rotate at a constant speed. Moreover, consistent with embodiments of the invention, feed tube **1708** may feed first conductor **202** and second conductor **204** at a variable speed and multiple conductor container assembly **100** may rotate at a variable speed. By varying the feed first conductor **202** and second conductor **204** and/or the speed at which multiple conductor container assembly **100**, the placement location of first conductor **202** and second conductor **204** in multiple conductor container assembly **100** may be controlled.

Also, during manufacturing, feed tube **1708** may be stationary or it too, may rotate. For example, consistent with embodiments of the invention, both feed tube **1708** and multiple conductor container assembly **100** (as indicated in FIG. **18A** by assembly **1810**) may rotate about axis **1812** as indicated by arrow **1814**. While assembly **1810** may be rotating about axis **1812**, multiple conductor container assembly **100** may or may not be rotating about axis **1806** as described above. In this way, the placement location of first conductor **202** and second conductor **204** in multiple conductor container assembly **100** may be controlled. In addition and as described above the feed rate for feed tube **1708** may be constant or variable and the rotation of multiple conductor container assembly **100** about axis **1806** may be constant or variable.

In addition, while FIGS. **18A** and **18B** show two cables (first conductor **202** and second conductor **204**) being installed in multiple conductor container assembly **100**, there may be a second cable feeding assembly that may feed a third cable or feed tube **1708** may feed a third cable. For instance, FIG. **2** shows first conductor **202** and second conductor **204** located in multiple conductor container assembly **100**. To achieve this configuration, there may be a second feed tube that lays the third conductor simultaneously with first conductor **202** and second conductor **204**. Or each cable located in multiple conductor container assembly **100** may be laid down in separate stages. For example, first conductor **202** may be loaded in multiple conductor container assembly **100** at a first loading stage and second conductor **204** may be loaded in multiple conductor container assembly **100** at a second loading stage.

FIG. **19** shows a flow chart for a method **1900** for using multiple conductor container assembly **100**. In other words, FIG. **19** shows a flow chart for method **1900** where a non-rotating container is use to payoff multiple conductors. Method **1900** may begin at stage **1902** where multiple conductor container assembly **100** may be positioned at a job site. For example, multiple conductor container assembly **100** may be placed in a desired location using a cart as

described in U.S. Patent Application having Ser. No. 61/536,786, which is hereby incorporated by reference in its entirety.

After multiple conductor container assembly **100** is located at the job site, method **1900** may proceed to stage **1904** where a user may set up multiple conductor container assembly **100**. For example, the user may feed first conductor **202** and second conductor **204** from multiple conductor container assembly **100** through container tap wire guide **302**. From container tap wire guide **302** the user may connect the multiple conductors to a pulling apparatus (e.g., electrician's fish tape).

After setting up multiple conductor container assembly **100**, the user may payoff the multiple conductors from multiple conductor container assembly **100**. For example, the user may pull the fish tape through a conduit. As the fish tape is pulled through the conduit, the multiple conductors may payoff from multiple conductor container assembly **100** and be pulled through the conduit.

FIG. **20** shows the multiple conductor container assembly **100** and a coupler **2010** through which the multiple conductors may pass as the multiple conductors payoff from multiple conductor container assembly **100**. As shown in FIG. **20**, each of the multiple conductors may have varying lengths prior to passing through the coupler **2010**. This may cause at least one of the multiple conductors to form a bow prior to passing through the coupler **2010**. As the multiple conductors pass through the coupler **2010**, a bow that exists prior to passing through the coupler **2010** is not allowed to pass. This may restrict the multiple conductors to pass through the coupler **2010** at the same rate, and equivalently, at the same length. Furthermore, the coupler **2010** may assist in indicating a tangle within the multiple conductors coming as they come out of the multiple conductor container assembly **100**. If a conductor should become tangled, the coupler **2010** may correct a tangle in the conductor once it has happened. The coupler **2010** may also identify which conductors are too short or too long in comparison to the multiple conductors passing through the coupler **2010**. Moreover, the coupler **2010** allows a central point to true the wires back together. The coupler **2010** may be arranged such that it remains within multiple conductor container assembly **100** when the multiple individually sheathed conductors are paying off from such assembly. More specifically, the coupler **2010** may be arranged such that it remains below the top edge of the core centered within the multiple conductor container assembly **100**.

As shown in FIG. **21**, the coupler **2010** may be located amongst the layered multiple individually sheathed conductors within the multiple conductor container assembly **100**. In FIG. **21**, the multiple individually sheathed conductors may be coupled prior to the conductors paying off through the opening of the multiple conductor container assembly **100**. Coupling or restricting the multiple conductors prior to the conductors paying off through the opening of the multiple conductor container assembly **100** may provide a constant grouping point on multiple conductors while moving within the multiple conductor container assembly **100**. As the multiple individually sheathed conductors payoff, the coupler **2010** may move within the multiple conductor container assembly **100** as the container assembly remains stationary. The coupler **2010** in FIG. **21** also may act as an indicator or correct point to lift conductors out of the multiple conductor container assembly **100** if an end of a conductor is dropped back into the multiple conductor container assembly **100** by mistake.

The coupler **2010** may comprise any suitable material strong enough to contain the multiple individually sheathed conductors as such conductors pass through coupler **2010** but light enough to not impose an additional burden on paying off such conductors from the multiple conductor container assembly **100**. For example, the coupler **2010** may comprise plastic, including polyvinyl chloride, aluminum, copper, silicon, or any combination thereof. Likewise, the coupler **2010** may maintain a smooth inner surface so as to not create friction and wear-and-tear on the multiple conductors as the multiple conductors pass through coupler **2010**. Furthermore, while the coupler **2010** is shown in FIGS. **20-21** as being circular, embodiments may comprise other shapes. For example, the coupler **2010** may be square, rectangular, spherical, or any other appropriate shape. Moreover, the coupler **2010** may comprise various lengths, inner diameters, and outer diameters. Preferably, a length of the coupler **2010** may be between 0.5"-4" or other varying lengths. More preferably, a length of the coupler **2010** may be between 1"-2.5". In addition, more than one coupler **2010** may be employed to couple the multiple conductors paying off from multiple conductor container assembly **100**.

As indicated above, the coupler **2010** may be implemented in the multiple conductor container assembly **100** to payoff multiple individually sheathed conductors. A non-rotating multiple conductor container assembly **100** may be used to payoff multiple conductors. After the multiple conductor container assembly **100** is placed in a desired location using a cart, a user may prepare the multiple conductor container assembly **100** for payoff. For example, the user may feed first conductor and second conductor through coupler **2010** as part of the payoff of these conductors from multiple conductor container assembly **100**.

FIG. **22** is a block diagram of an operating environment **2200** for providing conductor identification in accordance with embodiments of the disclosure. As shown in FIG. **22**, operating environment **2200** may comprise multiple conductor container assembly **100** and container tap wire guide **302** as described above. A first conductor **2205** and a second conductor **2210** may be pulled from multiple conductor container assembly **100** through container tap wire guide **302**. While operating environment **2200** may show two conductors, any number of conductors may be used. Consistent with embodiments of the disclosure, first conductor **2205** and second conductor **2210** may be undistinguishable from one another in that they may look alike. For example, first conductor **2205** and second conductor **2210** may comprise the same color, the same size, may comprise the same markings or striping, or may have no markings or striping.

First conductor **2205** and second conductor **2210** may be pulled into a conduit **2215** disposed in a panel **2220**. Prior to being pulled into conduit **2215**, first tag **2225** may be placed on a first end of first conductor **2205** and a second tag **2230** may be placed on a first end of second conductor **2210**. First tag **2225** may include a first tag indicia **2235** and second tag **2230** may include a second tag indicia **2240**. First tag indicia **2235** and second tag indicia **2240** may be different from one another. For example, first tag indicia **2235** and second tag indicia **2240** may comprise numbers, letters, alphanumeric sequences, symbols, colors, or any combination thereof that may make first tag indicia **2235** and second tag indicia **2240** different from one another.

In addition to first tag **2225** and second tag **2230**, a first sleeve **2245** may be placed around first conductor **2205** and a second sleeve **2250** may be placed around second conductor **2210** respectively. First sleeve **2245** may comprise, for example, a cylinder, a clip, a "key-ring", a carabiner, a

serpentine helical spring, or any type construction that may allow first sleeve **2245** to be secured to and freely slide along first conductor **2205**. First sleeve **2245** may be placed around first conductor **2205** without having to thread an open end of first conductor **2205** through first sleeve **2245**. For example, a clip or carabiner construction may be clipped onto and around first conductor **2205**, a serpentine helical spring construction may be wrapped onto and around first conductor **2205**, and a key-ring construction may be spiraled onto and around first conductor **2205**.

Similarly, second sleeve **2250** may comprise, for example, a cylinder, a clip, a "key-ring", a carabiner, a serpentine helical spring, or any type construction that may allow second sleeve **2250** to be secured to and freely slide along second conductor **2210**. Second sleeve **2250** may be placed around second conductor **2210** without having to thread an open end of second conductor **2210** through second sleeve **2250**. For example, a clip or carabiner construction may be clipped onto and around second conductor **2210**, a serpentine helical spring construction may be wrapped onto and around second conductor **2210**, and a key-ring construction may be spiraled onto and around second conductor **2210**.

First sleeve **2245** may include a first sleeve indicia **2255** and second sleeve **2250** may include a second sleeve indicia **2260**. For example, first sleeve indicia **2255** and second sleeve indicia **2260** may comprise numbers, letters, alphanumeric sequences, symbols, colors, or any combination thereof that may make first sleeve indicia **2255** and second sleeve indicia **2260** different from one another.

First sleeve indicia **2255** may correspond to first tag indicia **2235** and second sleeve indicia **2260** may correspond to second tag indicia **2240**. First sleeve indicia **2255** may not correspond to second tag indicia **2240** and second sleeve indicia **2260** may not correspond to first tag indicia **2235**. In other words, first tag indicia **2235** and first sleeve indicia **2255** may have a visual or physical appearance that makes it clear to an observer that they correspond to one another and that they do not correspond to second tag indicia **2240** and second sleeve indicia **2260**. Likewise, second tag indicia **2240** and second sleeve indicia **2260** may have a visual or physical appearance that makes it clear to an observer that they correspond to one another and that they do not correspond to first tag indicia **2235** and second sleeve indicia **2260**.

A first harness **2265** may be placed between the sleeves (e.g., first sleeve **2245** and second sleeve **2250**) and conduit **2215**. A second harness **2270** may be placed between the sleeves (e.g., first sleeve **2245** and second sleeve **2250**) and container tap wire guide **302**. While FIG. **22** shows first sleeve **2245**, second sleeve **2250**, first harness **2265**, and second harness **2270** disposed between conduit **2215** and collar **510**, embodiments of the disclosure are not so limited. For example, first sleeve **2245**, second sleeve **2250**, first harness **2265**, and second harness **2270** may be disposed on the conductor container assembly **100** side of collar **510** between collar **510** and conductor container assembly **100** or in conductor container assembly **100**. When first sleeve **2245**, second sleeve **2250**, first harness **2265**, and second harness **2270** are disposed on the conductor container assembly **100** side of collar **510**, collar **510** may inhibit first sleeve **2245**, second sleeve **2250**, first harness **2265**, and second harness **2270** from sliding beyond container tap wire guide **302** when first conductor **2205** and second conductor **2210** are pulled into conduit **2215**.

First harness **2265** may be affixed, for example, it may be attached to conduit **2215** or panel **2220**. Second harness

2270 may be affixed, for example, it may be attached to panel 2220, container tap wire guide 302, collar 510, or multiple conductor container assembly 100. In this way, after first conductor 2205 and second conductor 2210 are pulled and then cut below second harness 2270, second harness 2270 may keep first sleeve 2245 and second sleeve 2250 from falling away from first conductor 2205 and second conductor 2210 respectively. Rather second harness 2270 may serve as a back stop for first sleeve 2245 and second sleeve 2250. FIG. 23 is a flow chart setting forth the general stages involved in a method 2300 consistent with an embodiment of the disclosure for providing conductor identification. Method 2300 may be implemented using operating environment 2200 as described in more detail above with respect to FIG. 22. Ways to implement the stages of method 2300 will be described in greater detail below.

Method 2300 may begin at starting block 2305 and proceed to stage 2310 where first sleeve 2245 may be placed around first conductor 2205. For example, a technician may wish to pull first conductor 2205 and second conductor 2210 through conduit 2215 in panel 2220 from multiple conductor container assembly 100. First conductor 2205 and second conductor 2210 may be undistinguishable from one another in that they may look alike. For example, first conductor 2205 and second conductor 2210 may comprise the same color, the same size, and may comprise the same markings or striping. Because first conductor 2205 and second conductor 2210 may be undistinguishable, a first end of the conductors pulled to the far end of conduit 2215 may be confused at a second end of the conductors at the panel 2220 end (e.g., near end) of conduit 2215. Consequently, first sleeve 2245 may be placed around first conductor 2205 to identify first conductor 2205 as first conductor 2205 when it is pulled through conduit 2215 and first sleeve 2245.

From stage 2310, where first sleeve 2245 is placed around first conductor 2205, method 2300 may advance to stage 2320 where second sleeve 2250 may be placed around second conductor 2210. For example, because first conductor 2205 and second conductor 2210 may be undistinguishable, the first end of the conductors pulled to the far end of conduit 2215 may be confused at the second end of the conductors at the panel 2220 end (e.g., near end) of conduit 2215. Consequently, second sleeve 2250 may be placed around second conductor 2210 to identify second conductor 2210 as second conductor 2210 as it is pulled through conduit 2215 and second sleeve 2250.

Once second sleeve 2250 is placed around second conductor 2210 in stage 2320, method 2300 may continue to stage 2330 where first tag 2225 may be placed on first conductor 2205. For example, first tag 2225 may be placed on the first end of first conductor 2205 before it is pulled into conduit 2215.

After first tag 2225 is placed on first conductor 2205 in stage 2330, method 2300 may proceed to stage 2340 where second tag 2230 may be placed on second conductor 2210. For example, second tag 2230 may be placed on the first end of second conductor 2210 before it is pulled into conduit 2215.

As stated above, first tag 2225 may include first tag indicia 2235 and second tag 2230 may include second tag indicia 2240. First tag indicia 2235 and second tag indicia 2240 may be different from one another. For example, first tag indicia 2235 and second tag indicia 2240 may comprise numbers, letters, alphanumerical sequences, symbols, colors, or any combination thereof that may make first tag indicia 2235 and second tag indicia 2240 different from one another. Moreover, first sleeve 2245 may include first sleeve

indicia 2255 and second sleeve 2250 may include second sleeve indicia 2260. For example, first sleeve indicia 2255 and second sleeve indicia 2260 may comprise numbers, letters, alphanumerical sequences, symbols, colors, or any combination thereof that may make first sleeve indicia 2255 and second sleeve indicia 2260 different from one another.

First sleeve indicia 2255 may correspond to first tag indicia 2235 and second sleeve indicia 2260 may correspond to second tag indicia 2240. First sleeve indicia 2255 may not correspond to second tag indicia 2240 and second sleeve indicia 2260 may not correspond to first tag indicia 2235. In other words, first tag indicia 2235 and first sleeve indicia 2255 may have a visual or physical appearance that makes it clear to an observer that they correspond to one another and that they do not correspond to second tag indicia 2240 and second sleeve indicia 2260. Likewise, second tag indicia 2240 and second sleeve indicia 2260 may have a visual or physical appearance that makes it clear to an observer that they correspond to one another and that they do not correspond to first tag indicia 2235 and first sleeve indicia 2255.

Once second tag 2230 is placed on second conductor 2210 in stage 2340, method 2300 may continue to stage 2350 where first conductor 2205 and second conductor 2210 may be pulled together through conduit 2215. As first conductor 2205 and second conductor 2210 are pulled together through conduit 2215, first conductor 2205 may slideably move through first sleeve 2245 and second conductor 2210 may slideably move through second sleeve 2250. As first conductor 2205 slideably moves through first sleeve 2245 and second conductor 2210 slideably moves through second sleeve 2250 during the pull, first sleeve 2245 and second sleeve 2250 may not enter conduit 2215. Rather first sleeve 2245 and second sleeve 2250 may remain between conduit 2215 and multiple conductor container assembly 100 during the pull with first conductor 2205 and second conductor 2210 respectively sliding through first sleeve 2245 and second sleeve 2250 during the pull.

When the pull is complete, the first end of first conductor 2205 and the first end of second conductor 2210 may be at the far end of conduit 2215 and tagged with first tag 2225 and second tag 2230 respectively at the far end. The second end of first conductor 2205 and the second end of second conductor 2210 may be at the near end of conduit 2215 and may still have first sleeve 2245 and second sleeve 2250 respectively around them. At the near end of conduit 2215, a technician may cut first conductor 2205, remove first sleeve 2245, and tag the second end (e.g., near end) with a tag corresponding to first sleeve indicia 2255. In this way, the first end of first conductor 2205 (e.g., at the far end of conduit 2215) and the second end of first conductor 2205 (e.g., at the near end of conduit 2215) may comprise corresponding tags. Rather than tagging the second end of first conductor 2205, the second end of first conductor 2205 may be terminated in panel 2220 at a first predetermined location.

Similarly, at the near end of conduit 2215, a technician may cut second conductor 2210, remove second sleeve 2250, and tag the second end (e.g., near end) with a tag corresponding to second sleeve indicia 2260. In this way, the first end of second conductor 2210 (e.g., at the far end of conduit 2215) and the second end of second conductor 2210 (e.g., at the near end of conduit 2215) may comprise corresponding tags. Rather than tagging the second end of second conductor 2210, the second end of second conductor 2210 may be terminated in panel 2220 at a second predetermined location. Consequently, consistent with embodiments of the disclosure, opposite ends of undistinguishable

conductors may be identified. Once first conductor **2205** and the second conductor **2210** are pulled together through conduit **2215** in stage **2350**, method **2300** may then end at stage **2360**.

Embodiments, for example, may be implemented as a computer process (method), a computing system, or as an article of manufacture, such as a computer program product or computer readable media. The computer program product may be a computer storage media readable by a computer system and encoding a computer program of instructions for executing a computer process. The computer program product may also be a propagated signal on a carrier readable by a computing system and encoding a computer program of instructions for executing a computer process. Accordingly, the present invention may be embodied in hardware and/or in software (including firmware, resident software, microcode, etc.). In other words, embodiments of the present invention may take the form of a computer program product on a computer-usable or computer-readable storage medium having computer-usable or computer-readable program code embodied in the medium for use by or in connection with an instruction execution system. A computer-usable or computer-readable medium may be any medium that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

The computer-usable or computer-readable medium may be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, device, or propagation medium. More specific computer-readable medium examples (a non-exhaustive list), the computer-readable medium may include the following: an electrical connection having one or more wires, a portable computer diskette, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, and a portable compact disc read-only memory (CD-ROM). Note that the computer-usable or computer-readable medium could even be paper or another suitable medium upon which the program is printed, as the program can be electronically captured, via, for instance, optical scanning of the paper or other medium, then compiled, interpreted, or otherwise processed in a suitable manner, if necessary, and then stored in a computer memory.

While certain embodiments have been described, other embodiments may exist. Furthermore, although embodiments have been described as being associated with data stored in memory and other storage mediums, data can also be stored on or read from other types of computer-readable media, such as secondary storage devices, like hard disks, floppy disks, or a CD-ROM, a carrier wave from the Internet, or other forms of RAM or ROM. Further, the disclosed methods' stages may be modified in any manner, including by reordering stages and/or inserting or deleting stages, without departing from the invention.

Embodiments, for example, are described above with reference to block diagrams and/or operational illustrations of methods, systems, and computer program products according to embodiments of the invention. The functions/acts noted in the blocks may occur out of the order as shown in any flowchart. For example, two blocks shown in succession may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

Both the foregoing general description and the following detailed description are examples and explanatory only, and should not be considered to restrict the invention's scope, as

described and claimed. Further, features and/or variations may be provided in addition to those set forth herein. For example, embodiments may be directed to various feature combinations and sub-combinations described herein.

While certain embodiments of the invention have been described, other embodiments may exist. While the specification includes examples, the invention's scope is indicated by the following claims. Furthermore, while the specification has been described in language specific to structural features and/or methodological acts, the claims are not limited to the features or acts described above. Rather, the specific features and acts described above are disclosed as examples for embodiments of the invention.

What is claimed is:

1. An apparatus comprising:

a first sleeve around a first conductor, the first sleeve comprising a first sleeve indicia, the first conductor having a first tag attached to a first end of the first conductor, the first tag comprising a first tag indicia corresponding to the first sleeve indicia, the first conductor being slideably moveable through the first sleeve; and

a second sleeve around a second conductor, the second sleeve comprising a second sleeve indicia, the second conductor having a second tag attached to a first end of the second conductor, the second tag comprising a second tag indicia corresponding to the second sleeve indicia, the second conductor being slideably moveable through the second sleeve, the first sleeve indicia not corresponding to the second tag indicia and the second sleeve indicia not corresponding to the first tag indicia, the first conductor and the second conductor being paired together for pulling through a conduit,

wherein the first sleeve indicia and first tag indicia are selected from at least one of the following: a first alphanumeric sequence, a first set of numbers, a first set of letters, a first set of symbols, a first set of colors, and combinations thereof.

2. The apparatus of claim 1, wherein the second sleeve indicia and second tag indicia are selected from at least one of the following: a second alphanumeric sequence, a second set of numbers, a second set of letters, a second set of symbols, a second set of colors, and combinations thereof.

3. The apparatus of claim 2, wherein the second sleeve indicia and second tag indicia comprise a second alphanumeric sequence.

4. The apparatus of claim 2, wherein the second sleeve indicia and second tag indicia comprise a second set of numbers.

5. The apparatus of claim 2, wherein the second sleeve indicia and second tag indicia comprise a second set of letters.

6. The apparatus of claim 2, wherein the second sleeve indicia and second tag indicia comprise a second set of symbols.

7. The apparatus of claim 2, wherein the second sleeve indicia and second tag indicia comprise a second set of colors.

8. The apparatus of claim 1, wherein the first sleeve indicia and first tag indicia comprise a first alphanumeric sequence.

9. The apparatus of claim 1, wherein the first sleeve indicia and first tag indicia comprise a first set of numbers.

10. The apparatus of claim 1, wherein the first sleeve indicia and first tag indicia comprise a first set of letters.

11. The apparatus of claim 1, wherein the first sleeve indicia and first tag indicia comprise a first set of symbols.

21

12. The apparatus of claim **1**, wherein the first sleeve indicia and first tag indicia comprise a first set of colors.

13. An apparatus comprising:

a first sleeve around a first conductor, the first sleeve comprising a first sleeve indicia, the first conductor having a first tag attached to a first end of the first conductor, the first tag comprising a first tag indicia corresponding to the first sleeve indicia, the first conductor being slideably moveable through the first sleeve; and

a second sleeve around a second conductor, the second sleeve comprising a second sleeve indicia, the second conductor having a second tag attached to a first end of the second conductor, the second tag comprising a second tag indicia corresponding to the second sleeve indicia, the second conductor being slideably moveable through the second sleeve, the first sleeve indicia not corresponding to the second tag indicia and the second sleeve indicia not corresponding to the first tag indicia,

22

the first conductor and the second conductor being paired together for pulling through a conduit, wherein the first sleeve is one of the following: a cylinder, a clip, a carabiner, a key ring and a helical spring.

14. The apparatus of claim **13**, wherein the first sleeve comprises a cylinder.

15. The apparatus of claim **13**, wherein the first sleeve comprises a clip.

16. The apparatus of claim **13**, wherein the first sleeve comprises a carabiner.

17. The apparatus of claim **13**, wherein the first sleeve comprises a key ring.

18. The apparatus of claim **13**, wherein the first sleeve comprises a helical spring.

19. The apparatus of claim **13**, wherein the second sleeve comprises at least one of a cylinder, a clip, a carabiner, a key ring or a helical spring.

20. The apparatus of claim **13**, wherein the first sleeve and the second sleeve comprise a cylinder.

* * * * *