

**(12) United States Patent**
Kalhan et al.**(10) Patent No.: US 11,950,275 B2**
(45) Date of Patent: *Apr. 2, 2024**(54) APPARATUS FOR CONTROLLING UE FOR D2D MEASUREMENT RESULTS****(71) Applicant: Kyocera Corporation, Kyoto (JP)****(72) Inventors: Amit Kalhan, San Diego, CA (US); Henry Chang, San Diego, CA (US)****(73) Assignee: Kyocera Corporation, Kyoto (JP)****(*) Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: 18/126,848**(22) Filed: Mar. 27, 2023****(65) Prior Publication Data**

US 2023/0239913 A1 Jul. 27, 2023

Related U.S. Application Data**(63)** Continuation of application No. 17/374,678, filed on Jul. 13, 2021, now Pat. No. 11,653,378, which is a continuation of application No. 16/228,251, filed on Dec. 20, 2018, now Pat. No. 11,102,794, which is a continuation of application No. 15/329,915, filed as
(Continued)**(51) Int. Cl.****H04W 72/543** (2023.01)**H04L 5/00** (2006.01)**H04W 72/54** (2023.01)**H04W 76/14** (2018.01)**(52) U.S. Cl.**CPC **H04W 72/543** (2023.01); **H04L 5/0048** (2013.01); **H04W 72/54** (2023.01); **H04W 76/14** (2018.02)**(58) Field of Classification Search**

CPC ... H04W 72/543; H04W 72/54; H04W 76/14; H04L 5/0048

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

8,787,323 B2 7/2014 Laroia et al.
10,194,452 B2 1/2019 Kalhan et al.
11,102,794 B2 8/2021 Kalhan et al.

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2013-074463 A1 5/2013
WO 2013-078946 A1 6/2013


(Continued)

OTHER PUBLICATIONS

Qualcomm Incorporated; "Reference Signal Design for D2D," R1-141963, 3GPP TSG-RAN WG1 #77; May 10, 2014; Seoul, South Korea.

Primary Examiner — Omar J Ghowrwal**(57) ABSTRACT**

A base station (eNB) determines device-to-device (D2D) transmission parameters for signal transmission over a D2D communication link between a first user equipment (UE) device and a second UE device. The eNB instructs the first UE device to transmit a reference signal that is received by the second UE device. The second UE device reports D2D channel characteristic information indicative of the received reference signal. Based on the D2D channel characteristic information, the base station determines the D2D transmission parameters and provides the parameters to the first UE device.

3 Claims, 10 Drawing Sheets

Related U.S. Application Data

application No. PCT/US2015/044075 on Aug. 6, 2015, now Pat. No. 10,194,452.

(60) Provisional application No. 62/034,951, filed on Aug. 8, 2014.

(56) **References Cited**

U.S. PATENT DOCUMENTS

11,653,378 B2 *	5/2023	Kalhan	H04W 72/543 370/329
2010/0246544 A1	9/2010	Brisebois et al.	
2014/0010172 A1	1/2014	Wei et al.	
2014/0016451 A1	1/2014	Muruganathan et al.	
2014/0233476 A1	8/2014	Kwak et al.	
2014/0321314 A1	10/2014	Fodor et al.	
2014/0328299 A1	11/2014	Kalhan et al.	
2014/0335853 A1	11/2014	Sartori et al.	
2015/0139003 A1	5/2015	Takahashi et al.	
2015/0296443 A1	10/2015	Lim et al.	
2016/0037322 A1	2/2016	Nguyen et al.	
2016/0156494 A1	6/2016	Zhao et al.	
2016/0249377 A1	8/2016	Jin et al.	
2017/0019830 A1	1/2017	Lindoff et al.	
2017/0332427 A1	11/2017	Yamazaki et al.	

FOREIGN PATENT DOCUMENTS

WO	2013-100831 A1	7/2013
WO	2014-015101 A1	1/2014

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2




FIG. 3





FIG. 4



500

FIG. 5





FIG. 6

**FIG. 7**




FIG. 8

APPARATUS FOR CONTROLLING UE FOR D2D MEASUREMENT RESULTS

CLAIM OF PRIORITY

The present application is a continuation of and claims priority to U.S. application Ser. No. 17/374,678, entitled “DEVICE-TO-DEVICE (D2D) CHANNEL MANAGEMENT WITH NETWORK-ASSISTED REFERENCE SIGNAL TRANSMISSION” and filed on Jul. 13, 2021; which is a continuation of and claims priority to U.S. application Ser. No. 16/228,251, entitled “DEVICE-TO-DEVICE (D2D) CHANNEL MANAGEMENT WITH NETWORK-ASSISTED REFERENCE SIGNAL TRANSMISSION” and filed on Dec. 20, 2018; which is a continuation of and claims priority to U.S. application Ser. No. 15/329,915, entitled “DEVICE-TO-DEVICE (D2D) CHANNEL MANAGEMENT WITH NETWORK-ASSISTED REFERENCE SIGNAL TRANSMISSION” and filed on Jan. 27, 2017; which is a national stage application of PCT/US2015/044075, entitled “DEVICE-TO-DEVICE (D2D) CHANNEL MANAGEMENT WITH NETWORK-ASSISTED REFERENCE SIGNAL TRANSMISSION” and filed on Aug. 6, 2015; which claims priority to Provisional Application No. 62/034,951 entitled “Network-Assisted D2D Transmit UE Reference Signal” and filed Aug. 8, 2014, all of which are assigned to the assignee hereof and hereby expressly incorporated by reference in their entirety.

FIELD

This invention generally relates to wireless communications and more particularly to device-to-device (D2D) channel management with network-assisted reference signal transmission.

BACKGROUND

Many wireless communication systems use base stations to provide geographical service areas where wireless communication user equipment (UE) devices communicate with the base station (evolved Node B, eNB) providing the particular geographical service area in which the wireless communication UE devices are located. The base stations are connected within a network allowing communication links to be made between the wireless communication devices and other devices. In some situations, the communication links may be between UE devices within the service area of a base station. A cellular communication link between the UE devices includes communication through the base station providing the service. Where channel quality is sufficient, the UE devices can communicate directly through a device-to-device (D2D) communication link that does not include routing data through the base station. Some situations, it may be preferred to have a direct D2D communication link between the two UE devices rather than communicating through a base station.

SUMMARY

A base station (eNB) determines device-to-device (D2D) transmission parameters for signal transmission over a D2D communication link between a first user equipment (UE) device and a second UE device. The eNB instructs the first UE device to transmit a reference signal that is received by the second UE device. The second UE device reports D2D channel characteristic information indicative of the received

reference signal. Based on the D2D channel characteristic information, the base station determines the D2D transmission parameters and provides the parameters to the first UE device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a block diagram of cellular communication system that supports device-to-device (D2D) communication where a base station (eNB) determines D2D transmission parameters for D2D communication between a first user equipment (UE) device and a second UE device based on D2D channel characteristic information determined from a reference signal received at the second UE device.

FIG. 1B is a block diagram of the communication system where the eNB instructs the first UE device to transmit a reference signal and the second UE device reports D2D channel characteristic information based on the received reference signal.

FIG. 1C is a block diagram of the communication system where the eNB instructs the first UE device and a third UE device to transmit reference signals at the same time and frequency to determine a level of interference.

FIG. 1D is a block diagram of the communication system where the eNB instructs the first UE device and a third UE device to transmit reference signals at the same time and frequency to determine a level of interference with other D2D devices.

FIG. 2 is a block diagram of an example of a UE device suitable for use as one of the UE devices.

FIG. 3 is a block diagram of an example of a base station (eNB) suitable for use as the base station (eNB) in FIG. 1.

FIG. 4 is a message diagram for an example of determining D2D transmission parameters based on network-assigned reference signal transmissions.

FIG. 5 is a message diagram for an example of determining a level of interference at the eNB 108 based on network-assigned reference signal transmissions.

FIG. 6 is a message diagram for an example of determining a level of interference at D2D UE devices based on network-assigned reference signal transmissions.

FIG. 7 is a flowchart of an example of a method of managing communication using network-assisted reference signal transmission performed at an eNB.

FIG. 8 is an illustration of an example of a transmission by a D2D UE device including reference signals.

DETAILED DESCRIPTION

FIG. 1A is a block diagram of cellular communication system 100 that supports device-to-device (D2D) communication where a base station (eNB) determines D2D transmission parameters for D2D communication between a first user equipment (UE) device 102 and a second UE device 104 based on D2D channel characteristic information determined from a reference signal received at the second UE device. For the example, each of the two UE devices 102, 104 can be a transmitting device and a receiving device although in some situations, a device may only be a receiving or transmitting device. For the example of FIG. 1A and FIG. 1B, the first UE device 102 and the second UE device 104 are within the geographic service area 106 provided by a base station (eNB) 108 and are capable of communicating over a D2D link. Even when the channel conditions may be adequate for supporting D2D communication, D2D may not be the preferred link. A D2D communication link 110, as well as a cellular communication link 112, can be estab-

lished for transmission of data between the first UE device **102** and the second UE device **104**. The D2D communication link **110** is a direct wireless communication link between the first UE device **102** and the second UE device **104** that does not route data through the base station (eNB) **108**. The cellular communication link **112** includes at least a first portion **116** from the first UE device **102** to the base station (eNB) **108** and a second portion **118** from the base station (eNB) **108** to the second UE device **104**. Therefore, sending data from the first UE device **102** to the second UE device **104** includes an uplink transmission to the eNB and a downlink transmission from the eNB to the second UE device. Uplink transmissions are transmitted in the first portion **116** over one or more uplink channels **124**. The base station **108** transmits the downlink transmissions to the second UE device **102** over one or more downlink channels **126**. The base station **108** can also transmit downlink signals to the first UE device **102** over downlink channels **128** and receive uplink signals from the second UE device over uplink channels **130**. Accordingly, for the example, the cellular communication link is bidirectional.

Sending the data from the first UE device **102** to the second UE device **104** over the D2D communication link **110** includes a D2D transmission **132** over one or more D2D transmission channels **134**. The first UE device can also receive signals from the second UE device **104** over D2D reception channels **136**. One or more of the D2D transmission channels **134** can be the same as the D2D reception channels **136**. For the examples herein, the D2D channels **134**, **136** are a subset of cellular uplink channels. In some cases, downlink channels can be used.

The base station (eNB) **108** provides wireless communication services to wireless communication user equipment (UE) devices **102**, **104** within the geographical service area **106**, sometimes referred to as a cell. Several base stations are typically interconnected through a backhaul (not shown) to provide several service areas to cover large areas. Other system components forming system entities and performing system functions such as Mobility Management Entity (MME), scheduling, gateway and other functions are omitted from FIG. 1 in the interest of brevity and clarity. Any description with reference FIG. 1 of the various functions and operations of such equipment may be implemented in any number of devices, circuits, or elements. Two or more functional blocks may be integrated in a single device, and the functions described as performed in any single device may be implemented over several devices in some circumstances. A cellular communication system is typically required to adhere to a communication standard or specification. The Third-Generation Partnership Project Long-Term Evolution (3GPP LTE) communication specification is a specification for systems where base stations (eNodeBs) provide service to wireless communication devices (user equipment (UE) devices) using orthogonal frequency-division multiplexing (OFDM) on the downlink and single-carrier frequency-division multiple access (SC-FDMA) on the uplink. Although the techniques described herein may be applied in other types of communication systems, the exemplary systems discussed herein operate in accordance with at least one revision of the 3GPP LTE communication specification.

The base station (eNB) **108** is a fixed transceiver station, sometimes referred to as an evolved Node B, eNodeB or eNB, which may include a controller in some circumstances. The base station **108** may be connected to a controller through a backhaul which may include any combination of wired, optical, and/or wireless communication channels.

The controller may include the functionality of the Mobility Management Entity (MME) and the Packet Gateway (P-GW) in a 3GPP LTE communication system.

The wireless (UE) communication devices (UE devices) **102**, **104** may be referred to as mobile devices, wireless devices, wireless communication devices, mobile wireless devices, user equipment, UEs, UE devices as well as by other terms. The UE devices **102**, **104** include electronics and code for communicating with base stations and with other wireless communication devices in D2D configurations. The UE devices may include devices such as cell phones, personal digital assistants (PDAs), wireless modem cards, wireless modems, televisions with wireless communication electronics, and laptop and desktop computers as well as other devices. The combination of wireless communication electronics with an electronic device, therefore, may form a UE device **102**, **104**. For example, a UE device may include a wireless modem connected to an appliance, computer, or television.

The base station **108** includes a wireless transceiver that exchanges wireless signals with the UE devices **102**, **104**. Transmissions from the base stations and from the UE devices **102**, **104** are governed by a communication specification that defines signaling, protocols, and parameters of the transmission. The communication specification may provide strict rules for communication and may also provide general requirements where specific implementations may vary while still adhering to the communication specification. Although the discussion below is directed to the 3GPP Long Term Evolution (LTE) communication specification, other communication specifications may be used in some circumstances. The communication specification defines at least a data channel and a control channel for uplink and downlink transmissions and specifies at least some timing and frequency parameters for physical downlink control channels from a base station to a UE device.

As discussed below in further detail, the eNB **108** instructs the first UE device **102** to transmit a reference signal. The first UE device transmits the reference signal **140** which is received by the second UE device **104**. Based on the received reference signal, the second UE device **104** determines and transmits D2D channel characteristics information **142** to the eNB **108**. Based on the D2D channel characteristics information **142**, the eNB determines the D2D transmission parameters that should be used by the first UE device **102** for D2D transmission **132** to the second UE device **104**.

FIG. 1B is a block diagram of the communication system **100** where the eNB **108** instructs the first UE device **102** to transmit a reference signal **140** and the second UE device reports D2D channel characteristic information **142** based on the received reference signal. The eNB **108** sends a reference signal transmission instruction **144** to the first UE device **102** instructing the UE device to transmit a reference signal **140**. The instruction **144** identifies the communication resources that should be used by the first UE device **102** to transmit the reference signal **140**. For the example, the instruction **144** is transmitted on a downlink channel such as the PDCCH/PDSCH or higher layer signaling. In some situations, the reference signal transmission instruction **144** can be broadcast over a System Information Block (SIB). Such as technique may be useful when a set of D2D UE devices are instructed at the same time. Other channels can be used to transmit the reference signal transmission instruction **144**.

The reference signal transmission instruction **144** specifically identifies the resources that the UE device should use

for transmitting the reference signal in some situations. In other situations, the reference signal transmission instruction **144** can identify a set of resources that the UE device may use for reference signal transmission and the UE device is instructed to autonomously select communication resources from the set to transmit a reference signal when the UE device is interested in D2D communication. For the examples, the reference signal transmission instruction **144** identifies the frequency/time communication resources for reference signal transmission and the power level for transmitting the reference signal. The power level may be based on the closed loop power control between the eNB and the first UE device. A fixed known transmission power level known to the eNB is used for the reference signal. In one example, the eNB can provide this parameter in the SIB messaging to all the UE devices. In another example, the eNB can indicate the transmission power level to the first UE device based on the received uplink power level.

The reference signal **140** is transmitted on the carrier that will be used for D2D communication. For the example, therefore, the reference signal **140** is transmitted on the uplink carrier that is allocated for D2D communication.

As discussed below with reference to FIG. 1C, the reference signal **140** may be received by the eNB in some situations. As discussed below, the eNB can instruct multiple UE devices to transmit the reference signal at the same frequency and time to determine the level of interference due to other UE devices. Such a technique is optional and may not be performed every time the D2D channel characteristic is reported, however. As a result, a dashed line represents the reference signal received by the eNB **108** in FIG. 1B.

The eNB **108** also transmits a reference signal reception instruction **146** to the second UE device **104** (target UE device) where the instruction **146** indicates the communication resources that will be used to transmit the reference signal **140** from the first UE device. For the example, the instruction **144** is transmitted in a downlink channel such as the PDCCH/PDSCH and/or higher layer signaling. Other channels can be used. In some situations, the reference signal reception instruction **146** identifies the set of resources that may be used for reference signal transmission. For example, the reference signal reception instruction **146** can be sent via SIB messaging. Therefore, the second UE device may report the D2D channel characteristics when the first UE device autonomously selects communication resources and transmits a reference signal that is received by the second UE device. The instruction **146** also identifies communication resources that should be used by the second UE device to transmit D2D channel characteristic information to the eNB **108**. In some situations, the communication resources for reporting the channel information may be provided by the eNB in a separate message. The second UE device **104** receives the reference signal **140** and determines the D2D channel characteristic information that is then reported to the eNB **108**.

The D2D channel characteristic information **142** determined by the second UE device **104** may include various types of information and formats. The second UE device **104** measures, or otherwise evaluates, the reference signal **140** transmitted from the transmitting UE device over the D2D transmission channel **134**. For the example, the technique for measuring evaluating the reference signal (D2D transmission channel) is similar to conventional techniques used in 3GPP LTE systems for determining uplink channel state information (CSI) by eNBs for the uplink channels. The actual D2D CSI parameters may be sent to the eNB **108** as

the D2D channel characteristic information **142**. In some situations, however, the D2D channel characteristic information **142** sent to the eNB **108** may be information based on the CSI parameters. For example, the information may be derived from the CSI parameters and not the actual CSI parameters. For the example, therefore, the D2D channel characteristic information **142** is at least indicative of the CSI parameters measured by the second UE device. Although the second UE device may report the D2D channel characteristic information after receiving a single reference signal, the UE device reports information based on multiple reference signals received over time in the example. For the example, therefore, multiple reference signals are received and processed to determine the CSI parameters. Techniques such as time averaging and filtering can be used to process the measurements and generate the CSI reports.

FIG. 1C is a block diagram of the communication system **100** where the eNB **108** instructs the first UE device **102** and a third UE device **148** to transmit reference signals **140**, **150** at the same time and frequency to determine a level of interference. For the example in FIG. 1C, the third UE device **148** is a cellular UE device that is, or will be, communicating using cellular communication links and not D2D communication links. The eNB **108** instructs the third UE device **148** to transmit the reference signal **150** by sending a reference signal transmission instruction **152** to the third UE device **148**. The instruction **152** provides reference signal transmission parameters that result in transmission of the reference **150** signal at the same time and frequency as the reference signal **140** transmitted from the first UE device. Under certain conditions, the reference signal **140** will cause interference with the reference signal **150**. The eNB receives both reference signals **140**, **150** and determines if the level of interference is tolerable (e.g., below a threshold). The eNB takes into account the interference level when determining the D2D transmission parameters. For example, if the interference cannot be tolerated, the time/frequency communication resources are not reused. In other words, the same communication resources are not assigned to different UE devices where interference of their reference signals is above a threshold.

FIG. 1D is a block diagram of the communication system **100** where the eNB **108** instructs the first UE device **102** and a third UE device **154** to transmit reference signals **140**, **156** at the same time and frequency to determine a level of interference with other D2D devices. When multiple pairs of D2D UE devices are communicating in proximity to each other, it is possible that their transmissions will cause interference when the same communication resources are being used. On the other hand, the objective to efficiently use communication resources requires that the communication be reused when possible. For the example of FIG. 1D, reference signal are used to determine whether communication resources can be reused for D2D communication between different sets of D2D UE devices. For the example of FIG. 1D, the third UE device **154** is a D2D UE device that is using, or has requested to use, D2D communication resources. The eNB **108** instructs the third UE device **154** to transmit the reference signal **156** by sending a reference signal transmission instruction **158** to the third UE device **154**. The instruction **158** provides reference signal transmission parameters that result in transmission of the reference **156** signal at the same time and frequency as the reference signal **140** transmitted from the first UE device. Under certain conditions, the reference signal **140** will cause interference with the reference signal **156** at other UE devices and/or the reference signal **156** will cause interference with

the reference signal **140**. The eNB sends a reference signal reception instruction **160** to a fourth UE device **162** inform the fourth UE device of the transmission of the reference signal **156** and to provide information to assist the UE device in receiving the reference signal **156**. The second UE device **104** determines the level of interference caused by the second reference signal **156** to the first reference signal **140** and reports the interference to the eNB. The fourth UE device **162** determines the level of interference caused by the first reference signal **140** to the second reference signal **156** and reports the interference to the eNB. The interference information that is reported may include any type of parameters that indicate the level of interference. Examples of suitable interference parameters include the power levels of the reference signals and power ratios of the power levels such as signal to-noise-ratio (SNR), signal-to-interference-plus-noise ratio (SINR) (also known as the signal-to-noise-plus-interference ratio (SNIR)) or combinations thereof. The interference information may be reported as part of the D2D channel characteristic information **164** from the 4th UE device or may be transmitted separately. The interference information determined by the second UE device may be transmitted in the D2D channel characteristic information **142**.

Based on the interference information, the eNB determines whether the same communication resources can be assigned to different sets of D2D UE devices. If the interference is below a threshold, the eNB reuses the communication resources.

FIG. 2 is a block diagram of an example of a UE device **200** suitable for use as one of the UE devices **102**, **104**, **148**, **154**, **162**. The UE device **200** includes a transceiver **202** and a controller **204**, as well as other components and circuitry (not shown) such as memory and a user interface, for example.

The transceiver **202** includes a transmitter that transmits uplink wireless signals to base stations (eNBs) and a receiver that receives downlink wireless signals from base stations (eNBs) over the uplink and downlink channels, respectively. The transceiver **202** is also configured to transmit and receive D2D signals using allocated cellular resources, such as uplink communication resources, for example. The controller **204** controls components of the UE device **200** to manage the functions of the device **200** described herein as well as to facilitate the overall functionality of the device **200**. The controller **204** is connected to the transceiver **202** and other components such as memory.

The receiver in the transceiver **202** may also be used to measure parameters to determine channel characteristics for the downlink channel and the D2D channels. The controller and the receiver measure one or more parameters that indicate channel characteristic information such as the quality of the channel, required transmission power for transmission through the channel, or power levels related to the received reference signal such as total received power, signal to-noise-ratio (SNR), signal-to-interference-plus-noise ratio (SINR) (also known as the signal-to-noise-plus-interference ratio (SNIR)) or combinations thereof. The controller **204** in the UE device **200** determines the CSI parameters based on the measured channel parameters and generates CSI reports that are sent to the eNB.

FIG. 3 is a block diagram of an example of a base station (eNB) **300** suitable for use as the base station (eNB) **108** in FIG. 1. The base station (eNB) **300** includes a transceiver **302**, a controller **304**, and a communication interface **306** as well as other components and circuitry (not shown) such as memory, for example.

The transceiver **302** exchanges wireless signals with the UE devices **104**, **106** within the service area **106**. Transmissions from the base station (eNB) and from the UE devices are governed by a communication specification that defines signaling, protocols, and parameters of the transmission. The communication specification may provide strict rules for communication and may also provide general requirements where specific implementations may vary while still adhering to the communication specification. Although the discussion herein is directed to the 3GPP Long Term Evolution (LTE) communication specification, other communication specifications may be used in some circumstances. The communication specification defines at least a data channel and a control channel for uplink and downlink transmissions and specifies at least some timing and frequency parameters for physical channels.

The transceiver **302**, therefore, includes at least a downlink transmitter for transmitting downlink signals and an uplink receiver for receiving uplink signals. The receiver and controller measure one or more parameters to determine characteristics of the uplink channels. The receiver, therefore, is capable of measuring the reference signal transmitted by the UE devices to determine cellular channel characteristic information such as the quality of the cellular channel, required transmission power for transmission through the channel, and/or power levels related to the received reference signal such as total received power, signal to-noise-ratio (SNR), signal-to-interference-plus-noise ratio (SINR) (also known as the signal-to-noise-plus-interference ratio (SNIR)) or combinations thereof.

For the example, the base station (eNB) **300** also includes a communication interface **306** for facilitating communication over the backhaul with other eNBs and network entities. Where X2 signaling is available, the communication interface **312** communicates over the backhaul using X2.

In addition to other functions, the controller evaluates the channel characteristic information to allocate and assign communication resources to UE devices including D2D UE devices and cellular UE devices. The examples discussed with reference to FIG. 1A, FIG. 1B, FIG. 1C and FIG. 1D may be performed independently or collectively. For example, the eNB may determine only D2D transmission parameters for a set of D2D UE devices in one situation. In other situations, the eNB may determine the D2D transmission parameters for multiple sets of D2D UE devices and allocate communication resources for D2D and cellular communication.

FIG. 4 is a message diagram **400** for an example of determining D2D transmission parameters based on network-assigned reference signal transmissions. The message transmission discussed with reference to FIG. 4, therefore, provide an example of message transmission suitable for the examples discussed with reference to FIG. 1A and FIG. 1B.

At transmission **402**, the eNB **108** transmits a reference signal transmission instruction **144** to the first UE device where the instruction identifies the communication resources that should be used by the first UE device to transmit a reference signal **140**. For the example, the instruction **144** is transmitted in the PDCCH/PDSCH although other channels can be used.

At transmission **404**, the eNB **108** transmits a reference signal reception instruction **146** to the second UE device where the instruction **146** identifies the communication resources that will be used by the first UE device to transmit the reference signal **140**. For the example, the instruction **146** is transmitted in the PDCCH/PDSCH although other channels can be used. In some situations, the reference

signal reception instruction **146** identifies communication resources that should be used by the second UE device to report the D2D channel characteristics to the eNB.

The first reference signal is transmitted by the first UE device **102** and received by the second UE device at transmission **406**.

At event **408**, the second UE device **104** determines the D2D channel characteristics D2D communication link **110**. For the example, the second UE device **104** received and evaluates toe reference signal to determine CSI parameters.

At transmission **410**, the second UE device sends the D2D channel characteristic information to the eNB **108**. For the example, the second UE device **104** sends a message indicative of the CSI parameters over the communication resources identified by the eNB **108**. Such communication resources may include resources in the PUCCH/PUSCH, for example.

At event **412**, the eNB determines the D2D transmission parameters for transmitting D2D signals from the first UE device **102** to the second UE device **104**. Based on the CSI parameters for the D2D channel, the eNB determines the appropriate transmission parameters that may include any combination of coding, modulation, transmission power, time/frequency resources and MIMO parameters. Other parameters may be included.

At transmission **414**, the eNB **108** transmits the D2D transmission parameters to the first UE device **102**. A suitable technique includes sending the parameters over the PDCCH/PDSCH.

FIG. **5** is a message diagram **500** for an example of determining a level of interference at the eNB **108** based on network-assigned reference signal transmissions. The message transmission discussed with reference to FIG. **5**, therefore, provides an example of message transmission suitable for the examples discussed with reference to FIG. **1A** and FIG. **1C**. For the example, the third UE device **148** is a cellular UE device that is, or will be communicating, using cellular communication. In the interest of brevity and clarity, some transmissions discussed with reference to other figures are not shown in FIG. **5**.

At transmission **502**, the eNB **108** transmits a reference signal transmission instruction **144** to the first UE device **102** where the instruction **144** identifies the communication resources that should be used by the first UE device **102** to transmit a first reference signal **140**. For the example, the instruction **144** is transmitted in the PDCCH/PDSCH although other channels can be used.

At transmission **504**, the eNB **108** transmits a reference signal transmission instruction **152** to the third UE device **148** where the instruction identifies the communication resources that should be used by the third UE device **148** to transmit a second reference signal **150**. For the example, the instruction **152** is transmitted in the PDCCH/PDSCH although other channels can be used.

The first reference signal **140** is transmitted by the first UE device **102** and received by the second UE device at transmission **506**. The second reference signal **150** is transmitted from the third UE device **148** at the same time as the first reference signal **140** is transmitted from the first UE device **102**. In the interest of clarity, FIG. **5** does not show the two transmissions **506**, **508** at the same location (frequency resource) within the message diagram. Therefore, although FIG. **5** shows the transmission **508** below the transmission **506**, the two transmissions **506**, **508** are occurring at the same time. The first reference signal is received at the second UE device and possibly received at the eNB. The second reference signal **150** is received at the eNB.

As discussed above, the second UE device **104** determines the D2D channel characteristic information. The D2D channel characteristic information such CSI parameters are reported to the eNB at transmission **510**.

At event **512**, the eNB determines the level of interference to the second reference signal **150** caused by the first reference signal **140** at the eNB. Examples of suitable techniques of determining the level of interference include measuring total power of the first reference signal or determining power ratios of the reference signals **140**, **150**. Based on the interference level, the eNB determines whether the communication resources assigned to the first UE device for D2D communication can be assigned to the third UE device **148**.

At transmission **514**, the eNB **108** transmits the D2D transmission parameters to the first UE device **102**. At transmission **516**, eNB **108** transmits the cellular transmission parameters **516** to the third UE device **102** where the assigned communication resources are based on the level of interference. If level of interference is sufficiently low, the same communication resources are reused and assigned to the first UE device and the third UE device.

FIG. **6** is a message diagram **600** for an example of determining a level of interference at D2D UE devices based on network-assigned reference signal transmissions. The message transmission discussed with reference to FIG. **6**, therefore, provides an example of message transmission suitable for the examples discussed with reference to FIG. **1A** and FIG. **1D**. For the example, the third UE device **148** is a D2D UE device that is communicating or is requesting to communicate, using D2D communication. In the interest of brevity and clarity, some transmissions discussed with reference to other figures and they may occur in some circumstances are not shown in FIG. **6**. For example, communications with a fourth UE device are omitted in FIG. **6**.

At transmission **602**, the eNB transmits a reference signal transmission instruction **144** to the first UE device **102** instructing the first UE device to transmit a reference signal. For the example, the instruction is transmitted over the PDCCH/PDSCH channel although other channels may be used.

At transmission **604**, the eNB transmits a reference signal transmission instruction **158** to the third UE device **154** instructing the third UE device to transmit a reference signal. For the example, the instruction is transmitted over the PDCCH/PDSCH channel although other channels may be used.

At transmission **606**, the eNB transmits a reference signal reception instruction **146** to the second UE device **104** providing the second UE device **104** with information that assists the second UE device in receiving the reference signal **140**. For the example, the instruction is transmitted over the PDCCH/PDSCH channel although other channels may be used.

At transmission **608** and transmission **810**, two UE devices transmit a reference signal at the same time and at the same frequency. The first UE device **102** transmits the first reference signal. The third UE device **154** transmits another reference signal **156** at the same time and at the same frequency as the first reference signal **140**.

At transmission **612**, the second UE device transmits D2D channel characteristic information that includes interference information regarding the level of interference to the first reference signal **140** caused by the other reference signal **156** at the second UE device. Examples of suitable techniques of determining the level of interference include

measuring total power of the first reference signal or determining power ratios of the reference signals.

At event **614**, the eNB selects the communication resources based on the reported interference levels. Based on the interference level, the eNB determines whether the communication resources assigned to the first UE device for D2D communication can be assigned to the third UE device **148**.

At transmission **616**, the eNB **108** transmits the D2D transmission parameters to the first UE device **102**. At transmission **616**, eNB **108** transmits the D2D transmission parameters to the third UE device **102** where the assigned communication resources are based on the level of interference. If the level of interference is sufficiently low, the same communication resources are reused and assigned to the first UE device and the third UE device.

FIG. **7** is a flowchart of an example of a method of managing communication using network-assisted reference signal transmission performed at an eNB **108**. For the examples herein, the method is performed by executing code on the controller and utilizing other components of the eNB **108**. The steps of the method may be performed in a different order and some steps may be performed simultaneously in some situations. For example, reference signal transmission instructions can be sent to multiple UE devices at the same time. As discussed above, the various examples discussed above may be performed individually or collectively. Therefore, some steps in FIG. **7** may be omitted in some situations. For example, in some situations, interference levels are not determined and step **706** is omitted.

At step **702**, the eNB instructs one or more UE devices to transmit a reference signal. The instructions may include messages indicating the specific resources or may indicate a set of resources that can be used by the devices for reference signals. In situations where the eNB explores the possibility of reusing communication resources, the reference signal transmission instructions are sent to multiple UE devices and specify the same time and frequency. For example, a cellular UE, one UE device from a first D2D pair and another UE device from a second D2D pair may be instructed to transmit reference signal at the same time and frequency. Where communication resource reuse is not contemplated, orthogonal communication resources for reference signal transmission are assigned to the different UE devices.

At step **704**, the eNB receives reference signals transmitted from UE devices. The eNB receives at least reference signals from cellular UE devices to facilitate cellular uplink channel management. Where D2D UE devices transmit reference signals, the eNB may also receive the D2D UE devices reference signals.

At step **706**, the eNB determines the level of interference at the eNB due to D2D reference signals. Where D2D reference signals are transmitted at the same time and frequency as cellular reference signals, the eNB determines the level of interference. The level of interference is used to determine whether communication resources can be used for cellular and D2D communication for the UE devices transmitting the reference signals.

At step **708**, the eNB receives the D2D channel characteristic information from the D2D UE devices receiving the D2D reference signals. In some situations, the D2D channel characteristic information includes interference level information. For example, where UE devices transmit reference signals at the same time and frequency, the reference signals may be received at other D2D UE devices and a level of interference may be determined and reported.

At step **710**, the eNB determines the D2D transmission parameters based on the reference signals (interference level) and the D2D channel characteristic information. The eNB determines where communication resources can be reused for D2D UE devices based in interference levels. The eNB also determines the appropriate transmission parameters that may include any combination of coding, modulation, transmission power, time/frequency resources and MIMO parameters. Other parameters may be included.

At step **712**, the D2D transmission parameters are assigned to the D2D UE devices. The parameters may be assigned using PDCCH/PDSCH.

FIG. **8** is an illustration of an example of a transmission by a D2D UE device including reference signals. The eNB configures the D2D UE device to transmit a reference signal **140**. The transmission in the cellular uplink communication band in accordance with one or more revisions of the 3GPP LTE specification, although the cellular downlink band may be used in some situations. For the example of FIG. **8**, the eNB configures the D2D UE device to transmit the reference signal in fixed frequency bands used for D2D transmission. Where multiple D2D UE devices are configured and interference is not determined, the eNB configures the D2D UE devices to transmit reference signal on orthogonal resources.

For the example, the reference signal **140** transmitted at a period of T subframes **802**. After transmitting the reference signal, the UE device receives the D2D transmission parameters from the eNB and transmits a scheduling assignment **804** in subframe n **806**. The scheduling assignment (SA) **804** indicates the D2D communication resources that will be used for D2D transmission in subsequent subframes. For the example, the SA **804** identifies D2D communication resources in four subframes **808**, **812**, **814**, **816** that should be used for D2D transmissions. In the subframe $n+x$ **808**, the UE device transmits a D2D transmission **810**. The UE devices also transmits data in the subframe $n+x+1$ **812**, the subframe $n+y$ **814** and the subframe $n+y+1$ **816**.

Clearly, other embodiments and modifications of this invention will occur readily to those of ordinary skill in the art in view of these teachings. The above description is illustrative and not restrictive. This invention is to be limited only by the following claims, which include all such embodiments and modifications when viewed in conjunction with the above specification and accompanying drawings. The scope of the invention should, therefore, be determined not with reference to the above description, but instead should be determined with reference to the appended claims along with their full scope of equivalents.

The invention claimed is:

1. An apparatus for controlling a first user equipment (UE) device, the apparatus comprising:

a memory; and

a processor configured to cause the first UE device to:

- receive, from a second UE device, a reference signal;
- receive first information, the first information identifying a first configuration for receiving the reference signal from the second UE device;
- determine device-to-device (D2D) measurement results by measuring at least one signal parameter of each of a plurality of UE device received reference signal signals that is the reference signal transmitted from the second UE device at different times as received at the first UE device; and
- transmit the D2D measurement results after receiving the first information and determining the D2D measurement results.

2. The apparatus of claim 1, wherein the processor is further configured to cause the first UE device to filter the plurality of UE device received reference signals received at the first UE device at different times.

3. The apparatus of claim 1, wherein the reference signal 5 is transmitted in response to receiving second information from a base station, the second information identifying a second configuration for transmitting the reference signal to the first UE device.

* * * * *