



US011969058B2

(12) **United States Patent**  
**Wilson, Jr.**

(10) **Patent No.:** **US 11,969,058 B2**  
(45) **Date of Patent:** **Apr. 30, 2024**

(54) **ARTICLE OF FOOTWEAR WITH RECONFIGURABLE FASTENING SYSTEM**

(71) Applicant: **Under Armour, Inc.**, Baltimore, MD (US)

(72) Inventor: **Reginald Wilson, Jr.**, Baltimore, MD (US)

(73) Assignee: **Under Armour, Inc.**, Baltimore, MD (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/974,008**

(22) Filed: **Oct. 26, 2022**

(65) **Prior Publication Data**  
US 2023/0049676 A1 Feb. 16, 2023

**Related U.S. Application Data**  
(63) Continuation of application No. 16/992,462, filed on Aug. 13, 2020, now Pat. No. 11,490,692, which is a continuation of application No. 15/916,640, filed on Mar. 9, 2018, now Pat. No. 10,765,173.

(60) Provisional application No. 62/469,835, filed on Mar. 10, 2017.

(51) **Int. Cl.**  
*A43B 23/02* (2006.01)  
*A43C 1/00* (2006.01)  
*A43C 1/04* (2006.01)  
*A43C 5/00* (2006.01)  
*A43C 11/00* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *A43C 1/003* (2013.01); *A43B 23/0245* (2013.01); *A43B 23/0265* (2013.01); *A43C 1/04* (2013.01); *A43C 5/00* (2013.01); *A43C 11/00* (2013.01)

(58) **Field of Classification Search**  
CPC ..... A43C 1/003; A43B 23/0245  
USPC ..... 36/50.1  
See application file for complete search history.

(56) **References Cited**  
U.S. PATENT DOCUMENTS

2,161,472 A	6/1939	Sol
2,222,178 A	11/1940	Harry et al.
2,440,393 A	4/1948	Clark
5,042,120 A	8/1991	Nichols
5,269,078 A	12/1993	Cochrane
5,291,671 A	3/1994	Caberlotto et al.
5,408,761 A	4/1995	Gazzano
6,052,921 A	4/2000	Oreck

(Continued)

FOREIGN PATENT DOCUMENTS


WO WO-2020033794 A1 \* 2/2020 ..... A43B 1/04

*Primary Examiner* — Timothy K Trieu  
(74) *Attorney, Agent, or Firm* — Edell, Shapiro & Finnan, LLC

(57) **ABSTRACT**

An article of footwear includes a sole, an upper coupled to the sole and having an inner surface and an outer surface, the upper being configured to receive at least a portion of a human foot within an interior cavity at least partially defined by the upper, a plurality of eyelets disposed on the upper, each eyelet including a pair of openings disposed in the upper, and a cord threaded through the pair of openings of each eyelet of the plurality of eyelets such that the cord includes a series of unexposed portions and a series of exposed portions. The series of exposed portions are disposed more proximate to the outer surface of the upper than the inner surface of the upper.

**7 Claims, 12 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

6,128,835	A *	10/2000	Ritter .....	A43C 1/00 36/114
6,286,233	B1	9/2001	Gaither	
7,343,701	B2	3/2008	Pare et al.	
8,037,621	B2	10/2011	Hooper	
8,051,585	B2	11/2011	Hope et al.	
10,092,060	B2	10/2018	Aveni et al.	
10,219,580	B2	3/2019	Taylor	
D932,762	S *	10/2021	Vella .....	D2/973
D959,124	S *	8/2022	Mace .....	D2/969
2002/0148142	A1	10/2002	Oorei et al.	
2004/0181972	A1 *	9/2004	Csorba .....	A43B 23/0265 36/50.1
2006/0117607	A1 *	6/2006	Pare .....	A43C 1/04 36/50.1
2007/0011910	A1	1/2007	Keen	
2008/0110048	A1	5/2008	Dua et al.	
2009/0071041	A1	3/2009	Hooper	
2013/0019500	A1	1/2013	Greene	
2014/0196216	A1	7/2014	Weitzel et al.	
2014/0196316	A1	7/2014	Follet	
2014/0223779	A1	8/2014	Elder et al.	
2016/0302524	A1 *	10/2016	Smith .....	A43B 13/12
2020/0029655	A1	1/2020	Nishiwaki et al.	

\* cited by examiner




FIG.1A




FIG.1B




FIG.1C




FIG.1D




FIG.2A




FIG. 2B






FIG.3A




FIG. 3B




FIG.3C




FIG. 4A




FIG.4B




FIG.5

1

## ARTICLE OF FOOTWEAR WITH RECONFIGURABLE FASTENING SYSTEM

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 16/992,462, entitled "Article of Footwear With Reconfigurable Fastening System," and filed on Aug. 13, 2020, which is a continuation of U.S. application Ser. No. 15/916,640, entitled "Article of Footwear With Reconfigurable Fastening System," and filed on Mar. 9, 2018, which claims priority under 35 U.S.C. 119(e) to U.S. Provisional Patent Application Ser. No. 62/469,835, entitled "Article of Footwear With Reconfigurable Fastening System", filed Mar. 10, 2017, the disclosures of which are incorporated herein by reference in their entireties for all purposes.

### FIELD OF THE INVENTION

The present invention relates to an article of footwear that provides an improved and custom fit of an upper around a foot.

### BACKGROUND OF THE INVENTION

Footwear, particularly athletic footwear, are worn in a variety of activities including running, walking, hiking, team and individual sports, and any other activity where the protection and support of human feet is desired. In one configuration, an article of footwear includes an upper that forms a cavity in which a user places his or her foot. The article of footwear further includes a sole that engages the bottom of the foot and separates the foot from the ground. Uppers in athletic footwear are usually formed from one or more pieces of fabric, leather, and/or plastic that are stitched, bonded, or otherwise attached together. Various fasteners, including laces or strings, are used to secure the foot in the cavity defined by the upper.

Every human foot differs in both shape and size. While conventional articles of footwear are sold in various sizes, these sizes are generalizations and fail to take into consideration the varying shapes between different feet that have the same size. Because conventional articles of footwear are incapable of accommodating varying shapes of feet, an article of footwear is limited to the number of people that find that article of footwear comfortable.

In addition, while conventional articles of footwear contain eyelets configured to receive a string or laces, the eyelets of the conventional articles of footwear are typically only aligned along the medial and lateral sides of the instep (i.e., proximate to a tongue of an article of footwear). Thus, as a wearer of the conventional article of footwear tightens the laces of the article of footwear, the article of footwear may contain portions that are tighter and more uncomfortable than other portions that are looser. The positioning of the eyelets of the conventional article of footwear inhibit the upper of the article of footwear from contouring and conforming to the shape of the foot within the article of footwear, reducing the comfort of the article of footwear. The positioning of the eyelets also prevents the article of footwear from providing proper support to the foot within the article of footwear, especially during athletic events, such as running.

It would be desirable to provide an article of footwear with a plurality of eyelets disposed over the surface of the upper in a variety of locations, where a lacing element or

2

fastener may be selectively threaded through select eyelets along the upper of an article of footwear in a configuration that is most comfortable to a wearer of the article of footwear. Moreover, it would be desirable to provide the plurality of eyelets to further enable the user of the article of footwear to selectively thread the fastener through select eyelets disposed on the upper of the article of footwear to tightly contour and conform the upper to the shape of any foot placed within the article of footwear, or to alter the amount of support provided by the upper based on an intended activity or event (e.g., running, cross-training, etc.).

### SUMMARY OF THE INVENTION

In accordance with example embodiments of the invention, an article of footwear comprises a sole, an upper, and a reconfigurable fastening system. The upper is coupled to the sole and includes medial and lateral quarters. Disposed on the medial and lateral quarters are a plurality of eyelets. Each of the eyelets includes a pair of openings disposed in the upper. The plurality of eyelets further includes at least one elongate member threaded through the pair of openings of each eyelet. The elongate member includes a series of first, or unexposed, portions that are disposed on an inner surface of the upper, and a series of second, or exposed, portions that are disposed on the outer surface of the upper. A fastener or lacing may be selectively threaded through an eyelet of the plurality of eyelets, where the fastener may be threaded between the second portion of the elongate member and the outer surface of the upper.

In accordance with another example embodiment of the invention, an article of footwear includes a sole structure and an upper. The upper is coupled to the sole structure and is configured to receive at least a portion of a human foot. The upper further includes a medial quarter, a lateral quarter, and an elongate member. A plurality of openings are disposed on at least the medial quarter of the upper. The elongate member is threaded through the plurality of openings such that the elongate member includes a series of unexposed portions and exposed portion. The unexposed portions are disposed on an interior surface of the medial quarter. The exposed portions are disposed on an exterior surface of the medial quarter. The exposed portions are configured to enable a fastener to be threaded between the exposed portion and the exterior surface of the medial quarter.

In yet another embodiment of the invention, an article of footwear includes a sole structure and an upper. The upper may be disposed on the sole structure, and may further include a medial side, a lateral side, a plurality of openings, and an elongate member. The plurality of openings may be disposed on the medial side and the lateral side in an array. The elongate member may be threaded through the plurality of openings such that the elongate member includes a series of unexposed portions and a series of exposed portions. The unexposed portions may be disposed on an interior surface of the upper. The exposed portions may be disposed on an exterior surface of the upper. The exposed portions may be configured to enable a fastener to be threaded between the exposed portion and the exterior surface of the upper.

The above and still further features and advantages of embodiments of the present invention will become apparent upon consideration of the following detailed description thereof, particularly when taken in conjunction with the accompanying drawings wherein like reference numerals in the various figures are utilized to designate like components.

BRIEF DESCRIPTION OF THE SEVERAL  
VIEWS OF THE DRAWING

FIG. 1A illustrates a side view in elevation of the medial side of an example embodiment of an article of footwear in accordance with the present invention.

FIG. 1B illustrates a side view in elevation of the lateral side of the example embodiment of the article of footwear illustrated in FIG. 1A.

FIG. 1C illustrates a top view of the toe cage and instep of the example embodiment of the article of footwear illustrated in FIG. 1A.

FIG. 1D illustrates a rear view in elevation of the heel end of the example embodiment of the article of footwear illustrated in FIG. 1A.

FIG. 2A illustrates a side view in elevation of the medial side of the example embodiment of the article of footwear illustrated in FIG. 1A, the side view showing the slits of the eyelets on the medial side of the upper of the article of footwear.

FIG. 2B illustrates a side view in elevation of the lateral side of the example embodiment of the article of footwear illustrated in FIG. 1A, the side view showing the slits of the eyelets on the lateral side of the upper of the article of footwear.

FIG. 3A illustrates a side view in elevation of the lateral side of the example embodiment of the article of footwear illustrated in FIG. 1A, the side view showing the positioning of the elongate members of the eyelets on the lateral side of the article of footwear.

FIG. 3B illustrates a top view of the toe cage and instep of the example embodiment of the article of footwear illustrated in FIG. 1A, the top view showing the positioning of the elongate members of the eyelets in the forefoot and midfoot sections of the article of footwear.

FIG. 3C illustrates a rear view in elevation of the heel end of the example embodiment of the article of footwear illustrated in FIG. 1A, the rear view showing the positioning of the elongate members of the eyelets on both the medial and lateral sides in the hindfoot section of the article of footwear.

FIG. 4A illustrates a side view in elevation of the medial side of a second embodiment of an article of footwear in accordance with the present invention.

FIG. 4B illustrates a side view in elevation of the lateral side of the second embodiment of the article of footwear illustrated in FIG. 4A.

FIG. 5 illustrates an interior view of the medial side of the second embodiment of the article of footwear illustrated in FIG. 4A.

Like reference numerals have been used to identify like elements throughout this disclosure.

DETAILED DESCRIPTION OF THE  
INVENTION

The present invention relates to an article of footwear with a plurality of eyelets disposed over the article of footwear, enabling the user to attach laces of the article of footwear at optimal locations based on the shape of the foot within the article of footwear, comfort of the user, and intended use of the article of footwear.

In the following detailed description, reference is made to the accompanying figures which form a part hereof wherein like numerals designate like parts throughout, and in which is shown, by way of illustration, embodiments that may be practiced. It is to be understood that other embodiments may

be utilized, and structural or logical changes may be made without departing from the scope of the present disclosure. Therefore, the following detailed description is not to be taken in a limiting sense, and the scope of embodiments is defined by the appended claims and their equivalents.

Aspects of the disclosure are disclosed in the description herein. Alternate embodiments of the present disclosure and their equivalents may be devised without parting from the spirit or scope of the present disclosure. It should be noted that any discussion herein regarding “one embodiment”, “an embodiment”, “an exemplary embodiment”, and the like indicate that the embodiment described may include a particular feature, structure, or characteristic, and that such particular feature, structure, or characteristic may not necessarily be included in every embodiment. In addition, references to the foregoing do not necessarily comprise a reference to the same embodiment. Finally, irrespective of whether it is explicitly described, one of ordinary skill in the art would readily appreciate that each of the particular features, structures, or characteristics of the given embodiments may be utilized in connection or combination with those of any other embodiment discussed herein.

Various operations may be described as multiple discrete actions or operations in turn, in a manner that is most helpful in understanding the claimed subject matter. However, the order of description should not be construed as to imply that these operations are necessarily order dependent. In particular, these operations may not be performed in the order of presentation. Operations described may be performed in a different order than the described embodiment. Various additional operations may be performed and/or described operations may be omitted in additional embodiments.

For the purposes of the present disclosure, the phrase “A and/or B” means (A), (B), or (A and B). For the purposes of the present disclosure, the phrase “A, B, and/or C” means (A), (B), (C), (A and B), (A and C), (B and C), or (A, B and C).

The terms “comprising,” “including,” “having,” and the like, as used with respect to embodiments of the present disclosure, are synonymous.

An article of footwear or shoe **10** includes a medial side **100** oriented along the medial or big toe side of the user’s foot, a lateral side **102** oriented along the lateral or little toe side of the user’s foot, a toe (i.e., front) end **104** that corresponds with the toes of the user’s foot, and a heel (i.e., rear) end **106** that corresponds with the heel of the user’s foot. While the example embodiment depicted in the FIGS. 1A, 1B, 1C, 1D, 2A, 2B, 3A, 3B, and 3C shows an article of footwear **10** configured for a right foot, it is noted that the same or similar features can also be provided for an article of footwear **10** configured for a left foot (where such features of the left footed article of footwear are a reflection of or “mirror image” symmetrical in relation to the right footed article of footwear, e.g., the embodiment depicted in FIGS. 1A, 1B, 1C, 1D, 2A, 2B, 3A, 3B, and 3C).

The article of footwear **10** may include a forefoot region **110** that generally aligns with the ball and toes of a user’s foot (i.e., when a user is wearing the article of footwear **10**), a midfoot region **112** that generally aligns with the arch and instep areas of the user’s foot, and a hindfoot region **114** that generally aligns with the heel and ankle areas of the user’s foot. The embodiment of the article of footwear **10** illustrated includes a sole structure **120** and an upper **130** affixed to the sole structure **120**. The article of footwear **10**, also referred to herein as a shoe, can be in the form of a running shoe or other type of athletic shoe. As is described in further detail herein, the upper **130** includes a first portion **140** and



a second portion 150, where a plurality of eyelets 160 are disposed across and within the first portion 140 of the upper 130. The number and placement of the plurality of eyelets 160 enable a user to selectively thread a fastener 170 (e.g., a lace, cord, string, etc.) through certain eyelets 160 to optimize the fit of the article of footwear 10 on the foot. In other words, the number and placement of the eyelets 160 along the upper 120 enable the user of the article of footwear 10 to selectively thread the fastener 170 through the eyelets in any desired manner or design that is best suited for the shape of the foot placed within the article of footwear 10, the comfort of the user of the article of footwear 10, and the intended use of the article of footwear (e.g., running, cross-training, etc.). The user of the article of footwear 10 may alter the support, comfort, and fit provided by the article of footwear 10 by, as described herein, altering the eyelets 160 through which the fastener 170 is threaded.

The upper 130 defines an envelope or pocket that covers and protects the foot of the wearer. In some embodiments, the upper 130 covers and protects the foot of the wearer together with the sole structure 120. The upper 130 includes a toe cage 132 disposed proximate to the front end 104 of the article of footwear 10 in the forefoot region 110 of the article of footwear 10. As further illustrated, the upper 130 also includes an instep 134, where the instep 134 is disposed rearward of the toe cage 132 within the midfoot region 112 of the article of footwear 10. The upper 130 may further include a heel cup 139 disposed in the hindfoot region 114 and around the heel end 106 of the article of footwear 10. In addition, the upper 130 includes a medial quarter 136 that extends through the midfoot region 112 from the toe cage 132 to the heel cup 139 along the medial side 100 of the article of footwear 10 and a lateral quarter 138 that extends through the midfoot region 112 from the toe cage 132 to the heel cup 139 along the lateral side 102 of the article of footwear 10. The toe cage 132 connects the medial quarter 136 to the lateral quarter 138 through the forefoot region 110, while the heel cup 139 connects the medial quarter 136 to the lateral quarter 138 through the hindfoot region 114. Thus, the medial quarter 136 and the lateral quarter 138 are not connected to one another through the instep 130, or midfoot region 112, of the upper 130.

As previously explained, the upper 130 may include a first portion 140 and a second portion 150. Both the first portion 140 and the second portion 150 are formed or constructed from a knit material/fabric (e.g., flat knit, circular knit, etc.) or a woven material/fabric. This enables the upper 130 to be a more flexible, elastic, and/or breathable material than uppers constructed of conventional materials (e.g., leather, suede, plastics, etc.). This also enables the upper 130 of the article of footwear 10 to be lighter than conventional footwear. As best illustrated in FIGS. 1A, 1B, 1C, and 1D, the first portion 140 may form a lower portion of the upper 130, while the second portion 150 may form an upper portion of the upper 130. The first portion 140 may form the toe cage 132, the medial quarter 136, the lateral quarter 138, and the heel cup 139 of the upper 130. The first portion 140 of the upper may form a first, lower collar 142. The second portion 150 of the upper 130 may be disposed within the first portion 140 of the upper 130, or may be disposed adjacent to the lower collar 142. As illustrated, the second portion 150 of the upper 130 may be configured to extend upward from the lower collar 142 of the first portion 140 of the upper 130, such that the second portion defines a second upper collar 152, which defines an aperture 154. The aperture 154 provides access to the interior cavity of the upper 130. The second portion 150 may also be disposed in the instep 134

of the upper 130, where the second portion 150 is disposed between the medial quarter 136 and the lateral quarter 138. While both the first and the second portions 140, 150 may be formed of knit/woven materials, the second portion 150 may be ribbed, resulting in a more resilient and elastic material than the first portion 140.

As best illustrated in FIG. 1B, the upper collar 152 of the second portion 150 may be stretched or expanded between a first, unstretched position (where the aperture 154 has a first diameter D1) and a second stretched position (where the aperture 154 has a second diameter D2). In one embodiment, the diameter D1 of the aperture 154 may be 90 mm, while the fully stretched diameter D2 of the aperture 154 may be 160 mm. The resiliency and stretchability of the second portion 150, and more specifically the upper collar 152, enables the aperture 154 to accommodate a foot being disposed within the upper 130. In addition, the resiliency and stretchability of the upper collar 152 of the second portion 150 of the upper 130 enables the upper collar 152 to accommodate ankles of various sizes and shapes. Because the second portion 150 may be more stretchable and resilient than the first portion 140 of the upper 130, and because the second portion 150 is disposed in the instep 130 between the medial and lateral quarters 136, 138, the second portion 150 enables the medial and lateral quarters 136, 138 to bend or flex outward and away from one another to accommodate both the placement of feet within the article of footwear 10 and the varying widths of feet disposed within the article of footwear 10.

As further detailed below, a plurality of eyelets 160 are disposed on the first portion 140 of the upper 130. The plurality of eyelets 160 are disposed on the portion of the instep 130 proximate to the forefoot region 110, the medial quarter 136, the lateral quarter 138, and on both the medial side 100 and the lateral side 102 of the heel cup 139. Each of the plurality of eyelets 160 is configured to receive a portion of the fastener 170. In other words, the fastener 170 may be threaded through each of the plurality of eyelets 160. Once the fastener 170 is threaded through at least one eyelet 160 on the medial side 100 of the article of footwear and at least one eyelet 160 on the lateral side 102 of the article of footwear 10, the fastener 170 may be pulled to tighten the first and second portions 140, 150 of the upper 130 around the foot disposed within the article of footwear 10.

As further illustrated in FIGS. 1A, 1B, and 1D, a loop/tab 180 is coupled to the first portion 140 of the upper 130 in the hindfoot region 114. The loop 180 is coupled to the heel cup 139 of the first portion 140 of the upper 130 on the heel end 106. The loop 180 may be coupled to the first portion 140 via a reinforcing cover 182 that is coupled to the first portion 140 via a stitching 184. In other embodiments, the reinforcing cover 182 may be coupled to the first portion 140 via any conventional means, including, but not limited to bonding, adhesives, etc. As best illustrated in FIG. 1D, the loop 180 is threaded through the reinforcing cover 182.

The upper 130 may possess any dimensions (size/shape) suitable for its described purpose. For example, the upper 130 may possess a low top configuration in which the upper extends beneath the wearer's ankle, as illustrated in FIGS. 1A, 1B, 1C, and 1D. Alternatively, in other embodiments, the upper 130 may possess a "mid top" configuration (in which the second portion 150 of the upper 130 extends to slightly below or at the wearer's ankle), a "high top" configuration (in which the hindfoot region 206 of the upper extends over and/or above at least a portion of a wearer's ankle), or any other suitable configuration.

Still referring to FIGS. 1A, 1B, 1C, and 1D, the upper **130** is coupled to the sole structure **120** via any conventional and/or other suitable manner (e.g., via any form of adhesion or bonding, via a woven connection, via one or more types of fasteners, etc.). In the particular embodiment depicted, the sole structure **120** may be constructed of a compression material such as ethylene-vinyl acetate (EVA) foam. The compression material is configured to compress on impact and provide cushion to the user's foot as the article of footwear **10** impacts a support surface.

The plurality of eyelets **160** and the fastener **170** form the reconfigurable fastening system of the article of footwear **10**. As previously explained, the medial side **100** of the article of footwear **10** includes a plurality of eyelets **160**, where the eyelets are disposed primarily within the midfoot region **112** and the hindfoot region **114**. As further illustrated, the eyelets **160** on the medial side **100** of the article of footwear **10** are disposed on the medial quarter **136** and the medial side **100** of the heel cup **139**. The lateral side **102** of the article of footwear **10** also includes a plurality of eyelets **160**, where the eyelets **160** are disposed primarily within the midfoot region **112** and the hindfoot region **114**. The eyelets **160** on the lateral side **102** of the article of footwear **10** are disposed on the lateral quarter **138** and the lateral side **102** of the heel cup **139**. The portion of the instep **134** proximate to the forefoot region **110** may also include eyelets **160**. As illustrated in FIGS. 1A, 1B, 1C, and 1D, the eyelets are disposed on the first portion **140** of the upper **130** in a grid-like array, where the eyelets **160** are aligned to form a series of rows **162(1)-162(3)** and columns **164(1)-164(7)**. As best illustrated in FIG. 1C, the first row **162(1)** is disposed on the medial quarter **136** and the lateral quarter **138** such that the first row **162(1)** extends only through the midfoot region **112**. Conversely, the second row **162(2)** extends from the medial side **100** of the heel cup **139**, through the medial quarter **136**, around the front end of the instep **130** (proximate to the forefoot region **110**), through the lateral quarter **138** and through the heel cup **139** such that the second row **162(2)** terminates on the lateral side **102** of the heel cup **139**. The third row **162(3)** of eyelets **160** on the medial side **100** extends from the heel cup **139** and the hindfoot region **114**, through the medial quarter **136** and the midfoot region **112**. The third row **162(3)** of eyelets **160** on the lateral side **102**, however, may only extend along the lateral quarter **138** and in the midfoot region **112**.

It should further be understood that the eyelets **160** need not be aligned in a series of rows **162(1)-162(3)** and columns **164(1)-164(7)**, and may be oriented on the first portion **140** of the upper **130** in other orientations. In addition, it should also be understood that the eyelets **160** may be located in other regions (i.e., forefoot region **110**) of the upper **130**, and on other portions (i.e., second portion **150**) and components of the upper **130**.

As best illustrated in FIGS. 2A, 2B, 3A, 3B, and 3C, each eyelet **160** is constructed from a pair of slits/openings **200** formed in the first portion **140** of the upper **130** and a portion of one of elongate members (e.g., cord, band, string, strand, lace, etc.) **300, 310, 320, 330** being threaded through the pairs of slits **200** such that the portion of the elongate members **300, 310, 320, 330** are exposed on the outer surface of the first portion **140** of the upper **130**. As best illustrated in FIGS. 2A and 2B, each slit **200** has a width *W* and a length or height *L*. Each of the slits **200** of a pair may be spaced from one another by a distance *D*. In the example embodiment illustrated, each slit **200** of each eyelet **160** has a width *W* of approximately 2 mm, a length *L* of approximately 8 mm, and the slits **200** of a pair may be spaced by

a distance *D* of approximately 6 mm. In other embodiments, the slits **200** of the eyelets **160** may be of any other width *W* and length *L*, and may be spaced from another slit in a pair by any other distance *D*, that enables the slits **200** of each eyelet **160** to receive a portion of one of the elongate members **300, 310, 320, 330**.

Continuing with FIGS. 2A and 2B, the eyelets **160** of the second row **162(2)** of eyelets **160**, which is disposed on both the medial and lateral sides **100, 102**, and across the instep **130**, include slits **200** that are mainly oriented in a first orientation **210** (except for the slits **200** that form the two eyelets **160** disposed on the instep **130** of the article of footwear **10**). The majority of the eyelets **160** that form the first and third rows **162(1), 162(3)** on both the medial and lateral sides **100, 102** of the first portion **140** of the article of footwear **10** contain slits **200** that are oriented in a second orientation **220**. The slits **200** of the eyelets **160** in columns **164(5)-164(7)** on the medial side **100**, however, are oriented in the first orientation **210**. The slits **200** of the eyelets **160** in row **162(2)** that are disposed in the instep **130** of the article of footwear **10** (i.e., not on the medial or lateral quarters **136, 138**) are oriented in the second orientation **220**. The slits **200** of the eyelets **160** that are oriented in the first orientation **210** such that the length *L* of the slits **200** extends predominately along the transverse or widthwise direction of the article of footwear **10** (i.e., the slits **200** are oriented such that they extend in the direction that crosses the article of footwear **10** from the medial side **100** to the lateral side **102**, or vice versa). The slits **200** of the eyelets **160** that are oriented in the second orientation **220** such that the length *L* of the slits **200** extends predominantly in the lengthwise direction of the article of footwear **10** (i.e., the slits **200** are oriented such that they extend along the length, from the heel end **106** to the toe end **104**, of the article of footwear **10**).

As previously stated, and as illustrated in FIGS. 3A, 3B, and 3C, the eyelets **160** of the reconfigurable fastening system of the article of footwear **10** includes elongate members **300, 310, 320, 330** that are threaded through the slits **200** of each eyelet **160**. The elongate members **300, 310, 320, 330** are flexible, possessing tensile strength sufficient for their described purpose (to capture a fastener **170** (e.g., lace) and secure a shoe to a user's foot). As previously explained, the elongate members **300, 310, 320, 330** may be in the form of a cord, a band, a string, a lace, or a strand, such that the elongate members **300, 310, 320, 330** can be formed from a single fiber, filament, or monofilament, as well as an ordered assemblage of textile fibers having a high ratio of length to diameter and normally used as a unit (e.g., slivers, roving, single yarns, plies yarns, cords, braids, ropes, etc.). In an example embodiment, an elongate member comprises one or more yarns (a continuous strand of textile fibers, filaments, or material in a form suitable for knitting, weaving, or otherwise intertwining to form a textile fabric). A yarn may include, but is not limited to, a number of fibers twisted together (spun yarn), a number of filaments laid together without twist (a zero-twist yarn), a number of filaments laid together with a degree of twist, and a single filament with or without twist (a monofilament). In another example, the elongate members **300, 310, 320, 330** can comprise a nylon cord, a polyester cord, or a cord formed of high molecular weight polyolefin (e.g., polyethylene). In still other embodiments, the elongate members **300, 310, 320, 330** can comprise a metal wire or cable. The elongate members **300, 310, 320, 330** may further include multiple lines, cables, or cords. In yet another embodiment, the

elongate members **300**, **310**, **320**, **330** may be constructed to be resilient and contain a degree of stretchability.

The first elongate member **300** contains a first end **302** and a second end **304**, where the first and second ends **302**, **304** of the first elongate member **300** are disposed proximate to one another on the heel end **106** of the article of footwear **10** such that the first end **302** is disposed on the lateral side **102** of the heel end **106** of the article of footwear **10** and the second end **304** is disposed on the medial side **100** of the heel end **106** of the article of footwear **10**. As further described herein, at least the first and second ends **302**, **304** of the first elongate member **300** are fastened to the interior surface of the upper **130**. The first elongate member **300** extends from the first end **302** through the lateral side **102** of the heel cup **139**, through the lateral quarter **138**, around the front end of the instep **130**, through the medial quarter **136**, and through the medial side **100** of the heel cup **139** to the second end **304**. Thus, the first elongate member **300** extends around the first portion **140** of the upper **130**.

The first elongate member **300** is aligned with the second row **162(2)** of the eyelets **160**, and is configured to be threaded through the slits **200** that are aligned with the second row **162(2)** of the eyelets **160**. Thus, the first elongate member **300** is primarily threaded through the slits **200** that are in the first orientation **210**. With the slits **200** of the eyelets **160** of the second row **162(2)** of eyelets **160** on the medial and lateral sides **100**, **102** in the first orientation **210** and the slits **200** of the eyelets **160** of the second row **162(2)** of eyelets **160** on the instep **134** be in the second orientation **220**, the first elongate member **300** is able to span or loop around the first portion **140** of the upper **130** from the lateral side **102** proximate to the heel end **106**, over the instep **134**, and to the medial side **100** proximate to the heel end **106**. The first elongate member **300** is primarily disposed on the interior surface of the first portion **140** of the upper **130**, except for the exposed portions **308**, which are disposed between pairs of slits **200** that form each eyelet **160** of the second row **162(2)** of the eyelets **160**. The exposed portions **308** of the first elongate member **300** are disposed on the outer surface of the first portion **140** of the upper **130**, enabling a fastener **170** to be threaded between the exposed portion **308** of the first elongate member **300** and the outer surface of the first portion **140** of the upper **130** (as illustrated in FIGS. **1A**, **1B**, **1C**, and **1D**).

The second and third elongate members **310**, **320** are substantially similar to one another, in that the second and third elongate members **310**, **320** are oriented in a sawtooth wave (e.g., zig-zag) pattern on the first portion **140** of the upper **130**. As illustrated in FIGS. **3A** and **3B**, the second elongate member **310** is primarily disposed on the lateral quarter **138**. The second elongate member **310** includes a first end **312** and a second end **314**, and extends across/over the portion of the first elongate member **300** disposed on the lateral quarter **138** in a sawtooth wave pattern. As further described herein, at least the first and second ends **312**, **314** of the second elongate member **310** are fastened to the interior surface of the lateral quarter **138** of the upper **130**. The second elongate member **310** is utilized to form the eyelets **160** located in the first row **162(1)** and the third row **162(3)** of columns **164(1)-164(4)** of eyelets **160** on the lateral side **102** of the first portion **140** of the upper **130**. Thus, the second elongate member **310** is only threaded through slits **200** that are in the second orientation **220**. With the slits **200** of the eyelets **160** that are located in the first and the third rows **162(1)**, **162(3)** and the columns **164(1)-164(4)** on the lateral side **102** being oriented in the second orientation **220**, the second elongate member **310** is able to have

a sawtooth wave pattern on the lateral side **102** of the upper **130**. The second elongate member **310** is primarily disposed on the interior surface of the first portion **140** of the upper **130**, except for the exposed portions **318**, which are disposed between each pair of slits **200** that form each eyelet **160** of the first and the third rows **162(1)**, **162(3)** of columns **164(1)-164(4)** of the eyelets **160** on the lateral side **102** of the upper **130**. The exposed portions **318** of the second elongate member **310** are disposed on the outer surface of the first portion **140** of the upper **130**, enabling a fastener **170** to be threaded between the exposed portion **318** of the second elongate member **310** and the outer surface of the first portion **140** of the upper **130** (as illustrated in FIGS. **1B** and **1C**).

While FIG. **3B** only partially illustrates the third elongate member **320**, the third elongate member **320** is substantially similar to the second elongate member **310**, except that the third elongate member **320** is disposed on the medial side **100** of first portion **140** of the upper **130**. More specifically, the third elongate member **320** is disposed on the medial quarter **136** of the first portion **140** of the upper **130**. While not illustrated, the third elongate member **320** includes a first end **322** and a second end **324**, where at least the first and second ends **322**, **324** of the third elongate member **320** are fastened to the interior surface of the medial quarter **136** of the upper **130**. FIG. **3B** illustrates, however, that the third elongate member **320** extends across/over the portion of the first elongate member **310** disposed on the medial quarter **136** in a sawtooth wave pattern. The third elongate member **320** is utilized to form the eyelets **160** located in the first row **162(1)** and the third row **162(3)** of columns **164(1)-164(4)** of the eyelets **160** on the medial side **100** of the first portion **140** of the upper **130**. Thus, similar to the second elongate member **310**, the third elongate member **320** is only threaded through slits **200** that are in the second orientation **220**. With the slits **200** of the eyelets **160** that are located in the first and the third rows **162(1)**, **162(3)** and the columns **164(1)-164(4)** on the medial side **100** being oriented in the second orientation **220**, the third elongate member **320** is able to have a sawtooth wave pattern on the medial side **100** of the upper **130**. The third elongate member **320** is primarily disposed on the interior surface of the first portion **140** of the upper **130**, except for the exposed portions **328**, which are disposed between each pair of slits **200** that form the eyelets **160** of the first and the third rows **162(1)**, **162(3)** of columns **164(1)-164(4)** of the eyelets **160** on the medial side **100** of the upper **130**. The exposed portions **328** of the third elongate member **320** are disposed on the outer surface of the first portion **140** of the upper **130**, enabling a fastener **170** to be threaded between the exposed portion **328** of the third elongate member **320** and the outer surface of the first portion **140** of the upper **130** (as illustrated in FIGS. **1A** and **1C**).

The article of footwear **10** also includes a fourth elongate member **330** disposed on the medial side **100** of the first portion **140** of the article of footwear **10**. While the fourth elongate member **330** is only partially illustrated in FIG. **3C**, the fourth elongate member **330** includes a first end **332** and a second end **334**. The first end **332** of the fourth elongate member **330**, while not illustrated, may be disposed on the medial side **100** of the first portion **140** of the article of footwear **10** within, or proximate to, the medial quarter **136**. The second end **334** of the fourth elongate member **330**, as best illustrated in FIG. **3C**, is disposed on the medial side **100** of the heel cup **139** proximate to the heel end **106**. As further described herein, at least the first and second ends **332**, **334** of the fourth elongate member **330** are fastened to

the interior surface of the upper 130. As further illustrated in FIG. 3C, the fourth elongate member 330 may be disposed lower in height on the medial side 100 of the first portion 140 of the upper 130 than the first elongate member 300.

The fourth elongate member 330 is aligned with the third row 162(3) of the eyelets 160 on the medial side 100 of the upper 130, and is configured to be threaded through the slits 200 of the eyelets 160 that are aligned with the third row 162(3) of the eyelets 160. Because the third elongate member 320 is utilized to form the eyelets 160 located in the third row 162(3) of columns 164(1)-164(4) of eyelets 160 on the medial side 100 of the first portion 140 of the upper 130, the fourth elongate member 330 may only be utilized to form the eyelets 160 located in the third row 162(3) of columns 164(5)-164(7) of the eyelets 160 on the medial side 100 of the first portion 140 of the upper 130. Furthermore, the eyelets 160 located in the third row 162(3) of columns 164(5)-164(7) may contain slits 200 of that are in the first orientation 210. Thus, the fourth elongate member 330 is primarily threaded through the slits 200 that are in the first orientation 210. Similar to the other elongate members 300, 310, 320, the fourth elongate member 330 is primarily disposed on the interior surface of the first portion 140 of the upper 130, except for the exposed portions 338, which are disposed between each pair of slits 200 that form each eyelet 160 of the third row 162(3) of columns 164(5)-164(7) of eyelets 160. The exposed portions 338 of the fourth elongate member 330 are disposed on the outer surface of the first portion 140 of the upper 130, enabling a fastener 170 to be threaded between the exposed portion 338 of the fourth elongate member 330 and the outer surface of the first portion 140 of the upper 130 (as illustrated in FIGS. 1A and 1D).

FIGS. 3A, 3B, and 3C further illustrate that the elongate members 300, 310, 320, 330 are secured to the interior surface of the first portion 140 of the upper 130 by a series of panels 305, 306, 307, 316, and 326 that are coupled to the interior surface of the first portion of the upper 130. The panels 305, 306, 307, 316, and 326 may be coupled to the interior surface of the first portion 140 of the upper 130 via any conventional means, including, but not limited to, stitching, bonding, adhesives, etc. Panel 305 is positioned behind the first elongate member 300 in columns 164(5)-164(7) of the second row 162(2) of eyelets 160 on the lateral side 102 of the upper 130 to secure the first elongate member 300 to the interior surface of the lateral side 102 of first portion 140 of the upper 130 at this location. Similarly, panel 306 is positioned behind the first elongate member 300 and the fourth elongate member 330 in columns 164(5)-164(7) of the second row 162(2) of eyelets 160 on the medial side 100 of the upper 130 to secure both the first elongate member 300 and the fourth elongate member 330 to the interior surface of the medial side 100 of first portion 140 of the upper 130 at this location. As best illustrated in FIG. 3B, panel 307 is positioned behind the portion of the first elongate member 300 that traverse the instep 134 proximate to the forefoot region 110 of the article of footwear 100. Thus, panel 307 extends across the instep 134 from the medial quarter 136 to the lateral quarter 138 to secure the first elongate member 300 to the interior surface of the first portion 140 of the upper 130 at this location. As described and illustrated, the first and fourth elongate members 300, 330 are secured to the interior surface of the upper 130 in relation to the panels 305, 306, 307 and the interior surface of the upper 130 that generally prevents or limits movement

of the first and fourth elongate members 300, 330 with respect to the panels 305, 306, 307 and the interior surface of the upper 130.

Panels 316 and 326 may differ in shape from panels 305, 306, 307. As illustrated in FIGS. 3A and 3B, the panels 316, 326 may have a sawtooth wave pattern or shaped like that of the second and third elongate members 310, 320, respectively. Panel 316 may be positioned behind both the first elongate member 300 and the second elongate member 310 in the columns 164(1)-164(4) of the rows 162(1)-162(3) of the eyelets 160 on the lateral side 102 of the upper 130. As illustrated, panel 316 extends along the first column 164(1) from the third row 162(3) of eyelets 160 to the first row 162(1) of eyelets 160, where panel 316 then extends diagonally from the eyelet 160 at row 162(1) and column 164(1) to the eyelet 160 at row 162(3) and column 164(2). Panel 316 may continue to extend along the second column 164(2) from the third row 162(3) of the eyelets 160 to the first row 162(1) of eyelets, where panel 316 then extends diagonally from the eyelet 160 at row 162(1) and column 164(2) to the eyelet 160 at row 162(3) and column 164(3). The panel 316 further continues to extend along the third column 164(3) from the third row 162(3) of the eyelets 160 to the first row 162(1) of eyelets 160, then extend diagonally from the eyelet 160 at row 162(1) and column 164(3) to the eyelet 160 at row 162(3) and column 164(4), and finally extend along the fourth column 164(4) from the third row 162(3) of eyelets 160 to the first row 162(1) of eyelets 160. Because the second elongate member 310 extends across/over, in a sawtooth wave pattern, the portion of the first elongate member 300 disposed on the lateral quarter 138, the panel 316 may secure both the first elongate member 300 and the second elongate member 310 to the interior surface of the lateral side 102 of first portion 140 of the upper 130 at the lateral quarter 138. As described and illustrated, the first and second elongate members 300, 310 are secured to the interior surface of the upper 130 in relation to panel 316 and the interior surface of the upper 130 that generally prevents or limits movement of the first and second elongate members 300, 310 with respect to panel 316 and the interior surface of the upper 130.

Panel 326 may be positioned behind both the first elongate member 300 and the third elongate member 320 in the columns 164(1)-164(4) of the rows 162(1)-162(3) of eyelets 160 on the medial side 100 of the upper 130. Panel 326 is disposed columns 164(1)-164(4) and rows 162(1)-162(3) in a sawtooth wave pattern similar to that of panel 316, such that panel 316 starts at the eyelet 160 of row 162(3) and column 164(1) and ends at the eyelet 160 of row 162(1) and column 164(4). Because the third elongate member 310 extends across/over, in a sawtooth wave pattern, the portion of the first elongate member 300 disposed on the medial quarter 136, the panel 326 may secure both the first elongate member 300 and the third elongate member 320 to the interior surface of the medial side 100 of first portion 140 of the upper 130 at the medial quarter 136. As described and illustrated, the first and third elongate members 300, 320 are secured to the interior surface of the upper 130 in relation to panel 326 and the interior surface of the upper 130 that generally prevents or limits movement of the first and third elongate members 300, 320 with respect to panel 316 and the interior surface of the upper 130.

In another embodiment, the panels 305, 306, 307, 316, 326 illustrated in FIGS. 3A, 3B, and 3C may only secure the ends 302, 304 of the first elongate member 300, the ends 312, 314 of the second elongate member 310, the ends 322, 324 of the third elongate member 320, and the ends 332, 334

of the fourth elongate member **340** to the interior surface of the upper **130**. Thus, when the elongate members **300, 310, 320, 330** are secured at only their ends **302, 304, 312, 314, 322, 324, 332, 334**, the elongate members **300, 310, 320, 330** may be configured to at least partially move with respect to the upper **130**. In this embodiment, the elongate members **300, 310, 320, 330** may also be capable of at least partially moving, threading, or passing through the slits **200**. The passage or threading of the elongate members **300, 310, 320, 330** through the slits **200** also maintains the elongate members **300, 310, 320, 330** in their position against the upper **130**. In yet another embodiment, the elongate members **300, 310, 320, 330** may be secured between the panels **305, 306, 307, 316, 326** and the interior surface of the upper **130** at the ends **302, 304, 312, 314, 322, 324, 332, 334** of the elongate members **300, 310, 320, 330** and/or at select portions of each of the elongate members **300, 310, 320, 330** between the ends **302, 304, 312, 314, 322, 324, 332, 334** of the elongate members **300, 310, 320, 330**.

The panels **305, 306, 307, 316, 326** not only serve to secure the elongate members **300, 310, 320, 330** to the interior surface of the first portion **140** of the upper **130**, but they also serve to make the upper **130** more comfortable for a user. By covering the portions of the elongate members **300, 310, 320, 330** on the interior surface of the first portion **140**, the interior surface will have a smoother, more comfortable feel to a foot disposed within the article of footwear **10**. The panels **326** also help to reduce chaffing or uncomfortable rubbing of the elongated portions **300, 310, 320, 330** on the foot disposed within the article of footwear **10**. In one embodiment, the panels **305, 306, 307, 316, 326** may be constructed from suede or other form of leather that is bonded to the interior surface of the first portion **140** of the upper **130**. In another embodiment, the panels **305, 306, 307, 316, 326** may be constructed from a synthetic leather or other nonwoven product. The panels **305, 306, 307, 316, 326** may be secured to the inner surface of the first portion **140** of the upper **130** via any conventional means, including, but not limited to, bonding, adhesives, stitching, etc.

As previously explained, each of the eyelets **160** of the reconfigurable fastening system of the article of footwear **10** is formed by one of the elongate members **300, 310, 320, 330** and the exterior surface of the first portion **140** of the upper **130**. More specifically, the configuration of each of the eyelets **160** includes a pair of slits **200** and a portion of one of the elongated members **300, 310, 320, 330** that is exposed or visible on an exterior of the upper **130** via the elongated members **300, 310, 320, 330** extending through the pairs of slits **200**. The opening of each eyelet **160**, as described herein, is formed or defined by the visible or exposed portion of one of the elongate members **300, 310, 320, 330** that is threaded or passed through a pair of slits **200** and the portion of the upper **130** that is disposed between each pair of slits **200**. The opening of each eyelet **160** is configured to receive a fastener **170**, where the fastener **170** is threaded or passed through the opening of the eyelet **160** (i.e., between the upper **130** and the exposed portion of the elongate member **300, 310, 320, 330**). The opening of each eyelet **160** may be oriented transverse or orthogonal to the orientation of the pair of slits **200** that formulate the eyelet **160**. Thus, for eyelets **160** formed with slits **200** in the first orientation **210**, the openings of the eyelets **160** are oriented in a first or transverse direction (i.e., a fastener **170** passes through the opening of the eyelet **160** along the widthwise direction of the article of footwear **10**). For eyelets **160** formed with slits **200** in the second orientation **220**, the openings of the eyelets **160** are oriented in a second or lengthwise direction

(i.e., a fastener **170** passes through the opening of the eyelet **160** along the lengthwise direction of the article of footwear **10**).

With this configuration, a fastener **170** may be selectively threaded through any of the eyelets **160** on the medial and lateral sides **100, 102** of the article of footwear **10** to alter fit of the article of footwear **10** for a specific level of comfort and/or to provide a specific amount of support. The plurality of eyelets **160** disposed on both sides **100, 102** of the upper **130** enable the user of the article of footwear **10** to customize the tightness/stiffness of the article of footwear **10**, the support provided by the article of footwear **10**, and ultimately, the amount of comfort of the article of footwear **10**. The more eyelets **160** through which the fastener **170** is threaded, the more support the article of footwear **10** is capable of providing. For example, if the fastener **170** were threaded through each of the eyelets **160** in the first and third rows **162(1), 162(3)** of columns **164(1)-164(4)** on both the medial and lateral sides **100, 102** of the article of footwear **10**, the fastener **170** may be tightened such that the article of footwear **10** is tightly compressed against a foot disposed within the article of footwear **10** and capable of providing support to the arch and instep of the foot. In another example, if the fastener **170** were threaded only through the eyelets **160** located in the first row **162(1)** of columns **164(1), 164(3)** on both the medial and lateral sides **100, 102** of the article of footwear **10**, the article of footwear **10** could be fit looser around the foot disposed within the article of footwear **10**, and may not be capable of providing as much support as the previously described example. In addition, the article of footwear **10** of the second example may be more comfortable for a user with a wider foot (enabling the medial and lateral quarters **136, 138** to spread farther apart from one another), while the article of footwear **10** of the first example may be more comfortable for a user with a thinner foot. Thus, the eyelets **160** of the reconfigurable fastening system of the article of footwear **10** enable the user to optimize the support and comfort levels of the article of footwear **10** by selectively threading the fastener **170** through chosen eyelets **160** disposed on the upper **130**. The optimization may be based on footwear usage (e.g., more support for athletic activities, such as running; less support when wearing the article of footwear **10** for a prolonged period of time) and/or based on the shape of the foot disposed within the article of footwear **10** (e.g., less eyelets **160** utilized for wider feet; more eyelets **160** utilized for narrow feet). The manner and number in which the fastener **170** is threaded through the eyelets **160** enables the user to alter the topography of the upper **130** to properly fit the shape of the foot disposed within the article of footwear **10**.

Illustrated in FIGS. **4A, 4B, and 5** is a second embodiment of an article of footwear or shoe **40** with a reconfigurable fastening system similar to that as previously described. This second embodiment **40** includes a medial side **400** oriented along the medial or big toe side of the user's foot, a lateral side **402** oriented along the lateral or little toe side of the user's foot, a toe (i.e., front) end **404** that corresponds with the toes of the user's foot, and a heel (i.e., rear) end **406** that corresponds with the heel of the user's foot. While the second embodiment **40** depicted in the FIGS. **4A, 4B, and 5** shows an article of footwear **40** configured for a right foot, it is noted that the same or similar features can also be provided for an article of footwear **40** configured for a left foot (where such features of the left footed article of footwear are a reflection of or "mirror image" symmetrical

in relation to the right footed article of footwear, e.g., the embodiment depicted in FIGS. 4A, 4B, and 5).

Similar to the first embodiment of the article of footwear 10, the second embodiment 40 may include a forefoot region 410 that generally aligns with the ball and toes of a user's foot (i.e., when a user is wearing the article of footwear 40), a midfoot region 412 that generally aligns with the arch and instep areas of the user's foot, and a hindfoot region 414 that generally aligns with the heel and ankle areas of the user's foot. The second embodiment of the article of footwear 40 further includes a sole structure 420 and an upper 430 affixed to the sole structure 420. The upper 430 defines an envelope or pocket that covers and protects the foot of the wearer. In some embodiments, the upper 430 covers and protects the foot of the wearer together with the sole structure 420. The upper 430 includes a toe cage 432 disposed proximate to the front end 404 of the forefoot region 410 of the article of footwear 40. As further illustrated, the upper 430 also includes an instep 434, where the instep 434 is disposed rearward of the toe cage 432 within the midfoot region 412 of the article of footwear 40. The upper 430 may further include a heel cup 439 disposed in the hindfoot region 414 and around the heel end 406 of the article of footwear 40. In addition, similar to the first embodiment of the article of footwear 10, the upper 430 of the second embodiment 40 includes a medial quarter 436 that extends through the midfoot region 412 from the toe cage 432 to the heel cup 439 along the medial side 400, and a lateral quarter 438 that extends through the midfoot region 412 from the toe cage 432 to the heel cup 439 along the lateral side 402. The upper 430 may further include an exterior surface 490 (illustrated in FIGS. 4A and 4B) and an interior surface 500 (illustrated in FIG. 5).

Like the first embodiment of the article of footwear 10, the upper 430 of the second embodiment of the article of footwear 40 includes a first portion 440 and a second portion 450. As illustrated in FIGS. 4A and 4B, the first portion 440 may form a lower portion of the upper 430, while the second portion 450 may form an upper portion of the upper 430. The second portion 450 may further define an aperture 454 that provides access to the interior of the second embodiment of the article of footwear 40. As illustrated, both the first portion 440 and the second portion 450 may be formed or constructed from a knit material/fabric (e.g., flat knit, circular knit, etc.) or a woven material/fabric. This enables the upper 430 to be a more flexible, elastic, and/or breathable material than uppers constructed of conventional materials (e.g., leather, suede, plastics, etc.). This also enables the upper 430 of the second embodiment of the article of footwear 40 to be lighter than conventional footwear. While both the first and the second portions 440, 450 may be formed of knit/woven materials, the second portion 450 may be more resilient and elastic material than the first portion 440.

As illustrated in FIGS. 4A and 4B, a plurality of eyelets 460 are disposed on the first portion 440 of the upper 430, and more specifically, the medial and lateral quarters 436, 438 of the upper 430. Each of the plurality of eyelets 460 of the second embodiment of the article of footwear 40 is configured to receive a portion of a fastener (i.e., a fastener may be threaded through each of the plurality of eyelets 460). As illustrated in FIGS. 4A, and 4B, the plurality of eyelets 460 are disposed on the medial and lateral sides 400, 402 of the upper 430 in a grid-like array (i.e., in a series of rows and columns) like that of the eyelets 160 of the first embodiment of the article of footwear 10. Unlike the first embodiment of the article of footwear 10, the second

embodiment 40 does not contain any eyelets 460 that are disposed across the instep 434 of the upper 430.

The plurality of eyelets 460 of the second embodiment 40 may be constructed in a similar manner as the eyelets 160 of the first embodiment 10, where each of the eyelets 460 is formed from a pair of slits disposed in the upper and an elongate member threaded through the slits such that an exposed portion of the elongate member is disposed on the exterior surface 490 of the upper 430. As best illustrated in FIG. 5, a single elongate member 510 is utilized to form the plurality of eyelets 460 on the medial side 400 of the second embodiment of the article of footwear 40, by threading the elongate member 510 through the pairs of slits on the medial side 400 in a square wave pattern. While not illustrated, a single elongate member is also utilized to form the plurality of eyelets 460 on the lateral side 402 of the second embodiment of the article of footwear 40 by threading the single elongate member through the pairs of slits on the lateral side 402 in a square wave pattern. Thus, only two elongate members are used to form the eyelets 460 of the second embodiment of the article of footwear 10.

The elongate member 510 is shown in FIG. 5 is disposed mainly on the interior surface 500 of the medial quarter 436. The elongate member 510 is illustrated as having gaps 520, which are the result of the elongate member 510 being threaded through the slits of the eyelets 460 to create the exposed portions of the elongate member 510 on the exterior surface 490 of the upper 430. A panel 530 may be disposed on the interior surface 500 of the medial quarter 436 and over the elongate member 510 to capture and secure portions of the elongate member 510 against the interior surface 500 of the medial quarter 436. The panel 530 may be constructed from any material (e.g., suede) that provides structure and rigidity to the medial quarter 436 of the upper 430 while also securing the elongate member 510 in place. Because the panel 530 covers the portions of the elongate member 510 disposed on the interior surface 500, the panel 530 may serve to make the interior surface 500 of the medial quarter 436 more comfortable (i.e., by smoothing the interior surface 500 and potentially eliminating or reducing any potential irritations caused by the portions of the elongate member 510 disposed on the interior surface 500). While the interior surface 500 of the lateral quarter 438 is not illustrated, the lateral quarter 438 may include an elongate member and panel that is substantially identical to that of the medial quarter 436.

A fastener may be threaded through one or more of the eyelets 460 on the medial side 400 of the article of footwear 40 and one or more of the eyelets 460 on the lateral side 402 of the article of footwear 40, where the fastener may be pulled to tighten the upper 130 around a foot disposed within the article of footwear 40. Unlike the eyelets 160 of the first embodiment of the article of footwear 10, the eyelets 460 of the second embodiment of the article of footwear 40 are all oriented in the same orientation (i.e., similar to the second orientation 220 of the eyelets 160 of the first embodiment of the article of footwear 10), where the openings (i.e., the space between the exposed portion of the elongate member 510 and the exterior surface 490 of the upper 430) of the eyelets 460 are oriented in a lengthwise direction (i.e., a fastener passes through the opening of the eyelet 460 along the lengthwise direction of the second embodiment article of footwear 40).

Like the first embodiment of the article footwear 10, the eyelets 460 of the reconfigurable fastening system of the second embodiment of the article of footwear 40 enable the user to optimize the support and comfort levels of the article

of footwear **10** by selectively threading a fastener through a chosen set of eyelets **460** disposed on the upper **430**. The optimization may be based on footwear usage (e.g., more support for athletic activities, such as running; less support when wearing the article of footwear **40** for a prolonged period of time) and/or based on the shape of the foot disposed within the article of footwear **40** (e.g., less eyelets **460** utilized for wider feet; more eyelets **460** utilized for narrow feet). Thus, the manner in which a fastener is threaded through the eyelets **460** enables a user to alter the topography of the upper **430** to properly fit the shape of the foot disposed within the article of footwear **40**.

It is to be understood that terms such as “left,” “right,” “top,” “bottom,” “front,” “rear,” “side,” “height,” “length,” “width,” “upper,” “lower,” “interior,” “exterior,” “inner,” “outer” and the like as may be used herein, merely describe points or portions of reference and do not limit the present invention to any particular orientation or configuration. Further, the term “exemplary” is used herein to describe an example or illustration. Any embodiment described herein as exemplary is not to be construed as a preferred or advantageous embodiment, but rather as one example or illustration of a possible embodiment of the invention.

Although the disclosed inventions are illustrated and described herein as embodied in one or more specific examples, it is nevertheless not intended to be limited to the details shown, since various modifications and structural changes may be made therein without departing from the scope of the inventions and within the scope and range of equivalents of the claims. In addition, various features from one of the embodiments may be incorporated into another of the embodiments. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the disclosure as set forth in the following claims.

What is claimed is:

1. An article of footwear comprising:

a sole;

an upper coupled to the sole, the upper including an inner surface and an outer surface, the upper being configured to receive at least a portion of a human foot within an interior cavity at least partially defined by the upper;

a plurality of eyelets disposed on the upper, each eyelet including a pair of openings disposed in the upper, the plurality of eyelets including a first set of eyelets and a second set of eyelets, each eyelet of the first set including a pair of openings that extend in a first direction that is a longitudinal direction of the article of footwear, and each eyelet of the second set including a pair of openings that extend in a second direction transverse the first direction; and

a plurality of cords threaded through pairs of openings of the plurality of eyelets such that each cord includes a series of unexposed portions and a series of exposed portions, wherein the series of exposed portions are disposed more proximate to the outer surface of the upper than the inner surface of the upper, and the

plurality of cords includes a first cord threaded through the eyelets of the first set and a second cord threaded through the eyelets of the second set.

2. The article of footwear of claim 1, wherein the series of unexposed portions are portions of each cord that are disposed between consecutive pairs of the eyelets, and the series of exposed portions are portions of each cord that are disposed between the pair of openings of each corresponding eyelet through which each cord is threaded.

3. The article of footwear of claim 1, wherein the upper includes a medial quarter, a lateral quarter, a toe cage, an instep, and a heel cup.

4. The article of footwear of claim 3, wherein the plurality of eyelets are disposed on at least one of the medial quarter, the lateral quarter, the instep, and the heel cup.

5. The article of footwear of claim 4, wherein:

the first cord is disposed proximate to the medial quarter or the lateral quarter and the first set of eyelets is disposed at the medial quarter or the lateral quarter; and the second cord extends through the second set of eyelets spanning a medial side of the heel cup, through the medial quarter, over the instep, through the lateral quarter, and to a lateral side of the heel cup.

6. An article of footwear comprising:

a sole;

an upper coupled to the sole, the upper being configured to receive at least a portion of a human foot; and

a plurality of eyelets disposed on the upper, each eyelet including a pair of slits disposed in the upper, the pair of slits of each eyelet of a first portion of the plurality of eyelets extending in a first direction, and the pair of slits of each eyelet of a second portion of the plurality of eyelets extending in a second direction that differs from the first direction, the first direction being in a longitudinal direction of the article of apparel and the second direction being transverse the first direction; a first cord extending through the first portion of the plurality of the eyelets; and

a second cord extending through the second portion of the plurality of the eyelets;

wherein each of the first cord and the second cord is threaded through the first portion of the plurality of the eyelets or the second portion of the plurality of the eyelets such that each of the first cord and the second cord includes a series of unexposed portions and a series of exposed portions.

7. The article of footwear of claim 6, wherein the unexposed portions of each of the first cord and the second cord are disposed between each of the eyelets of the first portion of the plurality of the eyelets or the second portion of the plurality of the eyelets, and the exposed portions of each of the first cord and the second cord are disposed between the pair of slits of each eyelet of the first portion of the plurality of the eyelets or the second portion of the plurality of the eyelets.

\* \* \* \* \*