



US011973821B2

(12) **United States Patent**
Koreeda et al.

(10) **Patent No.:** **US 11,973,821 B2**
(45) **Date of Patent:** ***Apr. 30, 2024**

(54) **DOWNLOAD CONTROL DEVICE**

(71) Applicant: **Maxell, Ltd.**, Kyoto (JP)

(72) Inventors: **Hiroyuki Koreeda**, Fujisawa (JP);
Satoshi Mio, Yokohama (JP)

(73) Assignee: **Maxell, Ltd.**, Kyoto (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/126,582**

(22) Filed: **Mar. 27, 2023**

(65) **Prior Publication Data**

US 2023/0239339 A1 Jul. 27, 2023

Related U.S. Application Data

(63) Continuation of application No. 17/678,354, filed on Feb. 23, 2022, now Pat. No. 11,641,390, which is a (Continued)

(30) **Foreign Application Priority Data**

Apr. 20, 2007 (JP) 2007-111200

(51) **Int. Cl.**

H04L 67/06 (2022.01)

G06F 16/958 (2019.01)

(Continued)

(52) **U.S. Cl.**

CPC **H04L 67/06** (2013.01); **G06F 16/958** (2019.01); **H04L 67/62** (2022.05); **H04L 67/02** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,862,325 A 1/1999 Reed et al.

6,212,188 B1 4/2001 Rochberger

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1698377 A 11/2005

JP 2001-051928 A 2/2001

(Continued)

OTHER PUBLICATIONS

Red Cruise Corp., "RSS Media Business Saizensen Denshi Mail, Web ni Tsuzuku Dai San no Internet Media", Internet magazine make innovation with technology; No. 127, Aug. 1, 2005; p. 44-71.

(Continued)

Primary Examiner — Ranodhi Serrao


(74) *Attorney, Agent, or Firm* — Mattingly & Malur, PC

(57)

ABSTRACT

When download operations get started in unison in conformity to RSS metafile delivery time-and-date information, the traffic is temporarily concentrated to a server, resulting in the risk of a system failure or else. In addition, it is inevitable to periodically check whether an RSS file on Web server is updated or not; so, users must delete update-unnecessary RSS files from those objects to be monitored. In view of this, the periodical update check timing of download control information is dispersed, thereby scattering download requests to the server. The download control information is provided with the information indicating whether such download control information is put under update management and/or expire time-and-date information in case the update management is to be done, whereby an information processing apparatus performs, based on the information, erase processing of the download control information when the download processing is completed.

20 Claims, 8 Drawing Sheets



Related U.S. Application Data

continuation of application No. 17/061,695, filed on Oct. 2, 2020, now Pat. No. 11,271,988, which is a continuation of application No. 16/224,914, filed on Dec. 19, 2018, now Pat. No. 10,834,172, which is a continuation of application No. 15/403,596, filed on Jan. 11, 2017, now Pat. No. 10,200,449, which is a continuation of application No. 12/596,517, filed as application No. PCT/JP2008/053269 on Feb. 26, 2008, now Pat. No. 9,576,063.

- (51) **Int. Cl.**
H04L 67/62 (2022.01)
H04L 67/02 (2022.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,456,600	B1	9/2002	Rochberger	
6,633,757	B1	10/2003	Hermann	
6,931,198	B1	8/2005	Hamada	
7,203,760	B2	4/2007	Shimada	
7,752,643	B2	7/2010	Ito et al.	
8,032,538	B2 *	10/2011	Iwatsu	G06Q 30/0603 707/752
8,051,449	B2 *	11/2011	Kunii	H04N 21/42209 725/54
8,079,029	B2 *	12/2011	Sakoh	H04L 63/10 705/51
8,090,764	B2 *	1/2012	Sato	H04N 21/8355 709/217
8,108,362	B2	1/2012	Hydrie et al.	
8,156,436	B2 *	4/2012	Matsutani	G11B 27/034 715/727
8,255,488	B2 *	8/2012	Tanaka	G06F 16/4387 709/219
8,370,196	B2 *	2/2013	Choi	H04L 67/04 705/14.64
8,806,027	B2	8/2014	Abanami	
9,100,547	B2 *	8/2015	Lavender	H04N 21/4331

9,887,789	B2 *	2/2018	Wu	H04H 20/82
2002/0062375	A1	5/2002	Teodosiu	
2002/0067371	A1	6/2002	Wu	
2002/0112058	A1	8/2002	Weisman	
2003/0182254	A1	9/2003	Plastina	
2003/0182315	A1	9/2003	Plastina	
2004/0098533	A1	5/2004	Henshaw	
2006/0025875	A1	2/2006	Smith et al.	
2006/0095543	A1	5/2006	Ito et al.	
2006/0168119	A1	7/2006	Inoue	
2006/0212943	A1	9/2006	Kitazato et al.	
2007/0061282	A1	3/2007	Ganguly et al.	
2007/0143390	A1	6/2007	Giambalvo et al.	
2008/0046544	A1	2/2008	Sakoh	
2008/0162666	A1	7/2008	Ebihara	
2008/0189099	A1	8/2008	Friedman et al.	
2008/0195620	A1	8/2008	Abanami	
2008/0195621	A1	8/2008	Tedesco	
2009/0313663	A1	12/2009	Kitazato	
2010/0046931	A1	2/2010	Takao	
2010/0100899	A1	4/2010	Bradbury	
2010/0138536	A1	6/2010	Koreeda	
2010/0322591	A1	12/2010	Takao	
2012/0233343	A1	9/2012	Tedisco	

FOREIGN PATENT DOCUMENTS

JP	2002-073455	A	3/2002
JP	2002-202927	A	7/2002
JP	2003-208376	A	7/2003
JP	2004-246822	A	9/2004
JP	2005-006203	A	1/2005
JP	2006-99341	A	4/2006
JP	2006-244336	A	9/2006
JP	2006-350500	A	12/2006
JP	2006-350746	A	12/2006

OTHER PUBLICATIONS

Office Action issued in Japanese Patent Application No. 2011-156265 dated Aug. 28, 2012.

* cited by examiner

FIG. 1




FIG.2

DOWNLOAD CONTROL METAFILE 120




FIG.3




FIG.4




FIG.5




FIG.6

DOWNLOADER UPDATE PROCESSING 1100






FIG.7

DOWNLOAD EXECUTION ORDER
DETERMINATION PROCESSING
1300



DOWNLOADER EXECUTION PROCESSING 1000

FIG.8



DOWNLOAD CONTROL DEVICE

INCORPORATION BY REFERENCE

This application is a continuation of U.S. patent application Ser. No. 17/678,354, filed Feb. 23, 2022, which is a continuation of U.S. patent application Ser. No. 17/061,695, filed Oct. 2, 2020, now U.S. Pat. No. 11,271,988 which is a continuation of U.S. patent application Ser. No. 16/224,914, filed Dec. 19, 2018, now U.S. Pat. No. 10,834,172, which is a continuation of U.S. patent application Ser. No. 15/403,596, filed Jan. 11, 2017, now U.S. Pat. No. 10,200,449, which is a continuation of U.S. patent application Ser. No. 12/596,517, filed Nov. 27, 2009, now U.S. Pat. No. 9,576,063, which relates to and claims priority from Japanese Patent Application No. 2007-111200 filed Apr. 20, 2007, the entire disclosure of which is incorporated herein by reference.

TECHNICAL FIELD

The technical field relates to a download control apparatus which controls the downloading of contents, such as data, programs and others.

BACKGROUND ART

Regarding the above-noted technical field, Patent Document 1, for example, is aimed at a challenge for “enabling an information distributor to continuously perform information delivery to registered users” and contains a written description as to the solution means thereof, which reads as follows: “An information delivery system comprises a transmission site **30** which transmits delivery information containing therein date information that is written in a specified format, an information delivery server **20** capable of acquiring the delivery information from each transmission site **30**, and an information terminal **10** which acquires delivery information from the information delivery server **20**. The information terminal **10** has a display means **14** capable of displaying a calendar browser **40** that displays delivery information in a calendar-like form, a mark generation means **16** which extracts date information from the delivery information acquired from the information delivery server **20** and which displays an information mark **47** indicative of the arrival of delivery information in a corresponding data column of the calendar browser **40** corresponding to the date information, and a display changeover means **17** which is responsive to selection of the date column with the information mark **47** being displayed, for switching to a content display screen that displays the contents of the delivery information as included in such selected date column. Thus provided is a contents delivery system capable of promptly delivering only high-necessity contents by taking account of the degree of necessity of a user on a per-content basis.” Patent Document 1: JP-A-2006-350746.

DISCLOSURE OF THE INVENTION

Problems to be Solved by Invention

As broadband Internet services become popular, a service for delivering via the Internet those contents attracts increasing attention, which contents include videos, photos, music, multimedia data and application programs.

When purchasing and downloading these various kinds of contents, an Internet browser is utilized in an information

processing apparatus, such as PC or the like, whereby the user uses an operation device to indicate contents that are linked from HTML contents to thereby perform purchasing and downloading operations.

At this time, in order to improve the convenience of such download of contents, it is desirable to provide a function which enables all-at-once downloading of a great number of contents, successive download of periodically delivered contents, and update of downloaded contents upon delivery of a new version of contents.

To provide this download function, a tag language of XML format, called RSS (RDF Site Summary) which is also recited in the above-noted patent document 1, is sometimes used as standardized download control information. In one RSS file, a title or name of the RSS file per se and its location on the Internet (URL) are written while letting a plurality of pieces of information necessary for contents downloading, called the items, be described therein. More specifically, there are recited the title of contents to be downloaded, data type, size, download destination (URL), delivery time-and-date, etc.

RSS files are put on a Web server, for example. An information processing apparatus is responsive to receipt of an instruction through a user’s operation, for reading an RSS file which is linked from HTML contents to thereby perform downloading of the contents that are recited in the RSS file in accordance with the description of a metafile.

However, in the Patent Document 1 and such downloader application, prior known RSS-based download control schemes are faced with problems which will be described below.

Firstly, in accordance with the RSS metafile delivery time-and-date information, information processing apparatuses complying with such metafile begin to perform download operations in unison, resulting in the traffic being temporarily concentrated to a server, which leads to the occurrence of operation failures, such as system down or the like. Especially, in cases where the information processing apparatus is home-use equipment that is designed to download home movies (e.g., a television set, recorder or else), the contents are videos so that these are large in capacity and, simultaneously, are large in number due to consumer use; thus, risks are worried in particular.

In addition, the use of such RSS file raises a need for the information processing apparatus to periodically check whether the RSS file on Web server is updated or not. Contents include update-unnecessary ones and those which are updated by a certain time of year but are no longer updated after the time. As far as these contents are concerned, the information processing apparatus is unable to know the presence or absence of an update event in future. For this reason, a user who uses the information processing apparatus is required to make his or her own decision by using information available from a service provider and perform deletion of an unnecessary RSS file from those objects to be monitored. This would result in an increase in complexity of user’s manual operations and/or waste of network traffic.

Means for Solving Problems

Consequently, the periodical update check time of download control information is dispersed to thereby scatter download requests as sent to a server, for example.

Additionally, the download control information is arranged so that it is provided with information indicative of whether such download control information performs

update management and/or time-and-date information of an update time limit in the case of the update management being performed, thereby permitting the information processing apparatus to perform, based on these information items, the erase processing for deletion of the download control information upon completion of download processing.

Advantageous Effects of Invention

According to the above-stated means, it is possible to avoid the traffic concentration, for example. It is also possible to perform appropriate update processing with respect to each of one-shot (only one time) delivered contents and a series of contents which are delivered periodically or opportunistically.

These and other objects, features and advantages of the invention will be apparent from the following description of an embodiment of the invention, as illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 A block diagram showing a configuration example of an information processing apparatus and system.

FIG. 2 A data diagram showing a configuration example of download control metafile.

FIG. 3 A flow diagram showing an example of processing sequence of Web server and information processing apparatus.

FIG. 4 A data diagram showing a configuration example of downloader management information.

FIG. 5 A flow diagram showing an example of system initial setup processing and timer interrupt processing.

FIG. 6 A flow diagram showing an example of downloader update processing.

FIG. 7 A flow diagram showing an example of download execution order determination processing.

FIG. 8 A flow diagram showing an example of downloader execution processing.

BEST MODE FOR CARRYING OUT THE INVENTION

An example of preferred form (embodiment) of this invention will be explained with reference to figures of the drawing. Note here that this invention should not be limited to this embodiment.

FIG. 1 shows the relationship of an information processing apparatus 400 and its related system.

In the information processing apparatus 400, a CPU 420 executes a program(s) that is stored in a memory 430 or HDD 450 to thereby execute various kinds of processing tasks. Examples of the information processing apparatus 400 are a television set, recorder, personal computer or else, which has a recording function with connection to a network.

The information processing apparatus 400 has a real time clock (RTC) 460 and thus holds a real time in any events, which can be referred from the above-noted program; so, it has the timer function for causing the CPU 420 to execute a program at any designated time of a day.

In addition, a hard disk drive (HDD) is connected through a hard disk interface (HDD I/F) 440 so that the above-noted program is able to perform read/write processing of a large capacity of data.

Additionally, it is connected to a router (this may be a gateway or else, which will also be collectively called the repeater device) 310 via a network interface (LAN I/F) 410 and thus is linked to the Internet 300. Servers which are accessible via the Internet include a Web server 100 and a file server 200.

The Web server 100 retains a Web page 110 to which reference is made in order to perform display by Web browsing function owned by the information processing apparatus 400 and a download control metafile 120 which describes control information needed for the information processing apparatus 400 to download various contents. It also has a hardware configuration, such as the information processing apparatus 400; for example, CPU executes a program that is stored in a memory or HDD to thereby perform various kinds of processing tasks.

In the file server 200, a main body of data of contents 210 to be downloaded is put. It also has a hardware configuration, such as the information processing apparatus 400; for example, CPU executes a program that is stored in a memory or HDD, thereby to perform various kinds of processings.

When a request for acquisition of contents is sent from the information processing apparatus 400 to the file server 200, data of such contents is delivered via the Internet; by recording it to the HDD via the HDD I/F 440, a downloading session is completed.

A more detailed example is as follows: first, after authentication of ID of the information processing apparatus 400 (or a user) is executed at a service provider, the Web server 100 acquires an HTML Web page. Upon execution of purchase processing of a package (contents) by use of such Web page, both the ID of such package (contents) and ID of information processing apparatus (or user) are sent to an accounting server for management of clients, followed by execution of billing. After completion of the billing, a download control metafile is downloaded from the Web server 100 to the information processing apparatus 400. In accordance with this download control metafile, the package (contents) is downloaded from the file server 200. When playing back the package (contents) thus downloaded, a playback control metafile or DRM key data or contents metadata is acquired if need arises.

Note here that the apparatuses which control download, such as the information processing apparatus 400 and servers 100 and 200, are collectively called the download control apparatus.

FIG. 2 shows a configuration example of the download control metafile 120. The download control metafile 120 contains download control information 130 which describes the contents of the metafile per se, and download execution information 140 which is used to download one or a plurality of contents. This download control metafile 120 is generated at the Web server 100, for example, including download control information 130, download execution information 140 and various kinds of data groups as shown in FIG. 2 in greater detail. This generating part (e.g., the unit for executing a program in CPU of Web server) is also referred to as a download control metafile generation unit.

This download control metafile 120 is described by RSS, as an example. Although the download control metafile is creatable (preparable) for a plurality of given contents within a package, it does not bridge between a plurality of packages. It is also possible to prepare a plurality of ones for a certain package. Note however that the metafile is prepared without fail in such a way that all the contents within a package are downloadable. The download control metafile

120 is updated from time to time; in view of this, a transmitter checks in a predetermined length of time cycle and updates a difference, if any. In the case of RSS, an enclosure url is used to perform discrimination between respective contents.

The download control information **130** has a download control metafile name **131** which indicates the title of a corresponding download control metafile **120** (e.g., download reservation title, file name, ID, etc.), a download control metafile location **132** which indicates the location of a corresponding download control metafile **120** (e.g., URL of a Web site on the Internet that provides download reservation, which may alternatively be an address that is not limited to URL—the same will be true on the location below), a download control metafile explanation sentence **133** which indicates an explanation of a corresponding download control metafile **120** (e.g., explanation as to download reservation, language type, etc.), an update check flag **134**, and an expire time-and-date **135**.

The update check flag **134** is a flag which is for determining whether the download control metafile **120** on the Web server **100** is changed in content and whether periodical check is performed or not. The flag takes a value of “Update” indicating the need to perform checking or a value of “One Shot” indicating elimination of periodical check after first acquisition. The expire time/date **135** is effective in the case of the update check flag **134** being set to “Update,” in which are recited the date and hour of a time limit of continuing to check the update of the download control metafile **120**.

The expire time/date **135** indicates a time limit of the update surveillance of contents. The unit of such time limit is arbitrarily settable (in units of dates, hours or minutes). It can also take a value indicating “No Time Limit,” i.e., semipermanently continuing to check.

In addition, as another embodiment, a special value (e.g., all zeros) of the expire time/date **135** is handled as the value indicating the “One Shot” of the update check flag **134**, thereby making it possible to realize an arrangement which omits the update check flag **134**.

The download execution information **140** is such that a plurality of ones are describable in the download control metafile **120**. For each set of contents to be downloaded, it stores several information, such as a delivery content title **141** which indicates the title of such content (this may be a TV program title or, alternatively, a file name or ID), an explanation sentence **142** of the delivery content which indicates an explanation of such content (such as features, remarks, etc.), a delivery time-and-date **143** indicating a date and hour for delivery of such content (this may be in units of days or minutes), a delivery content location **144** which indicates the location of such content, a category/type **145** of delivery content, a delivery content-use metafile location **146** which indicates the location of a metafile corresponding to such content, and a size **147** of the delivery content.

Although the delivery time/date **143** is usually arranged to describe the time and date on which content is stored in the file server **200** and laid open to the public, a delivery-scheduled time-and-date in future may alternatively be recited in the delivery time/date **143** in cases where the content is not laid open yet when the download control metafile **120** is delivered. In case once-delivered content are updated in content, a time and date of such updating are recited in the delivery time/date **143**.

The delivery content file type **145** is for recitation of the category or type of a video, photo, music, program, multimedia data or else. The video may be further divided into

more detailed ones, such as movies, news, sports and others whereas the music is further categorizable into several ones, such as classical music, rock, jazz, etc., the types of which may be recited therein.

The delivery content-use metafile is the attribute information that is needed for playback or execution of contents. One example of it is genre/keyword information for use in search of contents. Another example in the case of the content being video information is thumbnail or chapter information thereof.

It is noted that all or part of the download control metafile **120** and the download control information **130** and the download execution information **140** will be called the download control data.

FIG. 3 shows an example of a procedure which permits the information processing apparatus **400** to acquire the download control metafile **120**.

A program of the Web browser **500** which is executed by the information processing apparatus **400** (this will be simply referred to hereinafter as Web browser **500**) performs a request for acquisition of a Web page with respect to the Web server **100** and then displays the Web page acquired. In FIG. 3, first of all, a Web page a **111** (for example, including HTML and a display screen which displays titles of contents, such as a pack, cinema, TV program, music, etc.) is displayed; then, a user operates the contents by an operation device, such as a remote controller, and when selecting a button “Purchase,” a Web page b **112** which is link-recited at the “Purchase” button is acquired and displayed on the Web page a **111**. In the example of FIG. 3, a display screen is shown as the Web page a **111**, which displays a pack title “Kashiwa FC '06 Pack,” price “3,000 yen,” a message saying “All games of Kashiwa FC in 2006 are available,” a set of viewing/listening and copying conditions “No limits” and “3 Copies,” and buttons named “Purchase” and “Return.” Additionally a screen is shown as the Web page b **112**, which displays a TV program title “Kashiwa FC '06 Pack” and an ensemble of buttons for choosing contents to be downloaded from this pack (e.g., when choosing “All,” all contents included in the pack are downloaded; when selecting “June,” contents corresponding to June are downloaded). On this Web page, every download button is provided with its own download control metafile **120** which describes contents to be downloaded, with a link defined thereto. Upon selection of the “Kashiwa FC '06 Pack,” a download control metafile **120** is acquired, which contains download control information **130** that includes “Kashiwa FC '06 Pack” as the title **131** and download execution information **140** corresponding to a respective one of all games of Kashiwa FC in 2006 (if the game number is 50 then there are 50 items of download execution information **140**), for example. Alternatively, upon selection of “March,” a download control metafile **120** is obtained, which contains download control information **130** that includes “Kashiwa FC '06 Pack March” as the title **131** and download execution information **140** corresponding to a respective one of all games of Kashiwa FC of March in 2006 (if the game number is 5 then there are 5 sets of download execution information **140**), for example (the Web server **100** transfers, and information processing apparatus **400** receives).

On this Web page b **112**, when the user chooses the “Download” button, the Web browser **500** issues to the Web server **100** a request for sending the download control metafile **120** which is link-recited at the “Download” button. Upon receipt of the download control metafile **120**, the Web browser **500** passes such data to a downloader **550** (a

program of the downloader **550** to be executed by the information processing apparatus **400**).

The downloader **550** analyzes the content of this passed download control metafile **120** (at **560**) and registers the download reservation information **130** recited therein to a download reservation management table **850** which will be explained in FIG. **4** (**570**), and then registers its corresponding download execution information **140** to a download execution management table **870** which will be explained in FIG. **4** (**580**). Thereafter, it executes a download execution order determination processing **1300** which will be described later in FIG. **7** (**590**).

FIG. **4** shows a configuration example of a database which is under management of the downloader **550**.

Downloader management information **800** is the information that the downloader **550** manages timings of checking update of the download control metafile **120**. Check cycle information **810** is, for example, a predetermined check cycle time to be set by users. Last check time-and-date **820** is the information indicative of the date and hour of a check that was last performed in a periodical check event. Next check schedule time-and-date **830** is the data and hour that was determined by adding the check cycle information **810** to the last check time/date **820**; by setting this value to a timer of the RTC **460**, it is possible to check update of the download control metafile **120** at a time equal to the next check schedule time/date **830**.

The download reservation management table **850** is a table for management of download reservation corresponding to the download control metafile **120** that is instructed by the Web page **b 112** of FIG. **3**. It has a download reservation title **851**, download reservation location **852**, download reservation explanation sentence **853**, update check flag **854** and expire time/date **855**, in which are respectively stored the download control metafile name **131**, download control metafile location **132**, download control metafile explanation sentence **133**, update check flag **134** and expire time/date **135** of the download control information **130**.

The download execution management table **870** is a table for management of download execution situations with respect to respective contents. It has a delivery content title **871**, delivery content explanation sentence **872**, delivery time-and-date **873**, delivery content location **874**, delivery content type **875**, delivery content-use metafile location **876** and delivery content size **877**, in which are respectively stored a delivery content title **141**, delivery content explanation sentence **142**, delivery time-and-date **143**, delivery content location **144**, delivery content type **145**, delivery content-use metafile location **146** and delivery content size **147** of the download execution information **140** of the download control metafile **120** of FIG. **2**, which was imported.

A download execution state **878** has several values of "Not Executed," "Downloading," "Downloaded" and "Halt State" and is used by the downloader **550** in order to manage the download execution state. Download progress information **879** is the information that is used to manage the degree of progress of a download operation; as an example, it serially stores a size of download-completed contents. In this case, by obtaining a ratio of it to the delivery content size **877**, it is possible to display the download progress degree to the user in percentage (%), for example. At this time, in case the download execution state **878** is set to "Not Executed," the download progress information **879**'s value stays at zero; in the case of "Downloaded," the value of download progress information **879** is set equal to the delivery content size **877**.

An appropriate number (M) of download execution management tables **870** are prepared, which number corresponds to the number of download-manageable contents.

In download execution management table pointers (1 **856** to N **857**) of the download reservation management table **850**, the location of the download execution management table **870** (such as an address within HDD **450** or an address of the memory **430**) is stored. N is the number of importable download execution information **140**, which is different depending on a system design employed.

A download execution order table **900** is the table that the downloader **550** manages the priority degree of download execution. It includes an array of M pointers **910** relative to the download execution management table **870**. Let this array be in an execution order, for example. The execution order is determined by the download execution order determination processing **1300**.

The part that records the download control metafile in this way (e.g., HDD or memory) will also be called the download control metafile recording unit.

FIG. **5** shows a processing example to be performed by the downloader **550**.

It is a system initial setup processing **600** of FIG. **5** that is performed in the information processing apparatus **400**. Here, first, an input of a download control metafile check cycle is received from the user by means of the remote controller or else (at **610**). For example, the user is expected to input information at time intervals on a per-day or per-hour basis. The input check cycle time is set in a field of check cycle time **810** (**620**). Next, a random number is generated in such a way as to cause every information processing apparatus **400** to generate a different value (**630**); then, based on such value, a reference time-and-date for checking the first download control metafile is generated (**640**). The initial setup may be done in such a manner that the check cycle time is fixed in the absence of reception of the user's setup or, alternatively, it is variably set up by the user.

The time-and-date information thus generated is stored in the next check schedule time/date **830** (**650**); then, a timer interrupt generation request of the time point of the next check schedule time/date **830** is set in the RTC **460** (**660**).

It is a timer interrupt processing **700** that is executed after having set up the timer interrupt generation request at **660**.

At **660**, when it becomes the time point that is set by the timer, the timer interrupt processing **700** of FIG. **5** is executed. The timer interrupt processing **700** is such that the value of the next check schedule time/date **830** is copied to the last check time/date **820** (**720**) to thereby execute a download update processing **1100** (**730**).

Thereafter, a value obtained by adding the check cycle time **810** to the last check time/date **820** is stored in the next check schedule time/date **830** (**740**); then, the timer interrupt generation request of the time point of the next check schedule time/date **830** is set in the RTC **460** (**750**). Whereby, the timer interrupt processing **700** is performed in accordance with the check cycle time **810**; so, it is possible to check update of the download control metafile **120** in a fixed time cycle that was designated by the user, for example.

The part that sets up the update check timing (e.g., a part of the CPU which is executed by a program) in this way will also be called the check timing setup unit.

FIG. **6** shows a detailed example of the download update processing **1100** to be executed at **730** of FIG. **5**.

The download update processing **1100** is such that in a sequential order of from the top record of the download

reservation management table **850** (**1110**), a check is made to determine whether the value of the update check flag **854** is “Update” or not (**1120**). If “Update” then check whether the expire time/date **855** has a past value than the present time, i.e., whether it is expiration of limitation period or not (**1130**). If not the expiration of deadline, access is given to the URL that is indicated by the download reservation location **852**, thereby checking whether the download control metafile **120** is updated or not (**1140**). If the download control metafile **120** on a server is updated (**1150**), a new version of download control metafile **120** is downloaded; then, check a difference between corresponding download reservation management table **850** and download execution management table **870** (**1160**).

As a result of the checking, whether deletion is done from the download execution information **140** is checked as to the download execution management table **870** which is a referencing destination of the download execution management table pointers 1-N (**1170**); if any, a record of the corresponding download execution management table **870** is deleted (**1180**). Next, regarding the download execution management table **870** of the referencing destination of the download execution management table pointers 1-N, an attempt is made to check whether the download execution information **140** that does not present in the presently existing download execution management table **870** is added or not (**1190**); if any, add a record of the corresponding download execution management table **870** (**1200**). Further, as for the download execution management table **870** of the reference destination of download execution management table pointers 1-N, checking is done to specify whether information is updated or not in new download execution information **140** (**1210**); if any updated part is found, modify a corresponding field value of the download execution management table **870** (**1220**).

In this way, the processing starting from the box **1120** will be repeated until the checking of every download execution management table **870** is completed (**1230**).

With the processing above, download control metafile update is periodically checked with respect to the server at fixed time intervals, thereby making it possible to reflect a modified portion(s) upon the database of the downloader.

The part that checks the update of the download control metafile in this way (e.g., a part of the CPU which is executed by a program) will also be called the update check unit.

Lastly, the download execution order determination processing **1300** is executed, thereby determining again the download execution order (**1240**).

FIG. 7 shows a detailed example of the download execution order determination processing **1300** that is executed at **590** of FIG. 3. Firstly, certain ones of the download execution management table **870**, including one with the delivery time/date **873** having a futural value—i.e., the one that is not delivered yet and is set in the download-reserved state—and one with the download execution state **878** being set to “Downloaded,” are excluded from candidates for the execution order determination processing as not-to-be-executed objects (**1310**).

With respect to the remaining download execution management tables **870** to be executed, a download execution order is determined in accordance with a prespecified algorithm (**1320**); then, in accordance with this determined execution order, pointer values relative to the download execution management tables **870** are stored in the down-

load execution management table pointers **910** of the download execution sequence table **900** in the priority order (**1330**).

As for the “prespecified algorithm” of **1320**, its methodology to be implemented becomes different depending on the form of download services and/or the user’s desired performance and functionality. Examples of it are algorithms (a) to (f) which follow:

- (a) Contents are downloaded in the importing order of download control metafiles **120**; within the same download control metafile **120**, contents are downloaded in the description order of the download execution information **140**.
- (b) Higher priority is given to a one with the delivery content size **877** being smaller in value.
- (c) Those contents belonging to a download control metafile **120** with a shorter update cycle are prioritized.
- (d) In the case of an information processing apparatus capable of executing download of a plurality of contents in a parallel way, several sets of contents are downloaded simultaneously in a parallel manner.
- (e) In the case of several sets of contents of (d) being simultaneously downloaded in parallel, higher priority is given to the download of one which is put on the server of a respective separate domain.
- (f) The user expressly designates his or her preferred download execution order via the user interface of an information processing apparatus; then, download is performed in a way pursuant thereto.

FIG. 8 shows a processing example of downloader execution processing **1000** which performs the actual download processing in accordance with the download execution order table **900** that was set up by the download execution order determination processing **1300** of FIG. 7.

First of all, reference is made in the priority order to those records of the download execution management table **870** that is indicated by the download execution management table pointers **910** of the download execution sequence table **900** (**1010**).

If the download execution management table **870** is found (**1020**), the download of contents from the server gets started in accordance with the content of the download execution management table **870** (**1040**); then, the value of download execution state **878** is changed from the default value “Not Downloaded” to a value “Downloading” (**1040**).

After having completed the download of the contents, resulting in the contents being stored in HDD (**1050**), a related metafile needed for playback or execution of such contents is downloaded from the URL of the delivery content-use metafile location **876**, and is registered to the HDD together with the contents (**1055**); then, the value of the download execution state **878** is changed to “Downloaded” (**1060**); finally, a corresponding pointer field is deleted from the download execution sequence table **900**, followed by moving the remaining ones ahead (**1070**).

Next, reference is made to the download reservation management table **850** to which the download execution management table **870** of the download-completed contents belongs, thereby to check the download execution state **878** with respect to every download execution management table **870** belonging thereto (**1080**); if every download execution state **878** is set at “Downloaded” with the update check flag **854**=“One Shot” or with the check flag **854**=“Updated” and also the expire time/date **855** being past than a present time and date (**1080**), a decision is made to conclude that there is no need to further update the download control metafile, followed by deletion of its corresponding download reser-

11

vation management table **850** and the download execution management table **870** belonging thereto from the database of the downloader (**1100**).

Thereafter, based on a new database, the download execution order determination processing **1300** is executed again to thereby remake a download execution order table **900** (**1110**); then, the processing of from the block **1010** will be executed repeatedly.

In the block **1020**, if there is not any download execution management table **870** to be further executed, then wait until either the download reservation management table **850** or the download execution management table **870** is updated (**1120**). Upon occurrence of such updating, the processing is redone from the beginning thereof.

It is desirable that after having been started by system start-up processing, the above-stated downloader execution processing **1000** is rendered operative in at all times and repeatedly executed in background at low priority degree—in a way that it does not hinder or impede other processing—as far as the information processing apparatus is operating.

According to this embodiment, even in a case where there are a great number of same information processing apparatuses, the download update processing **1100** checks the update of download control metafiles at predetermined time intervals, while letting a per-equipment different time-and-date be as the start point thereof.

In addition, because of the execution of downloading based on the prespecified time cycle, it is possible to disperse the traffic with respect to the Web server **100** and file server **200**. This makes it possible to lower costs of such servers and communication lines for connection of such servers.

It is also possible to automatically delete monitoring-unnecessitated download control information from the database information of the downloader **550** to thereby ensure that unnecessary files are no longer stored in HDD **450** infinitely.

Although the invention has been described with reference to currently preferred embodiments thereof, this invention should not exclusively be limited thereto, and it will be apparent to those skilled in the art that various changes and modifications may be made therein without departing from the spirit and scope of the appended claims.

DESCRIPTION OF REFERENCE NUMERALS

120	Download Control Metafile	
134	Update Check Flag	50
135	Expire Time-and-Date	
210	Contents	
400	Information Processing Apparatus	
450	Hard Disk Drive	
460	Real Time Clock	55
500	Web Browser	
550	Downloader	
600	System Initial Setup Processor	
700	Timer Interrupt Processing	
800	Downloader Management Information	60
850	Download Reservation Management Table	
870	Download Execution Management Table	
900	Download Execution Order Table	
1000	Downloader Execution Processing	
1100	Downloader Update Processing	65
1300	Download Execution Order Determination Processing	

12

The invention claimed is:

1. A content download apparatus, comprising:
 - a network interface configured to communicate with a content server;
 - a storage configured to store a first content and download control meta information which includes at least update check information indicating whether or not an update to the download control meta information is checked, first address information by which the content server can address the first content, and first content size information indicating a data size of the first content; and
 a controller,
 - wherein the controller includes a processor and memory that stores instructions that when executed by the processor configures the controller to:
 - in a case where the update check information indicates to check for an update to the download control meta information, check whether the download control meta information has been updated;
 - when the download control meta information has been updated and when information of a second content has been added in the updated download control meta information, download the second content from the external server based on the updated download control meta information;
 - while downloading the second content, display a degree of progress of the downloading; and
 - store the downloaded second content into the storage.
2. The content download apparatus according to claim 1, wherein the first address information and the second address information are described in URL (Uniform Resource Locator) format.
3. The content download apparatus according to claim 1, wherein the controller is further configured to delete the first content and/or the download control meta information used for downloading the first content after downloading the second content.
4. The content download apparatus according to claim 1, wherein the download control meta information further includes expiration time information indicating a time of whether or not the update check information is checked.
5. The content download apparatus according to claim 1, wherein the controller is further configured to delete the download control meta information used for downloading the first content after downloading the first content, in a case where the expiration time information indicates that present time is past the time or the time is a specific value.
6. The content download apparatus according to claim 1, wherein the controller is further configured to reproduce the second content after downloading the second content from the content server.
7. The content download apparatus according to claim 1, wherein the download control meta information is described in RSS (RDF Site Summary) format.
8. The content download apparatus according to claim 1, wherein the controller is further configured to set up a time cycle for checking whether the download control meta information has been updated.
9. The content download apparatus according to claim 8, wherein the controller is further configured to add a random number to a start time, calculated by the time cycle, for checking.
10. The content download apparatus according to claim 1, wherein the controller includes a CPU.

13

11. The content download apparatus according to claim 1, wherein the controller is further configured to delete the first content and/or the first download execution information used for downloading of the first content after downloading the second content. 5
12. A content download apparatus, comprising:
 a network interface configured to communicate with a content server;
 a storage configured to store a first content, update check information and first download execution information, the first download execution information including at least
 first address information by which the content server can address the first content and
 first content size information indicating a data size of the first content; and
 a controller,
 wherein the controller includes a processor and memory that stores instructions that when executed by the processor configures the controller to:
 in a case where the update check information indicates to check for an update relating to a second content, check whether a second download execution information has been added or not;
 when the second execution information has been added, download the second content from the content server based on second address information and second content size information which are included in the second download execution information;
 while downloading the second content, display a degree of progress of the downloading; and
 store the downloaded second content into the storage.
13. The content download apparatus according to claim 12,
 wherein the first address information and the second address information are described in URL (Uniform Resource Locator) format.
14. The content download apparatus according to claim 12,
 wherein the first download execution information and the second download execution information further include delivery date information on which the first content or the second content is stored in the content server.
15. The content download apparatus according to claim 12,
 wherein the first download execution information further includes content title information of the first content, and the second download execution information further includes content title information of the second content.

14

16. The content download apparatus according to claim 12,
 wherein the controller is further configured to reproduce the second content after downloading the second content from the content server.
17. The content download apparatus according to claim 12,
 wherein the controller is further configured to set up a time cycle for checking whether the second download execution information has been added.
18. The content download apparatus according to claim 17,
 wherein the controller is further configured to add a random number to a start time, calculated by the time cycle, for checking.
19. The content download apparatus according to claim 12,
 wherein the controller includes a CPU.
20. A content download apparatus, comprising:
 a network interface configured to communicate with a content server;
 a storage configured to store a first content, update check information and first download execution information, the first download execution information including at least first address information by which the content server can address the first content and first content size information indicating a data size of the first content; and
 a controller,
 wherein the controller includes a processor and memory that stores instructions that when executed by the processor configures the controller to:
 in a case where the update check information indicates to check for an update relating to a second content, check whether a second download execution information has been added or not;
 when the second execution information has been added, download the second content from the content server based on second address information and second content size information which are included in the second download execution information;
 while downloading the second content, display a degree of progress of the downloading; and
 store the downloaded second content into the storage, and
 wherein the controller is further configured to delete the first content and/or the first download execution information used for downloading the first content after downloading the second content.

* * * * *