



US011976633B2

(12) **United States Patent**  
**Cai et al.**

(10) **Patent No.:** **US 11,976,633 B2**  
(45) **Date of Patent:** **May 7, 2024**

(54) **SYSTEMS AND METHODS FOR OPTIMAL SPEED PROTECTION FOR POWER TURBINE GOVERNING**

(71) Applicant: **RAYTHEON TECHNOLOGIES CORPORATION**, Farmington, CT (US)

(72) Inventors: **Chaohong Cai**, Weatogue, CT (US);  
**Timothy J Crowley**, Tolland, CT (US);  
**David Lei Ma**, Avon, CT (US);  
**Richard P Meisner**, Glastonbury, CT (US)

(73) Assignee: **RTX CORPORATION**, Farmington, CT (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 405 days.

(21) Appl. No.: **17/376,965**

(22) Filed: **Jul. 15, 2021**

(65) **Prior Publication Data**

US 2021/0340956 A1 Nov. 4, 2021

**Related U.S. Application Data**

(62) Division of application No. 15/971,300, filed on May 4, 2018, now Pat. No. 11,092,136.

(51) **Int. Cl.**  
**F03D 7/04** (2006.01)  
**F03D 7/02** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **F03D 7/043** (2013.01); **F03D 7/0224** (2013.01); **F03D 7/0272** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,807,129 A \* 2/1989 Perks ..... B64C 13/503  
701/3  
4,947,334 A \* 8/1990 Massey ..... G05D 1/0669  
701/4

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2018007011 1/2018

OTHER PUBLICATIONS

European Patent Office, European Search Report dated Sep. 25, 2019 in Application No. 19172293.3.


(Continued)

*Primary Examiner* — Jonathan M Dager  
(74) *Attorney, Agent, or Firm* — SNELL & WILMER L.L.P.

(57) **ABSTRACT**

A control system for limiting power turbine torque (QPT) of a gas turbine engine includes a controller including a processor and memory configured to control the gas turbine engine, the controller including an engine control module that provides an effector command signal to a gas generator of the gas turbine engine; a power turbine governor module that outputs a preliminary torque request (QPT\_req\_pre); and a power turbine torque (QPT) optimal limiter module that outputs a maximum torque topper (QPT\_max) to limit a power turbine speed overshoot of the gas turbine engine; wherein the controller outputs a minimum value between the preliminary torque request (QPT\_req\_pre) and the maximum torque topper (QPT\_max) to the engine control module.

**11 Claims, 4 Drawing Sheets**



(52) **U.S. Cl.**  
 CPC ..... *F03D 7/0276* (2013.01); *F05B 2270/327*  
 (2013.01); *F05D 2220/329* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,169,090 A \* 12/1992 Wright ..... G05D 1/0061  
 244/175  
 5,189,620 A \* 2/1993 Parsons ..... G05B 7/02  
 318/609  
 5,315,819 A \* 5/1994 Page ..... F02C 9/28  
 60/39.282  
 5,730,394 A \* 3/1998 Cotton ..... G05D 1/0858  
 701/8  
 5,971,325 A \* 10/1999 Gold ..... G05D 1/0858  
 244/17.23  
 6,059,225 A \* 5/2000 Vidal ..... B64C 13/503  
 701/4  
 6,259,975 B1 \* 7/2001 Rollet ..... G05D 1/0204  
 244/175  
 6,367,741 B2 \* 4/2002 Mezan ..... G05D 1/0858  
 244/230  
 6,422,023 B1 \* 7/2002 Dudd, Jr. .... F02C 9/28  
 60/773  
 6,648,269 B2 \* 11/2003 Gold ..... G05D 1/0858  
 701/3  
 6,735,500 B2 \* 5/2004 Nicholas ..... B64C 27/56  
 701/1  
 6,873,887 B2 \* 3/2005 Zagranski ..... G05B 5/01  
 701/4  
 6,882,889 B2 \* 4/2005 Fuller ..... G05B 13/042  
 702/185  
 6,986,641 B1 \* 1/2006 Desai ..... G05B 5/01  
 60/791  
 7,085,655 B2 \* 8/2006 Ferrer ..... G01H 1/006  
 702/56  
 7,756,612 B2 \* 7/2010 Salesse-Lavergne .....  
 G05D 1/0669  
 701/4  
 7,758,310 B2 \* 7/2010 Cotton ..... B64C 27/10  
 416/157 R  
 7,970,498 B2 \* 6/2011 Sahasrabudhe ..... G05D 1/0858  
 701/3  
 8,052,094 B2 \* 11/2011 Roesch ..... B64C 27/26  
 244/6  
 8,201,771 B2 \* 6/2012 Kessler ..... B64C 27/001  
 244/194  
 8,594,904 B2 \* 11/2013 Livshiz ..... F02D 41/0002  
 701/102  
 8,682,454 B2 \* 3/2014 Fuller ..... G05B 17/02  
 700/52  
 8,682,506 B2 \* 3/2014 Marton ..... B64C 19/00  
 703/2  
 8,862,361 B2 \* 10/2014 Mukavetz ..... F02C 9/28  
 701/14  
 8,989,921 B2 \* 3/2015 Nannoni ..... G05D 1/0858  
 701/16  
 9,304,516 B2 \* 4/2016 Christensen ..... G05D 1/0858  
 9,494,085 B2 11/2016 Cai

9,862,500 B2 \* 1/2018 Salesse-Lavergne .....  
 B64C 13/18  
 9,880,527 B2 \* 1/2018 Li ..... F02C 9/28  
 10,040,542 B1 \* 8/2018 Gillett ..... B64C 13/503  
 10,113,487 B2 \* 10/2018 Cai ..... F02C 9/54  
 10,316,760 B2 \* 6/2019 Meisner ..... F02C 9/00  
 10,344,695 B1 \* 7/2019 Bergstedt ..... F02D 41/30  
 10,584,646 B2 \* 3/2020 Meunier ..... F02C 9/263  
 11,047,253 B2 \* 6/2021 Liebschutz ..... F01D 17/00  
 11,079,733 B2 \* 8/2021 Meisner ..... G05B 5/01  
 2003/0066926 A1 \* 4/2003 Salesse-Lavergne .....  
 G05D 1/0055  
 244/17.13  
 2003/0066927 A1 \* 4/2003 Salesse-Lavergne .....  
 G05D 1/0858  
 244/17.13  
 2003/0135306 A1 \* 7/2003 Driscoll ..... G05B 5/01  
 701/4  
 2003/0191561 A1 \* 10/2003 Vos ..... G05B 11/32  
 701/3  
 2005/0217274 A1 \* 10/2005 Muramatsu ..... F02C 9/28  
 60/773  
 2006/0100751 A1 \* 5/2006 Saleese-Lavergne .....  
 G05D 1/102  
 701/11  
 2008/0249672 A1 \* 10/2008 Cherepinsky ..... G05D 1/0858  
 701/4  
 2009/0045294 A1 \* 2/2009 Richardson ..... B64C 27/26  
 244/7 A  
 2011/0208400 A1 \* 8/2011 Lickfold ..... F02C 9/44  
 701/100  
 2014/0229036 A1 \* 8/2014 Vallart ..... B64D 31/00  
 701/3  
 2015/0113996 A1 \* 4/2015 Cai ..... F02C 9/54  
 60/773  
 2015/0159625 A1 \* 6/2015 Hardwicke, Jr. .... F03D 80/70  
 290/44  
 2015/0377215 A1 \* 12/2015 Agarwal ..... F03D 7/0212  
 700/287  
 2016/0069277 A1 \* 3/2016 Meisner ..... F02C 9/28  
 60/773  
 2016/0208639 A1 \* 7/2016 Cai ..... G05B 13/048  
 2016/0208717 A1 \* 7/2016 Cai ..... F02C 3/10  
 2018/0030904 A1 \* 2/2018 Meunier ..... F02C 7/232  
 2018/0163638 A1 \* 6/2018 Gutz ..... F02C 9/28  
 2018/0306125 A1 \* 10/2018 Renold-Smith ..... F02C 9/46  
 2019/0309689 A1 \* 10/2019 Meisner ..... F02C 9/54  
 2021/0262400 A1 \* 8/2021 Cai ..... F02C 3/10

OTHER PUBLICATIONS

USPTO, Non-Final Rejection dated Dec. 15, 2020 in U.S. Appl. No. 15/971,300.  
 USPTO, Requirement for Restriction dated Sep. 3, 2020 in U.S. Appl. No. 15/971,300.  
 USPTO, Notice of Allowance dated Apr. 15, 2021 in U.S. Appl. No. 15/971,300.  
 European Patent Office, European Office Action dated Dec. 6, 2021 in Application No. 19172293.3.

\* cited by examiner




FIG.1




FIG.2




FIG.3




FIG.4

1

**SYSTEMS AND METHODS FOR OPTIMAL  
SPEED PROTECTION FOR POWER  
TURBINE GOVERNING**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application claims a divisional and claims priority to, and the benefit of U.S. Non-Provisional patent application Ser. No. 15/971,300, entitled “SYSTEMS AND METHODS FOR OPTIMAL SPEED PROTECTION FOR POWER TURBINE GOVERNING,” filed on May 4, 2018, which is hereby incorporated by reference in its entirety for all purposes.

FIELD

This disclosure relates to systems and methods for limiting rotor speeds of a gas turbine engine, such as configured for use in an aircraft, such as a helicopter.

BACKGROUND

Many helicopters use a type of gas turbine engine called a turboshaft engine. Turboshaft engines include a power turbine spool that communicates with a power turbine. Oftentimes, the power turbine is configured to drive an external load, such as the helicopter’s rotor(s). In such an application, it can be advantageous to prevent the rotor from over-shooting its target rotor speed as the load/power demand on the power turbine changes—such as when a desired helicopter maneuver requires a change in a collective pitch angle of the rotor.

SUMMARY

In various embodiments, a control system for limiting power turbine torque (QPT) of a gas turbine engine includes a controller including a processor and memory configured to control the gas turbine engine, the controller including an engine control module providing an effector command signal to a gas generator of the gas turbine engine; a power turbine governor module outputting a preliminary torque request (QPT\_req\_pre); and power turbine torque (QPT) optimal limiter module outputting a maximum torque toppler (QPT\_max) to limit a power turbine speed overshoot of the gas turbine engine; wherein the controller outputs a minimum value between the preliminary torque request (QPT\_req\_pre) and the maximum torque toppler (QPT\_max) to the engine control module.

In various embodiments: the minimum value limits a power turbine power or torque of the gas turbine engine; and/or the minimum value comprises a power turbine power or torque request that is provided to the electronic control module to limit the power turbine power or torque of the gas turbine engine; and/or the power turbine torque (QPT) optimal limiter module and the power turbine governor module receive a real-time output signal (NP\_sig) from a load system in communication with the gas turbine engine; and/or the real-time output signal (NP\_sig) is a power turbine speed signal; and/or the power turbine (QPT) torque optimal limiter module and the power turbine governor module receive a desired power turbine speed (NP\_ref) of the gas turbine engine; and/or the controller subtracts the real-time output signal (NP\_sig) from the desired power turbine speed (NP\_ref) to produce a signal difference (NP\_err); and/or the controller is compares the signal dif-

2

ference (NP\_err) against a baseline of zero to output a larger positive number between the signal difference (NP\_err) and zero; and/or the controller multiplies the larger positive number by twice the inertia of a power turbine and rotor load, an estimated power turbine torque rate limit (QRL), and a scaling factor to generate a multiplication product; and/or the controller calculates a square root of the multiplication product to calculate a relative torque limiter signal (dQLIM); and/or the control system further includes a rotor load function to generate an estimated torque signal of a load system (QPT\_load); and/or the controller adds the relative torque limiter signal (dQLIM) and the estimated power torque load signal of the load system to the calculate the maximum torque toppler (QPT\_max) that is output from the power turbine torque (QPT) optimal limiter module.

In various embodiments, a method of limiting power turbine torque of a gas turbine engine includes calculating, by a controller, a relative torque limiter signal (dQLIM); estimating, by the controller, a torque signal of a load system (QPT\_load); calculating a maximum torque toppler (QPT\_max) to limit a power turbine speed overshoot of the gas turbine engine using the relative torque limiter signal (dQLIM) and the torque signal of the load system (QPT\_load); and operating the gas turbine engine according to the maximum torque toppler (QPT\_max).

In various embodiments: calculating the relative torque limiter signal (dQLIM) includes subtracting, by the controller, a real-time output signal (NP\_sig) from a desired power turbine speed (NP\_ref) to produce a signal difference (NP\_err); and/or subtracting the real-time output signal (NP\_sig) from the desired power turbine speed (NP\_ref) to produce the signal difference (NP\_err) further includes comparing, by the controller, the signal difference (NP\_err) against a baseline of zero to output a larger positive number between the signal difference (NP\_err) and zero; and/or the method further includes multiplying, by the controller, the larger positive number by twice the inertia of the power turbine and rotor load, an estimated power turbine torque rate limit (QRL), and a scaling factor to generate a multiplication product; and/or the method further includes calculating, by the controller, a square root of the multiplication product to calculate the relative torque limiter signal (dQLIM); and adding, by the controller, the estimated torque signal of the load system (QPT\_load) and the relative torque limiter signal (dQLIM) to the calculate the maximum torque toppler (QPT\_max).

In various embodiments, a turboshaft engine for a helicopter includes a gas generator; a power turbine downstream from the gas generator; and a controller including a processor and memory configured to control the turboshaft engine, the controller including an engine control module providing an effector command signal to a gas generator of the gas turbine engine; a power turbine governor module outputting a preliminary torque request (QPT\_req\_pre); and a power turbine torque (QPT) optimal limiter module outputting a maximum torque toppler (QPT\_max) to limit a power turbine speed overshoot of the gas turbine engine; wherein the controller outputs a minimum value between the preliminary torque request (QPT\_req\_pre) and the maximum torque toppler (QPT\_max) to the engine control module.

In various embodiments: the minimum value limit is at least one of a power turbine power or torque of the turboshaft engine; and/or the minimum value comprises a power turbine power or torque request that is provided to the electronic control module to limit at least one of the power turbine power or torque of the turboshaft engine.

3

The forgoing features and elements may be combined in various combinations without exclusivity, unless expressly indicated herein otherwise. These features and elements, as well as the operation of the disclosed embodiments, will become more apparent in light of the following description and accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter of the present disclosure is particularly pointed out and distinctly claimed in the concluding portion of the specification. A more complete understanding of the present disclosure, however, may be obtained by referring to the detailed description and claims when considered in connection with the following illustrative figures.

FIG. 1 illustrates a representative gas turbine engine, in various embodiments;

FIG. 2 is a schematic representation of a power turbine control system for a gas turbine engine, in various embodiments;

FIG. 3 is a functional representation of a QPT optimal limiter, in various embodiments; and

FIG. 4 illustrates a method of protecting the speed of an engine, in various embodiments.

Elements and steps in the figures are illustrated for simplicity and clarity and have not necessarily been rendered according to any particular sequence. For example, steps that may be performed concurrently or in different order are illustrated in the figures to help improve understanding of various embodiments of the present disclosure.

#### DETAILED DESCRIPTION

This detailed description of exemplary embodiments makes reference to the accompanying drawings, which show exemplary embodiments by way of illustration. While these exemplary embodiments are described in sufficient detail to enable those skilled in the art to practice the disclosures, it should be understood that other embodiments may be realized and that logical changes and adaptations in design and construction may be made in accordance with this disclosure and the teachings herein. Thus, this detailed description is presented for purposes of illustration only and not of limitation.

The scope of the disclosure is defined by the appended claims and their legal equivalents rather than by merely the examples described. For example, the steps recited in any of the method or process descriptions may be executed in any order and are not necessarily limited to the order presented. Furthermore, any reference to singular includes plural embodiments, and any reference to more than one component or step may include a singular embodiment or step. Also, any reference to attached, connected, fixed, or the like may include full, partial, permanent, removable, temporary, and/or any other possible attachment option. Additionally, any reference to without contact (or similar phrases) may also include reduced contact or minimal contact.

Computer-based system program instructions and/or processor instructions may be loaded onto a tangible, non-transitory computer readable medium having instructions stored thereon that, in response to execution by a processor, cause the processor to perform various operations. The term “non-transitory” is to be understood to remove only propagating transitory signals per se from the claim scope and does not relinquish rights to all standard computer-readable media that are not only propagating transitory signals per se. Stated another way, the meaning of the term “non-transitory

4

computer-readable medium” and “non-transitory computer-readable storage medium” should be construed to exclude only those types of transitory computer-readable media that were found in *In re Nuijten* to fall outside the scope of patentable subject matter under 35 U.S.C. § 101.

Referring now to FIG. 1 and/or in various embodiments, an exemplary gas turbine engine 10 is shown. In various embodiments, the gas turbine engine 10 is a turboshaft engine, such as can be used in an aircraft application, such as a helicopter. In various embodiments, the gas turbine engine 10 comprises a gas generator 12 and/or a power turbine 14 arranged in a series flow with an upstream inlet proximate the gas generator 12 and a downstream exhaust proximate the power turbine 14.

In various embodiments, the gas generator 12 includes a compressor section 16 where air is compressed/pressurized, a combustor section 18 downstream of the compressor section 16 where the compressed air is mixed with fuel and ignited to generate hot combustion gases, and a turbine section 20 downstream of the combustor section 18 for extracting power from the hot combustion gases, such as by causing the blades of a turbine to rotate.

In various embodiments, the gas generator 12 further comprises a multi-spool coaxially nested configuration, including a low pressure spool 22 and a high pressure spool 24. In various embodiments, the low pressure spool 22 and the high pressure spool 24 operate in different directions, as well as at different pressures, speeds, and/or temperatures. In various embodiments, a low pressure turbine 26 is mounted to the low pressure spool 22 to drive a low pressure compressor 28, and a high pressure turbine 30 is mounted to the high pressure spool 24 to drive a high pressure compressor 32. As used herein, “low pressure” components generally experience lower pressures than corresponding “high pressure” components when the gas turbine engine 10 operates.

In various embodiments, the power turbine 14 comprises a turbine 34 mounted to a turbine spool 36. In operation, the gas generator 12 generates combustion gases that impart torque to the turbine spool 36 through the turbine 34. In various embodiments, the turbine spool 36 drives a load system 38, such as an electrical generator, power turbine, propeller, rotor, pump system, etc.

In various embodiments, the gas turbine engine 10 and the load system 38 are in communication with one another and with a controller 40 configured to control the gas turbine engine 10. In various embodiments, the controller 40 comprises a Full-Authority Digital Engine Control (FADEC) system for use with an aircraft gas turbine engine 10. In various embodiments, the controller 40 includes one or more processors 42 and one or more tangible, non-transitory memories 44 configured to implement digital or programmatic logic. In various embodiments, for example, the one or more processors 42 comprise one or more of an application specific integrated circuit (ASIC), digital signal processor (DSP), field programmable gate array (FPGA), general purpose processor, and/or other programmable logic device, discrete gate, transistor logic, or discrete hardware components, or any various combinations thereof and/or the like, and the one or more tangible, non-transitory memories 44 store instructions that are implemented by the one or more processors 42 for performing various functions, such as the systems and methods of the inventive arrangements described herein.

Referring now to FIG. 2 and/or in various embodiments, a power turbine control system 50 for the gas turbine engine 10 of FIG. 1 is shown, comprising the controller 40 of FIG.



## 5

1 and a plant **52** comprising the gas generator **12** and the load system **38** of FIG. **1**. In various embodiments, the power turbine control system **50** is configured to output one or more engine control commands to one or more components of the gas turbine engine **10**.

In various embodiments, the controller **40** comprises one or more processors that include an engine control module (ECM) **54**, an engine estimation module (EEM) **56**, a power turbine torque optimal limiter (QPT optimal limiter) module **58**, and/or a power turbine governor module (PTGM) **60**.

In various embodiments, the ECM **54** receives inputs such as the following: a maximum generator speed (NG\_max) signal **62**; a stability bleed (BLD) schedule **64**, such as relative positioning of bleed valves between the low pressure compressor **28** and the high pressure compressor **32** of FIG. **1**; an inlet guide vane (IGV) schedule **65**, such as relative positioning of stator vanes of the low pressure compressor **28** and stator vanes of the high pressure compressor **32** of FIG. **1**; engine limit (LIM) constraints **66**, such as acceleration, pressure, speed, stall, and temperature parameters for the gas turbine engine **10**; and state variable model estimates (SVM\_est) **68** of various engine state variables, such as pressure ( $P_e$ ), speed ( $N_e$ ), temperature ( $T_e$ ), and thrust ( $F_e$ ) from the EEM **56**. Referring generally, the BLD schedule **64** and IGV schedule **65** are adjusted or scheduled as a function of corrected compressor speed to manage compressor stability margin, in various embodiments.

In various embodiments, a power rating module **70** is configured to receive a power lever angle (PLA) signal **72**, which is used to generate the NG\_max signal **62** as input into the ECM **54**. In various embodiments, the speed of the gas generator **12** is a function of the PLA signal **72**. In various embodiments, the power rating module **70** is configured to, for example, utilize look-up tables in order to generate the NG\_max signal **62** based on the PLA signal **72**.

In various embodiments, the SVM\_est **68** input into the ECM **54** are output from the EEM **56**. In various embodiments, the EEM **56** receives an output signal **74** from the ECM **54** as an input into the EEM **56**. In various embodiments, the EEM **56** also receives real-time output measurement signals **76** from the gas generator **12** as inputs into the EEM **56**, such as pressure ( $P_m$ ), speed ( $N_m$ ), temperature ( $T_m$ ), and thrust ( $F_m$ ) signals.

In various embodiments, the gas generator **12** receives an effector command signal **78** from the ECM **54** as an input into the gas generator **12**, such as fuel flow (WF) requests, a BLD schedule **64**, and/or an IGV schedule **65**. In various embodiments, the gas generator **12** also receives an output signal **80** from the load system **38** as an input into the gas generator **12**, such as a power turbine speed (NP) of the turbine **34** of FIG. **1**.

In various embodiments, the load system **38** receives an output signal **82** from the gas generator **12** as an input into the load system **38**, such as a power turbine torque (QPT) of the turbine **34** of FIG. **1**.

In various embodiments, the PTGM **60** receives a real-time output signal **84** from the load system **38** as an input into the PTGM **60**, such as a power turbine speed signal (NP\_sig) of the turbine **34** of FIG. **1**. In various embodiments, the PTGM **60** also receives an input signal **86** as an input into the PTGM **60**, such as a desired power turbine speed (NP\_ref) of the turbine **34** of FIG. **1**. In various embodiments, the input signal **86** is received, for example, from an avionics or cockpit unit of an aircraft.

In various embodiments, the QPT optimal limiter module **58** also receives the real-time output signal **84** from the load

## 6

system **38** as an input into the QPT optimal limiter module **58**, as well as the input signal **86**. Additionally, the QPT optimal limiter module **58** also receives the LIM constraints **66** as an input into the QPT optimal limiter module **58** as well, in various embodiments.

In various embodiments, the QPT optimal limiter module **58** outputs a maximum torque topper (QPT\_max) signal **88** for protecting power turbine speed NP, which indicates a maxima torque rate for the power turbine control system **50**, as described further herein.

In various embodiments, the PTGM **60** outputs a preliminary torque request (QPT\_req\_pre) signal **90**.

In various embodiments, a minimum value between the QPT\_max signal **88** and the QPT\_req\_pre signal **90** is determined by a minimization (MIN) function **92** of the power turbine control system **50**. More specifically, the MIN function **92** receives the QPT\_max signal **88** and the QPT\_req\_pre signal **90** as inputs and outputs therefrom an output signal **94**, such as a power turbine power or turbine torque request (QPT\_req) that is provided as an input into the ECM **54**.

Referring now to FIG. **3** and/or in various embodiments, the functionality of the QPT optimal limiter module **58** of FIG. **2** will be described in additional detail. More specifically, the real-time output signal **84** and the input signal **86** are input into a subtraction node **100** within the QPT optimal limiter module **58** to produce a signal difference (NP\_err) **102** as a difference between the real-time output signal **84** subtracted from the input signal **86**. NP\_err **102** is then compared against a baseline of zero to determine if NP\_err **102** is a negative or positive number, with a larger positive number between NP\_err **102** and zero outputting from a maximizing (MAX) function **104**. Four numbers are then multiplied at a multiplier function (PROD) **106**, including the maximum number output by the MAX function **104**, twice the inertia of the power turbine and rotor load ( $2 \cdot I_{load}$ ), an estimated power turbine torque rate limit (QRL), and a scaling, or tuning, factor (K) as a function of QPT bandwidth. A square root function (SQRT) **108** then calculates the square root of the multiplication product to calculate a relative torque limiter signal (dQLIM) **110**.

Within the QPT optimal limiter module **58**, the real-time output signal **84**, real-time pilot input signals **112** (e.g., collective pitch angle of the rotor), and real-time flight conditions **114** (e.g., the real-time output measurement signals **76** from the gas generator **12** of FIG. **2**, such as pressure ( $P_m$ ), speed ( $N_m$ ), temperature ( $T_m$ ), and thrust ( $F_m$ ) signals) are input into a rotor load function **116** to generate an estimated torque signal (QPT\_load) **118** of the load system **38** of FIG. **1**. The dQLIM **110** and QPT\_load **118** are input into a summation node **120** within the QPT optimal limiter module **58** to produce an output signal **122** that is the addition of dQLIM **110** and QPT\_load **118**. Referring generally, the rotor load function **116** comprises a linear or non-linear (e.g., differential algebraic equations in numerical simulation form) physics and data-based model, in various embodiments.

In various embodiments, the output signal **122** is then compared against a power turbine torque validation signal (QPT\_valid) **124**, with a larger number between the output signal **122** and QPT\_valid **124** outputting from a maximizing (MAX) function **126** to generate the QPT\_max signal **88** for protecting power turbine speed.

In various embodiments, the QPT\_max signal **88** ensures minimal, near-zero, and/or zero power turbine overshoot. It

reflects a maximum torque limit for protecting power turbine speed and integrating with the power turbine control system **50** of FIG. **2**.

The QPT\_max signal **88** applies a boundary condition to constrain torque, protecting power turbine speed and minimizing speed excursion during aggressive and/or large power transients, such as when the gas turbine engine **10** of FIG. **1** is powered on, powered off, and/or transitioning between fly and idle modes. Without such power and/or torque protection, the power turbine governing can overrun to too high of a power level, forcing an inefficient recovery to a lower power level. In various embodiments, the QPT\_max signal **88** enables smaller rotor excursion during fast load changes, increases flight handling quality and performance at various power levels, and integrates with an airframe during load changes.

Referring now to FIG. **4**, a method **150** of protecting the speed of an engine begins at a step **152**, after which a relative torque limiter signal (dQLIM) is calculated at a step **154**. At a step **156**, a torque signal of a load system (QPT\_load) is estimated, after which a maximum torque topper (QPT\_max) is calculated using the dQLIM and QPT\_load at a step **158** to control a gas turbine engine, such as operating the gas turbine engine according to the maximum torque topper (QPT\_max) in step **160**. Thereafter, the method **150** ends at a step **162**. In accordance with the method **150**, a gas generator **12** of a gas turbine engine **10** controls a maximum torque output of a turbine **34** of a power turbine **14** of a gas turbine engine **10**, such as shown in FIG. **1** and/or in various embodiments.

In various embodiments, the present disclosure provides a power turbine control system **50** for a gas turbine engine **10**, such as a turboshaft engine used in an aircraft application, such as a helicopter. The disclosed systems and methods enable the gas turbine engine **10** to deliver a requested change in power demand during flight maneuvers, while, at the same time, minimizing power turbine speed excursion caused by overshooting rotor speeds at various power levels. In various embodiments, a technical effect of the power turbine control system **50** is to meet power demands under various engine operation limits. In operation, the disclosed systems and methods minimize overshooting rotor speed during changes in load and/or power demands, which can smooth transitions between rotor states and improve integration among different airframe states and operating conditions.

Benefits, other advantages, and solutions to problems have been described herein with regard to specific embodiments. Furthermore, the connecting lines shown in the various figures contained herein are intended to represent exemplary functional relationships and/or physical couplings between the various elements. It should be noted that many alternative or additional functional relationships or physical connections may be present in a practical system. However, the benefits, advantages, solutions to problems, and any elements that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as critical, required, or essential features or elements of the disclosures. The scope of the disclosures is accordingly to be limited by nothing other than the appended claims and their legal equivalents, in which reference to an element in the singular is not intended to mean "one and only one" unless explicitly so stated, but rather "one or more." Moreover, where a phrase similar to "at least one of A, B, or C" is used in the claims, it is intended that the phrase be interpreted to mean that A alone may be present in an embodiment, B alone may be present in an embodiment, C

alone may be present in an embodiment, or that any combination of the elements A, B and C may be present in a single embodiment; for example, A and B, A and C, B and C, or A and B and C.

Systems, methods, and apparatus are provided herein. In the detailed description herein, references to "various embodiments", "one embodiment," "an embodiment," "an example embodiment," etc., indicate that the embodiment described may include a particular characteristic, feature, or structure, but every embodiment may not necessarily include the particular characteristic, feature, or structure. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular character, feature, or structure is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to affect such character, feature, or structure in connection with other embodiments, whether or not explicitly described. After reading this detailed description, it will be apparent to one skilled in the relevant art(s) how to implement the disclosure in alternative embodiments.

Furthermore, no element, component, or method step in the present disclosure is intended to be dedicated to the public regardless of whether the element, component, or method step is explicitly recited in the claims. No claim element is intended to invoke 35 U.S.C. § 112(f) unless the element is expressly recited using the phrase "means for." As used herein, the terms "comprises," "comprising," and/or any other variations thereof are intended to cover non-exclusive inclusions, such that an apparatus, article, method, or process that comprises a list of elements does not include only those elements, but may include other elements not expressly listed or inherent to such apparatus, article, method, or process.

What is claimed is:

**1.** A method, comprising:

- commanding, via a processor, an effector command signal to a gas generator of a gas turbine engine;
- determining, via the processor, a preliminary torque request;
- determining, via the processor, a maximum torque topper to limit a power turbine speed overshoot of the gas turbine engine, wherein the determining the maximum torque topper includes:
  - calculating, by the processor, a relative torque limiter signal, wherein:
    - the calculating the relative torque limiter signal comprises subtracting, by the processor, a real-time output signal from a desired power turbine speed to produce a signal difference, and
    - the subtracting the real-time output signal from the desired power turbine speed to produce the signal difference further comprises comparing, by the processor, the signal difference against a baseline of zero to output a larger positive number between the signal difference and zero;
  - estimating, by the processor, a torque signal of a load system, and
  - calculating the maximum torque topper based on the relative torque limiter signal and the torque signal of the load system; and
- commanding, via the processor, operation of the gas turbine engine in accordance with the maximum torque topper.

**2.** The method of claim **1**, wherein the load system is in communication with the gas turbine engine.

9

3. A method of limiting power turbine torque of a gas turbine engine, comprising:

calculating, by a controller, a relative torque limiter signal, wherein:

the calculating the relative torque limiter signal comprises subtracting, by the controller, a real-time output signal from a desired power turbine speed to produce a signal difference, and

the subtracting the real-time output signal from the desired power turbine speed to produce the signal difference further comprises comparing, by the controller, the signal difference against a baseline of zero to output a larger positive number between the signal difference and zero;

estimating, by the controller, a torque signal of a load system;

calculating a maximum torque topper to limit a power turbine speed overshoot of the gas turbine engine using the relative torque limiter signal and the torque signal of the load system; and operating the gas turbine engine according to the maximum torque topper.

4. The method of limiting power turbine torque of claim 3, further comprising multiplying, by the controller, the larger positive number by twice an inertia of a power turbine and rotor load, an estimated power turbine torque rate limit (QRL), and a scaling factor to generate a multiplication product.

5. The method of limiting power turbine torque of claim 4, further comprising calculating, by the controller, a square root of the multiplication product to calculate the relative torque limiter signal.

6. The method of limiting power turbine torque of claim 5, further comprising adding, by the controller, the torque signal of the load system and the relative torque limiter signal to the calculate the maximum torque topper.

7. The method of limiting power turbine torque of claim 3, wherein the load system is in communication with the gas turbine engine.

10

8. An article of manufacture including a tangible, non-transitory computer-readable storage medium having instructions stored thereon that, in response to execution by a processor, cause the processor to perform operations comprising:

calculating, by the processor, a relative torque limiter signal, wherein:

the calculating the relative torque limiter signal comprises subtracting, by the processor, a real-time output signal from a desired power turbine speed to produce a signal difference, and

the subtracting the real-time output signal from the desired power turbine speed to produce the signal difference further comprises comparing, by the processor, the signal difference against a baseline of zero to output a larger positive number between the signal difference and zero;

estimating, by the processor, a torque signal of a load system;

calculating a maximum torque topper to limit a power turbine speed overshoot of a gas turbine engine using the relative torque limiter signal and the torque signal of the load system, wherein the gas turbine engine is operated in accordance with the maximum torque topper.

9. The article of claim 8, wherein the operations further comprise multiplying, by the processor, the larger positive number by twice an inertia of a power turbine and rotor load, an estimated power turbine torque rate limit, and a scaling factor to generate a multiplication product.

10. The article of claim 9, wherein the operations further comprise calculating, by the processor, a square root of the multiplication product to calculate the relative torque limiter signal.

11. The article of claim 10, wherein, the operations further comprise adding, by the processor, the torque signal of the load system and the relative torque limiter signal to the calculate the maximum torque topper.

\* \* \* \* \*