

US011994377B2

(12) **United States Patent**
Holz

(10) **Patent No.:** **US 11,994,377 B2**
(45) **Date of Patent:** ***May 28, 2024**

(54) **SYSTEMS AND METHODS OF LOCATING A CONTROL OBJECT APPENDAGE IN THREE DIMENSIONAL (3D) SPACE**

(58) **Field of Classification Search**
CPC G06F 3/017; G06F 3/011; G06F 3/0304; G06F 3/04883; G06F 3/041;
(Continued)

(71) Applicant: **Ultrahaptics IP Two Limited**, Bristol (GB)

(56) **References Cited**

(72) Inventor: **David S. Holz**, San Francisco, CA (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Ultrahaptics IP Two Limited**, Bristol (GB)

2,665,041 A 1/1954 Maffucci
4,175,862 A 11/1979 DiMatteo et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 330 days.

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

CN 1984236 A 6/2007
CN 201332447 Y 10/2009
(Continued)

(21) Appl. No.: **17/010,531**

OTHER PUBLICATIONS

(22) Filed: **Sep. 2, 2020**

Search Machine translation: Method For Measuring Roundness Of Round Wire of JP-2010523948-A to Studer, retrieved Sep. 10, 2022, 13 pages. (Year: 2022).*

(65) **Prior Publication Data**

US 2020/0400428 A1 Dec. 24, 2020

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 15/953,320, filed on Apr. 13, 2018, now Pat. No. 10,767,982, which is a
(Continued)

Primary Examiner — Matthew C Bella

Assistant Examiner — Dennis Rosario

(74) *Attorney, Agent, or Firm* — HAYNES BEFFEL & WOLFELD LLP; Andrew L. Dunlap; Paul A. Durdik


(51) **Int. Cl.**
G06V 40/20 (2022.01)
G01B 11/24 (2006.01)
(Continued)

(57) **ABSTRACT**

Methods and systems for capturing motion and/or determining the shapes and positions of one or more objects in 3D space utilize cross-sections thereof. In various embodiments, images of the cross-sections are captured using a camera based on reflections therefrom or shadows cast thereby.

(52) **U.S. Cl.**
CPC **G01B 11/2433** (2013.01); **G06T 7/292** (2017.01); **G06T 7/507** (2017.01);
(Continued)

19 Claims, 35 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/723,370, filed on May 27, 2015, now Pat. No. 9,945,660, which is a continuation of application No. 13/724,357, filed on Dec. 21, 2012, now Pat. No. 9,070,019, which is a continuation-in-part of application No. 13/414,485, filed on Mar. 7, 2012, now abandoned.

(60) Provisional application No. 61/724,091, filed on Nov. 8, 2012, provisional application No. 61/587,554, filed on Jan. 17, 2012.

(51) **Int. Cl.**

- G06F 3/01** (2006.01)
- G06T 7/292** (2017.01)
- G06T 7/507** (2017.01)
- G06T 7/586** (2017.01)
- G06T 7/593** (2017.01)
- G06T 17/00** (2006.01)
- G06V 10/145** (2022.01)
- G06V 20/40** (2022.01)
- G06V 20/64** (2022.01)
- G06V 40/10** (2022.01)
- G06T 17/10** (2006.01)

(52) **U.S. Cl.**

CPC **G06T 7/586** (2017.01); **G06T 7/593** (2017.01); **G06T 17/00** (2013.01); **G06V 10/145** (2022.01); **G06V 20/40** (2022.01); **G06V 20/64** (2022.01); **G06V 40/107** (2022.01); **G06V 40/28** (2022.01); **G06F 3/017** (2013.01); **G06T 17/10** (2013.01); **G06T 2207/10152** (2013.01); **G06T 2207/30196** (2013.01)

(58) **Field of Classification Search**

CPC . G06F 2203/04104; G06F 2203/04105; G06F 3/0488; G06F 3/04886; G06F 2203/04106; G06F 2203/04101; G06F 2203/04808; G06F 3/04186; G06F 2203/0339; G06F 2203/0331; G06F 2203/0338; G06V 40/28; G06V 40/107; G06V 20/64; G06V 10/25; G06V 40/11; G06V 40/117; G06V 40/113; G06V 40/20; G06V 40/25; G06V 40/23; G06T 2207/10016; G06T 7/70; G06T 2200/04; G06T 2207/10012; G06T 17/00; G06T 7/593; G06T 7/292; G06T 7/251; G06T 7/13; G06T 7/62; G06T 7/20; G06T 17/30; G06T 17/20; G06T 7/50; G06T 2207/10021; G06T 17/10; G06T 2207/30196; G06T 7/246; G06T 19/00; G06T 2200/08; G06T 7/60; G06T 7/10

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 4,876,455 A 10/1989 Sanderson et al.
- 4,879,659 A 11/1989 Bowlin et al.
- 4,893,223 A 1/1990 Arnold
- 5,038,258 A 8/1991 Koch et al.
- 5,134,661 A 7/1992 Reinsch
- 5,282,067 A 1/1994 Liu
- 5,434,617 A 7/1995 Bianchi
- 5,659,475 A 8/1997 Brown
- 5,691,737 A 11/1997 Ito et al.
- 5,742,263 A 4/1998 Wang et al.
- 5,940,538 A 8/1999 Spiegel et al.

- 6,031,161 A 2/2000 Baltenberger
- 6,031,661 A 2/2000 Tanaami
- 6,072,494 A 6/2000 Nguyen
- 6,075,895 A 6/2000 Qiao et al.
- 6,184,326 B1 2/2001 Razavi et al.
- 6,184,926 B1 2/2001 Khosravi et al.
- 6,256,400 B1 7/2001 Takata et al.
- 6,296,358 B1 10/2001 Cornsweet et al.
- 6,346,933 B1 2/2002 Lin
- 6,417,970 B1 7/2002 Travers et al.
- 6,463,402 B1 10/2002 Bennett et al.
- 6,492,986 B1 12/2002 Metaxas et al.
- 6,493,041 B1 12/2002 Hanko et al.
- 6,498,628 B2 12/2002 Iwamura
- 6,578,203 B1 6/2003 Anderson, Jr. et al.
- 6,597,801 B1 7/2003 Cham et al.
- 6,603,867 B1 8/2003 Sugino et al.
- 6,674,877 B1 1/2004 Jojic et al.
- 6,734,911 B1 5/2004 Lyons
- 6,738,424 B1 5/2004 Allmen et al.
- 6,771,294 B1 8/2004 Pulli et al.
- 6,804,654 B2 10/2004 Kobylevsky et al.
- 6,814,656 B2 11/2004 Rodriguez
- 6,901,170 B1 5/2005 Terada et al.
- 7,152,024 B2 12/2006 Marschner et al.
- 7,213,707 B2 5/2007 Hubbs et al.
- 7,257,237 B1 8/2007 Luck et al.
- 7,259,873 B2 8/2007 Sikora et al.
- 7,308,112 B2 12/2007 Fujimura et al.
- 7,333,648 B2 2/2008 Edic et al.
- 7,372,977 B2 5/2008 Fujimura et al.
- 7,472,047 B2 12/2008 Kramer et al.
- 7,483,049 B2 1/2009 Aman et al.
- 7,656,372 B2 2/2010 Sato et al.
- 7,769,994 B2 8/2010 Peles
- 7,948,493 B2 5/2011 Klefenz et al.
- 7,961,174 B1 6/2011 Markovic et al.
- 7,961,934 B2 6/2011 Thrun et al.
- 7,980,885 B2 7/2011 Gattwinkel et al.
- 8,005,263 B2 8/2011 Fujimura et al.
- 8,023,698 B2 9/2011 Niwa et al.
- 8,035,624 B2 10/2011 Bell et al.
- 8,045,825 B2 10/2011 Shimoyama et al.
- 8,064,704 B2 11/2011 Kim et al.
- 8,085,339 B2 12/2011 Marks
- 8,144,233 B2 3/2012 Fukuyama
- 8,213,707 B2 7/2012 Li et al.
- 8,218,858 B2 7/2012 Gu
- 8,229,134 B2 7/2012 Duraiswami et al.
- 8,235,529 B1 8/2012 Raffle et al.
- 8,249,345 B2 8/2012 Wu et al.
- 8,253,564 B2 8/2012 Lee et al.
- 8,270,669 B2 9/2012 Aichi et al.
- 8,289,162 B2 10/2012 Mooring et al.
- 8,304,727 B2 11/2012 Lee et al.
- 8,319,832 B2 11/2012 Nagata et al.
- 8,363,010 B2 1/2013 Nagata
- 8,395,600 B2 3/2013 Kawashima et al.
- 8,432,377 B2 4/2013 Newton
- 8,471,848 B2 6/2013 Tschesnok
- 8,553,037 B2 10/2013 Smith et al.
- 8,582,809 B2 11/2013 Halimeh et al.
- 8,593,417 B2 11/2013 Kawashima et al.
- 8,605,202 B2 12/2013 Muijs et al.
- 8,620,024 B2 12/2013 Huang et al.
- 8,631,355 B2 1/2014 Murillo et al.
- 8,638,989 B2 1/2014 Holz
- 8,659,658 B2 2/2014 Vassigh et al.
- 8,738,523 B1 5/2014 Sanchez et al.
- 8,744,122 B2 6/2014 Salgian et al.
- 8,768,022 B2 7/2014 Miga et al.
- 8,786,596 B2 7/2014 House
- 8,817,087 B2 8/2014 Weng et al.
- 8,842,084 B2 9/2014 Andersson et al.
- 8,843,857 B2 9/2014 Berkes et al.
- 8,872,914 B2 10/2014 Gobush
- 8,878,749 B1 11/2014 Wu et al.
- 8,891,868 B1 11/2014 Ivanchenko
- 8,902,224 B2 12/2014 Wyeld

(56)

References Cited

U.S. PATENT DOCUMENTS

8,907,982 B2	12/2014	Zontrop et al.	2010/0046842 A1	2/2010	Conwell
8,922,590 B1	12/2014	Luckett, Jr. et al.	2010/0053164 A1	3/2010	Imai et al.
8,929,609 B2	1/2015	Padovani et al.	2010/0053209 A1	3/2010	Rauch et al.
8,930,852 B2	1/2015	Chen et al.	2010/0053612 A1	3/2010	Ou-Yang et al.
8,942,881 B2	1/2015	Hobbs et al.	2010/0066737 A1	3/2010	Liu
8,954,340 B2	2/2015	Sanchez et al.	2010/0066975 A1	3/2010	Rehnstrom
8,957,857 B2	2/2015	Lee et al.	2010/0091110 A1	4/2010	Hildreth
9,014,414 B2	4/2015	Katano et al.	2010/0121189 A1	5/2010	Ma et al.
9,056,396 B1	6/2015	Linnell	2010/0127995 A1	5/2010	Rigazio et al.
9,070,019 B2	6/2015	Holz	2010/0141762 A1	6/2010	Siann et al.
9,119,670 B2	9/2015	Yang et al.	2010/0194863 A1	8/2010	Lopes et al.
9,122,354 B2	9/2015	Sharma	2010/0199230 A1	8/2010	Latta et al.
9,124,778 B1	9/2015	Crabtree	2010/0199232 A1	8/2010	Mistry et al.
9,135,503 B2	9/2015	Sundaresan et al.	2010/0201880 A1	8/2010	Iwamura
9,305,229 B2	4/2016	DeLean et al.	2010/0208942 A1	8/2010	Porter et al.
9,459,697 B2	10/2016	Bedikian et al.	2010/0222102 A1	9/2010	Rodriguez
9,721,383 B1	8/2017	Horowitz et al.	2010/0264833 A1	10/2010	Van Endert et al.
10,767,982 B2 *	9/2020	Holz G06T 7/507	2010/0302015 A1	12/2010	Kipman et al.
10,846,942 B1	11/2020	Horowitz et al.	2010/0303298 A1	12/2010	Marks et al.
11,461,966 B1	10/2022	Horowitz et al.	2010/0309097 A1	12/2010	Raviv et al.
2001/0044858 A1	11/2001	Rekimoto	2010/0329509 A1	12/2010	Fahn et al.
2001/0052985 A1	12/2001	Ono	2011/0007072 A1	1/2011	Khan et al.
2002/0008139 A1	1/2002	Albertelli	2011/0025818 A1	2/2011	Gallmeier et al.
2002/0041327 A1	4/2002	Hildreth et al.	2011/0043806 A1	2/2011	Guetta et al.
2002/0080094 A1	6/2002	Biocca et al.	2011/0057875 A1	3/2011	Shigeta et al.
2002/0105484 A1	8/2002	Navab et al.	2011/0066984 A1	3/2011	Li
2003/0081141 A1	5/2003	Mazzapica	2011/0080470 A1	4/2011	Kuno et al.
2004/0103111 A1	5/2004	Miller et al.	2011/0080490 A1	4/2011	Clarkson et al.
2004/0125984 A1	7/2004	Ito et al.	2011/0093820 A1	4/2011	Zhang et al.
2004/0155877 A1	8/2004	Hong et al.	2011/0116684 A1	5/2011	Coffman et al.
2004/0212725 A1	10/2004	Raskar	2011/0119640 A1	5/2011	Berkes et al.
2005/0007673 A1	1/2005	Chaoulov et al.	2011/0134112 A1	6/2011	Koh et al.
2005/0068518 A1	3/2005	Baney et al.	2011/0148875 A1	6/2011	Kim et al.
2005/0094019 A1	5/2005	Grosvenor et al.	2011/0176146 A1	7/2011	Alvarez Diez et al.
2005/0131607 A1	6/2005	Breed	2011/0193778 A1	8/2011	Lee et al.
2005/0156888 A1	7/2005	Xie et al.	2011/0213664 A1	9/2011	Osterhout et al.
2005/0168578 A1	8/2005	Gobush	2011/0243451 A1	10/2011	Oyaizu
2005/0238201 A1	10/2005	Shamaie	2011/0251896 A1	10/2011	Impollonia et al.
2005/0271279 A1	12/2005	Fujimura et al.	2011/0261178 A1	10/2011	Lo et al.
2006/0028656 A1	2/2006	Venkatesh et al.	2011/0279397 A1	11/2011	Rimon et al.
2006/0029296 A1	2/2006	King et al.	2011/0286676 A1	11/2011	El Dokor
2006/0034545 A1	2/2006	Mattes et al.	2011/0291988 A1	12/2011	Bamji et al.
2006/0050979 A1	3/2006	Kawahara	2011/0299737 A1	12/2011	Wang et al.
2006/0098899 A1	5/2006	King et al.	2011/0304600 A1	12/2011	Yoshida
2006/0111878 A1	5/2006	Pendyala et al.	2011/0310220 A1	12/2011	McEldowney
2006/0204040 A1	9/2006	Freeman et al.	2011/0314427 A1	12/2011	Sundararajan
2006/0262421 A1	11/2006	Matsumoto et al.	2012/0062736 A1	3/2012	Xiong
2007/0014466 A1	1/2007	Baldwin	2012/0065499 A1	3/2012	Chono
2007/0086621 A1	4/2007	Aggarwal et al.	2012/0068914 A1	3/2012	Jacobsen et al.
2007/0130547 A1	6/2007	Boillot	2012/0113316 A1	5/2012	Ueta et al.
2007/0230929 A1	10/2007	Niwa et al.	2012/0159380 A1	6/2012	Kocienda et al.
2008/0013826 A1	1/2008	Hillis et al.	2012/0163675 A1	6/2012	Joo et al.
2008/0019576 A1	1/2008	Senftner et al.	2012/0194517 A1	8/2012	Izadi et al.
2008/0030429 A1	2/2008	Hailpern et al.	2012/0204133 A1	8/2012	Guendelman et al.
2008/0031492 A1	2/2008	Lanz	2012/0223959 A1	9/2012	Lengeling
2008/0106637 A1	5/2008	Nakao et al.	2012/0236288 A1	9/2012	Stanley
2008/0110994 A1	5/2008	Knowles et al.	2012/0270654 A1	10/2012	Padovani et al.
2008/0118091 A1	5/2008	Serfaty et al.	2012/0274781 A1	11/2012	Shet et al.
2008/0126937 A1	5/2008	Pachet	2012/0281873 A1	11/2012	Brown et al.
2008/0187175 A1	8/2008	Kim et al.	2012/0293667 A1	11/2012	Baba et al.
2008/0244468 A1	10/2008	Nishihara et al.	2012/0314030 A1	12/2012	Datta et al.
2008/0246759 A1	10/2008	Summers	2012/0320080 A1	12/2012	Giese et al.
2008/0273764 A1	11/2008	Scholl	2013/0019204 A1	1/2013	Kotler et al.
2008/0278589 A1	11/2008	Thorn	2013/0038694 A1	2/2013	Nichani et al.
2008/0291160 A1	11/2008	Rabin	2013/0044951 A1	2/2013	Cherng et al.
2009/0002489 A1	1/2009	Yang et al.	2013/0050425 A1	2/2013	Im et al.
2009/0093307 A1	4/2009	Miyaki	2013/0086531 A1	4/2013	Sugita et al.
2009/0102840 A1	4/2009	Li	2013/0097566 A1	4/2013	Berglund
2009/0116742 A1	5/2009	Nishihara	2013/0120319 A1	5/2013	Givon
2009/0153655 A1	6/2009	Ike et al.	2013/0148852 A1	6/2013	Partis et al.
2009/0257623 A1	10/2009	Tang et al.	2013/0182079 A1	7/2013	Holz
2009/0309710 A1	12/2009	Kakinami	2013/0182897 A1	7/2013	Holz
2010/0013832 A1	1/2010	Xiao et al.	2013/0182902 A1	7/2013	Holz
2010/0020078 A1	1/2010	Shpunt	2013/0187952 A1	7/2013	Berkovich et al.
2010/0023015 A1	1/2010	Park	2013/0191911 A1	7/2013	Dellinger et al.
			2013/0208948 A1	8/2013	Berkovich et al.
			2013/0222640 A1	8/2013	Baek et al.
			2013/0239059 A1	9/2013	Chen et al.
			2013/0241832 A1	9/2013	Rimon et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0252691 A1 9/2013 Alexopoulos
 2013/0257736 A1 10/2013 Hou et al.
 2013/0258140 A1 10/2013 Lipson et al.
 2013/0271397 A1 10/2013 Macdougall et al.
 2013/0300831 A1 11/2013 Mavromatis et al.
 2013/0307935 A1 11/2013 Rappel et al.
 2013/0321265 A1 12/2013 Bychkov et al.
 2014/0002365 A1 1/2014 Ackley et al.
 2014/0010441 A1 1/2014 Shamaie
 2014/0064566 A1 3/2014 Shreve et al.
 2014/0081521 A1 3/2014 Frojdh et al.
 2014/0085203 A1 3/2014 Kobayashi
 2014/0125775 A1 5/2014 Holz
 2014/0125813 A1 5/2014 Holz
 2014/0132738 A1 5/2014 Ogura et al.
 2014/0134733 A1 5/2014 Wu et al.
 2014/0139425 A1 5/2014 Sakai
 2014/0139641 A1 5/2014 Holz
 2014/0157135 A1 6/2014 Lee et al.
 2014/0161311 A1 6/2014 Kim
 2014/0168062 A1 6/2014 Katz et al.
 2014/0176420 A1 6/2014 Zhou et al.
 2014/0189579 A1 7/2014 Rimon et al.
 2014/0192024 A1 7/2014 Holz
 2014/0201666 A1 7/2014 Bedikian et al.
 2014/0201689 A1 7/2014 Bedikian et al.
 2014/0222385 A1 8/2014 Muenster et al.
 2014/0223385 A1 8/2014 Ton et al.
 2014/0225826 A1 8/2014 Juni
 2014/0240215 A1 8/2014 Tremblay et al.
 2014/0240225 A1 8/2014 Eilat
 2014/0248950 A1 9/2014 Tosas Bautista
 2014/0253512 A1 9/2014 Narikawa et al.
 2014/0253785 A1 9/2014 Chan et al.
 2014/0267098 A1 9/2014 Na et al.
 2014/0282282 A1 9/2014 Holz
 2014/0307920 A1 10/2014 Holz
 2014/0344762 A1 11/2014 Grasset et al.
 2014/0364209 A1 12/2014 Perry
 2014/0364212 A1 12/2014 Osman et al.
 2014/0369558 A1 12/2014 Holz
 2014/0375547 A1 12/2014 Katz et al.
 2015/0003673 A1 1/2015 Fletcher
 2015/0009149 A1 1/2015 Gharib et al.
 2015/0016777 A1 1/2015 Abovitz et al.
 2015/0022447 A1 1/2015 Hare et al.
 2015/0029091 A1 1/2015 Nakashima et al.
 2015/0084864 A1 3/2015 Geiss et al.
 2015/0097772 A1 4/2015 Starner
 2015/0103004 A1 4/2015 Cohen et al.
 2015/0115802 A1 4/2015 Kuti et al.
 2015/0116214 A1 4/2015 Grunnet-Jepsen et al.
 2015/0131859 A1 5/2015 Kim et al.
 2015/0172539 A1 6/2015 Neglur
 2015/0193669 A1 7/2015 Gu et al.
 2015/0205358 A1 7/2015 Lyren
 2015/0205400 A1 7/2015 Hwang et al.
 2015/0206321 A1 7/2015 Scavezze et al.
 2015/0227795 A1 8/2015 Starner et al.
 2015/0234469 A1 8/2015 Akiyoshi
 2015/0234569 A1 8/2015 Hess
 2015/0253428 A1 9/2015 Holz
 2015/0258432 A1 9/2015 Stafford et al.
 2015/0261291 A1 9/2015 Mikhailov et al.
 2015/0304593 A1 10/2015 Sakai
 2015/0323785 A1 11/2015 Fukata et al.
 2016/0062573 A1 3/2016 Dascola et al.
 2016/0086046 A1 3/2016 Holz et al.
 2016/0093105 A1 3/2016 Rimon et al.

FOREIGN PATENT DOCUMENTS

CN 101729808 A 6/2010
 CN 101930610 A 12/2010
 CN 101951474 A 1/2011

CN 102053702 A 5/2011
 CN 201859393 U 6/2011
 CN 102201121 A 9/2011
 CN 102236412 A 11/2011
 DE 4201934 A1 7/1993
 DE 10326035 A1 1/2005
 DE 102007015495 A1 10/2007
 DE 102007015497 B4 1/2014
 EP 1477924 A2 11/2004
 EP 2369443 A2 9/2011
 GB 2419433 A 4/2006
 GB 2480140 A 11/2011
 GB 2519418 A 4/2015
 JP H02236407 A 9/1990
 JP H08261721 A 10/1996
 JP H09259278 A 10/1997
 JP 2000023038 A 1/2000
 JP 2002133400 A 5/2002
 JP 2003256814 A 9/2003
 JP 2004246252 A 9/2004
 JP 2006019526 A 1/2006
 JP 2006259829 A 9/2006
 JP 2007272596 A 10/2007
 JP 2008227569 A 9/2008
 JP 2009031939 A 2/2009
 JP 2009037594 A 2/2009
 JP 2010060548 A 3/2010
 JP 2010523948 A * 7/2010
 JP 2011010258 A 1/2011
 JP 2011501316 A 1/2011
 JP 2011065652 A 3/2011
 JP 2011107681 A 6/2011
 JP 4906960 B2 3/2012
 JP 2012527145 A 11/2012
 KR 101092909 B1 6/2011
 RU 2422878 C1 6/2011
 TW 200844871 A 11/2008
 WO 9426057 A1 11/1994
 WO 2010007662 A1 1/2010
 WO 2010088035 A2 8/2010
 WO 2010138741 A1 12/2010
 WO 2011024193 A2 3/2011
 WO 2011044680 A1 4/2011
 WO 2013109608 A2 7/2013
 WO 2013109609 A2 7/2013
 WO 2014200589 A2 12/2014
 WO 2014208087 A1 12/2014
 WO 2015026707 A1 2/2015

OTHER PUBLICATIONS

Syeda-Mahmood et al., Recognizing action events from multiple viewpoints, Jul. 8-8, 2001 [retrieved Sep. 10, 2022], Proceedings IEEE Workshop on Detection and Recognition of Events in Video, pp. 64-72. Retrieved: <https://ieeexplore.ieee.org/abstract/document/938868> (Year: 2001).*

Mateos, A Camera Calibration Technique Using Targets of Circular Features, Jan. 2000, uploaded Dec. 12, 2013, [retrieved Sep. 10, 2022], 13 pages. (Year: 2000) Retrieved: https://www.researchgate.net/publication/250669007_A_CAMERA_CALIBRATION_TECHNIQUE_USING_TARGETS_OF_CIRCULAR_FEATURES (Year: 2000).*

Ju et al., Analysis of gesture and action in technical talks for video indexing, Jun. 17-19, 1997 [retrieved Feb. 9, 2023], Proceedings of IEEE Computer Society Conference on Computer Vision and Pattern Recognition, pp. 595-601. Retrieved: <https://ieeexplore.ieee.org/abstract/document/609386> (Year: 1997).*

Lee et al., Robust fingertip extraction with improved skin color segmentation for finger gesture recognition in Human-robot interaction, Jun. 10-15, 2012 [retrieved Jul. 28, 2023], 2012 IEEE Congress on Evolutionary Computation, 7 pages. Retrieved: <https://ieeexplore.ieee.org/abstract/document/6256140> (Year: 2012).*

Olsson, K., et al., "Shape from Silhouette Scanner—Creating a Digital 3D Model of a Real Object by Analyzing Photos From Multiple Views," University of Linköping, Sweden, Copyright

(56)

References Cited

OTHER PUBLICATIONS

- VCG 2001, Retrieved from the Internet: <<http://liu.diva-portal.org/smash/get/diva2:18671/FULLTEXT01>> on Jun. 17, 2013, 52 pages.
- Forbes, K., et al., "Using Silhouette Consistency Constraints to Build 3D Models," University of Cape Town, Copyright De Beers 2003, Retrieved from the internet: <<http://www.dip.ee.uct.ac.za/~kforbes/Publications/Forbes2003Prasa.pdf>> on Jun. 17, 2013, 6 pages.
- May, S., et al., "Robust 3D-Mapping with Time-of-Flight Cameras," 2009 IEEE/RSJ International Conference on Intelligent Robots and Systems, Piscataway, NJ, USA, Oct. 10, 2009, pp. 1673-1678.
- Kanhangad, V., et al., "A Unified Framework for Contactless Hand Verification," IEEE Transactions on Information Forensics and Security, IEEE, Piscataway, NJ, US., vol. 6, No. 3, Sep. 1, 2011, pp. 1014-1027.
- Di Zenzo, S., et al., "Advances in Image Segmentation," Image and Vision Computing, Elsevier, Guildford, GBN, vol. 1, No. 1, Copyright Butterworth & Co Ltd., Nov. 1, 1983, pp. 196-210.
- Davis et al., "Toward 3-D Gesture Recognition", International Journal of Pattern Recognition and Artificial Intelligence, vol. 13, No. 03, 1999, pp. 381-393.
- Butail, S., et al., "Three-Dimensional Reconstruction of the Fast-Start Swimming Kinematics of Densely Schooling Fish," Journal of the Royal Society Interface, Jun. 3, 2011, retrieved from the Internet <<http://www.ncbi.nlm.nih.gov/pubmed/21642367>>, pp. 0, 1-12.
- Kim, et al., "Development of an Orthogonal Double-Image Processing Algorithm to Measure Bubble," Department of Nuclear Engineering and Technology, Seoul National University Korea, vol. 39 No. 4, Published Jul. 6, 2007, pp. 313-326.
- Barat et al., "Feature Correspondences From Multiple Views of Coplanar Ellipses", 2nd International Symposium on Visual Computing, Author Manuscript, 2006, 10 pages.
- Cheikh et al., "Multipeople Tracking Across Multiple Cameras", International Journal on New Computer Architectures and Their Applications (IJNCAA), vol. 2, No. 1, 2012, pp. 23-33.
- Kulesza, et al., "Arrangement of a Multi Stereo Visual Sensor System for a Human Activities Space," Source: Stereo Vision, Book edited by: Dr. Asim Bhatti, ISBN 978-953-7619-22-0, Copyright Nov. 2008, I-Tech, Vienna, Austria, www.intechopen.com, pp. 153-173.
- Heikkila, J., "Accurate Camera Calibration and Feature Based 3-D Reconstruction from Monocular Image Sequences", Infotech Oulu and Department of Electrical Engineering, University of Oulu, 1997, 126 pages.
- Arthington, et al., "Cross-section Reconstruction During Uniaxial Loading," Measurement Science and Technology, vol. 20, No. 7, Jun. 10, 2009, Retrieved from the Internet: <http://iopscience.iop.org/0957-0233/20/7/075701>, pp. 1-9.
- Pedersini, et al., Accurate Surface Reconstruction from Apparent Contours, Sep. 5-8, 2000 European Signal Processing Conference EUSIPCO 2000, vol. 4, Retrieved from the Internet: http://home.deib.polimi.it/sarti/CV_and_publications.html, pp. 1-4.
- Chung, et al., "International Journal of Computer Vision: Recovering LSHGCs and SHGCs from Stereo" [on-line], Oct. 1996 [retrieved on Apr. 10, 2014], Kluwer Academic Publishers, vol. 20, issue 1-2, Retrieved from the Internet: <http://link.springer.com/article/10.1007/BF00144116#>, pp. 43-58.
- Bardinet, et al., "Fitting of iso-Surfaces Using Superquadrics and Free-Form Deformations" [on-line], Jun. 24-25, 1994 [retrieved Jan. 9, 2014], 1994 Proceedings of IEEE Workshop on Biomedical Image Analysis, Retrieved from the Internet: http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=315882&tag=1, pp. 184-193.
- Dombeck, D., et al., "Optical Recording of Action Potentials with Second-Harmonic Generation Microscopy," The Journal of Neuroscience, Jan. 28, 2004, vol. 24(4): pp. 999-1003.
- U.S. Appl. No. 13/742,953—Office Action dated Jun. 14, 2013, 13 pages.
- U.S. Appl. No. 13/742,953—Notice of Allowance dated Nov. 4, 2013, 14 pages.
- PCT/US2013/021709—International Preliminary Report on Patent-ability dated Jul. 22, 2014, 22 pages (WO 2013/109608).
- U.S. Appl. No. 13/414,485—Office Action dated May 19, 2014, 16 pages.
- U.S. Appl. No. 13/414,485—Final Office Action dated Feb. 12, 2015, 30 pages.
- PCT/US2013/021709—International Search Report and Written Opinion dated Sep. 12, 2013, 22 pages.
- U.S. Appl. No. 13/414,485—Office Action dated Apr. 21, 2016, 24 pages.
- U.S. Appl. No. 15/953,320—Notice of Allowance, dated May 7, 2020, 35 pages.
- U.S. Appl. No. 13/414,485—Office Action dated Nov. 4, 2016, 29 pages.
- U.S. Appl. No. 14/723,370—Office Action dated Jan. 13, 2017, 33 pages.
- U.S. Appl. No. 15/953,320—Office Action dated Dec. 26, 2019, 68 pages.
- Veldhuis, Henri, et. al., "The 3D Reconstruction of Straight and Curved Pipes using Digital Line Photogrammetry", Mar. 20, 1997, 11 pages.
- Sundaresan, Aravind, et al., "Markerless Motion Capture using Multiple Cameras," 2005, 12 pages.
- Cumani, A., et al., "Recovering the 3D Structure of Tubular Objects from Stereo Silhouettes," Pattern Recognition, Elsevier, GB, vol. 30, No. 7, Jul. 1, 1997, 9 pages.
- Villa-Uriol et al., Automatic Creation of Three-Dimensional Avatars, Jan. 2003 [retrieved Jan. 6, 2017], Proceedings of SPIE—IS&T Electronic Imaging, vol. 5013, pp. 14-25. Retrieved from the Internet: <http://proceedings.spiedigitallibrary.org/proceeding.aspx?articleid=756080>.
- U.S. Appl. No. 14/723,370—Notice of Allowance dated Dec. 14, 2017, 11 pages.
- U.S. Appl. No. 14/723,370—Response to Office Action dated Jan. 13, 2017, filed Apr. 5, 2017, 4 pages.
- Wijewickrema et al., Reconstruction of Spheres using Occluding Contours from Stereo Images, Aug. 20-24, 2006 [retrieved Jul. 10, 2017], 18th International Conference on Pattern Recognition 2006, pp. 1-4. Retrieved from the Internet: [<http://ieeexplore.ieee.org/abstract/document/1698855/>].
- U.S. Appl. No. 14/723,370—Ex-Parte Quayle Action dated Jul. 18, 2017, 7 pages.
- Rasmussen, Mathew K., "An Analytical Framework for the Preparation and Animation of a Virtual Mannequin for the Purpose of Mannequin—Clothing Interaction Modeling", A Thesis Submitted in Partial Fulfillment of the Requirements for the Master of Science Degree in Civil and Environmental Engineering in the Graduate College of the University of Iowa, Dec. 2008, 98 pages.
- U.S. Appl. No. 13/414,485—Office Action dated Jul. 30, 2015, 22 pages.
- U.S. Appl. No. 13/414,485—Final Office Action dated May 11, 2017, 22 pages.
- PCT/US2013/069231—International Search Report and Written Opinion dated Mar. 13, 2014, 7 pages.
- Texas Instruments, "QVGA 3D Time-of-Flight Sensor," Product Overview: OPT 8140, Dec. 2013, Texas Instruments Incorporated, 10 pages.
- Texas Instruments, "4-Channel, 12-Bit, 80-MSPS ADC," VSP5324, Revised Nov. 2012, Texas Instruments Incorporated, 55 pages.
- Texas Instruments, "Time-of-Flight Controller (TFC)," Product Overview; OPT9220, Jan. 2014, Texas Instruments Incorporated, 43 pages.
- PCT/US2013/069231—International Preliminary Report with Written Opinion dated May 12, 2015, 8 pages.
- CN 2013800122765—Office Action dated Nov. 2, 2015, 17 pages.
- Matsuyama et al. "Real-Time Dynamic 3-D Object Shape Reconstruction and High-Fidelity Texture Mapping for 3-D Video," IEEE Transactions on Circuits and Systems for Video Technology, vol. 14, No. 3, Mar. 2004, pp. 357-369.
- Fukui et al. "Multiple Object Tracking System with Three Level Continuous Processes" IEEE, 1992, pp. 19-27.

(56)

References Cited

OTHER PUBLICATIONS

- Mendez, et al., "Importance Masks for Revealing Occluded Objects in Augmented Reality," Proceedings of the 16th ACM Symposium on Virtual Reality Software and Technology, 2 pages, ACM, 2009. JP 2014-552391—First Office Action dated Dec. 9, 2014, 6 pages. DE 11 2013 000 590.5—First Office Action dated Nov. 5, 2014, 7 pages. DE 11 2013 000 590.5—Response to First Office Action dated Nov. 5, 2014 filed Apr. 24, 2015, 1 page. DE 11 2013 000 590.5—Second Office Action dated Apr. 29, 2015, 7 pages. DE 11 2013 000 590.5—Response to Second Office Action dated Apr. 29, 2015 filed Sep. 16, 2015, 11 pages. DE 11 2013 000 590.5—Third Office Action dated Sep. 28, 2015, 4 pages. DE 11 2013 000 590.5—Response to Third Office Action dated Sep. 28, 2015 filed Dec. 14, 2015, 64 pages. DE 11 2013 000 590.5—Notice of Allowance dated Jan. 18, 2016, 8 pages. CN 2013800122765—Response to First Office Action dated Nov. 2, 2015 filed May 14, 2016, 14 pages. JP 2014-552391—Response to First Office Action dated Dec. 9, 2014 filed Jun. 8, 2016, 9 pages. JP 2014-552391—Second Office Action dated Jul. 7, 2015, 7 pages. JP 2014-552391—Response to Second Office Action dated Jul. 7, 2015 filed Dec. 25, 2015, 4 pages. JP 2014-552391—Third Office Action dated Jan. 26, 2016, 5 pages. CN 2013800122765—Second Office Action dated Jul. 27, 2016, 6 pages. CN 2013800122765—Response to Second Office Action dated Jul. 27, 2016 filed Oct. 11, 2016, 3 pages. Chung, et al., "Recovering LSHGCs and SHGCs from Stereo," International Journal of Computer Vision, vol. 20, No. 1/2, 1996, pp. 43-58. PCT/US2014/028265, Application (Determining Positional Information for an Object in Space), May 9, 2014, 117 pages. VCNL4020 Vishay Semiconductors. Datasheet [online]. Vishay Intertechnology, Inc, Doc No. 83476, Rev. 1.3, Oct. 29, 2013 [retrieved Mar. 4, 2014]. Retrieved from the Internet: <www.vishay.com>. 16 pages. VCNL4020 Vishay Semiconductors. Application Note [online]. Designing VCNL4020 into an Application. Vishay Intertechnology, Inc, Revised May 22, 2012 [retrieved Mar. 4, 2014]. Retrieved from the Internet: <www.vishay.com>. 21 pages. Schaar, R., VCNL4020 Vishay Semiconductors. Application Note [online]. Extended Detection Range with VCNL Family of Proximity Sensor Vishay Intertechnology, Inc, Revised Oct. 25, 2013 [retrieved Mar. 4, 2014]. Retrieved from the Internet: <www.vishay.com>. 4 pages. PCT/US2014/028265, International Search Report and Written Opinion, dated Jan. 7, 2015, 15 pages. Ballan et al., "Lecture Notes Computer Science: 12th European Conference on Computer Vision: Motion Capture of Hands in Action Using Discriminative Salient Points", Oct. 7-13, 2012 [retrieved Jul. 14, 2016], Springer Berlin Heidelberg, vol. 7577, pp. 640-653. Retrieved from the Internet: <http://link.springer.com/chapter/10.1007/978-3-642-33783-3_46>. Cui et al., "Applications of Evolutionary Computing: Vision-Based Hand Motion Capture Using Genetic Algorithm", 2004 [retrieved Jul. 15, 2016], Springer Berlin Heidelberg, vol. 3005 of LNCS, pp. 289-300. Retrieved from the Internet: <http://link.springer.com/chapter/10.1007/978-3-540-24653-4_30>. Delamarre et al., "Finding Pose of Hand in Video Images: A Stereo-based Approach", Apr. 14-16, 1998 [retrieved Jul. 15, 2016], Third IEEE Intern Conf on Auto Face and Gesture Recog, pp. 585-590. Retrieved from the Internet: <http://ieeexplore.ieee.org/xpl/login.jsp?tp=&arnumber=671011&url=http%3A%2F%2Fieeexplore.ieee.org%2Fxppls%2Fabs_all.jsp%3Farnumber%3D671011>. De La Gorce et al., "Model-Based 3D Hand Pose Estimation from Monocular Video", Feb. 24, 2011 [retrieved Jul. 15, 2016], IEEE Transac Pattern Analysis and Machine Intell, vol. 33, Issue: 9, pp. 1793-1805, Retri Internet: <http://ieeexplore.ieee.org/xpl/login.jsp?tp=&arnumber=5719617&url=http%3A%2F%2Fieeexplore.ieee.org%2Fxppls%2Fabs_all.jsp%3Farnumber%3D5719617>. Guo et al., Featured Wand for 3D Interaction, Jul. 2-5, 2007 [retrieved Jul. 15, 2016], 2007 IEEE International Conference on Multimedia and Expo, pp. 2230-2233. Retrieved from the Internet: <http://ieeexplore.ieee.org/xpl/login.jsp?tp=&arnumber=4285129&tag=1&url=http%3A%2F%2Fieeexplore.ieee.org%2Fxppls%2Fabs_all.jsp%3Farnumber%3D4285129%26tag%3D1>. Melax et al., "Dynamics Based 3D Skeletal Hand Tracking", May 29, 2013 [retrieved Jul. 14, 2016], Proceedings of Graphics Interface, 2013, pp. 63-70. Retriev from the Internet: <http://dl.acm.org/citation.cfm?id=2532141>. Oka et al., "Real-Time Fingertip Tracking and Gesture Recognition", Nov./Dec. 2002 [retrieved Jul. 15, 2016], IEEE Computer Graphics and Applications, vol. 22, Issue: 6, pp. 64-71. Retrieved from the Internet: <http://ieeexplore.ieee.org/xpl/login.jsp?tp=&arnumber=1046630&url=http%3A%2F%2Fieeexplore.ieee.org%2Fxppls%2Fabs_all.jsp%3Farnumber%3D1046630>. Schlattmann et al., "Markerless 4 gestures 6 DOF real-time visual tracking of the human hand with automatic Initialization", 2007 [retrieved Jul. 15, 2016], Eurographics 2007, vol. 26, No. 3, 10 pages, Retrieved from the Internet: <http://cg.cs.uni-bonn.de/aigaion2root/attachments/schlattmann-2007-markerless.pdf>. Wang et al., "Tracking of Deformable Hand in Real Time as Continuous Input for Gesture-based Interaction", Jan. 28, 2007 [retrieved Jul. 15, 2016], Proceedings of the 12th International Conference on Intelligent User Interfaces, pp. 235-242. Retrieved from the Internet: <http://dl.acm.org/citation.cfm?id=1216338>. Zhao et al., "Combining Marker-Based Mocap and RGB-D Camera for Acquiring High-Fidelity Hand Motion Data", Jul. 29, 2012 [retrieved Jul. 15, 2016], Proceedings of the ACM SIGGRAPH/Eurographics Symposium on Computer Animation, pp. 33-42, Retrieved from the Internet: <http://dl.acm.org/citation.cfm?id=2422363>. PCT/US2014/013012—International Search Report and Written Opinion dated May 14, 2014, published as WO 2014116991, 12 pages. Stenger, et al., "Model-Based 3D Tracking of an Articulated Hand", Computer Vision and Pattern Recognition, 2001. CVPR 2001 Proceedings of the 2001 IEEE Computer Society Conference on. vol. 2. IEEE, 2001, pp. 1-6. Yamamoto et al., "A Study for Vision Based Data Glove Considering Hidden Fingertip with Self-Occlusion", Aug. 8-10, 2012 [retrieved Mar. 16, 2018], 2012 13th ACIS Int. Conf on Soft Eng, AI, Network and Parallel & Dist Computing, pp. 315-320. Retrieved from the Internet: <<http://ieeexplore.ieee.org/abstract/document/6299298/>>. Hong et al., "Variable structure multiple model for articulated human motion tracking from monocular video sequences", May 2012 [retrieved Mar. 3, 2018], Science China Information Science, vol. 55, Issue 5, pp. 1138-1150. Retrieved from the Internet: <https://link.springer.com/article/10.1007/s11432-011-4529-8>. Calinon et al., A probabilistic approach based on dynamical systems to learn and reproduce gestures by imitation, Dec. 19, 2011 [retrieved Mar. 16, 2018], pp. 1-12. Retrieved from the Internet: <https://web.archive.org/web/20111219151051/http://infoscience.epfl.ch/record/147286/files/CalinonEtAIRAM2010.pdf?version=6>. Hamer et al., "Data-Driven Animation of Hand-Object Interactions", Mar. 21-25, 2011, Face and Gesture 2011, pp. 360-367. [retrieved on Jun. 19, 2019], Retrieved from the internet <https://ieeexplore.ieee.org/abstract/document/5771426>. Shimada et al., "Hand Gesture Estimation and Model Refinement using Monocular Camera-Ambiguity Limitation by Inequality v Constraints", Apr. 14-16, 1998, Proceedings 3rd IEEE Inter Confer Auto Face and Gesture Recog, pp. 1-6. [retrieved on Jun. 19, 2019], Retrieved from the internet <https://ieeexplore.ieee.org/abstract/document/670960>. PCT/US2013/021709, International Preliminary Report on Patentability and Written Opinion, dated Jul. 22, 2014, 22 pages.

(56)

References Cited

OTHER PUBLICATIONS

Delamarre et al., 3D Articulated Models and Multiview Tracking with Physical Forces, Mar. 2001 [retrieved Jun. 12, 2022], *Computer Vision and Image Understanding*, vol. 81, Issue 3, pp. 328-357. Retrieved: <https://www.sciencedirect.com/science/article/pii/S1077314200908920> (Year: 2001).

Kim et al., RetroDepth: 3D Silhouette Sensing for High-Precision Input On and Above Physical Surfaces, Apr. 26, 2014 [retrieved Jun. 12, 2022], CHI '14: Proceedings of the SIGCHI Conference on Human Factors in Computing Systems, pp. 1377-1386. Retrieved: (Year: 2014) <https://dl.acm.org/doi/abs/10.1145/2556288.2557336> (Year: 2014).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7

$$C_1x^2 + C_2xy + C_3y^2 - (2C_1x_c + C_2y_c)x - (2C_3y_c + C_2x_c)y + (C_1x_c^2 + C_2x_cy_c + C_3y_c^2 - 1) = 0$$

$$C_1 = \frac{\cos^2 \theta}{a^2} + \frac{\sin^2 \theta}{b^2}$$

$$C_2 = -2\cos\theta\sin\theta \left(\frac{1}{a^2} - \frac{1}{b^2} \right)$$

$$C_3 = \frac{\sin^2 \theta}{a^2} + \frac{\cos^2 \theta}{b^2}$$

FIG. 8




FIG. 9

$$\begin{aligned}
 A_1x + B_1y + D_1 &= 0 \\
 A_2x + B_2y + D_2 &= 0 \\
 A_3x + B_3y + D_3 &= 0 \\
 A_4x + B_4y + D_4 &= 0
 \end{aligned}$$

FIG. 10A

$$\begin{aligned}
 r_{13} &= \begin{bmatrix} A_1 & B_1 \\ A_3 & B_3 \end{bmatrix} \setminus \begin{bmatrix} -D_1 \\ -D_3 \end{bmatrix} \\
 r_{23} &= \begin{bmatrix} A_2 & B_2 \\ A_3 & B_3 \end{bmatrix} \setminus \begin{bmatrix} -D_2 \\ -D_3 \end{bmatrix} \\
 r_{14} &= \begin{bmatrix} A_1 & B_1 \\ A_4 & B_4 \end{bmatrix} \setminus \begin{bmatrix} -D_1 \\ -D_4 \end{bmatrix} \\
 r_{24} &= \begin{bmatrix} A_2 & B_2 \\ A_4 & B_4 \end{bmatrix} \setminus \begin{bmatrix} -D_2 \\ -D_4 \end{bmatrix}
 \end{aligned}$$

FIG. 10B

$$\begin{aligned}
 v &= \begin{bmatrix} G_2^2 & G_3^2 & G_4^2 \\ (G_2H_2)^2 & (G_3H_3)^2 & (G_4H_4)^2 \\ H_2^2 & H_3^2 & H_4^2 \end{bmatrix} \setminus \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix} \\
 w &= \begin{bmatrix} G_2^2 & G_3^2 & G_4^2 \\ (G_2H_2)^2 & (G_3H_3)^2 & (G_4H_4)^2 \\ H_2^2 & H_3^2 & H_4^2 \end{bmatrix} \setminus \begin{bmatrix} 0 \\ 1 \\ 0 \end{bmatrix}
 \end{aligned}$$

$$\begin{aligned}
 c1 &= (r_{13} + r_{24}) / 2 \\
 c2 &= (r_{14} + r_{23}) / 2 \\
 \delta1 &= c2_1 - c1_1 \\
 \delta2 &= c2_2 - c1_2 \\
 p &= \delta1 / \delta2 \\
 q &= c1_1 - c1_2 * p \\
 G &= Ap + B \\
 H &= Aq + D
 \end{aligned}$$

FIG. 10C

$$\begin{aligned}
 v_{A2} &= (v_1A_1)^2 + (v_2A_2)^2 + (v_3A_3)^2 \\
 v_{AB} &= (v_1A_1B_1)^2 + (v_2A_2B_2)^2 + (v_3A_3B_3)^2 \\
 v_{B2} &= (v_1B_1)^2 + (v_2B_2)^2 + (v_3B_3)^2 \\
 w_{A2} &= (w_1A_1)^2 + (w_2A_2)^2 + (w_3A_3)^2 \\
 w_{AB} &= (w_1A_1B_1)^2 + (w_2A_2B_2)^2 + (w_3A_3B_3)^2 \\
 w_{B2} &= (w_1B_1)^2 + (w_2B_2)^2 + (w_3B_3)^2
 \end{aligned}$$

FIG. 10D

$$0 = Q_8 t^8 + Q_7 t^7 + Q_6 t^6 + Q_5 t^5 + Q_4 t^4 + Q_3 t^3 + Q_2 t^2 + Q_1 t + Q_0$$

FIG. 10E

$$Q_8 = 4A_1^2 n^2 v_{B2}^2 + 4v_{B2} B_1^2 (1 - n^2 v_{A2}) - (G_1 (1 - n^2 v_{A2}) w_{B2} + n^2 v_{B2} w_{A2} + 2H_1 v_{B2})^2$$

FIG. 10F

$$Q_7 = - (2(2n^2 v_{AB} w_{A2} + 4H_1 v_{AB} + 2G_1 n^2 v_{AB} w_{B2} + 2G_1 (1 - n^2 v_{A2}) w_{AB})) (G_1 (1 - n^2 v_{A2}) w_{B2} + n^2 v_{B2} w_{A2} + 2H_1 v_{B2}) - 8A_1 B_1 n^2 v_{B2}^2 + 16A_1^2 n^2 v_{AB} v_{B2} + (4(2A_1 B_1 (1 - n^2 v_{A2}) + 2B_1^2 n^2 v_{AB})) v_{B2} + 8B_1^2 (1 - n^2 v_{A2}) v_{AB}$$

FIG. 10G

$$Q_6 = - (2(2H_1 v_{B2} + 2H_1 v_{A2} + n^2 v_{A2} w_{A2} + n^2 v_{B2} (-2w_{AB} + w_{B2})) + G_1 (n^2 v_{B2} + 1) w_{B2} + 4G_1 n^2 v_{AB} w_{AB} + G_1 (1 - n^2 v_{A2}) v_{A2})) \times (G_1 (1 - n^2 v_{A2}) w_{B2} + n^2 v_{B2} w_{A2} + 2H_1 v_{B2}) - (2n^2 v_{AB} w_{A2} + 4H_1 v_{AB} + 2G_1 n^2 v_{AB} w_{B2} + 2G_1 (1 - n^2 v_{A2}) w_{AB})^2 + 4B_1^2 n^2 v_{B2}^2 - 32A_1 B_1 n^2 v_{AB} v_{B2} + 4A_1^2 n^2 (2v_{A2} v_{B2} + 4v_{AB}^2) + 4A_1^2 n^2 v_{B2}^2 + (4(A_1^2 (1 - n^2 v_{A2}) + 4A_1 B_1 n^2 v_{AB} + B_1^2 (-n^2 v_{B2} + 1) + B_1^2 (1 - n^2 v_{A2}))) v_{B2} + (8(2A_1 B_1 (1 - n^2 v_{A2}) + 2B_1^2 n^2 v_{AB})) v_{AB} + 4B_1^2 (1 - n^2 v_{A2}) v_{A2}$$

FIG. 10H

$$\begin{aligned}
 Q_5 = & - (2(4H_1V_{AB} + 2G_1(-n^2v_{B2} + 1)W_{AB} + 2G_1n^2v_{AB}v_{A2} + 2n^2v_A(-2W_{AB} + W_{B2}))) (G_1(1 - n^2v_{A2})W_{B2} + n^2v_{B2}W_{A2} + 2H_1v_{B2}) - \\
 & (2(2H_1v_{B2} + 2H_1v_{A2} + n^2v_{A2}W_{A2} + n^2v_{B2}(-2W_{AB} + W_{B2}) + G_1(-n^2v_{B2} + 1)W_{B2} + 4G_1n^2v_{AB}W_{AB} + G_1(1 - n^2v_{A2})v_{A2})) \times \\
 & (2n^2v_{AB}W_{A2} + 4H_1v_{AB} + 2G_1n^2v_{AB}W_{B2} + 2G_1(1 - n^2v_{A2})W_{AB}) + 16B_1^2n^2v_{AB}v_{B2} - 8A_1B_1n^2(2v_{A2}v_{B2} + 4v_{AB}^2) + \\
 & 16A_1^2n^2v_{A2}v_{AB} - 8A_1B_1n^2v_{B2}^2 + 16A_1^2n^2v_{AB}v_{B2} + (4(2A_1^2n^2v_{AB} + 2A_1B_1(-n^2v_{B2} + 1) + 2A_1B_1(1 - n^2v_{A2}) + 2B_1^2n^2v_{AB}))v_{B2} + \\
 & (8(A_1^2(1 - n^2v_{A2}) + 4A_1B_1n^2v_{AB} + B_1^2(-n^2v_{B2} + 1) + B_1^2(1 - n^2v_{A2})))v_{AB} + (4(2A_1B_1(1 - n^2v_{A2}) + 2B_1^2n^2v_{AB}))v_{A2}
 \end{aligned}$$

FIG. 10I

$$\begin{aligned}
 Q_4 = & (4(A_1^2(-n^2v_{B2}) + A_1^2(1 - n^2v_{A2}) + 4A_1B_1n^2v_{AB} + B_1^2(-n^2v_{B2} + 1)))v_{B2} + \\
 & (8(2A_1^2n^2v_{AB} + 2A_1B_1(-n^2v_{B2} + 1) + 2A_1B_1(1 - n^2v_{A2}) + 2B_1^2n^2v_{AB}))v_{AB} + \\
 & (4(A_1^2(1 - n^2v_{A2}) + 4A_1B_1n^2v_{AB} + B_1^2(-n^2v_{B2} + 1) + B_1^2(1 - n^2v_{A2})))v_{A2} + 4B_1^2n^2(2v_{A2}v_{B2} + 4v_{AB}^2) - 32A_1B_1n^2v_{A2}v_{AB} + 4A_1^2n^2v_{A2} + \\
 & 4B_1^2n^2v_{B2}^2 - 32A_1B_1n^2v_{AB}v_{B2} + 4A_1^2n^2(2v_{A2}v_{B2} + 4v_{AB}^2) - \\
 & (2(G_1(-n^2v_{B2} + 1)v_{A2} + n^2v_{A2}(-2W_{AB} + W_{B2}) + 2H_1v_{A2})) (G_1(1 - n^2v_{A2})W_{B2} + n^2v_{B2}W_{A2} + 2H_1v_{B2}) - \\
 & (2(4H_1v_{AB} + 2G_1(-n^2v_{B2} + 1)W_{AB} + 2G_1n^2v_{AB}v_{A2} + 2n^2v_{AB}(-2W_{AB} + W_{B2}))) \times \\
 & (2n^2v_{AB}W_{A2} + 4H_1v_{AB} + 2G_1n^2v_{AB}W_{B2} + 2G_1(1 - n^2v_{A2})W_{AB}) - \\
 & (2H_1v_{B2} + 2H_1v_{A2} + n^2v_{A2}W_{A2} + n^2v_{B2}(-2W_{AB} + W_{B2}) + G_1(-n^2v_{B2} + 1)W_{B2} + 4G_1n^2v_{AB}W_{AB} + G_1(1 - n^2v_{A2})v_{A2})^2
 \end{aligned}$$

FIG. 10J

$$Q_3 = -(2(G_1(-n^2v_{B2} + 1)v_{A2} + n^2v_{A2}(-2w_{AB} + w_{B2}) + 2H_1v_{A2})) (2n^2v_{AB}w_{A2} + 4H_1v_{AB} + 2G_1n^2v_{AB}w_{B2} + 2G_1(1-n^2v_{A2})w_{AB}) - (2(4H_1v_{AB} + 2G_1(-n^2v_{B2} + 1)w_{AB} + 2G_1n^2v_{AB}v_{A2} + 2n^2v_{AB}(-2w_{AB} + w_{B2})))x \\ (2H_1v_{B2} + 2H_1v_{A2} + n^2v_{A2}w_{A2} + n^2v_{B2}(-2w_{AB} + w_{B2}) + G_1(-n^2v_{B2} + 1)w_{B2} + 4G_1n^2v_{AB}w_{AB} + G_1(1-n^2v_{A2})v_{A2}) + 16B_1^2n^2v_{A2}v_{AB} - 8A_1B_1n^2v_{A2}^2 + 16B_1^2n^2v_{AB}v_{B2} - 8A_1B_1n^2(2v_{A2}v_{B2} + 4v_{AB}^2) + 16A_1^2n^2v_{AB} + 4(2A_1^2n^2v_{AB} + 2A_1B_1(-n^2v_{B2} + 1))v_{B2} + (8(A_1^2(-n^2v_{B2} + 1) + A_1^2(1-n^2v_{A2}) + 4A_1B_1n^2v_{AB} + B_1^2(-n^2v_{B2} + 1)))v_{AB} + (4(2A_1^2n^2v_{AB} + 2A_1B_1(-n^2v_{B2} + 1) + 2A_1B_1(1-n^2v_{A2}) + 2B_1^2n^2v_{AB}))v_{A2}$$

FIG. 10K

$$Q_2 = 4A_1^2(-n^2v_{B2} + 1)v_{B2} + (8(2A_1^2n^2v_{AB} + 2A_1B_1(-n^2v_{B2} + 1)))v_{AB} + (4(A_1^2(-n^2v_{B2} + 1) + A_1^2(1-n^2v_{A2}) + 4A_1B_1n^2v_{AB} + B_1^2(-n^2v_{B2} + 1)))v_{A2} + 4B_1^2n^2v_{A2}^2 + 4B_1^2n^2(2v_{A2}v_{B2} + 4v_{AB}^2) - 32A_1B_1n^2v_{A2}v_{AB} + 4A_1^2n^2v_{A2}^2 - (2(G_1(-n^2v_{B2} + 1)v_{A2} + n^2v_{A2}(-2w_{AB} + w_{B2}) + 2H_1v_{A2}))x \\ (2H_1v_{B2} + 2H_1v_{A2} + n^2v_{A2}w_{A2} + n^2v_{B2}(-2w_{AB} + w_{B2}) + G_1(-n^2v_{B2} + 1)w_{B2} + 4G_1n^2v_{AB}w_{AB} + G_1(1-n^2v_{A2})v_{A2}) - (4H_1v_{AB} + 2G_1(-n^2v_{B2} + 1)w_{AB} + 2G_1n^2v_{AB}v_{A2} + 2n^2v_{AB}(-2w_{AB} + w_{B2}))^2$$

FIG. 10L

$$Q_1 = 8A_1^2(-n^2v_{B2} + 1)v_{AB} + (4(2A_1^2n^2v_{AB} + 2A_1B_1(-n^2v_{B2} + 1)))v_{A2} + 16B_1^2n^2v_{A2}v_{AB} - 8A_1B_1n^2v_{A2}^2 - (2(G_1(-n^2v_{B2} + 1)v_{A2} + n^2v_{A2}(-2w_{AB} + w_{B2}) + 2H_1v_{A2})) (4H_1v_{AB} + 2G_1(-n^2v_{B2} + 1)w_{AB} + 2G_1n^2v_{AB}v_{A2} + 2n^2v_{AB}(-2w_{AB} + w_{B2}))$$

FIG. 10M

$$Q_0 = 4A_1^2(-n^2v_{B2} + 1)v_{A2} - (G_1(-n^2v_{B2} + 1)v_{A2} + n^2v_{A2}(-2w_{AB} + w_{B2}) + 2H_1v_{A2})^2 + 4B_1^2n^2v_{A2}^2$$

FIG. 10N




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21A





FIG. 21B




FIG. 21C




FIG. 22




FIG. 23

CONVERTING IMAGES OF SHADOWS TO SHADOW POINTS




FIG. 24A




FIG. 24B




FIG. 25A




FIG. 25B




FIG. 25C




FIG. 26




FIG. 27




FIG. 28A




FIG. 28B




FIG. 28C

**SYSTEMS AND METHODS OF LOCATING A
CONTROL OBJECT APPENDAGE IN THREE
DIMENSIONAL (3D) SPACE**

CROSS-REFERENCE TO RELATED
APPLICATION

This application is a continuation of U.S. patent application Ser. No. 15/953,320, filed Apr. 13, 2018 entitled “SYSTEMS AND METHODS OF LOCATING A CONTROL OBJECT APPENDAGE IN THREE DIMENSIONAL (3D) SPACE”, which is a continuation of U.S. patent application Ser. No. 14/723,370, filed May 27, 2015, entitled “SYSTEMS AND METHODS OF LOCATING A CONTROL OBJECT APPENDAGE IN THREE DIMENSIONAL (3D) SPACE”, which is a continuation of U.S. patent application Ser. No. 13/724,357 filed Dec. 21, 2012, entitled “SYSTEMS AND METHODS FOR CAPTURING MOTION IN THREE-DIMENSIONAL SPACE”, which is a continuation in part of U.S. patent application Ser. No. 13/414,485 filed Mar. 7, 2012, entitled “MOTION CAPTURE USING CROSS-SECTIONS OF AN OBJECT”, which claims the benefit of U.S. Provisional Patent Application No. 61/587,554 filed Jan. 17, 2012, entitled “METHODS AND SYSTEMS FOR IDENTIFYING POSITION AND SHAPE OF OBJECTS IN THREE-DIMENSIONAL SPACE”. Additionally, U.S. patent application Ser. No. 13/724,357 filed Dec. 21, 2012, entitled “SYSTEMS AND METHODS FOR CAPTURING MOTION IN THREE-DIMENSIONAL SPACE”, claims priority to and the benefit of U.S. Provisional Patent Application No. 61/724,091 filed Nov. 8, 2012, entitled “SYSTEMS AND METHODS FOR CAPTURING MOTION IN THREE-DIMENSIONAL SPACE”. The foregoing applications are incorporated herein by reference in their entireties.

FIELD OF THE INVENTION

The present invention relates, in general, to image analysis, and in particular embodiments to identifying shapes and capturing motions of objects in three-dimensional space.

BACKGROUND

Motion capture has numerous applications. For example, in filmmaking, digital models generated using motion capture can be used as the basis for the motion of computer-generated characters or objects. In sports, motion capture can be used by coaches to study an athlete’s movements and guide the athlete toward improved body mechanics. In video games or virtual reality applications, motion capture can be used to allow a person to interact with a virtual environment in a natural way, e.g., by waving to a character, pointing at an object, or performing an action such as swinging a golf club or baseball bat.

The term “motion capture” refers generally to processes that capture movement of a subject in three-dimensional (3D) space and translate that movement into, for example, a digital model or other representation. Motion capture is typically used with complex subjects that have multiple separately articulating members whose spatial relationships change as the subject moves. For instance, if the subject is a walking person, not only does the whole body move across space, but the position of arms and legs relative to the person’s core or trunk are constantly shifting. Motion capture systems are typically interested in modeling this articulation.

Most existing motion capture systems rely on markers or sensors worn by the subject while executing the motion and/or on the strategic placement of numerous cameras in the environment to capture images of the moving subject from different angles. Such systems tend to be expensive to construct. In addition, markers or sensors worn by the subject can be cumbersome and interfere with the subject’s natural movement. Further, systems involving large numbers of cameras tend not to operate in real time, due to the volume of data that needs to be analyzed and correlated. Such considerations of cost, complexity and convenience have limited the deployment and use of motion capture technology.

Consequently, there is a need for an economical approach that captures the motion of objects in real time without attaching sensors or markers thereto.

SUMMARY

Embodiments of the present invention relate to methods and systems for capturing motion and/or determining the shapes and positions of one or more objects in 3D space using at least one cross-section thereof; the cross-section(s) may be obtained from, for example, reflections from the object or shadows cast by the object. In various embodiments, the 3D reflections or shadows captured using a camera are first sliced into multiple two-dimensional (2D) cross-sectional images. The cross-sectional position and shape (or “intersection region”) of the 3D objects in each 2D slice may be determined based on the positions of one or more light sources used to illuminate the objects and the captured reflections or shadows. The 3D structure of the object may then be reconstructed by assembling a collection of the intersection regions obtained in the 2D slices. In some embodiments, the 2D intersection regions are identified based on “true” intersection points—i.e., points within the volume defined by the intersection of all light beams, which volume includes the object. These true intersection points may be determined by the light sources and reflections or shadows—e.g., based on the number of reflection or shadow regions that they lie within or the locations of the geometric projection points calculated based on the positions of the light sources. In one embodiment, the light sources are arranged, for example, in a line or a plane such that the true intersection points are determined without identifying the actual locations thereof; this reduces the computational complexity, thereby increasing the processing speed. In some embodiments, the intersection region is split into a number of smaller intersection regions that can individually represent at least a portion of the reflections or shadows in the scene. Because determining each of the smaller intersection regions is computationally simpler than determining the entire intersection region, the processing time for obtaining the entire intersection region assembled from the individual smaller intersection regions is reduced (even if the smaller intersection regions are determined sequentially rather than in parallel). In various embodiments, the number of small split intersection regions that need to be identified is reduced by setting a criteria number U equal to the greatest number of intersection points in any intersection region; only regions or combinations of regions having a number of intersection points exceeding the criteria number U are further processed to identify the intersection regions therein.

In some embodiments, an image coordinate system using, for example, an imaging grid is incorporated into the system to easily define locations of the reflections or shadows. In

one implementation, the camera includes multiple color filters placed on the light sensors to generate multiple images, each corresponding to a different color filter. Application of the 2D approaches described above to the color-specific images may then determine both the locations and colors of the objects.

Accordingly, in one aspect, the invention pertains to a method of identifying a position and shape of an object (e.g., a human, a human body part, or a handheld object such as a pencil or a scalpel) in 3D space. In representative embodiments, the method includes capturing an image generated by casting an output from one or more sources (e.g., a light source or a sonic source) onto the object; analyzing the image to computationally slice the object into multiple 2D slices, where each slice corresponds to a cross-section of the object; identifying shapes and positions of multiple cross-sections of the object based at least in part on the image and a location of the one or more sources; and reconstructing the position and shape of the object in 3D space based at least in part on the multiple identified cross-sectional shapes and positions of the object. The position and shape of the object in 3D space may be reconstructed based on correlations between the multiple 2D slices.

In various embodiments, the cross-sectional shape and position of the object is identified by selecting a collection of intersection points generated by analyzing a location of the one or more sources and positions of points in the image (e.g., a shadow of the object) associated with the 2D slice. The intersection points may be selected based on the total number source(s) employed. Alternatively, the intersection points may be selected based on locations of projection points associated with the intersection points, where the projection points are projections from the intersection points onto the 2D slice (e.g., where the projection is dictated by the position(s) of the source(s)). In some embodiments, the method further includes splitting the cross-section of the object into multiple regions and using each region to generate one or more portions of the shadow image of the 2D slice, and identifying the regions based on the shadow image of the 2D slice and the location of the one or more sources. A region may be established or recognized if the number of the intersection points is equal to or greater than a predetermined criteria number. Additionally, the intersection points may be selected based on the location of the source(s) and the size of the image cross-section. The image may include reflections from the object and the intersection points may be selected based on time-of-flight data using a time-of-flight camera. In one implementation, the selected collection of intersection points in a first 2D slice is reused in a second 2D slice. In addition, the image may be generated by casting light from multiple light sources, aligned in a line or in a plane, onto the object.

In one embodiment, the method includes defining a 3D model of the object and reconstructing the position and shape of the object in 3D space based on the 3D model. In another embodiment, the method includes defining coordinates of the image. In one implementation, the image is separated into multiple primary images each including a color; various colors on the object are identified based on the primary images.

In various embodiments, the method includes manipulating one or more virtual objects displayed on a device based on the identified position and shape of the object. The device may be a head-mounted device or a TV. In one embodiment, the identified position and shape of the object is used to manipulate the virtual object via wireless cell phone communication. In some embodiments, the method further

includes authenticating a user based on the detected shape of the object and/or the detected motion of the object and subsequent matching thereof to data in a database record corresponding to the user.

In another aspect, the invention relates to a system for identifying a position and shape of an object in 3D space. In various embodiments, the system includes one or more cameras (e.g., a time-of-flight camera) oriented toward a field of view; one or more sources (e.g., a light source or a sonic source) to direct illumination onto the object in the field of view; and an image analyzer coupled to the camera and the source and configured to operate the camera to capture one or more images of the object and identify a position and shape of the object in 3D space based on the captured image and a location of the source.

In one implementation, the one or more light sources include multiple light sources each aligned in a line or in a plane. Additionally, the system may include multiple filters placed on light sensors of the camera to generate multiple images, each of which corresponds to a color filter. In one embodiment, the image analyzer is further configured to (i) slice the object into multiple 2D slices each corresponding to a cross-section of the object, (ii) identify a shape and position of the object based at least in part on an image captured by the camera and a location of the one or more light source, and (iii) reconstruct the position and shape of the object in 3D space based at least in part on the multiple identified cross-sectional shapes and positions of the object. In some embodiments, the image analyzer is further configured to define a 3D model of the object and reconstruct the position and shape of the object in 3D space based on the 3D model.

In various embodiments, the system further includes a secondary device (e.g., a head-mounted device or a mobile device) operatively connected to the system. The secondary device may be an authentication server for authenticating a user based on a shape and/or a jitter of the user's hand detected by the image analyzer.

Reference throughout this specification to "one example," "an example," "one embodiment," or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the example is included in at least one example of the present technology. Thus, the occurrences of the phrases "in one example," "in an example," "one embodiment," or "an embodiment" in various places throughout this specification are not necessarily all referring to the same example. Furthermore, the particular features, structures, routines, steps, or characteristics may be combined in any suitable manner in one or more examples of the technology. The headings provided herein are for convenience only and are not intended to limit or interpret the scope or meaning of the claimed technology.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, like reference characters generally refer to the same parts throughout the different views. Also, the drawings are not necessarily to scale, with an emphasis instead generally being placed upon illustrating the principles of the invention. In the following description, various embodiments of the present invention are described with reference to the following drawings, in which:

FIG. 1 is a simplified illustration of a motion capture system according to an embodiment of the present invention;

5

FIG. 2 is a simplified block diagram of a computer system that can be used according to an embodiment of the present invention;

FIGS. 3A (top view) and 3B (side view) are conceptual illustrations of how slices are defined in a field of view according to an embodiment of the present invention;

FIGS. 4A, 4B and 4C are top views illustrating an analysis that can be performed on a given slice according to an embodiment of the present invention. FIG. 4A is a top view of a slice. FIG. 4B illustrates projecting edge points from an image plane to a vantage point to define tangent lines. FIG. 4C illustrates fitting an ellipse to tangent lines as defined in FIG. 4B;

FIG. 5 graphically illustrates an ellipse in the xy plane characterized by five parameters;

FIGS. 6A and 6B provide a flow diagram of a motion-capture process according to an embodiment of the present invention;

FIG. 7 graphically illustrates a family of ellipses that can be constructed from four tangent lines;

FIG. 8 sets forth a general equation for an ellipse in the xy plane;

FIG. 9 graphically illustrates how a centerline can be found for an intersection region with four tangent lines according to an embodiment of the present invention;

FIGS. 10A, 10B, 10C, 10D, 10E, 10F, 10G, 10H, 10I, 10J, 10K, 10L, 10M and 10N set forth equations that can be solved to fit an ellipse to four tangent lines according to an embodiment of the present invention;

FIGS. 11A, 11B and 11C are top views illustrating instances of slices containing multiple disjoint cross-sections according to various embodiments of the present invention;

FIG. 12 graphically illustrates a model of a hand that can be generated using a motion capture system according to an embodiment of the present invention;

FIG. 13 is a simplified system diagram for a motion-capture system with three cameras according to an embodiment of the present invention;

FIG. 14 illustrates a cross-section of an object as seen from three vantage points in the system of FIG. 13;

FIG. 15 graphically illustrates a technique that can be used to find an ellipse from at least five tangents according to an embodiment of the present invention;

FIG. 16 schematically illustrates a system for capturing shadows of an object according to an embodiment of the present invention;

FIG. 17 schematically illustrates an ambiguity that can occur in the system of FIG. 16;

FIG. 18 schematically illustrates another system for capturing shadows of an object according to another embodiment of the present invention;

FIG. 19 graphically depicts a collection of the intersection regions defined by a virtual rubber band stretched around multiple intersection regions in accordance with an embodiment of the invention;

FIG. 20 schematically illustrates a simple intersection region constructed using two light sources in accordance with an embodiment of the invention;

FIGS. 21A, 21B and 21C schematically depict determinations of true intersection points in accordance with various embodiments of the invention;

FIG. 22 schematically depicts an intersection region uniquely identified using a group of the intersection points;

FIG. 23 illustrates an image coordinate system incorporated to define the locations of the shadows in accordance with an embodiment of the invention;

6

FIG. 24A illustrates separate color images captured using color filters in accordance with an embodiment of the invention;

FIG. 24B depicts a reconstructed 3D image of the object;

FIGS. 25A, 25B and 25C schematically illustrate a system for capturing an image of both the object and one or more shadows cast by the object from one or more light sources at known positions according to an embodiment of the present invention;

FIG. 26 schematically illustrates a camera-and-beamsplitter setup for a motion capture system according to another embodiment of the present invention;

FIG. 27 schematically illustrates a camera-and-pinhole setup for a motion capture system according to another embodiment of the present invention; and

FIGS. 28A, 28B, and 28C depict a motion capture system operatively connected to a head-mounted device, a mobile device, and an authentication server, respectively.

DETAILED DESCRIPTION

Embodiments of the present invention relate to methods and systems for capturing motion and/or determining position of an object using small amounts of information. For example, an outline of an object's shape, or silhouette, as seen from a particular vantage point can be used to define tangent lines to the object from that vantage point in various planes, referred to herein as "slices." Using as few as two different vantage points, four (or more) tangent lines from the vantage points to the object can be obtained in a given slice. From these four (or more) tangent lines, it is possible to determine the position of the object in the slice and to approximate its cross-section in the slice, e.g., using one or more ellipses or other simple closed curves. As another example, locations of points on an object's surface in a particular slice can be determined directly (e.g., using a time-of-flight camera), and the position and shape of a cross-section of the object in the slice can be approximated by fitting an ellipse or other simple closed curve to the points. Positions and cross-sections determined for different slices can be correlated to construct a 3D model of the object, including its position and shape. A succession of images can be analyzed using the same technique to model motion of the object. Motion of a complex object that has multiple separately articulating members (e.g., a human hand) can be modeled using techniques described herein.

In some embodiments, the silhouettes of an object are extracted from one or more images of the object that reveal information about the object as seen from different vantage points. While silhouettes can be obtained using a number of different techniques, in some embodiments, the silhouettes are obtained by using cameras to capture images of the object and analyzing the images to detect object edges.

FIG. 1 is a simplified illustration of a motion capture system 100 according to an embodiment of the present invention. System 100 includes two cameras 102, 104 arranged such that their fields of view (indicated by broken lines) overlap in region 110. Cameras 102 and 104 are coupled to provide image data to a computer 106. Computer 106 analyzes the image data to determine the 3D position and motion of an object, e.g., a hand 108, that moves in the field of view of cameras 102, 104.

Cameras 102, 104 can be any type of camera, including visible-light cameras, infrared (IR) cameras, ultraviolet cameras or any other devices (or combination of devices) that are capable of capturing an image of an object and representing that image in the form of digital data. Cameras

102, 104 are preferably capable of capturing video images (i.e., successive image frames at a constant rate of at least 15 frames per second), although no particular frame rate is required. The particular capabilities of cameras **102, 104** are not critical to the invention, and the cameras can vary as to
 5 frame rate, image resolution (e.g., pixels per image), color or intensity resolution (e.g., number of bits of intensity data per pixel), focal length of lenses, depth of field, etc. In general, for a particular application, any cameras capable of focusing on objects within a spatial volume of interest can be used. For instance, to capture motion of the hand of an otherwise stationary person, the volume of interest might be a meter on a side. To capture motion of a running person, the volume of interest might be tens of meters in order to observe several strides (or the person might run on a treadmill, in which case
 10 the volume of interest can be considerably smaller).

The cameras can be oriented in any convenient manner. In the embodiment shown, respective optical axes **112, 114** of cameras **102** and **104** are parallel, but this is not required. As described below, each camera is used to define a “vantage point” from which the object is seen, and it is required only that a location and view direction associated with each
 20 vantage point be known, so that the locus of points in space that project onto a particular position in the camera’s image plane can be determined. In some embodiments, motion capture is reliable only for objects in area **110** (where the fields of view of cameras **102, 104** overlap), and cameras **102, 104** may be arranged to provide overlapping fields of view throughout the area where motion of interest is expected to occur.

In FIG. **1** and other examples described herein, object **108** is depicted as a hand. The hand is used only for purposes of illustration, and it is to be understood that any other object can be the subject of motion capture analysis as described herein. Computer **106** can be any device that is capable of
 35 processing image data using techniques described herein. FIG. **2** is a simplified block diagram of computer system **200** implementing computer **106** according to an embodiment of the present invention. Computer system **200** includes a processor **202**, a memory **204**, a camera interface **206**, a display **208**, speakers **209**, a keyboard **210**, and a mouse **211**.

Processor **202** can be of generally conventional design and can include, e.g., one or more programmable microprocessors capable of executing sequences of instructions. Memory **204** can include volatile (e.g., DRAM) and non-volatile (e.g., flash memory) storage in any combination.
 45 Other storage media (e.g., magnetic disk, optical disk) can also be provided. Memory **204** can be used to store instructions to be executed by processor **202** as well as input and/or output data associated with execution of the instructions.

Camera interface **206** can include hardware and/or software that enables communication between computer system **200** and cameras such as cameras **102, 104** of FIG. **1**. Thus, for example, camera interface **206** can include one or more data ports **216, 218** to which cameras can be connected, as well as hardware and/or software signal processors to modify data signals received from the cameras (e.g., to reduce noise or reformat data) prior to providing the signals as inputs to a conventional motion-capture (“mocap”) program **214** executing on processor **202**. In some embodiments, camera interface **206** can also transmit signals to the cameras, e.g., to activate or deactivate the cameras, to control camera settings (frame rate, image quality, sensitivity, etc.), or the like. Such signals can be transmitted, e.g., in response to control signals from processor **202**, which may
 50 in turn be generated in response to user input or other detected events.

In some embodiments, memory **204** can store mocap program **214**, which includes instructions for performing motion capture analysis on images supplied from cameras connected to camera interface **206**. In one embodiment, mocap program **214** includes various modules, such as an
 5 image analysis module **222**, a slice analysis module **224**, and a global analysis module **226**. Image analysis module **222** can analyze images, e.g., images captured via camera interface **206**, to detect edges or other features of an object. Slice analysis module **224** can analyze image data from a slice of an image as described below, to generate an approximate cross-section of the object in a particular plane. Global analysis module **226** can correlate cross-sections across different slices and refine the analysis. Examples of operations that can be implemented in code modules of mocap program **214** are described below.

Memory **204** can also include other information used by mocap program **214**; for example, memory **204** can store image data **228** and an object library **230** that can include canonical models of various objects of interest. As described below, an object being modeled can be identified by matching its shape to a model in object library **230**.

Display **208**, speakers **209**, keyboard **210**, and mouse **211** can be used to facilitate user interaction with computer system **200**. These components can be of generally conventional design or modified as desired to provide any type of user interaction. In some embodiments, results of motion capture using camera interface **206** and mocap program **214** can be interpreted as user input. For example, a user can perform hand gestures that are analyzed using mocap program **214**, and the results of this analysis can be interpreted as an instruction to some other program executing on processor **200** (e.g., a web browser, word processor or the like). Thus, by way of illustration, a user might be able to use upward or downward swiping gestures to “scroll” a webpage currently displayed on display **208**, to use rotating gestures to increase or decrease the volume of audio output from speakers **209**, and so on.

It will be appreciated that computer system **200** is illustrative and that variations and modifications are possible. Computers can be implemented in a variety of form factors, including server systems, desktop systems, laptop systems, tablets, smart phones or personal digital assistants, and so on. A particular implementation may include other functionality not described herein, e.g., wired and/or wireless network interfaces, media playing and/or recording capability, etc. In some embodiments, one or more cameras may be built into the computer rather than being supplied as separate components.

While computer system **200** is described herein with reference to particular blocks, it is to be understood that the blocks are defined for convenience of description and are not intended to imply a particular physical arrangement of component parts. Further, the blocks need not correspond to physically distinct components. To the extent that physically distinct components are used, connections between components (e.g., for data communication) can be wired and/or wireless as desired.

An example of a technique for motion capture using the system of FIGS. **1** and **2** will now be described. In this embodiment, cameras **102, 104** are operated to collect a sequence of images of an object **108**. The images are time correlated such that an image from camera **102** can be paired with an image from camera **104** that was captured at the same time (within a few milliseconds). These images are then analyzed, e.g., using mocap program **214**, to determine the object’s position and shape in 3D space. In some
 65

embodiments, the analysis considers a stack of 2D cross-sections through the 3D spatial field of view of the cameras. These cross-sections are referred to herein as “slices.”

FIGS. 3A and 3B are conceptual illustrations of how slices are defined in a field of view according to an embodiment of the present invention. FIG. 3A shows, in top view, cameras 102 and 104 of FIG. 1. Camera 102 defines a vantage point 302, and camera 104 defines a vantage point 304. Line 306 joins vantage points 302 and 304. FIG. 3B shows a side view of cameras 102 and 104; in this view, camera 104 happens to be directly behind camera 102 and thus occluded; line 306 is perpendicular to the plane of the drawing. (It should be noted that the designation of these views as “top” and “side” is arbitrary; regardless of how the cameras are actually oriented in a particular setup, the “top” view can be understood as a view looking along a direction normal to the plane of the cameras, while the “side” view is a view in the plane of the cameras.)

An infinite number of planes can be drawn through line 306. A “slice” can be any one of those planes for which at least part of the plane is in the field of view of cameras 102 and 104. Several slices 308 are shown in FIG. 3B. (Slices 308 are seen edge-on; it is to be understood that they are 2D planes and not 1-D lines.) For purposes of motion capture analysis, slices can be selected at regular intervals in the field of view. For example, if the received images include a fixed number of rows of pixels (e.g., 1080 rows), each row can be a slice, or a subset of the rows can be used for faster processing. Where a subset of the rows is used, image data from adjacent rows can be averaged together, e.g., in groups of 2-3.

FIGS. 4A-4C illustrate an analysis that can be performed on a given slice. FIG. 4A is a top view of a slice as defined above, corresponding to an arbitrary cross-section 402 of an object. Regardless of the particular shape of cross-section 402, the object as seen from a first vantage point 404 has a “left edge” point 406 and a “right edge” point 408. As seen from a second vantage point 410, the same object has a “left edge” point 412 and a “right edge” point 414. These are in general different points on the boundary of object 402. A tangent line can be defined that connects each edge point and the associated vantage point. For example, FIG. 4A also shows that tangent line 416 can be defined through vantage point 404 and left edge point 406; tangent line 418 through vantage point 404 and right edge point 408; tangent line 420 through vantage point 410 and left edge point 412; and tangent line 422 through vantage point 410 and right edge point 414.

It should be noted that all points along any one of tangent lines 416, 418, 420, 422 will project to the same point on an image plane. Therefore, for an image of the object from a given vantage point, a left edge point and a right edge point can be identified in the image plane and projected back to the vantage point, as shown in FIG. 4B, which is another top view of a slice, showing the image plane for each vantage point. Image 440 is obtained from vantage point 442 and shows left edge point 446 and right edge point 448. Image 450 is obtained from vantage point 452 and shows left edge point 456 and right edge point 458. Tangent lines 462, 464, 466, 468 can be defined as shown. Given the tangent lines of FIG. 4B, the location in the slice of an elliptical cross-section can be determined, as illustrated in FIG. 4C, where ellipse 470 has been fit to tangent lines 462, 464, 466, 468 of FIG. 4B.

In general, as shown in FIG. 5, an ellipse in the xy plane can be characterized by five parameters: the x and y coordinates of the center (x_c , y_c), the semimajor axis (a), the

semiminor axis (b), and a rotation angle (θ) (e.g., the angle of the semimajor axis relative to the x axis). With only four tangents, as is the case in FIG. 4C, the ellipse is underdetermined. However, an efficient process for estimating the ellipse in spite of this has been developed. In various embodiments as described below, this involves making an initial working assumption (or “guess”) as to one of the parameters and revisiting the assumption as additional information is gathered during the analysis. This additional information can include, for example, physical constraints based on properties of the cameras and/or the object.

In some embodiments, more than four tangents to an object may be available for some or all of the slices, e.g., because more than two vantage points are available. An elliptical cross-section can still be determined, and the process in some instances is somewhat simplified as there is no need to assume a parameter value. In some instances, the additional tangents may create additional complexity. Examples of processes for analysis using more than four tangents are described below and in the '554 application noted above.

In some embodiments, fewer than four tangents to an object may be available for some or all of the slices, e.g., because an edge of the object is out of range of the field of view of one camera or because an edge was not detected. A slice with three tangents can be analyzed. For example, using two parameters from an ellipse fit to an adjacent slice (e.g., a slice that had at least four tangents), the system of equations for the ellipse and three tangents is sufficiently determined that it can be solved. As another option, a circle can be fit to the three tangents; defining a circle in a plane requires only three parameters (the center coordinates and the radius), so three tangents suffice to fit a circle. Slices with fewer than three tangents can be discarded or combined with adjacent slices.

In some embodiments, each of a number of slices is analyzed separately to determine the size and location of an elliptical cross-section of the object in that slice. This provides an initial 3D model (specifically, a stack of elliptical cross-sections), which can be refined by correlating the cross-sections across different slices. For example, it is expected that an object’s surface will have continuity, and discontinuous ellipses can accordingly be discounted. Further refinement can be obtained by correlating the 3D model with itself across time, e.g., based on expectations related to continuity in motion and deformation.

A further understanding of the analysis process can be had by reference to FIGS. 6A-6B, which provide a flow diagram of a motion-capture process 600 according to an embodiment of the present invention. Process 600 can be implemented, e.g., in mocap program 214 of FIG. 2.

At block 602, a set of images—e.g., one image from each camera 102, 104 of FIG. 1—is obtained. In some embodiments, the images in a set are all taken at the same time (or within a few milliseconds), although a precise timing is not required. The techniques described herein for constructing an object model assume that the object is in the same place in all images in a set, which will be the case if images are taken at the same time. To the extent that the images in a set are taken at different times, motion of the object may degrade the quality of the result, but useful results can be obtained as long as the time between images in a set is small enough that the object does not move far, with the exact limits depending on the particular degree of precision desired.

At block 604, each slice is analyzed. FIG. 6B illustrates a per-slice analysis that can be performed at block 604.

Referring to FIG. 6B, at block 606, edge points of the object in a given slice are identified in each image in the set. For example, edges of an object in an image can be detected using conventional techniques, such as contrast between adjacent pixels or groups of pixels. In some embodiments, if no edge points are detected for a particular slice (or if only one edge point is detected), no further analysis is performed on that slice. In some embodiments, edge detection can be performed for the image as a whole rather than on a per-slice basis.

At block 608, assuming enough edge points were identified, a tangent line from each edge point to the corresponding vantage point is defined, e.g., as shown in FIG. 4C and described above. At block 610 an initial assumption as to the value of one of the parameters of an ellipse is made, to reduce the number of free parameters from five to four. In some embodiments, the initial assumption can be, e.g., the semimajor axis (or width) of the ellipse. Alternatively, an assumption can be made as to eccentricity (ratio of semimajor axis to semiminor axis), and that assumption also reduces the number of free parameters from five to four. The assumed value can be based on prior information about the object. For example, if previous sequential images of the object have already been analyzed, it can be assumed that the dimensions of the object do not significantly change from image to image. As another example, if it is assumed that the object being modeled is a particular type of object (e.g., a hand), a parameter value can be assumed based on typical dimensions for objects of that type (e.g., an average cross-sectional dimension of a palm or finger). An arbitrary assumption can also be used, and any assumption can be refined through iterative analysis as described below.

At block 612, the tangent lines and the assumed parameter value are used to compute the other four parameters of an ellipse in the plane. For example, as shown in FIG. 7, four tangent lines 701, 702, 703, 704 define a family of inscribed ellipses 706 including ellipses 706a, 706b, and 706c, where each inscribed ellipse 706 is tangent to all four of lines 701-704. Ellipse 706a and 706b represent the “extreme” cases (i.e., the most eccentric ellipses that are tangent to all four of lines 701-704. Intermediate between these extremes are an infinite number of other possible ellipses, of which one example, ellipse 706c, is shown (dashed line).

The solution process selects one (or in some instances more than one) of the possible inscribed ellipses 706. In one embodiment, this can be done with reference to the general equation for an ellipse shown in FIG. 8. The notation follows that shown in FIG. 5, with (x, y) being the coordinates of a point on the ellipse, (x_c, y_c) the center, a and b the axes, and θ the rotation angle. The coefficients C_1, C_2 and C_3 are defined in terms of these parameters, as shown in FIG. 8.

The number of free parameters can be reduced based on the observation that the centers (x_c, y_c) of all the ellipses in family 706 lie on a line segment 710 (also referred to herein as the “centerline”) between the center of ellipse 706a (shown as point 712a) and the center of ellipse 706b (shown as point 712b). FIG. 9 illustrates how a centerline can be found for an intersection region. Region 902 is a “closed” intersection region; that is, it is bounded by tangents 904, 906, 908, 910. The centerline can be found by identifying diagonal line segments 912, 914 that connect the opposite corners of region 902, identifying the midpoints 916, 918 of these line segments, and identifying the line segment 920 joining the midpoints as the centerline.

Region 930 is an “open” intersection region; that is, it is only partially bounded by tangents 904, 906, 908, 910. In this case, only one diagonal, line segment 932, can be

defined. To define a centerline for region 930, centerline 920 from closed intersection region 902 can be extended into region 930 as shown. The portion of extended centerline 920 that is beyond line segment 932 is centerline 940 for region 930. In general, for any given set of tangent lines, both region 902 and region 930 can be considered during the solution process. (Often, one of these regions is outside the field of view of the cameras and can be discarded at a later stage.) Defining the centerline reduces the number of free parameters from five to four because y_c can be expressed as a (linear) function of x_c (or vice versa), based solely on the four tangent lines. However, for every point (x_c, y_c) on the centerline, a set of parameters $\{\theta, a, b\}$ can be found for an inscribed ellipse. To reduce this to a set of discrete solutions, an assumed parameter value can be used. For example, it can be assumed that the semimajor axis a has a fixed value a_0 . Then, only solutions $\{\theta, a, b\}$ that satisfy $a=a_0$ are accepted.

In one embodiment, the ellipse equation of FIG. 8 is solved for θ , subject to the constraints that: (1) (x_c, y_c) must lie on the centerline determined from the four tangents (i.e., either centerline 920 or centerline 940 of FIG. 9); and (2) a is fixed at the assumed value a_0 . The ellipse equation can either be solved for θ analytically or solved using an iterative numerical solver (e.g., a Newtonian solver as is known in the art). An analytic solution can be obtained by writing an equation for the distances to the four tangent lines given a y_c position, then solving for the value of y_c that corresponds to the desired radius parameter $a=a_0$. One analytic solution is illustrated in the equations of FIGS. 10A-10D. Shown in FIG. 10A are equations for four tangent lines in the xy plane (the slice). Coefficients A_i, B_i and D_i (for $i=1$ to 4) can be determined from the tangent lines identified in an image slice as described above. FIG. 10B illustrates the definition of four column vectors r_{12}, r_{23}, r_{14} and r_{24} from the coefficients of FIG. 10A. The “ \setminus ” operator here denotes matrix left division, which is defined for a square matrix M and a column vector v such that $M \setminus v=r$, where r is the column vector that satisfies $Mr=v$. FIG. 10C illustrates the definition of G and H , which are four-component vectors from the vectors of tangent coefficients A, B and D and scalar quantities p and q , which are defined using the column vectors r_{12}, r_{23}, r_{14} and r_{24} from FIG. 10B. FIG. 10D illustrates the definition of six scalar quantities $v_{A2}, v_{AB}, v_{B2}, w_{A2}, w_{AB}$, and w_{B2} in terms of the components of vectors G and H of FIG. 10C.

Using the parameters defined in FIGS. 10A-10D, solving for θ is accomplished by solving the eighth-degree polynomial equation shown in FIG. 10E for t , where the coefficients Q_i (for $i=0$ to 8) are defined as shown in FIGS. 10F-10N. The parameters $A_1, B_1, G_1, H_1, v_{A2}, v_{AB}, v_{B2}, w_{A2}, w_{AB}$, and w_{B2} used in FIGS. 10F-10N are defined as shown in FIGS. 10A-10D. The parameter n is the assumed semimajor axis (in other words, a_0). Once the real roots t are known, the possible values of θ are defined as $\theta=a \tan(t)$.

As it happens, the equation of FIGS. 10E-10N has at most three real roots; thus, for any four tangent lines, there are at most three possible ellipses that are tangent to all four lines and satisfy the $a=a_0$ constraint. (In some instances, there may be fewer than three real roots.) For each real root θ , the corresponding values of (x_c, y_c) and b can be readily determined. Depending on the particular inputs, zero or more solutions will be obtained; for example, in some instances, three solutions can be obtained for a typical configuration of tangents. Each solution is completely characterized by the parameters $\{\theta, a=a_0, b, (x_c, y_c)\}$.

Referring again to FIG. 6B, at block 614, the solutions are filtered by applying various constraints based on known (or

inferred) physical properties of the system. For example, some solutions would place the object outside the field of view of the cameras, and such solutions can readily be rejected. As another example, in some embodiments, the type of object being modeled is known (e.g., it can be known that the object is or is expected to be a human hand). Techniques for determining object type are described below; for now, it is noted that where the object type is known, properties of that object can be used to rule out solutions where the geometry is inconsistent with objects of that type. For example, human hands have a certain range of sizes and expected eccentricities in various cross-sections, and such ranges can be used to filter the solutions in a particular slice. These constraints can be represented in any suitable format, e.g., a physical model (as described below), an ordered list of parameters based on such a model, etc.

In some embodiments, cross-slice correlations can also be used to filter (or further filter) the solutions obtained at block 612. For example, if the object is known to be a hand, constraints on the spatial relationship between various parts of the hand (e.g., fingers have a limited range of motion relative to each other and/or to the palm of the hand) as represented in a physical model or explicit set of constraint parameters can be used to constrain one slice based on results from other slices. For purposes of cross-slice correlations, it should be noted that, as a result of the way slices are defined, the various slices may be tilted relative to each other, e.g., as shown in FIG. 3B. Accordingly, each planar cross-section can be further characterized by an additional angle θ , which can be defined relative to a reference direction 310 as shown in FIG. 3B.

At block 616, it is determined whether a satisfactory solution has been found. Various criteria can be used to assess whether a solution is satisfactory. For instance, if a unique solution is found (after filtering), that solution can be accepted, in which case process 600 proceeds to block 620 (described below). If multiple solutions remain or if all solutions were rejected in the filtering at block 614, it may be desirable to retry the analysis. If so, process 600 can return to block 610, allowing a change in the assumption used in computing the parameters of the ellipse.

Retrying can be triggered under various conditions. For example, in some instances, the initial parameter assumption (e.g., $a=a_0$) may produce no solutions or only nonphysical solutions (e.g., object outside the cameras' field of view). In this case, the analysis can be retried with a different assumption. In one embodiment, a small constant (which can be positive or negative) is added to the initial assumed parameter value (e.g., a_0) and the new value is used to generate a new set of solutions. This can be repeated until an acceptable solution is found (or until the parameter value reaches a limit). An alternative approach is to keep the same assumption but to relax the constraint that the ellipse be tangent to all four lines, e.g., by allowing the ellipse to be nearly but not exactly tangent to one or more of the lines. (In some embodiments, this relaxed constraint can also be used in the initial pass through the analysis.)

It should be noted that in some embodiments, multiple elliptical cross-sections may be found in some or all of the slices. For example, in some planes, a complex object (e.g., a hand) may have a cross-section with multiple disjoint elements (e.g., in a plane that intersects the fingers). Ellipse-based reconstruction techniques as described herein can account for such complexity; examples are described below. Thus, it is generally not required that a single ellipse be found in a slice, and in some instances, solutions entailing multiple ellipses may be favored.

For a given slice, the analysis of FIG. 6B yields zero or more elliptical cross-sections. In some instances, even after filtering at block 616, there may still be two or more possible solutions. These ambiguities can be addressed in further processing as described below.

Referring again to FIG. 6A, the per-slice analysis of block 604 can be performed for any number of slices, and different slices can be analyzed in parallel or sequentially, depending on available processing resources. The result is a 3D model of the object, where the model is constructed by, in effect, stacking the slices. At block 620, cross-slice correlations are used to refine the model. For example, as noted above, in some instances, multiple solutions may have been found for a particular slice. It is likely that the "correct" solution (i.e., the ellipse that best corresponds to the actual position of the object) will correlate well with solutions in other slices, while any "spurious" solutions (i.e., ellipses that do not correspond to the actual position of the object) will not. Uncorrelated ellipses can be discarded. In some embodiments where slices are analyzed sequentially, block 620 can be performed iteratively as each slice is analyzed.

At block 622, the 3D model can be further refined, e.g., based on an identification of the type of object being modeled. In some embodiments, a library of object types can be provided (e.g., as object library 230 of FIG. 2). For each object type, the library can provide characteristic parameters for the object in a range of possible poses (e.g., in the case of a hand, the poses can include different finger positions, different orientations relative to the cameras, etc.). Based on these characteristic parameters, a reconstructed 3D model can be compared to various object types in the library. If a match is found, the matching object type is assigned to the model.

Once an object type is determined, the 3D model can be refined using constraints based on characteristics of the object type. For instance, a human hand would characteristically have five fingers (not six), and the fingers would be constrained in their positions and angles relative to each other and to a palm portion of the hand. Any ellipses in the model that are inconsistent with these constraints can be discarded. In some embodiments, block 622 can include recomputing all or portions of the per-slice analysis (block 604) and/or cross-slice correlation analysis (block 620) subject to the type-based constraints. In some instances, applying type-based constraints may cause deterioration in accuracy of reconstruction if the object is misidentified. (Whether this is a concern depends on implementation, and type-based constraints can be omitted if desired.)

In some embodiments, object library 230 can be dynamically and/or iteratively updated. For example, based on characteristic parameters, an object being modeled can be identified as a hand. As the motion of the hand is modeled across time, information from the model can be used to revise the characteristic parameters and/or define additional characteristic parameters, e.g., additional poses that a hand may present.

In some embodiments, refinement at block 622 can also include correlating results of analyzing images across time. It is contemplated that a series of images can be obtained as the object moves and/or articulates. Since the images are expected to include the same object, information about the object determined from one set of images at one time can be used to constrain the model of the object at a later time. (Temporal refinement can also be performed "backward" in time, with information from later images being used to refine analysis of images at earlier times.)

At block **624**, a next set of images can be obtained, and process **600** can return to block **604** to analyze slices of the next set of images. In some embodiments, analysis of the next set of images can be informed by results of analyzing previous sets. For example, if an object type was determined, type-based constraints can be applied in the initial per-slice analysis, on the assumption that successive images are of the same object. In addition, images can be correlated across time, and these correlations can be used to further refine the model, e.g., by rejecting discontinuous jumps in the object's position or ellipses that appear at one time point but completely disappear at the next.

It will be appreciated that the motion capture process described herein is illustrative and that variations and modifications are possible. Steps described as sequential may be executed in parallel, order of steps may be varied, and steps may be modified, combined, added or omitted. Different mathematical formulations and/or solution procedures can be substituted for those shown herein. Various phases of the analysis can be iterated, as noted above, and the degree to which iterative improvement is used may be chosen based on a particular application of the technology. For example, if motion capture is being used to provide real-time interaction (e.g., to control a computer system), the data capture and analysis should be performed fast enough that the system response feels like real time to the user. Inaccuracies in the model can be tolerated as long as they do not adversely affect the interpretation or response to a user's motion. In other applications, e.g., where the motion capture data is to be used for rendering in the context of digital movie-making, an analysis with more iterations that produces a more refined (and accurate) model may be preferred. As noted above, an object being modeled can be a "complex" object and consequently may present multiple discrete ellipses in some cross-sections. For example, a hand has fingers, and a cross-section through the fingers may include as many as five discrete elements. The analysis techniques described above can be used to model complex objects.

By way of example, FIGS. **11A-11C** illustrate some cases of interest. In FIG. **11A**, cross-sections **1102**, **1104** would appear as distinct objects in images from both of vantage points **1106**, **1108**. In some embodiments, it is possible to distinguish object from background; for example, in an infrared image, a heat-producing object (e.g., living organisms) may appear bright against a dark background. Where object can be distinguished from background, tangent lines **1110** and **1111** can be identified as a pair of tangents associated with opposite edges of one apparent object while tangent lines **1112** and **1113** can be identified as a pair of tangents associated with opposite edges of another apparent object. Similarly, tangent lines **1114** and **1115**, and tangent lines **1116** and **1117** can be paired. If it is known that vantage points **1106** and **1108** are on the same side of the object to be modeled, it is possible to infer that tangent pairs **1110**, **1111** and **1116**, **1117** should be associated with the same apparent object, and similarly for tangent pairs **1112**, **1113** and **1114**, **1115**. This reduces the problem to two instances of the ellipse-fitting process described above. If less information is available, an optimum solution can be determined by iteratively trying different possible assignments of the tangents in the slice in question, rejecting non-physical solutions, and cross-correlating results from other slices to determine the most likely set of ellipses.

In FIG. **11B**, ellipse **1120** partially occludes ellipse **1122** from both vantage points. In some embodiments, it may or may not be possible to detect the "occlusion" edges **1124**, **1126**. If edges **1124** and **1126** are not detected, the image

appears as a single object and is reconstructed as a single elliptical cross-section. In this instance, information from other slices or temporal correlation across images may reveal the error. If occlusion edges **1124** and/or **1126** are visible, it may be apparent that there are multiple objects (or that the object has a complex shape) but it may not be apparent which object or object portion is in front. In this case, it is possible to compute multiple alternative solutions, and the optimum solution may be ambiguous. Spatial correlations across slices, temporal correlations across image sets, and/or physical constraints based on object type can be used to resolve the ambiguity.

In FIG. **11C**, ellipse **1140** fully occludes ellipse **1142**. In this case, the analysis described above would not show ellipse **1142** in this particular slice. However, spatial correlations across slices, temporal correlations across image sets, and/or physical constraints based on object type can be used to infer the presence of ellipse **1142**, and its position can be further constrained by the fact that it is apparently occluded. In some embodiments, multiple discrete cross-sections (e.g., in any of FIGS. **11A-11C**) can also be resolved using successive image sets across time. For example, the four-tangent slices for successive images can be aligned and used to define a slice with 5-8 tangents. This slice can be analyzed using techniques described below.

In one embodiment of the present invention, a motion capture system can be used to detect the 3D position and movement of a human hand. In this embodiment, two cameras are arranged as shown in FIG. **1**, with a spacing of about 1.5 cm between them. Each camera is an infrared camera with an image rate of about 60 frames per second and a resolution of 640x480 pixels per frame. An infrared light source (e.g., an IR light-emitting diode) that approximates a point light source is placed between the cameras to create a strong contrast between the object of interest (in this case, a hand) and background. The falloff of light with distance creates a strong contrast if the object is a few inches away from the light source while the background is several feet away.

The image is analyzed using contrast between adjacent pixels to detect edges of the object. Bright pixels (detected illumination above a threshold) are assumed to be part of the object while dark pixels (detected illumination below a threshold) are assumed to be part of the background. Edge detection may take approximately 2 ms with conventional processing capability. The edges and the known camera positions are used to define tangent lines in each of 480 slices (one slice per row of pixels), and ellipses are determined from the tangents using the analytical technique described above with reference to FIGS. **6A** and **6B**. In a typical case of modeling a hand, roughly 800-1200 ellipses are generated from a single pair of image frames (the number depends on the orientation and shape of the hand) within, in various embodiments, about 6 ms. The error in modeling finger position in one embodiment is less than 0.1 mm.

FIG. **12** illustrates a model **1200** of a hand that can be generated using the system just described. As can be seen, the model does not have the exact shape of a hand, but a palm **1202**, thumb **1204** and four fingers **1206** can be clearly recognized. Such models can be useful as the basis for constructing more realistic models. For example, a skeleton model for a hand can be defined, and the positions of various joints in the skeleton model can be determined by reference to model **1200**. Using the skeleton model, a more realistic image of a hand can be rendered. Alternatively, a more realistic model may not be needed. For example, model

1200 accurately indicates the position of thumb **1204** and fingers **1206**, and a sequence of models **1200** captured across time will indicate movement of these digits. Thus, gestures can be recognized directly from model **1200**. The point is that ellipses identified and tracked as described above can be used to drive visual representations of the object tracked by application to a physical model of the object. The model may be selected based on a desired degree of realism, the response time desired (or the latency that can be tolerated), and available computational resources.

It will be appreciated that this example system is illustrative and that variations and modifications are possible. Different types and arrangements of cameras can be used, and appropriate image analysis techniques can be used to distinguish object from background and thereby determine a silhouette (or a set of edge locations for the object) that can in turn be used to define tangent lines to the object in various 2D slices as described above. Given four tangent lines to an object, where the tangents are associated with at least two vantage points, an elliptical cross-section can be determined; for this purpose it does not matter how the tangent lines are determined. Thus, a variety of imaging systems and techniques can be used to capture images of an object that can be used for edge detection. In some cases, more than four tangents can be determined in a given slice. For example, more than two vantage points can be provided.

In one alternative embodiment, three cameras can be used to capture images of an object. FIG. **13** is a simplified system diagram for a system **1300** with three cameras **1302**, **1304**, **1306** according to an embodiment of the present invention. Each camera **1302**, **1304**, **1306** provides a vantage point **1308**, **1310**, **1312** and is oriented toward an object of interest **1313**. In this embodiment, cameras **1302**, **1304**, **1306** are arranged such that vantage points **1308**, **1310**, **1312** lie in a single line **1314** in 3D space. Two-dimensional slices can be defined as described above, except that all three vantage points **1308**, **1310**, **1312** are included in each slice. The optical axes of cameras **1302**, **1304**, **1306** can be but need not be aligned, as long as the locations of vantage points **1308**, **1310**, **1312** are known. With three cameras, six tangents to an object can be available in a single slice. FIG. **14** illustrates a cross-section **1402** of an object as seen from vantage points **1308**, **1310**, **1312**. Lines **1408**, **1410**, **1412**, **1414**, **1416**, **1418** are tangent lines to cross-section **1402** from vantage points **1308**, **1310**, **1312**, respectively.

For any slice with five or more tangents, the parameters of an ellipse are fully determined, and a variety of techniques can be used to fit an elliptical cross-section to the tangent lines. FIG. **15** illustrates one technique, relying on the “centerline” concept illustrated above in FIG. **9**. From a first set of four tangents **1502**, **1504**, **1506**, **1508** associated with a first pair of vantage points, a first intersection region **1510** and corresponding centerline **1512** can be determined. From a second set of four tangents **1504**, **1506**, **1514**, **1516** associated with a second pair of vantage points, a second intersection region **1518** and corresponding centerline **1520** can be determined. The ellipse of interest **1522** should be inscribed in both intersection regions. The center of ellipse **1522** is therefore the intersection point **1524** of centerlines **1512** and **1520**. In this example, one of the vantage points (and the corresponding two tangents **1504**, **1506**) are used for both sets of tangents. Given more than three vantage points, the two sets of tangents could be disjoint if desired.

Where more than five tangent points (or other points on the object’s surface) are available, the elliptical cross-section is mathematically overdetermined. The extra information can be used to refine the elliptical parameters, e.g., using

statistical criteria for a best fit. In other embodiments, the extra information can be used to determine an ellipse for every combination of five tangents, then combine the elliptical contours in a piecewise fashion. Alternatively, the extra information can be used to weaken the assumption that the cross-section is an ellipse and allow for a more detailed contour. For example, a cubic closed curve can be fit to five or more tangents.

In some embodiments, data from three or more vantage points is used where available, and four-tangent techniques (e.g., as described above) can be used for areas that are within the field of view of only two of the vantage points, thereby expanding the spatial range of a motion-capture system.

While thus far the invention has been described with respect to specific embodiments, one skilled in the art will recognize that numerous modifications are possible. The techniques described above can be used to reconstruct objects from as few as four tangent lines in a slice, where the tangent lines are defined between edges of a projection of the object onto a plane and two different vantage points. Thus, for purposes of the analysis techniques described herein, the edges of an object in an image are of primary significance. Any image or imaging system that supports determining locations of edges of an object in an image plane can therefore be used to obtain data for the analysis described herein.

For instance, in embodiments described above, the object is projected onto an image plane using two different cameras to provide the two different vantage points, and the edge points are defined in the image plane of each camera. However, those skilled in the art with access to the present disclosure will appreciate that it may be possible to use a single camera to capture motion and/or determine the shape and position of the object in 3D space.

Additionally, those skilled in the art with access to the present disclosure will appreciate that cameras are not the only tool capable of projecting an object onto an imaging surface. For example, a light source can create a shadow of an object on a target surface, and the shadow—captured as an image of the target surface—can provide a projection of the object that suffices for detecting edges and defining tangent lines. The light source can produce light in any visible or non-visible portion of the electromagnetic spectrum. Any frequency (or range of frequencies) can be used, provided that the object of interest is opaque to such frequencies while the ambient environment in which the object moves is not. The light sources used should be bright enough to cast distinct shadows on the target surface. Point-like light sources provide sharper edges than diffuse light sources, but any type of light source can be used.

In one such embodiment, a single camera is used to capture images of shadows cast by multiple light sources. FIG. **16** illustrates a system **1600** for capturing shadows of an object according to an embodiment of the present invention. Light sources **1602** and **1604** illuminate an object **1606**, casting shadows **1608**, **1610** onto a front side **1612** of a surface **1614**. Surface **1614** can be translucent so that the shadows are also visible on its back side **1616**. A camera **1618** can be oriented toward back side **1616** as shown and can capture images of shadows **1608**, **1610**. With this arrangement, object **1606** does not occlude the shadows captured by camera **1618**. Light sources **1602** and **1604** define two vantage points, from which tangent lines **1620**, **1622**, **1624**, **1626** can be determined based on the edges of shadows **1608**, **1610**. These four tangents can be analyzed using techniques described above.

In an embodiment such as system **1600** of FIG. **16**, shadows created by different light sources may partially overlap, depending on where the object is placed relative to the light source. In such a case, an image may have shadows with penumbra regions (where only one light source is contributing to the shadow) and an umbra region (where the shadows from both light sources overlap). Detecting edges can include detecting the transition from penumbra to umbra region (or vice versa) and inferring a shadow edge at that location. Since an umbra region will be darker than a penumbra region; contrast-based analysis can be used to detect these transitions.

Certain physical or object configurations may present ambiguities that are resolved in accordance with various embodiments we as now discussed. Referring to FIG. **17**, when two objects **1708**, **1710** are present, the camera **1720** may detect four shadows **1712**, **1714**, **1716**, **1718** and the tangent lines may create four intersection regions **1722**, **1724**, **1726**, **1728** that all lie within the shadow regions **1730**, **1732**, **1734**, **1736**. Because it is difficult to determine, from a single slice of the shadow image, which of these intersection regions contain portions of the object, an analysis of whether the intersection regions **1722**, **1724**, **1726**, **1728** are occupied by the objects may be ambiguous. For example, shadows **1712**, **1714**, **1716**, **1718** that are generated when intersection regions **1722** and **1726** are occupied are the same as those generated when regions **1724** and **1728** are occupied, or when all four intersection regions **1722**, **1724**, **1726**, **1728** are occupied. In one embodiment, correlations across slices are used to resolve the ambiguity in interpreting the intersection regions (or “visual hulls”) **1722**, **1724**, **1726**, **1728**.

In various embodiments, referring to FIG. **18**, a system **1800** incorporates a large number of light sources (i.e., more than two light sources) to resolve the ambiguity of the intersection regions when there are multiple objects casting shadows. For example, the system **1800** includes three light sources **1802**, **1804**, **1806** to cast light onto a translucent surface **1810** and a camera **1812** positioned on the opposite side of surface **1810** to avoid occluding the shadows cast by an object **1814**. As shown in FIG. **18**, because utilization of three light sources provides five or more tangents for one or more objects **1814** in a slice, the ellipse-fitting techniques described above may be used to determine the cross-sections of the objects. A collection of the cross-sections of the objects in 2D slices may then determine the locations and/or movement of the objects.

If multiple objects, however, are located in close proximity (e.g., the fingers of a hand), utilization of additional light sources may reduce the sizes of the various intersection regions as well as increase the total number of intersection regions. If the number of light sources is much greater than the number of the proximal objects, the intersection regions may be too small to be analyzed based on a known or assumed size scale of the object. Additionally, the increased number of intersection regions may result in more ambiguity in distinguishing intersection regions that contain objects from intersection regions that do not contain objects (i.e., “blind spots”). In various embodiments, whether an intersection region contains an object is determined based on the properties of a collection of intersection points therein. As described in greater detail below, an intersection point is defined by at least two shadow lines, each connecting a shadow point of the shadow and a light source. If the intersection points in an intersection region satisfy certain criteria, the intersection region is considered to have the

objects therein. A collection of the intersection regions may then be utilized to determine the shape and movement of the objects.

Referring to FIG. **19**, a collection of the intersection regions (a visual hull) **1930** is defined by a virtual rubber band **1932** stretched around multiple intersection regions **1931** (or “convex hulls”); each intersection region **1931** is defined by a smallest set of intersection points **1934**. When there are multiple intersection regions **1931**, distinguishing each intersection region **1931** from a collection of intersection points **1934** may be difficult. In some embodiments, referring to FIG. **20**, a simple visual hull is first constructed by a setup of two lights **2002**, **2004** (here denoted L_n , with $n=\{1, 2\}$ to permit further generalization to greater numbers of light sources, shadows, shadow regions, points, and visual hulls), each casting one shadow **2006A**, **2006B**, respectively. The light source L_1 and shadow **2006A** define a shadow region, $R_{1,1}$; similarly, light source L_2 and the shadow **2006B** define a shadow region, $R_{2,1}$; in general, the shadow region is denoted as, $R_{u,v}$, where u is the number of the corresponding light source and v is a number that denotes a left to right ordering in a scene within the set of all shadow regions from the light source u . Boundaries of the shadows (or “shadow points”) lie on an x axis and are denoted by $S_{u,v}$. The shadow points and each light source may then create shadow lines **2008**, **2010**, **2012**, **2014**; the shadow lines are referenced by the two connecting points; for example, $\overline{L_1 S_{1,2}}$, (abbreviated $\overline{S_{1,2}}$, where the first subscript also refers to the light number). The convex hull **2030** (or visual hull here since there is only one intersection region **2028**) may then be defined by the four intersection points **2034** in the example of FIG. **20**. In one embodiment, the intersection points **2034** are determined based on the intersections of every pair of shadow lines, for example, $\overline{S_{1,1}}$, $\overline{S_{1,2}}$, $\overline{S_{2,1}}$, and $\overline{S_{2,2}}$. Because pairs of shadow lines from the same light source L_1 or L_2 do not intersect, the intersection of the pairs of lines from the same light source may then be neglected.

When there are more than two light sources, determining all shadow line intersections no longer suffices to find intersection points that lie on the intersection region **2028**. Referring to FIG. **21A**, utilization of three light sources **2102**, **2104**, **2106**, may result in “true” intersection points **2134A**, **2134B**, **2134C**, **2134D**, **2134E**, **2134F** that form the intersection region **2128** occupied by the object **2108** and “false” intersection points **2135A**, **2135B**, **2135C**, **2135D**, **2135E**, **2135F** that clearly do not form the intersection region **2128**. For example, the false intersection point **2135E** created by a left shadow line **2124** of the shadow region **2118A** and a right shadow line **2126** of the shadow region **2118B** is a false intersection point because it does not lie inside the intersection region **2128**. Because the intersection region **2128** is an intersection of the shadow regions **2118A**, **2118B**, **2118C** created by the object **2108** and the light sources **2102**, **2104**, **2106**, the number of shadow regions in which each “true” intersection point lies is equal to the number of the light sources (i.e., three in FIG. **21A**). “False” intersection points, by contrast, lie outside the intersection region **2128** even though they may lie inside an intersection region that includes fewer number of shadow regions compared to the total number of light sources. In one embodiment, whether an intersection point is “true” or “false” is determined based on the number of shadow regions included in the intersection region in which the intersection point lies. For example, in the presence of three light sources in FIG. **21A**, the intersection point **2134A** is a true intersection point because it lies inside three shadow regions **2118A**, **2118B**,

2118C; whereas the intersection point **2135F** is a false intersection point because it lies inside only two shadow regions **2118B**, **2118C**.

Because the intersection regions are defined by a collection of intersection points, excessive computational effort may be required to determine whether an intersection point is contained by a correct number of regions (i.e., the number of the light sources). In some embodiments, this computational complexity is reduced by assuming that each intersection point is not “false” and then determining whether the results are consistent with all of the shadows captured by the camera. These configurations project each intersection point $I=[I_x, I_y]$ onto the x axis through a ray directed from each light source $L=[L_x, L_y]$ that is not involved in the original intersection determination. The solutions for these projections are given by

$$\left[\frac{L_y P_x - L_x P_y}{L_y - P_y}, 0 \right].$$

If a projection point on the x axis lies inside a shadow region from the testing light source, it is likely that the projected intersection point is a true intersection point. For example, referring to FIG. **21B**, the intersection point **2135E** is determined by the shadow lines **2124** and **2126** created by the light sources **2102** and **2106**. Projecting the intersection point **2135E** onto the x axis using the light source **2106**, which is not involved in determining the intersection point **2135E**, creates a projection point P_3 . Because the projection point P_3 does not lie inside the shadow region **2118C** created by the light source **2106** and the object **2108**, the intersection point **2135E** is considered to be a false intersection point; whereas the intersection point **2134E** is a true intersection point because the projection point P_1 thereof lies within the shadow region **2118A**. As a result, for every possible intersection point, an additional $N-2$ projections must be determined for the $N-2$ light sources that are not involved in determining the position of the intersection point (where N is the total number of light sources in the system). In other words, a projection check must be made for every light source other than the original two that are used to determine the tested intersection point. Because determining whether the intersection point is true or false based on the projections is simpler than checking the number of shadow regions in which each intersection point lies, the required computational requirements and processing time may be significantly reduced.

If, however, a large quantity of light sources is utilized in the system, the overall process may still be time-consuming. In various embodiments, the light sources $L_1, L_2,$ and L_3 are placed in a line parallel to the x axis, the location of the projection points can then be determined without finding the location of the intersection point for every pair of shadow lines. Accordingly, whether the intersection point **2134** is a true or false point may be determined without finding or locating the position thereof; this further reduces the processing time. For example, with reference to FIG. **21C**, assuming that the shadow points S_1 and S_3 are either known or have been determined, whether the intersection point I of the shadow lines $\overline{L_1 S_3}$ and $\overline{L_3 S_1}$ is true or false may be determined by the position of the projection point P_2 created by the light source L_2 . The distance between the projection point P_2 created by the light source L_2 and the shadow point S_1 is given as:

$$\overline{S_1 P_2} = \overline{S_1 S_3} \left[\frac{L_2 L_3}{L_1 L_3} \right] \quad (\text{Eq. 1})$$

Thus, the location of any one of the projection points projected from the intersection point, I , and light sources may be determined based on the other two shadow points and the distance ratios associated with light sources L_1, L_2 and L_3 . Because the ratio of the distances between the light sources is predetermined, the complexity in determining the projection point P_2 is reduced to little more than calculating distances between the shadow points and multiplying these distances by the predetermined ratio. If the distance between the projection point P_2 and the shadow point S_1 is larger than the size of the shadow, i.e., $\overline{S_1 S_3}$, that is captured by the camera, the intersection point, I , is a false point. If, on the other hand, the distance between the projection points S_2 and S_1 is smaller than the size of the shadow, the intersection point I is likely a true point. Although the location of the intersection point, I , may still be determined based on the shadow lines $\overline{L_1 S_3}$ and $\overline{L_3 S_1}$, this determination may be skipped during the process. Accordingly, by aligning the light sources in a line, the false intersection points can be quickly determined without performing the complex computations, thereby saving a large amount of processing time and power.

More generally, when there are N light sources, each denoted as L_i ($1 \leq i \leq N$), arranged on a line parallel to the x axis and each light source possesses a set of S_i shadow points (where i is the light number), a total number of M intersection calculations for all possible intersection pairs is given as:

$$M = \sum_{i=1}^{N-1} S_i \left(\sum_{k=i+1}^N S_k \right). \quad (\text{Eq. 2})$$

For example, if there are N light sources, each casting n shadows, the total number of intersection calculations M may then be given as

$$M = n^2 N(N-1). \quad (\text{Eq. 3})$$

Because each of these intersection calculations involves multiple operations (e.g., addition and multiplication), the total number of operations, T_o , may be given as

$$T_o = 2n^2 N(2N+1)(N-1). \quad (\text{Eq. 4})$$

For example, a total number of operations $T_o = 2(1)^2 3(2 \cdot 3 + 1)(3-1) = 84$ is required to determine the simplest visual hull **2028** shown in FIG. **20**. In one embodiment, there are, for example, 12 light sources (i.e., $N=12$), each casting 10 shadows (i.e., $n=10$); the number of required intersection calculations for this scenario is $M=13,200$, setting the number of total operations to be $T_o=660,000$. Again, this requires a significant amount of processing time. In some embodiments, the distance ratios between light sources are predetermined, and as a result, only one operation (i.e., multiplication) is needed to determine which pairs of shadow points produce true intersection points; this reduces the number of total operations to 13,200.

The computational load required to find the visual hull depends on the quantity of the true intersection points, which may not be uniquely determined by the number of shadows. Suppose, for example, that there are N light sources and each

23

object is a circle that casts one shadow per light; this results in N intersection regions (or $6N$ intersection points) per object. Because there are n objects, the resulting number of intersection points that need to be checked is $6Nn^2$ (i.e., roughly 6,000 for 10 objects cast by 12 light sources). As described above, the number of operations required for the projection check is 13,200; accordingly, a total number of operations 19,200 is necessary to determine the visual hull formed by the true intersection points. This is a 34-fold improvement in determining the solution for a single 2D scene compared to the previous estimate of 660,000 operations. The number of reduced operations may be given as:

$$T_p = n^2 N(N-1) + 6Nn^2 \quad (\text{Eq. 5})$$

The ratio of the required operations to the reduced operations may then be expressed as:

$$\frac{T_o}{T_p} = \frac{2n(2N+1)(N-1)}{nN-n+6n} \quad (\text{Eq. 6})$$

Based on Eq. 6, if the light sources lie along a line or lines parallel to the x axis, the improvement is around an order of magnitude for a small number of lights, whereas the improvement is nearly two orders of magnitude for a larger number of lights.

If the objects are reconstructed in 3D space and/or a fast real-time refresh rate (e.g., 30 frames per second) is used by the camera, the computational load may be increased by several orders of magnitude due to the additional complexity. In some embodiments, the visual hull is split into a number of small intersection regions that can generate at least a portion of the shadows in the scene; the smallest cardinality of the set of small intersection regions is defined as a “minimal solution.” In one embodiment, the number of the small intersection regions in the minimal solution is equal to the largest number of shadows generated by any single light source. The computational complexity of obtaining the visual hull may significantly be reduced by determining each of the small visual hulls prior to assembling them together into the visual hull.

Referring again to FIG. 19, the intersection points **1934** may form an amorphous cloud that does not imply particular regions. In various embodiments, this cloud is first split into a number of sets, each set determining an associated convex hull **1931**. As further described below, in one embodiment, a measure is utilized to determine the intersection region to which each intersection point belongs. The determined intersection region may then be assembled into an exact visual hull. In one implementation, the trivial case of a visual hull containing only one intersection region is ignored. In some embodiments, every intersection region ρ is assigned an N -dimensional subscript, where N is the number of light sources in the scene under consideration. The n th entry for this subscript of the intersection region ρ is defined as the value v of the u th subscript (where $u=n$) for each shadow region $R_{u,v}$ of which the intersection region is a subset; every intersection region thus has a unique identifier for grouping the intersection points, as shown in FIG. 22. Because two of the subscript entries for an intersection point can be determined directly from the two shadow lines, the resulting intersection point thereof is in the two shadow regions in which the shadow lines are located. For the rest of the entries, the locations of the projections of the intersection points may be recorded during the determination of true and

24

false intersection points. Complete knowledge of the particular intersection regions for each intersection point may thus be determined.

Once the distinct intersection regions have been determined, the smallest subset of intersection regions that can generate all of the final shadows may then be found. FIG. 22 depicts intersection regions $\rho_{1,1,1}$, $\rho_{2,2,2}$, $\rho_{3,3,3}$ resulting from casting light from three light sources onto three objects **2238A**, **2238B**, and **2238C**. Because the greatest number of shadows cast by any particular light source in this case is three and the number of intersection regions in the minimal solution is equal to the largest number of shadows generated by any single light source, every group that includes three intersection regions in the scene may be tested. If a group generates a complete set of shadows captured by the camera, this group is the minimum solution. The number of trios to test is equal to the binomial coefficient

$$C_u^j = \binom{j}{u} = \frac{j!}{u!(j-u)!},$$

where j is the total number of intersection regions. For example, there are $C_3^{13}=286$ combinations in FIG. 22. The likelihood that a trio having larger intersection regions can generate all of the captured shadows is higher than for a trio having smaller intersection regions; additionally, larger intersection regions usually have a greater number of intersection points. In some embodiments, the number of trios tested is reduced by setting a criterion value U equal to the greatest number of intersection points in any intersection region. For example, only regions or combinations of regions having a number of intersection points exceeding the criteria number U are checked. If there are no solutions, U may be reset to $U-1$ and the process may be repeated. For example, by setting $U=6$, there are only five regions, $\rho_{1,1,1}$, $\rho_{2,2,2}$, $\rho_{3,3,3}$, $\rho_{1,2,3}$, $\rho_{3,2,1}$, having six intersection points need to be checked. The region subscripts may be presented as a single number vector, e.g., $\rho_{1,1,1}=[1\ 1\ 1]$; and the combination of $\rho_{3,2,1}$, $\rho_{1,1,1}$, and $\rho_{2,2,2}$ may be written as a matrix,

$$\text{e.g., } \begin{bmatrix} 3 & 2 & 1 \\ 1 & 1 & 1 \\ 2 & 2 & 2 \end{bmatrix}.$$

There are nine additional combinations exist in FIG. 22:

$$\begin{bmatrix} 3 & 2 & 1 \\ 1 & 1 & 1 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 3 & 2 & 1 \\ 1 & 1 & 1 \\ 1 & 2 & 3 \end{bmatrix}, \begin{bmatrix} 3 & 2 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 3 & 2 & 1 \\ 2 & 2 & 2 \\ 1 & 2 & 3 \end{bmatrix},$$

$$\begin{bmatrix} 3 & 2 & 1 \\ 3 & 3 & 3 \\ 1 & 2 & 3 \end{bmatrix}, \begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 1 & 2 & 3 \end{bmatrix}, \begin{bmatrix} 1 & 1 & 1 \\ 3 & 3 & 3 \\ 1 & 2 & 3 \end{bmatrix}, \begin{bmatrix} 2 & 2 & 2 \\ 3 & 3 & 3 \\ 1 & 2 & 3 \end{bmatrix}.$$

Because the minimal solution alone can generate all of the shadows in the scene, each column of the minimal solution matrix has the numbers 1, 2, 3 (in no particular order). Accordingly, the 6th combination above having $\rho_{1,1,1}$, $\rho_{2,2,2}$, and $\rho_{3,3,3}$ is the minimal solution. This approach finds the minimal solution by determining whether there is at least one intersection region in every shadow region. This

approach, however, may be time-consuming upon reducing U to 3, as the regions that have three intersection point require a more complicated check. In some embodiments, the three-point regions are neglected since they are almost never a part of a minimal solution.

In some embodiments, the 3D scenes are decomposed into a number of 2D scenes that can be quickly solved by the approaches as described above to determine the 3D shape of the objects. Because many of these 2D scenes share the same properties (e.g., the shape or location of the intersection regions), the solution of one 2D slice may be used to determine the solution of the next 2D slice; this may improve the computational efficiency.

The light sources may be positioned to lie in a plane. In one embodiment, a number of “bar” light sources are combined with “point” light sources to accomplish more complex lighting arrangements. In another embodiment, multiple light arrays lying in a plane are combined with multiple outlier-resistant least squares fits to effectively reduce the computational complexity by incorporating previously known geometric parameters of the target object.

Referring to FIG. 23, in some embodiments, a shadow 2312 is cast on a translucent or imaginary surface 2340 such that the shadow 2312 can be viewed and captured by a camera 2338. The camera 2338 may take pictures with a number of light sensors (not shown in FIG. 23) arranged in a rectangular grid. In the camera 2338, there may be three such grids interlaced at small distances that essentially lie directly on top of each other. Each grid has a different color filter on all of its light sensors (e.g., red, green, or blue). Together, these sensors output three images, each comprising $A \times B$ light brightness values in the form of a matrix of pixels. The three color images together form an $A \times B \times 3$ RGB image matrix. The image matrices may have their own coordinate system, which is defined by the set of matrix cell subscripts for a given pixel. For example, indices $(x, y, z) = (0, 0, 0)$ may be defined and start in an upper left corner 2339 of the image. In one embodiment, the matrix of $z=1$ represents the red color image and $z=2$ and $z=3$ are the green and blue images, respectively. In one implementation, an “image row” is defined as all pixel values for a given constant coordinate value of y and an “image column” is defined as all pixel values for a given constant coordinate value of x .

Referring to FIG. 24A, a color image 2450 is split into images 2452, 2454, 2456 of three primary colors (i.e., red, green, and blue, respectively) by decomposing an $A \times B \times 3$ full color matrix in a memory into 3 different $A \times B$ matrices, one for each z value between 1 and 3. Pixels in each image 2452, 2454, 2456 are then compared to a brightness threshold value to determine which pixels represent shadow and which represent background to thereby generate three shadow images 2458, 2460, 2462, respectively. The brightness threshold value may be determined by a number of statistical techniques. For example, in some embodiments, a mean pixel brightness is determined for each image and the threshold is set by subtracting three times the standard deviation of the brightness of the same pixels in the same image. Edges of the shadow images 2458, 2460, 2462 may then be determined to generate shadow point images 2464, 2466, 2468, respectively, using a conventional edge-determining technique. For example, the edge of each shadow image may be determined by subtracting the shadow image itself from an offset image created by offsetting a single pixel on the left (or right, top and/or bottom) side thereof. The 2D approaches described above may be applied to each of the shadow point images 2464, 2466, 2468 to determine

the locations and colors of the objects. In some embodiments, shadow points in images 2464, 2466, 2468 are combined into a single $A \times B \times 3$ color matrix or image 2470. Application of the 2D approaches described above to the combined shadow point image 2470 can then reconstruct an image of the object 2472 (e.g., a hand, as shown in FIG. 24B). Reconstructing an object (e.g., a hand) from shadows using various embodiments in the present invention may then be as simple as reconstructing a number of 2D ellipses. For example, fingers may be approximated by circles in 2D slices, and a palm may be approximated as an ellipse. This reconstruction is thereby converted into a practical number of simpler, more efficient reconstructions; the reconstructed 2D slices are then reassembled into the final 3D solution. These efficient reconstructions may be computed using a single processor or multiple processors operating in parallel to reduce the processing time.

In various embodiments, referring again to FIG. 23, the image coordinate system (i.e., the “imaging grid” 2342) is imposed on the surface 2340 to form a standard Cartesian coordinate system thereon such that the shadow 2312 can be easily defined. For example, each pixel (or light measurement value) in an image may be defined based on the coordinate integers x and y . In some embodiments, the camera 2338 is perpendicular to the surface 2340 on which shadows 2312 are cast and a point on a surface in the image grid is defined based on its coordinate inside an image taken by the camera 2338. In one embodiment, all light sources lie along a line or lines on a plane perpendicular to one of the axes to reduce the computational complexity. In various embodiments, the z axis of the coordinate system uses the same distance units and is perpendicular to the x and y axes of image grid 2342 to capture the 3D images of the shadows. For example, the light sources may be placed parallel to the x or y axis and perpendicular to the z -axis; a 3D captured shadow structure in the image coordinate system may be split into multiple 2D image slices, where each slice is a plane defined by a given row on the imaging grid and the line of light sources. The 2D slices may or may not share similar shapes. For example, the 2D intersection region of a 3D intersection region for a spherical object is very similar, i.e., a circle; whereas the 2D intersection region of a 3D intersection region for a cone shape varies across the positions of the 2D slices.

As described above, the shape of multiple objects may be discerned by determining a minimal solution of each 2D slice obtained from the 3D shadow. Since two slices next to each other are typically very similar, multiple slices often have the same minimal solution. In various embodiments, when two nearby slices have the same number of intersection regions, different combinations of the intersection regions are bypassed between the slices and the combination that works for a previous slice is reused on the next slice. If the old combination works for the new slice, this solution becomes a new minimal solution for the new slice and any further combinatorial checks are not performed. The reuse of old combinations thus greatly reduces computational time and complexity for complicated scenes. Although various embodiments described above are related to determining the shapes and positions of objects in 3D space using cross-sections obtained from the shadows cast by the objects, one of ordinary skill in the art will understand that cross-sections obtained utilizing different approaches, e.g., reflections from the objects, are within the scope of the current invention.

In still other embodiments, a single camera can be used to capture an image of both the object and one or more shadows cast by the object from one or more light sources

at known positions. Such a system is illustrated in FIGS. 25A and 25B. FIG. 25A illustrates a system 2500 for capturing a single image of an object 2502 and its shadow 2504 on a surface 2506 according to an embodiment of the present invention. System 2500 includes a camera 2508 and a light source 2512 at a known position relative to camera 2508. Camera 2508 is positioned such that object of interest 2502 and surface 2506 are both within its field of view. Light source 2512 is positioned so that an object 2502 in the field of view of camera 2508 will cast a shadow onto surface 2506. FIG. 25B illustrates an image 2520 captured by camera 2508. Image 2520 includes an image 2522 of object 2502 and an image 2524 of shadow 2504. In some embodiments, in addition to creating shadow 2504, light source 2512 brightly illuminates object 2502. Thus, image 2520 will include brighter-than-average pixels 2522, which can be associated with illuminated object 2502, and darker-than-average pixels 2524, which can be associated with shadow 2504.

In some embodiments, part of the shadow edge may be occluded by the object. Where 30 the object can be reconstructed with fewer than four tangents (e.g., using circular cross-sections), such occlusion is not a problem. In some embodiments, occlusion can be minimized or eliminated by placing the light source so that the shadow is projected in a different direction and using a camera with a wide field of view to capture both the object and the unoccluded shadow. For example, in FIG. 25A, the light source could be placed at position 2512'.

In other embodiments, multiple light sources can be used to provide additional visible edge points that can be used to define tangents. For example, FIG. 25C illustrates a system 2530 with a camera 2532 and two light sources 2534, 2536, one on either side of camera 2532. Light source 2534 casts a shadow 2538, and light source 2536 casts a shadow 2540. In an image captured by camera 2532, object 2502 may partially occlude each of shadows 2538 and 2540. However, edge 2542 of shadow 2538 and edge 2544 of shadow 2540 can both be detected, as can the edges of object 2502. These points provide four tangents to the object, two from the vantage point of camera 2532 and one each from the vantage point of light sources 2534 and 2536.

As yet another example, multiple images of an object from different vantage points can be generated within an optical system, e.g., using beamsplitters and mirrors. FIG. 26 illustrates an image-capture setup 2600 for a motion capture system according to another embodiment of the present invention. A fully reflective front-surface mirror 2602 is provided as a "ground plane." A beamsplitter 2604 (e.g., a 50/50 or 70/30 beamsplitter) is placed in front of mirror 2602 at about a 20-degree angle to the ground plane. A camera 2606 is oriented toward beamsplitter 2604. Due to the multiple reflections from different light paths, the image captured by the camera can include ghost silhouettes of the object from multiple perspectives. This is illustrated using representative rays. Rays 2606a, 2606b indicate the field of view of a first virtual camera 2608; rays 2610a, 2610b indicate a second virtual camera 2612; and rays 2614a, 2614b indicate a third virtual camera 2616. Each virtual camera 2608, 2612, 2616 defines a vantage point for the purpose of projecting tangent lines to an object 2618.

Another embodiment uses a screen with pinholes arranged in front of a single camera. FIG. 27 illustrates an image capture setup 2700 using pinholes according to an embodiment of the present invention. A camera sensor 2702 is oriented toward an opaque screen 2704 in which are formed two pinholes 2706, 2708. An object of interest 2710

is located in the space on the opposite side of screen 2704 from camera sensor 2702. Pinholes 2706, 2708 can act as lenses, providing two effective vantage points for images of object 2710. A single camera sensor 2702 can capture images from both vantage points.

More generally, any number of images of the object and/or shadows cast by the object can be used to provide image data for analysis using techniques described herein, as long as different images or shadows can be ascribed to different (known) vantage points. Those skilled in the art will appreciate that any combination of cameras, beamsplitters, pinholes, and other optical devices can be used to capture images of an object and/or shadows cast by the object due to a light source at a known position.

Further, while the embodiments described above use light as the medium to detect edges of an object, other media can be used. For example, many objects cast a "sonic" shadow, either blocking or altering sound waves that impinge upon them. Such sonic shadows can also be used to locate edges of an object. (The sound waves need not be audible to humans; for example, ultrasound can be used.) The term "shadow" is herein used broadly to connote light or sonic shadows or other occlusion of a disturbance by an object, and the term "light" means electromagnetic radiation of any suitable wavelength(s) or wavelength range.

As described above, the general equation of an ellipse includes five parameters; where only four tangents are available, the ellipse is underdetermined, and the analysis proceeds by assuming a value for one of the five parameters. Which parameter is assumed is a matter of design choice, and the optimum choice may depend on the type of object being modeled. It has been found that in the case where the object is a human hand, assuming a value for the semimajor axis is effective. For other types of objects, other parameters may be preferred.

Further, while some embodiments described herein use ellipses to model the cross-sections, other shapes can be substituted. For instance, like an ellipse, a rectangle can be characterized by five parameters, and the techniques described above can be applied to generate rectangular cross-sections in some or all slices. More generally, any simple closed curve can be fit to a set of tangents in a slice. (The term "simple closed curve" is used in its mathematical sense throughout this disclosure and refers generally to a closed curve that does not intersect itself with no limitations implied as to other properties of the shape, such as the number of straight edge sections and/or vertices, which can be zero or more as desired.) The number of free parameters can be limited based on the number of available tangents. In another embodiment, a closed intersection region (a region fully bounded by tangent lines) can be used as the cross-section, without fitting a curve to the region. While this may be less accurate than ellipses or other curves, e.g., it can be useful in situations where high accuracy is not desired. For example, in the case of capturing motion of a hand, if the motion of the fingertips is of primary interest, cross-sections corresponding to the palm of the hand can be modeled as the intersection regions while fingers are modeled by fitting ellipses to the intersection regions.

In some embodiments, cross-slice correlations can be used to model all or part of the object using 3D surfaces, such as ellipsoids or other quadratic surfaces. For example, elliptical (or other) cross-sections from several adjacent slices can be used to define an ellipsoidal object that best fits the ellipses. Alternatively, ellipsoids or other surfaces can be determined directly from tangent lines in multiple slices from the same set of images. The general equation of an

ellipsoid includes nine free parameters; using nine (or more) tangents from two or three (or more) slices, an ellipsoid can be fit to the tangents. Ellipsoids can be useful, e.g., for refining a model of fingertip (or thumb) position; the ellipsoid can roughly correspond to the last segment at the tip of a finger (or thumb). In other embodiments, each segment of a finger can be modeled as an ellipsoid. Other quadratic surfaces, such as hyperboloids or cylinders, can also be used to model an object or a portion thereof.

In some embodiments, an object can be reconstructed without tangent lines. For example, given a sufficiently sensitive time-of-flight camera, it would be possible to directly detect the difference in distances between various points on the near surface of a finger (or other curved object). In this case, a number of points on the surface (not limited to edge points) can be determined directly from the time-of-flight data, and an ellipse (or other shape) can be fit to the points within a particular image slice. Time-of-flight data can also be combined with tangent-line information to provide a more detailed model of an object's shape.

Any type of object can be the subject of motion capture using these techniques, and various aspects of the implementation can be optimized for a particular object. For example, the type and positions of cameras and/or light sources can be optimized based on the size of the object whose motion is to be captured and/or the space in which motion is to be captured. As described above, in some embodiments, an object type can be determined based on the 3D model, and the determined object type can be used to add type-based constraints in subsequent phases of the analysis. In other embodiments, the motion capture algorithm can be optimized for a particular type of object, and assumptions or constraints pertaining to that object type (e.g., constraints on the number and relative position of fingers and palm of a hand) can be built into the analysis algorithm. This can improve the quality of the reconstruction for objects of that type, although it may degrade performance if an unexpected object type is presented. Depending on implementation, this may be an acceptable design choice. For example, in a system for controlling a computer or other device based on recognition of hand gestures, there may not be value in accurately reconstructing the motion of any other type of object (e.g., if a cat walks through the field of view, it may be sufficient to determine that the moving object is not a hand).

Analysis techniques in accordance with embodiments of the present invention can be implemented as algorithms in any suitable computer language and executed on programmable processors. Alternatively, some or all of the algorithms can be implemented in fixed-function logic circuits, and such circuits can be designed and fabricated using conventional or other tools.

Computer programs incorporating various features of the present invention may be encoded on various computer readable storage media; suitable media include magnetic disk or tape, optical storage media such as compact disk (CD) or DVD (digital versatile disk), flash memory, and any other non-transitory medium capable of holding data in a computer-readable form. Computer readable storage media encoded with the program code may be packaged with a compatible device or provided separately from other devices. In addition program code may be encoded and transmitted via wired optical, and/or wireless networks conforming to a variety of protocols, including the Internet, thereby allowing distribution, e.g., via Internet download.

The motion capture methods and systems described herein can be used in a variety of applications. For example,

the motion of a hand can be captured and used to control a computer system or video game console or other equipment based on recognizing gestures made by the hand. Full-body motion can be captured and used for similar purposes. In such embodiments, the analysis and reconstruction advantageously occurs in approximately real-time (e.g., times comparable to human reaction times), so that the user experiences a natural interaction with the equipment. In other applications, motion capture can be used for digital rendering that is not done in real time, e.g., for computer-animated movies or the like; in such cases, the analysis can take as long as desired. In intermediate cases, detected object shapes and motions can be mapped to a physical model whose complexity is suited to the application—i.e., which provides a desired processing speed given available computational resources. For example, the model may represent generic hands at a computationally tractable level of detail, or may incorporate the user's own hands by initial image capture thereof followed by texture mapping onto a generic hand model. The physical model is manipulated (“morphed”) according to the detected object orientation and motion.

Thus, although the invention has been described with respect to specific embodiments, it will be appreciated that the invention is intended to cover all modifications and equivalents within the scope of the following claims.

In various embodiments, the system and method for capturing 3D motion of an object as described herein may be integrated with other applications, such as a head-mounted device or a mobile device. Referring to FIG. 28A, a head-mounted device **2802** typically includes an optical assembly that displays a surrounding environment or a virtual environment to the user; incorporation of the motion-capture system **2804** in the head-mounted device **2802** allows the user to interactively control the displayed environment. For example, the virtual environment may include virtual objects that can be manipulated by the user's hand gestures, which are tracked by the motion-capture system **2804**. In one embodiment, the motion-capture system **2804** integrated with the head-mounted device **2802** detects a position and shape of user's hand and projects it on the display of the head-mounted device **2802** such that the user can see her gestures and interactively control the objects in the virtual environment. This may be applied in, for example, gaming or internet browsing.

Referring to FIG. 28B, in some embodiments, the motion-capture system **2804** is employed in a mobile device **2806** that communicates with other devices **2810**. For example, a television (TV) **2810** may include an input that connects to a receiver (e.g., a wireless receiver, a cable network or an antenna) to enable communication with the mobile device **2806**. The mobile device **2806** first uses the embedded motion-capture system **2804** to detect movement of the user's hands, and to remotely control the TV **2810** based on the detected hand movement. For example, the user may perform a sliding hand gesture, in response to which the mobile device **2806** transmits a signal to the TV **2810**; the signal may be a raw trajectory that circuitry associated with the TV interprets, or the mobile device **2806** may include programming that interprets the gesture and sends a signal (e.g., a code corresponding to “sliding hand”) to the TV **2810**. Either way, the TV **2810** responds by activating and displaying a control panel on the TV screen, and the user makes selections thereon using further gestures. The user may, for example, move his hand in an “up” or “down” direction, which the motion-capture system **2804** embedded in the mobile device **2806** converts to a signal that is

31

transmitted to the TV **2810**, and in response, the user's selection of a channel of interest from the control panel is accepted. Additionally, the TV **2810** may connect to a source of video games (e.g., video game console or web-based video game). The mobile device **2806** may capture the user's hand motion and transmit it to the TV for display thereon such that the user can remotely interact with the virtual objects in the video game.

Referring to FIG. **28C**, in various embodiments, the motion-capture system **2804** is integrated with a security system **2812**. The security system **2812** may utilize the detected hand shape as well as hand jitter (detected as motion) in order to authenticate the user **2814**. For example, an authentication server **2816** may maintain a database of users and corresponding hand shapes and jitter patterns. When a user **2814** seeks access to a secure resource **2812**, the motion-capture system **2804** integrated with the resource **2812** (e.g., a computer) detects the user's hand shape and jitter pattern and then identifies the user **2814** by transmitting this data to the authentication server **2816**, which compares the detected data with the database record corresponding to the access-seeking user **2814**. If the user **2814** is authorized to access the secure resource **2812**, the server **2816** transmits an acknowledgment to the resource **2812**, which thereupon grants access. It should be stressed that the user **2814** may be authenticated to the secure system **2812** based on the shape of any part of a human body that may be detected and recognized using the motion-capture system **2804**.

The terms and expressions employed herein are used as terms and expressions of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding any equivalents of the features shown and described or portions thereof. In addition, having described certain embodiments of the invention, it will be apparent to those of ordinary skill in the art that other embodiments incorporating the concepts disclosed herein may be used without departing from the spirit and scope of the invention. Accordingly, the described embodiments are to be considered in all respects as only illustrative and not restrictive.

What is claimed is:

1. A system for recognizing gestures from a control object moving in three dimensional (3D) space, the system including:

one or more processors coupled to a memory, the memory loaded with computer instructions that, when executed by the one or more processors, implement actions including:

receiving a result of analyzing a gesture;

interpreting the result of analyzing a gesture as an instruction to perform an operation,

wherein the result of analyzing a gesture is obtained from another program, which is executed on a processor, to analyze differences in positions of fit closed curves fit to observed edges of a control object thereby tracking motion of the control object while making a gesture in a 3D space by repeatedly: obtaining captured images of a control object moving in 3D space captured from at least two geometrically distinct predetermined vantages; calculating observed edges of the control object from the captured images;

fitting closed curves to the observed edges of the control object as captured in the captured images by selecting a closed curve from a family of

32

similar closed curves that fit the observed edges of the control object as captured using an assumed parameter;

whenever the control object is a complex control object that includes a palm and multiple fingers, applying actions including obtaining captured images, calculating observed edges, and fitting closed curves to construct multiple fingers of control object appendages; and

fitting cross sections of a palm to observed edges of a palm as captured in the captured images.

2. The system of claim 1, wherein one or more fitted parameters of a first fitted closed curve are substituted for one or more of the observed edges and the assumed parameter when fitting an adjacent second closed curve.

3. The system of claim 1, wherein a first fitted closed curve is used to filter fits of additional closed curves.

4. The system of claim 1, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

repeatedly applying actions including obtaining captured images, calculating observed edges, and fitting closed curves actions of claim 1 over time; and

calculating motion of the control object over time based on differences between modeled locations of the control object.

5. The system of claim 3, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

repeatedly applying actions including obtaining captured images, calculating observed edges, fitting closed curves and using a first fitted closed curve to filter fits of additional closed curves actions of claim 3 over time; and

calculating motion of a complex control object over time based on differences between modeled locations of a complex control object.

6. The system of claim 1, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

determining and fitting a circle selected from among closed curves for a plurality of portions of the control object from the captured images, including:

calculating three co planar tangents to observed edges of the control object from the captured images; and fitting a circle to the control object using at least the three co planar tangents.

7. The system of claim 6, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

for a complex control object model that includes a palm and multiple fingers, applying the determining and fitting a circle actions of claim 6 to construct multiple fingers of control object appendages; and

fitting cross sections of a palm to observed edges of the palm as captured in the captured images.

8. The system of claim 6, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

repeatedly applying the determining and fitting a circle actions of claim 6 over time; and

calculating motion of the control object over time based on differences between modeled locations of the control object.

9. The system of claim 7, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

33

repeatedly applying the determining and fitting a circle and fitting cross sections actions of claim 7 over time; and

calculating motion of a complex control object over time based on differences between modeled locations of the complex control object.

10. A non-transitory computer readable medium storing a plurality of instructions for programming one or more processors, which instructions, when executed by one or more processors, implement actions including:

receiving a result of analyzing a gesture;

interpreting as an instruction the result of analyzing a gesture; wherein the result of analyzing a gesture is obtained from another program executing on a processor from analysis of differences in positions of fit closed curves fit to observed edges of a control object thereby tracking motion of the control object while making a gesture in a 3D space including repeatedly:

obtaining captured images of a control object moving in 3D space captured from at least two geometrically distinct predetermined vantages;

calculating observed edges of the control object from the captured images;

fitting closed curves to the observed edges of the control object as captured in the captured images by selecting a closed curve from a family of similar closed curves that fit the observed edges of the control object as captured using an assumed parameter; and

whenever the control object is a complex control object that includes a palm and multiple fingers, applying actions including obtaining captured images, calculating observed edges, and fitting closed curves actions to construct multiple fingers of control object appendages; and

fitting cross sections of a palm to observed edges of a palm as captured in the captured images.

11. The non-transitory computer readable medium of claim 10,

wherein one or more fitted parameters of a first fitted closed curve are substituted for one or more of the observed edges and the assumed parameter when fitting an adjacent second closed curve.

12. The non-transitory computer readable medium of claim 10, wherein a first fitted closed curve is used to filter fits of additional closed curves to contiguous cross-sections.

13. The non-transitory computer readable medium of claim 10, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

repeatedly applying actions including obtaining captured images, calculating observed edges, and fitting closed curves actions of claim 10 overtime; and

calculating motion of the control object over time based on differences between modeled locations of the control object.

14. The non-transitory computer readable medium of claim 12, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

repeatedly applying actions including obtaining captured images, calculating observed edges, fitting closed curves and using a first fitted closed curve to filter fits of additional closed curves actions of claim 12 overtime; and

calculating motion of a complex control object over time based on differences between modeled locations of a complex control object.

34

15. The non-transitory computer readable medium of claim 10, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

determining and fitting a circle selected from among closed curves in the family of similar closed curves for a plurality of portions of the control object from the captured images, including:

calculating three co-planar tangents to observed edges of the control object from the captured images; and

fitting a circle to the control object using at least the three co-planar tangents.

16. The non-transitory computer readable medium of claim 15, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

for a complex control object model that includes a palm and multiple fingers, applying the determining and fitting a circle actions of claim 15 to construct multiple fingers of control object appendages; and

fitting cross sections of a palm to observed edges of the palm as captured in the images.

17. The non-transitory computer readable medium of claim 15, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

repeatedly applying the determining and fitting a circle actions of claim 15 over time; and

calculating motion of the control object over time based on differences between modeled locations of the control object.

18. The non-transitory computer readable medium of claim 16, wherein tracking motion of the control object while making a gesture in a 3D space further includes:

repeatedly applying the determining and fitting a circle and fitting cross sections actions of claim 16 overtime; and

calculating motion of a complex control object over time based on differences between modeled locations of a complex control object.

19. A method for executing a gesture command, the method including:

receiving a result of analyzing a gesture;

interpreting as an instruction the result of analyzing a gesture; wherein the result of analyzing a gesture is obtained from another program executing on a processor from analysis of differences in positions of fit closed curves fit to observed edges of a control object to track motion of the control object while making a gesture in a 3D space including repeatedly:

obtaining captured images of a control object moving in 3D space captured from at least two geometrically distinct predetermined vantages;

calculating observed edges of the control object from the captured images;

fitting closed curves to the observed edges of the control object as captured in the captured images by selecting a closed curve from a family of similar closed curves that fit the observed edges of the control object as captured using an assumed parameter; and

whenever the control object is a complex control object that includes a palm and multiple fingers, applying actions including obtaining captured images, calculating observed edges, and fitting closed curves to construct multiple fingers of control object appendages; and

fitting cross sections of a palm to observed edges of a palm as captured in the captured images.

* * * * *