



US012008514B2

(12) **United States Patent**
Hill et al.

(10) **Patent No.:** **US 12,008,514 B2**
(45) **Date of Patent:** ***Jun. 11, 2024**

(54) **PACKAGE TRACKING SYSTEMS AND METHODS**

(71) Applicant: **Position Imaging, Inc.**, Portsmouth, NH (US)

(72) Inventors: **Edward L. Hill**, Conway, NH (US); **Rafal Piotrowski**, Portsmouth, NH (US); **Harry Lee Deffebach, III**, Melbourne Beach, FL (US); **Krenar Komoni**, Worcester, MA (US)

(73) Assignee: **Position Imaging, Inc.**, Portsmouth, NH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

 This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/962,632**

(22) Filed: **Oct. 10, 2022**

(65) **Prior Publication Data**

 US 2023/0030356 A1 Feb. 2, 2023

Related U.S. Application Data

(63) Continuation of application No. 15/091,180, filed on Apr. 5, 2016, now Pat. No. 11,501,244.
 (Continued)

(51) **Int. Cl.**
 G06Q 10/0833 (2023.01)
 G06K 7/14 (2006.01)

(52) **U.S. Cl.**
 CPC **G06Q 10/0833** (2013.01); **G06K 7/1413** (2013.01); **G06K 7/1417** (2013.01)

(58) **Field of Classification Search**
CPC . G06Q 10/0833; G06K 7/1413; G06K 7/1417
See application file for complete search history.

(56) **References Cited**

 U.S. PATENT DOCUMENTS

 2,408,122 A 9/1946 Wirkler
 3,824,596 A 7/1974 Guion et al.
 (Continued)

 FOREIGN PATENT DOCUMENTS

 DE 102017205958 A1 10/2018
 WO 2001006401 A1 1/2001
 (Continued)

 OTHER PUBLICATIONS


 Raza, Rana Hammad, Three Dimensional Localization and Tracking for Site Safety Using Fusion of Computer Vision and RFID, Michigan State University, 2013.*
 (Continued)

Primary Examiner — Nathan Erb
(74) *Attorney, Agent, or Firm* — Schmeiser, Olsen & Watts LLP; Timothy P. Collins

(57) **ABSTRACT**

Methods and systems for tracking a package within an area obtain package identification information from a scannable medium associated with the package and image information of the area acquired by an optical sensing device. Image processing detects the presence and location of an object in the area that matches the package based on a comparison of the package identification information obtained from the scannable medium with the image information of the area acquired by the optical sensing device. The package is registered as being present in the area at the location of the detected object in response to detecting a match between the object and the package.

18 Claims, 10 Drawing Sheets



Related U.S. Application Data						
(60)	Provisional application No. 62/221,855, filed on Sep. 22, 2015, provisional application No. 62/143,332, filed on Apr. 6, 2015.		7,995,109	B2	8/2011	Kamada et al.
			8,009,918	B2	8/2011	Van Droogenbroeck et al.
			8,189,855	B2	5/2012	Opalach et al.
			8,201,737	B1	6/2012	Palacios Durazo et al.
			8,219,438	B1	7/2012	Moon et al.
			8,269,624	B2	9/2012	Chen et al.
			8,295,542	B2	10/2012	Albertson et al.
			8,406,470	B2	3/2013	Jones et al.
			8,457,655	B2	6/2013	Zhang et al.
			8,619,144	B1	12/2013	Chang et al.
(56)	References Cited		8,749,433	B2	6/2014	Hill
			8,843,231	B2	9/2014	Ragusa et al.
			8,860,611	B1	10/2014	Anderson et al.
			8,957,812	B1	2/2015	Hill et al.
			9,063,215	B2	6/2015	Perthold et al.
			9,092,898	B1	7/2015	Fraccaroli et al.
			9,120,621	B1	9/2015	Curlander et al.
			9,141,194	B1	9/2015	Keyes et al.
			9,171,278	B1	10/2015	Kong et al.
			9,174,746	B1	11/2015	Bell et al.
	9,269,022	B2	2/2016	Rhoads et al.		
	9,349,076	B1	5/2016	Liu et al.		
	9,424,493	B2	8/2016	He et al.		
	9,482,741	B1	11/2016	Min et al.		
	9,497,728	B2	11/2016	Hill		
	9,500,396	B2	11/2016	Yoon et al.		
	9,514,389	B1	12/2016	Erhan et al.		
	9,519,344	B1	12/2016	Hill		
	9,544,552	B2	1/2017	Takahashi		
	9,594,983	B2	3/2017	Alattar et al.		
	9,656,749	B1	5/2017	Hanlon		
	9,740,937	B2	8/2017	Zhang et al.		
	9,782,669	B1	10/2017	Hill		
	9,872,151	B1	1/2018	Puzanov et al.		
	9,904,867	B2	2/2018	Fathi et al.		
	9,933,509	B2	4/2018	Hill et al.		
	9,961,503	B2	5/2018	Hill		
	9,996,818	B1	6/2018	Ren et al.		
	10,001,833	B2	6/2018	Hill		
	10,148,918	B1	12/2018	Seiger et al.		
	10,163,149	B1	12/2018	Famularo et al.		
	10,180,490	B1	1/2019	Schneider et al.		
	10,257,654	B2	4/2019	Hill		
	10,324,474	B2	6/2019	Hill et al.		
	10,332,066	B1	6/2019	Palaniappan et al.		
	10,373,322	B1	8/2019	Buibas et al.		
	10,399,778	B1	9/2019	Shekhawat et al.		
	10,416,276	B2	9/2019	Hill et al.		
	10,444,323	B2	10/2019	Min et al.		
	10,455,364	B2	10/2019	Hill		
	10,605,904	B2	3/2020	Min et al.		
	10,664,795	B1	5/2020	Worley et al.		
	10,853,757	B1	12/2020	Hill et al.		
	11,361,536	B2	6/2022	Chakravarty et al.		
	11,416,805	B1	8/2022	Piotrowski et al.		
	11,562,318	B2	1/2023	Robinson et al.		
	2001/0027995	A1 *	10/2001	Patel G07G 1/0054 348/E7.087		
	2002/0021277	A1	2/2002	Kramer et al.		
	2002/0095353	A1 *	7/2002	Razumov G06Q 30/06 705/26.81		
	2002/0140745	A1	10/2002	Ellenby et al.		
	2002/0177476	A1	11/2002	Chou		
	2003/0024987	A1	2/2003	Zhu		
	2003/0053492	A1	3/2003	Matsunaga		
	2003/0110152	A1	6/2003	Hara		
	2003/0115162	A1	6/2003	Konick		
	2003/0120425	A1	6/2003	Stanley et al.		
	2003/0132279	A1	7/2003	Stemmle		
	2003/0176196	A1	9/2003	Hall et al.		
	2003/0184649	A1	10/2003	Mann		
	2003/0195017	A1	10/2003	Chen et al.		
	2004/0002642	A1	1/2004	Dekel et al.		
	2004/0095907	A1	5/2004	Agee et al.		
	2004/0107072	A1	6/2004	Dietrich et al.		
	2004/0176102	A1	9/2004	Lawrence et al.		
	2004/0203846	A1	10/2004	Caronni et al.		
	2004/0267640	A1	12/2004	Bong et al.		
	2005/0001712	A1	1/2005	Yarbrough		

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0057647	A1	3/2005	Nowak	2012/0081544	A1	4/2012	Wee	
2005/0062849	A1	3/2005	Foth et al.	2012/0087572	A1	4/2012	Dedeoglu et al.	
2005/0074162	A1	4/2005	Tu et al.	2012/0127088	A1	5/2012	Pance et al.	
2005/0143916	A1	6/2005	Kim et al.	2012/0176227	A1	7/2012	Nikitin	
2005/0154685	A1	7/2005	Mundy et al.	2012/0184285	A1	7/2012	Sampath et al.	
2005/0184907	A1	8/2005	Hall et al.	2012/0257061	A1 *	10/2012	Edwards	G08B 13/00 348/E7.085
2005/0275626	A1	12/2005	Mueller et al.	2012/0286933	A1	11/2012	Hsiao	
2006/0013070	A1	1/2006	Holm et al.	2012/0319822	A1	12/2012	Hansen	
2006/0022800	A1	2/2006	Krishna et al.	2013/0010144	A1	1/2013	Park	
2006/0061469	A1	3/2006	Jaeger et al.	2013/0017812	A1	1/2013	Foster	
2006/0066485	A1	3/2006	Min	2013/0018582	A1	1/2013	Miller et al.	
2006/0101497	A1	5/2006	Hirt et al.	2013/0021417	A1	1/2013	Ota et al.	
2006/0192709	A1	8/2006	Schantz et al.	2013/0029685	A1	1/2013	Moshfeghi	
2006/0208893	A1	9/2006	Anson et al.	2013/0036043	A1	2/2013	Faith	
2006/0279459	A1	12/2006	Akiyama et al.	2013/0051624	A1	2/2013	Iwasaki et al.	
2006/0290508	A1	12/2006	Moutchkaev et al.	2013/0063567	A1	3/2013	Burns et al.	
2007/0060384	A1	3/2007	Dohta	2013/0073093	A1	3/2013	Songkakul	
2007/0073552	A1	3/2007	Hileman	2013/0094693	A1 *	4/2013	Bolton	G06Q 10/0833 382/101
2007/0138270	A1	6/2007	Reblin	2013/0113993	A1	5/2013	Dagit, III	
2007/0205867	A1	9/2007	Kennedy et al.	2013/0117377	A1	5/2013	Miller	
2007/0210920	A1	9/2007	Panotopoulos	2013/0166067	A1	6/2013	Irwin et al.	
2007/0222560	A1	9/2007	Posamentier	2013/0182114	A1	7/2013	Zhang et al.	
2007/0237356	A1	10/2007	Dwinell et al.	2013/0191193	A1	7/2013	Calman et al.	
2008/0007398	A1	1/2008	DeRose et al.	2013/0226655	A1	8/2013	Shaw	
2008/0035390	A1	2/2008	Wurz	2013/0281084	A1	10/2013	Batada et al.	
2008/0048913	A1	2/2008	Macias et al.	2013/0293684	A1	11/2013	Becker et al.	
2008/0143482	A1	6/2008	Shoarinejad et al.	2013/0293722	A1	11/2013	Chen	
2008/0150678	A1	6/2008	Giobbi et al.	2013/0314210	A1	11/2013	Schoner et al.	
2008/0154691	A1	6/2008	Wellman et al.	2013/0335318	A1	12/2013	Nagel et al.	
2008/0156619	A1	7/2008	Patel et al.	2013/0335415	A1	12/2013	Chang	
2008/0174485	A1	7/2008	Carani et al.	2014/0022058	A1	1/2014	Strierner et al.	
2008/0183328	A1	7/2008	Danelski	2014/0108136	A1	4/2014	Zhao et al.	
2008/0204322	A1	8/2008	Oswald et al.	2014/0139426	A1	5/2014	Kryze et al.	
2008/0266253	A1	10/2008	Seeman et al.	2014/0253368	A1	9/2014	Holder	
2008/0281618	A1	11/2008	Mermet et al.	2014/0270356	A1 *	9/2014	Dearing	B07C 7/005 382/103
2008/0316324	A1	12/2008	Rofougaran et al.	2014/0300516	A1	10/2014	Min et al.	
2009/0043504	A1	2/2009	Bandyopadhyay et al.	2014/0317005	A1	10/2014	Balwani	
2009/0073428	A1	3/2009	Magnus et al.	2014/0330603	A1	11/2014	Corder et al.	
2009/0114575	A1	5/2009	Carpenter et al.	2014/0357295	A1	12/2014	Skomra et al.	
2009/0121017	A1	5/2009	Cato et al.	2014/0361078	A1	12/2014	Davidson	
2009/0149202	A1	6/2009	Hill et al.	2015/0009949	A1	1/2015	Khoryaev et al.	
2009/0164277	A1	6/2009	Bhattacharya	2015/0012396	A1	1/2015	Puerini et al.	
2009/0224040	A1	9/2009	Kushida et al.	2015/0019391	A1	1/2015	Kumar et al.	
2009/0243932	A1	10/2009	Moshfeghi	2015/0029339	A1	1/2015	Kobres et al.	
2009/0245573	A1	10/2009	Saptharishi et al.	2015/0039458	A1	2/2015	Reid	
2009/0323586	A1	12/2009	Hohl et al.	2015/0055821	A1	2/2015	Fotland	
2010/0019905	A1	1/2010	Boddie et al.	2015/0059374	A1	3/2015	Hebel	
2010/0076594	A1 *	3/2010	Salour	2015/0085096	A1	3/2015	Smits	
			G05B 19/41865 700/226	2015/0091757	A1	4/2015	Shaw et al.	
2010/0090852	A1	4/2010	Eitan et al.	2015/0130664	A1	5/2015	Hill et al.	
2010/0097208	A1	4/2010	Rosing et al.	2015/0133162	A1	5/2015	Meredith et al.	
2010/0103173	A1	4/2010	Lee et al.	2015/0134418	A1	5/2015	Leow et al.	
2010/0103989	A1	4/2010	Smith et al.	2015/0169916	A1	6/2015	Hill et al.	
2010/0123664	A1	5/2010	Shin et al.	2015/0170002	A1	6/2015	Szegedy et al.	
2010/0131340	A1	5/2010	Brown et al.	2015/0202770	A1	7/2015	Patron et al.	
2010/0159958	A1	6/2010	Naguib et al.	2015/0210199	A1	7/2015	Payne	
2010/0213256	A1	8/2010	Fjellstad et al.	2015/0221135	A1	8/2015	Hill et al.	
2011/0002509	A1	1/2011	Nobori et al.	2015/0227890	A1	8/2015	Bednarek et al.	
2011/0006774	A1	1/2011	Baiden	2015/0248765	A1	9/2015	Criminisi et al.	
2011/0037573	A1	2/2011	Choi	2015/0254906	A1	9/2015	Berger et al.	
2011/0066086	A1	3/2011	Aarestad et al.	2015/0278759	A1	10/2015	Harris et al.	
2011/0143779	A1	6/2011	Rowe et al.	2015/0310539	A1	10/2015	McCoy et al.	
2011/0166694	A1	7/2011	Griffits et al.	2015/0323643	A1	11/2015	Hill et al.	
2011/0187600	A1	8/2011	Landt	2015/0341551	A1	11/2015	Perrin et al.	
2011/0208481	A1	8/2011	Slastion	2015/0362581	A1	12/2015	Friedman et al.	
2011/0210843	A1	9/2011	Kummetz	2015/0371178	A1	12/2015	Abhyanker et al.	
2011/0241942	A1	10/2011	Hill	2015/0371319	A1	12/2015	Argue et al.	
2011/0256882	A1	10/2011	Markhovsky et al.	2015/0379366	A1	12/2015	Nomura et al.	
2011/0264520	A1	10/2011	Puhakka	2016/0035078	A1	2/2016	Lin et al.	
2011/0286633	A1	11/2011	Wang et al.	2016/0063610	A1	3/2016	Argue et al.	
2011/0313893	A1	12/2011	Weik, III	2016/0093184	A1	3/2016	Locke et al.	
2011/0315770	A1	12/2011	Patel et al.	2016/0098679	A1	4/2016	Levy	
2012/0013509	A1	1/2012	Wisher et al.	2016/0140436	A1	5/2016	Yin et al.	
2012/0020518	A1	1/2012	Taguchi	2016/0142868	A1	5/2016	Kulkarni et al.	
2012/0030133	A1	2/2012	Rademaker	2016/0150196	A1	5/2016	Horvath	
				2016/0156409	A1	6/2016	Chang	

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0178727	A1	6/2016	Bottazzi	
2016/0180283	A1	6/2016	Ghosh et al.	
2016/0180667	A1	6/2016	Bunker et al.	
2016/0189277	A1 *	6/2016	Davis	H04N 7/181 705/26.8
2016/0195602	A1	7/2016	Meadow	
2016/0232857	A1	8/2016	Tamaru	
2016/0238692	A1	8/2016	Hill et al.	
2016/0248969	A1	8/2016	Hurd	
2016/0256100	A1	9/2016	Jacofsky et al.	
2016/0286508	A1	9/2016	Khoryaev et al.	
2016/0300187	A1	10/2016	Kashi et al.	
2016/0335593	A1	11/2016	Clarke et al.	
2016/0366561	A1	12/2016	Min et al.	
2016/0370453	A1	12/2016	Boker et al.	
2016/0371574	A1	12/2016	Nguyen et al.	
2017/0030997	A1	2/2017	Hill et al.	
2017/0031432	A1	2/2017	Hill	
2017/0066597	A1	3/2017	Hiroi	
2017/0094251	A1	3/2017	Wolke et al.	
2017/0117233	A1	4/2017	Anayama et al.	
2017/0123426	A1	5/2017	Hill et al.	
2017/0140329	A1	5/2017	Bernhardt et al.	
2017/0234979	A1	8/2017	Mathews et al.	
2017/0261592	A1	9/2017	Min et al.	
2017/0280281	A1	9/2017	Pandey et al.	
2017/0293885	A1	10/2017	Grady et al.	
2017/0313514	A1	11/2017	Lert, Jr. et al.	
2017/0323174	A1	11/2017	Joshi et al.	
2017/0323376	A1	11/2017	Glaser et al.	
2017/0350961	A1	12/2017	Hill et al.	
2017/0351255	A1	12/2017	Anderson et al.	
2017/0359573	A1	12/2017	Kim et al.	
2017/0372524	A1	12/2017	Hill	
2017/0374261	A1	12/2017	Teich et al.	
2018/0003962	A1	1/2018	Urey et al.	
2018/0025417	A1	1/2018	Brathwaite et al.	
2018/0033151	A1	2/2018	Matsumoto et al.	
2018/0068100	A1	3/2018	Seo	
2018/0068266	A1	3/2018	Kirmani et al.	
2018/0094936	A1	4/2018	Jones et al.	
2018/0108134	A1	4/2018	Venable et al.	
2018/0139431	A1	5/2018	Simek et al.	
2018/0164103	A1	6/2018	Hill	
2018/0197139	A1	7/2018	Hill	
2018/0197218	A1	7/2018	Mallesan et al.	
2018/0231649	A1	8/2018	Min et al.	
2018/0242111	A1	8/2018	Hill	
2018/0339720	A1	11/2018	Singh	
2019/0029277	A1	1/2019	Skrædderdal et al.	
2019/0053012	A1	2/2019	Hill	
2019/0073785	A1	3/2019	Hafner et al.	
2019/0090744	A1	3/2019	Mahfouz	
2019/0098263	A1	3/2019	Seiger et al.	
2019/0138849	A1	5/2019	Zhang	
2019/0295290	A1	9/2019	Schena et al.	
2019/0394448	A1	12/2019	Ziegler et al.	
2020/0005116	A1	1/2020	Kuo	
2020/0011961	A1	1/2020	Hill et al.	
2020/0012894	A1	1/2020	Lee	
2020/0097724	A1	3/2020	Chakravarty et al.	
2022/0405704	A1	12/2022	Kirmani	

FOREIGN PATENT DOCUMENTS

WO	2005010550	A1	2/2005
WO	2007130529	A3	1/2008
WO	2009007198	A1	1/2009
WO	2018067127	A1	4/2018
WO	2020061276	A1	3/2020

OTHER PUBLICATIONS

Debo Sun, "Ultra-Tight GPS/Reduced IMU for Land Vehicle Navigation", Mar. 2010, UCGE Reports No. 20305; 254 pages.

Farrell & Barth, "The Global Positioning System & Inertial Navigation", 1999, McGraw-Hill; pp. 245-252.

Farrell, et al., "Real-Time Differential Carrier Phase GPS-Aided INS", Jul. 2000, IEEE Transactions on Control Systems Technology, vol. 8, No. 4; 13 pages.

Filho, et al., "Integrated GPS/INS Navigation System Based on a Gyroscope-Free IMU", DINCON Brazilian Conference on Dynamics, Control, and Their Applications, May 22-26, 2006; 6 pages.

Goodall, Christopher L., "Improving Usability of Low-Cost INS/GPS Navigation Systems using Intelligent Techniques", Jan. 2009, UCGE Reports No. 20276; 234 pages.

Grewal & Andrews, "Global Positioning Systems, Inertial Navigation and Integration", 2001, John Wiley and Sons, pp. 252-256.

International Search Report & Written Opinion in International Patent Application No. PCT/US12/64860, dated Feb. 28, 2013; 14 pages.

Jennifer Denise Gautier, "GPS/INS Generalized Evaluation Tool (GIGET) for the Design and Testing of Integrated Navigation Systems", Dissertation, Stanford University, Jun. 2003; 160 pages.

Jianchen Gao, "Development of a Precise GPS/INS/On-Board Vehicle Sensors Integrated Vehicular Positioning System", Jun. 2007, UCGE Reports No. 20555; 245 pages.

Li, et al. "Multifrequency-Based Range Estimation of RFID Tags," IEEE International Conference on RFID, 2009.

Notice of Allowance in U.S. Appl. No. 15/091,180 dated Sep. 21, 2022.

Non-Final Office Action in U.S. Appl. No. 15/270,749 dated Apr. 4, 2018; 8 pages.

Notice of Allowance in U.S. Appl. No. 15/270,749 dated Oct. 4, 2018; 5 pages.

Ex Parte Quayle Action in U.S. Appl. No. 15/416,379 dated Oct. 5, 2021; 6 pages.

Notice of Allowance in U.S. Appl. No. 15/416,379 dated Mar. 30, 2022; 16 pages.

Notice of Allowance in U.S. Appl. No. 15/259,474, dated Jul. 11, 2022.

Non-Final Office Action in U.S. Appl. No. 17/371,479 dated Aug. 18, 2022.

Pourhomayoun, Mohammad and Mark Fowler, "Improving WLAN-based Indoor Mobile Positioning Using Sparsity," Conference Record of the Forty Si11-14-2016 IDSth Asilomar Conference on Signals, Systems and Computers, Nov. 4-7, 2012, pp. 1393-1396, Pacific Grove, California.

Proakis, John G. and Masoud Salehi, "Communication Systems Engineering", Second Edition, Prentice-Hall, Inc., Upper Saddle River, New Jersey, 2002; 815 pages.

Santiago Alban, "Design and Performance of a Robust GPS/INS Attitude System for Automobile Applications", Dissertation, Stanford University, Jun. 2004; 218 pages.

Schmidt & Phillips, "INS/GPS Integration Architectures", NATO RTO Lecture Series, First Presented Oct. 20-21, 2003; 24 pages.

Shakeri, Moein and Hong Zhang, "Cooperative Targeting: Detection and Tracking of Small Objects with a Dual Camera System" Field and Service Robotics, Springer, Cham, 2015.

Sun, et al., "Analysis of the Kalman Filter With Different Ins Error Models for GPS/INS Integration in Aerial Remote Sensing Applications", Beijing, 2008, The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences Vol. Nov. 14, 2016 IDS11-14-2016 IDS11-14-2016 IDSVII, Part B5.; 8 pages.

Szeliski, R., "Image Alignment and Stitching: A Tutorial", Technical Report, MST-TR-2004-92, Dec. 10, 2006.

Vikas Kumar N., "Integration of Inertial Navigation System and Global Positioning System Using Kalman Filtering", M.Tech Dissertation, Indian Institute of Technology, Bombay, Mumbai, Jul. 2004; 69 pages.

Welch, Greg and Gary Bishop, "An Introduction to the Kalman Filter," Department of Computer Science, University of North Carolina at Chapel Hill, Chapel Hill, NC 27599-3175, Updated: Monday, Jul. 24, 2006.

Wilde, Andreas, "Extended Tracking Range Delay-Locked Loop," Proceedings IEEE International Conference on Communications, Jun. 1995, pp. 1051-1054.

(56)

References Cited

OTHER PUBLICATIONS

Xu, et al., "Performance Evaluation of Color Correction Approaches for Automatic Multi-View Image and Video Stitching", International Conference on Computer Vision and Pattern Recognition (CVPR10), San Francisco, CA, 2010.

Yong Yang, "Tightly Coupled MEMS INS/GPS Integration with INS Aided Receiver Tracking Loops" Jun. 2008, UCGE Reports No. 20270; 205 pages.

Piotrowski, et al. "Light-Based Guidance for Package Tracking Systems" U.S. Appl. No. 17/877,269, filed Jul. 29, 2022.

Notice of Allowance in U.S. Appl. No. 17/371,479 dated Dec. 20, 2022.

Non-Final Office Action in U.S. Appl. No. 15/861,414 dated Dec. 16, 2022.

Final Office Action in U.S. Appl. No. 15/091,180, dated Jan. 23, 2020; 17 pages.

Final Office Action in U.S. Appl. No. 15/091,180, dated Mar. 10, 2021; 24 pages.

Final Office Action in U.S. Appl. No. 15/091,180 dated May 12, 2022; 7 pages.

Non-Final Office Action in U.S. Appl. No. 15/091,180, dated Jun. 27, 2019; 11 pages.

Non-Final Office Action in U.S. Appl. No. 15/091,180 dated Oct. 1, 2020.

Non-Final Office Action in U.S. Appl. No. 15/091,180 dated Sep. 1, 2021.

Restriction Requirement in U.S. Appl. No. 15/091,180 dated Mar. 19, 2019; 8 pages.

Corrected Notice of Allowability in U.S. Appl. No. 15/270,749 dated Oct. 30, 2018; 5 pages.

Final Office Action in U.S. Appl. No. 16/206,745 dated Feb. 5, 2020; 15 pages.

Non-Final Office Action in U.S. Appl. No. 16/206,745 dated Sep. 23, 2020.

Non-Final Office Action in U.S. Appl. No. 15/416,366 dated Apr. 6, 2020; 13 pages.

Notice of Allowance in U.S. Appl. No. 15/416,366 dated Aug. 19, 2020; 13 pages.

Final Office Action in U.S. Appl. No. 15/259,474, dated Mar. 9, 2021; 23 pages.

Final Office Action in U.S. Appl. No. 15/259,474 dated Feb. 8, 2022.

Non-Final Office Action in U.S. Appl. No. 15/259,474, dated Sep. 1, 2020; 17 pages.

Non-Final Office Action in U.S. Appl. No. 15/259,474 dated Aug. 26, 2021.

Final Office Action in U.S. Appl. No. 15/861,414 dated Feb. 8, 2021.

Final Office Action in U.S. Appl. No. 15/861,414 dated Mar. 16, 2022.

Non-Final Office Action in U.S. Appl. No. 15/861,414 dated Apr. 6, 2020; 14 pages.

Non-Final Office Action in U.S. Appl. No. 15/861,414 dated Aug. 26, 2021.

Final Office Action in U.S. Appl. No. 16/437,767 dated Feb. 5, 2021.

Non-Final Office Action in U.S. Appl. No. 16/437,767, dated Jul. 15, 2020; 19 pages.

Notice of Allowance and Fees Due in U.S. Appl. No. 16/437,767, dated May 14, 2021; 8 pages.

Non-Final Office Action in U.S. Appl. No. 16/575,837, dated Apr. 21, 2021; 18 pages.

International Preliminary Report on Patentability in PCT/US2019/051874 dated Apr. 1, 2021.

Notice of Allowance and Fees Due in U.S. Appl. No. 16/740,679, dated Apr. 20, 2021; 15 pages.

International Preliminary Report on Patentability in PCT/US2020/013280 dated Jul. 22, 2021.

International Search Report and Written Opinion in PCT/US2020/013280 dated Mar. 10, 2020; 9 pages.

Raza, Rana Hammad "Three Dimensional Localization and Tracking for Site Safety Using Fusion of Computer Vision and RFID," 2013, Dissertation, Michigan State University.

"ADXL202/ADXL210 Product Sheet," Analog Devices, Inc., Analog.com, 1999; 11 pages.

Adrian Schumacher, "Integration of a GPS aided Strapdown Inertial Navigation System for Land Vehicles", Master of Science Thesis, KTH Electrical Engineering, 2006; 67 pages.

Brown, et al., "Automatic Panoramic Image Stitching Using Invariant Features", International Journal of Computer Vision, vol. 74, No. 1, pp. 59-73, 2007.

Final Office Action in U.S. Appl. No. 16/206,745 dated May 22, 2019; 9 pages.

Non-Final Office Action in U.S. Appl. No. 15/416,366 dated Jun. 13, 2019; 11 pages.

Non-Final Office Action in U.S. Appl. No. 15/259,474 dated May 29, 2019; 19 pages.

Morbella N50: 5-inch GPS Navigator User's Manual, Maka Technologies Group, May 2012.

Non-Final Office Action in U.S. Appl. No. 15/416,379, dated Jun. 27, 2019; 12 pages.

Final Office Action in U.S. Appl. No. 15/416,366 dated Oct. 7, 2019; 14 pages.

Non-Final Office Action in U.S. Appl. No. 16/206,745 dated Oct. 18, 2019; 8 pages.

Final Office Action in U.S. Appl. No. 15/259,474, dated Jan. 10, 2020; 19 pages.

Final Office Action in U.S. Appl. No. 15/416,379 dated Jan. 27, 2020; 15 pages.

Dictionary Definition for Peripheral Equipment. (2001). Hargrave's Communications Dictionary, Wiley. Hoboken, NJ: Wiley. Retrieved from https://search.credoreference.com/content/entry/hargravecomms/peripheral_equipment/0 (Year: 2001).

International Search Report and Written Opinion in PCT/US2019/051874 dated Dec. 13, 2020; 9 pages.

Non-Final Office Action in U.S. Appl. No. 15/416,379 dated Oct. 2, 2020.

Final Office Action in U.S. Appl. No. 15/861,414 dated Nov. 17, 2020.

Notice of Allowance and Fees Due in U.S. Appl. No. 16/206,745, dated Mar. 12, 2021; 9 pages.

Non-Final Office Action in U.S. Appl. No. 16/740,679 dated Jan. 6, 2021.

Final Office Action in U.S. Appl. No. 15/416,379, dated May 13, 2021; 18 pages.

Final Office Action in U.S. Appl. No. 16/575,837 dated Sep. 3, 2021.

Non-Final Office Action in U.S. Appl. No. 16/206,745 dated Jan. 7, 2019; 10 pages.

Non-Final Office Action in U.S. Appl. No. 17/894,472 dated Apr. 26, 2023.

Non-Final Office Action in U.S. Appl. No. 17/104,157 dated Mar. 29, 2023.

Non-Final Office Action in U.S. Appl. No. 17/877,269, dated Oct. 6, 2023.

Final Office Action in U.S. Appl. No. 17/894,472, dated Oct. 19, 2023.

Non-Final Office Action in U.S. Appl. No. 18/184,486, dated Sep. 28, 2023.

Restriction Requirement in U.S. Appl. No. 17/472,978, dated Nov. 6, 2023.

Final Office Action in U.S. Appl. No. 17/104,158, dated Sep. 21, 2023.

Farmer, Michael E and Anil K. Jain, "Smart Automotive Airbags: Occupant Classification and Tracking" IEEE Transactions on Vehicular Technology, vol. 56, No. 1, Jan. 2007, pp. 60-80.

Notice of Allowance in U.S. Appl. No. 17/877,269 mailed on Mar. 13, 2024.

Notice of Allowance in U.S. Appl. No. 17/894,472 mailed on Jan. 31, 2024.

Final Office Action in U.S. Appl. No. 18/184,486 mailed on Mar. 22, 2024.

(56)

References Cited

OTHER PUBLICATIONS

Non-Final Office Action in U.S. Appl. No. 17/472,978 mailed on Mar. 6, 2024.

Notice of Allowance in U.S. Appl. No. 17/104,158 mailed on Dec. 28, 2023.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6A





FIG. 6B






FIG. 7




FIG. 8

PACKAGE TRACKING SYSTEMS AND METHODS

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/091,180 filed Apr. 5, 2016, titled “Package Tracking Systems and Methods,” which claims the benefit of and priority to U.S. provisional application No. 62/143,332, filed Apr. 6, 2015, titled “Package Tracking System using Sensors,” and to U.S. provisional application No. 62/221,855, filed Sep. 22, 2015, titled “Package Tracking System using Sensors,” the entireties of which applications are incorporated by reference herein.

FIELD OF THE INVENTION

The invention relates generally to systems and methods of tracking packages and other assets.

BACKGROUND

The shipping of packages, including, but not limited to, letters, parcels, containers, and boxes of any shape and size, is big business, one that grows annually because of online shopping. Every day, people and businesses from diverse locations throughout the world ship millions of packages. Efficient and precise delivery of such packages to their correct destinations entails complex logistics.

Most package shippers currently use barcodes on packages to track movement of the packages through their delivery system. Each barcode stores information about its package; such information may include the dimensions of the package, its weight and destination. When shipping personnel pick up a package, he or she scans the barcode to sort the package appropriately. The delivery system uses this scanned information to track movement of the package.

For example, upon arriving at the city of final destination, a package rolls off a truck or plane on a roller belt. Personnel scan the package, and the system recognizes that the package is at the city of final destination. The system assigns the package to an appropriate delivery truck with an objective of having delivery drivers operating at maximum efficiency. An employee loads the delivery truck, scanning the package while loading it onto the truck. The scanning operates to identify the package as “out for delivery”. The driver of the delivery truck also scans the package upon delivery to notify the package-delivery system that the package has reached its final destination.

Such a package-delivery system provides discrete data points for tracking packages, but it has its weaknesses: there can be instances where the position or even the existence of the package is unknown. For example, a package loader may scan a package for loading on delivery truck A, but the package loader may place the package erroneously on delivery truck B. In the previously described package-delivery system, there is no way to prevent or quickly discover this error.

Further, package-delivery systems can be inefficient. Instructions often direct the person who is loading a delivery truck to load it for optimized delivery. This person is usually not the delivery person. Thus, his or her perception of an efficient loading strategy may differ greatly from that of the person unloading the vehicle. Further, different loaders may pack a vehicle differently. Additionally, the loader may toss packages into the truck or misplace them. Packages may also shift during transit. Time expended by drivers searching for

packages in a truck is expended cost and an inefficiency that financially impacts the shippers.

Industry has made attempts to track packages efficiently. One such attempt places RFID (Radio Frequency Identification) chips on the packages. Such a solution requires additional systems and hardware. For instance, this solution requires the placement of an RFID tag on every package and the use of readers by package loaders or the placement of readers throughout the facility to track packages.

SUMMARY

All examples and features mentioned below can be combined in any technically possible way.

In one aspect, a method for tracking a package within an area comprises obtaining package identification information from a barcode on a package, acquiring image information of the area, detecting a presence and location of an object in the area that matches the package based on a comparison of the package identification information obtained from the barcode with the image information of the area obtained by the optical sensing device, and registering the package as being present in the area at the location of the detected object in response to detecting a match between the object and the package.

In another aspect, a method of loading of a package into an area comprises determining package identification information from a scannable image associated with a package, acquiring three-dimensional (3D) image information of an area, determining a location in the area for placement of the package based on the package identification information and the 3D image information, and providing an indicator of the location in the area determined for placement of the package.

In still another aspect, a method of loading of a package into an area comprises determining a destination of a package to be transported based on package identification information obtained from a scannable image associated with the package, designating the package for loading on a given delivery vehicle based on the determined destination, associating the given delivery vehicle with a particular color, and illuminating the package with light of the particular color associated with the given delivery vehicle to guide loading of the package onto that delivery vehicle.

In one aspect, a package tracking system for use with a delivery vehicle comprises memory storing package identification information relating to a package that is to be loaded on the delivery vehicle. At least two optical sensing devices are positioned in the delivery vehicle to view an area inside of the delivery vehicle. An image processor is in communication with the at least two optical sensing devices. The image processor is configured to detect a presence and location of an object loaded in the area inside of the delivery vehicle and to determine information about the object. The image processor compares the stored package identification information to the information determined about the object, to determine if the stored package identification information substantially matches the information determined about the object.

In another aspect, a package tracking system comprises at least one camera disposed in a delivery vehicle and configured to view an area inside of the delivery vehicle. At least one depth sensor is disposed in the delivery vehicle and configured to view the area inside of the delivery vehicle. An image processor is in communication with the at least one camera and the at least one depth sensor. The image processor is configured to generate three-dimensional image

information of the area based on two-dimensional images of the area received from the at least one camera and depth images of the area received from the at least one depth sensor. The image processor is further configured to determine a location of a package in the area based on the generated three-dimensional image information and package identification information associated with the package.

In still yet another aspect, a package tracking system comprises at least one camera disposed in a delivery vehicle and configured to view an area of the delivery vehicle. At least one depth sensor is disposed in the delivery vehicle and configured to view the area. An image processor is in communication with the at least one camera and the at least one depth sensor. The image processor is configured to generate three-dimensional image information of the area based on two-dimensional images of the area received from the at least one camera and depth images of the area received from the at least one depth sensor. The image processor is further configured to determine a location for placement of a package in the area based on the generated three-dimensional image information and package identification information associated with the package.

In yet another aspect, a real-time package tracking system comprises at least one optical sensor configured to capture images continuously within a field of view of an area, and an image processor in communication with the at least one optical sensor to receive therefrom captured images. The image processor is configured to detect and identify, in real time, an object entering into or leaving the field of view based on the received captured images.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and further advantages of this invention may be better understood by referring to the following description in conjunction with the accompanying drawings, in which like numerals indicate like structural elements and features in various figures. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention.

FIG. 1 is a view of an embodiment of a package tracking system.

FIG. 2 is a diagram of an example implementation of the package tracking system within a delivery system.

FIG. 3 is a flow diagram of an embodiment of a process for general package tracking.

FIG. 4A is a diagram illustrating an example of a match between a detected package and a scanned package.

FIG. 4B is a diagram illustrating an example of a mismatch between a detected package and a scanned package.

FIG. 5 is a flow diagram of an embodiment of an image-processing process for identifying and matching a package.

FIGS. 6A, 6B, and 6C together are a flow diagram of an embodiment of an image-processing process that uses depth information to track a package.

FIG. 7 is a diagram of embodiments of a package tracking system that uses radio frequency position determinations in conjunction with optical tracking.

FIG. 8 is a schematic for an embodiment of a package tracking system.

DETAILED DESCRIPTION

Package tracking systems described herein actively tracking packages continuously. Advantageously such systems may not require major alterations in personnel behavior and

can be implemented with low hardware cost. In general, these systems employ cameras, depth sensors, or other optical sensors (herein referred to generally as cameras) to track packages, objects, assets, or items (herein referred to generally as packages). The cameras are placed in or adjacent to the holding area for the packages, for example, the cargo bay of a delivery vehicle or a package room. One or more cameras can also be situated near a package conveyor or roller belt, to track the movement of packages optically before the packages are placed into a holding area. A package barcode is scanned in conjunction with it being moved into the holding area. As used herein, a barcode is any readable or scannable medium, examples of which include, but are not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor media, or any suitable combination thereof. Package identification information about the package is determined from scanning the package barcode. Such package identification information typically includes dimensions, weight, contents or other information that may be utilized to detect and track the package.

An image processor analyzes the video stream from the cameras associated with the holding area to detect the presence of the package(s) contained within. When a package is identified, the image processor determines if the package corresponds to the package data derived from the package barcode. If the package barcode data and package image data match with a high degree of confidence, the system marks the package as existing within the camera area of coverage (e.g., within the delivery vehicle). Any user that thereafter views a stream of the camera view or a static image of the packages inside the holding area may receive an overlay that identifies the packages contained therein and their precise location.

A package tracking system can also employ one or more guidance mechanisms (e.g., audible, visual) to guide placement of a package into a holding area or to bring attention to the present location of a package (e.g., for purposes of removal).

FIG. 1 shows a view of one embodiment of a package tracking system **100** deployed in a tracking area **112**. Example embodiments of the tracking area **112** include, but are not limited to, the cargo bay of a delivery truck or water-going vessel, a storage room, and a warehouse. For illustrative purposes, the tracking area **112** includes a plurality of shelves **114-1**, **114-n** (generally, shelf or shelves **114**), and on the shelves **114** are packages and/or assets **116-1**, **116-2**, **116-3**, . . . **116-n** (generally, package **116**).

Shipper systems typically identify and track packages **116** using barcodes. A barcode is placed on a package **116** when the shipper takes possession of the package. The barcode includes package identification information about the package, including the package dimensions, identification number, delivery address, shipping route and other data. The term barcode is to be broadly understood herein to include images or markings on a package that contain information or data (coded or otherwise) pertaining to the package. The barcode on the package is initially scanned into the system **100** with a scanner **124**.

In general, the scanner **124** may be optical, magnetic, or electromagnetic means, depending on the type of barcode on the package. The scanner **124** may be a conventional barcode scanner or a smart phone or tablet-like device. The form factor of the scanner **124** is not limiting. Example embodiments of the scanner **124** and techniques for wirelessly tracking the scanner **124** are described in U.S. patent application Ser. No. 14/568,468, filed Dec. 12, 2014, titled

5

“Tracking System with Mobile Reader,” the entirety of which is incorporated by reference herein.

The system **100** includes an optical system. In this embodiment, the optical system includes four optical sensors represented by cameras **118-1**, **118-2**, **118-3**, and **118-4** (generally, camera **118**). Each camera **118** has a field of view **120** covering a portion of the area within which the packages **116** lie (to simplify the illustration, only one field of view is shown). An appropriate number of cameras **118** can be mounted inside the tracking area **112** in such a way to provide a complete field of view, or at least a functionally sufficient field of view, of the area **112**, and, in some cases, of an area outside the area **112** (e.g., a conveyor belt moving the packages prior to loading). Before the system **100** begins to operate, each camera position is fixed to ensure the camera(s) cover the tracking area **112**. The exact position and number of cameras **118** is within the discretion of the system designer.

The camera **118** may be a simple image or video capture camera in the visual range, an infrared light detection sensor, depth sensor, or other optical sensing approach. In general, this camera enables real-time package tracking when the package is within the camera’s area of coverage. The area of coverage is preferably the shelves **114** and tracking area **112**. In some instances, the field of view can extend beyond the tracking area **112**, to ensure that the packages scanned outside the tracking area **112** correspond to those packages placed inside the tracking area **112**.

In addition, each camera **118** is in communication with a processor **122** (CPU **122**), for example, a DSP (digital signal processor) or a general processor of greater or lesser capability than a DSP. In one embodiment, the CPU **122** is a Raspberry Pi. Although shown as a single CPU within the tracking area **112**, the processor **122** can be a processing system comprised of one or more processors inside the tracking area, outside of the tracking area, or a combination thereof. Communication between the cameras **118** and the CPU **122** is by way of a wired or wireless path or a combination thereof. The protocol for communicating images, the compression of image data (if desired), and the image quality required are within the scope of the designer.

In one embodiment, the cameras **118** are video cameras running in parallel, and the cameras simultaneously provide images to the CPU **122**, which performs an image processing solution. For this approach, the images are merged into a pre-determined map or layout of the tracking area **112** and used like a panorama. (Alternatively, or additionally, the CPU **122** can merge the images into a mosaic, as described in more detail below). The camera images are synchronized to fit the map and operate as one camera with a panorama view. In this embodiment, two (or more) cameras capture two different perspectives and the CPU **122** flattens the images by removing perspective distortion in each of them and merges the resulting image into the pre-determined map.

An image stitching process usually first performs image alignment using algorithms that can discover the relationships among images with varying degrees of overlap. These algorithms are suited for applications such as video stabilization, summarization, and the creation of panoramic mosaics, which can be used in the images taken from the cameras **118** (i.e., optical sensors) in the described system.

After alignment is complete, image-stitching algorithms take the estimates produced by such algorithms and blend the images in a seamless manner, while taking care of potential problems, such as blurring or ghosting caused by parallax and scene movement as well as varying image exposures inside the environment at which the cameras are

6

placed in. Example image stitching processes are described in “Image Alignment and Stitching: A Tutorial”, by Richard Szeliski, Dec. 10, 2006, Technical Report, MSR-TR-2004-92, Microsoft Research; “Automatic Panoramic Image Stitching using Invariant Features,” by Brown and D. Lowe, International Journal of Computer Vision, 74(1), pages 59-73, 2007; and “Performance Evaluation of Color Correction Approaches for Automatic Multiview Image and Video Stitching,” by Wei Xu and Jane Mulligan, In Intl. Conf on Computer Vision and Pattern Recognition (CVPR10), San Francisco, CA, 2010, the teachings of which are incorporated by reference herein in their entireties.

In an alternative embodiment, a mosaic approach may be utilized to integrate camera images. In this embodiment, one camera **118** is used for a certain area, a second (or third or fourth) camera **118** is used for another area, and a handoff is used during the tracking, with the images from cameras **118** being run in parallel on the CPU **122**. In a mosaic, like a panorama approach, image data from the multiple cameras (or from other sensors) are merged into the map of the tracking area **112** (e.g., truck, container, plane, etc.) with each viewpoint designated for the area that is seen by the camera **118**. It will be recognized that in both embodiments, a handoff is made when objects move from one viewpoint to another or are seen by one camera and not the others. These handoffs may be made using the images running in parallel on the cameras **118**, with the package placement and movement determined by the CPU **122** using whichever camera has the best view of the package **116**.

In an alternative embodiment, if the system **100** is using depth sensors, the image stitching operation can be omitted and each camera stream data is processed independently for change, object detection and recognition. Then, the result “areas of interest” are converted to individual point clouds (described further in connection with FIG. 6C) and transformed in to a single common coordinate system. The translation and rotation transformations used for this process are based on the camera sensors position and orientation in relations with each other. One camera is picked as the main sensor and all other camera data is transformed into the main coordinate system, achieving the same end result as the image stitching procedure, namely, unification of package coordinates between sensors.

In one embodiment, the image processing is performed by the CPU **122**. Alternatively, if bandwidth is not a significant concern, the image data can be transferred to a central server (FIG. 2) and image processing may be performed by the central server. Those of ordinary skill in the art will recognize that any controller, CPU, graphics processor or other computing device capable of processing image data to perform the image analysis described herein may be utilized.

The image processing CPU **122** creates the aforementioned map of the tracking area **112** under surveillance. Locating the shelves **114** assists the image processor **112** identification edge locations of packages **116**. Further, a priori calculation of the distance of each camera **118** from shelves **114** assists in properly calculating package dimensions. In one embodiment, a single reference dimension is needed and dimensions of a tracked asset **116** can be determined at any position in space relative to the known dimension. In case of image or video cameras only, a dimension reference has to be related to position in the tracking area **112** (i.e., the length and depth of the shelves are known, thus the dimensions of a package placed on these shelves can be determined in relation with these shelves). In this embodiment, pixel count or vector distances of contours

of these pixels can represent the package 116 and be used to help determine relevant package dimension data.

FIG. 2 shows an example of an implementation of the package tracking system 100 (FIG. 1) within a delivery system 200. For illustration purposes, the delivery system 200 includes multiple delivery vehicles 202-1, 202-n (generally, 202) and scanners 124-1, 124-n (generally, 124) used by personnel to obtain package identification information from packages. Although shown in FIG. 2 as trucks, a delivery vehicle 202 may be any form of transport, including, but not limited to, an airplane, automobile, van, sea-going vessel, train, airplane baggage cart. The delivery vehicles 202 and scanners 124 are in communication with a central server (or servers) 204 over communication connections 206. The server 204 (or servers) can be cloud based, meaning that a provider of the server 204 makes applications, services, and resources available on demand to users over a network (e.g., the Internet). The communication connections 206 may be established using any type of communication system including, but not limited to, a cellular network, private network, local network, wired network, wireless network, or any combination thereof.

The scanners 124 are in communication with the central server 204, either continuously or through data dumps, to transfer package identification information when a barcode on a package is scanned and the location. Typically, the location of the scanner 124 is generic (e.g., "Atlanta").

Each delivery vehicle 202 includes a tracking area 112, containing packages 116, and a processor 122. Each delivery vehicle 202 may have a GPS system (FIG. 7) for use in directing and tracking the vehicle 202. The cloud-based server 204 (or a central controller, not shown) identifies the appropriate shipping route, and the next appropriate delivery vehicle, if any. The delivery vehicles 202 may also communicate data (e.g., package identification information) to the central server 204. The transfer of data between the vehicles 202 and the central server 204, like the scanners, can be continuous or intermittent (e.g., data dumps). Based on such communications, the central server 204 not only can track the delivery vehicles 202, but also the progress of the packages 116 they carry through the shipping route. The central server 204 can use the package identification information to notify the driver of the next appropriate delivery vehicle, through the scanner of the driver, to expect the package.

FIG. 3 shows an embodiment of a process 300 for general package tracking. For purposes of illustrating the process 300 by example, reference is made to the delivery vehicle 202-1 and other elements of FIG. 2. Before loading a package 116-1 onto the delivery vehicle 202-1, a loader uses a scanner 124-1 to scan (step 302) a barcode associated with the package 116-1. The scanner 124 transmits (step 304) the barcode (package identification) information to the image processing CPU 122 of the delivery vehicle 202-1 or to the central server 204, which can then transmit the data to the CPU 122. Transmission of this information may be by Bluetooth, WIFI or other communication protocols, wired or wireless. By receiving the barcode information (e.g., identification number, size, color) describing the package 116-1, the image processing CPU 122 becomes notified (step 306) of the package 116-1 and expects this package 116-1 to be subsequently loaded onto the delivery vehicle 202-1. A loader places (step 308) the package 116-1 on a shelf of the vehicle 202-1. Light-based guidance may be used to direct the loader to the particular vehicle 202-1 upon which to load the package, the particular location on the shelf where to place the package 116-1, or both.

The image processing CPU 122 detects (step 310) the presence of the package 116-1, as described in more detail in connection with FIG. 5. The image processing CPU 122 then attempts to identify (step 312) the detected package as that package expected to be loaded (i.e., from step 306). Identifying the package 116-1 generally entails comparing certain visible characteristics of the package 116-1 to certain barcode information obtained during the scanning operation. In one embodiment, the size of the package measured using the camera(s) 118 of the delivery vehicle 202-1 is compared to the expected package dimensions as read from the barcode. In another embodiment, the image processor 122 registers the package 116-1 by virtue of the package 116-1 being the first package detected after notification (at step 306) of the package 116-1 being scanned. In such an instance, the image processor 122 can register the package 116-1 by associating image data captured by the camera(s) with the identification number read from the barcode of the detected package 116-1.

FIG. 4A shows an example of when such a comparison produces a match, thereby signifying a high level of confidence that the appropriate package was loaded on the delivery vehicle 202-1. In this example, the scanned barcode data identify the package 116-1 to be loaded as having package dimensions of 10" by 20". The images captured by the camera(s) 118 on the delivery vehicle 202-1 indicate that a package with dimensions of 9.8" by 19.7" was loaded on the delivery vehicle 202-1. The image processing CPU 122 is configured to consider the differences between the dimensions of the captured images and the dimensions according to the barcode data to fall within acceptable criteria for declaring a match.

FIG. 4B shows an example of when a comparison does not produce a match. In this example, a 10" by 20" package is scanned, but subsequent image capture data shows that a 7.4" by 12.3" package was loaded onto the delivery vehicle 202-1. The image processing CPU 122 can be configured to consider the differences between the dimensions to be too great to consider the detected package as a match to the scanned package.

Referring back to FIG. 3, if the data captured by the barcode scanner matches (within a predetermined threshold) the package image data captured by the camera 118, a match occurs. The matched package is not only marked or identified in real time as being within the delivery vehicle 202-1, but also the exact location of the package 116-1 in the vehicle may be made continuously available to the central server 204, loader, driver or anyone else with access to the system 200. This information, which may be referred to hereafter as package location data, can be stored on memory associated with the image processing CPU 122. Package location data includes the dimension information detected for the matched package associated with the location of the package within the delivery vehicle 202-1. More specifically, the image processing CPU 122 may overlay the initially created vehicle map with the package identification information in the corresponding location. If communications allow, marked package location data may be stored in memory at other locations, including (or additionally) in the central server 204.

As stated previously, the image processing CPU 122 includes wireless communication (commonly Bluetooth, Wi-Fi, or other communication methods and protocols suitable for the size of the area of coverage of the camera). The image processing CPU 122 continuously receives (step 314) real-time views captured by the cameras 118 in the delivery vehicle 202-1. Because the location of the matched package

is stored in memory of the image processing CPU, the real-time image data from the camera **118** is streamed to a handheld or fixed or mounted view screen to show the live view of the package overlaid with augmented reality markings identifying the package. The image processing CPU **122** continuously monitors and tracks (step **314**) within the vehicle **202-1** until motion of an object is detected (step **316**). In response to the detection of motion, the process **300** returns to detecting packages at step **310**.

Implications of such real-time tracking can be appreciated by the following illustration. A driver entering the delivery vehicle **202-1** may not and need not have any personal knowledge of what packages were loaded where in the vehicle. Instead, the driver carries a view screen (often in the form of a handheld tablet, smartphone, or scanner) that displays a stream of one of the cameras **118** in the cargo bay of the vehicle **202-1**. The image appearing on the view screen includes marks identifying various packages. A mark may be a box around the live view of the package with text stating the package name, identifier, intended addressee or most efficient package identifier. Upon arriving at a stop for an intended package addressee, for example Mr. Jones, the driver can walk to the back of the delivery vehicle. The system **200** may automatically display the package(s) intended for delivery to Mr. Jones using highlighting or demarcating for easy location. Alternatively, the driver can search the image data on the view screen for markings labeled "Jones" and such packages are demarcated on the view screen for easy location. In addition, the system **200** may employ light-based guidance to show the driver the location of the package.

In some embodiments, multiple live streams of the cargo in a vehicle are available, with one camera (e.g., **118-1** of FIG. 1) covering one area of the cargo bay and another camera (e.g., **118-2** of FIG. 2) covering another area of the cargo bay. The system **200** can thus quickly and effectively permit a loader or delivery person who enters the cargo area to locate a package using the camera stream overlaid with package marking (location). For a person using a tablet viewing the cargo area, the "video stream" in one embodiment can be a static image of the delivery vehicle sent from the image processing CPU. Since the central map of the delivery vehicle can be used for positioning the packages, that central map, with the location of each package of interest, is what is used for viewing on a device.

FIG. 5 shows an embodiment of an image-processing process **500** for identifying and matching a package. In a description of the process **500**, reference is made to elements of FIG. 1. At step **502**, color data (e.g., RGB) for at least two image frames (N and N-1) are acquired from a camera **118**. The color data is converted (step **504**) to grey scale data for the at least two image frames. Those of ordinary skill in the art are familiar with producing grey scale data from color image sensors.

At step **506**, an absolute difference is determined across the two images to detect the presence of new objects. To quicken the processing, threshold detection (step **508**) may be utilized to detect regions of interest. In addition, in those regions of interest data may be filtered (step **510**) to limit the amount of data processed. After filtering, threshold detection (step **512**) may be utilized on the filtered data.

At step **514**, if no changes between the grayscale images are found, this indicates a high probability of no new package being located; the system **100** does not identify or mark a package. For instance, the loader may not have moved or loaded a package, or a new package cannot be located. The system **100** then acquires (step **502**) the next

temporal two frames (N and N+1). Sampling frequency may be continuous or at regular intervals according to designer preference, available processing power, and bandwidth.

If a change in the images (N and N-1) is detected at step **514**, further analysis occurs. For example, the change detected by the system **100** may be the detection of the presence of the loader in the image. Alternatively, if changes in the images are indicative of a package moving, the image processing CPU **122** also continues to work on the current image data (frame N and N-1).

Those of ordinary skill in the art will recognize that a variety of images may be compared to determine loading or movement of a package. For example, an N 'current frame' and N-X 'previous frame' may be tested for motion, where X is greater than 1, and if motion occurs then the N-X frame (before motion occurred) may be saved as a background frame for later processing in comparison to a more recent image frame (i.e., a new N 'current frame'). After motion is stopped, the background frame and a new N current frame are used for package location and identification.

Whenever a new package is located, the package is to be identified. In one embodiment, the image processing CPU **122** uses edge detection to determine (step **516**) the dimensions of the package. Objects that are not compatible with being a package are filtered at this point. For example, if an object size is less than the smallest possible package, the object is ignored. The system **100** can also filter other objects of a size, dimension, or location that do not correspond to a package (e.g., the loader or a clipboard or tablet carried by the loader).

Various metrics may be utilized in addition to or conjunction with those described above to aid in identifying a package. For example, any object placed on a shelf (mapped as described above) may be weighted logically so as to be presumed to be the last scanned package. The package size, color (if cameras are color), contours or other distinguishing characteristics may be compared to any data captured by the barcode scanner. As previously described, when a package barcode is scanned, the system **100** expects that the next package detected will match the scanned package. Reliance on this assumption is accurate provided loaders handle packages sequentially, that is, a barcode of a package is scanned and then that package is sorted and moved appropriately. This a priori knowledge facilitates package identification.

At step **518**, the package dimensions are used to match the package to the scanned barcode data, as described previously in connection with FIG. 3. The size of a package as determined from image data is compared to the predicted package size based on barcode-scanned data to determine a package match. If the match occurs, the system **100** marks (step **520**) the loaded package as identified as described in more detail below. The system **100** provides a cue to anyone entering the cargo area of a delivery vehicle as to the location and identification of packages kept within.

In addition to view screens, other package location identification methods can be used to improve the locating process. For example, as a vehicle arrives at the destination address for the delivery of a certain package, a light projector (LED, laser or other) can be used to shine focused light, or a particular color light, on the location of the package within the cargo area to show the delivery person exactly where the "matched" package is in the vehicle. The focused light can be altered to change colors, blink, flash, or shine a pattern to signal additional information to the delivery person, for example, priorities of delivery and warnings of weight, or to signify that the package of interest

11

is behind or under another package. Information is directly overlaid on the package that to be picked up, without needing any other screen or sound interface that might consume time to read or hear and consequently prolong the delivery process.

The above discussion assumes that a package that is scanned is relatively quickly matched to a package placed in the delivery vehicle. However, there may be instances where no match occurs or where a delay in matching occurs. This may occur if the package is loaded on the wrong truck, the driver scans one package but loads a different package, the driver tosses a package into the truck but not within video coverage (e.g., the package is occluded from view) or the driver's body occludes video coverage of a package.

In such situations, an embodiment of the system **100** requires a deliverable (i.e., a particular outcome) after a package is scanned. For example, if no package is detected that matches the scanned package, the system **100** may disallow further packages from being scanned, the system **100** may mark the package as scanned but unidentified, issue a warning to the loader, notify a central server of an unidentified package, or any combination thereof. The system designer may choose how rigidly to require package identification and processing (i.e., no further scanning until the package is appropriately tracked or just marking the package as scanned but with an unconfirmed loading status).

In some situations, a package may be loaded without having been scanned. This may be a loader error, where the loader places the package on the wrong truck, or may be intentional as in the case of theft. In these situations, the image processing CPU **122** still recognizes the existence of a loaded package, but there will be no "match" of the loaded package to a scanned package. Such a package may be "marked" in image streams as "unidentified", instead of with data identifying the package, and the system may issue a "warning" to the loader (visual/auditory or other) that an unidentified package is in the vehicle. The warnings may allow the loader (or driver) to correct the issue by scanning the package, placing the package in the camera view and producing an appropriately matched package. Alternatively, the system **100** may be constructed to disallow further scanning of packages if such errors occur, may issue warnings, may send the errors to the central server, or any combination thereof. In one example of an unidentified package being loaded into a delivery vehicle, the driver upon first entering the delivery vehicle may receive a notice that **300** packages have been loaded in the vehicle, but that one of the packages is "unidentified". The driver's tablet can show the location of the unidentified package, and remedial action may be suggested to, or required from, the driver. Alternatively, a distinct light (i.e., red light) may be directed onto the location where the unidentified package rests.

Detection of a package may be delayed or inhibited by occlusion of the field of view (such as the loader's body or another package). Through prediction from threshold detection from the loader position inside the vehicle cargo area and the vehicle cargo area map already stored by CPU **122**, the system **100** can compare the known map of the vehicle cargo space before the loader enters with a package with the new map of the vehicle cargo space after the loader places a package in the cargo area to determine the location of the package. Thus, even if the loader's body temporarily occludes optical tracking as the package is placed inside the cargo area, the package can be located, identified, and matched by using image frames after the loader leaves the cargo area to frames before the loader entered the cargo area.

12

In one embodiment, the system **100** performs the process **500** to track packages continuously after they have been scanned, loaded, and "matched". The process **500** enables tracking of matched packages within an area of coverage after a package has been identified ("marked"). Specifically, after a package is loaded and marked in one place, the image processing CPU **122** can regularly (or continuously) perform the same (or similar) threshold detection to search for a "change" at the location of interest. This accounts for object movement during transport.

In this scenario, the system **100** has identified packages within the area of coverage and no new packages have been scanned. This may represent when the driver is driving the vehicle to a destination. If the image processing CPU **122** detects a change at or near a package location, a tracking subroutine is invoked. The detection of a change may comprise an image absolute difference comparison between frames as previously described with respect to detailed image processing. The processor **122** analyzes the location of the package within the image at which the change occurred and determines if the package at that location still matches the data for the package captured off the barcode. If the match is identical, the system **100** may continue to label the package as corresponding to the package scanned and placed at that location.

If, however, no package is detected at the location or if the package dimensions do not match the expected package dimensions with a high level of confidence, the image processor **122** searches for an "unidentified" package that matches the moved package dimensions. When the matching package is located, its overlay marking on the cargo system is updated to display the new package location.

The above ability to identify movement of previously located packages is particularly valuable in delivery vehicles. Drivers often shift packages forward in the vehicle during the delivery day to make packages accessible. By monitoring known package locations and tracking the movement of a package to a new location, the system **100** maintains a real time map of package locations.

In another embodiment, the system **100** can be configured to reduce potential human loading errors that occur from a breakdown of a sequential loading pattern of scanning a package then loading that package immediately into truck. This reduction may be achieved by, for example, providing additional scanners over the delivery vehicle loading doors to scan bar codes automatically as packages are placed into the vehicle. Such a system can guarantee that the packages scanned are the packages loaded into the truck. After a package is scanned, it is also viewed by the optical sensors in the vehicle; that direct and almost simultaneous registration improves package identification.

In another embodiment, the system **100** can alternatively provide continuous, real time tracking, albeit with more complicated image processing. In such a system, for example, a person (loader, driver, etc.) may be identified and the system may detect objects located in the vicinity of the hands of the person to determine if the object matches the package expected to be loaded. Further, an algorithm for identifying a package or its unique identifier (size, color, etc.) may be tailored to specific environments or hardware. The tradeoff of such a full real-time tracking system is increased system complexity.

In another embodiment of the system **100**, an augmented reality ("AR") real time video view may be presented to the loader/driver. For AR video in real time, a single perspective is shown of the vehicle cargo map with those designated packages needing to be taken being highlighted or lit. The

user may view one perspective of the vehicle from the front (or back, depending on how the user is removing the packages, that is, from either the front or from the back), one perspective of the left side of the vehicle and one perspective of the right side of the vehicle associated with each camera. The image processing CPU 122 may determine where the driver/delivery person is and provide a perspective on the tablet based on the driver position in relation to the package being delivered. As previously described, identifying the user position within the area of coverage is analogous to identifying a package.

Additional package delivery data may be gathered using the present system. For example, the system 100 may track package movement in real time. Therefore, tracking package movement, especially velocity, can help prevent mistreatment of packages through packages being thrown, dropped, or placed in positions that are not secure and risk having the packages fall. By tracking packages movement in real time and determining movement velocity, impact through rough handling can be monitored and reported to improve the quality of the loading and unloading procedures and to prevent damage to the packages. In this embodiment, velocity may be determined by dividing the distance a package moves by the frame rate in which such movement occurs.

FIGS. 6A, 6B, and 6C together show an embodiment of an image-processing process 600 that uses optical information supplemented with depth information to track a package, product, or item. Specifically, as is familiar to one of ordinary skill in the art, a two-dimensional (2D) optical image capture device (i.e., a camera) with a single aperture is capable of capturing 2D image information on a plane (film, CCD, etc). To acquire three-dimensional (3D) information typically requires acquisition of additional data. Three-dimensional data can be acquired using multiple cameras or by combining one or more cameras with one or more depth sensors. Cameras can utilize visible light, infrared light, or other optical wavelength ranges. Depth sensors can be based on infrared, laser or other wavelength emitters that transmit light to an object, or to a portion of the object. Depth sensors typically determine the distance to the object, or to portion of the object, from the light that is reflected or backscattered from the object. Alternatively, depth sensors can utilize acoustic signals to determine distance. In one embodiment, depth sensing is integrated into the optical camera, for example, the KINECT™ K000949, although other devices can be used.

Referring to FIG. 6A, at step 602, frames are acquired from the camera system. A camera system with depth sensing capability typically outputs video (e.g., RGB, CYMG) and depth field information. Video may optionally be encoded to a well known format, such as MPEG. At step 604, the optical and depth information are stitched together. Open libraries such as OpenCV or OpenNI (used to capture depth images) enable the optical and depth information to be stitched together. Alternatively, a user may develop customized software for generating 3D information for object data generated by optical images and depth sensors.

At step 606, an initial calibration is performed if a calibration has not been previously performed. A function of this initial calibration, which is performed over multiple image frames, is to determine background information both for 2D optical images and depth sensing. Any motion (e.g., people) is extracted or ignored (step 608) during background extraction until stable background optical (RGB) and depth information can be stored (step 610). Calibration may optionally include creation of a foreground or front-ground region. This front region limits the data set for analysis to a

region near shelves where objects of interest (e.g., packages) are to be located. Calibration may be performed on start-up, at intervals, be initiated by the user, or by the system, for example, if errors are detected.

After calibration is complete, the resulting spatial filter masks are used to extract the “area of interest.” In one embodiment, this area of interest corresponds to the area between the background and the foreground, so everything that is not the wall and the shelves (for background) and not the person in front of the shelves, is ignored. This ignoring of the background and foreground focuses on data within the depth threshold of the area of interest being monitored. Alternatively, the “area of interest” can include a different part of the scene, for example, the foreground in order to see where the person is in later recognition steps and can be expanded or contracted as system requirements dictate. In general, the area of interest applies to any cut-out of a scene that is to be the focus within which to perform object tracking.

Multiple image frames (e.g., N-1 and N) are obtained (step 612) and compared (step 614), similarly to that performed in process 500 (FIG. 5), although the image frames in the process 600 include depth information in addition to RGB data. Image and depth information can be filtered for noise and then processed to determine if a difference between two frames exists. This can be done with edge detection, threshold and difference algorithms, or other image processing techniques. In the process 600, information from the depth sensor is also processed to compare image frames.

Referring to FIG. 6B, when no image change is found (step 618), that is, when depth and optical data remain substantially unchanged, the process 600 continues with the next temporal images received (e.g., N and N+1). When a change is detected, the process 600 determines (step 620) whether a “background” object has moved. If a background object has not moved, the process 600 continues with the next temporal images received (e.g., N and N+1). If a background object is determined to have moved, the system 100 does not have to consider a package for tracking, and further general tracking continues. In this instance, the system 100 may go back to the calibration step to establish a new stable background data set having 2D optical image and depth information.

In one embodiment, the process 600 compares two frames of image information for change, ignoring the background/foreground masks; any actual change in the image triggers further analysis. However, it is less processing and power intensive to detect only changes in the “area of interest” between the background and foreground (if foreground masking is utilized). When the background is stable, at step 622 absolute background subtraction is performed (likewise for foreground). This step allows the resulting 3D information to be processed faster for determining areas of interest in which one or more new packages may be present. Absolute image subtraction may be formed using OpenCV library modules in one embodiment, though other alternative techniques may also be used.

With the background information (and foreground if applicable) subtracted, the process 600 checks (step 624) for changes in depth of any objects in the field of view of the camera(s) and the measurement field of the depth sensor(s). If no changes are found and no package has been scanned (step 626), this indicates that no package has been detected and the next images are processed (step 602). However, if a package was scanned (step 626), but no package was detected, the process 600 can use (step 628) historical

15

optical and depth information (or information from an adjacent wireless tracking system) to register that the last scanned package has not been located, indicate the last known location of the package, and inform the user of the ambiguity.

Referring now to FIG. 6C, if at step 624 a change in the depth of one or more objects has been detected, an area of interest around that region of change is generated (step 630). In one embodiment, an area of interest is generated using a software module from the OpenCV library, though other techniques may be employed. Typically, though not necessarily, the area of interest also includes movement information or vector information that indicates object motion.

When the area of interest is determined, a “point cloud” is generated (step 632) using the optic sensor(s) extrinsic and intrinsic parameters through algorithms for “2D to 3D” data representation conversion performed on the RGB and/or depth images obtained and processed through OpenNI and OpenCV. In one embodiment, the Point Cloud Library may be used. The object shape and location information generated from the Point Cloud Library are used to identify and track a package in three dimensions using edge detection, color detection, object recognition and/or other algorithms for determining an object within the scene. If object information is in the shape of a human, for example, then the process 600 continues processing further image data and does not track the human (unless the system 100 tracks user motion). However, if the size, shape or other appearance information indicates that the object is a package, the object is recorded as such. The process 600 resolves (step 634) the identity of a plurality of scanned packages based on this information by comparing expected package size, shape and/or appearance attributes (as established by information associated with scanning a package) with measured information. The use of both optical and depth sensing information allows the system to calculate package size based on the 3D data generated from the camera images and depth sensor data. The identity, location and other information (e.g., time of placement and motion) may be stored at a central server (e.g., 204 of FIG. 2) for later analysis.

When an object is detected and matches a scanned package in size and appearance, the object is registered. A variety of reasons exist for a detected object not to match a scanned package. For example, the object may be partially occluded or a different object may have been substituted. In some instances, further analysis on subsequent image frames is performed to resolve the object size and appearance. In such instances, further image processing occurs until the object is identified or marked unidentified (step 636).

The aforementioned description of the process 600 is with respect to a positive change in an image scene: specifically, a new object is located. A “negative change” can also be detected in a similar fashion and occurs when a package is removed from an area of interest. In such a situation, a difference is not mistaking package occlusion as object removal. Specifically, if a person steps in front of a package, then the system detects the motion and shape of the person. After the person moves away from the front of the package, the image processor 122 detects if the identified package was removed. Note that the user typically scans a package when moving it, so taking a package from a location without scanning it may trigger a flag to the user to scan or identify the package.

In many situations, a second package may be placed so as to partially occlude a first registered package. In those instances, the system 100 looks for evidence based on depth and size information that the first package is still in its

16

original location. Such evidence can be a corner of the package remaining visible behind the second package. If the first package is fully occluded, but not scanned to indicate its removal, then the system 100 may be designed to assume the first package is sitting behind the larger second package.

As previously described, the system 100 detects changes in a field of view to build a database of known packages. The database is used to locate and disregard these registered packages while looking for identifying new objects being placed into the field of view. While the registered packages are “disregarded” when looking for new packages that are being loaded, they are continually monitored to see if they have moved or been removed.

The process 600 may run continuously or be triggered upon user startup, detection of motion, or other triggers. Allowing the system 100 to drop to a lower state of analysis may be desirable in some instances to reduce bandwidth and power consumption. For example, if a delivery vehicle is being loaded, then the system 100 can run at full speed with processing of images at the maximum rate described by the camera. However, after loading is complete, the system 100 can operate at intervals (for example, by processing images once every 3 seconds) to conserve power, data storage and bandwidth while meeting the requirements of the specific application.

Augmented Package Loading Techniques

Package tracking systems described herein can track packages within conventional delivery systems wherein loaders place packages on vehicles according to their perception of proper loading protocols. This perception may vary by loader, region, delivery vehicle, or other factors. Such package tracking systems can also be configured to optimize package loading in addition to delivery. In one example, the central server 204 (FIG. 2) or image processor CPU 122 (FIG. 1) may keep a list of all packages intended for placement on a particular delivery vehicle. In this example, the package identification information for each package includes the intended addressee and package size information. The intended addressees are used to generate an order of delivery that may be used to place packages in a specific order in the delivery vehicle (e.g., packages to be delivered first are put in a position of easiest access). Package size may also be a factor affecting package loading. Heavy or large packages can be located on the floor or an appropriate (i.e., low) shelf, irrespective of the delivery order.

In one embodiment, when the loader scans a package and enters the delivery vehicle with the package, the CPU 122 activates a light that shines on the location for that package. The location and matching of the package may be confirmed as previously described. A focused light may be used to identify the proper loading place for the package. The source of the light can be the same light as that used to identify a package for a driver.

In the various embodiments detailed herein, the location of a package may be “marked” or indicated in a variety of manners: by projecting light on the package of interest (unidentified package, package to be delivered, etc.), by projecting light where the package is to be loaded, by marking the position of the package on a live camera feed of the cargo bay, in a representational view of the cargo bay with the package location identified, or in a projection of the marking in augmented reality glasses.

As an example of light-based guidance for package loading, consider a system that employs conveyor belts to move packages inside a facility. As the packages are transported on the conveyor belt they are scanned for identification, either

by optical, magnetic, or electromagnetic means. After each package is identified, the system continually monitors the position of the package as it moves from one area of the facility to the end destination for transportation vehicle loading. As packages reach areas for vehicle loading, the system uses a form of light guidance to help loaders identify proper vehicle package assignment. For example, if a package is assigned to particular truck, that truck could be assigned a particular color, say blue. The package designated for the blue truck is then illuminated with a blue light, through LED, laser, or related light guidance means, thus making package vehicle identification easy for loaders. After the loader places the package in the identified delivery truck, the package tracking system can detect its presence and register its location as previously described.

One of ordinary skill in the art will recognize that other cues (visual, auditory or the like) using various technologies may be used to mark package location for easy loading, delivery or tracking of packages.

Augmented Tracking

Various embodiments of the package tracking systems described herein may benefit from additional tracking technology. For example, in the bigger areas (e.g., freight, air cargo, large shipping containers), one may incorporate other techniques to make tracking more interactive, such as Ultra-wideband (UWB) or Wireless Lan (including, but not limited to, 802.11 protocol communications or the like). Example implementations of techniques for tracking can be found in U.S. patent application Ser. No. 14/614,734, filed Feb. 5, 2015, titled "Virtual Reality and Augmented Reality Functionality for Mobile Devices," the entirety of which is hereby incorporated by reference.

In a package tracking system that augments optical tracking with UWB tracking, the driver, the driver's tablet, the packages, or all of the above, are actively tracked as described in U.S. patent application Ser. No. 15/041,405, filed Feb. 11, 2016, titled "Accurate Geographic Tracking of Mobile Devices," the entirety of which is incorporated by reference herein. In one embodiment, the position of the driver's tablet is tracked so that the viewpoint from the tablet's camera associated with the tablet location and orientation is streamed to the tablet, with digital images overlaid onto the tablet's camera view, and is used for navigation or package identification. In this example, as the tablet camera views a stack of packages, the accurate tracking of the physical position and orientation of the tablet allows the system to overlay a digital image, for example, a flashing red light, on top of the package that is seen by the tablet camera. In this case, digital images are shown on the tablet camera view, not projected onto the actual package by an external light source.

Small delivery (and other delivery modes, like airfreight, cargo containers) may use of UWB or RF (radio frequency) to improve positional accuracy tracking for when and where packages are scanned. The packages may be tracked using UWB with tags on the packages until a handoff to the camera for optically tracking inside the delivery vehicle becomes possible. This is a benefit as it reduces or eliminates the need to do optical image processing in the delivery vehicle, but still provides package ID confirmation and tracking (which may then also be re-registered via dimension data inside the delivery vehicle by the cameras).

In addition, cumulative tracking methods (i.e., optics and UWB) help track the driver and packages. For example, in dark environments, large environments or in situations involving other issues with optical coverage, it may be preferable to use UWB or related RF-based tracking to

identify initial package location, and to switch to optical scanning after package location is generally identified. In such situations, UWB tracking may augment or supplant optical tracking.

Also, in some situations, one may want to track the loader using a tag physically associated with that person. In such an environment, one may scan a package and then track the loader using UWB to make sure the package goes to the correct delivery vehicle (for instance, they may be loading multiple trucks) or, in other use cases, track the driver as the driver leaves the delivery vehicle to insure proper delivery drop off location. In the scenario where a driver is being tracked, the driver is tracked as he leaves the delivery vehicle with the GPS position known either on the delivery vehicle or on the driver. As the driver leaves the delivery vehicle, the driver is tracked and when the package is dropped off, the package is scanned and the position in relation to the delivery vehicle is recorded to show proof of delivery. As described in the aforementioned U.S. patent application Ser. No. 15/041,405, augmented reality (AR) glasses can be used to track a driver. In this scenario, the AR glasses are being tracked by a form of RF tracking, and the orientation and position of the driver may be determined by the glasses.

Example implementations of UWB or other wireless tracking systems are described disclosed in U.S. patent application Ser. No. 13/975,724, filed Aug. 26, 2013, titled "Radio Frequency Communication System", the entirety of which is incorporated by reference herein. Tracking may be implemented outside the delivery to confirm that a package that was scanned by glasses or a finger scanner is the same package that gets loaded into the delivery vehicle. In such scenarios, a loader scans the package off a conveyor belt, and the loader is tracked by the UWB system to ensure that the package scanned is the package placed in the truck or is at the proper loading area of the delivery vehicle. Thereafter, the optical tracking system tracks packages within the area of coverage.

FIG. 7 shows a diagram of an embodiment of a package tracking system 700 including an optical tracking hub 702 augmented with a radio frequency (RF) positioning system 704. The package tracking system 700 includes a user device 706 and a cloud-based central server system 708. The hub 702 is deployed in an area 710 used to hold packages, assets, objects, items, or the like, and is in communication with the cloud-based central server system 708 over a wireless communications channel (e.g., cellular) 716. Depending on the service provider for cellular PHY communications, if the holding area (e.g., delivery truck) is outside of the service area, the hub 702 buffers the data, package identification information, transactions, etc., until the holding area comes into range of a facility with secure Wi-Fi (i.e., provided, for example, by the package delivery company). For purposes of enabling customers to push or pull data from the cloud-based central server system 708, the hub provides a "Cloud" API (application program interface).

The RF positioning system 704 includes four RF nodes 712-1, 712-2, 712-3, and 712-4 (generally, 712) and an RF tag 714. The RF positioning system 704 operates to track the position of the RF tag 714, which can be affixed to the package or worn by personnel, such as a driver or package loader. In general, the RF nodes 712 provide an interface over Wi-Fi to the user device 706. The RF nodes 712 are in communication with the user device 706 via Wi-Fi, and the user device 706 is in communication with the hub 702 via Wi-Fi; in effect, the hub 702 provides an ad hoc Wi-Fi hotspot to the user device 706 and RF nodes 712.

The user device **706** is any computing device capable of running applications and wireless communications. Examples of the user device **706** include, but are not limited to, tablets and smart phones. The user device **706** can be in communication with the hub **702** over a wireless communications link **718**, with the server system **708** over a wireless communications link **720**, or both. An example implementation of the communication links **718**, **720** is Wi-Fi.

The area **710** for holding assets can be stationary or mobile. A stationary holding area can be disposed anywhere along the delivery chain, from a warehouse to a package delivery center. Examples of stationary holding areas include, but are not limited to, package rooms, closets, warehouses, inventory rooms, storage rooms, and trailers. Examples of mobile holding areas include, but are not limited to, delivery trucks, tractor trailers, railway cars, shipping containers, and airplane cargo bays. Each holding area (i.e., each facility, truck, etc.) is equipped with an optical tracking hub **702**. An example of a delivery truck than can be equipped with an optical tracking hub **702** is the standard Ford® P1000.

The RF tag **714** is in communication with the user device **706** over a wireless communication link **722**, for example, Bluetooth, and with the RF nodes **712** by way of RF signals **724**.

During operation, in general the hub **702** provides interior tracking (e.g., inside a delivery vehicle) of a package using optical techniques and the RF positioning system **704** provides exterior tracking (e.g., outside of the delivery vehicle) of the RF tag **714** using RF signals. In one embodiment, the user device **706** directly communicates with the server system **708** (e.g., in the cloud). In another embodiment, the user device **706** provides data to the hub **702**, and the hub **702** communicates with the server system **708**. In this embodiment, any feedback information from the server system **708** goes through the hub **702**, which communicates such information to the user device **706** by Wi-Fi.

FIG. **8** is a schematic for an embodiment of a package tracking system **800** including a holding area **802**, configured for optical tracking and augmented with RF tracking, in communication with a hub and power subsystem **804**. The holding area **802** includes four RF nodes **806-1**, **806-2**, **806-3**, **806-4** (generally, **806**) with antennae, three cameras (with depth sensors) **808-1**, **808-2**, **808-3** (generally, **808**), and an optional monitor or display device **810** (e.g., an HDMI video display, with or without a speaker) to provide a visual status of the system **800**. In one embodiment, the three cameras **808** are USB3-based. Each RF node **806**, camera **808**, and display device **810** is connected to a power bus **812** (e.g., a 12 VDC). The holding area **802** can also include a light projector (not shown) to shine focused light, or a particular color light, on the location within the area, to show personnel where a particular package can be currently found or where a particular package being loaded should be placed.

The hub and power subsystem **804** includes an image processor **814**, a power subsystem **816** connected to a power source **818**, and an optional charger **820**. The power subsystem **816** provides power to the image processor **814** and charger **820** by the power bus **814**. In one embodiment, the power source **818** is a battery (e.g., 12 VDC, 55 aH). An accessory power source **838** is connected to the power subsystem **816**. In communication with the image processor **814** is a cellular antenna **822**, a GPS antenna **824** and a Wi-Fi antenna **826**. The image processor **814** is also in communication with the cameras **808** by communication links **828**

and with the optional display device **810** by communication link **830**. Also shown are the user device **832**, RF tag **834**, and scanner **836**. An optional light projector external to the holding area **802** (not shown) can be used to shine light on a package before the package is loaded, for purposes of guiding a loader to the location where the package is to be loaded (e.g., a particular delivery truck).

In one embodiment, the image processor **814** is implemented with a bCOM6-L1400 Express Module produced by General Electric of Fairfield, CT. The interfaces of the image processor **814** include: at least three USB3 ports for connecting to the cameras **808** and a USB2 port for connecting to an optional light-projector gimbal; an HDMI port for connecting to the display device **810**; an integral GPS unit with the external GPS antenna; a cellular PHY card/interface (e.g., LTE, GSM, UMTS, CDMA or WCDMA, or WiMAX) with a cellular antenna jack (for an appropriate multiband cellular antenna operating at 800-950 MHz, 1800-1900, 1900-2000, 2100-2200 MHz bands, and can be a different physical antenna depending on the cellular PHY provider chosen for the given area) to enable a wireless connection to a cellular data service provider; and a Wi-Fi module with a Wi-Fi antenna jack (the antenna is omni-directional, providing 500 m of range, and operating over the 2400-2480 MHz range).

The holding area **802** can be stationary or mobile. For a mobile holding area **802**, such as a delivery truck, the RF nodes **806** can be mounted externally on the roof of the cargo area at the four corners, with the cameras **808** and display device **810** mounted internally within the holding area **802**. All of the cameras **808** are mounted near the ceiling of the truck box, facing towards the back of the truck, one camera at each front corner of the truck box, with the third camera at the front of the truck box disposed between the other two cameras. The cellular antenna **822** and Wi-Fi antenna **826** are mounted inside the truck and the GPS antenna **824** is mounted on the roof. In addition, a standard small form factor 2-axis gimbal can be mounted to the ceiling or rafter of the truck box. The gimbal provides azimuth (180 degree) and elevation angle (90 degree) positioning of the optional interior light projector (e.g., a laser pointer), which can be turned on and off. A USB2 interface of the image processor to a light projector sets the azimuth, elevation, and on/off state of the light.

The hub and power subsystem **804** can be placed within the cab of the truck, for example, behind the driver's seat. The system **800** is not attached directly to the vehicle DC power terminals, or directly to the battery of the vehicle, to avoid draining the battery of the delivery vehicle. Power subsystem **818** can connect to the accessory power **838** of the vehicle on a fuse. When the delivery vehicle is parked and off, the accessory power **838** is turned off, and the system **800** runs on the internal battery **818**. The battery **818** thus ensures that when the delivery vehicle is off (such as during package loading) the various components of the system **800** remain powered. When the vehicle is idling or in motion, the system **800** charges the battery **818**. The power subsystem **818** also provides 12 VDC and 5 VDC dedicated for the RF Nodes **806** and the cameras **808**.

For a stationary holding area **802**, the RF nodes **806** can be mounted externally near an entrance to the area **802**, with the cameras **808** and display device **810** installed inside. The hub and power subsystem **804** can also be installed inside or outside of the holding area **802**. For a stationary holding area **802**, the cellular antenna **822** and GPS antenna **824** are optional.

A schematic diagram, as shown in FIG. 8, without the RF nodes 806 and RF tag 834, can illustrate an embodiment of a package tracking system that is not augmented with RF tracking.

As will be appreciated by one skilled in the art, aspects of the systems described herein may be embodied as a system, method, and computer program product. Thus, aspects of the systems described herein may be embodied in entirely hardware, in entirely software (including, but not limited to, firmware, program code, resident software, microcode), or in a combination of hardware and software. All such embodiments may generally be referred to herein as a circuit, a module, or a system. In addition, aspects of the systems described herein may be in the form of a computer program product embodied in one or more computer readable media having computer readable program code embodied thereon.

Any combination of one or more computer readable medium(s) may be utilized. The computer readable medium may be a computer readable signal medium or a computer readable storage medium. The computer readable medium may be a non-transitory computer readable storage medium, examples of which include, but are not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device, or any suitable combination thereof.

As used herein, a computer readable storage medium may be any tangible medium that can contain or store a program for use by or in connection with an instruction execution system, apparatus, device, computer, computing system, computer system, or any programmable machine or device that inputs, processes, and outputs instructions, commands, or data. A non-exhaustive list of specific examples of a computer readable storage medium include an electrical connection having one or more wires, a portable computer diskette, a floppy disk, a hard disk, a random access memory (RAM), a read-only memory (ROM), a USB flash drive, an non-volatile RAM (NVRAM or NOVRAM), an erasable programmable read-only memory (EPROM or Flash memory), a flash memory card, an electrically erasable programmable read-only memory (EEPROM), an optical fiber, a portable compact disc read-only memory (CD-ROM), a DVD-ROM, an optical storage device, a magnetic storage device, or any suitable combination thereof.

A computer readable signal medium may include a propagated data signal with computer readable program code embodied therein, for example, in baseband or as part of a carrier wave. Such a propagated signal may take any of a variety of forms, including, but not limited to, electromagnetic, optical, or any suitable combination thereof. A computer readable signal medium may be any computer readable medium that is not a computer readable storage medium and that can communicate, propagate, or transport a program for use by or in connection with an instruction execution system, apparatus, or device. As used herein, a computer readable storage medium is not a computer readable propagating signal medium or a propagated signal.

Program code may be embodied as computer-readable instructions stored on or in a computer readable storage medium as, for example, source code, object code, interpretive code, executable code, or combinations thereof. Any standard or proprietary, programming or interpretive language can be used to produce the computer-executable instructions. Examples of such languages include C, C++, Pascal, JAVA, BASIC, Smalltalk, Visual Basic, and Visual C++.

Transmission of program code embodied on a computer readable medium can occur using any appropriate medium including, but not limited to, wireless, wired, optical fiber cable, radio frequency (RF), or any suitable combination thereof.

The program code may execute entirely on a user's device, partly on the user's device, as a stand-alone software package, partly on the user's device and partly on a remote computer or entirely on a remote computer or server. Any such remote computer may be connected to the user's device through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider).

Additionally, the methods described herein can be implemented on a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, a hard-wired electronic or logic circuit such as discrete element circuit, a programmable logic device such as PLD, PLA, FPGA, PAL, or the like. In general, any device capable of implementing a state machine that is in turn capable of implementing the proposed methods herein can be used to implement the principles described herein.

Furthermore, the disclosed methods may be readily implemented in software using object or object-oriented software development environments that provide portable source code that can be used on a variety of computer or workstation platforms. Alternatively, the disclosed system may be implemented partially or fully in hardware using standard logic circuits or a VLSI design. Whether software or hardware is used to implement the systems in accordance with the principles described herein is dependent on the speed and/or efficiency requirements of the system, the particular function, and the particular software or hardware systems or microprocessor or microcomputer systems being utilized. The methods illustrated herein however can be readily implemented in hardware and/or software using any known or later developed systems or structures, devices and/or software by those of ordinary skill in the applicable art from the functional description provided herein and with a general basic knowledge of the computer and image processing arts.

Moreover, the disclosed methods may be readily implemented in software executed on programmed general-purpose computer, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of the principles described herein may be implemented as program embedded on personal computer such as JAVA® or CGI script, as a resource residing on a server or graphics workstation, as a plug-in, or the like. The system may also be implemented by physically incorporating the system and method into a software and/or hardware system.

While the aforementioned principles have been described in conjunction with a number of embodiments, it is evident that many alternatives, modifications, and variations would be or are apparent to those of ordinary skill in the applicable arts. References to "one embodiment" or "an embodiment" or "another embodiment" means that a particular, feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment described herein. A reference to a particular embodiment within the specification do not necessarily all refer to the same embodiment. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Accordingly,

23

it is intended to embrace all such alternatives, modifications, equivalents, and variations that are within the spirit and scope of the principles described herein.

What is claimed is:

1. A package tracking system, comprising:
 - a data acquirer configured to acquire package information associated with a package being placed in a holding area;
 - at least one optical sensor disposed in or near the holding area to capture an image of the package being placed in the holding area; and
 - at least one processor configured to detect in the image a presence of an item at a location in the holding area, the at least one processor being configured to:
 - identify the item appearing in the image as the package associated with the acquired package information if a comparison between image data acquired from the image of the item and the acquired package information associated with the package satisfy a criterion between the image data and the acquired package information to confirm that the item appearing in the image is the package associated with the acquired package information, and
 - register the package as currently being at the location in the holding area where the item appeared in response to the comparison satisfying the criterion, the package tracking system further comprising:
 - a light source in the holding area, and wherein the at least one processor is further configured to cause the light source to produce light on or near the location in the holding area where the package is being placed, before or after the package is placed in the holding area.
2. The system of claim 1, wherein the holding area is within a delivery vehicle.
3. The system of claim 1, wherein a color of the light on the package or near the location of the package operates to guide placement of the package in the holding area.
4. The system of claim 1, wherein light on the package or near the location of the package operates to show where in the holding area the package resides.
5. The system of claim 1, wherein the at least one processor is further configured to communicate with a user computer, to display a real-time view of the holding area on a view screen of the user computer, and to show the registered location of the package on the real-time view displayed on the view screen of the user computer using an augmented reality marking.
6. The system of claim 1, wherein the at least one processor is further configured to communicate with a user computer, to display a graphical representation of the holding area on a view screen of a user computer, and to show the registered location of the package on the graphical representation of the holding area with a representation of the package.
7. The system of claim 1, wherein the at least one processor is configured to track movement within the holding area of the package.
8. The system of claim 1, wherein the at least one optical sensor is configured to capture images at intervals, and the at least one processor is configured to acquire and associate image data in the images captured at these intervals with the package information associated with the package in real time.
9. The system of claim 1, further comprising at least one depth sensor disposed to view the holding area; and wherein the at least one processor is configured to generate three-dimensional image data of the holding area based on two-

24

dimensional images of the holding area received from the at least one optical sensor and depth images of the holding area received from the at least one depth sensor.

10. A package tracking system, comprising:

- a data acquirer configured to acquire package information associated with a package being removed from a holding area;
 - at least one optical sensor disposed in or near the holding area to capture an image of the package being removed from the holding area; and
 - at least one processor configured to identify a registered location of the package in the holding area in response to the acquired package information, to detect in the image removal of an item from a position in the holding area, to satisfy a criterion between the image and the acquired package information to confirm that the item appearing in the image is the package associated with the acquired package information, and to confirm proper removal of the package from the holding area if the position from which the item is removed and the registered location of the package match, the system further comprising:
 - a light source in the holding area, and wherein the at least one processor is further configured to cause the light source to produce light at the registered location of the package to guide a person at the holding area to remove the package.
11. The system of claim 10, wherein the data acquirer includes an augmented reality device that reads markings of the package information.
 12. The system of claim 10, wherein the at least one processor is further configured to communicate with a user computer, to display a streamed real-time view of the holding area on a view screen of the user computer, and to show the registered location of the package in the real-time view displayed on the view screen of the user computer using an augmented reality marking.
 13. The system of claim 10, wherein the at least one processor is further configured to communicate with a user computer, to display a graphical representation of the holding area on a view screen of the user computer, and to show the registered location of the package on the graphical representation of the holding area with a representation of the package.
 14. A method of loading of a package into a holding area, the method comprising the steps of:
 - acquiring package information associated with a package being placed in the holding area;
 - acquiring, by: (i) multiple cameras, (ii) at least one camera and at least one depth sensor, or (iii) at least one camera including multiple sensors, three-dimensional (3D) image information of the holding area;
 - determining a location in the holding area for placing the package based on the package information associated with the package and the 3D image information of the holding area;
 - providing guidance to the location in the holding area for placing the package;
 - detecting, by a computer processor, in an image a presence of an item at the location in the holding area, wherein the item appearing in the image is unidentified as the package associated with the acquired package information when the presence of the item is detected;
 - identifying the item appearing in the image as the package associated with the acquired package information in response to a comparison between image data acquired

25

from the image of the item and the acquired package information associated with the package satisfying a criterion; and

registering the package as currently being at the location in the holding area where the item appeared in response 5 to the comparison satisfying the criterion.

15. The method of claim **14**, wherein the step of providing guidance to the location in the holding area for placing the package includes the step of illuminating the location in response to acquiring the package information. 10

16. The method of claim **14**, wherein step of providing guidance to the location in the holding area for placing the package includes the steps of:

displaying a streamed real-time view or a static image of the holding area on a view screen of a user computer; 15 and

showing the location of the package in the streamed real-time view or static image displayed on the view screen of the user device using an augmented reality marking. 20

17. The method of claim **14**, wherein the holding area is within a delivery vehicle.

18. The method of claim **17**, further comprising the steps of:

determining a destination of the package based on the 25 acquired package information;

designating the package for loading on the delivery vehicle based on the determined destination;

associating the delivery vehicle with a color; and

illuminating the package with light of the color associated 30 with the delivery vehicle to guide loading of the package onto that delivery vehicle.

* * * * *

26