

US012053137B2

(12) **United States Patent**
Nam et al.

(10) **Patent No.: US 12,053,137 B2**
(45) **Date of Patent: *Aug. 6, 2024**

(54) **CLEANER**

(71) Applicant: **LG Electronics Inc.**, Seoul (KR)

(72) Inventors: **Bohyun Nam**, Seoul (KR); **Namhee Kim**, Seoul (KR); **Jinju Kim**, Seoul (KR); **Hyeonjeong An**, Seoul (KR); **Jungbae Hwang**, Seoul (KR)

(73) Assignee: **LG ELECTRONICS INC.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/212,491**

(22) Filed: **Mar. 25, 2021**

(65) **Prior Publication Data**

US 2021/0204773 A1 Jul. 8, 2021

Related U.S. Application Data

(63) Continuation of application No. 16/723,785, filed on Dec. 20, 2019, now Pat. No. 10,980,380, which is a
(Continued)

(30) **Foreign Application Priority Data**

Mar. 31, 2016 (KR) 10-2016-0039814
Jun. 7, 2016 (KR) 10-2016-0070220

(51) **Int. Cl.**
A47L 5/24 (2006.01)
A47L 5/28 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A47L 5/28** (2013.01); **A47L 5/24** (2013.01); **A47L 9/00** (2013.01); **A47L 9/12** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC A47L 9/1608; A47L 9/246; A47L 9/2857;
A47L 9/1666; A47L 9/165; A47L 5/28;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,454,978 A 7/1969 Kuwahara
5,062,870 A 11/1991 Dyson et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2260428 7/2000
CA 2484587 A 4/2005
(Continued)

OTHER PUBLICATIONS

Merriam Webster, Definition of Overlap, 2014 (Year: 2014).*
(Continued)

Primary Examiner — David S Posigian


Assistant Examiner — Tyler James McFarland

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A cleaner includes: a suction unit; a suction motor that generates suction force for sucking air through the suction unit and includes an impeller; a dust separation unit that includes one or more cyclone units generating cyclonic flow to separate dust from air flowing inside through the suction unit; a dust container that stores dust separated by the dust separation unit and is disposed under the suction motor; a battery disposed behind the dust container to supply power to the suction motor; and a handle disposed behind the suction motor, wherein a rotational axis of the impeller and an axis of the cyclonic flow vertically extend and an extension line from the rotational axis of the impeller passes through the one or more cyclone units.

23 Claims, 18 Drawing Sheets



Related U.S. Application Data					
continuation of application No. 15/475,476, filed on Mar. 31, 2017, now Pat. No. 10,575,689.					
(51)	Int. Cl.		10,617,270 B2 *	4/2020	Nam A47L 9/106
	<i>A47L 9/00</i>	(2006.01)	10,729,294 B2	8/2020	Conrad et al.
	<i>A47L 9/12</i>	(2006.01)	10,736,475 B2	8/2020	Paulla et al.
	<i>A47L 9/14</i>	(2006.01)	10,912,432 B2	2/2021	Nam et al.
	<i>A47L 9/16</i>	(2006.01)	11,229,335 B2	1/2022	Conrad
	<i>A47L 9/22</i>	(2006.01)	2001/0018865 A1	9/2001	Wegelin et al.
	<i>A47L 9/28</i>	(2006.01)	2001/0027585 A1	10/2001	Lee
(52)	U.S. Cl.		2002/0189048 A1	12/2002	Maruyama et al.
	CPC	<i>A47L 9/149</i> (2013.01); <i>A47L 9/1608</i> (2013.01); <i>A47L 9/1616</i> (2013.01); <i>A47L</i> <i>9/1625</i> (2013.01); <i>A47L 9/1641</i> (2013.01); <i>A47L 9/22</i> (2013.01); <i>A47L 9/2842</i> (2013.01); <i>A47L 9/2857</i> (2013.01); <i>A47L 9/2884</i> (2013.01)	2003/0037403 A1	2/2003	Lang et al.
			2003/0066273 A1	4/2003	Choi et al.
			2003/0115713 A1	6/2003	Yang
			2003/0167590 A1	9/2003	Oh
			2004/0088819 A1	5/2004	Haffling et al.
			2004/0158952 A1	8/2004	Stein
			2004/0163201 A1	8/2004	Murphy et al.
			2004/0163207 A1	8/2004	Oh
			2004/0194250 A1	10/2004	Conrad et al.
			2004/0211025 A1	10/2004	Jung et al.
			2004/0244139 A1	12/2004	Lee
			2004/0261382 A1	12/2004	Baldinger et al.
			2005/0081321 A1	4/2005	Milligan et al.
			2005/0132528 A1	6/2005	Yau
			2005/0138763 A1	6/2005	Tanner et al.
			2005/0155177 A1	7/2005	Baer et al.
(58)	Field of Classification Search		2006/0137305 A1	6/2006	Jung
	CPC	A47L 5/24; A47L 9/1625; A47L 9/1641; A47L 9/22; A47L 9/2842; A47L 9/2884	2006/0156508 A1	7/2006	Khalil
	USPC	15/350	2006/0230715 A1	10/2006	Oh et al.
	See application file for complete search history.		2006/0254226 A1	11/2006	Jeon
(56)	References Cited		2007/0084160 A1	4/2007	Kim
	U.S. PATENT DOCUMENTS		2007/0144116 A1	6/2007	Hong et al.
	5,078,761 A	1/1992 Dyson	2007/0186372 A1	8/2007	Rowntree et al.
	5,134,749 A	8/1992 Sakurai et al.	2007/0283521 A1	12/2007	Foster et al.
	5,205,014 A	4/1993 Yoo	2008/0134460 A1	6/2008	Conrad et al.
	5,248,323 A	9/1993 Stevenson	2008/0256744 A1	10/2008	Rowntree et al.
	5,267,371 A	12/1993 Soler et al.	2009/0019663 A1	1/2009	Rowntree
	5,974,623 A	11/1999 Cummins et al.	2009/0245958 A1	10/2009	Lau et al.
	6,113,663 A	9/2000 Liu	2009/0307863 A1 *	12/2009	Milne B04C 5/08 15/344
	6,192,551 B1	2/2001 Roth	2010/0192314 A1	8/2010	Otsuka et al.
	6,482,252 B1	11/2002 Conrad et al.	2010/0205916 A1	8/2010	Yoo
	6,532,620 B2	3/2003 Oh	2010/0209271 A1	8/2010	Yoo
	6,546,592 B1	4/2003 Cockburn et al.	2010/0223751 A1	9/2010	Liddell
	6,647,587 B1	11/2003 Ohara et al.	2010/0229324 A1	9/2010	Conrad
	6,712,868 B2	3/2004 Murphy et al.	2010/0229335 A1	9/2010	Conrad
	6,782,585 B1	8/2004 Conrad et al.	2010/0242221 A1	9/2010	Horne et al.
	6,804,857 B1	10/2004 Olewiler	2010/0251507 A1	10/2010	Conrad et al.
	6,928,692 B2	8/2005 Oh et al.	2011/0016659 A1	1/2011	Dyson et al.
	7,845,046 B2	12/2010 Milligan et al.	2012/0222251 A1	9/2012	Conrad
	7,867,308 B2	1/2011 Conrad	2013/0091654 A1	4/2013	Smith
	8,146,201 B2	4/2012 Conrad	2013/0091655 A1	4/2013	Smith
	8,156,609 B2	4/2012 Milne et al.	2013/0091658 A1	4/2013	Smith
	8,302,250 B2	11/2012 Dyson et al.	2013/0091660 A1 *	4/2013	Smith A47L 9/1683 55/459.1
	8,308,832 B2	11/2012 Yoo	2013/0091661 A1	4/2013	Smith
	8,343,654 B2	1/2013 Churchill	2013/0091810 A1	4/2013	Smith
	8,486,170 B2	7/2013 Conrad et al.	2013/0091813 A1	4/2013	Smith
	8,728,186 B2	5/2014 Kim et al.	2013/0091814 A1	4/2013	Smith
	8,763,201 B2	7/2014 Kim et al.	2013/0091815 A1	4/2013	Smith
	8,925,145 B2	1/2015 Wilson	2013/0111696 A1 *	5/2013	Morgan A47L 9/0444 55/377
	9,005,325 B2	4/2015 Smith	2013/0139348 A1	6/2013	Otsuka et al.
	9,021,654 B2	5/2015 Fischer	2013/0192020 A1	8/2013	Kang
	9,089,248 B2	7/2015 Yoo	2013/0205538 A1	8/2013	Thompson
	9,451,858 B2	9/2016 Stickney et al.	2013/0207615 A1	8/2013	Sunderland et al.
	9,655,489 B2	5/2017 Ha et al.	2013/0219654 A1	8/2013	Ruben
	9,711,986 B2	7/2017 Sunderland et al.	2013/0305483 A1	11/2013	Dyson et al.
	9,757,001 B2	9/2017 Hwang et al.	2014/0020205 A1	1/2014	Makarov
	9,826,868 B2	11/2017 Conrad	2014/0041151 A1 *	2/2014	Ford A47L 9/1691 15/353
	9,848,745 B2	12/2017 Hill et al.	2014/0137362 A1	5/2014	Smith
	9,943,199 B2	4/2018 Grey et al.	2014/0137363 A1	5/2014	Wilson et al.
	9,962,047 B2	5/2018 Brown et al.	2014/0137364 A1	5/2014	Stickney et al.
	10,165,914 B2	1/2019 Conrad et al.	2014/0237758 A1	8/2014	Conrad
	10,406,535 B2	9/2019 Ni	2014/0325789 A1	11/2014	Hill et al.
	10,561,287 B2 *	2/2020 Nam A47L 9/1608	2014/0366314 A1	12/2014	Conrad
	10,568,476 B2	2/2020 Nam et al.	2014/0366495 A1	12/2014	Stickney et al.
	10,568,479 B2	2/2020 Ni	2015/0093973 A1	4/2015	Sergyeyenko et al.
	10,575,689 B2 *	3/2020 Nam A47L 9/1625	2015/0143659 A1	5/2015	Pilch
	10,582,821 B2 *	3/2020 Nam A47L 9/1675	2015/0320284 A1	11/2015	Ha et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0037987	A1	2/2016	Caro et al.
2016/0051109	A1	2/2016	Hwang et al.
2016/0088988	A1	3/2016	Eo et al.
2016/0128527	A1	5/2016	Grey et al.
2016/0270614	A1	9/2016	Kawamura et al.
2016/0270615	A1	9/2016	Kawamura et al.
2016/0287043	A1	10/2016	Ha et al.
2017/0215663	A1	8/2017	Conrad et al.
2017/0280950	A1	10/2017	Nam et al.
2017/0280951	A1	10/2017	Nam et al.
2017/0280952	A1	10/2017	Nam et al.
2017/0296007	A1	10/2017	Warren et al.
2017/0332860	A1	11/2017	Nam et al.
2018/0333022	A1	11/2018	Nam et al.
2018/0333023	A1	11/2018	Nam et al.
2018/0333024	A1	11/2018	Nam et al.
2018/0333025	A1	11/2018	Nam et al.
2018/0333026	A1	11/2018	Nam et al.
2018/0333029	A1	11/2018	Nam et al.
2018/0333030	A1	11/2018	Nam et al.
2018/0333031	A1	11/2018	Nam et al.
2018/0333032	A1	11/2018	Nam et al.
2018/0333033	A1	11/2018	Nam et al.
2021/0204772	A1 *	7/2021	Nam A47L 9/12

FOREIGN PATENT DOCUMENTS

CA	2658033	9/2010
CA	2917900	9/2010
CN	1050981 A	5/1991
CN	1323566	11/2001
CN	1377626 A	11/2002
CN	1442109 A	9/2003
CN	1456124	11/2003
CN	1530061	9/2004
CN	1541604	11/2004
CN	2684751	3/2005
CN	1739440	3/2006
CN	1864619	11/2006
CN	1889877 A	1/2007
CN	1303931	3/2007
CN	1951297 A	4/2007
CN	1951307	4/2007
CN	2920567	7/2007
CN	101023856	8/2007
CN	101057763	10/2007
CN	101248972	8/2008
CN	101288572 A	10/2008
CN	101489458	7/2009
CN	101508105	8/2009
CN	201481300	5/2010
CN	101816531	9/2010
CN	101822506	9/2010
CN	101841071	9/2010
CN	101842040	9/2010
CN	102342800	2/2012
CN	102438497	5/2012
CN	102452069	5/2012
CN	102485158 A	6/2012
CN	102613940	8/2012
CN	102755140	10/2012
CN	102813488	12/2012
CN	202699032 U	1/2013
CN	102973205	3/2013
CN	103040404	4/2013
CN	103040413	4/2013
CN	103040414 A	4/2013
CN	103156553	6/2013
CN	103169422 A	6/2013
CN	103239191 A	8/2013
CN	103247830 A	8/2013
CN	103346596	10/2013
CN	103519750	1/2014
CN	103536250 A	1/2014
CN	103784081	5/2014

CN	201410038854	5/2014
CN	103860103 A	6/2014
CN	203738747	7/2014
CN	104172986	12/2014
CN	204107201 U	1/2015
CN	204169772	2/2015
CN	104421223 A	3/2015
CN	104545695	4/2015
CN	104822301	8/2015
CN	104840152	8/2015
CN	204520530	8/2015
CN	204581145	8/2015
CN	204654807	9/2015
CN	303387623	9/2015
CN	204722978 U	10/2015
CN	105125143	12/2015
CN	105212829	1/2016
CN	105266718 A	1/2016
CN	105361812	3/2016
CN	205107552	3/2016
CN	205107553	3/2016
CN	205107554	3/2016
CN	105962846	9/2016
CN	207384196	5/2018
CN	207384197	5/2018
CN	207384198	5/2018
DE	19650749	10/1997
EP	0496837	8/1992
EP	0557096	8/1993
EP	0650690	5/1995
EP	1674018	6/2006
EP	1803381	7/2007
EP	1955630	8/2008
EP	2508265	10/2012
EP	2581017	4/2013
EP	2581018	4/2013
EP	2811885	12/2014
GB	1527034 A	10/1978
GB	2440107	1/2008
GB	2440109	1/2008
GB	2475312	5/2011
GB	2508035 A	5/2014
JP	S4842757	12/1973
JP	S4948057	4/1974
JP	S5214775	2/1977
JP	S5674643 U	6/1981
JP	H05176871	7/1993
JP	06054778	3/1994
JP	H0654778 A	3/1994
JP	H1156692	3/1999
JP	H11099097	4/1999
JP	2003199694 A	7/2003
JP	2003210370	7/2003
JP	2003290096	10/2003
JP	2007089925	4/2007
JP	3933855	6/2007
JP	2009279230	12/2009
JP	201082167	4/2010
JP	2011143209	7/2011
JP	2012050564	3/2012
JP	2012120582	6/2012
JP	2013000137	1/2013
JP	2013059525	4/2013
JP	2013071018	4/2013
JP	2013106842	6/2013
JP	2014083241	5/2014
JP	2014100571	6/2014
JP	2014100572	6/2014
JP	2014176567	9/2014
JP	2014200325	10/2014
JP	2014217758	11/2014
JP	2015034514	2/2015
JP	2015-096200	5/2015
JP	2015089478	5/2015
JP	2015119878	7/2015
JP	2015173674	10/2015
JP	2016021997	2/2016
JP	2016137095	8/2016
KR	1998013972	6/1998

(56)

References Cited

FOREIGN PATENT DOCUMENTS

KR	100237047	B1	1/2000
KR	20020031435		5/2002
KR	200291206		10/2002
KR	2003-0028999		4/2003
KR	20030058054		7/2003
KR	20030088639		11/2003
KR	1020040040092		5/2004
KR	20040080093		9/2004
KR	100474807		2/2005
KR	20050056769	A	6/2005
KR	1020060004810		1/2006
KR	100555862		3/2006
KR	100570293	B1	4/2006
KR	100595176	B1	7/2006
KR	1020060074617		7/2006
KR	100671891		1/2007
KR	100787062		12/2007
KR	101127088		4/2008
KR	100640830		11/2008
KR	1020090006821		1/2009
KR	1020090063346		6/2009
KR	10-20090079143		7/2009
KR	101606890		8/2010
KR	1020110066782		6/2011
KR	1020110106917		9/2011
KR	20110121997		11/2011
KR	1020110122699		11/2011
KR	1020110132193		12/2011
KR	1020110132196		12/2011
KR	101262385		5/2013
KR	1020140123087		10/2014
KR	1020140127305		11/2014
KR	20150047370		5/2015
KR	101539020		7/2015
KR	1020150082575		7/2015
KR	1020150125224		11/2015
KR	1020150128425		11/2015
KR	1020150133815		11/2015
KR	20160023134		3/2016
KR	1020160034041		3/2016
TW	M325088		1/2008
TW	200824633		6/2008
WO	WO2012073576		6/2012
WO	WO2013077122		5/2013
WO	WO2014162773		10/2014
WO	WO2014195711		12/2014
WO	WO2015/068817		5/2015
WO	WO2015129441		9/2015
WO	WO2016/054538		4/2016
WO	WO2017083497		5/2017
WO	WO2017/150861		9/2017
WO	WO2017181484		10/2017

OTHER PUBLICATIONS

Office Action in Chinese Appln. No. 202111240251.3, dated Jun. 2, 2022, 26 pages (with English translation).
Office Action in Japanese Appln. No. 2021-044519, dated May 25, 2022, 9 pages (with English translation).
Office Action in U.S. Appl. No. 17/212,489, dated Jun. 6, 2022, 18 pages.
United States Notice of Allowance and Fees Due in U.S. Appl. No. 16/236,804, dated May 17, 2021, 110 pages.
Office Action in Taiwanese Appln. No. 11120614350, dated Jun. 23, 2022, 24 pages (with English translation).
Office Action in Taiwanese Appln. No. 11120620150, dated Jun. 27, 2022, 22 pages (with English translation).
Korean Notice of Allowance in Korean Appln. No. KR10-2020-0093644, dated Apr. 15, 2021, 6 pages (with English translation).
Australian Office Action in Australian Application No. 2019271881, dated Oct. 30, 2020, 8 pages.
Australian Office Action in Australian Appln. No. 2019271878, dated Nov. 18, 2020, 7 pages.

Chinese Office Action in Chinese Appln. No. 10920664650, dated Jul. 14, 2020, 4 pages (with English translation).
Chinese Office Action in Chinese Appln. No. 201780020238.2, dated Apr. 3, 2020, 16 pages (with English translation).
Chinese Office Action in Chinese Appln. No. 201780021020.9, dated Jun. 19, 2020, 15 pages (with English translation).
Chinese Office Action in Chinese Appln. No. 201811324337.2, dated Jun. 2, 2020, 14 pages (with English translation).
Chinese Office Action in Chinese Appln. No. 201811324363.5, dated Jun. 5, 2020, 13 pages (with English translation).
Chinese Office Action in Chinese Appln. No. 201811324655.9, dated Jun. 5, 2020, 13 pages (with English translation).
Chinese Office Action in Chinese Appln. No. 201910114499.1, dated Aug. 19, 2020, 10 pages (with English translation).
Chinese Office Action in Chinese Appln. No. 202010940092.7, dated Feb. 5, 2021, 14 pages (with English translation).
Extended European Search Report in European Application No. 17775923.0, dated Jul. 31, 2019, 7 pages.
Extended European Search Report in European Application No. 17775919.8, dated Oct. 17, 2019, 9 pages.
International Search Report in International Application No. PCT/KR2017/003587, dated Jun. 29, 2017, 3 pages (with partial English translation).
International Search Report in International Appln. No. PCT/KR2017/003588, dated Jun. 29, 2017, 3 pages (with partial English translation).
Japanese Office Action in Japanese Application No. 2018-539344, dated Jul. 23, 2019, 6 pages.
Japanese Office Action in Japanese Appln. No. 2018-540837, dated Jun. 9, 2020, 7 pages (with English translation).
Korean Notice of Allowance in Korean Application No. 10-2018-0074685, dated Jul. 29, 2019, 2 pages.
Korean Office Action in Korean Appln. No. 10-2019-0108144, dated Jun. 22, 2020, 85 pages (with English translation).
Office Action in Australian Patent No. 2018100945, dated Sep. 17, 2018, 6 pages.
Office Action in Australian Patent No. 2018100947, dated Sep. 14, 2018, 5 pages.
Office Action in Australian Patent No. 2018100948, dated Oct. 17, 2018, 5 pages.
Office Action in Australian Patent No. 2018100949, dated Oct. 17, 2018, 5 pages.
Office Action in Australian Patent No. 2018100950, dated Sep. 14, 2018, 5 pages.
Office Action in Australian Patent No. 2018100953, dated Sep. 14, 2018, 5 pages.
Office Action in Australian Patent No. 2018100954, dated Sep. 17, 2018, 6 pages.
Office Action in Australian Patent No. 2018100966, dated Sep. 14, 2018, 5 pages.
Office Action in Australian Patent No. 2018100967, dated Sep. 7, 2018, 6 pages.
Office Action in Australian Patent No. 2018100968, dated Sep. 7, 2018, 5 pages.
Office Action in Australian Patent No. 2018100969, dated Sep. 7, 2018, 5 pages.
Office Action in Australian Patent No. 2018100970, dated Sep. 13, 2018, 5 pages.
Office Action in Australian Patent No. 2018100971, dated Sep. 7, 2018, 5 pages.
Office Action in Australian Patent No. 2018100972, dated Sep. 13, 2018, 5 pages.
Office Action in U.S. Appl. No. 15/475,476, dated Jan. 14, 2019, 9 pages.
Office Action in U.S. Appl. No. 16/050,852, dated Jan. 11, 2019, 28 pages.
Office Action in U.S. Appl. No. 16/050,883, dated Jan. 4, 2019, 16 pages.
Office Action in U.S. Appl. No. 16/050,945, dated Dec. 28, 2018, 22 pages.
Office Action in U.S. Appl. No. 16/050,956, dated Dec. 28, 2018, 20 pages.

(56)

References Cited

OTHER PUBLICATIONS

Office Action in U.S. Appl. No. 16/051,072, dated Dec. 27, 2018, 16 pages.

Office Action in U.S. Appl. No. 16/051,227, dated Jan. 14, 2019, 14 pages.

Russian Office Action in Russian Application No. 2018138167/12(063476), dated Apr. 19, 2019, 8 pages.

United States Office Action in U.S. Appl. No. 15/475,460, dated Apr. 23, 2019, 26 pages.

United States Office Action in U.S. Appl. No. 15/475,550, dated May 3, 2019, 26 pages.

United States Office Action in U.S. Appl. No. 16/723,785, dated Jul. 16, 2020, 3 pages.

United States Office Action in U.S. Appl. No. 16/777,512, dated Aug. 7, 2020, 3 pages.

United States Office Action in U.S. Appl. No. 16/777,563, dated Sep. 4, 2020, 31 pages.

United States Office Action in U.S. Appl. No. 16/777,582, dated Jul. 30, 2020, 2 pages.

CN Office Action in Chinese Appln. No. 201780020238.2, dated Jun. 17, 2021, 18 pages (with English translation).

TW Office Action in Taiwanese Appln. No. 110116620, dated Aug. 3, 2021, 11 pages (with English translation).

Office Action in U.S. Appl. No. 17/033,268, dated Nov. 12, 2021, 64 pages.

Korean Notice of Allowance in Korean Appln. No. 10-2019-0108144, dated Mar. 21, 2021, 5 pages (with English translation).

Japanese Office Action in Japanese Appln. No. 2020-022103, dated Mar. 18, 2021, 6 pages (with English translation).

United States Notice of Allowance in U.S. Appl. No. 16/919,757, dated Mar. 26, 2021, 41 pages.

Office Action in Taiwanese Appln. No. 11120254860, dated Mar. 15, 2022, 27 pages (with English translation).

United States Office Action in U.S. Appl. No. 16/777,563, dated Apr. 22, 2021, 3 pages.

Non-Final Office Action in U.S. Appl. No. 16/777,563, dated Jan. 24, 2022, 43 pages.

Non-Final Office Action in U.S. Appl. No. 16/777,582, dated Jan. 26, 2022, 22 pages.

Notice of Allowance in Chinese Appln. No. 201910114499.1, dated Jan. 6, 2022, 14 pages (with English translation).

Office Action in Chinese Appln. No. 202110452448.7, dated Jan. 21, 2022, 17 pages (with English translation).

Japanese Office Action in JP Appln. No. 2020-022102, dated Mar. 22, 2021, 4 pages (with English translation).

Office Action in Chinese Appln. No. 202110198694.4, dated Nov. 17, 2021, 14 pages (with English).

Office Action in U.S. Appl. No. 17/003,372, dated Nov. 9, 2021, 58 pages.

Office Action in Australian Appln. No. 2021201319, dated Nov. 2, 2021, 8 pages.

Extended European Search Report in European Appln. No. 22184889.8, dated Sep. 12, 2022, 7 pages.

Office Action in Chinese Appln. No. 202210021828.x, dated Aug. 17, 2022, 9 pages (with English translation).

Office Action in Chinese Appln. No. 202210021846.8, dated Aug. 18, 2022, 23 pages (with English translation).

Office Action in Chinese Appln. No. 202210022899.1, dated Aug. 26, 2022, 10 pages.

Office Action in Chinese Appln. No. 202210022906.8, dated Aug. 12, 2022, 18 pages (with English translation).

Office Action in Chinese Appln. No. 202210050454.4, dated Sep. 2, 2022, 9 ages.

Office Action in Korean Appln. No. 10-2016-0059472, dated Sep. 27, 2022, 14 pages (with English translation).

Office Action in Korean Appln. No. 10-2016-0070220, dated Sep. 5, 2022, 17 pages (with English translation).

Office Action in Korean Appln. No. 10-2021-0138950, dated Sep. 5, 2022, 13 pages (with English translation).

Extended European Search Report in European Appl. No. 22212714, mailed on Apr. 17, 2023, 7 pages.

Office Action in Chinese Appln. No. 202110455062.1, dated Mar. 10, 2023, 21 pages (with English Translation).

Office Action in European Appl. No. 22184902, mailed on Feb. 9, 2023, 44 pages.

Office Action in Japanese AppIn. No. 2021199917, dated Mar. 7, 2023, 5 pages (with English translation).

Office Action in Taiwanese Appln. No. 110135016, mailed on Mar. 31, 2023, 11 pages (with Machine translation).

Office Action in U.S. Appl. No. 16/998,784, mailed on Apr. 21, 2023, 10 pages.

Office Action in U.S. Appl. No. 17/212,489, mailed on Feb. 23, 2023, 9 pages.

Office Action in Japanese Appln. No. 2021-044519, dated Jul. 19, 2022, 10 pages (with English translation).

Office Action in Australian Appln. No. 2021269409, mailed on Dec. 2, 2022, 8 pages.

Office Action in Korean Appln. No. 10-2016-0108313, mailed on Nov. 9, 2022, 12 pages (with English translation).

Office Action in Korean Appln. No. 10-2023-0106923, mailed on Nov. 28, 2023, 17 pages (with English machine translation).

Office Action in U.S. Appl. No. 17/239,226, mailed on Dec. 18, 2023, 7 pages.

Office Action in Japanese Appln. No. 2022-196052, mailed on Sep. 26, 2023, 10 pages (with English translation).

Office Action in Korean Appln. No. 10-2016-0070220, mailed on Jul. 28, 2023, 5 pages (with English translation).

Notice of Allowance in Chinese Appln. No. 202110913524.X, mailed on Apr. 26, 2023, 10 pages (with English translation).

Office Action in U.S. Appl. No. 17/033,268, mailed on May 29, 2024, 20 pages.

* cited by examiner

Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8




Fig.9




Fig.10




Fig.11




Fig.12




Fig.13




Fig.14




Fig.15




Fig.16




Fig.17





Fig.18



1

CLEANER

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. application Ser. No. 16/723,785, filed on Dec. 20, 2019, which is a continuation application of U.S. application Ser. No. 15/475,476, filed on Mar. 31, 2017, now U.S. Pat. No. 10,575,689, which claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2016-0039814, filed in Korea on Mar. 31, 2016, and Korean Patent Application No. 10-2016-0070220, filed in Korea on Jun. 7, 2016. The disclosures of the prior applications are incorporated by reference in their entirety.

BACKGROUND

The present disclosure relates to a cleaner.

Cleaners may be classified into a manual cleaner that a user moves in person for cleaning and an automatic cleaner that automatically moves for cleaning.

Manual cleaners may fall into, depending on the types, a canister cleaner, an upright cleaner, a handy cleaner, and a stick cleaner.

Meanwhile, in the related art, a handheld vacuum cleaner has been disclosed in Korean Patent No. 10-1127088 (registered on 8 Mar. 2012).

The handheld vacuum cleaner includes a suction pipe, an airflow generator, a cyclone, a power supply, and a handle.

The cyclone is disposed between the handle and the suction pipe, the airflow generator is disposed right over the handle, and the power supply is disposed right under the handle. Accordingly, the airflow generator and the power supply are disposed behind the cyclone.

The airflow generator and the power supply are relatively heavy parts of the components.

According to this document, since the relatively heavy airflow generator and power supply are disposed right over and under the handle, respectively, the center of gravity concentrates on the handle in the entire handheld vacuum cleaner, so it is inconvenient for a user to use the handheld vacuum cleaner and the user's wrist may be injured.

Further, according to the document, since the airflow generator is disposed behind the cyclone, the channel for guiding air from the cyclone to the airflow generator is necessarily long and the air discharged from the cyclone is sent to the airflow generator with the flow direction changed, which causes a large flow loss.

Further, according to the document, since the airflow generator is disposed right over the handle, the air discharged from the airflow generator directly touches the hand holding the handle.

SUMMARY

The present disclosure provides a cleaner that users can more conveniently use by distributing the overall weight.

The present disclosure provides a cleaner in which the length of a passage from a dust separation unit to a suction motor is minimized.

The present disclosure provides a cleaner that does not discharge air that has passed through a suction motor to a user.

A cleaner includes: a suction unit; a suction motor that generates suction force for sucking air through the suction unit and includes a rotary impeller; a dust separation unit

2

that includes one or more cyclone units generating cyclonic flow to separate dust from air flowing inside through the suction unit; a dust container that stores dust separated by the dust separation unit and is disposed under the suction motor; a battery disposed behind the dust container to supply power to the suction motor; and a handle disposed behind the suction motor, wherein a rotational axis of the impeller and an axis of the cyclonic flow vertically extend and an extension line from the rotational axis of the impeller passes through the one or more cyclone units.

A cleaner includes: a suction unit; a suction motor that generates suction force for sucking air through the suction unit and includes a rotary impeller; a dust separation unit that includes one or more cyclone units generating cyclonic flow to separate dust from air flowing inside through the suction unit; a dust container that stores dust separated by the dust separation unit; a battery that supplies power to the suction motor; a handle disposed behind the suction motor; and a discharge cover that has air exits formed through the top thereof to discharge air that has passed through the suction motor, wherein an axis of the cyclonic flow passes through the discharge cover.

A cleaner includes: a suction unit that has a longitudinal axis; a suction motor that generates suction force for sucking air through the suction unit; a dust separation unit disposed to vertically overlap the suction motor in a state in which the longitudinal axis of the suction unit horizontally is positioned, and separates dust from air flowing inside through the suction unit; a dust container that has includes a dust collection body for storing dust separated from the dust separation unit and a body cover for opening and closing the dust collection body; and air exits for discharging air that has passed through the suction motor, wherein in a state in which the longitudinal axis of the suction unit is horizontally positioned, the longitudinal axis of the suction unit is positioned over the body cover and the direction in which air is sucked through the suction unit crosses the direction in which air is discharged through the air exits.

A cleaner includes: a suction unit; a suction motor that generates suction force for sucking air through the suction unit; a dust separation unit that separates dust from air flowing inside through the suction unit; a dust container that stores dust separated by the dust separation unit; a battery that supplies power to the suction motor; a handle disposed behind the suction motor; and air exits that are disposed over the suction motor to discharge air that has passed through the suction motor.

The suction motor vertically overlaps the dust separation unit.

The suction motor includes a rotary impeller and a rotational axis of the impeller vertically extends and vertically overlaps the dust separation unit and the dust container.

The suction motor includes a rotary impeller and the rotational axis of the impeller vertically extends, and an extension line from the rotational axis passes through the dust separation unit and the dust container.

The dust separation unit has one or more cyclone unit that generates cyclonic flow, and the rotational axis of the impeller and an axis of at least one cyclonic flow are positioned on the same line.

The cleaner further includes: a motor housing that receives the suction motor; and a discharge cover that is at least partially positioned over the motor housing and has the air exits.

The discharge cover includes a flow guide for discharging air discharged through the air exits at an angle from a vertical line.

The suction motor includes a rotary impeller, wherein an axis of the impeller vertically extends, and a barrier for blocking air discharged through the air exits is disposed in at least some area between the rotational axis of the impeller and the handle.

The cleaner further includes: a pre-filter that filters air discharged from the dust separation unit before the air flows into the suction motor; and an air guide that surrounds the suction motor in the motor housing and guides the air discharged from the dust separation unit to the suction motor.

The air discharged from the dust separation unit flows upward through the pre-filter, the air that has passed through the pre-filter flows back downward through the suction motor, and the air that has passed through the suction motor flows upward again and is discharged outside through the air exits.

Air discharged from the dust separation unit flows upward through the suction motor and is then discharged to the outside through the air exits.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a cleaner according to an embodiment of the present invention.

FIG. 2 is a side view of the cleaner according to an embodiment of the present invention.

FIG. 3 is a plan view of the cleaner according to an embodiment of the present invention.

FIG. 4 is a cross-sectional view of the cleaner according to an embodiment of the present invention.

FIG. 5 is a horizontal cross-sectional view of the cleaner according to an embodiment of the present invention.

FIG. 6 is a view when a discharge cover and filters have been separated in the cleaner according to an embodiment of the present invention.

FIG. 7 is a view showing a structure for receiving a HEPA (High Efficiency Particulate Air) filter in the discharge cover.

FIG. 8 is a view showing airflow in the cleaner according to an embodiment of the present invention.

FIG. 9 is a view showing a lower structure of the cleaner according to an embodiment of the present invention.

FIG. 10 is a perspective view of a body cover according to an embodiment of the present invention.

FIG. 11 is a view showing the body cover that has been rotated from the state in FIG. 9.

FIG. 12 is a view when a battery according to an embodiment of the present invention has been separated from a battery housing.

FIG. 13 is a perspective view of the battery according to an embodiment of the present invention.

FIG. 14 is a view showing a coupling groove of a battery housing according to an embodiment of the present invention.

FIG. 15 is a view when the cleaner equipped with a suction nozzle is used to sweep a floor.

FIG. 16 is a view showing a cleaner according to another embodiment of the present invention.

FIG. 17 is a view showing airflow in a cleaner according to another embodiment of the present invention.

FIG. 18 is a view showing airflow in a cleaner according to another embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Hereinafter, some embodiments of the present disclosure will be described in detail with reference to the accompa-

nying drawings. It should be noted that when components in the drawings are designated by reference numerals, the same components have the same reference numerals as far as possible even though the components are illustrated in different drawings. Further, in description of embodiments of the present disclosure, when it is determined that detailed descriptions of well-known configurations or functions disturb understanding of the embodiments of the present disclosure, the detailed descriptions will be omitted.

Also, in the description of the embodiments of the present disclosure, the terms such as first, second, A, B, (a) and (b) may be used. Each of the terms is merely used to distinguish the corresponding component from other components, and does not delimit an essence, an order or a sequence of the corresponding component. It should be understood that when one component is "connected", "coupled" or "joined" to another component, the former may be directly connected or joined to the latter or may be "connected", coupled" or "joined" to the latter with a third component interposed therebetween.

FIG. 1 is a perspective view of a cleaner according to an embodiment of the present invention, FIG. 2 is a side view of the cleaner according to an embodiment of the present invention, FIG. 3 is a plan view of the cleaner according to an embodiment of the present invention.

FIG. 4 is a vertical cross-sectional view of the cleaner according to an embodiment of the present invention and FIG. 5 is a horizontal cross-sectional view of the cleaner according to an embodiment of the present invention.

Referring to FIGS. 1 to 5, a cleaner 1 according to an embodiment of the present invention may include a main body 2.

The main body 2 may include a suction unit 5 that sucks air containing dust.

The main body 2 may further include a dust separation unit 10 for separating dust sucked inside through the suction unit 5 and a dust container 50 for storing dust separated by the dust separation unit 10.

The dust separation unit 10 may include a first cyclone unit 110 that can separate dust, for example, using cyclonic flow.

The first cyclonic unit section 110 may communicate with the suction unit 5.

The air and dust sucked through the suction unit 5 helically flow along the inner side of the first cyclone unit 110.

The axis A2 of the cyclonic flow in the first cyclone unit 110 may vertically extend.

The dust separation unit 10 may further include a second cyclone unit 130 that secondarily separates dust from the air discharged out of the first cyclone unit 110. The second cyclone unit 130 may be disposed inside the first cyclone unit 110 to minimize the size of the dust separation unit 10. The second cyclone unit 130 may include a plurality of cyclone bodies arranged in a row. Further the axis of the cyclonic flow in the cyclone bodies vertically extends and may pass through a suction motor 230.

As another example, the dust separation unit may include one cyclone unit, in which the axis A2 of the cyclonic flow may also vertically extend.

The dust container 50 may include a cylindrical dust collection body 510 and a body cover 502 rotatably coupled to the bottom of the dust collection body 510.

In this embodiment, the upper portion of the dust collection body 510 may function as the first cyclone unit 110 without a separate first cyclone unit 110.

5

At least a portion of the second cyclone unit **130** may be positioned inside the dust container **50**.

A dust storage guide **504** that guides the dust separated by the second cyclone unit **130** to be stored may be disposed in the dust collecting body **510**. The dust storage guide **504** may be coupled to the bottom of the second cyclone unit **130** in contact with the top of the body cover **520**.

The dust storage guide **504** may divide the internal space of the dust collecting body **10** into a first dust storage part **502** where the dust separated by the first cyclone unit **110** is stored and a second dust storage part **506** where the dust separated by the second cyclone unit **130** is stored.

The internal space of the dust storage guide **504** is the second dust storage part **506** and the space between the dust storage guide **504** and the dust collecting body **10** is the first dust storage part **502**.

The body cover **520** can open/close both of the first dust storage part **502** and the second dust storage part **506**.

The body cover **520** may include a rib **521** for preventing the dust in the first dust storage part **502** from being rotated by cyclonic flow. The rib **521** may extend upward from the body cover **520**. The rib **521** may be positioned close to the inner side of the dust collection body **510** when the body cover **520** covers the first and second dust storage parts **502** and **506**.

The cyclonic flow is generated along the inner side of the dust collection body **510** in the first dust storage part **502**, so when the rib **521** is positioned close to the inner side of the dust collection body **510**, the cyclonic flow is blocked by the rib **521**, whereby it is possible to prevent the dust from rotating in the first dust storage part **502**.

The main body **2** may further include a suction force generation unit **20** for generating suction force. The suction force generation unit **20** may include a motor housing **210** and a suction motor **230** disposed in the motor housing **210**.

At least a portion of the suction motor **230** may be disposed over the dust separation unit **10**. Accordingly, the suction motor **230** is disposed over the dust container **50**.

That is, the dust separation unit **10** may be arranged to vertically overlap the suction motor **230**, in a state in which the longitudinal axis of the suction unit **5** is positioned in the horizontal direction. For example, a portion of the suction motor **230** may be positioned in the first cyclone unit **110**.

The bottom of the suction motor **230** may be connected to the top of the second cyclone unit **130**. Accordingly, the axis **A2** of the cyclonic flow in the dust separation unit **10** may pass through the suction motor **230**. The suction motor **230** is positioned higher than the longitudinal axis **A3** of the suction unit **5**.

When the suction motor **230** is disposed over the second cyclone unit **130**, the air discharged from the second cyclone unit **130** can flow directly to the suction motor **230**, so the channel between the dust separation unit **10** and the suction motor **230** can be minimized.

The suction motor **230** may include a rotary impeller **232**. The impeller **232** may be fitted on a shaft **233**. The shaft **233** is vertically disposed and may be at least partially positioned in the dust separation unit **10**. In this case, when the dust container **50** and the suction motor **230** are vertically arranged, the height of the cleaner **1** can be reduced. An extension line from a rotational axis **A1** of the impeller **232** (which may be the axis of the suction motor) may pass the dust separation unit **10** and the dust container **50**.

The rotational axis **A1** of the impeller **232** and the axis **A2** of the cyclonic flow in the first cyclone unit **110** may be on the same line.

6

According to the present invention, there is the advantage that the path through which the air discharged from the dust separation unit, that is, the air discharged upward from the second cyclone unit **130** flows to the suction motor **230** can be reduced and a change in direction of air can be decreased, so a loss of airflow can be reduced.

As the loss of airflow is reduced, suction force can be increased and the lifetime of the battery **40** for supplying power to the suction motor **230** can be increased.

A PCB **250** for controlling the suction motor **230** may be disposed between the suction motor **230** and the second cyclone unit **130**. For example, the PCB **250** is accommodated within a covering **236** that covers a lower side of the suction motor **230**.

The cleaner **1** may further include a handle **30** for a user to hold and a battery **40** for supplying power to the suction motor **230**.

The handle **30** may be disposed behind the suction motor **230**. Accordingly, the axis of the suction motor **230** may be positioned between the suction unit **5** and the handle **30**.

As for directions, with respect to the suction motor **230** in the cleaner **1**, the direction in which the suction unit **5** is positioned is the front direction and the direction in which the handle **30** is positioned is the rear direction.

The battery **40** may be disposed under the handle **30**. The battery **40** may be disposed behind the dust container **50**.

Accordingly, the suction motor **230** and the battery **40** may be arranged not to vertically overlap each other and may be disposed at different heights.

According to the present invention, since the suction motor **230** that is heavy is disposed ahead of the handle **30** and the battery **40** that is heavy is disposed behind the handle **30**, so weight can be uniformly distributed throughout the cleaner **1**. It is possible to prevent injuries to the user's wrist when a user cleans with the handle **30** in his/her hand. That is, since the heavy components are distributed at the front and rear portions and at different heights in the cleaner **1**, it is possible to prevent the center of gravity of the cleaner **1** from concentrating on any one side.

Since the battery **40** is disposed under the handle **30** and the suction motor **230** is disposed in front of the handle **30**, there is no component over the handle **30**. That is, the top of the handle **30** forms a portion of the external appearance of the top of the cleaner **1**.

Accordingly, it is possible to prevent any component of the cleaner **1** from coming in contact with the user's arm while the user cleans with the handle **30** in his/her hand.

The handle **30** may include a first extension **310** extending vertically to be held by a user and a second extension **314** extending toward the suction motor **230** over the first extension **310**. The second extension **314** may at least partially horizontally extend.

A stopper **312** for preventing a user's hand holding the first extension **310** from moving in the longitudinal direction of the first extension **310** (vertically in FIG. 2) may be formed on the first extension **310**. The stopper **312** may extend toward the suction motor **230** from the first extension **310**.

The stopper **312** is spaced apart from the second extension **314**. Accordingly, a user is supposed to hold the first extension **310**, with some of the fingers over the stopper **312** and the other fingers under the stopper **312**.

For example, the stopper **312** may be positioned between the index finger and the middle finger.

In the present invention, the longitudinal axis A3 of the suction unit 5 passes through the first extension 310. The stopper 312 is positioned higher than the longitudinal axis A3 of the suction unit 5.

According to this arrangement, when a user holds the first extension 310, the longitudinal axis A3 of the suction unit 5 may pass through the user's wrist.

When the longitudinal axis A3 of the suction unit 5 passes through the user's wrist and the user's arm is stretched, the longitudinal axis A3 of the suction unit 5 may be substantially aligned with the user's stretched arm. Accordingly, there is the advantage in this state that the user uses minimum force when pushing or pulling the cleaner 1 with the handle 30 in his/her hand.

The handle 310 may include an inclined surface 315 where an operation unit 316 is disposed. It is possible to input instructions to turn on/off the cleaner through the operation unit 316. The inclined surface 315 may be formed to face a user. For example, the operation unit 380 may be formed at the rear side of the second extension 314. The operation unit 316 may be disposed opposite to the stopper 312 with the handle 30 therebetween. The operation unit 316 on the inclined surface 315 is positioned higher than the stopper 312.

Accordingly, a user can easily operate the operation unit 390 with his/her thumb with the first extension 310 in his/her hand.

Further, since the operation unit 316 is positioned outside the first extension 310, it is possible to prevent the operation unit 316 from being unexpectedly operated when a user cleans with the first extension 310 in his/her hand.

A display unit 318 for showing operational states may be disposed on the second extension 314. The display unit 318 may be, for example, disposed on the top of the second extension 314. Accordingly, a user can easily check the display unit 314 on the top of the second extension 318 while cleaning.

The display unit 318, though not limited, may include a plurality of light emitting devices. The light emitting devices may be spaced apart from each other in the longitudinal direction of the second extension 314.

A battery housing 410 is disposed under the handle 30 and the battery 40 is received in the battery housing 410. That is, the battery housing 410 is disposed under the first extension 310.

The battery 40 may be detachably combined with the battery housing 60. For example, the battery 40 may be inserted into the battery housing 60 from under the battery housing 60.

A heat discharge hole 412 for discharging heat from the battery 40 to the outside may be formed through the battery housing 410.

The rear side of the battery housing 410 and the rear side of the first extension 310 may form a continuous surface. Accordingly, the battery housing 410 and the first extension 310 can be shown like a single unit.

Referring to FIG. 3, the cleaner 1 may further include a discharge cover 211 having air exits 212 for discharging the air that has passed through the suction motor 230.

A HEPA (High Efficiency Particulate Air) filter 246 for filtering air may be disposed in the discharge cover 211. The axis of the cyclonic flow may pass through the discharge cover 211.

The air exits 212, for example, may be arranged around the rotary shaft 233 of the impeller 232. The discharge cover 210 has a flow guide 213 so that the air to be discharged through the air exits 212 is discharged at an angle from the

rotary shaft A1 of the impeller 232. The direction in which air is sucked through the suction unit 5 crosses the direction in which air is discharged through the air exits 212.

An air exit may not be formed at least in some area between the rotary shaft 233 of the impeller 232 and the handle 30 in FIG. 3 to prevent the air discharged from the air exits 212 from flowing to a user. That is, assuming that the cleaner is divided to the front and rear from the axis A2 of the cyclonic flow, some of the air exits 212 is positioned ahead of the axis A2 of the cyclonic flow.

As another example, referring to FIG. 3, a barrier for stopping air discharged from the air exits 212 may be disposed at least in some area between the rotary axis A1 of the impeller 232 and the handle 30.

FIG. 6 is a view when a discharge cover and filters have been separated in the cleaner according to an embodiment of the present invention is combined with the flow guide and FIG. 7 is a view showing a structure for receiving a HEPA (High Efficiency Particulate Air) filter in the discharge cover.

Referring to FIGS. 6 and 7, the cleaner 1 may further include a pre-filter 242 for filtering air flowing into the suction motor 230.

The pre-filter 242 may be disposed to surround a portion of the suction motor 230. The rotary shaft A1 of the impeller 232 may pass through the pre-filter 242.

The air that has passed through the pre-filter 242 flows to the impeller 232 inside the suction motor 230 and then passes through the suction motor 230. Further, the air passes through the HEPA filter 246 and then finally can be discharged outside through the air exits 212.

It should be noted that although the cleaner 1 includes the pre-filter 242 and the HEPA filter 246 in the present invention, the type and number of the filters are not limited. In this specification, the pre-filter 242 may be called a first filter and the HEPA filter 246 may be called a second filter.

The discharge cover 211 may include a receiving portion 214 for receiving the HEPA filter 246. The filter receiving portion 214 is open downward, so the HEPA filter 246 can be inserted into the receiving portion 214 from under the discharge cover 211.

Further, the air exits 212 of the discharge cover 211 face the HEPA filter 246.

When being inserted in the receiving portion 214, the HEPA filter 246 is covered by the filter cover 244. The filter cover 244 has one or more holes 244a for passing air. The filter cover 244 may be detachably coupled to the discharge cover 211.

The discharge cover 211 may be separably combined with the motor housing 210. Accordingly, it is possible to separate the discharge cover 211 from the motor housing 210 to clean the HEPA filter 246. It is possible to take the HEPA filter 246 out of the receiving portion 214 by separating the filter cover 244 from the discharge cover 211 separated from the motor housing 210.

In a state in which the discharge cover 211 is separated from the motor housing 210, the pre-filter 242 can be exposed to the outside. Accordingly, a user can clean the pre-filter 242 after separating the pre filter 242 exposed to the outside from the motor housing 210.

According to the present invention, a user can reach the HEPA filter 246 and the pre-filter 242 by separating the discharge cover 211 from the motor housing 210, he/she can easily separate and clean the filters 242 and 246.

FIG. 8 is a view showing airflow in the cleaner according to an embodiment of the present invention.

The airflow in the cleaner 1 is described with reference to FIG. 8.

Air and dust sucked through the suction unit **5** by the suction motor **230** are separated from each other while flowing along the inner side of the first cyclone unit **110**.

The dust separated from the air drops into the first dust storage part **502**. The air separated from the dust flows into the second cyclone unit **130**. The air flowing in the second cyclone unit **130** is separated again from dust.

The dust separated from the air in the second cyclone unit **130** drops into the second dust storage part **506**. On the other hand, the air separated from the dust in the second cyclone unit **130** is discharged upward to the suction motor **230** from the second cyclone unit **130**.

An air guide **215** for guiding the air discharged from the second cyclone unit **130** to the pre-filter **242** may be disposed outside the suction motor **230**. The air guide **215** surrounds the outer side of the suction motor **230** and may be at least partially spaced apart from the suction motor **230**.

Accordingly, air flows upward along the air guide **215** outside the suction motor **230** and then passes through the pre filter **242**. The air that has passed through the pre-filter **242** passes through the suction motor **230**. The air is discharged to an exhaust channel **216** between the air guide **215** and the motor housing **210** after flowing in the suction motor **230** by the impeller **232**.

The air discharged into the exhaust channel **216** passes through the HEPA filter **246** and is then discharged to the outside through the air exits **212** of the discharge cover **211**.

FIG. **9** is a view showing a lower structure of the cleaner according to an embodiment of the present invention, FIG. **10** is a perspective view of a body cover according to an embodiment of the present invention, and FIG. **11** is a view showing the body cover that has been rotated from the state in FIG. **9**.

Referring to FIGS. **9** to **11**, the body cover **520** can open/close the bottom of the dust collection body **510** by rotating.

The body cover **520** may include a hinge **522** for rotating. The hinge **522** may be coupled to the dust collection body **510** or to a separate hinge coupling portion **420** on the dust collection body **510**. When the hinge coupling portion **420** is formed separately from the dust collection body **510**, the hinge coupling portion **420** may be coupled to the dust collection body **510**.

The hinge **522** of the body cover **520** may be positioned between the axis **A2** of the cyclonic flow and the battery **40**.

Accordingly, when the body cover **520** is rotated about the hinge **522**, the body cover **520** is rotated toward a user, as in FIG. **11**.

After the body cover **520** is rotated toward a user, the body cover **520** prevents dust from flying to the user when the dust in the dust collection body **510** drops.

The body cover **520** may include a coupling lever **550** that can be moved by a user and is coupled to the dust collection body **510**. The coupling lever **550** may be coupled in parallel with the longitudinal axis **A3** of the suction unit **5**.

The body cover **520** may include a first guide **524** that can guide the coupling lever **550** and prevents the coupling lever **550** from separating downward. The first guide **524** extends downward from the body cover **520** and at least a portion of the first guide **524** is positioned under the coupling lever **550**.

The body cover **520** may further include a second guide **526** that can guide the coupling lever **550** and prevents the coupling lever **550** from separating downward. The second guide **526** protrudes from a side of the body cover **520** and may pass through the coupling lever **550**.

The second guide **526** may pass through the coupling lever **550** in parallel with the longitudinal axis **A3** of the suction unit **5**. A hole **556** for the second guide **554** may be formed in the coupling lever **550**.

The coupling lever **552** may have a ring-shaped portion **552** for a user to easily operate the coupling lever **550** by putting a finger in it. The ring-shaped portion **552** may be positioned between the hinge **522** of the body cover **520** and the axis **A2** of the cyclonic flow so that a user can easily reach the ring-shaped portion **552**.

The coupling lever **550** includes a coupling hook **556** and the dust collection body **510** may include a hook slot **514** for locking the coupling hook **556**.

The coupling hook **556** may be locked to the hook slot **514** inside the dust collection body **510**. Though not shown in the figures, an elastic member that applies elasticity to the coupling lever **550** to maintain the coupling hook **556** locked in the hook slot **514** may be disposed between the body cover **520** and the coupling lever **550**.

When a user pulls the ring-shaped portion **552** of the coupling lever **550** toward himself/herself, the coupling hook **556** is pulled out of the hook slot **514**, so the body cover **520** can be rotated.

On the other hand, the hinge coupling portion **420** may include main body terminals **600** for charging the battery **40** in the battery housing **410**. It is possible to bring charging stand terminals in contact with the main body terminals **600** by placing the cleaner **1** on a charging stand (not shown).

The main body terminals **600** are disposed on the bottom of the hinge coupling portion **420**, but can be spaced apart from the floor when the cleaner **1** is placed on the floor. Accordingly, damage to the main body terminal **600** can be prevented.

FIG. **12** is a view when a battery according to an embodiment of the present invention has been separated from a battery housing, FIG. **13** is a perspective view of the battery according to an embodiment of the present invention, and FIG. **14** is a view showing a coupling groove of a battery housing according to an embodiment of the present invention.

Referring to FIGS. **9**, and **12** to **14**, the battery may include battery cells (not shown) and a frame **450** protecting the battery cells.

A protrusion **460** is formed on the top of the frame **450** and terminals **462** may be disposed in the protrusion **460**.

The battery **40** may include a plurality of coupling portions **470** and **480**. The coupling portions **470** and **480** may include a first coupling portion **470** disposed on a first side of the frame **450** and a second coupling portion **480** disposed on a second side of the frame **450**. The first coupling portion **470** and the second coupling portion **480**, for example, may be positioned opposite to each other.

The first coupling portion **470** may be a hook rotatably coupled to the frame **450**.

The first coupling portion **470**, for example, may be coupled to the hinge coupling portion **420** when the battery **40** is inserted in the battery housing **410**. Accordingly, the hinge coupling portions **420** may be called as battery coupling portions.

A locking rib **422** for locking a portion of the hinge coupling portion **470** may be formed on the hinge coupling portion **420**.

As another example, the hinge coupling portion **420** may be integrally formed with the battery housing **410** or the locking rib **422** may be formed on the battery housing **410**.

11

The second coupling portion **480** may be a hook that is integrally formed with the frame **450** and can be deformed by external force.

An opening **411** for inserting the battery **40** is formed at the bottom of the battery housing **410**. An exposing opening **415** for exposing the second coupling portion **480** to the outside may be formed so that the second coupling portion **480** can be operated with the battery **40** in the battery housing **410**.

A coupling groove **416** for coupling the second coupling portion **480** may be formed over the exposing opening **415** in the battery housing **410**.

A space **530** for operating the first coupling portion **470** is defined between the dust container **50** and the first coupling portion **470** when the battery **40** is inserted in the battery housing **410**.

Accordingly, a user can put a finger into the space **530** and unlock the locking rib **422** from the first coupling portion **470**. Further, the user can unlock the second coupling portion **480** from the battery housing **410** by operating the second coupling portion **480** exposed to the outside of the battery housing **410**.

According to the present invention, since the battery **40** can be separated from the battery housing **410**, it is possible to place only the battery **40** on the charging stand to charge it.

Further, since the cleaner **1** includes the main body terminal **600**, it is possible to charge the battery **4** by placing the cleaner **1** on the charging stand with the battery **40** in the battery housing **410**.

FIG. **15** is a view when the cleaner equipped with a suction nozzle is used to sweep a floor.

Referring to FIG. **15**, an extension pipe **700** having a nozzle **710** extending from the lower end may be connected to the suction unit **5** of the cleaner **1** of the present invention.

In this state, a user can clean by moving the suction nozzle **710** on the floor.

When a user cleans using the suction nozzle **710** in the present invention, he/she can clean while changing the angle between the extension pipe **70** and the floor changing from about 45 degrees.

The suction motor **230** and the battery **40** may be positioned opposite to each other with a vertical line VL, which passes through the lowermost end of the dust container **50**, therebetween. That is, the suction motor **230** is positioned at a side from the vertical line VL (for example, ahead of the vertical line VL) and the battery **40** is positioned at the other side (for example, behind the vertical line VL). The vertical line VL may pass through the handle **30**.

Further, the heights of the suction motor **230** and the battery **40** from the floor are almost the same in the state shown in FIG. **15**.

Accordingly, when a user holds the handle **30** and sweeps a floor, the weight of the cleaner is balanced throughout the front and rear sides from the user's hand holding the handle, thereby maintaining weight balance. In this case, the user can clean using the cleaner **1** with small force and injuries that may be applied to the user's wrist can be prevented.

Further, in the process of sweeping the floor, as in FIG. **15**, the discharge cover **211** is positioned ahead of the vertical line VL and the user's hand holding the handle is positioned behind the vertical line VL. Accordingly, the air discharged through the discharge cover **211** flows away from the handle **30**, so it is possible to prevent the air discharged through the discharge cover **211** from flowing to the user's hand.

Obviously, only a portion of the suction motor **30** may be positioned opposite to the battery **40** with the vertical line

12

VL therebetween, depending on the angle between the extension pipe **700** and the floor. This case corresponds to cases when sweeping specific spaces such as window frames or couches.

FIG. **16** is a view showing a cleaner according to another embodiment of the present invention.

This embodiment is the same as the previous embodiment except for the shape of the discharge cover. Accordingly, only characteristic parts of this embodiment are described hereafter.

Referring to FIG. **16**, a discharge cover **211a** in this embodiment may have flow guides **213a** for guiding air to be discharged.

In detail, a plurality of flow guides **213a** is arranged with gaps in the circumferential direction of the discharge cover **211a**. The spaces between the flow guides **213a** function as air exits **212a**.

The flow guides **213a** may be inclined from a vertical line.

According to this embodiment, similarly, it is possible to prevent the air discharged from the air exits **212a** from flowing to a user while the user cleans using a suction nozzle.

Further, the discharge cover **211a** is disposed at the top of the cleaner, so it is possible to prevent dust around the cleaner from flying due to the air discharged from the air exits **212a**.

FIG. **17** is a view showing airflow in a cleaner according to another embodiment of the present invention.

This embodiment is the same as the previous embodiment except for the structure of the storage guide. Accordingly, only characteristic parts of this embodiment are described hereafter.

Referring to FIG. **17**, a dust storage guide **504** of this embodiment may at least partially taper downward. For example, a portion of the upper portion of the dust flow guide **504** may taper downward.

Further, the dust storage guide **504** may have an anti-flying rib **504a** extending downward from the upper end of the dust storage guide **504**. The anti-flying rib **504a** may be formed, for example, in a cylindrical shape and may surround the upper portion of the dust storage guide **504**.

Since the upper portion of the dust storage guide **504** tapers downward, a space is defined between the outer side of the upper portion of the dust storage guide **504** and the anti-flying rib **504a**.

As described in the previous embodiment, the cyclonic flow generated along the inner side of the dust collection body **510** may move down. When the cyclonic flow comes in contact with the rib **521** on the body cover **520** while moving down, the rotating flow can be changed into rising flow by the rib **521**. If there is rising flow in the first dust storage part **502**, the dust in the first dust storage part **502** flies upward and flows backward into the second cyclone unit **130**.

According to the present invention, rising flow in the first dust storage part **502** is changed into falling flow by the anti-flying rib **504a** in the space between the anti-flying rib **504a** and the upper portion of the dust storage guide **504**, so the dust in the first dust storage part **502** does not fly upward and accordingly it does not flow backward into the second cyclone unit **130**.

Further, since the rib **504a** extends downward from the upper end of the dust storage guide **504**, the dust separated by the cyclonic flow in the first cyclone unit **110** can be smoothly sent into the first dust storage part **502** by the anti-flying rib **504a**.

13

FIG. 18 is a view showing airflow in a cleaner according to another embodiment of the present invention.

This embodiment is the same as the previous embodiments except for the position of the impeller in the suction motor. Accordingly, only characteristic parts of this embodiment are described hereafter.

Referring to FIGS. 8 to 18, a suction motor 230a of this embodiment is disposed in a motor housing, with an impeller 232a at a lower portion therein. That is, the suction motor 230a may be positioned with an air inlet facing the second cyclone unit 130.

According to this embodiment, the air discharged from the second cyclone unit 130 directly flow upward to the impeller 232a and the air that has passed through the impeller 232a keeps flowing upward, whereby it can be discharged out of the cleaner.

According to the arrangement of the suction motor, the channel for the air that is discharged out of the cleaner from the second cyclone unit 130 is minimized, so a flow loss is minimized.

What is claimed is:

1. A cleaner comprising:

a suction guide configured to guide air into the cleaner,
a suction motor configured to generate suction force to thereby draw air into the cleaner through the suction guide;

a rotary impeller configured to rotate about a rotational axis extending in an axial direction of the suction motor and;

a dust separation unit comprising:

a first cyclone unit configured to separate dust from air that is suctioned into the cleaner through the suction guide,

a second cyclone unit configured to separate dust from air that is discharged from the first cyclone unit, an upper end of the second cyclone unit being disposed below the suction motor;

a discharge cover defining one or more air exits that are configured to discharge air that has passed through the suction motor;

a covering spaced above from the upper end of the second cyclone unit in the axial direction, the covering surrounding a lower portion of the suction motor and being configured to guide air discharged from the second cyclone unit to flow upward toward an outer circumference of the suction motor; and

a pre-filter disposed along the outer circumference of the suction motor and configured to filter the air guided from the covering, and

wherein the discharge cover, the suction motor, the covering, and the second cyclone unit are sequentially arranged to overlap with one another vertically along the axial direction of the suction motor.

2. The cleaner of claim 1, wherein the rotary impeller is positioned between the discharge cover and the suction motor, and

wherein an extension line of the rotational axis of the rotary impeller is configured to pass through the discharge cover.

3. The cleaner of claim 1, wherein in a state in which the cleaner is oriented with the rotational axis of the rotary impeller arranged longitudinally along a vertical direction, at least part of the discharge cover is disposed above the rotary impeller in the vertical direction, the rotary impeller is disposed above the suction motor, and the second cyclone unit is disposed below the suction motor in the vertical direction.

14

4. The cleaner of claim 3, wherein the pre-filter extends in a circumference direction and surrounds the outer circumference of the suction motor.

5. The cleaner of claim 4, wherein the discharge cover is disposed to overlap the pre-filter in a direction parallel to the axial direction of the suction motor.

6. The cleaner of claim 1, wherein the pre-filter is disposed to circumferentially surround at least part of the suction motor to filter the air before the air is suctioned into the suction motor.

7. The cleaner of claim 1, wherein the covering is spaced apart from the suction motor and the second cyclone unit in the axial direction.

8. The cleaner of claim 7, wherein a first surface of the covering extends in a radial direction with respect to the rotational axis and faces the second cyclone unit, the first surface being configured to guide air discharged from the second cyclone unit to flow upward to the outer circumference of the suction motor, and

wherein a second surface of the covering is disposed opposite to the first surface and faces a lower side of the suction motor.

9. The cleaner of claim 8, further comprising a printed circuit board (PCB) that is configured to control operation of the suction motor, the PCB being disposed below the suction motor and accommodated by the second surface of the covering.

10. The cleaner of claim 1, further comprising a printed circuit board (PCB) that is configured to control an operation of the suction motor and accommodated within the covering between the suction motor and the covering, wherein the covering is configured to surround the PCB in a direction toward the suction motor.

11. The cleaner of claim 4, wherein the pre-filter is disposed over the covering, and wherein the covering is configured to guide air to flow upward along a first surface of the covering to an outer circumference of the pre-filter.

12. The cleaner of claim 6, further comprising an exhaust filter accommodated within the discharge cover and configured to filter air that has passed through the suction motor, wherein the exhaust filter is configured to surround an extension line of the rotational axis of the rotary impeller.

13. The cleaner of claim 12, wherein in a state in which the cleaner is oriented with the rotational axis of the rotary impeller arranged longitudinally along a vertical direction, an upper portion of the discharge cover is vertically spaced apart from an upper end of the rotary impeller.

14. The cleaner of claim 13, wherein a void portion is defined between the upper end of the rotary impeller and the upper portion of the discharge cover.

15. The cleaner of claim 14, wherein the exhaust filter is configured to surround the void portion circumferentially with respect to the extension line of the rotational axis of the rotary impeller.

16. The cleaner of claim 15, wherein the discharge cover includes a receiving portion having a ring shape that is centered about the extension line of the rotational axis of the rotary impeller, the receiving portion being formed below the upper portion of the discharge cover, and

wherein the exhaust filter is provided in the receiving portion.

17. The cleaner of claim 16, wherein the receiving portion is configured to extend in the vertical direction along an outer periphery of the discharge cover and surround circumferentially the void portion.

15

18. The cleaner of claim **12**, further comprising a housing that receives the suction motor and configured to define an external appearance of the cleaner,

wherein the discharge cover is configured to be coupled to and separated from the housing.

19. The cleaner of claim **18**, wherein the discharge cover includes a receiving portion configured to extend in a vertical direction along an outer periphery of the discharge cover and surround the extension line of the rotational axis of the rotary impeller, and

wherein the exhaust filter is provided in the receiving portion.

20. The cleaner of claim **19**, wherein in a state where the discharge cover is removed from the housing, the exhaust filter is configured to be separated from the receiving portion of the discharge cover.

21. The cleaner of claim **18**, wherein the pre-filter is configured to be separated from the housing by removing the discharge cover from the housing.

16

22. The cleaner of claim **21**, wherein the discharge cover and the pre-filter are configured to be removed from the housing while the rotary impeller and the suction motor remain inside the housing.

23. The cleaner of claim **22**, further comprising a dust container provided under the housing, the dust container having a body cover rotatably coupled to a bottom of the dust container,

wherein:

the suction motor is provided in the housing,

the dust separation unit and the dust container vertically overlap along the rotational axis,

the body cover is configured to be opened in a lower direction along the rotational axis at the bottom of the dust container, and

the pre-filter is configured to be removed from an upper portion of the housing in an upper direction along the rotational axis.

* * * * *