



US012056552B2

(12) **United States Patent**
Nudel et al.

(10) **Patent No.:** **US 12,056,552 B2**
(45) **Date of Patent:** **Aug. 6, 2024**

(54) **DYNAMIC OPTICAL PROPERTY WINDOWS
IN INDICIA WITH SENSORS**

USPC 235/492
See application file for complete search history.

(71) Applicant: **Temptime Corporation**, Morris Plains,
NJ (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Eric A. Nudel**, Chicago, IL (US);
Mohannad Abdo, Clifton, NJ (US);
Nicholas A. Maas, Morristown, NJ
(US); **Thaddeus Prusik**, Stroudsburg,
PA (US)

3,999,946 A	12/1976	Patel et al.
4,189,399 A	2/1980	Patel
4,384,980 A	5/1983	Patel
4,646,066 A	2/1987	Baughman et al.
4,729,671 A	3/1988	Asano et al.
4,778,729 A	10/1988	Mizobuchi
4,788,151 A	11/1988	Preziosi et al.

(Continued)

(73) Assignee: **TEMPTIME CORPORATION**,
Morris Plains, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

CN	101769884	7/2010
CN	103295043	9/2013

(Continued)

(21) Appl. No.: **18/236,220**

(22) Filed: **Aug. 21, 2023**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2023/0394268 A1 Dec. 7, 2023

Windl, et al., “Reactivable passive radio-frequency identification
temperature indicator” J. Appl. Phys. 117, 17C125 (2015).

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 17/222,087, filed on
Apr. 5, 2021, now Pat. No. 11,734,539.

Primary Examiner — Michael G Lee

Assistant Examiner — David Tardif

(74) *Attorney, Agent, or Firm* — K&L Gates LLP

(51) **Int. Cl.**
G06K 19/07 (2006.01)
G06K 19/06 (2006.01)


(57) **ABSTRACT**

(52) **U.S. Cl.**
CPC ... **G06K 19/0717** (2013.01); **G06K 19/06028**
(2013.01); **G06K 19/0723** (2013.01)

An environmental exposure indicator includes a substrate
and an environmental exposure indicator (“EEI”) material
provided on the substrate that is configured to change an
optical property between a creation state and an end state.
The environmental exposure indicator material has a deploy-
ment state, between the creation state and the end state, at a
deployment time. The environmental exposure indicator
also includes calibration data based on the deployment state.

(58) **Field of Classification Search**
CPC G06K 19/0717; G06K 19/06028; G06K
19/0723

31 Claims, 13 Drawing Sheets



US 12,056,552 B2

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

4,789,637	A	12/1988	Preziosi
4,935,206	A	6/1990	Heim
5,045,283	A	9/1991	Patel
5,053,339	A	10/1991	Patel
5,057,434	A	10/1991	Prusik et al.
5,109,864	A	5/1992	Lu
5,254,473	A	10/1993	Patel
5,667,303	A	9/1997	Arens et al.
5,709,472	A	1/1998	Prusik et al.
5,827,617	A	10/1998	Krauter
6,042,264	A	3/2000	Prusik et al.
6,043,021	A *	3/2000	Manico G03C 3/00 430/617
6,070,805	A	6/2000	Kaufman et al.
6,517,239	B1	2/2003	Roth
6,614,728	B2	9/2003	Spevacek
6,642,016	B1	11/2003	Sjoholm et al.
6,685,094	B2	2/2004	Cameron
6,741,523	B1	5/2004	Bommarito et al.
6,832,729	B1	12/2004	Perry et al.
7,139,226	B2 *	11/2006	Haas G04F 1/06 368/327
7,209,042	B2	4/2007	Martin et al.
7,490,575	B2	2/2009	Taylor et al.
7,517,146	B2	4/2009	Smith et al.
7,604,398	B1	10/2009	Akers et al.
7,691,634	B2	4/2010	Vaillant
7,719,404	B2	5/2010	Makela et al.
7,878,410	B2	2/2011	Norrby et al.
8,267,576	B2	9/2012	Haarer et al.
8,395,521	B2	3/2013	Kauffman et al.
8,579,193	B2	11/2013	Nemet et al.
8,629,081	B2	1/2014	Azizian
8,671,871	B2	3/2014	Huffman et al.
8,757,503	B2	6/2014	Conzelmann
8,870,082	B2	10/2014	Cattaneo et al.
8,899,829	B1	12/2014	Butera et al.
8,957,780	B2	2/2015	Cooperman
8,968,662	B2	3/2015	Haarer et al.
9,011,794	B2	4/2015	Haarer et al.
9,546,911	B2	1/2017	Huffman et al.
9,563,798	B1	2/2017	Laser et al.
9,606,140	B2	3/2017	Burghardt
10,318,781	B2	6/2019	Prusik et al.
10,546,172	B2	1/2020	Prusik et al.
11,120,241	B2	9/2021	Abdo et al.
11,151,434	B2	10/2021	Abdo et al.
11,182,579	B2	11/2021	Prusik et al.
2003/0042317	A1	3/2003	Behm et al.
2003/0098357	A1	5/2003	Cummings et al.
2004/0092023	A1	5/2004	Wright
2004/0212509	A1	10/2004	Zweig
2005/0162274	A1	7/2005	Shniberg et al.
2006/0083657	A1	4/2006	McDonnell et al.
2006/0145863	A1	7/2006	Martin et al.
2006/0227669	A1	10/2006	Pennaz et al.
2007/0029388	A1	2/2007	Liu
2007/0058493	A1	3/2007	Kuczynski et al.
2007/0076779	A1	4/2007	Haarer
2007/0275467	A1	11/2007	Louvet
2008/0063575	A1	3/2008	Rakow et al.
2008/0173712	A1	7/2008	Nemet et al.
2008/0232427	A1	9/2008	Leute et al.
2009/0010304	A1	1/2009	Skinner et al.
2009/0020609	A1	1/2009	Cohen et al.
2009/0166438	A1	7/2009	Sanchez et al.
2010/0012018	A1	1/2010	Ribi
2011/0006109	A1	1/2011	Nemet et al.
2011/0084128	A1	4/2011	Haarer et al.
2011/0258130	A1	10/2011	Grabiner et al.
2011/0312096	A1	12/2011	Whitman et al.
2012/0079981	A1	4/2012	Huffman et al.
2012/0172825	A1	7/2012	Ales et al.
2012/0175412	A1	7/2012	Grabiner et al.
2012/0286028	A1	11/2012	Simske et al.

2012/0326878	A1	12/2012	Viguie et al.
2013/0002265	A1 *	1/2013	Martin G09F 3/0291 324/705
2013/0015236	A1	1/2013	Porter
2013/0027495	A1	1/2013	Savagian
2013/0215004	A1	8/2013	Nordlinder
2013/0224875	A1	8/2013	Haarer et al.
2014/0009605	A1	1/2014	Lane
2014/0023264	A1	1/2014	Branch et al.
2014/0127738	A1	5/2014	Lee et al.
2014/0154808	A1	6/2014	Patel
2014/0252096	A1	9/2014	Nemet
2014/0334723	A1	11/2014	Chatow et al.
2014/0339312	A1	11/2014	Simske
2015/0116093	A1	4/2015	Swager et al.
2015/0118362	A1	4/2015	Raczynski
2015/0193677	A1	7/2015	Nemet
2015/0199545	A1	7/2015	Sakina et al.
2015/0317896	A1 *	11/2015	Planton G08B 21/182 340/584
2015/0332135	A1	11/2015	Dixit
2016/0154939	A1	6/2016	Grabiner et al.
2016/0292486	A1	10/2016	Prusik et al.
2017/0193260	A1	7/2017	Prusik et al.
2017/0322090	A1 *	11/2017	Jones G01K 1/022
2019/0197377	A1	6/2019	Studnicka et al.
2019/0210806	A1	7/2019	Aida et al.
2019/0267045	A1	8/2019	Rueger et al.
2019/0316975	A1	10/2019	Tada et al.
2019/0383649	A1	12/2019	Abdo
2020/0005237	A1	1/2020	Simons
2020/0158579	A1	5/2020	Tokuda et al.
2020/0234019	A1	7/2020	Prusik et al.
2021/0034831	A1	2/2021	Abdo et al.
2021/0034933	A1	2/2021	Abdo et al.
2022/0067468	A1	3/2022	Smith et al.

FOREIGN PATENT DOCUMENTS

CN	103543146	1/2014
CN	104250715	12/2014
CN	204155296	2/2015
CN	108256607	7/2018
CN	108682283	10/2018
DE	19912529	9/2000
DE	10325714	10/2004
DE	202005006301	6/2005
DE	102006004974	8/2007
DE	102013011238	1/2015
EP	1048476	11/2000
EP	1319928	6/2003
EP	1645856	4/2006
FI	200300299	2/2003
GB	2430257	3/2007
IN	1280/CHENP/2004	5/2006
JP	2002099879	4/2002
JP	2008233909	3/2007
JP	2007285838	11/2007
JP	2013122341	6/2013
JP	5723474	5/2015
KR	101519317	5/2015
WO	WO 200550192	4/2006
WO	WO 200756752	5/2007
WO	WO 200806154	1/2008
WO	WO 200961831	5/2009
WO	WO 201061134	6/2010
WO	WO 201078422	7/2010
WO	WO 201085755	7/2010
WO	WO 201302552	1/2013
WO	WO 201390407	6/2013
WO	WO 2014027424	2/2014
WO	WO 2014102556	7/2014
WO	WO 2014153476	9/2014
WO	WO 2015113086	8/2015
WO	WO 2016160912	10/2016
WO	WO 2018000051	1/2018

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 2019206130	10/2019
WO	WO 2019241431	12/2019

OTHER PUBLICATIONS

Extended European Search Report Dated Dec. 8, 2020 Issued for European Patent Application No. 18772467.9.
Examination Report Dated Jul. 27, 2020 Issued for Australian Patent Application No. 2018239238.
Patent Office Action dated Jan. 23, 2012 issued for Korean Patent Application No. 10-2019-7031049 and English summary.
International Search Report and Written Opinion dated Aug. 5, 2016 issued for International PCT Application No. PCT/US16/24884 filed: Mar. 30, 2016.
International Search Report and Written Opinion dated Jul. 26, 2018 issued for International PCT Application No. PCT/US18/23068.
International Search Report and Written Opinion mailed Dec. 15, 2020 issued for International PCT Application No. PCT/US20/44081.
International Search Report and Written Opinion mailed Dec. 18, 2020 issued for International PCT Application No. PCT/US20/44055.
International Search Report and Written Opinion dated Oct. 10, 2019 issued for International PCT Application No. PCT/US2019/036837.

International Search Report and Written Opinion dated Aug. 3, 2022 issued for International PCT Application No. PCT/US22/21261.
R. E. Blahut, “Theory and Practice of Error Control Codes (corr. Edition)”, 1983, p. 166.
S.A. Vanstone et al., “An Introduction to Error Correcting Codes with Applications”, 1989, p. 219.
FreshCode TTI Labels—Varcode.
GSI General Specifications, V15, Issue 2, Jan. 2015, http://www.gs1.org/docs/barcodes/GS1_General_Specifications.pdf.
Tanguy, et al., “Enhanced Radio Frequency Biosensor for Food Quality Detection Using Functionalized Carbon . . .”, ACS Appl. Mater. Interfaces, 2015, 7 (22), pp. 11939-11947.
Wu, et al., “3D-printed microelectronics for integrated circuitry and passive wireless sensors”, Microsystems & Nanoengineering 1, Article No. 15013 (2015).
Yang, “3D-printed ‘smart cap’ uses electronics to sense spoiled food”, Jul. 20, 2015, UC Berkeley, <http://news.berkeley.edu/2015/07/20/3d-printed-electronic-smart-cap/>.
Wan, A new type of TTI based on an electrochemical pseudo transistor, Journal of Food Engineering, vol. 168, Jan. 2016, pp. 79-83.
News: New 3D technique . . . Aug. 15, 2015, AIPIA Active & Intelligent Packaging Industry Assoc., <http://www.aipia.info/news-New-3D-technique-Prints-Embedded-Smart-Cap--Sensor-444.php>.
<http://www.businesswire.com/news/home/20151013005396/en/3615067/Palladio-Group-Ink-Introduce-PhutureMed%E2%84%A2-Advanced-Packaging>.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3





FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11B




FIG. 11A




FIG. 12A

FIG. 12B




FIG. 13A

FIG. 13B

DYNAMIC OPTICAL PROPERTY WINDOWS IN INDICIA WITH SENSORS

CROSS-REFERENCE TO RELATED APPLICATION

The present application is a continuation application of U.S. patent application Ser. No. 17/222,087 filed on Apr. 5, 2021, the contents of which is herein incorporated by reference in its entirety.

BACKGROUND

Environmental indicators may include environmental exposure indicator materials and indicia, such as machine-readable symbols or barcodes. The indicia may be provided in static form as a printed indicia, etched indicia (e.g., laser etched), etc. Additionally, the indicia may be provided along with the environmental exposure indicator materials onto documents or media such as tags, labels, packaging, cards, or wristbands using substances such as ink, dye, paint, toner, or wax to track the environmental exposure history of products associated with such tags, etc.

SUMMARY

The present disclosure provides a new and innovative indicia with sensors (e.g., environmental exposure indicator materials) and apparatus, systems, methods and techniques for dynamically calibrating optical property windows in indicia with sensors. Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, an environmental exposure indicator includes a substrate and an environmental exposure indicator (“EEI”) material provided on the substrate that is configured to change an optical property between a creation state and an end state. The environmental exposure indicator material has a deployment state, between the creation state and the end state, at a deployment time. The environmental exposure indicator also includes calibration data based on the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is encoded in an indicia provided on the substrate.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the indicia is a barcode.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is encoded in an RFID tag coupled to the substrate.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the optical property of the EEI material changes responsive to a cumulative exposure to a first environmental condition before the deployment time and the optical property of the EEI material changes responsive to a second cumulative exposure to a second environmental condition after the deployment time.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the first environmental condition is temperature and the second environmental condition is temperature.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the optical property is reflectivity of light in the visible spectrum.

5 In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the indicator is configured for attachment to an item and the indicia further comprises data associated with the item.

10 Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, a media processing device includes a processor and an image capture assembly. The image capture assembly is configured to capture an image of a media comprising an environmental exposure indicator (“EEI”) material, analyze the captured image to detect a current optical property of the environmental exposure indicator material, determine calibration data based on the detected optical property, and encode the calibration data to the media.

20 In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, encoding includes printing an indicia on the media.

25 In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, encoding includes encoding an RFID tag in the media.

30 In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is further based on a deployment state of the EEI material.

35 In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is further based on at least one of an end state and a nominal end state of the EEI material.

40 In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is further based on deployment data.

45 In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, an optical property of the EEI material is configured to change between the current optical property and an end state optical property in response to a cumulative exposure to an environmental condition.

50 Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, a system for reading an environmental exposure indicator comprising an indicia and an environmental exposure indicator (“EEI”) material includes an image capture subsystem and a controller. The image capture subsystem is configured to capture an image of the environmental exposure indicator. The controller is configured to decode calibration data from the indicia, analyze the captured image to detect a current optical property of the EEI material, compare the detected property with the calibration data, and output an indication of the comparison. The calibration data is associated with a property of the EEI material at an earlier time.

65 Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, a system for reading an environmental exposure indicator includes a processor, a memory coupled to the pro-

cessor, and an optical input device coupled to the processor. The processor is configured to cause the optical input device to capture an image of a field of view. The field of view includes the environmental exposure indicator, which includes an indicia associated with an environmental exposure indicator material that is configured, responsive to the a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state and an end state, causing a change in an optical property of the environmental exposure indicator material. The environmental exposure indicator material has a deployment state, between the creation state and the end state, at a deployment time. The processor is further configured to store the image in the memory, process the image to identify the indicia within the captured image, and analyze the indicia to determine calibration data from the indicia based on the deployment state. The calibration data is configured to be used to adjust indications of the environmental exposure indicator provided by the environmental exposure indicator material to compensate for a difference between the deployment state and the creation state. Additionally, the calibration data includes at least one of (i) the creation data, (ii) the deployment data, and (iii) analysis data. The processor is further configured to determine an optical property associated with the environmental exposure indicator material, determine a characteristic of the environmental exposure indicator based on the calibration data and the determined optical property, and output the characteristic.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data includes a timestamp indicative of a time of manufacture of the environmental exposure material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data includes an initial optical property associated with the creation state of the environmental exposure material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is encoded within the environmental exposure indicator.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is linked to the environmental exposure indicator and obtained from an external database upon reading.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the optical property is a reflectance value, a saturation value, a color value, a color density value, an optical density value or a color hue value.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the indicia includes at least one of a symbol and a dataform.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the dataform is a machine readable symbol.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the machine readable symbol is a barcode symbol.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of

aspects listed herein, the barcode symbol is a two-dimensional barcode symbol that includes encoded data identifiers. A first data identifier indicates product life equation parameters associated with the optical property of the environmental exposure indicator material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the product life equation parameters are Arrhenius equation parameters.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the encoded data identifiers further includes a second data identifier that indicates a size and a location of the environmental exposure indicator material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the system is one of a barcode reader and a barcode scanner.

Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, a system for reading an environmental exposure indicator includes a processor, a memory coupled to the processor, and an optical input device coupled to the processor. The processor is configured to cause the optical input device to read an optical value from an environmental indicator. The environmental indicator has an optical property that changes continuously from a creation state to an end state, and a rate of change of the optical property is dependent on exposure to an environmental condition. The processor is also configured to cause the optical input device to read digital data from an indicia associated with the environmental indicator. Based on the data from the indicia indicating a respective state of the environmental indicator at a deployment time before the indicia was printed, the processor is configured to determine an amount of exposure to the environmental condition since the deployment time. Additionally, the processor is configured to determine a property of a product associated with the environmental exposure indicator. The data from the indicia is configured to provide a calibration prior to determining the property of the product, and the property of the product is based on the calibration.

Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, a method of reading an environmental exposure indicator includes scanning an indicia associated with an environmental exposure indicator material that is configured, responsive to a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state and an end state, causing a change in an optical property of the environmental exposure indicator material. The environmental exposure indicator material has a deployment state, between the creation state and the end state, at a deployment time. The method also includes determining calibration data encoded within the indicia based on the deployment state, the calibration data is configured to be used to adjust indications of the environmental exposure indicator provided by the environmental exposure indicator material to compensate for a difference between the deployment state and the creation state. Additionally, the method includes determining, at a time of scanning, an optical property associated with the environmental exposure indicator material, and determining

5

a characteristic of the environmental exposure indicator based on the calibration data and the determined optical property.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the characteristic is a remaining product life of a product associated with the environmental exposure indicator.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the indicia includes at least one of a symbol and a dataform.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the dataform is a machine readable symbol.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the machine readable symbol is a barcode symbol.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the barcode symbol is a two-dimensional barcode symbol that includes encoded data identifiers, and a first data identifier indicates product life equation parameters associated with the optical determined optical property of the environmental exposure indicator material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the product life equation parameters are Arrhenius equation parameters.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the encoded data identifiers further include a second data identifier that indicates a size and a location of the environmental exposure indicator material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the first data identifier and the second data identifier are the same data identifier.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the environmental condition is selected from the group consisting of time, temperature, time-temperature product, and cumulative time-temperature.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the environmental exposure indicator material is configured to continuously change its respective optical property between the creation state and the end state when exposed to the environmental condition.

Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, an environmental exposure indicator includes a substrate, an environmental exposure indicator material provided on the substrate, and an indicia provided on the substrate that is associated with the environmental exposure indicator. The environmental exposure indicator material is configured, responsive to a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state and an end state, causing a change in an optical property of the environmental exposure indicator material. The optical property provides exposure information indicating an amount of exposure to the environmental condition of the environmental exposure material since the environmental exposure

6

material was in the creation state. The environmental exposure indicator has a deployment state, between the creation state and the end state, at a deployment time. Additionally, the indicia is associated with calibration data based on the deployment state, and the calibration data is configured to be used to adjust indications of the cumulative environmental exposure provided by the environmental exposure material to compensate for a difference between the deployment state and the creation state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, between the creation state and the end state is inclusive of the creation state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is configured to be used to determine an optical property range based on the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the optical property range starts at the deployment state and ends at an intermediate state between the deployment state and the end state, and the intermediate state is one of a nominal end state and a calibrated end state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the intermediate state is associated with a future optical property indicative of an end of a product life.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data includes at least one of (i) creation data, (ii) deployment data, and (iii) analysis data.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the deployment state is at least one of (i) estimated based on the creation state or a nominal creation state and exposure data and (ii) measured at the deployment time.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data includes one of (i) a measured optical property at the deployment time and (ii) inputs to calculate the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data includes a link to one of (i) a measured optical property at the deployment time and (ii) inputs to calculate the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the link provides access to a database that stores at least one of (i) the measured optical property at the deployment time and (ii) the inputs to calculate the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the deployment state is associated with a current reflectance value.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the current reflectance value is determined at the deployment time, and the deployment time is when the indicia is provided on the substrate.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of

aspects listed herein, the indicia is at least one of (i) provided on the substrate along with calibration data and (ii) provided on the substrate along with a link to the calibration data.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the indicia at least one of (i) encodes the calibration data and (ii) encodes information needed to retrieve the calibration data from a data repository.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data includes a time-stamp indicative of a time of manufacture of the environmental exposure material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data includes a value of the optical property of the environmental exposure material in the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the optical property is reflectance, saturation, color, color density, optical density or a color hue.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the environmental exposure indicator material is positioned in the indicia.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the indicia includes at least one of a symbol and a dataform.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the dataform is a machine readable symbol.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the machine readable symbol is a barcode symbol.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the barcode symbol is a two-dimensional barcode symbol that includes encoded data identifiers, and a first data identifier indicates product life equation parameters associated with the optical property of the environmental exposure indicator material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the product life equation parameters are Arrhenius equation parameters.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the encoded data identifiers further include a second data identifier that indicates a size and a location of the environmental exposure indicator material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the first data identifier and the second data identifier are the same data identifier.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the environmental condition is selected from the group consisting of time, temperature, time-temperature product, and cumulative time-temperature.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the environmental exposure indicator

material is configured to continuously change its respective optical property between the creation state and the end state when exposed to the environmental condition.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the environmental exposure indicator material reaches an intermediate state between the creation state and the end state when the cumulative exposure to the environmental condition exceeds a threshold value.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the threshold value is associated with an end of a labeled product life.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the environmental exposure indicator material dynamically changes to a plurality of different states related to one of expended product life and remaining labeled product life.

Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, a device includes a processor, a memory coupled to the processor, an image sensor communicatively coupled to the processor, and an imaging subsystem communicatively coupled to the processor. The processor is configured to obtain creation data associated with an environmental exposure indicator material provided on a substrate. The environmental exposure indicator material is configured, responsive to a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state and an end state, causing a change in an optical property of the environmental exposure indicator material. The processor is also configured to obtain deployment data of the environmental exposure indicator material. The environmental exposure indicator material has a deployment state, between the creation state and the end state, at a deployment time. Additionally, the processor is configured to cause the imaging subsystem to apply an indicia on the substrate. The indicia is associated with calibration data based on the deployment state, and the calibration data is configured to be used to adjust indications of the cumulative environmental exposure provided by the environmental exposure material to compensate for a difference between the deployment state and the creation state. The calibration data includes at least one of (i) the creation data, (ii) the deployment data, and (iii) analysis data.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, obtaining deployment data includes one of (i) estimating the deployment state and (ii) measuring the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, obtaining deployment data includes causing the image sensor to read a current optical property of the environmental exposure indicator material to determine the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the deployment state is estimated based on the creation state and exposure data.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the deployment data includes one of (i) a measured optical property at the deployment time and (ii) inputs to calculate the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the deployment data includes a link to one of (i) a measured optical property at the deployment time and (ii) the inputs to calculate the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the link provides access to a database that stores at least one of (i) the measured optical property at the deployment time and (ii) the inputs to calculate the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the deployment state is associated with a current reflectance value, the current reflectance value is determined at the deployment time, and the deployment time is when the indicia is applied to the substrate.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the imaging subsystem is a print head, and causing the imaging subsystem to apply the indicia on the substrate includes causing the print head to print the indicia on the substrate.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the imaging subsystem is a laser etcher, and causing the imaging subsystem to apply the indicia on the substrate includes causing the laser etcher to etch the indicia into the substrate.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the calibration data is configured to be used to determine an optical property range based on the deployment state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the optical property range starts at the deployment state and ends at an intermediate state between the deployment state and the end state.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the intermediate state is associated with a future optical property indicative of an end of a product life.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the deployment state is associated with an optical property of the environmental exposure indicator at the deployment state as read by the image sensor.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the optical property is a reflectance value, saturation value, color value, color density value, optical density value or color hue value.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the image sensor is configured to measure the optical property to obtain the deployment data. Responsive to obtaining the deployment data, the imaging subsystem is configured to apply the indicia. Additionally, the indicia is based, at least in part, on the measured optical property.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, at least a portion of the calibration data

associated with the environmental exposure indicator material is provided on the substrate prior to supplying the device with the substrate.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the imaging subsystem is configured to at least one of (i) apply the indicia on the substrate along with calibration data and (ii) apply the indicia on the substrate along with a link to the calibration data.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the indicia at least one of (i) encodes the calibration data and (ii) encodes information needed to retrieve the calibration data from a data repository.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the creation data includes a timestamp indicative of a time of manufacture of the environmental exposure material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the image sensor is caused to read a respective optical property of the environmental exposure indicator material, and the processor is further configured to compare the respective optical property to at least a portion of the calibration data.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the processor is configured to cause the imaging subsystem to apply the indicia on the substrate such that the environmental exposure indicator material is positioned in the indicia.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the indicia includes at least one of a symbol and a dataform.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the dataform is a machine readable symbol.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the machine readable symbol is a barcode symbol.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the barcode symbol is a two-dimensional barcode symbol that includes encoded data identifiers, and a first data identifier indicates product life equation parameters associated with the optical property of the environmental exposure indicator material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the product life equation parameters are Arrhenius equation parameters.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the encoded data identifiers further include a second data identifier that indicates a size and a location of the environmental exposure indicator material.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the first data identifier and the second data identifier are the same data identifier.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the environmental condition is selected

11

from the group consisting of time, temperature, time-temperature product, and cumulative time-temperature.

In another aspect of the present disclosure, which may be used in combination with any other aspect or combination of aspects listed herein, the device is a printer.

Aspects of the subject matter described herein may be useful alone or in combination with one or more other aspects described herein. In an aspect of the present disclosure, a system for reading an environmental exposure indicator includes a light source configured to illuminate the environmental exposure indicator, an image capture subsystem, and a controller. The image capture subsystem has a two-dimensional detector and is configured to capture image data. Additionally, the image capture subsystem is configured to receive light from the environmental exposure indicator during a time period. The environmental exposure indicator includes an indicia associated with an environmental exposure indicator material that is configured, responsive to a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state and an end state, causing a change in an optical property of the environmental exposure indicator material. The environmental exposure indicator material has a deployment state, between the creation state and the end state, at a deployment time. The image capture subsystem is also configured to capture at least one image from the received light. The controller is configured to analyze one of the at least one image to decode calibration data from the indicia based on the deployment state. The calibration data is configured to be used to adjust indications of the environmental exposure indicator provided by the environmental exposure indicator material to compensate for a difference between the deployment state and the creation state. Additionally, the calibration data includes at least one of (i) the creation data, (ii) the deployment data, and (iii) analysis data. The controller is also configured to analyze one of the at least one image to detect a current optical property of the environmental exposure indicator material according to the received light and associate a characteristic of the indicia with the detected current optical property. The characteristic is based on the calibration data and the detected current optical property. The controller is also configured to output the associated characteristic.

Additional features and advantages of the disclosed system, method, and apparatus are described in, and will be apparent from, the following Detailed Description and the Figures.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1A, 1B and 1C illustrate an example environmental exposure indicator **100** through various stages of manufacturing and environmental exposure according to an example of the present disclosure.

FIGS. 2A, 2B, 2C and 2D are representations of a progression of an environmental exposure indicator material according to examples of the present disclosure.

FIG. 3 is a block diagram of an example media processing device interacting with media according to an example of the present disclosure.

FIG. 4 is a block diagram of an example system for reading an environmental exposure indicator and a corresponding environmental exposure indicator according to an example of the present disclosure.

FIG. 5 is a block diagram of an example reader according to an example of the present disclosure.

12

FIGS. 6A and 6B are representations of an environmental exposure indicator according to an example of the present disclosure.

FIGS. 7A and 7B are representations of an environmental exposure indicator (e.g., a 26×26 Data Matrix) according to an example of the present disclosure.

FIG. 8A is a representation of an environmental exposure indicator according to an example of the present disclosure.

FIG. 8B is a representation of an environmental exposure indicator (e.g., a 26×26 Data Matrix) according to an example of the present disclosure.

FIG. 9 is a representation of various examples of how calibration data is provided according to examples of the present disclosure.

FIG. 10 is a flowchart illustrating an example process for reading an environmental exposure indicator according to an example of the present disclosure.

FIG. 11A is a block diagram of an example indicia processing subsystem according to an example embodiment of the present disclosure.

FIG. 11B is flowchart illustrating example processes performed by the indicia processing subsystem according to an example embodiment of the present disclosure.

FIG. 12A is a block diagram of an example EEI material processing subsystem according to an example embodiment of the present disclosure.

FIG. 12B is flowchart illustrating example processes performed by the EEI material subsystem according to an example embodiment of the present disclosure.

FIG. 13A is a block diagram of an example calibration data processing subsystem according to an example embodiment of the present disclosure.

FIG. 13B is flowchart illustrating example processes performed by the calibration data processing subsystem according to an example embodiment of the present disclosure.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

Environmental exposure indicator materials (“EEI materials”) may be associated with indicia (e.g., machine-readable codes, such as barcodes) to create an environmental exposure indicator (“EEI”) that is applied to a product to track the product’s exposure to an environmental condition. For example, (i) temperature sensitive products, such as frozen food product(s) may include an EEI that tracks the food product’s exposure to temperatures above freezing, (ii) light sensitive products, such as film product(s) may include an EEI that tracks the film product’s exposure to UV light, (iii) moisture sensitive products, such as semiconductors and other electronic product(s) may include an EEI that tracks the electronic product’s exposure to humidity, etc.

Some example, environmental exposure indicators include HEATmarker®, available from Zebra Technologies’ Temptime Division, which is a time-temperature indicator provided as a self-adhesive label that can be applied directly to temperature sensitive products. HEATmarker® gradually changes color as heat exposure accumulates. An example peak or threshold temperature exposure indicator is the Safe-T-Vue® indicator, available from Zebra Technologies’ Temptime Division. Safe-T-Vue® indicators are nonreversible temperature indicators for blood products and temperature-sensitive biologics. The Safe-T-Vue® indicator attaches directly to a blood bag and is adapted for maintaining quality control during temporary storage and transport. In an

example, the Safe-T-Vue® indicator changes color from white to red when a specified temperature has been reached or exceeded.

In response to exposure to a specified environmental condition, the EEI materials may change state (e.g., an optical property, such as color or reflectance) to indicate the amount of exposure. For example, an EEI material may change from an initial state (e.g., white color) to an end state (e.g., red color) in response to exposure to a specified environmental condition (e.g., temperature exposure). This transition may occur gradually in response to the environmental condition over time. The EEI material may be carefully tuned so that the response of the product is similar to that of a product to be monitored, so that the EEI material transitions to a particular state at a time when the product should be judged no longer acceptable and should be discarded, rather than used. In an ideal scenario, the property, e.g., an optical property, such as reflectance, of the EEI material does not change from its initial state (e.g., reflectance value at the time of manufacturing) until the EEI material is associated with indicia (e.g., machine-readable codes, such as barcodes) to create an environmental exposure indicator (“EEI”) that is applied to a product. However, unwanted progression often occurs with the EEI material before the EEI material is associated with the indicia or a product. Specifically, after the EEI material (e.g., time-temperature sensitive material) is manufactured, the EEI material may start progressing. For example, the property, e.g., an optical property, of the EEI material may start to change due to exposure of temperature, UV light, moisture, and/or time. This unwanted progression may occur during shipping and/or storage of the EEI material. This will result in the EEI material less accurately reflecting the state of the product, and reaching the end state before the product would reach an unacceptable state, thereby causing the undesirable disposal of product that would otherwise be acceptable.

The unwanted progression may reduce the accuracy in tracking the product’s exposure to an environmental condition. In an illustrative example, a moisture sensitive EEI material that has unwanted exposure before being applied to a moisture sensitive product (e.g., a semiconductor) may not accurately track the semiconductor’s humidity exposure. Specifically, if the EEI material has already progressed 15 percent to 20 percent beyond its initial state (due to humidity exposure during storage or shipping) before being associated with an indicia to create a humidity indicator label for the semiconductor, then the semiconductor may appear to be unusable (e.g., beyond an upper threshold of humidity exposure requiring the semiconductor to be discarded) once the EEI material reaches its end state. However, since 15 to 20 percent of the humidity exposure occurred before the EEI material was associated with the semiconductor, the semiconductor is in fact still usable as the semiconductor has not yet experienced the upper limit of humidity.

In another illustrative example, a medication may become unusable after 10 minutes of exposure to temperatures above 40° F. and a temperature sensitive EEI material used to create an EEI to track the time-temperature exposure history of the medication may experience temperature exposure during shipping or storage. Specifically, the EEI material may experience some exposure (e.g., three minutes of exposure) to temperatures above 40° F. during shipping, storage, or while handling the EEI material. Once the EEI material is applied to the medication, thirty percent (e.g., three minutes of the 10 minutes of exposure to temperatures above 40° F.) of the allowable temperature exposure has already occurred. Therefore, even if the medication has only experienced

8 minutes of exposure to temperatures above 40° F., the EEI will indicate that the medication has exceeded its allowable temperature exposure thresholds (e.g., 10 or more minutes of exposure to temperatures above 40° F.) even though the medication is still usable. In the above example, the EEI material may change state (e.g., optical property, such as reflectance) based on the exposure. Specifically, the reflectance of the EEI material may be read to determine whether the associated product (e.g., medication) is usable. Thus, the premature progression of the EEI material before being applied or incorporated into an EEI to track a product disadvantageously leads to waste and inaccurate environmental tracking.

By determining a current property, e.g., an optical property such as reflectance, of the EEI material before associating the EEI material with the indicia (e.g., barcode), the current property may be used to calibrate the sensor information provided by the EEI. For example, the current reflectance, which may be estimated or measured, may be used to set a new initial reflectance (e.g., initial state of the EEI material) and a new endpoint reflectance (e.g., end state of the EEI material), which typically differ from the initial reflectance and endpoint reflectance at the time of the EEI material is manufactured. Furthermore, by setting the new initial reflectance and the new endpoint reflectance, the full reference window for the EEI is advantageously restored thereby providing more accurate readings throughout the EEI’s and associated product’s life. The new initial reflectance and the new endpoint reflectance may be stored as calibration data that is then dynamically stored in the indicia (e.g., barcode). For example, if the indicia is a barcode, the barcode may include the calibration data such that when scanned, the barcode is capable of calibrating a reader, such that the reader determines an output from the environmental sensor based on environmental history since the deployment time instead of since the time of manufacturing.

As used herein, an “EEI material” refers to a material that changes state in a detectable way in response to a predetermined environmental condition. In an example, the “EEI material” is configured to undergo a continuous chemical or physical state change between a “creation state” and an “end state”. The change of state may be a change in a property, e.g., an optical property, such as a reflectance value, saturation value, color value, color density value, optical density value or color hue value of the “EEI material”. Specifically, the state change (e.g., optical property change) provides exposure information indicating an amount of exposure to the environmental condition of the EEI material since the EEI was in the “creation state.”

As used herein, exposure to an “environmental condition” is exposure to conditions such as temperature (e.g., heat), moisture (e.g., humidity), light (e.g., UV), etc.

As used herein, “creation state” refers to a state of the EEI material at a time of creation (e.g., when the EEI material is manufactured). For example, the EEI material may be applied to a roll or strip of printable media, which is then shipped to customers for creating EEIs. As soon as the EEI material is applied to the printable media, the EEI material may start changing based on environmental exposure.

As used herein, “end state” refers to a state of the EEI material that is indicative of a maximum environmental exposure for the EEI material. Specifically, in the “end state” there is no more discernable progression (e.g., change in an optical property) of the EEI material once the EEI material is in the end state. In an example, the “end state” may be indicative of an end of life of a product. However, in many cases, the “end state” may be a state beyond a “threshold end

15

state” that is indicative of the end of life of a product. For example, the EEI material may reach a “threshold end state”, which is near the true “end state”, but any progression beyond the “threshold end state” may be difficult to discern and therefore may be deemed unusable for commercial purposes. Depending on the composition of the EEI material and its progression characteristics, the “end state” and the “threshold end state” may be the same state.

As used herein, “deployment state” refers to a state of the EEI material at a “deployment time” (e.g., the time the EEI material is created into an EEI and associated with a product. The “deployment state” may be any state between, and including the “creation state” and the “end state”. In an example where the EEI is created immediately after the EEI material is created, the “deployment state” may be the same as the “creation state”.

As used herein, “deployment time” refers to the time the EEI material is used to create an EEI and associated with a product.

As used herein, “calibrated end state” refers to a state of the EEI material that is indicative of a maximum allowable environmental exposure for a product. For example, once the EEI material progresses from the “deployment state” to the “calibrated end state”, that is the maximum amount of environmental exposure for the associated product according to a reader that is calibrated by “calibration data”.

As used herein, “nominal” refers to a state that is predetermined or selected by a user. Specifically, a “nominal creation state” may be selected such that there is a buffer between the “creation state” and the “nominal creation state”. Similarly, a “nominal end state” may be selected such that there is a buffer between the “end state” and the “nominal end state”. The “nominal creation state” and the “nominal end state” may be interpreted by a reader, scanner or other image capture device as the “creation state” and the “end state” as opposed to the actual state of the indicator. Specifically, the reader, scanner or other image capture device may interpret the “EEI material” in terms of its transition between the “nominal creation state” and the “nominal end state”.

As used herein, “calibration data” refers to any “creation data”, “deployment data” and/or “analysis data”.

As used herein, “creation data” refers to any data associated with the EEI material at the time of creation. The “creation data” may include a timestamp, the property, e.g., an optical property, of the EEI material in the “creation state”, the estimated “end state”, etc.

As used herein, “deployment data” refers to any data associated with the EEI material at the “deployment time”. The “deployment data” may include a timestamp, the property, e.g., an optical property, of the EEI material in the “deployment state”, the estimated “calibrated end state”, etc.

As used herein, “analysis data” refers to any data associated with analyzing optical properties of the EEI material and associating the property, e.g., an optical property, with a product characteristic, such as lifetime, usable life, etc.

As used herein, a “barcode symbol” is a machine-readable pattern encoding data. The barcode symbol is one type of dataform. Other types or examples of dataforms include text, numbers, graphics, etc. Text is a dataform representing written language, numbers are dataforms representing arithmetical values, and graphics are dataforms representing images.

A barcode symbol may be made up of one or more barcode elements, which may be referred to as a barcode module. An element or module is a set of contrasting patterns that are arranged on a substrate to facilitate decod-

16

ing data by a barcode reader or scanner. A barcode element or module may describe both a “black” box and a “white” box, or a “light absorbing” box and a “light reflective” box. In other examples, a barcode element or module may also describe a “light emitting” element. Some barcode symbols include quiet space(s), a region surrounding a set of elements or modules, which is free of contrasting marks, to enable the barcode reader to detect the barcode symbol in a captured image. Some barcode symbols include elements or modules, called finder patterns, that provide a consistent pattern to enable the barcode reader to detect the barcode symbol in a captured image.

The manner in which data is encoded in the barcode symbol, the arrangement of the barcode elements or modules within the barcode symbol, and any requirements for elements or modules and quiet space are defined by a set of rules, known as a barcode symbology. Data may be encoded into the contrasting patterns by software, such as a computer application or printer firmware.

Barcode symbols, which may be generally referred to herein as barcodes, may be displayed on a screen or marked on a substrate. Barcode elements or modules may be marked on a substrate with a variety of printing or imaging methods and techniques. Black bars (rectangles, squares, circles, or triangles, or other shapes are generally called bars, or elements, in a barcode) may be printed on a white or mirrored substrate to create the contrasting pattern of an element or module. Similarly, white patterns may be printed on a black or transparent substrate to create the contrasting pattern of an element or module. In either case, a barcode reader would capture an image of the barcode by receiving light reflected from the white portions of the element or module at a greater intensity than light reflected from the black portions of the element or module. The contrasting intensity pattern of the captured image is then processed by the barcode reader to decode the data carried by the barcode. In some embodiments, a reflective or mirrored surface may provide the contrasting pattern. Barcode elements or modules may also be marked on a substrate by etching or denting a smooth surface; in this case light is received at different intensities from a smooth surface than the textured surface.

In some embodiments, the contrasting pattern comprises two different visible colors. The two different visible colors reflect light of different frequencies. Barcode readers receive and filter the light then process the captured image to decode the data carried by the barcode. Either or both intensity and frequency of the received light may be processed to decode the data. In some embodiments, the contrasting pattern received by the barcode reader comprises at least one light emitted by the barcode. For instance, an electronic screen may display a barcode element or module using at least two different visible colors to create the contrasting pattern; the barcode reader receives and filters the light then processes the captured image to decode the data. An electronic screen may flash a rendition of an element or module, a barcode, or of multiple barcodes to exchange data with the barcode reader.

EEI materials, such as inks, toners, dyes, paints, waxes and other coatings, may be provided on products, packaging, and labels due to the increasing need for monitoring environmental exposure experienced by products through the supply chain. The EEI material may change state, e.g., by either changing color, reflectance or some other property, e.g., optical property, when exposed to particular environmental condition. The environmental condition(s) required to trigger the state change, color change or change in optical property may vary. The EEI materials may be provided on

labels, tags or other sensors to monitor or track environmental exposure for the product associated with the label, tag or other sensor.

The apparatus, systems, methods and techniques described herein discuss calibration of EEI materials after incorporating the EEI materials, such as a temperature exposure indicator materials with labels, barcodes, etc. The EEI material may form an EEI or an EEI indicia. The EEI material may also be referred to as an active material or a dynamic material.

The EEI material may be incorporated in or used in conjunction with labels, barcodes, etc. For example, media such as tags, labels, cards, wristbands, and/or ribbons containing this EEI material can be used in conjunction with printers, displays, vision systems, and hand-held devices (e.g., for reading and verification). The EEI material may be utilized to provide environmental exposure tracking on products carrying labels or indicia, such as 2D barcodes, to enhance environmental exposure traceability.

FIGS. 1A-1C illustrate an example environmental exposure indicator **100** in various stages of the manufacturing process and at different levels of exposure to an environmental condition. FIG. 1A illustrates an environmental exposure indicator (“EEI”) material **120** provided on a substrate **110**. As illustrated in FIG. 1A, the EEI material **120** is in a creation state before the EEI material **120** is associated with an indicia (e.g., indicia **130a** and/or indicia **130b**, hereinafter referred to generally as indicia **130**) or used to create an EEI **100**. Once the EEI material **120** is used to create an EEI **100**, as illustrated in FIG. 1B, the EEI **100** is in the deployment state at a deployment time. As illustrated in FIG. 1B, the EEI material **120** has shown progression from its creation state illustrated in FIG. 1A to the deployment state illustrated in FIG. 1B. Specifically, the deployment state or the state at the deployment time may represent the time the EEI material **120** is associated with other data or indicia **130** thereby creating an EEI **100** that is attached to a product. The environmental progression that occurs between FIG. 1A and 1B may be due to environmental exposure that the EEI material **120** experiences during storage, shipping, etc. prior to being associated with indicia **130**. In one example, the substrate **110** may be a roll or strip of paper that includes the EEI material **120**, which is then shipped to a customer to create an EEI **100**.

For example, the EEI **100** illustrated in FIG. 1B may be used to create a label or tag that is applied to a product such that the EEI **100** can track the environmental exposure history the product experiences throughout the supply chain. FIG. 1C illustrates the EEI **100** after deployment while the EEI **100** is applied to the product. As illustrated in FIG. 1C, the EEI material **120** appears even darker than in FIG. 1B, which indicates that the product, and more specifically the EEI material **120**, has experienced additional exposure to the specific environmental condition that the EEI material **120** is sensitive to. The state of the EEI material **120** in FIG. 1C may be the end state. Referring back to FIG. 1A, the EEI material **120** is the lightest, indicating the creation state before the EEI material **120** has been exposed to the specific environmental condition. Then, FIG. 1B shows the EEI material **120** after some exposure and FIG. 1C shows the EEI material **120** after even more exposure. Specifically, as illustrated in FIG. 1C, the EEI material **120** appears darker indicating additional environmental exposure since the deployment time.

The EEI material **120** may be responsive to (i) a cumulative exposure of a first environmental condition before the deployment time and (ii) a cumulative exposure of a second

environmental condition (although it may be additional exposure to a condition of the same type) after the deployment time. In an example, the EEI material **120** may comprise different components or may be a combination of different EEI materials **120** such that one of the components or materials is responsive to (i) while the other component or material is responsive to (ii). In another example, the EEI material **120** may be responsive to multiple environmental conditions, such as diacetylene, which is responsive to both temperature and UV. In the illustrated example, the EEI material **120** is responsive to a cumulative exposure of the same environmental condition (e.g., temperature) both before the deployment time and after the deployment time. Furthermore, in the illustrated example, the property, e.g., optical property, of the EEI material **120** changes based on the cumulative exposure to the environmental condition. For example, the optical property may be reflectivity of light, such that as the EEI material **120** changes between the creation state and the end state, the optical property of the EEI material **120** dynamically changes between the creation state and the end state. In one example, the EEI material **120** may exhibit a low reflectivity of light in the creation state, which dynamically progresses to a higher and higher reflectivity of light as the EEI material **120** transitions from the creation state to the end state. In another example, the EEI material **120** may exhibit a high reflectivity of light in the creation state and may dynamically progress to a lower reflectivity of light as the EEI material **120** transitions to the end state.

In several of the examples described herein, changes in optical properties, such as changes in reflectance of the EEI material, are provided to describe the state change of the EEI material. It should be appreciated that the change of state may be a change in a property other than an optical property. Specifically, other property changes may apply to the descriptions below even though optical property changes are used as examples.

As illustrated in FIGS. 1B and 1C, the EEI **100** may include one or more indicia (e.g., indicia **130a** and **130b**), such as a machine-readably symbol (e.g., barcode **132**), an RFID tag **134** or both. Calibration data may be encoded in the one or more indicia **130**. Even though the EEI material **120** is illustrated as separate from the indicia **130** in FIGS. 1B and 1C, as described in more detail in FIGS. 6A, 6B, 7A, 7B, 8A and 8B below, the EEI material **120** may be integrated within the indicia **130**, and may even operate as part of the indicia, which may change over time as described in U.S. Pat. Nos. 10,318,781; 10,546,172; U.S. patent application Ser. Nos. 16/526,505 and 16/526,527.

FIGS. 2A, 2B, 2C and 2D further illustrate the advantages provided by the calibration data and disadvantages of creating an EEI **100** without using calibration data. For example, FIG. 2A illustrates the progression of the EEI material **120** between the creation state **202** and the end state **204**. Specifically, as the EEI material **120** experiences environmental exposure to a specific environmental condition, a property, e.g., an optical property (illustrated as color or the level of darkness in FIGS. 2A-2D), of the EEI material **120** dynamically changes. For illustrative purposes, the examples in FIGS. 2A-2D are described in relation to temperature exposure. The creation state **202** of the EEI material **120** in FIG. 2A is shown as white, indicating no temperature exposure on the far left of the exposure history. The end state **204** of the EEI material **120** in FIG. 2A is shown as dark gray and is representative of a fully activated

EEI material **120**. For example, one could imagine the EEI material **120** as a film, with the end state **204** being fully developed.

However, in practice, the optical properties associated with the creation state **202** and the end state **204** may be predetermined, e.g., by appropriately tuning the properties of the EEI material, to improve the usability of the EEI material **120**. In the illustrated example, buffers **210a** and **210b** may be provided such that the nominal creation state **202'** and the nominal end state **204'** (as recognized by a reader) are offset from the true creation state **202** and the true end state **202** illustrated in FIG. 2A. One reason for buffers **210a** and **210b**, hereinafter referred to buffer(s) **210**, may be to improve accuracy when measuring a property, e.g., an optical property, of the EEI material **120**. For example, the EEI material **120** may rapidly progress from creation state **202** (illustrated in FIG. 2A) to the nominal creation state **202'** (illustrated in FIG. 2B) without much of discernable change in the optical property. Furthermore, the optical property of the end state **204** (illustrated in FIG. 2A) may be nearly identical to the optical property of the nominal end state **204'** (illustrated in FIG. 2B), such that a reader is programmed to view the nominal end state **204'** as a fully “developed” EEI material **120**. Another advantage of buffer **210b** may be to ensure that a reader can determine an exact time the EEI material **120** reaches the nominal end state **204'**. For example, if an EEI **100** associated the end of a product’s life with the end state **204** of the EEI material **120** as illustrated in FIG. 2A, the EEI material **120** could sit fully “developed” for a week with no further changes in its associated optical property, since the EEI material **120** already reached the end state **204**. Therefore, regardless of the additional environmental exposure experienced by the EEI material **120**, the EEI material **120** would remain in the end state **204**, making it unclear exactly when the product expired. By using buffer **210b**, the EEI material **120** may progress further, thereby allowing a reader to potentially determine when the product expired or how far beyond expiration the product is.

The various optical properties between the nominal creation state **202'** and the nominal end state **204'** creates an optical property range or window **215**. Specifically the range or window **215** may represent each respective optical property within a product’s usable life, such that a reading of any optical property within that range or window **215** would indicate that the product is still usable, and a reading outside the range or window **215** (e.g., a reading of an optical property to the right of window **215**) would indicate that the product is no longer usable or expired.

However, as discussed above, in many instances, the EEI material **120** may experience unwanted progression or “development” due to environmental exposure during shipping, storage, etc. before the EEI material **120** is used to create an EEI **100**. As illustrated in FIG. 2C, the EEI material **120** may be deployed (e.g., used to create an EEI **100** and associated with a product) at a deployment time after a non-insignificant amount of environmental exposure. The optical property of the EEI material **120** at the deployment time is considered a deployment state **206**. For example, temperature exposure during shipping or storage of the EEI material **120** may account of 15-20% of the usable range or window **215**. Specifically, the deployment state **206** of the EEI material **120** may be well ahead (e.g., further progressed or developed) of the nominal creation state **202'** thereby effectively reducing the window **215** to a reduced range or window **217**.

The unwanted progression may reduce the accuracy in tracking the product’s exposure to an environmental condition. Thus, when the EEI **100** created from the EEI material **120** is associated with a product, the product may appear to be unusable (e.g., beyond an upper threshold of temperature exposure requiring the product to be discarded) once the EEI material **120** reaches its nominal end state **204'** even though 15-20% of the temperature exposure occurred before the EEI material **120** was associated with the product. Thus, even though the product is in fact still usable, the EEI **100** made from the EEI material **120** indicates that the product has exceeded its maximum allowable temperature exposure.

As illustrated in FIG. 2D, calibration data may be used to adjust or calibrate the EEI **100** to shift the range or window **215** to a new usable range or window, which may also be referred to a calibrated range or window **215'**. Specifically, an optical property at the deployment state **206** may be determined and used to determine a new end state, which may be referred to as a calibrated end state **208**. The calibrated range or window **215'** accounts for any pre-deployment environmental exposure (e.g., temperature exposure) experienced by the EEI material **120** prior to being deployed (e.g., applied to a product as an EEI **100**). After calibrating the EEI **100**, or more specifically reading of the EEI material **120**, the EEI **100** may advantageously track the full range of environmental exposure (e.g., temperature exposure) experienced by the product and therefore accurately represent the environmental exposure experienced by the product post-deployment. By calibrating the EEI **100** in such a manner, the EEI **100** may retain full usability even after pre-deployment exposure.

A media processing device may be used to determine calibration data and then (i) create an EEI **100**, (ii) complete creation of a partially formed EEI **100**, (iii) update an EEI **100**, based on the determined calibration data. FIG. 3 illustrates an example of a media processing device **300**, which may be an industrial scanner, a printer, a laser etching machine, an engraving machine, a digital camera, or any combination thereof. For example, the media processing device **300** may be an industrial printer, such as Zebra’s ZT600 Series Industrial Printer, which may have its software or firmware appropriately modified to carry out the operations described in the present disclosure. As illustrated in FIG. 3, a media processing device **300** may include a processor (e.g., CPU **310**) and an image capture assembly **320**. The media processing device **300** may also include memory (e.g., a memory device **330**) and an input/output (“I/O”) device **340**. Furthermore, the media processing device **300** may include an analysis subsystem **312**, a determination subsystem **314** and an encoding subsystem **316**. One or more of the analysis subsystem **312**, determination subsystem **314** and encoding subsystem **316** may be specialized subsystems that make up the CPU **310**. Conversely, one or more of the analysis subsystem **312**, a determination subsystem **314** and an encoding subsystem **316** may be their own processing subsystems that reside on separate CPUs, GPUs or other processing equipment.

The image capture assembly **320** may be configured to capture an image **360** of a media **350** (e.g., a tag or label) comprising the EEI material **120**. In an alternative example, an optical property of the EEI material **120** may be measured directly, e.g., by a sensor, reader or scanner, e.g., a dedicated handheld reader to read and analyze the EEI material **120**, such as a modified handheld reader provided by Zebra Technologies. The media **350** may be an EEI **100**. The image capture assembly **320** may also be configured to analyze the captured image **360** to detect a current optical property **365**

of the EEI material **120**. Based on the detected optical property, appropriate calibration data **370** for the EEI may be determined, e.g., indicating how much exposure the EEI may have already had to the relevant environmental condition based on the detected optical property **365**. The image capture assembly may also be configured to provide information to the encoding subsystem **316** and/or the imaging subsystem **380**, such that the encoding subsystem **316** and/or the imaging subsystem **380** may encode the calibration data **370** to the media **350**, which is illustrated in FIG. 3 as encoded calibration data **370'**. The image capture assembly **320** may first provide information to the CPU **310**, analysis subsystem **312**, determination subsystem **314** or a combination thereof, which may then communicate appropriate information to either the encoding subsystem **316**, the imaging subsystem **380** or both for encoding the calibration data **370** to the media **350**.

In an example, the analysis subsystem **312** may be configured to analyze the captured image **360** to detect the current optical property **365** of the EEI material **120**. Additionally, the determination subsystem **314** may be configured to determine the calibration data **370** based on the detected optical property **365**. Similarly, the encoding subsystem **316** may be configured to encode the calibration data **370** to the media **350**, e.g. by encoding the media **350** (e.g., indicia **130**), such as a 2D barcode **132**, such that when the indicia **130** is read or scanned, the scanner or reader interprets the current optical property **365** in relation to the deployment state **206** and the calibrated end state **208** of the EEI material **120** instead of the creation state **202** (or nominal creation state **202'**) and the end state **204** (or nominal end state **204'**). Specifically, the media **350** (e.g., indicia **130**), such as the 2D barcode **132**, may be encoded with appropriate information such that the reader or scanner determines that the optical property associated with the calibrated end state **208** is indicative of a product being expired or reaching its end of life. Data, such as the calibration data **370**, may be encoded to the media **350** (e.g., indicia **130**) according to any of the methods or techniques described in U.S. Pat. Nos. 10,318,781; 10,546,172; U.S. patent application Ser. Nos. 16/526,505 and 16/526,527.

Alternatively, the processor (e.g., CPU **310**) may analyze the captured image **360** to detect the current optical property **365** of the EEI material **120** at the deployment time, associate the current optical property **365** with the deployment state **206** of the EEI material **120**, and determine the calibration data **370** based, at least in part, on the detected optical property **365**. After determining the calibration data **370**, the processor (e.g., CPU **310**) may encode the calibration data **370** to the media **350** according to any of the methods or techniques described in U.S. Pat. Nos. 10,318,781; 10,546,172; U.S. patent application Ser. Nos. 16/526,505 and 16/526,527. In another example, the processor (e.g., CPU **310**) may cause another component of the media processing device **300** to perform the analyzing, determining and/or encoding.

Encoding the calibration data **370** as encoded calibration data **370'** in the media **350** may include at least one of (i) printing or otherwise applying an indicia **130** (e.g., a barcode symbol **132**) in the media **350**, (ii) encoding an RFID tag **132** in the media **350**, and (iii) including a reference to a database, where the reference may be encoded in the indicia **130** or RFID tag **132**, and saving the calibration data in the database. Instead of printing the indicia **130**, the indicia may be etched, imaged, or applied (e.g., as a sticker) to the media.

It should be appreciated that other techniques for applying the indicia **130** in the media **350** or to the media **350** may be used.

In another example, the media processing device **300** may include an image sensor **322**, which may be part of the image capture assembly **320**. For example, the image capture assembly **320** may include an image sensor **322**, such as a camera. The media processing device **300** may also include an imaging subsystem **380** (e.g., a print head, laser etcher, etc.). Both the image sensor **322** and the imaging subsystem **380** may be communicatively coupled to the processor (e.g., CPU **310**), which may be configured to obtain creation data **372** associated with an environmental exposure indicator material **120** provided on a substrate (e.g., substrate **110**). Additionally, the processor may be configured to obtain deployment data **374** of the environmental exposure indicator material **120**. Obtaining the deployment data **374** may include causing the image sensor **322** to read a current optical property **365** of the EEI material **120** to determine the deployment state of the EEI material **120**. Other examples of obtaining the deployment data **374** include estimating the deployment state or a respective optical property **365** at the deployment time and/or obtaining inputs to calculate or estimate the deployment state or a respective optical property **365** at the deployment time.

Furthermore, the processor may be configured to cause the imaging subsystem **380** to apply the indicia **130** on the substrate (e.g., substrate **110**). As noted above, the indicia **130** or media **350** is associated with calibration data (e.g., encoded calibration data **370'**), which is configured to be used to adjust indications of the cumulative environmental exposure provided by the EEI material **120** to compensate for a difference between the deployment state and the creation state. In one example, the imaging subsystem **380** may be a print head and causing the imaging subsystem **380** to apply the indicia **130** on the substrate (e.g., substrate **110**) includes causing the print head to print the indicia **130** on the substrate. Alternatively, the imaging subsystem may be a laser etcher, and causing the imaging subsystem **380** to apply the indicia **130** to the substrate includes causing the laser etcher to etch the indicia **130** into the substrate.

FIG. 4 illustrates a system **400** for reading an environmental exposure indicator (e.g., an EEI **100** including an indicia **130** and an environmental exposure indicator material **120** and any corresponding calibration data **470**). For example, the system **400** may be used anywhere along the supply chain or in the field to determine a respective optical property **365** of the EEI material **120** of an EEI **100** and correlate that respective optical property **365** to a product characteristic based on the calibration data **470**. In the illustrated example, the system **400** includes an image capture subsystem **420** and a controller **450**. In an example, the system **400** may also include a processor (e.g., CPU **410**), a memory (e.g., a memory device **430**) and an input/output ("I/O") device **440**. Furthermore, the system **400** may include a decoding subsystem **412**, an analysis subsystem **414**, and a comparison subsystem **416**. One or more of the decoding subsystem **412**, analysis subsystem **414**, and comparison subsystem **416** may be specialized subsystems that make up the CPU **410** or controller **450**. Conversely, one or more of the decoding subsystem **412**, analysis subsystem **414**, and the comparison subsystem **416** may be their own processing subsystems that reside on separate CPUs, GPUs or other processing equipment.

The image capture subsystem **420** may be configured to capture an image (e.g., image **360**) of the environmental exposure indicator **100**. The image capture subsystem may

be a digital camera, image sensor or other imager provided by Zebra, such as a hands-free imager (e.g., Zebra's DS9208 hands-free imager). Additionally, the controller **450** may be configured to decode calibration data **470** from the indicia **100**, analyze the captured image (e.g., image **360**) to detect a current optical property **365** of the environmental exposure indicator material **120**, compare the detected property (e.g., optical property **365**) with the calibration data **470**, and output an indication of the comparison. Example output indications are described according to any of the illustrative examples described in U.S. patent application Ser. No. 16/526,505 (e.g., see example representations of a barcode reader display provided in FIG. 9 and FIG. 10). The calibration data **470** may be associated with a property or characteristic of the EEI material **120** at an earlier time.

Reader

FIG. 5 illustrate example devices **500a** and **500b** (referred to herein generally as reader **500**) for reading EEI(s) **100**, the associated indicia **130**, and the associated EEI material **120**. The reader **500** may also be configured to read calibration data associated with the EEI(s) **100**. The reader **500** may be a dedicated reader (e.g., reader **500a**) or an apparatus configured to read EEI(s) **100**, indicia **130** and/or EEI material **120** (e.g., reader **500b**) such as a mobile device, a personal digital assistant or PDA, a smartphone, a laptop, a tablet computer, or a desktop computer, as well as any other user devices. In a more specific example, reader **500** may be a Scanner provided by Zebra, such as any of the Zebra scanners or handheld computers (e.g., Zebra's EC50 and EC55 Enterprise Mobile Computers, MC2200 and MC2700, TC21 and TC26, etc.)

The reader **500** may be adapted to read EEI(s) with various indicia **130**, such as machine-readable symbols (e.g., 1D and 2D barcodes). Additionally, the reader **500** may also transmit, receive, or exchange data with other network devices via a communication network. A network device may be a computer, a different reader **500**, or any other device accessible via a communication network. Certain data may be stored in the reader **500**, which may also be stored on a server within the network, either temporarily or permanently, for example in memory or a storage device (e.g., memory devices **502A-B**). The network connection may be any type of network connection, such as a cellular or wireless connection, an Ethernet connection, digital subscriber line, telephone line, coaxial cable, etc. Access to a reader **500** or image data obtained by the reader **500** may be controlled by appropriate security software or security measures. An individual users' access may be defined by reader **500** and limited to certain data and/or actions.

The reader may include a processor **510**, such as a microprocessor, that is communication with memory (e.g., memory devices **502A-B**) and input/output devices **504A-B**. The processor **510** may also communicate with an image sensor **520**, image optics **530**, an illumination subsystem **540**, a power subsystem **570** and display **580**. The image sensor **520** may receive light from image optics **530**, which may include a lens **532** and a filter **534**. The image sensor may pass the received light to an image or signal processor **550**, which may send the signal to a converter **560** before sending the information to processor **510**.

The processor **510** may be an integrated circuit microprocessor, such as a programmable logic or gate array. In an example, processor **510** may provide control inputs to control circuits (e.g., the illumination driver circuit **544**) as well as other control circuits (not pictured). For example, the

processor **510** may also provide control inputs for the image sensor **520** such as timing inputs.

The image sensor **520** may be a sensor array. The image sensor **520** may be configured to sense or detect light at a specific wavelength (e.g., visible wavelengths, non-visible wavelengths, etc.). In an example, the image sensor **520** may be a CMOS based image sensor array. In another example, the image sensor **520** may be a CCD based image sensor array. The image sensor may include a two-dimensional array of pixels that each includes a photosensitive sensitive region. The image sensor **520** may also be controlled by a sensor control subsystem (not pictured), which may send control signals to the image sensor **520**.

The image optics **530** may include lens **532** and a filter **534**. It should be appreciated that the image optics **530** may include multiple lenses **532** and/or filters **534**. Additionally, the image optics **530** and illumination subsystem **540** may include a variety of optical technologies to achieve illuminating at least a portion of the EEI(s) **100** and receiving reflected light from the indicia **130** as well as any associated EEI material **120**. As illustrated in FIG. 5, the illumination subsystem **540** may include a light source **542** and illumination driver circuit **544**. The light source **542** may include an LED or bank of LEDs. In another example, the light source **542** may also include a laser diode to indicate a scanning region. The light source is configured to direct light or light energy toward a target object (e.g., an EEI **100**). The reflected light or radiation from the target object (e.g., the EEI **100**) may be focused by the image optics **530** (e.g., lens **532**) onto the image sensor **520**. In an example, the light source **542** is configured to provide light of sufficient intensity to allow the image sensor **520** to capture an image of at least a portion of the EEI **100** (e.g., the entire EEI **100**, the indicia **130**, the EEI material **120**, etc.). In an example, the illumination driver circuit **544** may cause the light source **542** to emit light, which may pass through various apertures and lenses before reaching the target object (e.g., the EEI **100**).

The image or signal processor **550** may be configured to process and decode information received and captured by the image sensor **520**. For example, the image or signal processor **550** or processor **510** may perform image processing, analysis and/or decoding. The image or signal processor **550** may include an indicia processing subsystem **552**, an EEI material processing subsystem **554**, and a calibration data processing subsystem **556**. The indicia processing subsystem **552** may be configured to perform image processing, analysis and/or decoding of the portion of the image related to the indicia **130**. Similarly, the EEI material processing subsystem **554** may be configured to perform image processing, analysis and/or decoding of the portion of the image related to the EEI material **120** and the calibration data processing subsystem **556** may be configured to perform image processing, analysis and/or decoding of the portion of the image related to the calibration data.

Data from the image or signal processor **550** may be passed to a converter **560** before being sent to the processor **510**. For example, the converter **560** may be an analog-to-digital converter. In another example, the signal (e.g., analog signal) may be amplified before being converted to a digital signal by converter **560**.

The reader **500** may be used to obtain the product life data. The product life data may be obtained based on, at least a portion of one or more of the encoded data of the indicia **130**, the EEI material **120**, and the calibration data. For example, an image sensor **520** of a reader **500**, such as a smartphone carrying a TTI App reader, may be used to scan

25

the indicia **130** (e.g., 2D barcode), the associated EEI material **120**, and possibly any associated calibration data. For example, the image may be captured from an image sensor **520**, such as the smartphone camera, using a light source **542** (e.g., camera flash, such as a smartphone white flash). The nominally white flash intensity may overwhelm the ambient light and set the color temperature for image capture by the sRGB sensor of the camera. The image sensor **520** may capture the white incident light reflectance of the pixels, including those of the indicia **130** and EEI material **120**.

In an example, a filter **534** (e.g., a physical color filter) may be positioned over the camera lens when the sRGB image is captured. Alternatively, a filter **534**, such as a digital filter may be applied over the sRGB image pixel map to create a colored light filter effect on the reflectance data. As an example the digital filter may be programmed to process the sRGB image based on an appropriate center wavelength and range, as in a bandpass filter. Then, the filtered color image RGB values may be reduced to a greyscale value (e.g., range 0 to 255) and a greyscale pixel map for the indicia **130** (e.g., Data Matrix barcode) may be created. In an example, the indicia **130** (e.g., 2D barcode) may include encoded data to provide the appropriate inputs and may be used to program or calibrate a barcode reader for reading an optical property (e.g., a reflectance value, a saturation value, a color value, a color density value, an optical density value or a color hue value) of the EEI material **120**. For example, through encoded data (e.g., calibration data), data identifiers (DIs) and/or Application Identifiers (AIs), the indicia **130** can automatically program the reader **500** to properly sense an optical property (e.g., a reflectance value, a saturation value, a color value, a color density value, an optical density value or a color hue value) of the EEI material **120**. The encoded data in the data identifiers (e.g., Application Identifiers) or the calibration data may also include the appropriate lifetime equation parameters such that the reader **500** can estimate the used and/or remaining product life at a specified temperature for the scanned product.

After scanning the EEI **100**, and more specifically indicia **130**, and obtaining the appropriate life data, the reader **500** may display information about the marked product and the remaining life on display **580**. For example, a medical product may be scanned to reveal product lifetime data, such as a Monitor Category, 80 percent life remaining, expiration date (e.g., calculated from the estimated remaining life or based on some other criteria), and product authenticity. Additionally, indicia data may be revealed, which may include AI (01) for a GTIN, AI (10) batch number, and AI (21) serial number that are displayed by the reader **500**. After reflectance data is obtained from the image sensor **520**, the appropriate equation parameters can be used to determine equivalent exposure time (t_e) at the reference temperature, and subtracting (t_e) from the lifetime may provide the remaining product life at the reference temperature.

After reflectance data is obtained from the image sensor **520**, the appropriate equation parameters can be used to determine equivalent exposure time (t_e) at the reference temperature. Subtracting (t_e) from the lifetime gives the remaining product life at the reference temperature. If the remaining life is positive, then the percentage of really remaining life may be calculated by dividing t_e by L , and the barcode reader may display "Tests Passed", along with the vaccine's available remaining life. Referring back to FIGS. 2A-2D, the calibration data advantageously allows for more accuracy when determining characteristics of the product (e.g., remaining life) by adjusting the range or window, or

26

more specifically the deployment state **206** and the calibrated end state **208** of the EEI material **120**.

It should be understood that various changes and modifications to the example embodiments described herein will be apparent to those skilled in the art. Such changes and modifications can be made without departing from the spirit and scope of the present subject matter and without diminishing its intended advantages. It is therefore intended that such changes and modifications be covered by the appended claims. Also, it should be appreciated that the features of the dependent claims may be embodied in the systems, methods, and apparatus of each of the independent claims.

Calibration Data

Referring back to FIG. 3, the calibration data **370** may be based, at least partially on, at least one or more of the creation state **202** of the EEI material **120**, the deployment state **206** of the EEI material **120**, the end state **208** of the EEI material **120**, and any other environmental history information associated with the EEI material **120** between the creation state **202** and the deployment state **206**. In an example, the calibration data **370** may be used to determine the optical property range or window (e.g., calibrated window **215'** from FIG. 2D). The calibration data **370** may include any of creation data **372**, deployment data **374**, analysis data **376** and any combination thereof.

Creation data **372** may include information related to the creation of the EEI material **120**. For example, the creation data **372** may include any of (i) a timestamp related to a creation time or time of manufacture of the EEI material **120**, (ii) the optical property of the EEI material **120** at the creation time or time of manufacture (e.g., the optical property of the creation state), (iii) the expected optical property at the end state **204** at the creation time or time of manufacture (e.g., the optical property of the end state), or any other information regarding the EEI material **120** at the time of creation. It should be appreciated that (ii) may be a measured value, an estimated value or a calculated value and may also include any inputs required to calculate the creation state **202** or an optical property associated with the creation state **202**. Similarly, (iii) may be an estimated value, a calculated value, or a supplied value (e.g., a value from an EEI material spec sheet or look-up table).

Deployment data **374** may include information related to the deployment of the EEI material **120** in an EEI **100**. For example, the deployment data **374** may include any of (i) a timestamp related to the deployment time of the EEI material **120**, (ii) the optical property of the EEI material **120** at the deployment time (e.g., the optical property of the deployment state **206**), (iii) the expected optical property at the end state **204'** at the deployment time (e.g., the optical property of the calibrated end state **208**), (iv) cumulative environmental exposure information from the creation time to the deployment time, (v) current environmental exposure information or data at the deployment time (e.g., exposure data such as history or time of exposure, age of the EEI material **120** since creation, exposure history), or any other information regarding the EEI material **120** at the deployment time. It should be appreciated that (ii) may be a measured value, an estimated value or a calculated value and may also include any inputs required to calculate the deployment state **206** or an optical property associated with the deployment state **206**. Similarly, (iii) may be an estimated value, a calculated value, or a supplied value (e.g., a value from an EEI material spec sheet or look-up table).

Analysis data 376 may include information related to the analysis of the optical properties of the EEI material 120 in an EEI 100. For example, the analysis data 374 may include any of (i) data identifiers for an indicia associated with the EEI material 120 to create the EEI 100, (ii) product life equation parameters associated with the optical property of the EEI material 120, (iii) Arrhenius equation parameters of the EEI material 120, (iii) size information of the EEI material 120, (iv) location information of the EEI material 120, (v) equation(s) or estimation methodologies for determining the calibrated end state 208, which may be based on the creation state 202, deployment state 204, the creation data 372 and/or the deployment data 374.

Looking ahead to FIG. 9, the calibration data (e.g., calibration data 370, 470, which is illustrated as calibration data 370 in FIG. 9) may be provided and used for various calibration techniques. For example, in example 710, the calibration data 370 may be obtained and directly encoded into an indicia 130 provided by the media processing device 300, such as a printer. In one example, the calibration data 370 or a portion of the calibration data 370 may be provided on the print media fed to the printer, which may be manually input by a user when creating EEI(s) 100 with the printer. In another example, the printer may be associated with an image sensor or camera that is configured to determine an optical property of the EEI material 120 at the time of printing. The printer may determine calibration data 370 (e.g., deployment data 374) to encode into the indicia 130 based on the optical property 365 of the EEI material 120 immediately prior to printing. Once the indicia 130 is encoded with the calibration data 370 (e.g., analysis data 376), the encoded data may automatically calibrate a reader when scanning the indicia 130, such that the reader accurately reads to EEI material 120 (e.g., only accounts for environmental exposure from the deployment time until the time of scanning).

As indicated in example 720, the calibration data 370, which may include an input, such as the optical property of the EEI material 120 at the deployment time, may be determined and then manually programmed by a user into a printer control window before the indicia 130 is created. Similarly, the calibration data 370 may be encoded such that upon reading the EEI 100 with a reader, the reader outputs various values to be used as inputs in the reader when further scanning the EEI material 120.

As indicated in examples 730 and 740, the calibration data 370 may be provided in a database or some other remote data repository. Once the calibration data 370 is determined at the time of printing (e.g., the deployment time) the calibration data may be stored in the database. Then, the indicia 130 is encoded such that upon reading the indicia 130, the reader is redirected, via a link to the database or remote data repository, to retrieve the stored calibration data 370. In this manner, each indicia 130 can be encoded with a static link to the calibration data 370 while the database is dynamically updated with the calibration data. Similarly, when reading the indicia 130 and the EEI material 120 of the calibrated EEI 100, the reader may also redirect to the database such that the information stored on the database may be used to calibrate the reader. For example, the calibration data 370 may automatically calibrate the reader or provide inputs to a user to manually input into the reader for calibration, such that the reader accurately reads to EEI material 120 (e.g., only accounts for environmental exposure from the deployment time until the time of scanning).

Positioning and Placement of EEI Material

As described in the examples herein, the EEI material 120 is provided as part of an environmental exposure indicator.

For example, the EEI material may be provided proximate to an indicia 130, such as a computer-readable symbol (e.g., a barcode symbol), such that the EEI material 120 is associated with the indicia 130. For example, if the indicia 130 is a barcode, the EEI material 120 may be positioned within the barcode or in an area outside of the barcode, but near the barcode. The proximity of the EEI material 120 to the indicia (e.g., barcode symbol) may be up to a few bars or modules from an outside edge of dark regions of the barcode symbol, which is described in more detail with reference to FIGS. 8A and 8B. In some examples, the EEI material 120 may partially or completely surround the indicia 130 (e.g., barcode). By providing the EEI material 120 in a region outside of the indicia 130 (e.g., barcode), more of the EEI material 120 (e.g., the entire environmentally sensitive portion of the indicator) may be read by a reader to determine the properties of the EEI material 120. Additionally, since each portion of the EEI material 120 (e.g., the entire environmentally sensitive portion of the indicator 100) may be read and utilized for analysis, less EEI material 120 may be needed for the same accuracy as other indicators including machine-readable symbols, such as barcode symbols with overprinted or underprinted EEI material 120 portions positioned within the barcode (e.g., in an invariant area), thereby further reducing waste and cost. In some embodiments, providing the EEI material 120 proximate to the indicia 130 (e.g., barcode symbol) may assist a user in presenting the EEI material to a reader or scanner because the both the barcode symbol and the EEI material may be in the field of view of the reader or scanner at the same time.

As discussed above, the EEI material 120 may be implemented as part of an environmental exposure indicator (EEI) 100. The EEI 100 may be a one-dimensional indicator (e.g., 1D barcode as illustrated in FIGS. 6A and 6B) or a two-dimensional indicator (e.g., 2D barcode as illustrated in FIGS. 7A and 7B). FIGS. 6A and 6B illustrate a representation of an EEI indicator 100, which includes an indicia 130, such as a one-dimensional barcode symbol 132 with an EEI material portion(s) 650a and 650b, hereinafter referred to as EEI material portion(s) 650. As illustrated in FIG. 6A, the EEI material portions 650 includes the EEI material 120 in a portion of the bars, modules or elements 620a and 620b of the barcode symbol 132. FIG. 6B illustrates another example where the EEI material portions 650a and 650b fill an entire bar, module or element 620. In another example, the entire barcode symbol 132 may be made of the EEI material 120. For example, all of the encoded data in the barcode may be provided by EEI material 120. Specifically, each of the bars, modules or elements may be printed in the EEI material 120. The barcode symbol 132 may include quiet zones, which are further described in U.S. patent application Ser. No. 17/007,795.

The EEI 100 or more specifically, the barcode symbol 132 may provide guidance and information regarding the reading or scanning of the EEI material portion(s) 650. In some implementations, the bar code symbol 132 itself may be used for calibration, for reference, or for location. For example, calibration data may be encoded within the barcode 132 and may be used as a reference when evaluation optical properties of the EEI material portion(s) 650. Alternatively, the EEI material portion(s) 650 may be in a known location, e.g., at a particular position with respect to the barcode, or with respect to location elements in the barcode, such as guard bars or a quiet zone (e.g., quiet zones) of a UPC-A barcode or the position detection patterns, alignment

patterns, and/or quiet zone of a QR code. It should be appreciated that the quiet zones may include EEI material 120.

As discussed above, the EEI material 120 may be incorporated on a data carrying labels or tag, such as a barcode. It should be appreciated that the illustrative indicia 130 (e.g., barcode) examples disclosed herein may extend to other data carrying labels or tags. For example, the EEI material 120 may be applied to other text or graphics in a similar fashion. The systems and methods disclosed herein may apply to computer readable indicia, and more specifically the computer readable indicia that encode a data codeword(s). In an example, the computer readable indicia is a barcode symbol 132 or an RFID tag 134.

FIGS. 7A and 7B illustrate another representation of an EEI 100, which includes a two-dimensional error-correcting barcode symbol 132, which may be referred to herein generally as a 2D barcode 132, (e.g., a 26×26 Data Matrix) with an EEI material portion 650, according to an example embodiment of the present disclosure. The EEI 100 includes a barcode 132 or barcode region that includes a plurality of modules or elements 620a-n in a permanent or static color state (e.g., black elements). As illustrated in FIG. 7A, the barcode region 110 has a length and a width. The EEI 100 may also include an empty region(s) 630, which is void of elements or modules in a permanent or static color state (e.g., black elements) which advantageously further separates the EEI material portion 650 from the static portion to prevent degradation of any EEI material 120 within the EEI material portion 650. The empty region 630 has a length and a width. In an example, the EEI material portion 650 may entirely occupy the empty region 630 (as illustrated in FIG. 7A) or partially occupy the empty region 630 (as illustrated in FIG. 7B).

The empty region 630 is void of modules or elements 620 in the permanent or static color state. For example, the barcode 132 or barcode region may be provided with an empty space, such as a gap or cutout that forms the empty region 630. The empty region 630 is empty with respect to the static barcode symbol 132, but includes an EEI material portion 650 that includes an EEI material 120. Since the EEI material 120 may be provided on print media before supplying the print media to a printer, the barcode 132 or barcode region may be printed onto the print media with the EEI material 120 and arranged in such a manner to ensure that the gap or area void of modules or elements 620 corresponds to the portion of the print media including the EEI material 120. In other examples, the barcode 132 or barcode region and the EEI material portion 650 may be printed at the same time such that during the printing process an empty region 630 is not created and then filled with an EEI material 120, but instead the barcode 132 and the EEI material portion 650 are printed together.

In another example, the EEI material portion 650 of an EEI 100 may be positioned outside of the indicia 130 (e.g., barcode 132 or RFID tag 134). For example, the EEI(s) 100 illustrated in FIGS. 8A and 8B include a substrate with the indicia 130 (e.g., barcode 132) and EEI material 120 provided on the substrate near the indicia 130. As illustrated in FIGS. 8A and 8B, the EEI material 120 (applied to EEI material portion 650) is provided outside and spaced from the indicia 130 (e.g., barcode 132). By providing the EEI material 120 (applied to EEI material portion 650) outside and spaced from the indicia 130, the EEI material 120 is advantageously unaffected by the imaging process (e.g., printing process) of the indicia 130 (e.g., barcode 132).

FIG. 8A illustrates a representation of a one-dimensional EEI 100 and FIG. 8B illustrates a representation of a two-dimensional EEI 100. In an example, the EEI 100 may be a two-dimensional error-correcting indicator. The 2D EEI 100 may include an indicia 130, such as a barcode 132 (e.g., a 26×26 Data Matrix) and an EEI material portion 650.

It should be appreciated that a 26×26 Data Matrix is provided for illustration purposes only. A 26×26 Data Matrix contains 72 codewords, each formed of eight modules corresponding to the eight bits of the codeword, referred to as a “utah.” The 24×24 bitmap matrix shows the layout of all the 72 codewords in a 26×26 Data Matrix. A “utah” is an arrangement of 8 modules to encode one codeword. It may be arranged either as a single connected group with a pattern frequently in the shape of the State of Utah in Data Matrix, or formed as two subgroups of connected modules split across two or more utah patterns. The systems and methods described herein may apply to other Data Matrix sizes and other styles of 1D and 2D barcodes. For example, the Data Matrix may be 10×10, 12×12, 14×14, 40×40, up to 144×144 and may have 8, 12, 18, 162 or 2178 codewords respectively. Additionally, it should be appreciated that the example embodiments disclosed herein may translate to various 2D barcodes including an Aztec Code, Code 1, CronoSign, CyberCode, DataGlyphs, Data Matrix, Datastrip code, EZcode, High Capacity Color Barcode, InterCode, MaxiCode, MMCC, NexCode, PDF417, QR code, ShotCode, SPARQCode, and the like.

As discussed above, the 1D and 2D barcodes 132 include a plurality of modules or elements 620a-n in a permanent or static color state (e.g., black elements). As illustrated in FIGS. 8A and 8B, the EEI material portion(s) 650 may occupy a hollow rectangular or square region surrounding the barcode 132. Additionally, the EEI material portion(s) 650 may be positioned in different spaces surrounding the barcode 132 as described in U.S. patent application Ser. Nos. 16/526,527 and 17/007,795. The EEI material portion 650 may be a continuous region surrounding the barcode 110 (as illustrated in FIGS. 8A and 8B) or may partially occupy the space around the barcode 132 in different regions.

As illustrated in FIG. 7B, the EEI material portion 650 is provided with a gap or border 660 such that the EEI material portion 650 occupies less area than the empty region 630. The gap or border 660 may provide a buffer between the imaging process (e.g., printing process) of the barcode 132 or barcode region and printing of the indicia 130. In an example of FIG. 7B, the gap 660 is a single module-wide or single element-wide border (e.g., as wide as an element 620) around the EEI material portion 650.

In some examples, the EEI 100 may include multiple EEI material portions 650. Each EEI material portion may include a different EEI material 120. In another example, an EEI material portion 650 may include multiple EEI materials 120. For example, the EEI material portion 650 may include two different EEI materials 120 that are adjacent to each other in the EEI material portion 650. Each of the EEI materials 120 may change in response to or exposure to different environmental conditions. Specifically, the EEI material(s) 120 may include various components that are triggered or react at different exposure levels or to different exposure events.

Barcode Elements/Modules

The indicia 130 may be provided as a barcode 132. Specifically, a one-dimensional barcode symbol 132 may be employed (See FIGS. 6A, 6B and 8A) as part of EEI 100.

Additionally, a two-dimensional error-correcting barcode symbol **132** may be provided as part of EEI **100**. Barcode modules, bars or elements **620** may be used to encode barcode data. For example, each module or element (e.g., modules **620a-n**) of the Data Matrix symbol may be used to encode one bit of data.

The barcode(s) **132** may be provided in a permanent or static color state, and the modules or elements **620** may optionally be square, rectangular, or circular. Each module or element in the barcode **132** is colored either nominally colored (e.g., black) or nominally empty or reflective (e.g., white). Nominally colored modules or elements may be black when printed on a light substrate or may be a lighter color when printed on a dark substrate. The nominally empty or reflective modules may not require any printing and may instead allow the substrate to show through. It will be appreciated that the example approaches disclosed herein may be extended to multi-color barcodes. The modules or elements **620** may form a module matrix, which is the visual manifestation of the binary bitmap matrix contained within the area of the symbol bounded by the Finder Pattern. The Finder Pattern may be an 'L' formed by connected solid lines along two edges of the symbol module matrix, with a Clock Track formed by an alternating pattern of white and black modules or elements along the opposite edges of the symbol. It will be appreciated that in other bar code symbologies, other finder patterns may be employed.

Environmental Exposure Indicator Material

EEI material **120**, such as environmentally sensitive materials may be provided as a compound, ink, toner, dye, paint or wax with environmentally sensitive pigments, which each may be generally referred to as an "EEI material". The corresponding EEI material portion(s) **650** of the EEI **100** may comprise the EEI material that has a chemistry that is predictably responsive to a specified environmental condition, undergoing a chemical or physical state change between a creation state and the end state. The chemical or physical state change may be a continuous state change, causing a continuous change in an optical property (e.g., a color state) of the EEI material **650** and corresponding EEI material **120** or a binary optical property state change once the measured environmental parameter crosses a predefined threshold.

In an example, the EEI material **120** may be sensitive to an environmental factor such as temperature, time, time and temperature, freezing, radiation, toxic chemicals, or a combination of such factors, or the like. In an example, the material may be a thermochromic material, such as a water-based irreversible thermochromic material designed to change permanently from white to black at 40° C. Additionally, the thermochromic material may be reversible. For example, the reversible thermochromic material may be a liquid crystal material or a leuco dye material (examples include QCR Solutions Reversible Thermochromic Inks and H.W. Sands Corporation inks). The material may also be a photochromic material (e.g., changes based on exposure to UV light). The material may be an ink, toner, dye, paint, wax or other coating(s) sensitive to time and temperature (an example includes the OnVu indicator).

The EEI material **120** may change from a darker color to a lighter color, a lighter color to a darker color, may change levels of transparency or opacity, and/or may change levels of reflectivity or absorptivity, or may change any other suitable characteristic. Additionally, the EEI material **120** may continuously change between a range of from a creation

state (e.g., an initial color state) to the end state (e.g., an end color state). For example, a dynamic material may change from a lighter color to a dark blue, which may be alternatively transformed by a reader to values on continuous "greyscale". The greyscale (which is not necessarily truly grey but is a continuous tone of some hue) is determined reducing the R, G and B values of each pixel to a single greyscale value by a formula of form:

$$\text{Greyscale value} = (aR + bG + cB) / K$$

Where {a, b, c} represent the relative contribution of each sRGB color in the pixel, and K is scaling factor. Additionally, a dynamic material or dynamic indicator may continuously change from a white or clear color to a dark red or blue (e.g., changing from white, to a faint red, become less and less opaque until it reaches a solid red color at the end color state). Moreover, any suitable combination of colors may be used for the states of one or more dynamic materials.

Subsystems and Methods

In an example, a smartphone application may be designed to read and analyze a captured image with the EEI material **120** in one or more of states to determine a property of the captured image based on a current value of an optical property of the EEI material **120**. The property may be adjusted based on calibration data associated with the EEI **100**. In other examples, dedicated handheld readers may read and analyze the EEI material **120**, such as a modified handheld reader provided by Zebra Technologies.

As described herein, the EEI material **120** may be present proximate to (e.g., within or near) an indicia **130** associated with the EEI **100**. FIG. 10 illustrates a flowchart of an example method **800** for reading an environmental exposure indicator **100**. Although the example method **800** is described with reference to the flowchart illustrated in FIG. 10, it will be appreciated that many other methods of performing the acts associated with the method **800** may be used. For example, the order of some of the blocks may be changed, certain blocks may be combined with other blocks, blocks may be repeated, and some of the blocks described are optional. The method **800** may be performed by processing logic that may comprise hardware (circuitry, dedicated logic, etc.), software, or a combination of both.

The example method **800** may include scanning (e.g., optically scanning) an indicia **130** associated with an EEI material **120** (block **810**). The EEI material **120** may be configured, responsive to a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state **202** and an end state **204**, causing a change in a respective optical property **365** of the environmental exposure indicator material **120**. In an example, the EEI material **120** has a deployment state **206** with a respective optical property **365**, such as a deployment optical property, in the deployment state **206**. The deployment state is between the creation state **202** and the end state **204**. In an example, the deployment state **206** is inclusive of the creation state **202**, such that if the EEI **100** is deployed at the same time the EEI material **120** is created, then the creation state **202** and the deployment state **206** are the same state.

Method **800** may also include determining calibration data **370**, **470** encoded within the indicia **130** based on a deployment state **206** of the EEI material **120** (block **820**). The calibration data **370**, **470** may be used to adjust indications of the EEI **100** provided by the EEI material **120** to

compensate for a difference between the deployment state **206** and the creation state **204**.

Additionally, method **800** may include determining an optical property **365** associated with the EEI material **120** (block **830**). For example, at the time of scanning or reading, the method may include determining the optical property **365** associated with the EEI material **120**. Determining the optical property **365** at the time of scanning or reading may include estimating the optical property **365**, calculating the optical property **365**, measuring the optical property **365**, etc.

Furthermore, method **800** may include determining a characteristic of the EEI **100** based on the calibration data **370**, **470** and the determined optical property **365** (block **840**). For example, the characteristic may be remaining product life, expiration information, environmental exposure history information, etc. In an example, the characteristic is determined based, at least in part, on the calibration data **370**, **470** and the determined optical property **365** at the time of scanning. For example, some of the calibration data **370**, **470** may be encoded in the indicia **130** as encoded data identifiers, such as product life equation parameters (e.g., Arrhenius equation parameters) that are adjusted based on the deployment state to ensure that the reading disregards and post-deployment environmental exposure.

In an example, the EEI **100** may be scanned at any point in the supply chain (e.g., using a smartphone with carrying an environmental exposure reader App, or other special reader) to check the environmental exposure history for the labeled product. Additionally, the optical property may be determined by capturing an image(s) of the EEI **100**. For example, the front facing camera of a smartphone may capture image(s) of the EEI **100** and the reader (e.g., smartphone) may process pixels in the image to assign or determine optical value(s) associated with the pixels. Optical values, especially for portions of the EEI material **120** may be an instantaneous value or an average value of one or more of the following properties: a reflectance value, a saturation value, a color value, a color density value, an optical density value or a color hue value.

As illustrated in FIG. **11A**, the indicia processing subsystem **552** may include a dedicated CPU **1105**, memory device **1115** and input/output device **1125**. Additionally, the indicia processing subsystem **552** may include a location subsystem **1135**, a decoding subsystem **1145**, and a recovery subsystem **1155**. The location subsystem **1135** may locate or identify the indicia **130**, such as a barcode symbol **132**. The decoding subsystem **1145** may decode the identified indicia **130**, such as the barcode symbol **132** and recover a symbol codeword sequence. Additionally, the recovery subsystem **1155** may recover underlying data codewords from the symbol codeword sequence.

FIG. **11B** illustrates a flowchart of an example method **1100** that describes example processes performed by the indicia processing subsystem **552** of FIG. **11A** according to an example embodiment of the present disclosure. Although the example processes are described with reference to the flowchart illustrated in FIG. **11B**, it will be appreciated that many other methods of performing the acts associated with the method **1100** may be used. For example, the order of some of the blocks may be changed, certain blocks may be combined with other blocks, blocks may be repeated, and some of the blocks described are optional. The method **1100** may be performed by processing logic that may comprise hardware (circuitry, dedicated logic, etc.), software, or a combination of both.

The example processes illustrated in method **1100** include capturing image(s) of an EEI **100** (block **1110**). The indicia processing subsystem **552** may also be configured to construct a scanned pixel map containing optical values in a computer readable indicia **130**, such as a barcode symbol **132** (block **1120**). The indicia processing subsystem **552** may also process the pixels in the scanned pixel map to assign a binary optical value to each pixel and may form a pixel map, such as a binarised pixel map (block **1130**). The indicia processing subsystem **552** may identify the computer readable indicia **130** encoding a data codeword in the pixel map (block **1140**). Additionally, the indicia processing subsystem **552** may decode the identified computer readable indicia **130**, such as the barcode symbol **132**, in the pixel map to recover a symbol codeword sequence (block **1150**). The indicia processing subsystem **552** may also recover underlying data codewords from the symbol codeword sequence (block **1160**). The indicia processing subsystem **552** may also output computer readable indicia data, such as barcode data (block **1170**). The indicia data or barcode data may be associated with other data obtained from one or more of an EEI material **120** and calibration data associated with the EEI **100**.

As illustrated in FIG. **12A**, the EEI material processing subsystem **554** may include a dedicated CPU **1205**, memory device **1215** and input/output device **1225**. Additionally, the EEI material processing subsystem **554** may include a location subsystem **1235**, a comparison subsystem **1245**, and a property determination subsystem **1255**. The location subsystem **1235** may locate or identify EEI material **120** associated with an indicia **130** or an EEI **100**. The comparison subsystem **1245** may compare a respective state of the EEI material **120** to other information regarding any one of the creation state **202**, nominal creation state **202'**, end state **204**, nominal end state **204'** deployment state **206** and/or calibrated end state **208** of the EEI material **120**. Additionally, the property determination subsystem **1255** may determine a property of the EEI material **120**. For example, the property determination subsystem **1255** may determine a property of the EEI material **120** based on the comparison performed by the comparison subsystem **1245**.

FIG. **12B** illustrates a flowchart of an example method **1200** that describes example processes performed by the EEI material processing subsystem **554** of FIG. **12A** according to an example embodiment of the present disclosure. Although the example processes are described with reference to the flowchart illustrated in FIG. **12B**, it will be appreciated that many other methods of performing the acts associated with the method **1200** may be used. For example, the order of some of the blocks may be changed, certain blocks may be combined with other blocks, blocks may be repeated, and some of the blocks described are optional. The method **1200** may be performed by processing logic that may comprise hardware (circuitry, dedicated logic, etc.), software, or a combination of both.

The example processes illustrated in method **1200** include an EEI material **120** experiencing an environmental exposure (block **1210**). Additionally, the EEI material processing subsystem **554** may be configured to capture image(s) of the EEI material **120** (block **1220**). Alternatively, the EEI material processing subsystem **554** may gather information of the EEI material **120** without capturing image(s) of the EEI material **120** and instead may be a sensor that reads a property, e.g., an optical property, such as reflectance directly. The EEI material processing subsystem **554** may also be configured to identify and/or locate the EEI material **120** (block **1230**). Additionally, the EEI material processing

35

subsystem **554** may determine a property of the EEI material **120** (block **1240**). For example, the EEI material **120** may have a chemistry that is predictably responsive to a specified environmental condition, such that the chemistry undergoes a chemical or physical state change between an initial state and an end state. The chemical or physical state change may be a continuous state change, causing a continuous change in the state of the EEI material **120** (e.g., a continuous change in an optical property, such as a color, reflectance, etc., of the EEI material **120**). For example, the EEI material **120** may serve as an environmental indicator or sensor, such as a temperature monitor, measuring either cumulative heat exposure or passing beyond a set high or low temperature threshold value(s).

As illustrated in FIG. **13A**, the calibration data processing subsystem **556** may include a dedicated CPU **1305**, memory device **1315** and input/output device **1325**. Additionally, the calibration data processing subsystem **556** may include a location subsystem **1335**, a comparison sub system **1345** and an instruction sub system **1355**. The location sub system **1335** may locate or identify the calibration data. The comparison subsystem may compare the calibration data against data obtained by the indicia processing subsystem **552** and the EEI material processing subsystem **554**. Additionally, the instruction subsystem **1355** may send instructions to a device for calibration purposes (e.g., to calibrate a reader, scanner, printer, etc. based on the calibration data).

FIG. **13B** illustrates a flowchart of an example method **1300** that describes example processes performed by the calibration data processing subsystem **556** of FIG. **13A** according to an example embodiment of the present disclosure. Although the example processes are described with reference to the flowchart illustrated in FIG. **13B**, it will be appreciated that many other methods of performing the acts associated with the method **1300** may be used. For example, the order of some of the blocks may be changed, certain blocks may be combined with other blocks, blocks may be repeated, and some of the blocks described are optional. The method **1300** may be performed by processing logic that may comprise hardware (circuitry, dedicated logic, etc.), software, or a combination of both.

The example processes illustrated in method **1300** include identifying and/or locating the calibration data (block **1310**). The calibration data processing subsystem **556** may identify and/or locate the calibration data based on information obtained from the indicia processing subsystem **552**, the EEI material processing subsystem **554** or a combination thereof. For example, the calibration data may be encoded within an indicia **130** and may be obtained by the indicia processing subsystem **552**. The calibration data processing subsystem **556** may determine the values or information associated with the calibration data (block **1320**). For example, calibration data processing subsystem **556** may read the calibration data from a database or obtain the calibration data based on the decoded information read from the indicia processing subsystem **552**. Then, the calibration data processing subsystem **556** may calibrate a device (block **1330**). Specifically, the calibration data processing subsystem **556** may determine what calibration data should be encoded in the indicia **130** and provide that information to an imager, such that the imager properly encodes or otherwise provides the calibration data in an EEI **100**. Alternatively, the calibration data processing subsystem **556** may determine the calibration data information when reading an EEI and calibrate the reader, such that the reader associates a respective property of the EEI material **120** with an appropriate product characteristic.

36

Referring back to FIGS. **3** and **4**, the analysis subsystems **312**, **412** may perform similar processes and techniques as indicia processing subsystem **552** and EEI material processing subsystem **554**. Similarly, determination subsystem **314** may perform similar processes and techniques as EEI material processing subsystem **554**.

Encoding subsystem **316** may perform encoding processes and techniques according to any of the encoding described in U.S. Pat. Nos. 10,318,781; 10,546,172 U.S. patent application Ser. Nos. 16/526,505 and 16/526,527. In an example, a Zebra printer or encoder may perform encoding, such as the ZT400 Sereis RFID printers/encoders, which includes a factory or field-installable UHF RFID encoder to support a broad range of applications. Similarly, decoding subsystem **412** may perform decoding processes and techniques according to any of the decoding described in U.S. Pat. Nos. 10,318,781; 10,546,172; U.S. patent application Ser. Nos. 16/526,505 and 16/526,527. In an example, Zebra's PL5000 Series of hardware decoders may perform decoding and data capture for imagers and image capture subsystems. Specifically, the decoding subsystem **412** may provide decoding and data capture capabilities for 1D and 2D imagers.

Imaging subsystem **380** may perform imaging processes and techniques according to any of the imaging (e.g., printing, etching, etc.) described in U.S. Pat. Nos. 10,318,781; 10,546,172; U.S. patent application Ser. Nos. 16/526,505; 16/526,527; and 16/439,247. In an example, any of Zebra's desktop printers, industrial printers, mobile printers, card and badge printers, RFID printers and print engines may perform imaging.

Many modifications to and other embodiments of the invention set forth herein will come to mind to one skilled in the art to which these inventions pertain, once having the benefit of the teachings in the foregoing descriptions and associated drawings. Therefore, it is understood that the inventions are not limited to the specific embodiments disclosed, and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purpose of limitation.

The invention is claimed as follows:

1. A method of reading an environmental exposure indicator, the method comprising:
 - scanning an indicia associated with an environmental exposure indicator material that is configured, responsive to a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state and an end state, causing a change in an optical property of the environmental exposure indicator material, wherein the environmental exposure indicator material has a deployment state, between the creation state and the end state, at a deployment time;
 - determining calibration data encoded within the indicia based on the deployment state, the calibration data configured to be used to adjust indications of the environmental exposure indicator provided by the environmental exposure indicator material to compensate for a difference between the deployment state and the creation state;
 - determining, at a time of scanning, an optical property associated with the environmental exposure indicator material; and

37

determining a characteristic of the environmental exposure indicator based on the calibration data and the determined optical property.

2. The method of claim 1, wherein the characteristic is a remaining product life of a product associated with the environmental exposure indicator.

3. The method of claim 1, wherein the indicia includes a two-dimensional barcode symbol that includes encoded data identifiers, and wherein a first data identifier indicates product life equation parameters associated with the optical determined optical property of the environmental exposure indicator material.

4. The method of claim 1, wherein the environmental condition is selected from the group consisting of time, temperature, time-temperature product, and cumulative time-temperature.

5. The method of claim 1, wherein the environmental exposure indicator material is configured to continuously change its respective optical property between the creation state and the end state when exposed to the environmental condition.

6. An environmental exposure indicator comprising:
a substrate;

an environmental exposure indicator material provided on the substrate that is configured, responsive to a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state and an end state, causing a change in an optical property of the environmental exposure indicator material, wherein the optical property provides exposure information indicating an amount of exposure to the environmental condition of the environmental exposure material since the environmental exposure material was in the creation state;
an indicia provided on the substrate and associated with the environmental exposure indicator;
the environmental exposure indicator having a deployment state, between the creation state and the end state, at a deployment time; and
wherein the indicia is associated with calibration data based on the deployment state, the calibration data configured to be used to adjust indications of the cumulative environmental exposure provided by the environmental exposure material to compensate for a difference between the deployment state and the creation state.

7. The environmental exposure indicator of claim 6, wherein the calibration data includes at least one of (i) creation data, (ii) deployment data, and (iii) analysis data.

8. The environmental exposure indicator material of claim 6, wherein the deployment state is at least one of (i) estimated based on the creation state or a nominal creation state and exposure data and (ii) measured at the deployment time.

9. The environmental exposure indicator of claim 6, wherein the calibration data includes one of (i) a measured optical property at the deployment time and (ii) inputs to calculate the deployment state, or links to (i) or (ii).

10. The environmental exposure indicator of claim 6, wherein the indicia at least one of (i) encodes the calibration data and (ii) encodes information needed to retrieve the calibration data from a data repository.

11. The environmental exposure indicator of claim 6, wherein the calibration data includes a value of the optical property of the environmental exposure material in the deployment state.

38

12. The environmental exposure indicator of claim 6, wherein the optical property is reflectance, saturation, color, color density, optical density or a color hue.

13. The environmental exposure indicator of claim 6, wherein the indicia includes a two-dimensional barcode symbol that includes encoded data identifiers, and wherein a first data identifier indicates product life equation parameters associated with the optical property of the environmental exposure indicator material.

14. The environmental exposure indicator of claim 6, wherein the environmental condition is selected from the group consisting of time, temperature, time-temperature product, and cumulative time-temperature.

15. The environmental exposure indicator of claim 6, wherein the environmental exposure indicator material is configured to continuously change its respective optical property between the creation state and the end state when exposed to the environmental condition.

16. A device comprising:

a processor;
a memory coupled to the processor;
an image sensor communicatively coupled to the processor; and
an imaging subsystem communicatively coupled to the processor, the processor configured to:
obtain creation data associated with an environmental exposure indicator material provided on a substrate, wherein the environmental exposure indicator material is configured, responsive to a cumulative exposure to an environmental condition, to undergo a continuous chemical or physical state change between a creation state and an end state, causing a change in an optical property of the environmental exposure indicator material,
obtain deployment data of the environmental exposure indicator material, wherein the environmental exposure indicator material has a deployment state, between the creation state and the end state, at a deployment time,
cause the imaging subsystem to apply an indicia on the substrate, wherein the indicia is associated with calibration data based on the deployment state, the calibration data configured to be used to adjust indications of the cumulative environmental exposure provided by the environmental exposure material to compensate for a difference between the deployment state and the creation state, and wherein the calibration data includes at least one of (i) the creation data, (ii) the deployment data, and (iii) analysis data.

17. The device of claim 16, wherein obtaining deployment data includes one of (i) estimating the deployment state and (ii) measuring the deployment state.

18. The device of claim 16, wherein obtaining deployment data includes causing the image sensor to read a current optical property of the environmental exposure indicator material to determine the deployment state.

19. The device of claim 16, wherein the deployment state is estimated based on the creation state and exposure data.

20. The device of claim 16, wherein the deployment data includes one of (i) a measured optical property at the deployment time and (ii) inputs to calculate the deployment state, or a link to one of (i) or (ii).

21. The device of claim 20, wherein the link provides access to a database that stores at least one of (i) the measured optical property at the deployment time and (ii) the inputs to calculate the deployment state.

39

22. The device of claim 16, wherein the deployment state is associated with a current reflectance value, the current reflectance value is determined at the deployment time, and the deployment time is when the indicia is applied to the substrate.

23. The device of claim 16, wherein the deployment state is associated with an optical property of the environmental exposure indicator at the deployment state as read by the image sensor.

24. The device of claim 16, wherein the optical property is a reflectance value, saturation value, color value, color density value, optical density value or color hue value.

25. The device of claim 24, wherein the image sensor is configured to measure the optical property to obtain the deployment data, and wherein responsive to obtaining the deployment data, the imaging subsystem is configured to apply the indicia, wherein the indicia is based, at least in part, on the measured optical property.

26. The device of claim 16, wherein at least a portion of the calibration data associated with the environmental exposure indicator material is provided on the substrate prior to supplying the device with the substrate.

40

27. The device of claim 16, wherein the imaging subsystem is configured to at least one of (i) apply the indicia on the substrate along with calibration data and (ii) apply the indicia on the substrate along with a link to the calibration data.

28. The device of claim 16, wherein the indicia at least one of (i) encodes the calibration data and (ii) encodes information needed to retrieve the calibration data from a data repository.

29. The device of claim 16, wherein the creation data includes a timestamp indicative of a time of manufacture of the environmental exposure material.

30. The device of claim 16, wherein the image sensor is caused to read a respective optical property of the environmental exposure indicator material, and wherein the processor is further configured to compare the respective optical property to at least a portion of the calibration data.

31. The device of claim 16, wherein the environmental condition is selected from the group consisting of time, temperature, time-temperature product, and cumulative time-temperature.

* * * * *