



US012057715B2

(12) **United States Patent**
Leabman et al.

(10) **Patent No.:** **US 12,057,715 B2**
(45) **Date of Patent:** ***Aug. 6, 2024**

(54) **SYSTEMS AND METHODS OF WIRELESSLY DELIVERING POWER TO A WIRELESS-POWER RECEIVER DEVICE IN RESPONSE TO A CHANGE OF ORIENTATION OF THE WIRELESS-POWER RECEIVER DEVICE**

(71) Applicant: **Energous Corporation**, San Jose, CA (US)
(72) Inventors: **Michael A. Leabman**, San Ramon, CA (US); **Gregory Scott Brewer**, Livermore, CA (US)

(73) Assignee: **Energous Corporation**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/296,339**

(22) Filed: **Apr. 5, 2023**

(65) **Prior Publication Data**
US 2023/0352982 A1 Nov. 2, 2023

Related U.S. Application Data
(63) Continuation of application No. 17/216,474, filed on Mar. 29, 2021, now Pat. No. 11,652,369, which is a (Continued)

(51) **Int. Cl.**
H02J 7/00 (2006.01)
H02J 50/20 (2016.01)
(Continued)

(52) **U.S. Cl.**
CPC **H02J 50/20** (2016.02); **H02J 7/00034** (2020.01); **H02J 50/402** (2020.01); **H02J 50/80** (2016.02)

(58) **Field of Classification Search**
CPC H02J 50/20
(Continued)

(56) **References Cited**
U.S. PATENT DOCUMENTS
787,412 A 4/1905 Tesla
2,811,624 A 10/1957 Haagensen
(Continued)


FOREIGN PATENT DOCUMENTS
CN 1829999 A 9/2006
CN 101465471 A 6/2009
(Continued)

OTHER PUBLICATIONS
Energous Corp., IPRP, PCT/US2014/037072, Nov. 10, 2015, 6 pgs.
(Continued)

Primary Examiner — Yalkew Fantu
(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**
An example wireless-power receiver comprises one or more processors configured to perform operations, including receiving, via one or more antenna elements of an antenna array, a plurality of first electromagnetic (EM) signals. Each antenna element of the one or more antenna elements of the antenna array has a respective polarization. The one or more processors are further configured to perform operations including, in response to a change in an orientation of the wireless-power receiver, changing the respective polarization to a changed polarization for the one or more antenna elements of the antenna array, and receiving, via the one or more antenna elements of the antenna array, and while the one or more antenna elements have the changed polarization, a plurality of second EM signals.

20 Claims, 17 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/912,520, filed on Mar. 5, 2018, now Pat. No. 10,965,164, which is a continuation-in-part of application No. 13/891,399, filed on May 10, 2013, now Pat. No. 9,912,199, said application No. 15/912,520 is a continuation-in-part of application No. 13/891,445, filed on May 10, 2013, now Pat. No. 10,103,582.

(60) Provisional application No. 61/668,799, filed on Jul. 6, 2012, provisional application No. 61/677,706, filed on Jul. 31, 2012, provisional application No. 61/720,798, filed on Oct. 31, 2012.

(51) **Int. Cl.**

H02J 50/40 (2016.01)
H02J 50/80 (2016.01)

(58) **Field of Classification Search**

USPC 320/108
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,863,148 A 12/1958 Gammon et al.
3,167,775 A 1/1965 Guertler
3,434,678 A 3/1969 Brown et al.
3,696,384 A 10/1972 Lester
3,754,269 A 8/1973 Clavin
4,101,895 A 7/1978 Jones, Jr.
4,360,741 A 11/1982 Fitzsimmons et al.
4,944,036 A 7/1990 Hyatt
4,995,010 A 2/1991 Knight
5,142,292 A 8/1992 Chang
5,200,759 A 4/1993 McGinnis
5,211,471 A 5/1993 Rohrs
5,276,455 A 1/1994 Fitzsimmons et al.
5,548,292 A 8/1996 Hirshfield et al.
5,556,749 A 9/1996 Mitsuhashi et al.
5,568,088 A 10/1996 Dent et al.
5,631,572 A 5/1997 Sheen et al.
5,646,633 A 7/1997 Dahlberg
5,697,063 A 12/1997 Kishigami et al.
5,712,642 A 1/1998 Hulderman
5,936,527 A 8/1999 Isaacman et al.
5,982,139 A 11/1999 Parise
6,046,708 A 4/2000 MacDonald, Jr. et al.
6,061,025 A 5/2000 Jackson et al.
6,127,799 A 10/2000 Krishnan
6,127,942 A 10/2000 Welle
6,163,296 A 12/2000 Lier et al.
6,176,433 B1 1/2001 Uesaka et al.
6,271,799 B1 8/2001 Rief
6,289,237 B1 9/2001 Mickle et al.
6,329,908 B1 12/2001 Frecska
6,400,586 B2 6/2002 Raddi et al.
6,421,235 B2 7/2002 Ditzik
6,437,685 B2 8/2002 Hanaki
6,456,253 B1 9/2002 Rummeli et al.
6,476,795 B1 11/2002 Derocher et al.
6,501,414 B2 12/2002 Arndt et al.
6,583,723 B2 6/2003 Watanabe et al.
6,597,897 B2 7/2003 Tang
6,615,074 B2 9/2003 Mickle et al.
6,650,376 B1 11/2003 Obitsu
6,664,920 B1 12/2003 Mott et al.
6,680,700 B2 1/2004 Hilgers
6,798,716 B1 9/2004 Charych
6,803,744 B1 10/2004 Sabo
6,853,197 B1 2/2005 McFarland
6,856,291 B2 2/2005 Mickle et al.
6,911,945 B2 6/2005 Korva
6,960,968 B2 11/2005 Odendaal et al.
6,967,462 B1 11/2005 Landis

6,988,026 B2 1/2006 Breed et al.
7,003,350 B2 2/2006 Denker et al.
7,012,572 B1 3/2006 Schaffner et al.
7,027,311 B2 4/2006 Vanderelli et al.
7,068,234 B2 6/2006 Sievenpiper
7,068,991 B2 6/2006 Parise
7,079,079 B2 7/2006 Jo et al.
7,183,748 B1 2/2007 Unno et al.
7,191,013 B1 3/2007 Miranda et al.
7,193,644 B2 3/2007 Carter
7,196,663 B2 3/2007 Bolzer et al.
7,205,749 B2 4/2007 Hagen et al.
7,215,296 B2 5/2007 Abramov et al.
7,222,356 B1 5/2007 Yonezawa et al.
7,274,334 B2 9/2007 O'Riordan et al.
7,274,336 B2 9/2007 Carson
7,351,975 B2 4/2008 Brady et al.
7,359,730 B2 4/2008 Dennis et al.
7,372,408 B2 5/2008 Gaucher
7,392,068 B2 6/2008 Dayan
7,403,803 B2 7/2008 Mickle et al.
7,443,057 B2 10/2008 Nunally
7,451,839 B2 11/2008 Perlman
7,463,201 B2 12/2008 Chiang et al.
7,471,247 B2 12/2008 Saily
7,535,195 B1 5/2009 Horovitz et al.
7,614,556 B2 11/2009 Overhultz et al.
7,639,994 B2 12/2009 Greene et al.
7,643,312 B2 1/2010 Vanderelli et al.
7,652,577 B1 1/2010 Madhow et al.
7,679,576 B2 3/2010 Riedel et al.
7,702,771 B2 4/2010 Ewing et al.
7,786,419 B2 8/2010 Hyde et al.
7,812,771 B2 10/2010 Greene et al.
7,830,312 B2 11/2010 Choudhury et al.
7,844,306 B2 11/2010 Shearer et al.
7,868,482 B2 1/2011 Greene et al.
7,898,105 B2 3/2011 Greene et al.
7,904,117 B2 3/2011 Doan et al.
7,911,386 B1 3/2011 Itoh et al.
7,925,308 B2 4/2011 Greene et al.
7,948,208 B2 5/2011 Partovi et al.
8,049,676 B2 11/2011 Yoon et al.
8,055,003 B2 11/2011 Mittleman et al.
8,070,595 B2 12/2011 Alderucci et al.
8,072,380 B2 12/2011 Crouch
8,092,301 B2 1/2012 Alderucci et al.
8,099,140 B2 1/2012 Arai
8,115,448 B2 2/2012 John
8,159,090 B2 4/2012 Greene et al.
8,159,364 B2 4/2012 Zeine
8,180,286 B2 5/2012 Yamasuge
8,184,454 B2 5/2012 Mao
8,228,194 B2 7/2012 Mickle
8,234,509 B2 7/2012 Gioscia et al.
8,264,101 B2 9/2012 Hyde et al.
8,264,291 B2 9/2012 Morita
8,276,325 B2 10/2012 Clifton et al.
8,278,784 B2 10/2012 Cook et al.
8,284,101 B2 10/2012 Fusco
8,310,201 B1 11/2012 Wright
8,338,991 B2 12/2012 Von Novak et al.
8,362,745 B2 1/2013 Tinaphong
8,380,255 B2 2/2013 Shearer et al.
8,384,600 B2 2/2013 Huang et al.
8,410,953 B2 4/2013 Zeine
8,411,963 B2 4/2013 Luff
8,432,062 B2 4/2013 Greene et al.
8,432,071 B2 4/2013 Huang et al.
8,446,248 B2 5/2013 Zeine
8,447,234 B2 5/2013 Cook et al.
8,451,189 B1 5/2013 Fluhler
8,452,235 B2 5/2013 Kirby et al.
8,457,656 B2 6/2013 Perkins et al.
8,461,817 B2 6/2013 Martin et al.
8,467,733 B2 6/2013 Leabman
8,497,601 B2 7/2013 Hall et al.
8,497,658 B2 7/2013 Von Novak et al.
8,552,597 B2 8/2013 Song et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,558,661 B2	10/2013	Zeine	9,520,748 B2	12/2016	Hyde et al.
8,560,026 B2	10/2013	Chanterac	9,521,926 B1	12/2016	Leabman et al.
8,564,485 B2	10/2013	Milosavljevic et al.	9,522,270 B2	12/2016	Perryman et al.
8,604,746 B2	12/2013	Lee	9,532,748 B2	1/2017	Denison et al.
8,614,643 B2	12/2013	Leabman	9,537,354 B2	1/2017	Bell et al.
8,621,245 B2	12/2013	Shearer et al.	9,537,357 B2	1/2017	Leabman
8,626,249 B2	1/2014	Ungari et al.	9,537,358 B2	1/2017	Leabman
8,629,576 B2	1/2014	Levine	9,538,382 B2	1/2017	Bell et al.
8,653,966 B2	2/2014	Rao et al.	9,544,640 B2	1/2017	Lau
8,655,272 B2	2/2014	Saunamäki	9,559,553 B2	1/2017	Bae
8,674,551 B2	3/2014	Low et al.	9,564,773 B2	2/2017	Pogorelik et al.
8,686,685 B2	4/2014	Moshfeghi	9,571,974 B2	2/2017	Choi et al.
8,686,905 B2	4/2014	Shtrom	9,590,317 B2	3/2017	Zimmerman et al.
8,712,355 B2	4/2014	Black et al.	9,590,444 B2	3/2017	Walley
8,712,485 B2	4/2014	Tam	9,620,996 B2	4/2017	Zeine
8,718,773 B2	5/2014	Wills et al.	9,647,328 B2	5/2017	Dobric
8,729,737 B2	5/2014	Schatz et al.	9,706,137 B2	7/2017	Scanlon et al.
8,736,228 B1	5/2014	Freed et al.	9,711,999 B2	7/2017	Hietala et al.
8,760,113 B2	6/2014	Keating	9,723,635 B2	8/2017	Nambord et al.
8,770,482 B2	7/2014	Ackermann et al.	9,787,103 B1	10/2017	Leabman et al.
8,772,960 B2	7/2014	Yoshida	9,793,758 B2	10/2017	Leabman
8,823,319 B2	9/2014	Von Novak, III et al.	9,793,764 B2	10/2017	Perry
8,832,646 B1	9/2014	Wendling	9,800,080 B2	10/2017	Leabman et al.
8,854,176 B2	10/2014	Zeine	9,800,172 B1	10/2017	Leabman
8,860,364 B2	10/2014	Low et al.	9,806,564 B2	10/2017	Leabman
8,897,770 B1	11/2014	Frolov et al.	9,812,890 B1	11/2017	Leabman et al.
8,903,456 B2	12/2014	Chu et al.	9,819,230 B2	11/2017	Petras et al.
8,917,057 B2	12/2014	Hui	9,824,815 B2	11/2017	Leabman et al.
8,923,189 B2	12/2014	Leabman	9,825,674 B1	11/2017	Leabman
8,928,544 B2	1/2015	Massie et al.	9,831,718 B2	11/2017	Leabman et al.
8,937,408 B2	1/2015	Ganem et al.	9,838,083 B2	12/2017	Bell et al.
8,946,940 B2	2/2015	Kim et al.	9,843,201 B1	12/2017	Leabman et al.
8,963,486 B2	2/2015	Kirby et al.	9,843,213 B2	12/2017	Leabman et al.
8,970,070 B2	3/2015	Sada et al.	9,843,229 B2	12/2017	Leabman
8,989,053 B1	3/2015	Skaaksrud et al.	9,843,763 B2	12/2017	Leabman et al.
9,000,616 B2	4/2015	Greene et al.	9,847,669 B2	12/2017	Leabman
9,001,622 B2	4/2015	Perry	9,847,677 B1	12/2017	Leabman
9,006,934 B2	4/2015	Kozakai et al.	9,847,679 B2	12/2017	Bell et al.
9,021,277 B2	4/2015	Shearer et al.	9,853,361 B2	12/2017	Chen et al.
9,030,161 B2	5/2015	Lu et al.	9,853,458 B1	12/2017	Bell et al.
9,059,598 B2	6/2015	Kang et al.	9,853,485 B2	12/2017	Contopanagos
9,059,599 B2	6/2015	Won et al.	9,853,692 B1	12/2017	Bell et al.
9,077,188 B2	7/2015	Moshfeghi	9,859,756 B2	1/2018	Leabman et al.
9,083,595 B2	7/2015	Rakib et al.	9,859,757 B1	1/2018	Leabman et al.
9,088,216 B2	7/2015	Garrity et al.	9,859,758 B1	1/2018	Leabman
9,124,125 B2	9/2015	Leabman et al.	9,859,797 B1	1/2018	Leabman
9,130,397 B2	9/2015	Leabman et al.	9,866,279 B2	1/2018	Bell et al.
9,130,602 B2	9/2015	Cook	9,867,032 B2	1/2018	Verma
9,142,998 B2	9/2015	Yu et al.	9,867,062 B1	1/2018	Bell et al.
9,143,000 B2	9/2015	Leabman et al.	9,871,301 B2	1/2018	Contopanagos
9,143,010 B2	9/2015	Urano	9,871,387 B1	1/2018	Bell et al.
9,153,074 B2	10/2015	Zhou et al.	9,871,398 B1	1/2018	Leabman
9,178,389 B2	11/2015	Hwang	9,876,379 B1	1/2018	Leabman et al.
9,225,196 B2	12/2015	Huang et al.	9,876,380 B1	1/2018	Leabman et al.
9,240,469 B2	1/2016	Sun et al.	9,876,394 B1	1/2018	Leabman
9,242,411 B2	1/2016	Kritchman et al.	9,876,536 B1	1/2018	Bell et al.
9,244,500 B2	1/2016	Cain et al.	9,876,648 B2	1/2018	Bell
9,252,628 B2	2/2016	Leabman et al.	9,882,394 B1	1/2018	Bell et al.
9,270,344 B2	2/2016	Rosenberg	9,882,395 B1	1/2018	Leabman et al.
9,276,329 B2	3/2016	Jones et al.	9,882,427 B2	1/2018	Leabman et al.
9,282,582 B1	3/2016	Dunsbergen et al.	9,882,430 B1	1/2018	Leabman et al.
9,294,840 B1	3/2016	Anderson et al.	9,887,584 B1	2/2018	Bell et al.
9,297,896 B1	3/2016	Andrews	9,887,739 B2	2/2018	Leabman et al.
9,318,898 B2	4/2016	John	9,891,669 B2	2/2018	Bell
9,368,020 B1	6/2016	Bell et al.	9,893,535 B2	2/2018	Leabman
9,401,977 B1	7/2016	Gaw	9,893,538 B1	2/2018	Bell et al.
9,409,490 B2	8/2016	Kawashima	9,893,554 B2	2/2018	Bell et al.
9,419,335 B2	8/2016	Pintos	9,893,555 B1	2/2018	Leabman et al.
9,419,443 B2	8/2016	Leabman	9,893,564 B2	2/2018	de Rochemont
9,438,045 B1	9/2016	Leabman	9,899,744 B1	2/2018	Contopanagos et al.
9,438,046 B1	9/2016	Leabman	9,899,844 B1	2/2018	Bell et al.
9,444,283 B2	9/2016	Son et al.	9,899,861 B1	2/2018	Leabman et al.
9,450,449 B1	9/2016	Leabman et al.	9,912,199 B2	3/2018	Leabman et al.
9,461,502 B2	10/2016	Lee et al.	9,916,485 B1	3/2018	Lilly et al.
9,520,725 B2	12/2016	Masaoka et al.	9,917,477 B1	3/2018	Bell et al.
			9,923,386 B1	3/2018	Leabman et al.
			9,939,864 B1	4/2018	Bell et al.
			9,965,009 B1	5/2018	Bell et al.
			9,966,765 B1	5/2018	Leabman

(56)

References Cited

U.S. PATENT DOCUMENTS

9,966,784 B2	5/2018	Leabman	10,396,604 B2	8/2019	Bell et al.
9,967,743 B1	5/2018	Bell et al.	10,439,442 B2	10/2019	Hosseini et al.
9,973,008 B1	5/2018	Leabman	10,447,093 B2	10/2019	Hosseini
10,003,211 B1	6/2018	Leabman et al.	10,476,312 B2	11/2019	Johnston et al.
10,008,777 B1	6/2018	Broyde et al.	10,483,768 B2	11/2019	Bell et al.
10,014,728 B1	7/2018	Leabman	10,490,346 B2	11/2019	Contopanagos
10,027,159 B2	7/2018	Hosseini	10,491,029 B2	11/2019	Hosseini
10,038,337 B1	7/2018	Leabman et al.	10,498,144 B2	12/2019	Leabman et al.
10,050,462 B1	8/2018	Leabman et al.	10,511,097 B2	12/2019	Kornaros et al.
10,056,782 B1	8/2018	Leabman	10,511,196 B2	12/2019	Hosseini
10,063,064 B1	8/2018	Bell et al.	10,516,289 B2	12/2019	Leabman et al.
10,068,703 B1	9/2018	Contopanagos	10,516,301 B2	12/2019	Leabman
10,075,008 B1	9/2018	Bell et al.	10,523,033 B2	12/2019	Leabman
10,090,699 B1	10/2018	Leabman	10,523,058 B2	12/2019	Leabman
10,090,714 B2	10/2018	Bohn et al.	10,554,052 B2	2/2020	Bell et al.
10,090,886 B1	10/2018	Bell et al.	10,594,165 B2	3/2020	Hosseini
10,103,552 B1	10/2018	Leabman et al.	10,615,647 B2	4/2020	Johnston et al.
10,103,582 B2	10/2018	Leabman et al.	10,680,319 B2	6/2020	Hosseini et al.
10,110,046 B1	10/2018	Esquibel et al.	10,714,984 B2	7/2020	Hosseini et al.
10,122,219 B1	11/2018	Hosseini et al.	10,734,717 B2	8/2020	Hosseini
10,124,754 B1	11/2018	Leabman	10,778,041 B2	9/2020	Leabman
10,128,686 B1	11/2018	Leabman et al.	10,965,164 B2 *	3/2021	Leabman H02J 50/20
10,134,260 B1	11/2018	Bell et al.	10,985,617 B1	4/2021	Johnston et al.
10,135,112 B1	11/2018	Hosseini	11,652,369 B2 *	5/2023	Leabman H02J 50/20
10,135,294 B1	11/2018	Leabman			307/104
10,141,771 B1	11/2018	Hosseini et al.	2001/0027876 A1	10/2001	Tsukamoto et al.
10,148,097 B1	12/2018	Leabman et al.	2002/0001307 A1	1/2002	Nguyen et al.
10,153,645 B1	12/2018	Bell et al.	2002/0024471 A1	2/2002	Ishitobi
10,153,653 B1	12/2018	Bell et al.	2002/0028655 A1	3/2002	Rosener et al.
10,153,660 B1	12/2018	Leabman et al.	2002/0034958 A1	3/2002	Oberschmidt et al.
10,158,257 B2	12/2018	Leabman	2002/0054330 A1	5/2002	Jinbo et al.
10,158,259 B1	12/2018	Leabman	2002/0065052 A1	5/2002	Pande et al.
10,164,478 B2	12/2018	Leabman	2002/0072784 A1	6/2002	Sheppard et al.
10,170,917 B1	1/2019	Bell et al.	2002/0095980 A1	7/2002	Breed et al.
10,177,594 B2	1/2019	Contopanagos	2002/0103447 A1	8/2002	Terry
10,181,756 B2	1/2019	Bae et al.	2002/0123776 A1	9/2002	Von Arx
10,186,892 B2	1/2019	Hosseini et al.	2002/0133592 A1	9/2002	Matsuda
10,186,893 B2	1/2019	Bell et al.	2002/0171594 A1	11/2002	Fang
10,186,911 B2	1/2019	Leabman	2002/0172223 A1	11/2002	Stilp
10,186,913 B2	1/2019	Leabman et al.	2003/0005759 A1	1/2003	Breed et al.
10,193,396 B1	1/2019	Bell et al.	2003/0038750 A1	2/2003	Chen
10,199,835 B2	2/2019	Leabman	2003/0058187 A1	3/2003	Billiet et al.
10,199,849 B1	2/2019	Bell	2003/0076274 A1	4/2003	Phelan et al.
10,199,850 B2	2/2019	Leabman	2003/0179152 A1	9/2003	Watada et al.
10,205,239 B1	2/2019	Contopanagos et al.	2003/0179573 A1	9/2003	Chun
10,206,185 B2	2/2019	Leabman et al.	2003/0192053 A1	10/2003	Sheppard et al.
10,211,674 B1	2/2019	Leabman et al.	2004/0019624 A1	1/2004	Sukegawa
10,211,680 B2	2/2019	Leabman et al.	2004/0020100 A1	2/2004	O'Brien et al.
10,211,682 B2	2/2019	Bell et al.	2004/0036657 A1	2/2004	Forster et al.
10,211,685 B2	2/2019	Bell et al.	2004/0066251 A1	4/2004	Eleftheriades et al.
10,218,207 B2	2/2019	Hosseini et al.	2004/0107641 A1	6/2004	Walton et al.
10,218,227 B2	2/2019	Leabman et al.	2004/0113543 A1	6/2004	Daniels
10,223,717 B1	3/2019	Bell	2004/0119675 A1	6/2004	Washio et al.
10,224,758 B2	3/2019	Leabman et al.	2004/0130425 A1	7/2004	Dayan et al.
10,224,982 B1 *	3/2019	Leabman H02J 50/20	2004/0130442 A1	7/2004	Breed
10,230,266 B1	3/2019	Leabman et al.	2004/0142733 A1	7/2004	Parise
10,243,414 B1	3/2019	Leabman et al.	2004/0145342 A1	7/2004	Lyon
10,256,657 B2	4/2019	Hosseini et al.	2004/0155832 A1	8/2004	Yuanzhu
10,256,677 B2	4/2019	Hosseini et al.	2004/0196190 A1	10/2004	Mendolia et al.
10,263,432 B1 *	4/2019	Leabman H02J 50/402	2004/0203979 A1	10/2004	Attar et al.
10,263,476 B2	4/2019	Leabman	2004/0207559 A1	10/2004	Milosavljevic
10,277,054 B2	4/2019	Hosseini	2004/0218759 A1	11/2004	Yacobi
10,291,055 B1	5/2019	Bell et al.	2004/0241402 A1	12/2004	Kawate
10,291,066 B1	5/2019	Leabman	2004/0259604 A1	12/2004	Mickle et al.
10,291,294 B2	5/2019	Leabman	2004/0263124 A1	12/2004	Wieck et al.
10,298,024 B2	5/2019	Leabman	2005/0007276 A1	1/2005	Barrick et al.
10,298,133 B2	5/2019	Leabman	2005/0030118 A1	2/2005	Wang
10,305,315 B2	5/2019	Leabman et al.	2005/0046584 A1	3/2005	Breed
10,312,715 B2	6/2019	Leabman	2005/0055316 A1	3/2005	Williams
10,320,446 B2	6/2019	Hosseini	2005/0077872 A1	4/2005	Single
10,333,332 B1	6/2019	Hosseini	2005/0093766 A1	5/2005	Turner
10,355,534 B2	7/2019	Johnston et al.	2005/0116683 A1	6/2005	Cheng
10,381,880 B2	8/2019	Leabman et al.	2005/0117660 A1	6/2005	Vialle et al.
10,389,161 B2	8/2019	Hosseini et al.	2005/0134517 A1	6/2005	Gottl
10,396,588 B2	8/2019	Leabman	2005/0171411 A1	8/2005	KenKnight
			2005/0198673 A1	9/2005	Kit et al.
			2005/0227619 A1	10/2005	Lee et al.
			2005/0232469 A1	10/2005	Schofield
			2005/0237249 A1	10/2005	Nagel

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0237258	A1	10/2005	Abramov et al.	2008/0211458	A1	9/2008	Lawther et al.
2005/0282591	A1	12/2005	Shaff	2008/0233890	A1	9/2008	Baker
2006/0013335	A1	1/2006	Leabman	2008/0248758	A1	10/2008	Schedelbeck et al.
2006/0019712	A1	1/2006	Choi	2008/0248846	A1	10/2008	Stronach et al.
2006/0030279	A1	2/2006	Leabman et al.	2008/0258993	A1	10/2008	Gummalla et al.
2006/0033674	A1	2/2006	Essig, Jr. et al.	2008/0266191	A1	10/2008	Hilgers
2006/0056855	A1	3/2006	Nakagawa et al.	2008/0278378	A1	11/2008	Chang et al.
2006/0071308	A1	4/2006	Tang et al.	2008/0309452	A1	12/2008	Zeine
2006/0092079	A1	5/2006	de Rochemont	2009/0002493	A1	1/2009	Kates
2006/0094425	A1	5/2006	Mickle et al.	2009/0010316	A1	1/2009	Rofougaran et al.
2006/0113955	A1	6/2006	Nunally	2009/0019183	A1	1/2009	Wu et al.
2006/0119532	A1	6/2006	Yun et al.	2009/0036065	A1	2/2009	Siu
2006/0136004	A1	6/2006	Cowan et al.	2009/0039828	A1	2/2009	Jakubowski
2006/0160517	A1	7/2006	Yoon	2009/0047998	A1	2/2009	Alberth, Jr.
2006/0183473	A1	8/2006	Ukon	2009/0058354	A1	3/2009	Harrison
2006/0190063	A1	8/2006	Kanzius	2009/0058361	A1	3/2009	John
2006/0192913	A1	8/2006	Shutou et al.	2009/0058731	A1	3/2009	Geary et al.
2006/0199620	A1	9/2006	Greene et al.	2009/0060012	A1	3/2009	Gresset et al.
2006/0238365	A1	10/2006	Vecchione et al.	2009/0067198	A1	3/2009	Graham et al.
2006/0266564	A1	11/2006	Perlman et al.	2009/0067208	A1	3/2009	Martin et al.
2006/0266917	A1	11/2006	Baldis et al.	2009/0073066	A1	3/2009	Jordon et al.
2006/0278706	A1	12/2006	Hatakayama et al.	2009/0096412	A1	4/2009	Huang
2006/0284593	A1	12/2006	Nagy et al.	2009/0096413	A1	4/2009	Partovi
2006/0287094	A1	12/2006	Mahaffey et al.	2009/0102292	A1	4/2009	Cook et al.
2007/0007821	A1	1/2007	Rossetti	2009/0102296	A1	4/2009	Greene et al.
2007/0019693	A1	1/2007	Graham	2009/0108679	A1	4/2009	Porwal
2007/0021140	A1	1/2007	Keyes, IV et al.	2009/0122847	A1	5/2009	Nysen et al.
2007/0060185	A1	3/2007	Simon et al.	2009/0128262	A1	5/2009	Lee et al.
2007/0070490	A1	3/2007	Tsunoda et al.	2009/0157911	A1	6/2009	Aihara
2007/0090997	A1	4/2007	Brown et al.	2009/0174604	A1	7/2009	Keskitalo
2007/0093269	A1	4/2007	Leabman et al.	2009/0180653	A1	7/2009	Sjursen et al.
2007/0097653	A1	5/2007	Gilliland et al.	2009/0200985	A1	8/2009	Zane et al.
2007/0103110	A1	5/2007	Sagoo	2009/0206791	A1	8/2009	Jung
2007/0106894	A1	5/2007	Zhang	2009/0207090	A1	8/2009	Pettus et al.
2007/0109121	A1	5/2007	Cohen	2009/0207092	A1	8/2009	Nysen et al.
2007/0139000	A1	6/2007	Kozuma	2009/0218884	A1	9/2009	Soar
2007/0149162	A1	6/2007	Greene et al.	2009/0218891	A1	9/2009	McCollough
2007/0164868	A1	7/2007	Deavours et al.	2009/0219903	A1	9/2009	Alamouti et al.
2007/0173196	A1	7/2007	Gallic	2009/0243397	A1	10/2009	Cook et al.
2007/0173214	A1	7/2007	Mickle et al.	2009/0256752	A1	10/2009	Akkermans et al.
2007/0178857	A1	8/2007	Greene et al.	2009/0264069	A1	10/2009	Yamasuge
2007/0178945	A1	8/2007	Cook et al.	2009/0271048	A1	10/2009	Wakamatsu
2007/0182367	A1	8/2007	Partovi	2009/0280866	A1	11/2009	Lo et al.
2007/0191074	A1	8/2007	Harrist et al.	2009/0281678	A1	11/2009	Wakamatsu
2007/0191075	A1	8/2007	Greene et al.	2009/0284082	A1	11/2009	Mohammadian
2007/0197281	A1	8/2007	Stronach	2009/0284083	A1	11/2009	Karalis et al.
2007/0210960	A1	9/2007	Rofougaran et al.	2009/0284220	A1	11/2009	Toncich et al.
2007/0222681	A1	9/2007	Greene et al.	2009/0284227	A1	11/2009	Mohammadian et al.
2007/0228833	A1	10/2007	Stevens et al.	2009/0284325	A1	11/2009	Rossiter et al.
2007/0229261	A1	10/2007	Zimmerman et al.	2009/0286475	A1	11/2009	Toncich et al.
2007/0240297	A1	10/2007	Yang et al.	2009/0286476	A1	11/2009	Toncich et al.
2007/0257634	A1	11/2007	Leschin et al.	2009/0291634	A1	11/2009	Saarisalo
2007/0273486	A1	11/2007	Shiotsu	2009/0299175	A1	12/2009	Bernstein et al.
2007/0291165	A1	12/2007	Wang	2009/0308936	A1	12/2009	Nitzan et al.
2007/0296639	A1	12/2007	Hook et al.	2009/0312046	A1	12/2009	Clevenger et al.
2007/0298846	A1	12/2007	Greene et al.	2009/0315412	A1	12/2009	Yamamoto et al.
2008/0014897	A1	1/2008	Cook et al.	2009/0322281	A1	12/2009	Kamijo et al.
2008/0024376	A1	1/2008	Norris et al.	2010/0001683	A1	1/2010	Huang et al.
2008/0048917	A1	2/2008	Achour et al.	2010/0007307	A1	1/2010	Baarman et al.
2008/0062062	A1	3/2008	Borau et al.	2010/0007569	A1	1/2010	Sim et al.
2008/0062255	A1	3/2008	Gal	2010/0019686	A1	1/2010	Gutierrez, Jr.
2008/0067874	A1	3/2008	Tseng	2010/0019908	A1	1/2010	Cho et al.
2008/0074324	A1	3/2008	Puzella et al.	2010/0026605	A1	2/2010	Yang et al.
2008/0089277	A1	4/2008	Alexander et al.	2010/0027379	A1	2/2010	Saulnier et al.
2008/0110263	A1	5/2008	Klessel et al.	2010/0029383	A1	2/2010	Dai
2008/0113816	A1	5/2008	Mahaffey et al.	2010/0033021	A1	2/2010	Bennett
2008/0122297	A1	5/2008	Arai	2010/0033390	A1	2/2010	Alamouti et al.
2008/0123383	A1	5/2008	Shionoiri	2010/0034238	A1	2/2010	Bennett
2008/0129536	A1	6/2008	Randall et al.	2010/0041453	A1	2/2010	Grimm, Jr.
2008/0140278	A1	6/2008	Breed	2010/0044123	A1	2/2010	Perlman et al.
2008/0169910	A1	7/2008	Greene et al.	2010/0054200	A1	3/2010	Tsai
2008/0197802	A1	8/2008	Onishi	2010/0060534	A1	3/2010	Oodachi
2008/0204342	A1	8/2008	Kharadly	2010/0066631	A1	3/2010	Puzella et al.
2008/0204350	A1	8/2008	Tam et al.	2010/0075607	A1	3/2010	Hosoya
2008/0210762	A1	9/2008	Osada et al.	2010/0079005	A1	4/2010	Hyde et al.
				2010/0079011	A1	4/2010	Hyde et al.
				2010/0082193	A1	4/2010	Chiappetta
				2010/0087227	A1	4/2010	Franco et al.
				2010/0090524	A1	4/2010	Obayashi

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0090656	A1	4/2010	Shearer et al.	2011/0074349	A1	3/2011	Ghovanloo
2010/0109443	A1	5/2010	Cook et al.	2011/0074620	A1	3/2011	Wintermantel
2010/0117596	A1	5/2010	Cook et al.	2011/0078092	A1	3/2011	Kim et al.
2010/0117926	A1	5/2010	DeJean, II	2011/0090126	A1	4/2011	Szini et al.
2010/0119234	A1	5/2010	Suematsu et al.	2011/0109167	A1	5/2011	Park et al.
2010/0123618	A1	5/2010	Martin et al.	2011/0114401	A1	5/2011	Kanno
2010/0123624	A1	5/2010	Miner et al.	2011/0115303	A1	5/2011	Baarman et al.
2010/0124040	A1	5/2010	Diebel et al.	2011/0115432	A1	5/2011	El-Maleh
2010/0127660	A1	5/2010	Cook et al.	2011/0115605	A1	5/2011	Dimig et al.
2010/0142418	A1	6/2010	Nishioka et al.	2011/0121660	A1	5/2011	Azancot et al.
2010/0142509	A1	6/2010	Zhu et al.	2011/0122018	A1	5/2011	Tarnig et al.
2010/0148723	A1	6/2010	Cook et al.	2011/0122026	A1	5/2011	DeLaquil et al.
2010/0151808	A1	6/2010	Toncich et al.	2011/0127845	A1	6/2011	Walley et al.
2010/0156721	A1	6/2010	Alamouti et al.	2011/0127952	A1	6/2011	Walley et al.
2010/0156741	A1	6/2010	Vazquez et al.	2011/0133655	A1	6/2011	Recker et al.
2010/0164296	A1	7/2010	Kurs et al.	2011/0133691	A1	6/2011	Hautanen
2010/0164433	A1	7/2010	Janefalkner et al.	2011/0148578	A1	6/2011	Aloi et al.
2010/0167664	A1	7/2010	Szini	2011/0148595	A1	6/2011	Miller et al.
2010/0171461	A1	7/2010	Baarman et al.	2011/0151789	A1	6/2011	Viglione et al.
2010/0171676	A1	7/2010	Tani et al.	2011/0154429	A1	6/2011	Stantchev
2010/0174629	A1	7/2010	Taylor et al.	2011/0156493	A1	6/2011	Bennett
2010/0176934	A1	7/2010	Chou et al.	2011/0156494	A1	6/2011	Mashinsky
2010/0181961	A1	7/2010	Novak et al.	2011/0156640	A1	6/2011	Moshfeghi
2010/0181964	A1	7/2010	Huggins et al.	2011/0163128	A1	7/2011	Taguchi et al.
2010/0194206	A1	8/2010	Burdo et al.	2011/0175455	A1	7/2011	Hashiguchi
2010/0201189	A1	8/2010	Kirby et al.	2011/0175461	A1	7/2011	Tinaphong
2010/0201201	A1	8/2010	Mobarhan et al.	2011/0181120	A1	7/2011	Liu et al.
2010/0201314	A1	8/2010	Toncich et al.	2011/0182245	A1	7/2011	Malkamaki et al.
2010/0207572	A1	8/2010	Kirby et al.	2011/0184842	A1	7/2011	Melen
2010/0210233	A1	8/2010	Cook et al.	2011/0188207	A1	8/2011	Won et al.
2010/0213895	A1	8/2010	Keating et al.	2011/0193688	A1	8/2011	Forsell
2010/0214177	A1	8/2010	Parsche	2011/0194543	A1	8/2011	Zhao et al.
2010/0222010	A1	9/2010	Ozaki et al.	2011/0195722	A1	8/2011	Walter et al.
2010/0225270	A1	9/2010	Jacobs et al.	2011/0199046	A1	8/2011	Tsai et al.
2010/0227570	A1	9/2010	Hendin	2011/0215086	A1	9/2011	Yeh
2010/0231470	A1	9/2010	Lee et al.	2011/0217923	A1	9/2011	Ma
2010/0237709	A1	9/2010	Hall et al.	2011/0220634	A1	9/2011	Yeh
2010/0244576	A1	9/2010	Hillan et al.	2011/0221389	A1	9/2011	Won et al.
2010/0253281	A1	10/2010	Li	2011/0222272	A1	9/2011	Yeh
2010/0256831	A1	10/2010	Abramo et al.	2011/0227725	A1	9/2011	Muirhead
2010/0259110	A1	10/2010	Kurs et al.	2011/0243040	A1	10/2011	Khan et al.
2010/0259447	A1	10/2010	Crouch	2011/0243050	A1	10/2011	Yanover
2010/0264747	A1	10/2010	Hall et al.	2011/0244913	A1	10/2011	Kim et al.
2010/0277003	A1	11/2010	Von Novak et al.	2011/0248573	A1	10/2011	Kanno et al.
2010/0277121	A1	11/2010	Hall et al.	2011/0248575	A1	10/2011	Kim et al.
2010/0279606	A1	11/2010	Hillan et al.	2011/0249678	A1	10/2011	Bonicatto
2010/0289341	A1	11/2010	Ozaki et al.	2011/0254377	A1	10/2011	Wildmer et al.
2010/0295372	A1	11/2010	Hyde et al.	2011/0254503	A1	10/2011	Widmer et al.
2010/0308767	A1	12/2010	Rofougaran et al.	2011/0259953	A1	10/2011	Baarman et al.
2010/0309079	A1	12/2010	Rofougaran et al.	2011/0273977	A1	11/2011	Shapira et al.
2010/0309088	A1	12/2010	Hyvonen et al.	2011/0278941	A1	11/2011	Krishna et al.
2010/0315045	A1	12/2010	Zeine	2011/0279226	A1	11/2011	Chen et al.
2010/0316163	A1	12/2010	Forenza et al.	2011/0281535	A1	11/2011	Low et al.
2010/0327766	A1	12/2010	Recker et al.	2011/0282415	A1	11/2011	Eckhoff et al.
2010/0328044	A1	12/2010	Waffenschmidt et al.	2011/0285213	A1	11/2011	Kowalewski
2010/0332401	A1	12/2010	Prahlad et al.	2011/0286374	A1	11/2011	Shin et al.
2011/0009057	A1	1/2011	Saunamäki	2011/0291489	A1	12/2011	Tsai et al.
2011/0013198	A1	1/2011	Shirley	2011/0302078	A1	12/2011	Failing
2011/0018360	A1	1/2011	Baarman et al.	2011/0304216	A1	12/2011	Baarman
2011/0028114	A1	2/2011	Kerselaers	2011/0304437	A1	12/2011	Beeler
2011/0031928	A1	2/2011	Soar	2011/0304521	A1	12/2011	Ando et al.
2011/0032149	A1	2/2011	Leabman	2012/0007441	A1	1/2012	John
2011/0032866	A1	2/2011	Leabman	2012/0013196	A1	1/2012	Kim et al.
2011/0034190	A1	2/2011	Leabman	2012/0013198	A1	1/2012	Uramoto et al.
2011/0034191	A1	2/2011	Leabman	2012/0013296	A1	1/2012	Heydari et al.
2011/0043047	A1	2/2011	Karalis et al.	2012/0019419	A1	1/2012	Prat et al.
2011/0043163	A1	2/2011	Baarman et al.	2012/0025622	A1	2/2012	Kim et al.
2011/0043327	A1	2/2011	Baarman et al.	2012/0043887	A1	2/2012	Mesibov
2011/0050166	A1	3/2011	Cook et al.	2012/0051109	A1	3/2012	Kim et al.
2011/0055037	A1	3/2011	Hayashigawa et al.	2012/0051294	A1	3/2012	Guillouard
2011/0056215	A1	3/2011	Ham	2012/0056486	A1	3/2012	Endo et al.
2011/0057607	A1	3/2011	Carobolante	2012/0056741	A1	3/2012	Zhu et al.
2011/0057853	A1	3/2011	Kim et al.	2012/0068906	A1	3/2012	Asher et al.
2011/0062788	A1	3/2011	Chen et al.	2012/0074891	A1	3/2012	Anderson et al.
2011/0074342	A1	3/2011	MacLaughlin	2012/0075072	A1	3/2012	Pappu
				2012/0080944	A1	4/2012	Recker et al.
				2012/0080957	A1	4/2012	Cooper et al.
				2012/0086284	A1	4/2012	Capanella et al.
				2012/0086615	A1	4/2012	Norair

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0095617	A1	4/2012	Martin et al.	2012/0309295	A1	12/2012	Maguire
2012/0098350	A1	4/2012	Campanella et al.	2012/0309308	A1	12/2012	Kim et al.
2012/0098485	A1	4/2012	Kang et al.	2012/0309332	A1	12/2012	Liao
2012/0099675	A1	4/2012	Kitamura et al.	2012/0313446	A1	12/2012	Park et al.
2012/0103562	A1	5/2012	Alexander	2012/0313449	A1	12/2012	Kurs
2012/0104849	A1	5/2012	Jackson	2012/0313835	A1	12/2012	Gebretnsae
2012/0105252	A1	5/2012	Wang	2012/0326660	A1	12/2012	Lu et al.
2012/0112532	A1	5/2012	Kesler et al.	2013/0002550	A1	1/2013	Zalewski
2012/0119914	A1	5/2012	Uchida	2013/0005252	A1	1/2013	Lee et al.
2012/0126743	A1	5/2012	Rivers, Jr.	2013/0018439	A1	1/2013	Chow et al.
2012/0132647	A1	5/2012	Beverly et al.	2013/0024059	A1	1/2013	Miller et al.
2012/0133214	A1	5/2012	Yun et al.	2013/0026981	A1	1/2013	Van Der Lee
2012/0142291	A1	6/2012	Rath et al.	2013/0026982	A1	1/2013	Rothenbaum
2012/0146426	A1	6/2012	Sabo	2013/0032589	A1	2/2013	Chung
2012/0146576	A1	6/2012	Partovi	2013/0033571	A1	2/2013	Steen
2012/0146577	A1	6/2012	Tanabe	2013/0038124	A1	2/2013	Newdoll et al.
2012/0147802	A1	6/2012	Ukita et al.	2013/0038402	A1	2/2013	Karalis et al.
2012/0149307	A1	6/2012	Terada et al.	2013/0043738	A1	2/2013	Park et al.
2012/0150670	A1	6/2012	Taylor et al.	2013/0044035	A1	2/2013	Zhuang
2012/0153894	A1	6/2012	Widmer et al.	2013/0049471	A1	2/2013	Oleynik
2012/0157019	A1	6/2012	Li	2013/0049475	A1	2/2013	Kim et al.
2012/0161531	A1	6/2012	Kim et al.	2013/0049484	A1	2/2013	Weissentern et al.
2012/0161544	A1	6/2012	Kashiwagi et al.	2013/0057078	A1	3/2013	Lee
2012/0169276	A1	7/2012	Wang	2013/0057205	A1	3/2013	Lee et al.
2012/0169278	A1	7/2012	Choi	2013/0057210	A1	3/2013	Nergaard et al.
2012/0173418	A1	7/2012	Beardsmore et al.	2013/0057364	A1	3/2013	Kesler et al.
2012/0179004	A1	7/2012	Roesicke et al.	2013/0058379	A1	3/2013	Kim et al.
2012/0181973	A1	7/2012	Lyden	2013/0062959	A1	3/2013	Lee et al.
2012/0182427	A1	7/2012	Marshall	2013/0063082	A1	3/2013	Lee et al.
2012/0187851	A1	7/2012	Huggins et al.	2013/0063143	A1	3/2013	Adalsteinsson et al.
2012/0188142	A1	7/2012	Shashi et al.	2013/0063266	A1	3/2013	Yunker et al.
2012/0193999	A1	8/2012	Zeine	2013/0069444	A1	3/2013	Waffenschmidt et al.
2012/0200399	A1	8/2012	Chae	2013/0076308	A1	3/2013	Niskala et al.
2012/0201153	A1	8/2012	Bharadia et al.	2013/0077650	A1	3/2013	Traxler et al.
2012/0201173	A1	8/2012	Jain et al.	2013/0078918	A1	3/2013	Crowley et al.
2012/0206299	A1	8/2012	Valdes-Garcia	2013/0082651	A1	4/2013	Park et al.
2012/0211214	A1	8/2012	Phan	2013/0082653	A1	4/2013	Lee et al.
2012/0212071	A1	8/2012	Miyabayashi et al.	2013/0083774	A1	4/2013	Son et al.
2012/0212072	A1	8/2012	Miyabayashi et al.	2013/0088082	A1	4/2013	Kang et al.
2012/0214462	A1	8/2012	Chu et al.	2013/0088090	A1	4/2013	Wu
2012/0214536	A1	8/2012	Kim et al.	2013/0088192	A1	4/2013	Eaton
2012/0228392	A1	9/2012	Cameron et al.	2013/0088331	A1	4/2013	Cho
2012/0228956	A1	9/2012	Kamata	2013/0093388	A1	4/2013	Partovi
2012/0231856	A1	9/2012	Lee et al.	2013/0099389	A1	4/2013	Hong et al.
2012/0235636	A1	9/2012	Partovi	2013/0099586	A1	4/2013	Kato
2012/0242283	A1	9/2012	Kim et al.	2013/0106197	A1	5/2013	Bae et al.
2012/0248886	A1	10/2012	Kesler et al.	2013/0107023	A1	5/2013	Tanaka et al.
2012/0248888	A1	10/2012	Kesler et al.	2013/0119777	A1	5/2013	Rees
2012/0248891	A1	10/2012	Drennen	2013/0119778	A1	5/2013	Jung
2012/0249051	A1	10/2012	Son et al.	2013/0119929	A1	5/2013	Partovi
2012/0262002	A1	10/2012	Widmer et al.	2013/0120052	A1	5/2013	Siska
2012/0265272	A1	10/2012	Judkins	2013/0120205	A1	5/2013	Thomson et al.
2012/0267900	A1	10/2012	Huffman et al.	2013/0120206	A1	5/2013	Biancotto et al.
2012/0268238	A1	10/2012	Park et al.	2013/0120217	A1	5/2013	Ueda et al.
2012/0270592	A1	10/2012	Ngai	2013/0130621	A1	5/2013	Kim et al.
2012/0274154	A1	11/2012	DeLuca	2013/0132010	A1	5/2013	Winger et al.
2012/0280650	A1	11/2012	Kim et al.	2013/0134923	A1	5/2013	Smith
2012/0286582	A1	11/2012	Kim et al.	2013/0137455	A1	5/2013	Xia
2012/0292993	A1	11/2012	Mettler et al.	2013/0141037	A1	6/2013	Jenwatanavet et al.
2012/0293021	A1	11/2012	Teggatz et al.	2013/0148341	A1	6/2013	Williams
2012/0293119	A1	11/2012	Park et al.	2013/0149975	A1	6/2013	Yu et al.
2012/0299389	A1	11/2012	Lee et al.	2013/0154387	A1	6/2013	Lee et al.
2012/0299540	A1	11/2012	Perry	2013/0155748	A1	6/2013	Sundstrom
2012/0299541	A1	11/2012	Perry	2013/0157729	A1	6/2013	Tabe
2012/0299542	A1	11/2012	Perry	2013/0162335	A1	6/2013	Kim et al.
2012/0300588	A1	11/2012	Perry	2013/0169061	A1	7/2013	Miroshnichenko et al.
2012/0300592	A1	11/2012	Perry	2013/0169219	A1	7/2013	Gray
2012/0300593	A1	11/2012	Perry	2013/0169348	A1	7/2013	Shi
2012/0306284	A1	12/2012	Lee et al.	2013/0171939	A1	7/2013	Tian et al.
2012/0306433	A1	12/2012	Kim et al.	2013/0175877	A1	7/2013	Abe et al.
2012/0306572	A1	12/2012	Hietala et al.	2013/0178253	A1	7/2013	Karaoguz
2012/0306705	A1	12/2012	Sakurai et al.	2013/0181881	A1	7/2013	Christie et al.
2012/0306707	A1	12/2012	Yang et al.	2013/0187475	A1	7/2013	Vendik
2012/0306720	A1	12/2012	Tamai et al.	2013/0190031	A1	7/2013	Persson et al.
2012/0307873	A1	12/2012	Kim et al.	2013/0193769	A1	8/2013	Mehta et al.
				2013/0197320	A1	8/2013	Albert et al.
				2013/0200064	A1	8/2013	Alexander
				2013/0207477	A1	8/2013	Nam et al.
				2013/0207604	A1	8/2013	Zeine

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0207879	A1	8/2013	Rada et al.	2014/0139034	A1	5/2014	Sankar et al.
2013/0210357	A1	8/2013	Qin et al.	2014/0139039	A1	5/2014	Cook et al.
2013/0221757	A1	8/2013	Cho et al.	2014/0139180	A1	5/2014	Kim et al.
2013/0222201	A1	8/2013	Ma et al.	2014/0141838	A1	5/2014	Cai et al.
2013/0234530	A1	9/2013	Miyauchi	2014/0142876	A1	5/2014	John et al.
2013/0234536	A1	9/2013	Chemishkian et al.	2014/0143933	A1	5/2014	Low et al.
2013/0234658	A1	9/2013	Endo et al.	2014/0145879	A1	5/2014	Pan
2013/0241306	A1	9/2013	Aber et al.	2014/0145884	A1	5/2014	Dang et al.
2013/0241468	A1	9/2013	Moshfeghi	2014/0152117	A1	6/2014	Sanker
2013/0241474	A1	9/2013	Moshfeghi	2014/0159651	A1	6/2014	Von Novak et al.
2013/0249478	A1	9/2013	Hirano	2014/0159652	A1	6/2014	Hall et al.
2013/0249479	A1	9/2013	Partovi	2014/0159662	A1	6/2014	Furui
2013/0249682	A1	9/2013	Van Wiemeersch et al.	2014/0159667	A1	6/2014	Kim et al.
2013/0250102	A1	9/2013	Scanlon et al.	2014/0169385	A1	6/2014	Hadani et al.
2013/0254578	A1	9/2013	Huang et al.	2014/0175876	A1	6/2014	Cheatham, III et al.
2013/0264997	A1	10/2013	Lee et al.	2014/0175893	A1	6/2014	Sengupta et al.
2013/0268782	A1	10/2013	Tam et al.	2014/0176054	A1	6/2014	Porat et al.
2013/0270923	A1	10/2013	Cook et al.	2014/0176061	A1	6/2014	Cheatham, III et al.
2013/0278076	A1	10/2013	Proud	2014/0176082	A1	6/2014	Visser
2013/0278209	A1	10/2013	Von Novak, III et al.	2014/0177399	A1	6/2014	Teng et al.
2013/0285464	A1	10/2013	Miwa	2014/0183964	A1	7/2014	Walley
2013/0285477	A1	10/2013	Lo et al.	2014/0184148	A1	7/2014	Van Der Lee et al.
2013/0285606	A1	10/2013	Ben-Shalom et al.	2014/0184155	A1	7/2014	Cha
2013/0288600	A1	10/2013	Kuusilinna et al.	2014/0184163	A1	7/2014	Das et al.
2013/0288617	A1	10/2013	Kim et al.	2014/0184170	A1	7/2014	Jeong
2013/0293423	A1	11/2013	Moshfeghi	2014/0191568	A1	7/2014	Partovi
2013/0300356	A1	11/2013	Yang	2014/0191818	A1	7/2014	Waffenschmidt et al.
2013/0307751	A1	11/2013	Yu-Juin et al.	2014/0194092	A1	7/2014	Wanstedt et al.
2013/0310020	A1	11/2013	Kazuhiro	2014/0194095	A1	7/2014	Wynne et al.
2013/0311798	A1	11/2013	Sultenfuss	2014/0197691	A1	7/2014	Wang
2013/0328417	A1	12/2013	Takeuchi	2014/0203629	A1	7/2014	Hoffman et al.
2013/0334883	A1	12/2013	Kim et al.	2014/0206384	A1	7/2014	Kim et al.
2013/0339108	A1	12/2013	Ryder et al.	2014/0210281	A1	7/2014	Ito et al.
2013/0343208	A1	12/2013	Sexton et al.	2014/0217955	A1	8/2014	Lin
2013/0343251	A1	12/2013	Zhang	2014/0217967	A1	8/2014	Zeine et al.
2013/0343585	A1	12/2013	Bennett et al.	2014/0225805	A1	8/2014	Pan et al.
2014/0001846	A1	1/2014	Mosebrook	2014/0232320	A1	8/2014	Ento July et al.
2014/0001875	A1	1/2014	Nahidipour	2014/0232610	A1	8/2014	Shigemoto et al.
2014/0001876	A1	1/2014	Fujiwara et al.	2014/0239733	A1	8/2014	Mach et al.
2014/0006017	A1	1/2014	Sen	2014/0241231	A1	8/2014	Zeine
2014/0008992	A1	1/2014	Leabman	2014/0245036	A1	8/2014	Oishi
2014/0008993	A1	1/2014	Leabman	2014/0246416	A1	9/2014	White
2014/0009108	A1	1/2014	Leabman	2014/0247152	A1	9/2014	Proud
2014/0009110	A1	1/2014	Lee	2014/0252813	A1	9/2014	Lee et al.
2014/0011531	A1	1/2014	Burstrom et al.	2014/0252866	A1	9/2014	Walsh et al.
2014/0015336	A1	1/2014	Weber et al.	2014/0265725	A1	9/2014	Angle et al.
2014/0015344	A1	1/2014	Mohamadi	2014/0265727	A1	9/2014	Berte
2014/0021907	A1	1/2014	Yu et al.	2014/0265943	A1	9/2014	Angle et al.
2014/0021908	A1	1/2014	McCool	2014/0266025	A1	9/2014	Jakubowski
2014/0024325	A1	1/2014	Iun et al.	2014/0266946	A1	9/2014	Bily et al.
2014/0035524	A1	2/2014	Zeine	2014/0273819	A1	9/2014	Nadakuduti et al.
2014/0035526	A1	2/2014	Tripathi et al.	2014/0273892	A1	9/2014	Nourbakhsh
2014/0035786	A1	2/2014	Ley	2014/0281655	A1	9/2014	Angle et al.
2014/0043248	A1	2/2014	Yeh	2014/0292090	A1	10/2014	Cordeiro et al.
2014/0049422	A1	2/2014	Von Novak et al.	2014/0292451	A1	10/2014	Zimmerman
2014/0054971	A1	2/2014	Kissin	2014/0300452	A1	10/2014	Rofe et al.
2014/0055098	A1	2/2014	Lee et al.	2014/0312706	A1	10/2014	Fiorello et al.
2014/0057618	A1	2/2014	Zirwas et al.	2014/0325218	A1	10/2014	Shimizu et al.
2014/0062395	A1	3/2014	Kwon et al.	2014/0327320	A1	11/2014	Muhs et al.
2014/0082435	A1	3/2014	Kitgawa	2014/0327390	A1	11/2014	Park et al.
2014/0086125	A1	3/2014	Polo et al.	2014/0333142	A1	11/2014	Desrosiers
2014/0086592	A1	3/2014	Nakahara et al.	2014/0346860	A1	11/2014	Aubry et al.
2014/0091756	A1	4/2014	Ofstein et al.	2014/0354063	A1	12/2014	Leabman et al.
2014/0091968	A1	4/2014	Harel et al.	2014/0354221	A1	12/2014	Leabman et al.
2014/0091974	A1	4/2014	Desclos et al.	2014/0355718	A1	12/2014	Guan et al.
2014/0103869	A1	4/2014	Radovic	2014/0357309	A1	12/2014	Leabman et al.
2014/0104157	A1	4/2014	Burns	2014/0368048	A1	12/2014	Leabman et al.
2014/0111147	A1	4/2014	Soar	2014/0368161	A1	12/2014	Leabman et al.
2014/0111153	A1	4/2014	Kwon et al.	2014/0368405	A1	12/2014	Ek et al.
2014/0113689	A1	4/2014	Lee	2014/0370929	A1	12/2014	Khawand et al.
2014/0117946	A1	5/2014	Muller et al.	2014/0375139	A1	12/2014	Tsukamoto
2014/0118140	A1	5/2014	Amis	2014/0375253	A1	12/2014	Leabman et al.
2014/0128107	A1	5/2014	An	2014/0375255	A1	12/2014	Leabman et al.
2014/0132210	A1	5/2014	Partovi	2014/0375258	A1	12/2014	Arkhipenkov
2014/0133279	A1	5/2014	Khuri-Yakub	2014/0375261	A1	12/2014	Manova-Elssibony et al.
				2014/0376646	A1	12/2014	Leabman et al.
				2015/0001949	A1	1/2015	Leabman et al.
				2015/0002086	A1	1/2015	Matos et al.
				2015/0003207	A1	1/2015	Lee et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0008980	A1	1/2015	Kim et al.	2015/0233987	A1	8/2015	Von Novak, III et al.
2015/0011160	A1	1/2015	Jurgovan et al.	2015/0234144	A1	8/2015	Cameron et al.
2015/0015180	A1	1/2015	Miller et al.	2015/0236520	A1	8/2015	Baarman
2015/0015182	A1	1/2015	Brandtman et al.	2015/0236877	A1	8/2015	Peng et al.
2015/0015192	A1	1/2015	Leabman et al.	2015/0244070	A1	8/2015	Cheng et al.
2015/0015194	A1	1/2015	Leabman et al.	2015/0244080	A1	8/2015	Gregoire
2015/0015195	A1	1/2015	Leabman et al.	2015/0244187	A1	8/2015	Horie
2015/0021990	A1	1/2015	Myer et al.	2015/0244201	A1	8/2015	Chu
2015/0022008	A1	1/2015	Leabman et al.	2015/0244341	A1	8/2015	Ritter et al.
2015/0022009	A1	1/2015	Leabman et al.	2015/0249484	A1	9/2015	Mach et al.
2015/0022010	A1	1/2015	Leabman et al.	2015/0255989	A1	9/2015	Walley et al.
2015/0022194	A1	1/2015	Almalki et al.	2015/0256097	A1	9/2015	Gudan et al.
2015/0023204	A1	1/2015	Wik et al.	2015/0260835	A1	9/2015	Widmer et al.
2015/0028688	A1	1/2015	Masaoka	2015/0262465	A1	9/2015	Pritchett
2015/0028694	A1	1/2015	Leabman et al.	2015/0263534	A1	9/2015	Lee et al.
2015/0028697	A1	1/2015	Makino et al.	2015/0263548	A1	9/2015	Cooper
2015/0028875	A1	1/2015	Irie et al.	2015/0270618	A1	9/2015	Zhu et al.
2015/0029397	A1	1/2015	Leabman et al.	2015/0270622	A1	9/2015	Takasaki et al.
2015/0035378	A1	2/2015	Calhoun et al.	2015/0270741	A1	9/2015	Leabman et al.
2015/0035709	A1	2/2015	Lim	2015/0278558	A1	10/2015	Priev et al.
2015/0035715	A1	2/2015	Kim et al.	2015/0280429	A1	10/2015	Makita et al.
2015/0039482	A1	2/2015	Fujinaga	2015/0280484	A1	10/2015	Radziemski et al.
2015/0041459	A1	2/2015	Leabman et al.	2015/0288074	A1	10/2015	Harper et al.
2015/0042264	A1	2/2015	Leabman et al.	2015/0288438	A1	10/2015	Maltsev et al.
2015/0042265	A1	2/2015	Leabman et al.	2015/0311585	A1	10/2015	Church et al.
2015/0044977	A1	2/2015	Ramasamy et al.	2015/0312721	A1	10/2015	Singh
2015/0046526	A1	2/2015	Bush et al.	2015/0318729	A1	11/2015	Leabman
2015/0061404	A1	3/2015	Lamenza et al.	2015/0326024	A1	11/2015	Bell et al.
2015/0076917	A1	3/2015	Leabman et al.	2015/0326025	A1	11/2015	Bell et al.
2015/0076927	A1	3/2015	Leabman et al.	2015/0326051	A1	11/2015	Bell et al.
2015/0077036	A1	3/2015	Leabman et al.	2015/0326063	A1	11/2015	Leabman et al.
2015/0077037	A1	3/2015	Leabman et al.	2015/0326068	A1	11/2015	Bell et al.
2015/0091520	A1	4/2015	Blum et al.	2015/0326069	A1	11/2015	Petras et al.
2015/0091706	A1	4/2015	Chemishkian et al.	2015/0326070	A1	11/2015	Petras et al.
2015/0097442	A1	4/2015	Muurinen	2015/0326071	A1	11/2015	Contopanagos
2015/0097663	A1	4/2015	Sloo et al.	2015/0326072	A1	11/2015	Petras et al.
2015/0102681	A1	4/2015	Leabman et al.	2015/0326142	A1	11/2015	Petras et al.
2015/0102764	A1	4/2015	Leabman et al.	2015/0326143	A1	11/2015	Petras et al.
2015/0102769	A1	4/2015	Leabman et al.	2015/0327085	A1	11/2015	Hadani
2015/0102942	A1	4/2015	Houser et al.	2015/0333528	A1	11/2015	Leabman
2015/0102973	A1	4/2015	Hand et al.	2015/0333529	A1	11/2015	Leabman
2015/0108848	A1	4/2015	Joehren	2015/0333573	A1	11/2015	Leabman
2015/0109181	A1	4/2015	Hyde et al.	2015/0333800	A1	11/2015	Perry et al.
2015/0115877	A1	4/2015	Arai et al.	2015/0339497	A1	11/2015	Kurian
2015/0115878	A1	4/2015	Park	2015/0340759	A1	11/2015	Bridgelall et al.
2015/0116153	A1	4/2015	Chen et al.	2015/0340903	A1	11/2015	Bell et al.
2015/0123483	A1	5/2015	Leabman et al.	2015/0340909	A1	11/2015	Bell et al.
2015/0123496	A1	5/2015	Leabman et al.	2015/0340910	A1	11/2015	Petras et al.
2015/0128733	A1	5/2015	Taylor et al.	2015/0340911	A1	11/2015	Bell et al.
2015/0130285	A1	5/2015	Leabman et al.	2015/0341087	A1	11/2015	Moore et al.
2015/0130293	A1	5/2015	Hajimiri et al.	2015/0349574	A1	12/2015	Leabman
2015/0137612	A1	5/2015	Yamakawa et al.	2015/0358222	A1	12/2015	Berger et al.
2015/0148664	A1	5/2015	Stolka et al.	2015/0365137	A1	12/2015	Miller et al.
2015/0155737	A1	6/2015	Mayo	2015/0365138	A1	12/2015	Miller et al.
2015/0155738	A1	6/2015	Leabman et al.	2016/0005068	A1	1/2016	Im et al.
2015/0162662	A1	6/2015	Chen et al.	2016/0012695	A1	1/2016	Bell et al.
2015/0162751	A1	6/2015	Leabman et al.	2016/0013560	A1	1/2016	Daniels
2015/0162779	A1	6/2015	Lee et al.	2016/0013656	A1	1/2016	Bell et al.
2015/0171512	A1	6/2015	Chen et al.	2016/0013661	A1	1/2016	Kurs et al.
2015/0171513	A1	6/2015	Chen et al.	2016/0013677	A1	1/2016	Bell et al.
2015/0171656	A1	6/2015	Leabman et al.	2016/0013678	A1	1/2016	Bell et al.
2015/0171658	A1	6/2015	Manova-Elssibony et al.	2016/0013855	A1	1/2016	Campos
2015/0171931	A1	6/2015	Won et al.	2016/0020636	A1	1/2016	Khlat
2015/0177326	A1	6/2015	Chakraborty et al.	2016/0020647	A1	1/2016	Leabman et al.
2015/0180133	A1	6/2015	Hunt	2016/0020649	A1	1/2016	Bell et al.
2015/0180249	A1	6/2015	Jeon et al.	2016/0020830	A1	1/2016	Bell et al.
2015/0180284	A1	6/2015	Kang et al.	2016/0028403	A1	1/2016	McCaughan et al.
2015/0181117	A1	6/2015	Park et al.	2016/0033254	A1	2/2016	Zeine et al.
2015/0187491	A1	7/2015	Yanagawa	2016/0042206	A1	2/2016	Pesavento et al.
2015/0188352	A1	7/2015	Peek et al.	2016/0043571	A1	2/2016	Kesler et al.
2015/0199665	A1	7/2015	Chu	2016/0043572	A1	2/2016	Cooper et al.
2015/0201385	A1	7/2015	Mercer et al.	2016/0054395	A1	2/2016	Bell et al.
2015/0207333	A1	7/2015	Baarman et al.	2016/0054396	A1	2/2016	Bell et al.
2015/0207542	A1	7/2015	Zeine	2016/0054440	A1	2/2016	Younis
2015/0222126	A1	8/2015	Leabman et al.	2016/0056635	A1	2/2016	Bell
				2016/0056640	A1	2/2016	Mao
				2016/0056669	A1	2/2016	Bell
				2016/0056966	A1	2/2016	Bell
				2016/0065005	A1	3/2016	Won et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0079799	A1	3/2016	Khlat		2017/0085437	A1	3/2017	Condeixa et al.
2016/0087483	A1	3/2016	Hietala et al.		2017/0092115	A1	3/2017	Sloo et al.
2016/0087486	A1	3/2016	Pogorelik et al.		2017/0104263	A1	4/2017	Hosseini
2016/0094091	A1	3/2016	Shin et al.		2017/0110886	A1	4/2017	Reynolds et al.
2016/0094092	A1	3/2016	Davlantes et al.		2017/0110887	A1	4/2017	Bell et al.
2016/0099601	A1	4/2016	Leabman et al.		2017/0110888	A1	4/2017	Leabman
2016/0099602	A1	4/2016	Leabman et al.		2017/0110889	A1	4/2017	Bell
2016/0099609	A1	4/2016	Leabman et al.		2017/0110910	A1	4/2017	Zeine et al.
2016/0099610	A1	4/2016	Leabman et al.		2017/0110914	A1	4/2017	Bell
2016/0099611	A1	4/2016	Leabman et al.		2017/0127196	A1	5/2017	Blum et al.
2016/0099612	A1	4/2016	Leabman et al.		2017/0134686	A9	5/2017	Leabman
2016/0099613	A1	4/2016	Leabman et al.		2017/0141582	A1	5/2017	Adolf et al.
2016/0099614	A1	4/2016	Leabman et al.		2017/0141583	A1	5/2017	Adolf et al.
2016/0099755	A1	4/2016	Leabman et al.		2017/0163076	A1	6/2017	Park et al.
2016/0099756	A1	4/2016	Leabman et al.		2017/0168595	A1	6/2017	Sakaguchi et al.
2016/0099757	A1	4/2016	Leabman et al.		2017/0179763	A9	6/2017	Leabman
2016/0099758	A1	4/2016	Bell et al.		2017/0179771	A1	6/2017	Leabman
2016/0100124	A1	4/2016	Leabman et al.		2017/0187198	A1	6/2017	Leabman
2016/0100312	A1	4/2016	Bell et al.		2017/0187222	A1	6/2017	Hosseini
2016/0112787	A1	4/2016	Rich		2017/0187223	A1	6/2017	Hosseini
2016/0126749	A1	5/2016	Shichino et al.		2017/0187228	A1	6/2017	Hosseini
2016/0126752	A1	5/2016	Vuori et al.		2017/0187248	A1	6/2017	Leabman
2016/0126776	A1	5/2016	Kim et al.		2017/0214422	A1	7/2017	Na et al.
2016/0141908	A1	5/2016	Jakl et al.		2017/0274787	A1	9/2017	Salter et al.
2016/0164563	A1	6/2016	Khawand et al.		2017/0338695	A1	11/2017	Port
2016/0174162	A1	6/2016	Nadakuduti et al.		2018/0006611	A1	1/2018	de Jong et al.
2016/0181849	A1	6/2016	Govindaraj		2018/0040929	A1	2/2018	Chappelle
2016/0181854	A1	6/2016	Leabman		2018/0048178	A1	2/2018	Leabman
2016/0181867	A1	6/2016	Daniel et al.		2018/0090992	A1	3/2018	Shrivastava et al.
2016/0181873	A1	6/2016	Mitcheson et al.		2018/0123400	A1	5/2018	Leabman
2016/0191121	A1	6/2016	Bell		2018/0131238	A1	5/2018	Leabman
2016/0197511	A1*	7/2016	Atasoy	H02J 50/10 307/104	2018/0159355	A1	6/2018	Leabman
					2018/0166924	A1	6/2018	Hosseini
					2018/0166925	A1	6/2018	Hosseini
					2018/0226840	A1*	8/2018	Leabman
								H02J 50/20
2016/0197522	A1	7/2016	Zeine et al.		2018/0227018	A1	8/2018	Moshfeghi
2016/0202343	A1	7/2016	Okutsu		2018/0241255	A1	8/2018	Leabman
2016/0204622	A1	7/2016	Leabman		2018/0262040	A1	9/2018	Contopanagos
2016/0204642	A1	7/2016	Oh		2018/0262050	A1	9/2018	Yankowitz
2016/0218545	A1	7/2016	Schroeder et al.		2018/0262060	A1	9/2018	Johnston
2016/0233582	A1	8/2016	Piskun		2018/0287431	A1	10/2018	Liu et al.
2016/0238365	A1	8/2016	Wixey et al.		2018/0301934	A1	10/2018	Prabhala et al.
2016/0240908	A1	8/2016	Strong		2018/0309314	A1	10/2018	White, II et al.
2016/0248276	A1	8/2016	Hong et al.		2018/0343040	A1	11/2018	Luzinski et al.
2016/0294225	A1	10/2016	Blum et al.		2018/0375340	A1	12/2018	Bell et al.
2016/0299210	A1	10/2016	Zeine		2018/0375368	A1	12/2018	Leabman et al.
2016/0301240	A1	10/2016	Zeine		2018/0376235	A1	12/2018	Leabman
2016/0322868	A1	11/2016	Akuzawa et al.		2019/0052979	A1	2/2019	Chen et al.
2016/0323000	A1	11/2016	Liu et al.		2019/0074728	A1	3/2019	Leabman
2016/0336804	A1	11/2016	Son et al.		2019/0074862	A1	3/2019	Wang et al.
2016/0339258	A1	11/2016	Perryman et al.		2019/0131827	A1	5/2019	Johnston
2016/0344098	A1	11/2016	Ming		2019/0148967	A1*	5/2019	Bae
2016/0359367	A1	12/2016	Rothschild					H02J 50/80 320/108
2016/0380464	A1	12/2016	Chin et al.					
2016/0380466	A1	12/2016	Yang et al.		2019/0173323	A1	6/2019	Hosseini
2017/0005481	A1	1/2017	Von Novak, III		2019/0245389	A1	8/2019	Johnston et al.
2017/0005516	A9	1/2017	Leabman et al.		2019/0288567	A1	9/2019	Kabiri et al.
2017/0005524	A1	1/2017	Akuzawa et al.		2019/0296586	A1	9/2019	Moshfeghi
2017/0005530	A1	1/2017	Zeine et al.		2019/0326782	A1	10/2019	Graham et al.
2017/0012448	A1	1/2017	Miller et al.		2019/0372384	A1	12/2019	Hosseini et al.
2017/0025887	A1	1/2017	Hyun et al.		2019/0386522	A1	12/2019	Park et al.
2017/0025903	A1	1/2017	Song et al.		2019/0393729	A1	12/2019	Contopanagos et al.
2017/0026087	A1	1/2017	Tanabe		2019/0393928	A1	12/2019	Leabman
2017/0040700	A1	2/2017	Leung		2020/0006988	A1	1/2020	Leabman
2017/0043675	A1	2/2017	Jones et al.		2020/0021128	A1	1/2020	Bell et al.
2017/0047784	A1	2/2017	Jung et al.		2020/0044488	A1	2/2020	Johnston et al.
2017/0187225	A1	2/2017	Hosseini		2020/0091608	A1	3/2020	Alpman et al.
2017/0063168	A1	3/2017	Uchida		2020/0112204	A1	4/2020	Hosseini et al.
2017/0077733	A1	3/2017	Jeong et al.		2020/0119592	A1	4/2020	Hosseini
2017/0077735	A1	3/2017	Leabman		2020/0153117	A1	5/2020	Papio-Toda et al.
2017/0077736	A1	3/2017	Leabman		2020/0203837	A1	6/2020	Kornaros et al.
2017/0077764	A1	3/2017	Bell et al.		2020/0235614	A1	7/2020	Swan et al.
2017/0077765	A1	3/2017	Bell et al.		2020/0244102	A1	7/2020	Leabman et al.
2017/0077979	A1	3/2017	Papa et al.		2020/0244104	A1	7/2020	Katajamaki et al.
2017/0077995	A1	3/2017	Leabman		2020/0244111	A1	7/2020	Johnston et al.
2017/0085120	A1	3/2017	Leabman et al.					
2017/0085127	A1	3/2017	Leabman					

(56)

References Cited

U.S. PATENT DOCUMENTS

2020/0252141 A1 8/2020 Sarajedini
2020/0274397 A1 8/2020 Hwang et al.

FOREIGN PATENT DOCUMENTS

CN 201278367 Y 7/2009
CN 101507044 A 8/2009
CN 102027690 A 4/2011
CN 102089952 A 6/2011
CN 102292896 A 12/2011
CN 102860037 A 1/2013
CN 103151848 A 6/2013
CN 103348563 A 10/2013
CN 103594776 A 2/2014
CN 104040789 A 9/2014
CN 203826555 U 9/2014
CN 104090265 A 10/2014
CN 104167773 A 11/2014
CN 104347915 A 2/2015
CN 105762946 A 7/2016
CN 105765821 A 7/2016
CN 105932407 A 9/2016
CN 106329116 A 1/2017
CN 103380561 B 9/2017
DE 20016655 U1 2/2002
DE 102013216953 A1 2/2015
DE 102014219679 A1 3/2016
EP 1028482 A2 8/2000
EP 1081506 A1 3/2001
EP 2346136 A1 7/2011
EP 2397973 A1 2/2012
EP 2545635 A2 1/2013
EP 2747195 A1 6/2014
EP 3067983 A1 9/2016
EP 3118970 A1 1/2017
EP 3145052 A1 3/2017
GB 2404497 A 2/2005
GB 2556620 A 6/2018
JP 2000323916 A 11/2000
JP 2002209343 A 7/2002
JP 2002319816 A 10/2002
JP 2006157586 A 6/2006
JP 2007043432 A 2/2007
JP 2007135335 A 5/2007
JP 2008092704 A 4/2008
JP 2008167017 A 7/2008
JP 2009525715 A 7/2009
JP 2009201328 A 9/2009
JP 2011514781 A 5/2011
JP 2012016171 A 1/2012
JP 2012023950 A 2/2012
JP 2012095226 A 5/2012
JP 2012157167 A 8/2012
JP 2013099249 A 5/2013
JP 2013162624 A 8/2013
JP 2014501080 A 1/2014
JP 2014075927 A 4/2014
JP 2014112063 A 6/2014
JP 2014176131 A 9/2014
JP 2014223018 A 11/2014
JP 2015027345 A 2/2015
JP 2015128349 A 7/2015
JP 2015128370 A 7/2015
JP WO2015177859 A1 4/2017
KR 20060061776 A 6/2006
KR 20070044302 A 4/2007
KR 100755144 B1 9/2007
KR 20110132059 A 12/2011
KR 20110135540 A1 12/2011
KR 20120009843 A 2/2012
KR 20120108759 A 10/2012
KR 20130026977 A 3/2013
KR 20140023409 A 2/2014
KR 20140023410 A 3/2014
KR 20140085200 A 7/2014

KR 20140148270 A 12/2014
KR 20150077678 A 7/2015
RU 2658332 C1 6/2018
WO WO 199508125 A1 3/1995
WO WO 199831070 A1 7/1998
WO WO 199952173 A1 10/1999
WO WO 2000111716 A1 2/2001
WO WO 2003091943 A1 11/2003
WO WO 2004077550 A1 9/2004
WO WO 2006122783 A2 11/2006
WO WO 2007070571 A2 6/2007
WO WO 2008024993 A2 2/2008
WO WO 2008156571 A2 12/2008
WO WO 2010022181 A1 2/2010
WO WO 2010039246 A1 4/2010
WO WO 2010116441 A1 10/2010
WO WO 2010138994 A1 12/2010
WO WO 2011112022 A2 9/2011
WO WO 2012177283 A1 12/2012
WO WO 2013031988 A1 3/2013
WO WO 2013035190 A1 3/2013
WO WO 2013038074 A2 3/2013
WO WO 2013042399 A1 3/2013
WO WO 2013052950 A1 4/2013
WO WO 2013105920 A2 7/2013
WO WO 2013175596 A1 11/2013
WO WO 2014068992 A1 5/2014
WO WO 2014075103 A1 5/2014
WO WO 2014113093 A1 7/2014
WO WO 2014132258 A1 9/2014
WO WO 2014134996 A1 9/2014
WO WO 2014156465 A1 10/2014
WO WO 2014182788 A2 11/2014
WO WO 2014182788 A3 11/2014
WO WO 2014197472 A1 12/2014
WO WO 2014209587 A1 12/2014
WO WO 2015038773 A1 3/2015
WO WO 2015097809 A1 7/2015
WO WO 2015130902 A1 9/2015
WO WO 2015161323 A1 10/2015
WO WO 2016024869 A1 2/2016
WO WO 2016048512 A1 3/2016
WO WO 2016088261 A1 6/2016
WO WO 2016187357 A1 11/2016
WO WO 2017112942 A1 6/2017

OTHER PUBLICATIONS

Energous Corp., IPRP, PCT/US2014/037109, Apr. 12, 2016, 9 pgs.
Energous Corp., IPRP, PCT/US2014/037170, Nov. 10, 2015, 8 pgs.
Energous Corp., IPRP, PCT/US2014/040648, Dec. 8, 2015, 8 pgs.
Energous Corp., IPRP, PCT/US2014/040697, Dec. 8, 2015, 9 pgs.
Energous Corp., IPRP, PCT/US2014/040705, Dec. 8, 2015, 6 pgs.
Energous Corp., IPRP, PCT/US2014/041323, Dec. 22, 2015, 8 pgs.
Energous Corp., IPRP, PCT/US2014/041342, Dec. 15, 2015, 8 pgs.
Energous Corp., IPRP, PCT/US2014/041534, Dec. 29, 2015, 7 pgs.
Energous Corp., IPRP, PCT/US2014/041546, Dec. 29, 2015, 9 pgs.
Energous Corp., IPRP, PCT/US2014/041558, Dec. 29, 2015, 6 pgs.
Energous Corp., IPRP, PCT/US2014/044810, Jan. 5, 2016, 10 pgs.
Energous Corp., IPRP, PCT/US2014/045102, Jan. 12, 2016, 11 pgs.
Energous Corp., IPRP, PCT/US2014/045119, Jan. 12, 2016, 9 pgs.
Energous Corp., IPRP, PCT/US2014/045237, Jan. 12, 2016, 12 pgs.
Energous Corp., IPRP, PCT/US2014/046941, Jan. 19, 2016, 9 pgs.
Energous Corp., IPRP, PCT/US2014/046956, Jan. 19, 2016, 7 pgs.
Energous Corp., IPRP, PCT/US2014/046961, Jan. 19, 2016, 8 pgs.
Energous Corp., IPRP, PCT/US2014/047963, Jan. 26, 2016, 10 pgs.
Energous Corp., IPRP, PCT/US2014/048002, Feb. 12, 2015, 8 pgs.
Energous Corp., IPRP, PCT/US2014/049666, Feb. 9, 2015, 5 pgs.
Energous Corp., IPRP, PCT/US2014/049669, Feb. 9, 2016, 8 pgs.
Energous Corp., IPRP, PCT/US2014/049673, Feb. 9, 2016, 6 pgs.
Energous Corp., IPRP, PCT/US2014/054891, Mar. 15, 2016, 10 pgs.
Energous Corp., IPRP, PCT/US2014/054897, Mar. 15, 2016, 8 pgs.
Energous Corp., IPRP, PCT/US2014/054953, Mar. 22, 2016, 5 pgs.
Energous Corp., IPRP, PCT/US2014/055195, Mar. 22, 2016, 9 pgs.
Energous Corp., IPRP, PCT/US2014/059317, Apr. 12, 2016, 10 pgs.

(56)

References Cited

OTHER PUBLICATIONS

- Energous Corp., IPRP, PCT/US2014/059340, Apr. 12, 2016, 11 pgs.
 Energous Corp., IPRP, PCT/US2014/059871, Apr. 12, 2016, 9 pgs.
 Energous Corp., IPRP, PCT/US2014/062661, May 3, 2016, 10 pgs.
 Energous Corp., IPRP, PCT/US2014/062672, May 10, 2016, 8 pgs.
 Energous Corp., IPRP, PCT/US2014/062682, May 3, 2016, 8 pgs.
 Energous Corp., IPRP, PCT/US2014/068282, Jun. 7, 2016, 10 pgs.
 Energous Corp., IPRP, PCT/US2014/068568, Jun. 14, 2016, 8 pgs.
 Energous Corp., IPRP, PCT/US2014/068586, Jun. 14, 2016, 8 pgs.
 Energous Corp., IPRP, PCT/US2015/067242, Jun. 27, 2017, 7 pgs.
 Energous Corp., IPRP, PCT/US2015/067243, Jun. 27, 2017, 7 pgs.
 Energous Corp., IPRP, PCT/US2015/067245, Jun. 27, 2017, 7 pgs.
 Energous Corp., IPRP, PCT/US2015/067246, Jun. 27, 2017, 9 pgs.
 Energous Corp., IPRP, PCT/US2015/067249, Jun. 27, 2017, 7 pgs.
 Energous Corp., IPRP, PCT/US2015/067250, Mar. 30, 2016, 10 pgs.
 Energous Corp., IPRP, PCT/US2015/067271, Jul. 4, 2017, 5 pgs.
 Energous Corp., IPRP, PCT/US2015/067275, Jul. 4, 2017, 7 pgs.
 Energous Corp., IPRP, PCT/US2015/067279, Jul. 4, 2017, 7 pgs.
 Energous Corp., IPRP, PCT/US2015/067282, Jul. 4, 2017, 6 pgs.
 Energous Corp., IPRP, PCT/US2015/067287, Jul. 4, 2017, 6 pgs.
 Energous Corp., IPRP, PCT/US2015/067291, Jul. 4, 2017, 4 pgs.
 Energous Corp., IPRP, PCT/US2015/067294, Jul. 4, 2017, 6 pgs.
 Energous Corp., IPRP, PCT/US2015/067325, Jul. 4, 2017, 8 pgs.
 Energous Corp., IPRP, PCT/US2015/067334, Jul. 4, 2017, 5 pgs.
 Energous Corp., IPRP, PCT/US2016/068495, Jun. 26, 2018, 7 pgs.
 Energous Corp., IPRP, PCT/US2016/068498, Jun. 26, 2018, 6 pgs.
 Energous Corp., IPRP, PCT/US2016/068504, Jun. 26, 2018, 5 pgs.
 Energous Corp., IPRP, PCT/US2016/068551, Jun. 26, 2018, 6 pgs.
 Energous Corp., IPRP, PCT/US2016/068565, Jun. 26, 2018, 9 pgs.
 Energous Corp., IPRP, PCT/US2016/068987, Jul. 3, 2018, 7 pgs.
 Energous Corp., IPRP, PCT/US2016/068993, Jul. 3, 2018, 10 pgs.
 Energous Corp., IPRP, PCT/US2016/069313, Jul. 3, 2018, 7 pgs.
 Energous Corp., IPRP, PCT/US2016/069316, Jul. 3, 2018, 12 pgs.
 Energous Corp., IPRP, PCT/US2017/046800, Feb. 12, 2019, 10 pgs.
 Energous Corp., IPRP, PCT/US2017/065886, Jun. 18, 2019, 10 pgs.
 Energous Corp., IPRP, PCT/US2018/012806, Jul. 9, 2019, 6 pgs.
 Energous Corp., IPRP, PCT/US2018/025465, Oct. 1, 2019, 8 pgs.
 Energous Corp., IPRP, PCT/US2018/031768, Nov. 12, 2019, 8 pgs.
 Energous Corp., IPRP, PCT/US2018/031786, Apr. 14, 2020, 7 pgs.
 Energous Corp., IPRP, PCT/US2018/039334, Dec. 24, 2019, 8 pgs.
 Energous Corp., IPRP, PCT/US2018/051082, Mar. 17, 2020, 9 pgs.
 Energous Corp., IPRP, PCT/US2018/058178, May 5, 2020, 7 pgs.
 Energous Corp., IPRP, PCT/US2019/015820, Aug. 4, 2020, 7 pgs.
 Energous Corp., IPRP, PCT/US2019/021817, Sep. 15, 2020, 7 pgs.
 Energous Corp., IPRP, PCT/US2020/067566, Jul. 5, 2022, 8 pgs.
 Energous Corp., ISRWO, PCT/US2014/037072, Sep. 12, 2014, 8 pgs.
 Energous Corp., ISRWO, PCT/US2014/037109, Apr. 8, 2016, 12 pgs.
 Energous Corp., ISRWO, PCT/US2014/037170, Sep. 15, 2014, 11 pgs.
 Energous Corp., ISRWO, PCT/US2014/040648, Oct. 10, 2014, 11 pgs.
 Energous Corp., ISRWO, PCT/US2014/040697, Oct. 1, 2014, 12 pgs.
 Energous Corp., ISRWO, PCT/US2014/040705, Sep. 23, 2014, 8 pgs.
 Energous Corp., ISRWO, PCT/US2014/041323, Oct. 1, 2014, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/041342, Jan. 27, 2015, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/041534, Oct. 13, 2014, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/041546, Oct. 16, 2014, 12 pgs.
 Energous Corp., ISRWO, PCT/US2014/041558, Oct. 10, 2014, 8 pgs.
 Energous Corp., ISRWO, PCT/US2014/044810 Oct. 21, 2014, 12 pgs.
 Energous Corp., ISRWO, PCT/US2014/045102, Oct. 28, 2014, 14 pgs.
 Energous Corp., ISRWO, PCT/US2014/045119, Oct. 13, 2014, 11 pgs.
 Energous Corp., ISRWO, PCT/US2014/045237, Oct. 13, 2014, 16 pgs.
 Energous Corp., ISRWO, PCT/US2014/046941, Nov. 6, 2014, 11 pgs.
 Energous Corp., ISRWO, PCT/US2014/046956, Nov. 12, 2014, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/046961, Nov. 24, 2014, 16 pgs.
 Energous Corp., ISRWO, PCT/US2014/047963, Nov. 7, 2014, 13 pgs.
 Energous Corp., ISRWO, PCT/US2014/048002, Nov. 13, 2014, 11 pgs.
 Energous Corp., ISRWO, PCT/US2014/049666, Nov. 10, 2014, 7 pgs.
 Energous Corp., ISRWO, PCT/US2014/049669, Nov. 13, 2014, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/049673, Nov. 18, 2014, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/054891, Dec. 18, 2014, 12 pgs.
 Energous Corp., ISRWO, PCT/US2014/054897, Feb. 17, 2015, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/054953, Dec. 4, 2014, 7 pgs.
 Energous Corp., ISRWO, PCT/US2014/055195, Dec. 22, 2014, 11 pgs.
 Energous Corp., ISRWO, PCT/US2014/059317, Feb. 24, 2015, 13 pgs.
 Energous Corp., ISRWO, PCT/US2014/059340, Jan. 15, 2015, 13 pgs.
 Energous Corp., ISRWO, PCT/US2014/059871, Jan. 23, 2015, 12 pgs.
 Energous Corp., ISRWO, PCT/US2014/062661, Jan. 27, 2015, 12 pgs.
 Energous Corp., ISRWO, PCT/US2014/062672, Jan. 26, 2015, 11 pgs.
 Energous Corp., ISRWO, PCT/US2014/062682, Feb. 12, 2015, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/068282, Mar. 19, 2015, 13 pgs.
 Energous Corp., ISRWO, PCT/US2014/068568, Mar. 20, 2015, 10 pgs.
 Energous Corp., ISRWO, PCT/US2014/068586, Mar. 20, 2015, 11 pgs.
 Energous Corp., ISRWO, PCT/US2015/067242, Mar. 16, 2016, 9 pgs.
 Energous Corp., ISRWO, PCT/US2015/067243, Mar. 10, 2016, 11 pgs.
 Energous Corp., ISRWO, PCT/US2015/067245, Mar. 17, 2016, 8 pgs.
 Energous Corp., ISRWO, PCT/US2015/067246, May 11, 2016, 18 pgs.
 Energous Corp., ISRWO, PCT/US2015/067249, Mar. 29, 2016, 8 pgs.
 Energous Corp., ISRWO, PCT/US2015/067250, Mar. 30, 2016, 11 pgs.
 Energous Corp., ISRWO, PCT/US2015/067271, Mar. 11, 2016, 6 pgs.
 Energous Corp., ISRWO, PCT/US2015/067275, Mar. 3, 2016, 8 pgs.
 Energous Corp., ISRWO, PCT/US2015/067279, Mar. 11, 2015, 13 pgs.
 Energous Corp., ISRWO, PCT/US2015/067282, Jul. 5, 2016, 7 pgs.
 Energous Corp., ISRWO, PCT/US2015/067287, Feb. 2, 2016, 8 pgs.
 Energous Corp., ISRWO, PCT/US2015/067291, Mar. 4, 2016, 10 pgs.
 Energous Corp., ISRWO, PCT/US2015/067294, Mar. 29, 2016, 7 pgs.

(56)

References Cited

OTHER PUBLICATIONS

Energous Corp., ISRWO, PCT/US2015/067325, Mar. 10, 2016, 9 pgs.
 Energous Corp., ISRWO, PCT/US2015/067334, Mar. 3, 2016, 6 pgs.
 Energous Corp., ISRWO, PCT/US2016/068495, Mar. 30, 2017, 9 pgs.
 Energous Corp., ISRWO, PCT/US2016/068498, May 17, 2017, 8 pgs.
 Energous Corp., ISRWO, PCT/US2016/068504, Mar. 30, 2017, 8 pgs.
 Energous Corp., ISRWO, PCT/US2016/068551, Mar. 17, 2017, 8 pgs.
 Energous Corp., ISRWO, PCT/US2016/068565, Mar. 8, 2017, 11 pgs.
 Energous Corp., ISRWO, PCT/US2016/068987, May 8, 2017, 10 pgs.
 Energous Corp., ISRWO, PCT/US2016/068993, Mar. 13, 2017, 12 pgs.
 Energous Corp., ISRWO, PCT/US2016/069313, Nov. 13, 2017, 10 pgs.
 Energous Corp., ISRWO, PCT/US2016/069316, Mar. 16, 2017, 15 pgs.
 Energous Corp., ISRWO, PCT/US2017/046800, Sep. 11, 2017, 13 pgs.
 Energous Corp., ISRWO, PCT/US2017/065886, Apr. 6, 2018, 13 pgs.
 Energous Corp., ISRWO, PCT/US2018/012806, Mar. 23, 2018, 9 pgs.
 Energous Corp., ISRWO, PCT/US2018/025465, Jun. 22, 2018, 9 pgs.
 Energous Corp., ISRWO, PCT/US2018/031768, Jul. 3, 2018, 9 pgs.
 Energous Corp., ISRWO, PCT/US2018/031786, Aug. 8, 2018, 9 pgs.
 Energous Corp., ISRWO, PCT/US2018/039334, Sep. 11, 2018, 9 pgs.
 Energous Corp., ISRWO, PCT/US2018/051082, Dec. 12, 2018, 9 pgs.
 Energous Corp., ISRWO, PCT/US2018/058178, Mar. 13, 2019, 10 pgs.
 Energous Corp., ISRWO, PCT/US2018/064289, Apr. 25, 2019, 12 pgs.
 Energous Corp., ISRWO, PCT/US2019/015820, May 14, 2019, 9 pgs.
 Energous Corp., ISRWO, PCT/US2019/021817, Apr. 6, 2019, 11 pgs.
 Energous Corp., ISRWO, PCT/US2019/039014, Oct. 4, 2019, 15 pgs.
 Energous Corp., ISRWO, PCT/US2019/061445, Jan. 7, 2020, 19 pgs.
 Energous Corp., ISRWO, PCT/US2020/015450, May 18, 2020, 8 pgs.
 Energous Corp., ISRWO, PCT/US2020/016975, May 15, 2020, 15 pgs.
 Energous Corp., ISRWO, PCT/US2020/027409, Jul. 24, 2020, 11 pgs.
 Energous Corp., ISRWO, PCT/US2020/067566, Apr. 27, 2021, 12 pgs.
 Notice of Intent to Issue Reexam Certificate: 90/013793 Feb. 2, 2017, 8 pgs.
 Order Granting Reexamination Request, App No. 90/013793 Aug. 31, 2016, 23 pgs.
Ossia Inc. vs Energous Corp., Declaration of Stephen B. Hepe in Support of Petition for Post-Grant Review of U.S. Pat. No. 9,124,125, PGR2016-00023, May 31, 2016, 144 pgs.
Ossia Inc. vs Energous Corp., Declaration of Stephen B. Hepe in Support of Petition for Post-Grant Review of U.S. Pat. No. 9,124,125, PGR2016-00024, May 31, 2016, 122 pgs.
Ossia Inc. vs Energous Corp., Patent Owner Preliminary Response, Sep. 8, 2016, 95 pgs.

Ossia Inc. vs Energous Corp., Petition for Post Grant Review of U.S. Pat. No. 9,124,125, May 31, 2016, 86 pgs.
Ossia Inc. vs Energous Corp., Petition for Post-Grant Review of U.S. Pat. No. 9,124,125, May 31, 2016, 92 pgs.
Ossia Inc. vs Energous Corp., PGR2016-00023—Institution Decision, Nov. 29, 2016, 29 pgs.
Ossia Inc. vs Energous Corp., PGR2016-00024—Institution Decision, Nov. 29, 2016, 50 pgs.
Ossia Inc. vs Energous Corp., PGR2016-00024—Judgement-Adverse, Jan. 20, 2017, 3 pgs.
 Extended European Search Report, EP14818136.5, Jul. 21, 2016, 9 pgs.
 Extended European Search Report, EP14822971.9, Feb. 10, 2017, 10 pgs.
 Extended European Search Report, EP14868901.1, Jul. 17, 2017, 6 pgs.
 Extended European Search Report, EP15874273.4, May 11, 2018, 7 pgs.
 Extended European Search Report, EP15876033.0, Jun. 13, 2018, 10 pgs.
 Extended European Search Report, EP15876036.3, May 3, 2018, 9 pgs.
 Extended European Search Report, EP15876043.9, Aug. 9, 2018, 9 pgs.
 Extended European Search Report, EP16189052.0, Feb. 10, 2017, 13 pgs.
 Extended European Search Report, EP16189300.3, Mar. 24, 2017, 6 pgs.
 Extended European Search Report, EP16189319.3, Feb. 10, 2017, 11 pgs.
 Extended European Search Report, EP16189974.5, Mar. 13, 2017, 7 pgs.
 Extended European Search Report, EP16189982.8, Feb. 7, 2017, 11 pgs.
 Extended European Search Report, EP16189987.7, Feb. 9, 2017, 10 pgs.
 Extended European Search Report, EP16189988.5, Mar. 13, 2017, 6 pgs.
 Extended European Search Report, EP16193743.8, Feb. 8, 2017, 9 pgs.
 Extended European Search Report, EP16196205.5, Apr. 7, 2017, 9 pgs.
 Extended European Search Report, EP16880139.7, Jul. 12, 2019, 5 pgs.
 Extended European Search Report, EP16880153.8, Jul. 2, 2019, 9 pgs.
 Extended European Search Report, EP16880158.7, Jul. 15, 2019, 8 pgs.
 Extended European Search Report, EP16882597.4, Aug. 7, 2019, 9 pgs.
 Extended European Search Report, EP16882696.4, Jul. 3, 2019, 10 pgs.
 Extended European Search Report, EP17840412.5, Jul. 15, 2019, 8 pgs.
 Extended European Search Report, EP17882087.4, Sep. 17, 2019, 10 pgs.
 Extended European Search Report, EP18204043.6, Feb. 14, 2019, 5 pgs.
 Extended European Search Report, EP18797695.6, Nov. 19, 2020, 9 pgs.
 Extended European Search Report, EP19214719.7, Jan. 17, 2020, 9 pgs.
 Extended European Search Report, EP20909157.8, Sep. 15, 2023, 9 pgs.
 Adamiuk et al., “Compact, Dual-Polarized UWB-Antenna, Embedded in a Dielectric,” IEEE Transactions on Antenna and Propagation, IEEE Service Center, Piscataway, NJ, US vol. 56, No. 2, Feb. 1, 2010, 8 pgs.
 Gill et al., “A System for Change Detection and Human Recognition in Voxel Space using the Microsoft Kinect Sensor,” 2011 IEEE Applied Imagery Pattern Recognition Workshop. 8 pgs.

(56)

References Cited

OTHER PUBLICATIONS

Han et al., Enhanced Computer Vision with Microsoft Kinect Sensor: A Review, IEEE Transactions on Cybernetics vol. 43, No. 5., pp. 1318-1334, Oct. 3, 2013.

Hsieh et al., "Development of a Retrodirective Wireless Microwave Power Transmission System", IEEE, 2003, pp. 393-396.

Leabman, "Adaptive Band-partitioning for Interference Cancellation in Communication System," Thesis Massachusetts Institute of Technology, Feb. 1997, pp. 1-70.

Li et al., "High-Efficiency Switching-Mode Charger System Design Considerations with Dynamic Power Path Management," Mar./Apr. 2012 Issue, 8 pgs.

Mao et al., "BeamStar: An Edge-Based Approach to Routing in Wireless Sensors Networks", IEEE Transactions on Mobile Computing, IEEE Service Center, Los Alamitos, CA, vol. 6, No. 11, Nov. 1, 2007, 13 pgs.

Mascarenas et al., "Experimental Studies of Using Wireless Energy Transmission for Powering Embedded Sensor Nodes," Nov. 28, 2009, Journal of Sound and Vibration, 13 pgs.

Mishra et al., "SIW-based Slot Array Antenna and Power Management Circuit for Wireless Energy Harvesting Applications", IEEE APSURSI, Jul. 2012, 2 pgs.

Nenzi et al., "U-Helix: On-Chip Short Conical Antenna", 7th European Conference on Antennas and Propagation (EUCAP), ISBN: 978-1-4673-2187-7, IEEE, Apr. 8, 2013, 5 pgs.

Qing et al., "UHF Near-Field Segmented Loop Antennas with Enlarged Interrogation Zone," 2012 IEEE International Workshop on Antenna Technology (iWAT), Mar. 1, 2012, pp. 132-135, XP055572059, ISBN: 978-1-4673-0035-3.

Singh, "Wireless Power Transfer Using Metamaterial Bonded Microstrip Antenna for Smart Grid WSN", 4th International Conference on Advances in Computing and Communications (ICACC), Aug. 27-29, 2014, 1 pg.

Smolders, "Broadband Microstrip Array Antennas", Institute of Electrical and Electronics Engineers, Digest of the Antennas and Propagation Society International Symposium, Seattle, WA, Jun. 19-24, 1994, 3 pgs.

Van Veen et al., "Beamforming: A Versatile Approach to Spatial Filtering", IEEE, ASSP Magazine, Apr. 1988, pp. 4-24.

Wei et al., "Design of a Wideband Horizontally Polarized Omnidirectional Printed Loop Antenna," IEEE Antennas and Wireless Propagation Letters, vol. 11, Jan. 3, 2012, 4 pgs.

Zeng et al., "A Compact Fractal Loop Rectenna for RF Energy Harvesting," IEEE Antennas and Wireless Propagation Letters, vol. 16, Jun. 26, 2017, 4 pgs.

Zhai et al., "A Practical Wireless Charging System Based on Ultra-Wideband Retro-Reflective Beamforming", 2010 IEEE Antennas and Propagation Society International Symposium, Toronto, ON, 2010, 4 pgs.

* cited by examiner




Figure 1

200




Figure 2

300




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7

800




Figure 8




Figure 9A




Figure 9B




Figure 9C

1000




Figure 10

1100




Figure 11

1200




Figure 12




Figure 13




Figure 14A




Figure 14B




Figure 15

1600




Figure 16

1700




Figure 17

1800




Figure 18

1900




Figure 19




Figure 20A




Figure 20B




Figure 21

**SYSTEMS AND METHODS OF WIRELESSLY
DELIVERING POWER TO A
WIRELESS-POWER RECEIVER DEVICE IN
RESPONSE TO A CHANGE OF
ORIENTATION OF THE WIRELESS-POWER
RECEIVER DEVICE**

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/216,474, filed Mar. 29, 2021, entitled “Systems And Methods Of Determining A Location Of A Receiver Device And Wirelessly Delivering Power To A Focus Region Associated With The Receiver Device,” which is a continuation of U.S. patent application Ser. No. 15/912,520, filed Mar. 5, 2018 (now U.S. Pat. No. 10,965,164), entitled “Systems And Methods Of Wirelessly Delivering Power To A Receiver Device” (the “Parent Application”) which is a continuation-in-part of U.S. patent application Ser. No. 13/891,399, filed May 10, 2013 (now U.S. Pat. No. 9,912,199), entitled “Receivers for Wireless Power Transmission,” which claims priority to U.S. Provisional Application No. 61/668,799, filed on Jul. 6, 2012, U.S. Provisional Application No. 61/677,706, filed on Jul. 31, 2012, and U.S. Provisional Application No. 61/720,798, filed on Oct. 31, 2012. Each of these applications is hereby incorporated by reference in its respective entirety.

This Parent Application is also a continuation-in-part of U.S. patent application Ser. No. 13/891,445, filed May 10, 2013 (now U.S. Pat. No. 10,103,582) entitled “Transmitters for Wireless Power Transmission,” which claims priority to U.S. Provisional Application No. 61/668,799, filed on Jul. 6, 2012, U.S. Provisional Application No. 61/677,706, filed on Jul. 31, 2012, and U.S. Provisional Application No. 61/720,798, filed on Oct. 31, 2012. Each of these applications is hereby incorporated by reference in its respective entirety.

BACKGROUND

People are increasingly relying on electronic devices to perform aspects of everyday life. As an example, many people spend a majority of their day interacting with a computing device, such as a smart phone or tablet computer, in order to obtain information and communicate with others, among other such tasks. The frequent use of these devices can require a significant amount of power, which can quickly drain a battery for devices such as portable computing devices that have relatively small battery lives. A user then must often plug in the device to recharge, which can limit the usefulness of the portable device. Further, a user first has to locate a free outlet, which might be difficult in at least some locations. If a user forgets to plug in or otherwise charge a device, the device can run out of power and then be of no use to the user until the user is again able to charge the device. For frequently used devices, such as remote control units for older electronics or gaming controllers for older systems, the batteries might run out of power in between uses, which can be frustrating for a user.

There have been various approaches to minimizing the impact of the charging needs of these devices. In some cases the devices have replaceable rechargeable batteries, such that a new set of batteries can be used if the current set runs out of power. Such an approach requires a user to carry around extra batteries, and also ensure that these extra batteries are charged. Some approaches involve a mat or pad that is able to charge a device without physically connecting a plug of the device, but such an approach still requires the

device to be placed in a certain location for a certain amount of time in order to charge, which limits the improvement over physical power connections. Even for devices that do not run from battery power, the need to place these devices within a distance of a power outlet or other such component can limit the usefulness or flexibility of these devices. As users continue to use these devices, and as the number and type of devices grow, there is a desire to improve the way in which power can be delivered to these and other such devices.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the present invention may be more clearly ascertained, some embodiments will now be described, by way of example, with reference to the accompanying drawings, in which:

FIG. 1 illustrates a situation in which power can be delivered wirelessly in accordance with one embodiment;

FIG. 2 illustrates an example of a receiver that can be used in accordance with various embodiments;

FIG. 3 illustrates an example transmitter that can be used in accordance with various embodiments;

FIG. 4 illustrates a first receiver configuration that can be used in accordance with various embodiments;

FIG. 5 illustrates a second receiver configuration that can be used in accordance with various embodiments;

FIG. 6 illustrates a third receiver configuration that can be used in accordance with various embodiments;

FIG. 7 illustrates a fourth receiver configuration that can be used in accordance with various embodiments;

FIG. 8 illustrates a novel flat panel antenna array design that can be utilized in accordance with various embodiments;

FIGS. 9A-9C illustrate example logical schematics for implementations of a flat panel antenna array such as that illustrated in FIG. 8, which can be utilized in accordance with various embodiments;

FIG. 10 illustrates a receiver built into a computing device that can be utilized in accordance with various embodiments;

FIG. 11 illustrates a battery with a built-in receiver that can charge wirelessly while contained in a computing device that can be utilized in accordance with various embodiments;

FIG. 12 illustrates an example of an attachment that can be used to wirelessly receive power to a computing device that can be utilized in accordance with various embodiments;

FIG. 13 illustrates an example transmitter configuration that can be used in accordance with various embodiments;

FIGS. 14A and 14B illustrate example power delivery approaches that can be used in accordance with various embodiments;

FIG. 15 illustrates an example transmitter configuration that can be used in accordance with various embodiments;

FIG. 16 illustrates a transmitter built into a computing device that can be utilized in accordance with various embodiments;

FIG. 17 illustrates a transmitter built into a battery pack that can be utilized in accordance with various embodiments;

FIGS. 18-19 illustrate examples of an attachment that can be used to wirelessly transmit power from a computing device that can be utilized in accordance with various embodiments;

FIGS. 20A-20B illustrate example antenna panel configuration that can be used in accordance with various embodiments; and

FIG. 21 illustrates an example antenna panel configuration that can be utilized in accordance with various embodiments.

DETAILED DESCRIPTION

Embodiments described in accordance with the various embodiments overcome at least some of the aforementioned and other deficiencies in conventional approaches to power delivery. In particular, various embodiments enable power to be delivered wirelessly, without the need for a physical connection between a source and a recipient of the power delivery. In at least some embodiments, a transmitter can be used that includes two or more antennas in communication with control circuitry and/or components. The transmitter can utilize an approach such as “beamforming” to direct a signal, such as a radio frequency (RF) signal, in a determined direction. The transmitter can also utilize the antennas to determine the location of a receiver of the power transmission, in order to determine how to adjust the antennas to deliver the power to the appropriate location, as well as to determine how to “form” the beam in order to provide for an appropriate amount of focusing of the signal, such as may correspond to a size of an antenna array of a receiver of the target device.

The power can be received by a receiver component, which can be part of, connected to, or separate from a device to be powered. The receiver can include one or more antennas for receiving the signal from the transmitter, and components or circuitry useful in converting the signal into power for powering a device, charging a battery, or performing another such function. The receiver can communicate with the transmitter using the antennas, and in at least some embodiments each can also include at least one wireless communication component for communicating information over a sideband channel. Such an approach can help the transmitter to ensure that power is being delivered to the appropriate device, and that the device (or user of the device) is “authorized” or otherwise has permission to receive power from the transmitter. Further, the transmitter can receive information about a current battery state or power level from the device, for example, and can deliver power only when power is necessary. The ability to transmit power only when power is needed and where it is needed can help to improve the overall efficiency of the power delivery system.

Various other functions and advantages are described and suggested below as may be provided in accordance with the various embodiments.

Approaches in accordance with various embodiments can take advantage of one of a plurality of advanced power communication antenna designs. These designs can be implemented on any appropriate device that relies on power for at least a portion of its operation or intended function, such as may include a smart phone, a tablet computer, a television remote, or a child’s toy, among many other such devices.

As an example, FIG. 1 illustrates an example situation **100** wherein a notebook computer **102** is connected to a receiver **104** including an antenna array that is configured to receive a transmitted signal from a transmitter **106**, which also includes an array of antennas **108**. The array in this example includes a plurality of “flat” elements with one or more desired polarizations, including vertical pole, horizon-

tal pole, circularly polarized, left hand polarized, right hand polarized, or a combination of polarizations. The receiver **104** for the notebook computer **102** can be embedded in the computer, such as may be contained behind a screen of the notebook, attached to a back of the notebook computer, or connected to the notebook computer as part of a separate component, among other such options. Since the array is associated with a portable device in this situation, the receiver will be referred to as a mobile receiver **104**. The mobile receiver in this embodiment can communicate with the notebook computer over a wired or wireless connection, as discussed elsewhere herein. In at least some embodiments, the receiver can communicate with the notebook to determine a current power level of the device, as well as to obtain other information such as a type of device, device identifier, user identifier, and the like. As discussed, any appropriate electronic device can be used with receivers discussed herein, and the notebook computer is just one example of this type of device, as may also include smart phones, remote controls, toys, tablet computers, media players, gaming systems and controllers, and the like. Further, while the mobile receiver **102** is illustrated as communicating with a power transmitter **106**, it should be noted that communications with any viable target are equally possible. This can include, for example, other mobile devices or other mobile platforms.

The antenna of the mobile receiver **104** can include one or more antenna elements as discussed herein, which can include at least one omni-antenna, directional antenna, array of antennas, or flat paneled system. In some embodiments, novel flat panel systems are usable, as will be discussed in greater detail below. Regardless of the type of antenna used, a directional beam **110** can be directed from the transmitter **106** to the receiver **104**. Directionality can be accomplished through any appropriate mechanism, as may include physical geometry (i.e., parabolic dish) or through signal reinforcement/interference (i.e., beamforming). The term “beamforming” derives from the fact that early spatial filters were designed to form pencil beams in order to receive a signal radiating from a specific location and attenuate signals from other locations. “Forming beams” seems to indicate radiation of energy; however, beamforming is applicable to either radiation or reception of energy.

Systems designed to receive spatially propagating signals often encounter the presence of interference signals. If the desired signal and interferers occupy the same temporal frequency band, temporal filtering cannot be used to separate signal from interference. However, the desired and interfering signals usually originate from different spatial locations. This spatial separation can be exploited to separate signal from interference using a spatial filter at the receiver. Implementing a temporal filter requires processing of data collected over a temporal aperture. Similarly, implementing a spatial filter requires processing of data collected over a spatial aperture.

In some embodiments, a beamformer linearly combines the spatially sampled time series from each sensor to obtain a scalar output time series in the same manner that an FIR (finite impulse response) filter linearly combines temporally sampled data. Spatial discrimination capability depends on the size of the spatial aperture; as the aperture increases, discrimination improves. The absolute aperture size is not important in at least some embodiments, rather its size in wavelengths is an important parameter. A single physical antenna (continuous spatial aperture) capable of providing the requisite discrimination is often practical for high frequency signals since the wavelength is short. However,

5

when low frequency signals are of interest, an array of sensors can often synthesize a much larger spatial aperture than that practical with a single physical antenna. Note each composite antenna represents a sensor in some embodiments.

A second very significant advantage of using an array of sensors, relevant at any wavelength, is the spatial filtering versatility offered by discrete sampling. In many application areas it is necessary to change the spatial filtering function in real time to maintain effective suppression of interfering signals. This change is easily implemented in a discretely sampled system by changing the way in which the beamformer linearly combines the sensor data. Changing the spatial filtering function of a continuous aperture antenna is impractical.

Beamforming takes advantage of interference to change the directionality of the array whereby constructive interference generates a beam and destructive interference generates the null space. If one issue of current communication antennas on mobile platforms is the inherent cost, bulk and unreliability of moving mechanical bases, it can be desirable to use and be able to change the direction in which RF emissions radiate using non-mechanical means. Beamforming using a smart antenna array, during transmission, is accomplished by controlling the phase and/or relative amplitude of the signal at each transmitter, in order to create a pattern of constructive and destructive interference in the wave front. Similarly, when receiving, information from different sensors is combined in such a way that the expected pattern of radiation is preferentially observed (null steering).

The ability to beamform in this manner requires a minimum of two antennas in the antenna array. This directionality benefit of beamforming has been known generally by those skilled in the art for some time. In general, beamforming may be accomplished in a number of ways, as known by those skilled in the art. For an example of a particular method of implementing directional beamforming, see: B. D. V. Veen and K. M. Buckley. Beamforming: A versatile approach to spatial filtering. IEEE ASSP Magazine, pages 4-24, April 1988.

An additional example of the mathematics behind beamforming may be found in the article by Michael Leabman entitled "Adaptive Band-Partitioning for Interference Cancellation in Communication Systems," Massachusetts Institute of Technology Press, February 1997.

Most array literature specifies spatial dependence in terms of "angles" which is intuitive. It is also possible to define the wavenumber variable \vec{k} which is a spatial vector in terms of Euclidean space, where, $|\vec{k}| = \omega/c$, ω being the radian frequency, ($2\pi f$), and c being the propagation speed in free space. Thus $|\vec{k}| = \omega/c = 2\pi f/c = 2\pi/\lambda$ has dimensions of 1/length, where the wavelength $\lambda = c/f$, and $c = 3 \cdot 10^8$ m/s for radio waves. While the standard angular representation does describe the response over the region for all real signals, the full wavenumber space, or 'virtual' space, is more useful in analyzing the consequences of spatial aliasing.

Now consider an array of N elements sampling an area of space where the element locations are governed by $[\vec{z}_{i,i}=1, \dots, N]$. The output from each sensor is input to a linear, time invariant filter having the impulse response $w_i(\tau)$. The outputs of the filter are summed to produce the output of the array $y(t)$,

$$y(t) = \sum_{i=1}^N \int_{-\infty}^{\infty} w_i(t - \tau) x(\tau, \vec{z}_i) d\tau$$

6

Using the Fourier representation for a space-time signal, a plane wave $x(t, \vec{z}_i)$ of a single frequency may be represented by a complex exponential in terms of a radian frequency ω , and vector wavenumber \vec{k} :

$$x(t, \vec{z}) = e^{j(\omega t - \vec{k} \cdot \vec{z}_i)}$$

The array response to a plane wave is as follows:

$$\begin{aligned} y(t) &= \sum_{i=1}^N \int_{-\infty}^{\infty} w_i(t - \tau) x(\tau, \vec{z}_i) d\tau \\ &= \sum_{i=1}^N \int_{-\infty}^{\infty} w_i(t - \tau) e^{j(\omega(t - \tau) - \vec{k} \cdot \vec{z}_i)} d\tau \\ &= \sum_{i=1}^N \int_{-\infty}^{\infty} w_i(t') e^{-j\omega t'} e^{-j\vec{k} \cdot \vec{z}_i} e^{j\omega t} dt' \quad \text{where } \tau = t' \\ &= \sum_{i=1}^N w_i(\omega) e^{j(\omega t - \vec{k} \cdot \vec{z}_i)} \end{aligned}$$

letting,

$$W(\omega) = \begin{bmatrix} w_1(\omega) \\ \vdots \\ w_N(\omega) \end{bmatrix} \text{ and}$$

$$E(k) = \begin{bmatrix} e^{-j\vec{k} \cdot \vec{z}_1} \\ \vdots \\ e^{-j\vec{k} \cdot \vec{z}_N} \end{bmatrix}$$

$$\text{becomes } y(t) = W^+(\omega) E(k) e^{j\omega t}$$

where $W(\omega, \vec{k}) = W^+(\omega) E(k)$ is the frequency wavenumber response. The frequency wavenumber response evaluated versus direction \vec{k} , is known as the beam pattern,

$$B(a(\theta, \phi)) = W(\omega, \vec{k}) \Big|_{k = \frac{2\pi}{\lambda} a(\theta, \phi)}$$

where $a(\theta, \phi)$ is the unit vector in spherical coordinates.

The most widely used array, suitable for some embodiments, is a linear uniformly weighted array with N elements and an inter-element spacing of Δz . Note such an array is used by way of example, and other array designs are considered within the scope of various embodiments.

If a frequency independent uniform weighting of $1/N$ is used, a frequency wavenumber response is arrived at:

$$W(\omega, k) = \frac{1}{N} \sum_{n=-\frac{N-1}{2}}^{\frac{N-1}{2}} e^{-j\vec{k} \cdot \hat{a}_z n \Delta z},$$

$$\text{where } k \cdot \hat{a}_z = k_z = \frac{\sin c \left(k_z \frac{L}{2} \right)}{\sin c \left(k_z \frac{\Delta z}{2} \right)}$$

7

Evaluating for $k_z = |k| \sin(\Theta) = \sin(\Theta)$, where (Θ) is defined with respect to the angle to the z axis, a beam pattern is calculated as:

$$B(\omega, \theta) = \frac{\sin c\left(2\pi \sin(\theta) \frac{L}{2\lambda}\right)}{\sin c\left(2\pi \sin(\theta) \frac{\Delta z}{2\lambda}\right)}, \text{ where}$$

$$L = N\Delta z$$

In some embodiments, combinations of beams and nulls may be utilized in order to increase gain in the target axis, while reducing the effective (or equivalent) isotropic radiated power (EIRP) in off axis angles. With more antennas on the array the number of beams/nulls is extendable to meet any specialized requirements.

In order to transfer power using a beamforming (or other such) approach, an example system includes at least one transmitter and at least one receiver. A component level example of a receiver **200** is illustrated in FIG. 2. As discussed, the receiver includes at least one antenna element **204** operable to receive a signal of the desired wavelength. The antenna typically will be contained in some type of housing **202**, which can include a housing dedicated to the receiver or a housing of an electronic device, where the receiver is embedded in the device. Other such configurations can be utilized as well. The housing can be made of any appropriate material, such as a plastic, hard rubber, or other such material that enables transmission of the signal to be received. The receiver can also include, internal or external to the housing **202**, at least one rectifier **206** and at least one converter **208**. The rectifier **206** can include any components known or used for such purposes, as may include at least one diode, capacitor, and resistor, among other such options. The rectifier is configured to convert the signal (e.g., an RF signal) received by the antenna **204** into a voltage (e.g., DC). Conventional or novel rectifiers can be used for such purposes in various embodiments. In some embodiments, as discussed elsewhere herein, the receiver can include multiple antennas and/or rectifiers in order to increase performance and efficiency, as well as to enable the receiver to scale in capacity.

The receiver in this example can also include at least one converter **208**, such as a DC-to-DC converter, that enables the receiver to output or provide the intended voltage. In one embodiment the receiver puts out a voltage in the range of about five volts to about 40 volts, while in other embodiments a receiver can output down to a quarter of a volt or less, or up to hundreds or even thousands of volts or more using scaling approaches discussed and suggested elsewhere herein. The converter in this example can take any power coming from the rectifier **206** and ensure that five volts are being output, such as to a battery **212** for charging. As discussed elsewhere herein, it should be understood that the power can be output to any appropriate device, system, component, or service, and in some embodiments can be the sole power source for an electronic device that might not include a dedicated battery or power source. Other such options can be used as well.

In some embodiments, the receiver can use the antenna(s) **204** to communicate with a transmitter, such as by "chirping" or generating a short signal (e.g., RF) that can be received by a transmitter or other such device. In some embodiments, the receiver can additionally (or alternatively) utilize at least one communications component **210** in order

8

to communicate with other devices or components. The communications component can be internal or external to the housing, and in some embodiments the receiver can leverage at least one communications component of a device to which the receiver is connected, or into which the receiver is embedded, among other such options. In at least some embodiments the communications component **210** enables the receiver to communicate using a wireless protocol. The wireless protocol can be a proprietary protocol, or in at least some embodiments can utilize a known or conventional wireless protocol in order to enable the receiver to communicate with additional types of devices. For example, the communications component can enable the receiver to communicate over a Bluetooth® channel, Wi-Fi, ZigBee, etc. As mentioned, the communications component can be used to transfer information such as an identifier for the device or a user of the device, and can also be used to transfer battery level information for a connected device, geographic location data, or other such information that can be useful in determining when to send power to the receiver, as well as the location at which to send the power beam. The communication can also include information about the receiver itself, such as the number of antenna elements, size and arrangement of those elements, power capacity, and other such information that can help to determine the size at which to focus the beam, as well as how much power should be transmitted via the beam. Other such information can be communicated as well, such as account information for use in charging the user for the power, or ensuring that the user, device, and/or receiver is authorized to receive power. Various other information can be transmitted as well in other embodiments.

A receiver can include other communication components as well. For example, the receiver housing **202** might include at least one lighting or display element, such as an LCD display or at least one LED, which can display or flash information that can be detected by a camera or sensor of another device, transmitter, or other such component. Similarly, the receiver might include at least one audio component, such as a speaker or microphone, that enables location determination via sonic triangulation or other such methods. Various other communication approaches can be utilized as well, as should be apparent.

FIG. 3 illustrates an example of a transmitter **300** that can be used to transmit power to a receiver such as that illustrated in FIG. 2. In this example, the transmitter includes at least two antenna elements **304** in order to be able to perform beamforming and/or signal direction for purposes of power transmission. In this example the antenna can be a patch or flat antenna with a diameter on the order of a quarter of an inch to ten inches, with a diameter of at least four inches in some embodiments. The antennas in at least some embodiments can be arranged in a flat array, while in other embodiments two or more orientations of the antenna elements can be used. In some embodiments the transmitter uses at least eight antenna elements, and in some embodiments 256 elements or more can be used for beamforming. As discussed elsewhere herein, however, any appropriate number, size, type, and configuration of antenna elements can be used based at least in part upon the power, distance, efficiency, and other such requirements of the system. Also as discussed, the antenna elements can have at least one polarization, or can have a selection of polarizations. These polarizations can include, for example, vertical pole, horizontal pole, circularly polarized, left hand polarized, right hand polarized, or a combination of polarizations. A transmitter might include a combination of horizontal and verti-

cal polarizations, or might include circular polarization, in order to maximize the directionality and efficiency of the power transmission, as a receiver might be in any of a number of orientations with respect to the transmitter, and there might be various obstructions or path directions that might advantageously utilize specific polarizations. The selection of polarizations can vary for different use cases and embodiments. Further, in some embodiments the antenna elements **304** may be located on more than one surface of the transmitter.

The transmitter can include, internal or external to a housing **302** of the transmitter, at least one signal generation component, such as an analog RF component. In this example, the transmitter includes at least one RF integrated circuit (RFIC) **306** including a plurality of analog RF circuits and/or components that are operable to control aspects of the antenna elements **304**, as may include the gain and/or phase of those elements, in order to form and steer a beam with the desired properties (e.g., direction, focus, power level, etc.). In at least some embodiments the RFIC is placed as close to the antenna elements as is practical, in order to minimize losses. One or more digital controllers, such as at least one microcontroller **308**, can be attached to the analog RF circuitry in order to control aspects such as when a beam is formed, the direction for the beam, and other such aspects. The microcontroller can be any appropriate microcontroller, such as a PIC-class microprocessor. At least some transmitters can include more than one layer of digital and/or analog RF circuits. Further, in some embodiments each antenna element or a subset of the antenna elements can be connected to a corresponding RF circuit, which can then be connected to one or more microcontrollers.

The housing **302** of the transmitter can take any appropriate form, and can be made of any appropriate material as discussed for the receiver housing. For flat antenna arrays, the receiver housing might take the form of a relatively flat housing, such as may be hung on a wall or ceiling, embedded into a panel, etc. Various other forms can be utilized as well. In some embodiments, the antenna elements and RFIC elements might be included in a first housing, with at least some of the other components being in a separate housing. For example, a power supply **312** and plug for connecting to an outlet or other power source might be part of a “base station” or component that can be placed near an outlet, on a table, on a floor, or in another appropriate location. The base station might be connected to a separate “antenna panel” including the antenna elements and RFIC components, among other possible elements such as one or more microcontrollers, in order to enable the panel to be placed in any appropriate location independent of a location of the base station. The use of a separate base station also enables alternate and/or additional array panels to be utilized without having to purchase or obtain an additional or alternate base station. The base station, antenna panel, or other transmitter also can include at least one communication component **310**, as discussed with respect to the receiver, in order to communicate with one or more receivers. In some embodiments, a transmitter might include multiple communication components in order to communicate with devices or receivers using different communication protocols. As discussed, the transmitter also can use the antennas, a camera, a sensor, a display, an LED, or another such element to enable, or assist with, communication. The transmitter can also be very low band with respect to other transmission technologies, such as the 2.4 GHz or 5.8 GHz of Wi-Fi.

The transmitter can thus focus a beam to an appropriate location and size associated with the antenna(s) of the

receiver, which can then be rectified by the rectifier of the receiver. The components of the rectifier such as the diode, however, can become relatively expensive as the power requirements increase. This can have the unfortunate result of increasing the cost of the receiver to a point that might make the system impractical or at least too expensive for certain users or applications. Accordingly, approaches in accordance with various embodiments can take advantage of multiple, lower power rectifiers that are significantly cheaper than equivalent higher power rectifiers. FIG. 4 illustrates a configuration **400** wherein multiple rectifiers **404** are connected in parallel between an antenna element **402**, or antenna array, and a DC converter **406** of the receiver. In an example where the receiver is attempting to convert 10 Watts, a large and expensive diode would be needed if only a single diode was to be used, as the diode dictates the amount that can be converted. There are relatively inexpensive diodes that can handle smaller amounts, such as on the order of a quarter of a Watt, although other size diodes can be used as well based on factors such as cost, space, etc. By using multiple, smaller rectifiers in parallel, the RF signals received by the antenna element can go through multiple parallel circuits, each of which can handle a portion of the wattage. In at least some embodiments, the wattage can be combined at the DC converter **406**. In other embodiments, there might also be multiple converters in parallel, and once the signal is converted to DC a conventional battery or power component can combine the power as needed.

There can be any appropriate number of rectifiers used. In some embodiments there can be two, four, six, or eight rectifiers (e.g., 2.5 GHz rectifiers) per antenna, depending at least in part upon the amount of power to be converted. In an example where power is to be provided to a notebook computer that requires twenty Watts, the receiver might include a single RFIC that includes a set of diodes arranged in parallel, or the receiver might include multiple RFIC elements connected in parallel. Other such configurations can be utilized as well within the scope of the various embodiments.

In at least some embodiments, it also can be desirable to utilize multiple, independent antenna elements as well. For example, FIG. 5 illustrates an example configuration **500** wherein multiple antenna elements **502** are connected in parallel to a rectifier **504** and DC converter **506**. In this example, each antenna might be able to handle a certain wattage, such as about one Watt each. Similar to the rectifiers and converters, the capacity of the receiver can be scaled by increasing the number of antenna elements to provide the necessary capacity. In the example where a notebook computer requires 20 Watts, if each antenna element can handle one Watt then twenty antenna elements can be combined in order to deliver the appropriate capacity. In embodiments where each antenna element is a small patch, for example, there can be enough room on (or within) the casing of the computer to embed multiple antenna elements, such as four antenna elements or more. Each antenna element can be connected to one or more rectifiers, or a subset of the antenna elements can be connected to one of a set of rectifiers, among other such options that can also be selected based upon factors such as cost, space, and capacity, among others. For example, if 20 Watts are needed and each antenna can handle 1 Watt, then 20 antenna elements might be used. Further, if each rectifier diode can handle $\frac{1}{4}$ Watt, then four rectifiers are needed in parallel for each antenna in this example. The rectifiers can be separate, or at least some can be contained on one or more chips or boards that have an

appropriate number of inputs. Other configurations and options can be used as well within the scope of the various embodiments. In at least some embodiments, the number of antenna elements that can be used might be limited by the size of the receiver housing or the size of the beam that can be transmitted by the transmitter, among other such factors.

FIG. 6 illustrates an example configuration 600 that can be used for a receiver in at least some embodiments. In this example, a number of antenna elements 602 are combined and their output is split across an array of rectifiers 604 configured to process the output in parallel. As discussed, it can be desirable in at least some embodiments for the rectifiers to be as close to the antennas as possible. Thus, although the rectifiers are shown “below” the antenna array in this example, it should be understood that in at least some embodiments the rectifiers can be behind or “within” the array in order to shorten the average path length and reduce losses. Further, in some embodiments each antenna can be connected to a dedicated rectifier, in order to further shorten the paths between the antennas and the rectifiers.

FIG. 7 illustrates yet another configuration 700, wherein the receiver includes a group of antenna/rectifier sets 702, 704, 706, and 708. Each of these sets can include a subset of the number of antenna elements in the array (e.g., one or more), and can include at least one rectifier. Such an approach enables each rectifier to be very close to the respective antenna(s). The output from each rectifier can then be combined either before or after the converter for the receiver. In this example the receiver also includes a number of converters 710, where each converter receives the output from one of the antenna/rectifier sets, and the output from the converters is then combined. It should also be understood that the output from the sets could be combined before the converters, which could then process the output in parallel. Various other options can be utilized as well in accordance with the various embodiments.

In these and other embodiments, a converter is capable of outputting a specific voltage, such as five volts in some examples, by converting any power or voltage coming in. As the amount of power increases the speed at which a battery or other such power source can be charged. Thus, it can be desirable in at least some embodiments, and where cost and space provide, for example, to include additional elements than are necessary to charge a particular device, in order to charge that device in less time. When multiple receivers are used with a single transmitter, for example, this can also improve the ability for a receiver to receive power when needed, as less time will be dedicated to other receivers. In one example, a device that can be charged using one Watt can be charged in 20% of the time it would take using one Watt by receiving five Watts. Further, the number of antenna elements on a receiver can, in at least some embodiments, also improve the efficiency of the wireless power delivery. In some embodiments, each receiver includes a number of antenna elements, such as ten elements, in order to provide for a range of power amounts, which can increase charging speed for at least some devices, and can guarantee a minimum efficiency of the power delivery. It should be understood that the efficiency and capacity also can be a factor of the number of antenna elements on the transmitter side. In some embodiments, a number of antenna elements can be determined for desired performance, and that number can be split among the transmitter and the receiver. For size, cost, and various other reasons, it will be the case in many embodiments that it will be more practical to place more of the antenna elements in the transmitter than in the receiver. Further, the number of elements needed on the transmitter is

a function of the number of elements on the receiver. If it is desirable to put 1,000 antennas on the transmitter, the same basic functionality can be achieved by placing ten antenna elements on the receiver and one hundred on the transmitter, as one element on the receiver side is roughly equivalent to about ten such elements on the transmitter side. In at least some embodiments, then, it can be desirable to place as many antenna elements (up to a potential target number of elements) as is practical. This is further advantageous in at least some instances as receivers can be cheaper to manufacture (and purchase) than receivers for at least some systems. In some embodiments receivers have on the order of from about ten elements to over one-hundred elements, such as forty elements in one example receiver device.

In at least some embodiments, the beam from the transmitter to the receiver is formed along the path of least resistance. For example, if there is an object positioned between the transmitter and the receiver, the transmitter might form the beam to reflect from the ceiling or a wall, which can have less attenuation than the object. Further, although the levels utilized for various applications are safe to operate around humans, such an approach can be further desirable as energy is sent around people instead of through them.

As discussed, although receivers in accordance with certain embodiments utilize single polarizations, it can be desirable in at least some embodiments to include antenna elements of multiple polarizations in a receiver. The use of multiple polarizations can be particularly beneficial for certain types of devices such as portable or mobile devices, where the orientation of the device will change at various times. In some embodiments half of the antenna arrays might be vertical polarized and half horizontal polarized. In other embodiments, right and left circular polarization can be used as well, in any desirable proportion or ratio. For receivers used with devices such as two-handed video game controllers that typically have a range of orientations, there might be greater number of one polarization than another in order to improve efficiency, charging speed, or other such aspects. Other types of antenna designs might be used as well, such as fractal antennas of appropriate bandwidth. An advantage of horizontal and vertical image patches, among other such designs, is that the patches can be the same, with the polarization being determined by the side from which the patch is connected to the receiver. In embodiments with an appropriate controller, each patch can be fed from either of two sides, and the receiver can dynamically adjust the polarization of each patch in order to improve performance. In this way the ratio of horizontal to vertical polarized antennas can be updated as needed to optimize performance for the current orientation and environment. Other antenna elements can be used as well, such as metamaterial antennas that can be significantly more efficient than conventional patch antennas, and in at least some embodiments can be on the order of 10% of the size of a conventional patch or less, all while providing the same gain capacity. Such elements can help to reduce the size of the transmitters and receivers as well.

In some embodiments, the transmitter might use less than a total number of antenna elements in a transmitter antenna array to transmit energy to the receiver. As long as at least two elements are used, the transmitter can perform advanced beamforming to implement beamnulling around mechanically point angle. Such an approach enables a suppression of off-axis sidelobes, and can result in a greater degree of compliance with FCC regulations than other approaches. Antenna designs utilized in accordance with various

embodiments can also enable a smaller antenna profile than is utilized for conventional antenna arrays used for communications and other such purposes, and reduces the need for a moving base or other such mechanical mechanism.

FIG. 8 illustrates a flat panel antenna array design **800** that can be used in accordance with various embodiments. This antenna array is illustrated as including 1005 separate elements in a circular arrangement that is approximately 34 inches in diameter. Alternate permutations are also possible including cut-off circular pattern, square, or other polygon arrangements. Additionally, this example array may be broken into numerous pieces and distributed across multiple surfaces (multi-faceted). While other numbers of elements are possible, the gain requirements for power transmitting favor at least 256 elements in this example. In some embodiments where size is an issue, the size of the antenna can be very small, such as on the order of about 4 inches in diameter, and can include as few as eight elements or less in various embodiments. In at least some embodiments a patch is a thin planar piece of metal, such as quarter mill metal. The antennas in some embodiments can be etched onto a printed circuit board, while in other embodiments the elements can be printed onto plastic or formed on a silicon chip, among other such options.

FIGS. 9A-9C illustrate cross section illustrations **900**, **920**, **940** of components of a flat panel antenna array such as that illustrated in FIG. 8. In the array configuration **900** of FIG. 9A the elements **902** are seen on a substrate layer **904**. The elements **902** may be horizontal pole, vertical pole, circular polarized, left hand polarized, right hand polarized or some combination thereof. The substrate layer **904** provides mechanical stability and heat absorption properties, for example. Wires can be seen extending from each element **902** to a corresponding RF circuit **906**. Due to the processing requirements of 1005 individual elements in this example, a combination of analog RF circuits **906** and one or more digital circuit(s) may be utilized to reduce processing requirements. However, since these elements are putting out very small signals, it can be desirable in at least some embodiments that the analog RF circuits **904** are physically closely aligned with the elements **902** in order to minimize loss. The phase and amplitude of each element **902** may be modulated by the respective RF circuit **904** in order to generate the desired beamform and null steering.

While FIG. 9A illustrates an array that has each element **902** coupled to a single RF circuit **906**, in FIG. 9B an array configuration **920** is illustrated where a subset of the elements **922** are coupled to a single RF circuit **926**. In this example, the RF circuit **926** couples to four elements **922**. More or fewer elements **922** may be controlled by each RF circuit **926**, in some embodiments. The determination of the required number of elements to be coupled to a single controller may be based at least in part upon processing requirements, desired array cost, and the needs of the final application, among other such factors. In some applications, very high levels of control and granularity may be desired, resulting in a lower ratio of controllers to elements. In other applications, fewer controllers are needed because beams control can be less granular.

For example, in FIG. 9C an array configuration **940** is illustrated where a pair of elements **942** couples to a single RF circuit **946**. This can provide greater control over beamforming than the previous example that coupled one controller to four elements. Two of these RF circuits may then couple to a second layer analog RF circuit **948**. In turn, two

of the second layer RF circuits **948** may couple to a single final RE circuit **950**. This RF circuit **950** may be an analog or a digital circuit.

In certain embodiments, the RF chips or other such components can be placed as closely to the antennas as possible by embedding the RF chips in a printed circuit board (PCB) positioned just behind, or adjacent to, the respective antenna elements. Such an approach avoids the need to run long traces or RF cables, etc. Since large antenna arrays can require hundreds of such cables, such an approach can significantly reduce the overall cabling length and associated losses. The RF chips can be embedded in locations selected to reduce the length of wire needed. Thus, the array of antenna or dipole elements can have the RFIC analog chip or other such component embedded right behind, in order to minimize the trace length and, thus, the amount of loss.

The package size can be increased in some embodiments in order to have an embedded antenna array on a semiconductor. The die (e.g., RFIC) can be relatively small, but a physical package could be utilized that includes a PCB with wires running as necessary. The die can be positioned on a piece of silicon and/or bonded to a piece of aluminum. In one embodiment a piece of silicon can be used that has on the order of sixteen wires going to the edges, for example. The silicon could be soldered onto a piece of metal, for example, which then becomes the package. Alternatively, the silicon could have a metal ground plane initially. Since the silicon piece generally will be small, however, it can be desirable to place the silicon on a PCB or piece of metal, among other such substrates.

Many embodiments can utilize such a multilayered approach including several-to-many controllers. For example, in some embodiments an array of 1,000 elements may include a first layer of RF circuits that service 10 elements apiece (100 RF circuits). Ten of these RF circuits may feed to a second layer RF circuit (10 second layer RF circuits). These 10 second layer RF circuits then feeds to a final RF circuit. Such a "nested" RF circuit design may be able to provide better control over beamforming than current systems.

In many embodiments phasing is performed in analog, and groups of elements can be combined in analog before converting to digital. In some embodiments, all the elements are combined with an analog RF circuit and then one digital RF circuit. In other embodiments, a group of elements may be controlled using analog RF circuits, and then these groups may be combined using a smaller group of digital RF circuits. For example, every horizontal row of a number (e.g., 8) of elements could be combined in analog, and then the output of these eight rows combined in digital.

Beamforming can be performed on a very short time scale that can seem nearly instantaneous, whereas mechanical movement of a beam is comparatively very slow. Thus such an array may track a moving object (in relation to the mobile platform) much more tightly than mechanically dependent antennas. Further, the flat geometry of such an antenna, and the ability for the array to be static, can enable a nearly flush profile. On very fast moving objects, or those prone to elemental or human damage, this profile may prevent significant drag or damage of the array. Moreover, the lack of complex moving parts reduces maintenance and possible mechanical failures of the antenna compared to traditional antennas. Further, the cost of such an array can be significantly lower than those which rely upon mechanical hardware. In addition to advantages enumerated above, it should also be noted that an array of this sort can have very close

15

control of null spaces. This allows the array to “beamshape” by steering null spaces around the central beamform.

As discussed, the components of a receiver can be connected to an electronic device, embedded in an electronic device, or otherwise positioned in order to deliver power to the device. For example, in FIG. 10 the receiver 1010 is embedded in a device 1000, such that the device can receive power from the receiver which can be provided to a power source 1008 of the device without having to connect any external components to the device. The device can include a communication module 1012 as discussed which can receive information from a processor 1002 or I/O component 1006 of the device to send to a transmitter, in order to cause power to be transmitted to the device. Such an approach can be used to charge a battery of the device or power the device without need for a battery, among other such options.

In the configuration 1100 of FIG. 11, the receiver is part of a battery or battery back utilized by the device. In this way, the battery can receive power in order to charge itself without having to be removed from the device, and in at least some embodiments can be charged during operation of the device. In other embodiments, such a “battery” pack enables the device to be powered using the transmitted power, without having to include a battery or even a device for storing power for the device.

In the configuration 1200 of FIG. 12, the receiver 1212 and a communication element 1214 are contained in a component 1204 that is separate from the electronic device 1202. The component can be plugged into, or otherwise attached to, any of a number of different devices, such that a customer can use a single receiver with various devices. The component also can take a number of different forms, such as a case for the device 1202, a dongle, a USB device, a third-party accessory, etc. In this example the receiver is able to provide power to the device, and the communication module is able to obtain information to be conveyed to the transmitter in order to ensure that an appropriate amount of energy is sent at an appropriate time. Various other configurations and functionality can be used as discussed elsewhere herein.

As mentioned, the transmitter can focus at least one beam to an appropriate location and size associated with the antenna(s) of the receiver, which can then be rectified by the rectifier of the receiver. The ability to precisely form a beam of a desired size and power can depend at least in part upon the number of antenna elements in the transmitter and/or the receiver. Accordingly, approaches in accordance with various embodiments can utilize dozens, hundreds, or even thousands of antenna elements in order to provide desired beamforming capabilities and performance. Using analog elements instead of digital elements can provide significant cost savings, and can allow for the inclusion of additional elements in a transmitter without a substantial increase in cost to the customer. Further, analog elements work over a wide band, not a small portion of the overall spectrum, such that an analog transmitter can also offer greater flexibility than digital transmitters in at least some embodiments.

In the example configuration 1300 of FIG. 13, an antenna panel 1302, or housing, is displayed that is connected to a base station 1312. As illustrated in the example of FIG. 3, the components can alternatively be placed in a single housing or otherwise arranged within the scope of the various embodiments. In this example, a number of antenna elements 1304 are arranged within the panel, with each of the antenna elements being connected (not shown) by an appropriate wire, cable, line, or other such mechanism to analog

16

control circuitry, such as at least one RF integrated circuit (RFIC) 1306 including components operable to control aspects of the antenna elements 1304, as may include the gain and/or phase of those elements, in order to form and steer a beam as discussed above. The RFIC in this example is also placed within the panel 1302 in order to place the RFIC as close to the antenna elements as is practical, in order to minimize losses as discussed above. Other components of the transmitter then can be included in the base station 1312. In this example the base station includes the microcontroller 1314 for the antenna array, as well as the power components that are configured to receive power from an outlet and provide the necessary type of power to the microcontroller and other components. The base station in this example also includes a wireless communication element 1318 for communicating with one or more receivers or other such devices, although in at least some embodiments components such as the microcontroller and communication component(s) can be included in the transmitter panel 1302 as well. An advantage to having a panel 1302 separate from the base station 1312 is that components such as the power components might include a significant amount of weight, but elements such as the antenna elements and RFIC components are relatively light. Thus, separating the components can make it easier to hang the antenna panel on a wall or ceiling, for example. Further, the power components typically will need to be plugged into an electrical outlet in certain embodiments, so the separation enables the base station to be near the outlet and the panel placed where desired. In embodiments where the transmitter is hardwired into the location or building, for example, it might be more desirable to use a combined arrangement as illustrated in FIG. 3. Another advantage of the separation is that the customer can purchase a base station and separately purchase an antenna panel of the desired shape and/or capacity, such that the customer can pay for just what the customer wants and more options or combinations can be provided. Further, if the customer’s demands change, the customer can buy a new panel instead of a whole new transmitter, which can provide significant cost savings in at least some embodiments.

In this example the panel 1302 can be any appropriate shape and/or size, as may be determined based at least in part upon the number and configuration of antenna elements to be contained within the panel. The panel can be made of any appropriate material, such as a lightweight plastic, rubber, or polymer material. The panel housing also can come in different colors or shapes that might be customizable or selectable by a user. In some embodiments, skins or other mechanisms can be used to adjust the appearance of the panel as well. In some embodiments a customer might utilize the panel behind a wall surface, picture, ceiling panel, or other such object such that appearance or form might not be of concern, other than potentially including helpful mounting mechanisms or other such components. At least some panels might be designed to hang on the visible surface of a wall or ceiling, such that an aesthetically pleasing design and/or color might be desirable, or at least a design that is as visually unobtrusive as possible.

Similarly, the base station can be made of any appropriate material, which can be similar to, or different from, the material used for the panel. The base station may or may not include mounting hardware, depending at least in part upon whether the base station is part of the panel assembly or a separate component connected to the panel by power and communication cabling, or another such component. The base station can include any additional components as may

be appropriate, such as a cooling fan, power switch, LED element for providing operation and/or other notifications to a user, a display element for displaying an interface to a user, one or more input buttons or keys, a touch screen, or other such elements. In some embodiments the components of the base station might be built into another device as discussed elsewhere herein.

A transmitter can focus energy using all the antenna elements in the array in order to deliver the maximum amount of power capable of being provided to a receiver. In some embodiments, however, it might be desirable to only utilize a subset of the antenna elements. For example, a receiver might only be able to charge a device up to a certain rate or amount, a user might have specified a power limit, or another such factor might come into play. Increasing the number of antenna elements used can improve the ability to shape the beam, the amount of power able to be transferred via the beam, and other such aspects, but in some cases less than the total number of elements may be sufficient. Logic in the microcontroller or an attached device can determine how many elements to use for a given purpose at a given time.

In some embodiments, such logic can also determine when and how to charge devices when there are more than two devices or receivers that want to receive a charge. For example, FIG. 14A illustrates an example situation 1400 wherein there are two computing devices 1402 and 1414 within a transmission range of a transmitter 1406, or at least an antenna panel of a transmitter, in accordance with at least one embodiment. In this example, each device 1402, 1414 can communicate over a wireless channel (Bluetooth, Wi-Fi, acoustic, optical, etc.) with the transmitter 1406 in order to convey information about a current power level, power stage, charging need, or other such information. In at least some embodiments, each of the devices 1402, 1414 can have software installed that communicates with a power receiver, which can be built in or external that can determine information about one or more power states of the respective device and communicate that information to the transmitter. In some embodiments, the software can cause power level information to periodically be transmitted to the transmitter, such as via a periodic heartbeat or in response to periodic polling from the transmitter, among other such options, while in other embodiments a receiver may send a request or transmission only when charging of the device is determined to be appropriate. For example, each device might have a determined power level at which the device requests charging to ensure that the device does not run out of power, at least before a next charging opportunity. In other embodiments, a user might configure or set a level at which to obtain charging. In still other embodiments a device might be set to periodically request charging to make sure that the device (or a battery or other power component of the device) is at or near a full charge. Various other timing and charge determining approaches can be used as well within the scope of the various embodiments.

In FIG. 14A, one of the devices, here a notebook computer 1402, has indicated to the transmitter 1406 that the device is requesting to receive power. Accordingly, the transmitter 1406 can attempt to determine the location of the notebook computer 1402 in order to attempt to deliver power to the antenna array 1404 of the notebook. As discussed, the transmitter can attempt to determine the location to which to deliver power in a number of different ways. In one approach, the antenna elements of the notebook computer can be caused to “chirp” or otherwise emit a signal that can be detected by the antenna elements of the trans-

mitter, which can be analyzed by the components of the transmitter in order to adjust a gain or phase of at least some of the antenna elements in order to deliver power to that location, including an appropriate amount of beamforming and focus, etc. For example, a transmitter or receiver receiving a chirp can compare the signal to a local crystal, determine a difference in the local antenna elements, and adjust the phases accordingly. In other embodiments, the wireless or sideband channel can be used to send geo-location information, as may be determined using a GPS or other sensor of the notebook computer, among other such options. The information can be used to focus a beam 1410 to a focus region 1412 that is approximately the size of the antenna array 1404 of the notebook computer, in order to minimize losses due to portions of the beam that are not detected by the array. For at least some embodiments, the beam can be split and focused on different portions of the array, or even individual antenna elements, in order to further improve efficiency.

While power is being transmitted to the notebook computer 1402, the notebook computer can periodically send updates as to the current power state in at least some embodiments. Such an approach can not only help the transmitter to determine when to stop delivering power to the device, but can also help the transmitter to determine when and where to deliver power as will be discussed later herein. In some embodiments, a device might only send another signal to the transmitter when charging is complete, such that the transmitter knows to stop transmitting power to that device. Since such an approach might cause issues if the device is powered off or removed, in at least some embodiments a device must send a periodic message during charging in order to signal to the transmitter to continue sending a charge to the device. Various other approaches can be used as well within the scope of the various embodiments.

In FIG. 14A, however, there is also a tablet computer 1414 that also includes antenna elements of a power receiver, and is able to communicate with the transmitter to provide location and charging information, for example, in order to also obtain power as for the notebook computer 1402. The transmitter can determine the location and the need for charging, and can focus a beam on the antenna array of the tablet computer.

It might be the case, however, where at certain times both devices 1402, 1414 request power from the transmitter. A number of different approaches can be taken to provide power to both devices. In a first example, the needs of the devices are determined and ranked, such as to determine which device is more in need of power delivery, and then power is delivered to that device first, followed by the other device. In other embodiments, the transmitter 1406 can include logic to cause power to be delivered in an alternating fashion between the two devices. For example, the transmitter might determine equal periods of time to deliver power to each device. Since the antenna elements can adjust the beam very rapidly, the power can be delivered for a period of time to the first device, then for a period to the second device, then again for the first device, etc., until at least one of the devices is fully charged or otherwise no longer requires (or is able to obtain) charging. In some embodiments, the periods might be different for each device. For example, one device might be closer to losing power, or might be consuming more power, such that the transmitter can (if receiving such information from the devices) determine an appropriate ratio of charging periods to use for each device. As should be understood, such an approach can be used with more than two devices as well.

In some embodiments, the antenna array of the transmitter **1406** can also be configured to simultaneously deliver power to both devices using different subsets of the antenna array. For example, FIG. **14B** illustrates an example situation **1420** where a first subset **1422** of antenna elements of the transmitter is configured to deliver power to the notebook computer **1402** and a second subset **1424** is configured to form and send a beam **1426** that is focused on the antenna array **1428** of the tablet computer. Such an approach can enable both devices to be charged concurrently, which can be desirable in at least some situations, such as where an external receiver is connected to a device and the device has some delay or time constraints on charging, constantly notifies the user with changes in charge state, etc. Further, in at least some embodiments one or more devices might not include a battery or otherwise might operate using the power delivered from the transmitter, such that periodic charging may not be sufficient. Such approaches might be used to enable the devices to be very light, without need for a battery, as well as to provide for security, where a device must provide authentication to receive power and cannot work outside a designated area. Various other such situations exist as well.

In some embodiments, the ability to use different portions of the array for different purposes also can allow for other types of transmission as well, such as a power transmission using a first subset and a data transmission using a second subset.

The transmitter can utilize any of a number of types of information to determine whether to charge in an alternating or concurrent manner, or in a combination thereof wherein at least one device receives continuous power and other devices might alternatively receive power. Further, the transmitter can determine information such as the number of elements available, size of beam needed, amount of power needed, and other such information to determine how many and which elements to use to deliver power to each device. Different devices or receivers can have different numbers of antenna elements, such that the logic on the transmitter can determine how to fairly distribute power based on capacity or other such factors. Also as discussed, in some situations a device might need more power than another device, such that the transmitter can determine how to split up the power delivery in a proportion that is still as fair as possible to all receivers. Various other approaches and logic can be used as well.

The devices and transmitter can remain in communication such that power delivery can change as needed. For example, an amount of power consumption by one device might change, the user might plug a device into a wall socket, etc., such that the amount of power needed can change while charging. The transmitter can receive this information in at least some embodiments, and can determine how to adjust delivery. In some embodiments, the receivers (or devices attached to the receivers) can determine an amount of power delivery needed in response to a change, action, or event, and can communicate that information to the transmitter. Thus, the number of elements or approach used to power various devices can change at any time, even during charging.

As mentioned, the transmitter can include a number of antenna elements that can have different polarizations and arrangements in order to handle multiple different receiver orientations and/or locations. Such differences can also affect how many elements are used to deliver power to a given device, as certain polarizations or orientations may be more effective for certain device orientations or locations,

and in at least some embodiments the transmitter can be configured to optimize for efficiency to the extent possible while still providing sufficient power delivery.

It also should be stated that such delivery approaches can advantageously be used with other types of signals as well, such as for communications or other such purposes.

FIG. **15** illustrates an example transmitter panel **1500** that can be utilized in accordance with various embodiments. In this example the panel includes a large number of antenna elements **1504**, which could include over one-hundred elements in this example. It is possible that a single RFIC could be used with all these antenna elements. Such an RFIC can be relatively expensive, and as discussed it can be desirable to minimize the path length between antenna elements and the RFIC elements in order to minimize loss. Accordingly approaches in accordance with various embodiments utilize several smaller RFIC devices **1506** that are each connected to a subset of the antenna elements **1504** in the antenna panel housing **1502**. In this example each RFIC is able to connect to eight antenna elements, although any appropriate number of connections can be made in various embodiments. Small analog RFIC devices are relatively inexpensive, so such an approach can minimize losses by enabling the RFIC devices to be placed relatively close to the connected antenna elements, but also can substantially reduce costs over a larger, single RFIC device. In this example, at least one additional layer of RFIC devices **1508** can be used to connect or “cascade” the RFIC devices **1506** in order to combine the connections of the various antenna elements to a single output (or at least fewer outputs).

The ability to inexpensively add additional RFIC devices and antenna elements provides the scaling desired for various transmission applications, as the beamforming capability can scale with the number of phase shifters and amplifiers of the RFIC devices for the respective antenna elements. Although two layers are shown in the example, there can be any of a number of layers of RF chips or other such devices cascading to support the number of antenna elements, with the number of RF chips per layer and number of layers being a factor of the number of antenna elements and the number of connectors on each RF chip. In an embodiment where each chip can accept sixteen inputs, an assembly of seventeen RFIC chips can support up to two-hundred and fifty-six antenna elements. A similar approach can be performed where the transmitter is also configured to act as a receiver.

Although in many instances a transmitter will be a stand-alone component, as a single unit or as a base station and antenna panel, for example, in some embodiments one or more components of a computing or electronic device can be utilized with a transmitter as well. For example, the components of a transmitter can be connected to an electronic device, embedded in an electronic device, or otherwise positioned in order to deliver power to the device. For example, in FIG. **16** the transmitter **1610** is embedded in a device **1600**, such that the device can provide power obtained from a power source **1608** of the device without having to connect any external components to the device. The device can include a communication module **1612** as discussed which can receive information from a processor **1602** or I/O component **1606** of the device to send to a receiver, in order to cause power to be transmitted to the receiver. Such an approach can be used to charge a battery of the receiving device or power the device without need for a battery, among other such options.

In the configuration **1700** of FIG. **17**, the transmitter is part of a battery or battery back **1710** utilized by the device. In this way, the battery can transmit power to other devices

in order to charge those devices, such as may be useful in a gaming console or similar device that has controllers or other accessories that might require power.

In the configuration **1800** of FIG. **18**, the transmitter **1812** and a communication element **1814** are contained in a component **1804** that is separate from the electronic device **1802**. The component can be plugged into, or otherwise attached to, any of a number of different devices, such that a customer can use a single receiver with various devices. The component also can take a number of different forms, such as a case for the device **1802**, a dongle, a USB device, a third-party accessory, etc. In this example the receiver is able to obtain power from the device, and the communication module is able to obtain information to be conveyed to the receiver in order to ensure that an appropriate amount of energy is sent at an appropriate time. Various other configurations and functionality can be used as discussed elsewhere herein.

In the configuration **1900** of FIG. **19**, it is shown that additional antenna elements and/or assemblies **1914** can be added to such a device as well, using approaches discussed elsewhere herein.

In at least some instances, a user might want the ability to increase the amount of power that can be delivered, in order to more rapidly charge one or more devices. A user might also want the ability to power more devices concurrently. In many cases a user also, or alternatively, will want to improve the overall efficiency of power transmission using various transmitters discussed herein. As mentioned, these goals can be achieved in at least some embodiments by increasing the number of antenna elements used for the transmission(s). A user thus can purchase a new transmitter, or can purchase a new antenna panel as discussed with respect to FIG. **15**, that includes additional antenna elements.

Replacing an entire transmission system can be expensive, however, particularly where the user also has to replace the base station including the power components. Swapping in a different antenna panel can be less expensive, but still can result in unused panels and can increase the amount of waste produced if the user gets rid of the old panel. Further still, purchasing a larger antenna panel does not take advantage of the fact that the user already has a number of antenna elements in the user's possession.

Accordingly, approaches in accordance with various embodiments enable users to utilize additional antenna panels, arrays, assemblies, or other such configurations or components, in addition to those that the user might already utilize. For example, consider the situation **2000** of FIG. **20A**. In this example the user already has an antenna panel **2002** plugged into a base station **2012**, where the panel includes a number of antenna elements **2006** and control circuitry or components **2008**, as discussed elsewhere herein. If the user wants to increase the number of antenna elements in the transmission system, the user can plug another antenna panel **2004** into the base station **2012**. In this example both antenna panels include the same number of antenna elements **2006** (although different numbers, sizes, or configurations can be used within the scope of various embodiments) such that the number of antenna elements in the system is doubled, without any waste with respect to the original panel **2002**. Each panel can have a cable **2010** or other connector that is able to be received by a port or other connection mechanism of the base station **2012**. The number of panels that can be connected in this example might be limited only by the number of ports or connectors available on the base station. The base station can be configured such that the controller **2014** can detect the addition of another

panel **2004**, and can determine information such as the number and arrangement of elements, among other such information that might be stored by the panel or otherwise obtainable based at least in part upon some information or identifier provided by the panel or input into the base station, etc. The controller can enable the panels **2002**, **2004** to share the controller **2014** and power elements **2016**, as well as the wireless device **2018** or other mechanisms of the base station. It should be understood, however, that in some embodiments one or more of these components might also be contained in at least one of the panels, such that not every panel needs to share all functionality of each appropriate component in a given base station.

The controller **2014** in the base station can then choose to treat the panels separately or as part of a larger, single array of antenna elements **2006**. The controller also can select sub-sets of one or the other, or across both panels, to use to direct energy (or data, etc.) to various destinations. The increased number of antenna elements enables improved beamforming and focus versus for a single panel, such that efficiency can be improved. Further, the larger number of elements enables additional groups of those elements to be used to power more devices concurrently, or deliver more power to each device concurrently receiving power, etc.

In FIG. **20A** each panel **2002**, **2004** is connected by a cable **2010** or other connector directly to the base station **2012**. FIG. **20B** illustrates another example configuration **2020**, wherein only one of the panels **2004** is connected to the base station **2012**, and a second panel **2002** is directly connected to that panel **2004** by a cable **2022** or other appropriate connector. It should be understood that while direct connections are shown for purposes of explanation, it is possible that indirect connections can be made as well within the scope of the various embodiments.

An advantage to such an assembly is that the panels might be located in a position, such as on a wall or in a ceiling, that is at a significant distance from the base station, and requiring each panel to connect to the base station can involve running an additional connector to the base station, which can be impractical in at least some situations. Accordingly, approaches in accordance with at least some embodiments can enable the panels to connect to each other, such that the number of antenna elements can be increased without having to run another cable to the base station. In this example, each antenna panel assembly **2002**, **2004** includes a number of antenna elements (of similar or different number, size, shape, material, orientation, transmission capability, etc.) and appropriate RF or other such circuitry, with a single controller of the base station **2012** used to drive the antennas.

It is possible, however, that each panel (or at least one of the panels) might also include its own microcontroller, or other such control mechanism, that can work together with the controller of the base station **2004** and potentially any other controller of any other antenna panel. Further, each panel might be able to connect to a number of other panels, such as is illustrated in the example situation **2100** of FIG. **21**. In this example, each panel **2102** can connect on a side to another panel, with each panel being able to connect to up to four panels in order to effectively create a larger antenna panel assembly. It should be understood that other configurations and numbers of connections can be used as well, including stacking, connecting in shaped configurations, etc.

In this example, each panel includes its own microcontroller that can communicate with the controller of the base station, although in at least some embodiments a single controller in the base station might be used. Upon a panel

being connected to the assembly, the controller of the base station can obtain information about the panel, either by receiving information pushed by the microcontroller of the added panel, polling the panels for new information, or other such mechanisms. In some embodiments a user might use an interface to indicate to the base station and/or assembly that a panel has been added, where the panel was added, how many elements are included, etc. In some embodiments, the user (or system, etc.) might execute a software program that provides such information and/or programs the base station to control the additional panel. In other embodiments, configuration information might be stored in each panel that can be read by the base station, and the connection port(s) or mechanism(s) to which the panel is connected can be used to determine the relative location of the panel in the assembly. Various other approaches can be used as well.

In this example each panel can “snap” into, or otherwise connect with, an adjacent panel. Other approaches might connect using only data cables or other such mechanisms. In embodiments that do not include separate housings, additional elements or set of elements might be able to be added as desired, such as by plugging another set into a board or assembly, among other such options. Such an approach enables each panel to operate separately using the respective microcontroller, but also allows any set or grouping of the antenna elements of the connected panel assembly to be used for transmission to a particular destination. A controller of the base station can include logic (or can be in communication with a component having logic) that enables the base station to determine which of the connected antennas to use for a particular amount of power delivery, destination, etc., and can contact the individual microcontrollers where appropriate. Approaches for determining how to utilize the antenna arrays can be similar to the logic discussed above wherein the antenna elements are all part of a single assembly, among other such options.

In some embodiments, each panel includes a printed circuit board (PCB) with a number of antenna elements or patches positioned thereon, that are connected to an RF chip configured to control those patches. As discussed, each panel can include at least one microcontroller, or can communicate with a microcontroller in a base station or other such component. In some embodiments, a panel may include space to add circuit boards with additional elements within the same housing. Various other components such as LEDs, display elements, audio components, wireless communications components, or other such existing or conventional components can be used as well within the scope of the various embodiments. The base station can include power components and other components as discussed elsewhere herein, and can include, or enable attachment of, a power plug or other such component for obtaining power from a power outlet or other such source.

The number of antenna elements in each panel can vary, and may be selected based on any of a number of factors. For example, different numbers of elements may be selected for different panels of different sizes, in order to provide panels of different cost and power delivery capability, as well as to enable customers to select panels or other housings of antenna elements that will fit in various spaces. Further, in some embodiments depending upon geographic location and amount of power to be transmitted, there might be federal, local, or other applicable regulations regarding the amount of power transmitted, or other such aspects, although beamforming with multiple antennas allows the amount of power transmitted to be increased with respect to other potential approaches.

A small example panel for home or office use, for example, might include sixteen or thirty-two patches, and might be able to deliver about half a Watt over a range of about twenty feet. If the user wants to move the transmission system to a larger room, or wants more power to charge devices more quickly, the user can plug in an additional panel with more antenna elements. In some embodiments, the packaging for each panel can give guidance as to the amount of additional power each can provide. In some embodiments, a user might be able to run a software program where the user inputs various parameters, such as room size, number of devices to be charged, cost, and/or speed at which devices should be charged, and can receive a recommendation as to the number of antenna elements, number of panels, or size of additional panel(s) to be added to provide those values. For example, in some embodiments, adding a second panel with a similar number of antenna elements can double the amount of power that can be delivered and cut the charging time in half. Each additional model can reduce the charging time proportionally.

Each additional panel or other antenna assembly can obtain power from the base station (directly or indirectly through another antenna assembly), and can utilize control logic from the base station and/or other components. It is desired in at least some situations that when a user adds another panel, the transmission system does not require any additional configuration by the user and acts as if the larger number of antenna elements were included in the system as originally installed. As mentioned, each antenna assembly can have one or more RFIC's or other such circuits, which can be controlled by a local and/or remote controller or microcontroller. In at least some embodiments, the panels do not include power supplies or microcontrollers in order to reduce redundancy and decrease the cost of the system, among other such advantages.

As mentioned, in some situations there might be regulations limiting the amount of power that can be delivered in a particular geographic area. In some embodiments there can be a GPS element included in the base station to determine the location, which can then be used to determine the local regulations, such as by checking against a local storage or making a call to a network if the base station includes one or more networking components, such as WiFi, 4G, etc. In some embodiments where the base station is able to communicate with devices such as smart phones or tablet computers over a wireless connection, such as Bluetooth, the base station can request location information from the device, and can even leverage the network connection of the device, where permitted, to obtain local regulation information from across the relevant network(s). The controller of the base station then can ensure that power is not delivered in a way that violates local regulations, and can monitor usage of the system when the system has the capability to exceed those regulations to notify the user of any request or application that might violate the regulations. In some embodiments the base station can communicate with a user, such as by a display element on the station or a panel, by communicating with one of the nearby devices, by sending a text or instant message, etc., to indicate that adding additional panels might only enable more devices to be charged concurrently, as the maximum amount of power delivery to a single device has already been reached. Various other information and notifications can be provided as well within the scope of the various embodiments.

As mentioned, when a controller (or microcontroller) in the base station controls the antenna patches of each panel, the controller will need to be able to determine the presence,

number, and configuration of the additional elements, in order to be able to control those elements for purposes of beamforming, etc. While the RFIC or other such circuitry and/or components are doing the actual adjustments for the respective elements or patches in a panel, the microcontroller is providing the instructions to the RFIC, with some I/O requests or other such communications. In some embodiments, an 8-bit, I²C, MIPI, SPI, or other such bus might be used for communications. As mentioned, in some embodiments each panel might include its own microcontroller, which can receive instructions (wired or wirelessly) from the base station or another such component and determine how to instruct the local RFIC elements.

Each panel in at least some embodiments can have at least one “power in” and at least one “power out” port or connector to enable additional panels to receive power from the base station, in addition to communication ports or connections. Each panel only needs to receive power from one other panel, or the base station, so a single power in and single power out can be sufficient in at least some embodiments. In one embodiment, 5V AC can be fed across the panels such that there is no need to pay for another AC to DC conversion. In some embodiments, the same cable or connection can be used for communication and power delivery, such as a USB cable or other such connector, although the microcontrollers can communicate wirelessly using a protocol such as ZigBee or Bluetooth in at least some embodiments. In some embodiments each panel can have an identifier, and instructions emitted by the controller can include the identifier in a header portion, metadata, etc., such that even though some or all of the panels might receive the instructions, each local component (e.g., microcontroller and/or RFIC) can ignore the instructions including any other identifier. Certain panels can communicate with the microcontroller to be dynamically assigned an identifier that is different from the other panels, or a user might set one or more switches or other inputs to establish an identifier, or designate a panel as a “master” or a “slave,” among other such options. Further, the base station controller might receive configuration information from the user as to where each panel is attached, or might be able to determine from the order each panel is added, and the ports or connectors used to connect that panel, where the panel is in the system. Various other such approaches can be used as well within the scope of the various embodiments.

In some embodiments it might also be possible to scale the base station, such as by adding additional base stations or additional modules. Such an approach can enable new communications or control mechanisms, additional ports or power connections, or other such components to be added to a transmission system, without need to purchase a new (or larger overall) base station. In some embodiments such as commercial establishments where there might be a large number of panels in different locations, there might be multiple base stations used to provide power and instructions, but those base stations can communicate in order to coordinate the delivery of power from different panels that might be connected to different base stations. In some embodiments there might be a master base station that manages the overall delivery for the location, sending instructions and exchanging information with each other base station connected to the system. Various other reasons for adding base stations or station components can apply as well in various situations. Various other upgrade paths can be possible as well, as may be implemented through software upgrades, new cards or chips, etc.

While this invention has been described in terms of several embodiments, there are alterations, permutations, modifications and various substitute equivalents, which fall within the scope of this invention. It should also be noted that there are many alternative ways of implementing the methods and systems of the present invention. It is therefore intended that the following appended claims be interpreted as including all such alterations, permutations, modifications, and various substitute equivalents as fall within the true spirit and scope of the present invention.

What is claimed is:

1. A wireless-power receiver, comprising:
 - one or more processors configured to perform operations, including:
 - receiving, via one or more antenna elements of an antenna array, a plurality of first electromagnetic (EM) signals, wherein
 - each antenna element of the one or more antenna elements of the antenna array has a respective polarization;
 - in response to a change in an orientation of the wireless-power receiver, changing the respective polarization to a changed polarization for the one or more antenna elements of the antenna array; and
 - receiving, via the one or more antenna elements of the antenna array, and while the one or more antenna elements have the changed polarization, a plurality of second EM signals.
2. The wireless-power receiver of claim 1, wherein the plurality of second EM signals received at the wireless-power receiver are configured to be used to provide usable power to an electronic device, wherein:
 - a power transfer efficiency of the plurality second EM signals is configured to be greater than a power transfer efficiency of the plurality first EM signals.
3. The wireless-power receiver of claim 1, wherein the changed polarization of the one or more antenna elements of the antenna array is based on the orientation of the wireless-power receiver.
4. The wireless-power receiver of claim 1, wherein the changed orientation of the wireless-power receiver is an orientation of the wireless-power receiver relative to a wireless-power transmitter.
5. The wireless-power receiver of claim 4, wherein the wireless-power receiver further includes a communications component configured to communicate at least one of a location, an orientation, and charging information with the wireless-power transmitter.
6. The wireless-power receiver of claim 1, wherein the changed polarization of the one or more antenna elements of the antenna array is configured to be determined by the one or more processors such that a power transfer efficiency of the plurality of second EM signals is maximized.
7. The wireless-power receiver of claim 1, wherein:
 - the one or more processors are configured to perform further operations, including:
 - in response to a second change in the orientation of the wireless-power receiver, changing the respective polarization to a second changed polarization for the one or more antenna elements of the antenna array; and
 - receiving, via the one or more antenna elements of the antenna array, and while the one or more antenna elements have the second changed polarization, a plurality of third EM signals.

8. The wireless-power receiver of claim 1, wherein:
the one or more processors are configured to perform
further operations, including:
receiving, via one or more second antenna elements of
a second antenna array, a plurality of fourth EM
signals, wherein
each second antenna element of the one or more
second antenna elements of the second antenna
array has a respective second polarization;
in response to a change in the orientation of the
wireless-power receiver, changing the respective
second polarization to a second changed polarization
for the one or more second antenna elements of the
second antenna array; and
receiving, via the one or more second antenna elements
of the second antenna array, and while the one or
more second antenna elements have the second
changed polarization, a plurality of fifth EM signals.
9. The wireless-power receiver of claim 1, wherein the
changed polarization is at least one of a vertical pole,
horizontal pole, circular polarization, left-hand polarization,
right-hand polarization, and a combination of polarizations.
10. The wireless-power receiver of claim 1, wherein the
one or more antenna elements of the antenna array include
at least one of an omni-directional antenna, a directional
antenna, and a flat-panel antenna.
11. A system for wireless power transmission, compris-
ing:
a wireless-power receiver configured to:
receive, via one or more antenna elements of an
antenna array of the wireless-power receiver, a plu-
rality of first electromagnetic (EM) signals, wherein
each antenna element of the one or more antenna
elements of the antenna array has a respective
polarization; and
in response to a change in an orientation of the wire-
less-power receiver, change the respective polariza-
tion to a changed polarization for the one or more
antenna elements of the antenna array; and
a wireless-power transmitter configured to transmit, while
the one or more antenna elements have the changed
polarization, a plurality of second EM signals to the one
or more antenna elements of the antenna array.
12. The system for wireless power transmission of claim
11, wherein the plurality of second EM signals received at
the wireless-power receiver are configured to be used to
provide usable power to an electronic device, wherein:
a power transfer efficiency of the plurality second EM
signals is configured to be greater than a power transfer
efficiency of the plurality first EM signals.
13. The system for wireless power transmission of claim
11, wherein the changed polarization of the one or more
antenna elements of the antenna array is based on the
orientation of the wireless-power receiver.
14. The system for wireless power transmission of claim
11, wherein the changed orientation of the wireless-power
receiver is an orientation of the wireless-power receiver
relative to a wireless-power transmitter.
15. The system for wireless power transmission of claim
11, wherein the wireless-power receiver is further config-
ured to:
receiving, via one or more second antenna elements of a
second antenna array, a plurality of fourth EM signals,
wherein

- each second antenna element of the one or more second
antenna elements of the second antenna array has a
respective second polarization;
in response to a change in the orientation of the wireless-
power receiver, changing the respective second polar-
ization to a second changed polarization for the one or
more second antenna elements of the second antenna
array; and
receiving, via the one or more second antenna elements of
the second antenna array, and while the one or more
second antenna elements have the second changed
polarization, a plurality of fifth EM signals.
16. A non-transitory computer-readable storage medium,
storing one or more programs configured for execution by
one or more processors, the one or more programs including
instructions for:
receiving, via one or more antenna elements of an antenna
array of a wireless-power receiver, a plurality of first
electromagnetic (EM) signals, wherein
each antenna element of the one or more antenna
elements of the antenna array has a respective polar-
ization;
in response to a change in an orientation of the wireless-
power receiver, changing the respective polarization to
a changed polarization for the one or more antenna
elements of the antenna array; and
receiving, via the one or more antenna elements of the
antenna array, and while the one or more antenna
elements have the changed polarization, a plurality of
second EM signals.
17. The non-transitory computer-readable storage
medium of claim 16, wherein the plurality of second EM
signals received at the wireless-power receiver are config-
ured to be used to provide usable power to an electronic
device, wherein:
a power transfer efficiency of the plurality second EM
signals is configured to be greater than a power transfer
efficiency of the plurality first EM signals.
18. The non-transitory computer-readable storage
medium of claim 16, wherein the changed polarization of the
one or more antenna elements of the antenna array is based
on the orientation of the wireless-power receiver.
19. The non-transitory computer-readable storage
medium of claim 16, wherein the changed orientation of the
wireless-power receiver is an orientation of the wireless-
power receiver relative to a wireless-power transmitter.
20. The non-transitory computer-readable storage
medium of claim 16, wherein the one or more programs
further include instructions for:
receiving, via one or more second antenna elements of a
second antenna array, a plurality of fourth EM signals,
wherein
each second antenna element of the one or more second
antenna elements of the second antenna array has a
respective second polarization;
in response to a change in the orientation of the wireless-
power receiver, changing the respective second polar-
ization to a second changed polarization for the one or
more second antenna elements of the second antenna
array; and
receiving, via the one or more second antenna elements of
the second antenna array, and while the one or more
second antenna elements have the second changed
polarization, a plurality of fifth EM signals.