



US012067204B2

(12) **United States Patent**  
**Matsumoto**

(10) **Patent No.:** **US 12,067,204 B2**  
(45) **Date of Patent:** **Aug. 20, 2024**

(54) **DATA PROCESSING DEVICE**

(71) Applicant: **Semiconductor Energy Laboratory Co., Ltd., Atsugi (JP)**

(72) Inventor: **Hiroshi Matsumoto, Aiko (JP)**

(73) Assignee: **Semiconductor Energy Laboratory Co., Ltd., Atsugi (JP)**

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/229,228**

(22) Filed: **Aug. 2, 2023**

(65) **Prior Publication Data**

US 2023/0376155 A1 Nov. 23, 2023

**Related U.S. Application Data**

(63) Continuation of application No. 17/569,640, filed on Jan. 6, 2022, now Pat. No. 11,720,218, which is a (Continued)

(30) **Foreign Application Priority Data**

Jul. 2, 2013 (JP) ..... 2013-138895

(51) **Int. Cl.**  
**G06F 3/044** (2006.01)  
**G06F 1/16** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/0446** (2019.05); **G06F 1/1626** (2013.01); **G06F 1/1637** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC .... G06F 3/0446; G06F 3/0412; G06F 3/1431; G06F 3/1446; G06F 3/03; G06F 1/1626;  
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,788,292 B1 9/2004 Nako et al.  
6,972,752 B2 12/2005 Nako et al.  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 001334690 A 2/2002  
CN 101120295 A 2/2008  
(Continued)

OTHER PUBLICATIONS

International Search Report (Application No. PCT/JP2014/066751)  
Dated Sep. 16, 2014.

(Continued)


*Primary Examiner* — Brent D Castiaux

(74) *Attorney, Agent, or Firm* — Eric J. Robinson;  
Robinson Intellectual Property Law Office, P.C.

(57) **ABSTRACT**

To provide a highly browsable data processing device or a highly portable data processing device, a data processing device including the following is devised: an input/output unit provided with a display portion which can be folded and unfolded and a sensor portion that can sense the folded and unfolded states of the display portion and can supply data on fold, and an arithmetic unit that stores a program for executing different processing depending on the data on fold.

**6 Claims, 10 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 16/572,908, filed on Sep. 17, 2019, now Pat. No. 11,221,720, which is a continuation of application No. 15/695,195, filed on Sep. 5, 2017, now Pat. No. 10,452,104, which is a continuation of application No. 14/311,842, filed on Jun. 23, 2014, now Pat. No. 9,753,495.

- (51) **Int. Cl.**  
*G06F 3/041* (2006.01)  
*G06F 3/14* (2006.01)
- (52) **U.S. Cl.**  
 CPC ..... *G06F 1/1641* (2013.01); *G06F 1/1643* (2013.01); *G06F 1/1677* (2013.01); *G06F 3/0412* (2013.01); *G06F 3/1431* (2013.01); *G06F 3/1446* (2013.01); *G09G 2300/0426* (2013.01); *G09G 2330/04* (2013.01); *G09G 2340/0442* (2013.01); *G09G 2354/00* (2013.01); *G09G 2380/02* (2013.01)
- (58) **Field of Classification Search**  
 CPC .... *G06F 1/1637*; *G06F 1/1641*; *G06F 1/1643*; *G06F 1/1677*; *G09G 2300/0426*; *G09G 2330/04*; *G09G 2340/0442*; *G09G 2354/00*; *G09G 2380/02*; *Y02E 10/549*  
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,433,179	B2	10/2008	Hisano et al.
7,714,801	B2	5/2010	Kimmel
7,787,917	B2	8/2010	Aoki et al.
7,816,863	B2	10/2010	Yamazaki et al.
8,170,631	B2	5/2012	Aoki et al.
8,283,862	B2	10/2012	Yamazaki et al.
8,319,725	B2	11/2012	Okamoto et al.
8,369,075	B2	2/2013	Huang
8,504,936	B2	8/2013	Gimpl et al.
8,543,166	B2	9/2013	Choi et al.
8,547,197	B2	10/2013	Byun et al.
8,803,816	B2	8/2014	Kilpatrick, II et al.
8,825,121	B2	9/2014	Aoki et al.
8,836,611	B2	9/2014	Kilpatrick, II et al.
8,860,632	B2	10/2014	Kilpatrick, II et al.
8,860,765	B2	10/2014	Kilpatrick, II et al.
8,863,038	B2	10/2014	King et al.
8,866,840	B2	10/2014	Dahl et al.
8,872,731	B2	10/2014	Gimpl et al.
8,873,225	B2	10/2014	Huitema et al.
8,899,791	B2	12/2014	Liu
8,911,653	B2	12/2014	Yamazaki et al.
8,933,874	B2	1/2015	Lundqvist et al.
8,947,320	B2	2/2015	King et al.
9,000,442	B2	4/2015	Hatano et al.
9,009,984	B2	4/2015	Caskey et al.
9,235,238	B2	1/2016	Ishizuka
10,804,489	B2	10/2020	Yamazaki et al.
10,910,597	B2	2/2021	Yamazaki et al.
11,005,071	B2	5/2021	Yamazaki et al.
2002/0005818	A1	1/2002	Bruzzone
2006/0034042	A1	2/2006	Hisano et al.
2007/0085845	A1	4/2007	Kikuchi et al.
2007/0097014	A1	5/2007	Solomon et al.
2007/0226384	A1	9/2007	Robbin et al.
2010/0056223	A1	3/2010	Choi et al.
2010/0060664	A1	3/2010	Kilpatrick, II et al.
2010/0064244	A1	3/2010	Kilpatrick, II et al.
2010/0064536	A1	3/2010	Caskey et al.
2010/0066643	A1	3/2010	King et al.
2010/0079355	A1	4/2010	Kilpatrick, II et al.
2010/0085274	A1	4/2010	Kilpatrick, II et al.
2010/0085382	A1	4/2010	Lundqvist et al.

2010/0121741	A1	5/2010	Hotelling et al.
2010/0131567	A1	5/2010	Dorogusker et al.
2010/0169509	A1	7/2010	Marriott
2011/0069094	A1*	3/2011	Knapp ..... G09G 3/3426 345/82
2011/0111798	A1	5/2011	Jeon et al.
2011/0126141	A1	5/2011	King et al.
2011/0216064	A1*	9/2011	Dahl ..... H04M 1/0247 345/428
2012/0033354	A1	2/2012	Huang
2012/0084791	A1	4/2012	Benedek et al.
2012/0162049	A1	6/2012	Aoki et al.
2012/0206386	A1	8/2012	Xu et al.
2012/0217516	A1	8/2012	Hatano et al.
2012/0235894	A1	9/2012	Phillips
2012/0259876	A1	10/2012	Mathai et al.
2012/0262367	A1	10/2012	Chiu et al.
2012/0276958	A1*	11/2012	Inami ..... H04M 1/0241 455/566
2012/0306910	A1	12/2012	Kim et al.
2012/0307423	A1	12/2012	Bohn et al.
2012/0329528	A1	12/2012	Song
2013/0009909	A1	1/2013	Yamazaki et al.
2013/0010405	A1	1/2013	Rothkopf et al.
2013/0019183	A1	1/2013	Reeves et al.
2013/0080143	A1	3/2013	Reeves et al.
2013/0080909	A1	3/2013	Reeves et al.
2013/0080940	A1	3/2013	Reeves et al.
2013/0154298	A1	6/2013	Ricci
2013/0167159	A1	6/2013	Ricci et al.
2013/0173035	A1	7/2013	Fadell et al.
2013/0208417	A1	8/2013	Sirpal
2014/0164240	A1	6/2014	Gautier et al.
2014/0227963	A1	8/2014	Ng et al.
2014/0361980	A1	12/2014	Iwaki et al.
2014/0380203	A1	12/2014	Freedman
2015/0006035	A1	1/2015	Ricci
2015/0012821	A1	1/2015	Mirrashidi et al.
2015/0015613	A1	1/2015	Iwaki
2015/0016126	A1	1/2015	Hirakata. et al.
2015/0022515	A1	1/2015	Ikeda et al.
2015/0022561	A1	1/2015	Ikeda et al.
2015/0046858	A1	2/2015	Gimpl et al.
2015/0058611	A1	2/2015	Reeves et al.
2015/0169617	A1	6/2015	Fadell
2015/0234482	A1	8/2015	Jobs et al.
2015/0234544	A1	8/2015	Sirpal et al.
2015/0242070	A1	8/2015	Sirpal et al.
2015/0254805	A1	9/2015	Sirpal et al.
2015/0262152	A1	9/2015	Muller et al.
2015/0268851	A1	9/2015	Sirpal
2016/0034175	A1	2/2016	Cassar et al.
2016/0034176	A1	2/2016	Sirpal
2016/0041696	A1	2/2016	Sirpal et al.
2016/0041697	A1	2/2016	Sirpal et al.
2016/0041704	A1	2/2016	Reeves et al.
2016/0041715	A1	2/2016	Sirpal et al.
2016/0041756	A1	2/2016	Sirpal et al.
2016/0041757	A1	2/2016	Sirpal et al.
2016/0044152	A1	2/2016	Sirpal et al.
2016/0048165	A1	2/2016	Becze
2016/0048299	A1	2/2016	Sirpal et al.
2016/0048301	A1	2/2016	Sirpal et al.
2016/0054757	A1	2/2016	Reeves et al.
2016/0054862	A1	2/2016	Reeves et al.
2016/0054880	A1	2/2016	Sirpal et al.
2016/0054902	A1	2/2016	Sirpal et al.
2016/0054970	A1	2/2016	Reeves et al.
2016/0062554	A1	3/2016	Sirpal et al.
2016/0062583	A1	3/2016	Ricci
2016/0062593	A1	3/2016	Schrock
2016/0062631	A1	3/2016	Webber
2016/0070456	A1	3/2016	Ricci et al.
2016/0070527	A1	3/2016	Ricci
2016/0082839	A1	3/2016	Ricci
2016/0085384	A1	3/2016	Selim
2016/0085406	A1	3/2016	Sirpal et al.
2016/0086391	A1	3/2016	Ricci
2016/0098064	A1	4/2016	Becze et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0098121 A1 4/2016 Sirpal et al.  
 2016/0098417 A1 4/2016 Reeves  
 2016/0103597 A1 4/2016 Gimpl et al.  
 2016/0103603 A1 4/2016 Sirpal et al.  
 2016/0110049 A1 4/2016 Cassar et al.  
 2016/0110150 A1 4/2016 Sirpal et al.  
 2016/0114745 A1 4/2016 Ricci  
 2016/0127887 A1 5/2016 Ricci  
 2016/0140776 A1 5/2016 Ricci  
 2016/0149995 A1 5/2016 Heller et al.  
 2016/0163133 A1 6/2016 Ricci  
 2016/0170633 A1 6/2016 Sirpal et al.  
 2016/0179208 A1 6/2016 Reeves et al.  
 2016/0179350 A1 6/2016 Reeves et al.  
 2016/0179367 A1 6/2016 Gimpl et al.  
 2016/0185222 A1 6/2016 Ricci et al.  
 2016/0188190 A1 6/2016 Ricci et al.  
 2016/0188204 A1 6/2016 Sirpal et al.  
 2016/0189544 A1 6/2016 Ricci  
 2016/0196007 A1 7/2016 Reeves et al.  
 2016/0196059 A1 7/2016 Sirpal et al.  
 2016/0205419 A1 7/2016 Ricci et al.  
 2016/0255408 A1 9/2016 Ricci  
 2016/0255575 A1 9/2016 Ricci  
 2016/0266759 A1 9/2016 Reeves  
 2016/0274783 A1 9/2016 Schrock et al.  
 2016/0291920 A1 10/2016 Sirpal et al.  
 2016/0306615 A1 10/2016 Ricci  
 2016/0306766 A1 10/2016 Ricci  
 2016/0313730 A1 10/2016 Ricci et al.  
 2016/0313964 A1 10/2016 De Paz et al.  
 2016/0320921 A1 11/2016 Sirpal  
 2017/0038934 A1 2/2017 Sirpal et al.  
 2017/0039019 A1 2/2017 De Paz  
 2017/0052634 A1 2/2017 Reeves  
 2017/0066406 A1 3/2017 Ricci  
 2017/0067747 A1 3/2017 Ricci  
 2017/0068404 A1 3/2017 Jobs et al.  
 2017/0068438 A1 3/2017 Ricci  
 2017/0075701 A1 3/2017 Ricci et al.  
 2017/0078223 A1 3/2017 Ricci et al.  
 2017/0078472 A1 3/2017 Ricci  
 2017/0082447 A1 3/2017 Ricci  
 2017/0093643 A1 3/2017 Ricci et al.  
 2017/0097243 A1 4/2017 Ricci  
 2017/0099295 A1 4/2017 Ricci  
 2017/0108935 A1 4/2017 Ricci  
 2017/0131712 A1 5/2017 Ricci et al.  
 2017/0132917 A1 5/2017 Ricci  
 2017/0228208 A1 8/2017 Sirpal et al.  
 2017/0232888 A1 8/2017 Ricci  
 2017/0247000 A1 8/2017 Ricci  
 2017/0249095 A1 8/2017 Ricci  
 2017/0249474 A1 8/2017 Ricci et al.  
 2017/0357797 A1 12/2017 Rubinstein et al.  
 2018/0052854 A1 2/2018 Cue et al.  
 2018/0060012 A1 3/2018 Jouin  
 2018/0074776 A1 3/2018 Sirpal et al.  
 2019/0115564 A1 4/2019 Yamazaki et al.  
 2022/0181584 A1 6/2022 Yamazaki et al.

FOREIGN PATENT DOCUMENTS

CN 102150095 A 8/2011  
 CN 102150097 A 8/2011  
 CN 102150126 A 8/2011  
 CN 202058412 U 11/2011  
 CN 102541177 A 7/2012  
 CN 102723058 A 10/2012  
 CN 102857592 A 1/2013  
 CN 102999309 A 3/2013  
 CN 103050064 A 4/2013

CN 103149979 A 6/2013  
 EP 1058181 A 12/2000  
 EP 2456175 A 5/2012  
 EP 2500898 A 9/2012  
 EP 2521002 A 11/2012  
 EP 2521003 A 11/2012  
 EP 2530941 A 12/2012  
 EP 2565751 A 3/2013  
 EP 2755459 A 7/2014  
 EP 3057385 A 8/2016  
 EP 3190476 A 7/2017  
 EP 3537274 A 9/2019  
 JP 11-272656 A 10/1999  
 JP 2005-108825 A 4/2005  
 JP 2005-115536 A 4/2005  
 JP 2006-053678 A 2/2006  
 JP 2006-243621 A 9/2006  
 JP 2006-287982 A 10/2006  
 JP 2008-294490 A 12/2008  
 JP 2009-105817 A 5/2009  
 JP 2009-164760 A 7/2009  
 JP 2010-021740 A 1/2010  
 JP 2010-140410 A 6/2010  
 JP 2011-003537 A 1/2011  
 JP 2011-518391 6/2011  
 JP 2011-209899 A 10/2011  
 JP 2012-502321 1/2012  
 JP 2012-502368 1/2012  
 JP 2012-502372 1/2012  
 JP 2012-190794 A 10/2012  
 JP 2012-198541 A 10/2012  
 JP 2012-231330 A 11/2012  
 JP 2013-025617 A 2/2013  
 JP 2013-105312 A 5/2013  
 KR 2011-0053269 A 5/2011  
 KR 2011-0055718 A 5/2011  
 KR 2011-0066165 A 6/2011  
 KR 2011-0085904 A 7/2011  
 KR 2012-0122227 A 11/2012  
 KR 2013-0006295 A 1/2013  
 TW 201024977 7/2010  
 TW M395340 12/2010  
 TW M430653 6/2012  
 WO WO-2006/072670 7/2006  
 WO WO-2008/083361 7/2008  
 WO WO-2009/131447 10/2009  
 WO WO-2010/028394 3/2010  
 WO WO-2010/028397 3/2010  
 WO WO-2010/028399 3/2010  
 WO WO-2010/028402 3/2010  
 WO WO-2010/028403 3/2010  
 WO WO-2010/028404 3/2010  
 WO WO-2010/028405 3/2010  
 WO WO-2010/028406 3/2010  
 WO WO-2010/028407 3/2010  
 WO WO-2012/044747 4/2012  
 WO WO-2014/175455 10/2014

OTHER PUBLICATIONS

Written Opinion (Application No. PCT/JP2014/066751) Dated Sep. 16, 2014.  
 Chinese Office Action (Application No. 201480037540.5) Dated Mar. 20, 2018.  
 Taiwanese Office Action (Application No. 103121720) Dated Mar. 27, 2018.  
 Chinese Office Action (Application No. 201910041998.2) Dated Nov. 17, 2021.  
 Chinese Office Action (Application No. 201910041998.2) Dated Jul. 22, 2022.  
 Chinese Office Action (Application No. 202210133259.8) Dated Apr. 3, 2024.

\* cited by examiner

FIG. 1A




FIG. 1B1




FIG. 1B2




FIG. 1C1




FIG. 1C2




FIG. 2A




FIG. 2B




FIG. 3A1




FIG. 3A2




FIG. 3B1




FIG. 3B2




FIG. 3C1




FIG. 3C2




FIG. 3D1




FIG. 3D2




FIG. 3E1




FIG. 3E2




FIG. 3F1




FIG. 3F2




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A1




FIG. 7A2




FIG. 7B1




FIG. 7B2




FIG. 7C1




FIG. 7C2




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B





FIG. 10



## 1

## DATA PROCESSING DEVICE

## TECHNICAL FIELD

The present invention relates to an object, a method, or a manufacturing method. In addition, the present invention relates to a process, a machine, manufacture, or a composition of matter. In particular, the present invention relates to, for example, a human interface, a semiconductor device, a display device, a light-emitting device, a power storage device, a driving method thereof, or a manufacturing method thereof. In particular, the present invention relates to, for example, a method and a program for processing and displaying image data, and a device including a recording medium in which the program is recorded. In particular, the present invention relates to, for example, a method for processing and displaying image data by which an image including data processed by a data processing device provided with a display portion is displayed, a program for displaying an image including data processed by a data processing device provided with a display portion, and a data processing device including a recording medium in which the program is recorded.

## BACKGROUND ART

The social infrastructures relating to means for transmitting information have advanced. This has made it possible to acquire, process, and send out many pieces and a variety of information with the use of a data processing device not only at home or office but also at other visiting places.

With this being the situation, portable data processing devices are under active development.

For example, portable data processing devices are often used outdoors, and force might be accidentally applied by dropping to the data processing devices and display devices included in them. As an example of a display device that is not easily broken, a display device having high adhesiveness between a structure body by which a light-emitting layer is divided and a second electrode layer is known (Patent Document 1).

A multi-panel electronic device including the following functions is known. First acceleration data is received from a first sensor coupled to a first portion of an electronic device. In addition, second acceleration data is further received from a second sensor coupled to a second portion of the electronic device, and a position of the first portion is movable with respect to a position of the second portion. Moreover, a structure of the electronic device is further determined at least on the basis of part of the first acceleration data and part of the second acceleration data (Patent Document 2).

## REFERENCE

## Patent Document

[Patent Document 1] Japanese Published Patent Application No. 2012-190794

[Patent Document 2] Japanese Published Patent Application No. 2012-502372

## DISCLOSURE OF INVENTION

Display devices with large screens on which much information can be displayed are excellent in browsability. Therefore, such display devices are suitable for data processing device.

## 2

On the other hand, the display devices with large screens deteriorate in portability compared to display devices with small screens.

One embodiment of the present invention is made in view of the foregoing technical background. Therefore, one object is to provide a highly browsable data processing device. Alternatively, another object is to provide a highly portable data processing device.

Note that the descriptions of these objects do not disturb the existence of other objects. In one embodiment of the present invention, there is no need to achieve all the objects. Other objects will be apparent from and can be derived from the description of the specification, the drawings, the claims, and the like.

One embodiment of the present invention is a data processing device including an input/output unit which supplies data on whether the data processing device is fold (data on fold) and to which image data is supplied and an arithmetic unit to which the data on fold is supplied and which supplies the image data. The input/output unit includes a display portion which can be folded in two or more different states or unfolded and a sensor portion that can sense the state of the display portion and supply the data on fold. The arithmetic unit includes an arithmetic portion and a memory portion that stores a program for making the arithmetic portion execute processing. The program makes the arithmetic portion execute different processing depending on the data on fold.

The program that the data processing device of one embodiment of the present invention stores includes a first step of specifying a folded state on the basis of the data on fold; a second step of loading an application for processing allocated to the folded state; a third step of allowing interrupt processing; a fourth step of executing the interrupt processing and processing predetermined data; a fifth step of proceeding to a sixth step in the case where a termination instruction is supplied, whereas proceeding to the first step in the case where the termination instruction is not supplied; and the sixth step of terminating the program. The interrupt processing includes a seventh step of specifying the folded state on the basis of the data on fold; an eighth step of proceeding to a ninth step in the case where the folded state is changed, whereas proceeding to a tenth step in the case where the folded state is not changed; the ninth step of terminating the application; and the tenth step of recovering from the interrupt processing.

The data processing device of one embodiment of the present invention includes an input/output unit provided with a display portion which can be folded and unfolded and a sensor portion that can sense the folded and unfolded states of the display portion and can supply data on fold; and an arithmetic unit that stores a program for executing different processing depending on the data on fold. Accordingly, a highly browsable data processing device can be provided. Alternatively, a highly portable data processing device can be provided.

Another embodiment of the present invention is a data processing device including a connection housing provided with a first plane and a second plane opposite to the first plane; a sensor portion that discerns a first sign and a second sign which can approach the first plane of the connection housing, and a third sign and a fourth sign which can approach the second plane of the connection housing; a first housing connected to the connection housing so as to be movable from a position at which a first plane of the first housing faces the first plane of the connection housing to a position at which a second plane of the first housing opposite

to the first plane thereof faces the second plane of the connection housing; and a second housing connected to the connection housing so as to be movable from a position at which a first plane of the second housing faces the first plane of the connection housing to a position at which a second plane of the second housing opposite to the first plane thereof faces the second plane of the connection housing. The connection housing, the first housing, and the second housing support a display portion having flexibility so that the display portion can be folded. The first housing is provided with the first sign on the first plane and the third sign on the second plane, and the second housing is provided with the second sign on the first plane and the fourth sign on the second plane.

In the data processing device of the another embodiment of the present invention, the second housing is provided with a fifth sign on the first plane and a sixth sign on the second plane, and the sensor portion discerns the sixth sign that approaches the first plane of the first housing and the fifth sign that approaches the second plane of the first housing.

The data processing device of the another embodiment of the present invention includes the display portion which can be folded and unfolded and the sensor portion that can sense the folded and unfolded states of the display portion and can supply data on fold. Accordingly, a highly browsable data processing device can be provided. Alternatively, a highly portable data processing device can be provided.

According to one embodiment of the present invention, a highly browsable data processing device can be provided. Alternatively, a highly portable data processing device can be provided.

#### BRIEF DESCRIPTION OF DRAWINGS

FIGS. 1A, 1B1, 1B2, 1C1, and 1C2 are a block diagram and schematic views illustrating a structure of a data processing device of one embodiment.

FIGS. 2A and 2B are flow charts showing a program to be executed by an arithmetic portion of the data processing device of one embodiment of the present invention.

FIGS. 3A1, 3A2, 3B1, 3B2, 3C1, 3C2, 3D1, 3D2, 3E1, 3E2, 3F1, and 3F2 are schematic views illustrating two or more different states of a folded display portion of a data processing device of one embodiment.

FIGS. 4A and 4B illustrate an unfolded data processing device of one embodiment.

FIGS. 5A to 5D illustrate a double-fold data processing device of one embodiment.

FIGS. 6A to 6D illustrate a double-fold data processing device of one embodiment.

FIGS. 7A1, 7A2, 7B1, 7B2, 7C1, and 7C2 illustrate a tri-fold data processing device of one embodiment.

FIGS. 8A to 8C illustrate a structure of an input/output unit that can be applied to a data processing device of one embodiment.

FIGS. 9A and 9B illustrate a structure of an input/output unit that can be applied to a data processing device of one embodiment.

FIG. 10 illustrates a structure of an input/output unit that can be applied to a data processing device of one embodiment.

#### BEST MODE FOR CARRYING OUT THE INVENTION

Embodiments described below include one embodiment of the present invention which has been made focusing on an

input/output unit provided with a display portion which can be folded in two or more different states and a sensor portion that senses the folded states of the display portion.

A data processing device of one embodiment of the present invention includes an input/output unit provided with a display portion which can be folded and unfolded and a sensor portion that can sense the folded and unfolded states of the display portion and can supply data on fold; and an arithmetic unit that stores a program for executing different processing depending on the data on fold.

According to the data processing device of one embodiment of the present invention, the arithmetic unit can execute different processing depending on the folded state of the data processing device. Accordingly, highly browsable data processing device can be provided. Alternatively, highly portable data processing device can be provided.

Embodiments will be described in detail with reference to drawings. Note that the present invention is not limited to the description below, and it is easily understood by those skilled in the art that various changes and modifications can be made without departing from the spirit and scope of the present invention. Accordingly, the present invention should not be interpreted as being limited to the content of the embodiments below. Note that in the structures of the invention described below, the same portions or portions having similar functions are denoted by the same reference numerals in different drawings, and description of such portions is not repeated.

#### Embodiment 1

In this embodiment, a structure of a data processing device of one embodiment of the present invention will be described with reference to FIGS. 1A, 1B1, 1B2, 1C1, and 1C2 and FIGS. 2A and 2B.

FIG. 1A shows a block diagram of a structure of a data processing device 100 of one embodiment of the present invention.

FIGS. 1B1 and 1B2 are schematic views illustrating a structure of the data processing device 100 of one embodiment of the present invention.

FIGS. 1C1 and 1C2 are schematic views illustrating operation of folding the data processing device 100 of one embodiment of the present invention.

FIGS. 2A and 2B are flow charts showing a program to be executed by an arithmetic portion of the data processing device 100 of one embodiment of the present invention. FIG. 2A is a flow chart illustrating main processing, and FIG. 2B is a flow chart illustrating interrupt processing.

The data processing device 100 described in this embodiment includes an input/output unit 120 which supplies data SENS on fold and to which image data VIDEO is supplied and an arithmetic unit 110 to which the data SENS on fold is supplied and supplies the image data VIDEO (see FIG. 1A).

The input/output unit 120 includes a display portion 122 which can be folded in two or more different states or unfolded and a sensor portion 123 that can sense the state of the display portion 122 and supply the data SENS on fold.

The arithmetic unit 110 includes an arithmetic portion 111 and a memory portion 112 that stores a program for making the arithmetic portion 111 execute processing, and the program makes the arithmetic portion 111 execute different processing depending on the data SENS on fold.

The data processing device 100 described in this embodiment includes the input/output unit 120 provided with the display portion 122 which can be folded and unfolded and

the sensor portion **123** that can sense the folded and unfolded states of the display portion **122** and can supply the data SENS on fold; and the arithmetic unit **110** that stores a program for executing different processing depending on the data SENS on fold. Accordingly, the display portion **122** can be unfolded and used. As a result, highly browsable data processing device can be provided. Alternatively, the display portion **122** can be folded. Thus, highly portable data processing device can be provided.

The arithmetic unit **110** described as an example in this embodiment includes an input/output interface **115** and a transmission path **114** (see FIG. 1A).

The input/output interface **115** can supply data to the input/output unit **120** and receive data supplied from the input/output unit **120**.

The transmission path **114** can supply data to the arithmetic portion **111**, the memory portion **112**, and the input/output interface **115**. In addition, the arithmetic portion **111**, the memory portion **112**, and the input/output interface **115** can supply data to the transmission path **114**.

The input/output unit **120** includes an input means **121**, a sign **129**, a communication portion **125**, and the like.

The input means **121** can supply an operation instruction INPUT including a termination instruction or the like. Note that the termination instruction is an instruction to terminate the program.

The sign **129** is placed near the display portion **122** and sensed by the sensor portion **123**. Accordingly, the folded state of the display portion can be sensed.

Note that these portions cannot be clearly distinguished and one portion also serves as another portion or include part of another portion in some cases. For example, a touch panel in which a display portion overlaps with a touch sensor serves as the input means **121** as well as the display portion **122**.

The data processing device **100** described as an example in this embodiment includes the memory portion **112** that stores the program including the following steps (see FIGS. 2A and 2B).

<<Program>>

In a first step, the folded state of the display portion **122** is specified by the data SENS on fold (see FIG. 2A (S1)).

A method of specifying the folded state of display portion **122** by the data SENS on fold will be described in detail in Embodiment 2.

In a second step, an application for processing allocated to the folded state is loaded (see FIG. 2A (S2)).

Note that as the application for processing allocated to the folded state, applications for viewing an electronic book, reproducing music, broadcasting, or viewing a moving image and for a game, a camera, or the like with the data processing device can be given.

In a third step, interrupt processing is allowed (see FIG. 2A (S3)).

In a fourth step, the interrupt processing is executed and predetermined data is processed (see FIG. 2A (S4)).

Note that as the data processing in the fourth step, processing for outputting the data in the memory portion **112** to the input/output unit **120** can be given. Specifically, the following processing can be given as examples: processing for enlarging image data which is compressed and stored in the memory portion **112** and displaying the image data on the display portion **122**; processing for enlarging compressed and stored audio data and outputting the data to a speaker or the like; and processing for adjusting and displaying text data on the basis of layout data.

In the case where a termination instruction is supplied in a fifth step, the fifth step proceeds to a sixth step, whereas in the case where the termination instruction is not supplied, the fifth step proceeds to the first step (see FIG. 2A (S5)).

In the sixth step, the program is terminated (see FIG. 2A (S6)).

Next, the interrupt processing is described (see FIG. 2B). Note that when the interrupt processing is allowed, the arithmetic portion can receive an instruction to execute the interrupt processing. The arithmetic portion that has received the instruction to execute the interrupt processing stops the main processing and executes the interrupt processing. For example, the arithmetic portion that has received an event associated with the instruction executes the interrupt processing and stores the execution result in the memory portion. Then, the arithmetic portion that has recovered from the interrupt processing can resume the main processing on the basis of the execution result of the interrupt processing.

In a seventh step, the folded state is specified by the data SENS on fold by the interrupt processing (see FIG. 2B (T7)).

In the case where the folded state is changed in an eighth step, the eighth step proceeds to a ninth step, whereas in the case where the folded state is not changed, the eighth step proceeds to a tenth step (see FIG. 2B (T8)).

Note that the change of the folded state can be judged by comparing the folded state with that specified in the first step.

In the ninth step, the application is terminated (see FIG. 2B (T9)).

In the tenth step, the arithmetic portion is recovered from the interrupt processing (see FIG. 2B (T10)).

The following describes individual components included in the data processing device **100** of one embodiment of the present invention.

<<Input/Output Unit>>

The input/output unit **120** is connected to the transmission path **114** through the input/output interface **115**. The input/output unit **120** can supply external data to the data processing device **100**. Moreover, internal data of the data processing device **100** can be supplied to the outside.

<<Sensor Portion and Sign>>

The sensor portion **123** senses at least the folded state of the display portion **122** and supplies the data SENS on fold.

The sensor portion **123** is provided with a sensor for sensing the sign **129** placed near the display portion **122**. Accordingly, the sensor portion **123** can supply a fold signal in accordance with the folded state of the display portion **122**.

For example, the shape or place of an object such as a protrusion, an electromagnetic wave such as light, an electric wave, or a magnetic force, or the like can serve as the sign **129**. Specifically, the above serving as the sign **129** may have different polarities (e.g., the N- and S-poles of a magnet) or different signals (e.g., electromagnetic waves which are modulated by different methods), for example.

A sensor that can identify the sign **129** is selected as the sensor included in the sensor portion **123**.

Specifically, in the case where a structure having different shapes or in different places (e.g., a protrusion) is used as the sign **129**, a switch or the like having different shapes or in different places can be used for the sensor so that the structure can be identified. Alternatively, in the case where light is used as the sign **129**, a photoelectric conversion element or the like can be used for the sensor. In the case where an electric wave is used as the sign **129**, an antenna or the like can be used for the sensor. In the case where a

magnetic force is used as the sign 129, a magnetic sensor or the like can be used for the sensor.

A method of specifying the folded state of the display portion 122 by a signal supplied from the sensor that senses the sign will be described in detail in Embodiment 2.

Note that the sensor portion 123 senses acceleration, a direction, a global positioning system (GPS) signal, temperature, humidity, or the like and may supply data thereon. <<Input Means>>

As the input means 121, any of a variety of human interfaces and the like can be used. Specifically, a keyboard, a mouse, a touch sensor, a microphone, a camera, or the like can be used. In particular, supplying an operation instruction using a pointer is convenient because it enables intuitional operation.

For example, in the case where a touch panel is used as the input means 121 that is overlapped with and integrally formed with the display portion, a user of the data processing device 100 can input an operation instruction INPUT including a termination instruction or the like by gestures (e.g., tap, drag, swipe, and pinch-in) using a finger as a pointer on the touch panel.

<<Display Portion>>

The display portion 122 has flexibility and therefore can be bent.

A first plane (also referred to as a surface) of the display portion 122 which is provided in a planar manner is shown in FIG. 1B1. A second plane (also referred to as a rear surface) opposite to the first plane is shown in FIG. 1B2.

The folded state of the display portion 122 is shown in FIGS. 1C1 and 1C2.

Note that the structure of the display portion having flexibility that can be applied to this embodiment will be described in detail in Embodiments 4 and 5.

Note that although the display portion 122 foldable in three parts is provided in the data processing device 100 described in this embodiment, the foldable number in one embodiment of the present invention is not limited to three. Specifically, the display portion may be foldable in two parts or in four or more parts. As the foldable number gets larger, a highly browsable data processing device can be provided. Alternatively, a highly portable data processing device can be provided.

<<Communication Unit>>

The communication portion 125 connects an external network and the data processing device 100. The data processing device 100 obtains or supplies data COM from or to the outside. Specifically, a network connection device, a modem, or the like can be used as the communication portion 125.

<<Other Components>>

As the input/output unit 120, for example, a camera, a microphone, a read-only external memory portion, an external memory portion, a communication unit, a scanner, a speaker, or a printer can be used.

Specifically, as a camera, a digital camera, digital video camera, or the like can be used.

As an external memory portion, a hard disk, a removable memory, or the like can be used. As a read-only external memory portion, a CD-ROM, a DVD-ROM, or the like can be used.

This embodiment can be combined as appropriate with any of the other embodiments in this specification.

#### Embodiment 2

In this embodiment, a structure of a data processing device of one embodiment of the present invention will be

described with reference to FIGS. 1A to 1C2 and FIGS. 3A1, 3A2, 3B1, 3B2, 3C1, 3C2, 3D1, 3D2, 3E1, 3E2, 3F1, and 3F2.

Specifically, the data processing device 100 including the foldable display portion 122, a foldable housing that supports the display portion 122, the sign 129 placed on the housing, and the sensor portion 123 that senses the sign 129 is described. A signal on fold, which is supplied by the sensor portion 123 depending on the folded state of the data processing device 100, is described.

FIGS. 3A1 to 3F2 are schematic views illustrating the folded states of the display portion 122 and the housing that support the display portion 122 of the data processing device 100 of one embodiment of the present invention. Specifically, the schematic views illustrate the unfolded state and 10 kinds of different folded states.

The data processing device 100 described in this embodiment includes a connection housing C provided with a first plane (also referred to a surface; see FIG. 1B1) and a second plane (also referred to as a rear surface; see FIG. 1B2) opposite to the first plane.

The data processing device 100 includes the sensor portion 123 that discerns a first sign 129(1) and a second sign 129(2) which can approach the first plane of the connection housing C and a third sign 129(3) and a fourth sign 129(4) which can approach the second plane thereof. Note that the sensor portion 123 includes a sensor 123L.

The data processing device 100 includes a first housing L connected to the connection housing C so as to be movable from the position at which the first plane of the first housing L faces the first plane of the connection housing C to the position at which the second plane of the first housing L opposite to the first plane thereof faces the second plane of the connection housing C (see FIG. 1C1).

The data processing device 100 further includes a second housing R connected to the connection housing C so as to be movable from the position at which the first plane of the second housing R faces the first plane of the connection housing C to the position at which the second plane of the second housing R opposite to the first plane thereof faces the second plane of the connection housing C (see FIG. 1C2).

The connection housing C, the first housing L, and the second housing R support the display portion 122 having flexibility so that the display portion 122 can be folded.

The first housing L is provided with the first sign 129(1) on the first plane and the third sign 129(3) on the second plane.

The second housing R is provided with the second sign 129(2) on the first plane and the fourth sign 129(4) on the second plane.

The data processing device 100 described in this embodiment includes the display portion 122 which can be folded and unfolded and the sensor portion 123 that can sense the folded and unfolded states of the display portion 122 and can supply the data on fold. Accordingly, a highly browsable data processing device can be provided. Alternatively, a highly portable data processing device can be provided.

In the data processing device 100 described in this embodiment, the second housing R is provided with a fifth sign 129(5) on the first plane and a sixth sign 129(6) on the second plane. The sensor portion 123 discerns the sixth sign 129(6) that approaches the first plane of the first housing L and the fifth sign 129(5) that approaches the second plane of the first housing L. Note that the sensor portion 123 includes a sensor 123U.

The data processing device 100 described in this embodiment can sense the folded and unfolded states of the display

portion **122** and can supply the data SENS on fold. Specifically, the data processing device **100** can be unfolded or folded in 10 kinds of different ways and the sensor portion **123** can supply different data SENS on fold that corresponds to the states. Accordingly, respective programs for executing different processing can be allocated to 11 different kinds of states. As a result, a data processing device that can be used in such a manner that a folding manner is changed to easily select any of a variety of functions can be provided.

Two or more different folded states of the display portion **122** of the data processing device **100** are described with reference to FIGS. **3A1** to **3F2**.

The sensor portion **123** is provided with the sensor **123L** in the connection housing **C** and the sensor **123U** in the first housing **L**. Note that the sensor **123L** and the sensor **123U** can discern the signs **129** that approach the first plane and the signs **129** that approach the second plane.

The sensor portion **123** generates and supplies data SENS on fold that can specify the folded state of the display portion **122** in accordance with a combination of signals supplied from the sensor **123L** and the sensor **123U**.

Note that in the case where a sign **129(x)** approaches the first plane and a sign **129(y)** approaches the second plane, the sensor **123L** and the sensor **123U** supply a signal (x, y). In the case where the sign **129** does not approach the first plane or the second plane, a signal (0, 0) is supplied. Note that this expression is for convenience, and the format of a signal is not limited thereto as long as the sign **129** that approaches the first plane or the second plane can be discerned.

<Unfolded State>

The unfolded state of the connection housing **C**, the first housing **L**, and the second housing **R** of the data processing device **100** is illustrated in FIGS. **3A1** and **3A2**. Note that FIG. **3A1** is a schematic view seen from the first plane (also referred to as a surface) and FIG. **3A2** is a schematic view seen from the second plane (also referred to as a rear surface) opposite to the first plane.

Note that the signs **129(1)** to **129(6)**, the display portion **122**, the sensor **123L**, and the sensor **123U** are not illustrated in FIGS. **3B1** to **3F2** so that complicated drawings do not disturb the understanding of the invention. These drawings can be easily understood by those skilled in the art by being compared with FIGS. **3A1** and **3A2**.

In the unfolded state of the connection housing **C**, the first housing **L**, and the second housing **R** of the data processing device **100**, any of the signs is not sensed by the sensor **123U** and the sensor **123L**. Accordingly, the sensor **123U** supplies a signal (0, 0) and the sensor **123L** supplies a signal (0, 0). <Double-Fold States>

In the case where the first housing **L** of the data processing device **100** is folded over the second plane, the sensor **123L** senses the third sign **129(3)** placed on the second plane of the first housing **L** and supplies a signal (0, 3) (see FIG. **3B1**).

In the case where the first housing **L** of the data processing device **100** is folded over the first plane, the sensor **123L** senses the first sign **129(1)** placed on the first plane of the first housing **L** and supplies a signal (1, 0) (see FIG. **3B2**).

In the case where the second housing **R** of the data processing device **100** is folded over the second plane, the sensor **123L** senses the fourth sign **129(4)** placed on the second plane of the second housing **R** and supplies a signal (0, 4) (see FIG. **3C1**).

In the case where the second housing **R** of the data processing device **100** is folded over the first plane, the

sensor **123L** senses the second sign **129(2)** placed on the first plane of the second housing **R** and supplies a signal (2, 0) (see FIG. **3C2**).

Note that in the double-fold states, any of the signs is not sensed by the sensor **123U**. Accordingly, the sensor **123U** supplies a signal (0, 0).

<Tri-Folded States>

In the case where the first housing **L** of the data processing device **100** is folded over the second plane and the second housing **R** thereof is folded over the first plane, the sensor **123L** senses the third sign **129(3)** placed on the second plane of the first housing **L** and the second sign **129(2)** placed on the first plane of the second housing **R** and supplies a signal (2, 3) (see FIG. **3D1**).

Note that the connection housing **C** is provided between the sensor **123U** placed on the first housing **L** and the fifth sign **129(5)** placed on the first plane of the second housing **R**. Accordingly, the sensor **123U** supplies a signal (0, 0).

In the case where the first housing **L** of the data processing device **100** is folded over the first plane and the second housing **R** thereof is folded over the second plane, the sensor **123L** senses the first sign **129(1)** placed on the first plane of the first housing **L** and the fourth sign **129(4)** placed on the second plane of the second housing **R** and supplies a signal (1, 4) (see FIG. **3D2**).

Note that the connection housing **C** is provided between the sensor **123U** placed on the first housing **L** and the sixth sign **129(6)** placed on the second plane of the second housing **R**. Accordingly, the sensor **123U** supplies a signal (0, 0).

In the case where the first housing **L** of the data processing device **100** is folded over the second plane and the second housing **R** thereof is folded over the second plane so as to overlap with the first housing **L**, the sensor **123L** senses the third sign **129(3)** placed on the second plane of the first housing **L** and supplies a signal (0, 3) (see FIG. **3E1**). The sensor **123U** senses the sixth sign **129(6)** placed on the second plane of the second housing **R** and supplies a signal (6, 0).

In the case where the second housing **R** of the data processing device **100** is folded over the second plane and the first housing **L** thereof is folded over the second plane so as to overlap with the second housing **R**, the sensor **123L** senses the fourth sign **129(4)** placed on the second plane of the second housing **R** and supplies a signal (0, 4) (see FIG. **3E2**). The sensor **123U** senses the fifth sign **129(5)** placed on the first plane of the second housing **R** and supplies a signal (0, 5).

In the case where the first housing **L** of the data processing device **100** is folded over the first plane and the second housing **R** thereof is folded over the first plane so as to overlap with the first housing **L**, the sensor **123L** senses the first sign **129(1)** placed on the first plane of the first housing **L** and supplies a signal (1, 0) (see FIG. **3F1**). The sensor **123U** senses the fifth sign **129(5)** placed on the first plane of the second housing **R** and supplies a signal (0, 5).

In the case where the second housing **R** of the data processing device **100** is folded over the first plane and the first housing **L** thereof is folded over the first plane so as to overlap with the second housing **R**, the sensor **123L** senses the second sign **129(2)** placed on the first plane of the second housing **R** and supplies a signal (2, 0) (see FIG. **3F2**). The sensor **123U** senses the sixth sign **129(6)** placed on the second plane of the second housing **R** and supplies a signal (6, 0).

This embodiment can be combined as appropriate with any of the other embodiments in this specification.

## 11

## Embodiment 3

In this embodiment, a structure of a data processing device **200** of one embodiment of the present invention will be described with reference to FIGS. **4A** and **4B**, FIGS. **5A** to **5D**, FIGS. **6A** to **6D**, and FIGS. **7A1**, **7A2**, **7B1**, **7B2**, **7C1**, and **7C2**.

FIG. **4A** is a top view illustrating a structure of the data processing device **200** of one embodiment of the present invention which is unfolded, and FIG. **4B** is a side view thereof.

FIG. **5A** is a top view illustrating a structure of the data processing device **200** of one embodiment of the present invention which is double-folded, and FIG. **5B** is a side view thereof. FIG. **5C** is a top view illustrating a structure of the data processing device **200** of one embodiment of the present invention which is double-folded in a manner different from that of the structure in FIG. **5A**, and FIG. **5D** is a side view thereof.

FIG. **6A** is a top view illustrating a structure of the data processing device **200** of one embodiment of the present invention which is double-folded in a manner different from those of the structures in FIGS. **5A** and **5C**, and FIG. **6B** is a side view thereof. FIG. **6C** is a top view illustrating a structure of the data processing device **200** of one embodiment of the present invention which is double-folded in a manner different from that of the structure in FIG. **6A**, and FIG. **6D** is a side view thereof.

FIG. **7A1** is a top view illustrating a structure of the data processing device **200** of one embodiment of the present invention which is tri-folded, and FIG. **7A2** is a side view thereof.

FIG. **7B1** is a top view illustrating a structure of the data processing device **200** of one embodiment of the present invention which is tri-folded in a manner different from that of the structure in FIG. **7A1**, and FIG. **7B2** is a side view thereof.

FIG. **7C1** is a top view illustrating a structure of the data processing device **200** of one embodiment of the present invention which is tri-folded in a manner different from that of the structure in FIGS. **7A1** and **7B1**, and FIG. **7C2** is a side view thereof.

The data processing device **200** described as an example in this embodiment includes the connection housing **C**. The connection housing **C** is provided with the sensor **123L** that discerns the approach of a sign (see FIG. **4A**).

The data processing device **200** includes the first housing **L**. The first housing **L** is connected to the connection housing **C** with a link **211** therebetween. Accordingly, the first housing **L** is movable from the position at which the first plane of the first housing **L** faces the first plane of the connection housing **C** to the position at which the second plane of the first housing **L** opposite to the first plane thereof faces the second plane of the connection housing **C** (see FIG. **4B**). As a result, the data processing device **200** can be folded.

The first housing **L** is provided with the sensor **123U**. The first housing **L** is provided with the first sign **129(1)** on the first plane and the third sign **129(3)** on the second plane.

The data processing device **200** includes the second housing **R**. The second housing **R** is connected to the connection housing **C** with a link **212** therebetween. Accordingly, the second housing **R** is movable from the position at which the first plane of the second housing **R** faces the first plane of the connection housing **C** to the position at which the second plane of the second housing **R** opposite to the first

## 12

plane thereof faces the second plane of the connection housing **C**. As a result, the data processing device **200** can be folded.

The second housing **R** is provided with the second sign **129(2)** and the fifth sign **129(5)** on the first plane and the fourth sign **129(4)** and the sixth sign **129(6)** on the second plane.

The data processing device **200** is provided with a sensor portion including the sensor **123L** and the sensor **123U**.

The sensor **123L** discerns the first sign **129(1)** and the second sign **129(2)** that approach the first plane of the connection housing **C** and the third sign **129(3)** and the fourth sign **129(4)** that approach the second plane thereof.

The sensor **123U** discerns the sixth sign **129(6)** that approaches the first plane of the first housing **L** and the fifth sign **129(5)** that approaches the second plane thereof.

The connection housing **C**, the first housing **L**, and the second housing **R** of the data processing device **200** support the display portion **222** having flexibility. Note that the arrows in FIG. **4B** indicate the direction in which the display portion **222** displays an image.

The data processing device **200** described in this embodiment includes the display portion **222** which can be folded and unfolded and the sensor portion **123** that can sense the folded and unfolded states of the display portion **222** and can supply data on fold. Accordingly, a highly browsable data processing device can be provided. Alternatively, a highly portable data processing device can be provided.

<Unfolded State>

In the unfolded state of the connection housing **C**, the first housing **L**, and the second housing **R** of the data processing device **200**, any of the signs is not sensed by the sensor **123U** and the sensor **123L**. Accordingly, the sensor **123U** supplies a signal (0, 0) and the sensor **123L** supplies a signal (0, 0) (see FIG. **4A**).

<Double-Fold States>

In the case where the first housing **L** of the data processing device **200** is folded over the first plane, the sensor **123L** senses the first sign **129(1)** placed on the first plane of the first housing **L** and supplies a signal (0, 1) (see FIGS. **5A** and **5B**).

As illustrated in FIGS. **5A** and **5B**, the data processing device **200** can be used by folding the first housing **L** over the first plane such that the second plane of the first housing **L** and the first plane of the second housing **R** face a user.

Note that an input means (e.g., a keyboard **121K**) can be provided on the second plane of the first housing **L** (see FIG. **5A**).

For example, a signal on fold supplied by the sensor portion in the case where the data processing device **200** is folded in this state can be correlated to an application for processing an e-mail. Accordingly, a user can deal with an e-mail by folding the data processing device **200** as illustrated in FIGS. **5A** and **5B**. Specifically, text data or the like can be input from the keyboard **121K** with the use of the display portion **222** supported by the second housing **R**. In addition, display on the display portion **222** supported by the first housing **L** and the connection housing **C** can be stopped to reduce power consumption.

In the case where the first housing **L** of the data processing device **200** is folded over the second plane, the sensor **123L** senses the third sign **129(3)** placed on the second plane of the first housing **L** and supplies a signal (0, 3) (see FIGS. **5C** and **5D**).

As illustrated in FIGS. **5C** and **5D**, the data processing device **200** can be used by folding the first housing **L** over

## 13

the second plane such that the first planes of the connection housing C and the second housing R face a user.

For example, a signal on fold supplied by the sensor portion in the case where the data processing device 200 is folded in this state can be correlated to an application for viewing an electronic book. Accordingly, a user can view an electronic book by folding the data processing device 200 as illustrated in FIGS. 5C and 5D.

In addition, display on the display portion 222 of the data processing device 200 which is folded in this state and supported by the first housing L can be stopped because the display portion 222 supported by the first housing L does not face a user. Accordingly, power consumption can be reduced.

In the case where a touch panel is provided so as to overlap with the display portion 222 which does not face a user, the touch panel may be used as an input means. Accordingly, the data processing device 200 can be supported or operated by a thumb on the user's side and a finger which does not face the user.

In the case where the second housing R of the data processing device 200 is folded over the first plane, the sensor 123L senses the second sign 129(2) placed on the first plane of the second housing R and supplies a signal (0, 2) (see FIGS. 6A and 6B).

Note that an input means (e.g., a control button 121B) can be provided on the second plane of the second housing R (see FIG. 6A).

For example, the signal on fold supplied by the sensor portion in the case where the data processing device 200 is folded in this state can be correlated to an application of a game. Accordingly, a user can enjoy the game by folding the data processing device 200 as illustrated in FIGS. 6A and 6B. Specifically, a character and the like can be handled by data input from the control button 121B with the use of the display portion 222 supported by the first housing L. In addition, display on the display portion 222 supported by the second housing R and the connection housing C can be stopped to reduce power consumption.

In the case where the second housing R of the data processing device 200 is folded over the first plane, the sensor 123R senses the fourth sign 129(4) placed on the second plane of the second housing R and supplies a signal (0, 4) (see FIGS. 6C and 6D).

For example, the signal on fold supplied by the sensor portion in the case where the data processing device 200 is folded in this state can be correlated to an application for viewing websites on the Internet. Accordingly, a user can view a website by folding the data processing device 200 as illustrated in FIGS. 6C and 6D.

Note that the application allocated to the data processing device 200 folded as illustrated in FIGS. 5A to 5D and the application allocated to the data processing device 200 folded as illustrated in FIGS. 6A to 6D may be able to be selected by a user. For example, the application to be allocated may be changed depending on whether user is right-handed or left-handed.

<Tri-Folded States>

In the case where the first housing L of the data processing device 200 is folded over the second plane and the second housing R thereof is folded over the second plane so as to overlap with the first housing L, the sensor 123L senses the third sign 129(3) placed on the second plane of the first housing L and supplies a signal (0, 3) (see FIGS. 7A1 and 7A2). The sensor 123U which is not illustrated senses the sixth sign 129(6) placed on the second plane of the second housing R and supplies a signal (6, 0).

## 14

In the case where the first housing L of the data processing device 200 is folded over the second plane and the second housing R thereof is folded over the first plane, the sensor 123L senses the third sign 129(3) placed on the second plane of the first housing L and the second sign 129(2) placed on the first plane of the second housing R and supplies a signal (2, 3) (see FIGS. 7B1 and 7B2). Although not illustrated, the connection housing C is provided between the sensor 123U placed on the first housing L and the fifth sign 129(5) placed on the first plane of the second housing R. Accordingly, the sensor 123U supplies a signal (0, 0).

Note that an input means (e.g., a camera 121C) can be provided on the second plane of the second housing R (see FIG. 7B1).

For example, the signal on fold supplied by the sensor portion in the case where the data processing device 200 is folded in this state can be correlated to an application for capturing an image. Accordingly, a user can capture an image by folding the data processing device 200 as illustrated in FIGS. 7B1 and 7B2. Specifically, an image can be captured from the camera 121C with the use of the display portion 222 supported by the first housing L. In addition, display on the display portion 222 supported by the second housing R and the connection housing C can be stopped to reduce power consumption.

In the case where the second housing R of the data processing device 200 is folded over the first plane and the first housing L thereof is folded over the first plane so as to overlap with the second housing R, the sensor 123L senses the second sign 129(2) placed on the first plane of the second housing R and supplies a signal (2, 0) (see FIGS. 7C1 and 7C2). The sensor 123U senses the sixth sign 129(6) placed on the second plane of the second housing R and supplies a signal (6, 0).

For example, the signal on fold supplied by the sensor portion in the case where the data processing device 200 is folded in this state can be correlated to an instruction to bring the data processing device into a standby state. Accordingly, display on the display portion 222 can be stopped to reduce power consumption by folding the data processing device 200 as illustrated in FIGS. 7C1 and 7C2.

This embodiment can be combined as appropriate with any of the other embodiments in this specification.

## Embodiment 41

In this embodiment, a structure of an input/output unit that can be used for the data processing device of one embodiment of the present invention will be described with reference to FIGS. 8A to 8C.

FIG. 8A is a top view illustrating the structure of an input/output unit that can be used in the data processing device of one embodiment of the present invention.

FIG. 8B is a cross-sectional view taken along line A-B and line C-D in FIG. 8A.

FIG. 8C is a cross-sectional view taken along line E-F in FIG. 8A.

<Top View>

An input/output unit 300 described as an example in this embodiment includes a display portion 301 (see FIG. 8A).

The display portion 301 includes a plurality of pixels 302 and a plurality of imaging pixels 308. The imaging pixels 308 can sense a touch of a finger or the like on the display portion 301. Thus, a touch sensor can be formed using the imaging pixels 308.

Each of the pixels 302 includes a plurality of sub-pixels (e.g., a sub-pixel 302R). In addition, in the sub-pixels,

light-emitting elements and pixel circuits that can supply electric power for driving the light-emitting elements are provided.

The pixel circuits are electrically connected to wirings through which selection signals can be supplied and wirings through which image signals can be supplied.

Furthermore, the input/output unit **300** is provided with a scan line driver circuit **303g(1)** that can supply selection signals to the pixels **302** and an image signal line driver circuit **303s(1)** that can supply image signals to the pixels **302**. Note that when the image signal line driver circuit **303s(1)** is placed in a portion other than a bendable portion, malfunction can be inhibited.

The imaging pixels **308** include photoelectric conversion elements and imaging pixel circuits that drive the photoelectric conversion elements.

The imaging pixel circuits are electrically connected to wirings through which control signals can be supplied and wirings through which power supply potentials can be supplied.

Examples of the control signals include a signal for selecting an imaging pixel circuit from which a recorded imaging signal is read, a signal for initializing an imaging pixel circuit, and a signal for determining the time it takes for an imaging pixel circuit to sense light.

The input/output unit **300** is provided with an imaging pixel driver circuit **303g(2)** that can supply control signals to the imaging pixels **308** and an imaging signal line driver circuit **303s(2)** that reads out imaging signals. Note that when the imaging signal line driver circuit **303s(2)** is placed in a portion other than a bendable portion, malfunction can be inhibited.

<<Cross-Sectional View>>

The input/output unit **300** includes a substrate **310** and a counter substrate **370** opposite to the substrate **310** (see FIG. **8B**).

The substrate **310** is a stacked body in which a substrate **310b** having flexibility, a barrier film **310a** that prevents diffusion of unintentional impurities to the light-emitting elements, and an adhesive layer **310c** that attaches the barrier film **310a** to the substrate **310b** are stacked.

The counter substrate **370** is a stacked body including a substrate **370b** having flexibility, a barrier film **370a** that prevents diffusion of unintentional impurities to the light-emitting elements, and an adhesive layer **370c** that attaches the barrier film **370a** to the substrate **370b** (see FIG. **8B**).

A sealant **360** attaches the counter substrate **370** to the substrate **310**. The sealant **360** also serving as an optical adhesive layer has a refractive index higher than that of air. The pixel circuits and the light-emitting elements (e.g., a first light-emitting element **350R**) and the imaging pixel circuits and photoelectric conversion elements (e.g., a photoelectric conversion element **308p**) are provided between the substrate **310** and the counter substrate **370**.

<<Structure of Pixel>>

Each of the pixels **302** includes a sub-pixel **302R**, a sub-pixel **302G**, and a sub-pixel **302B** (see FIG. **8C**). The sub-pixel **302R** includes a light-emitting module **380R**, the sub-pixel **302G** includes a light-emitting module **380G**, and the sub-pixel **302B** includes a light-emitting module **380B**.

For example, the sub-pixel **302R** includes the first light-emitting element **350R** and the pixel circuit that can supply electric power to the first light-emitting element **350R** and includes a transistor **302t** (see FIG. **8B**). Furthermore, the light-emitting module **380R** includes the first light-emitting element **350R** and an optical element (e.g., a first coloring layer **367R**).

The first light-emitting element **350R** includes a first lower electrode **351R**, an upper electrode **352**, and a layer **353** containing a light-emitting organic compound between the first lower electrode **351R** and the upper electrode **352** (see FIG. **8C**).

The layer **353** containing a light-emitting organic compound includes a light-emitting unit **353a**, a light-emitting unit **353b**, and an intermediate layer **354** between the light-emitting units **353a** and **353b**.

The light-emitting module **380R** includes the first coloring layer **367R** on the counter substrate **370**. The coloring layer transmits light of a particular wavelength and is, for example, a layer that selectively transmits light of red, green, or blue color. A region that transmits light emitted from the light-emitting element as it is may be provided as well.

The light-emitting module **380R**, for example, includes the sealant **360** that is in contact with the first light-emitting element **350R** and the first coloring layer **367R**.

The first coloring layer **367R** is positioned in a region overlapping with the first light-emitting element **350R**. Accordingly, part of light emitted from the first light-emitting element **350R** passes through the sealant **360** that also serves as an optical adhesive layer and through the first coloring layer **367R** and is emitted to the outside of the light-emitting module **380R** as indicated by arrows in FIGS. **8B** and **8C**.

<<Structure of Input/Output Unit>>

The input/output unit **300** includes a light-blocking layer **367BM** on the counter substrate **370**. The light-blocking layer **367BM** is provided so as to surround the coloring layer (e.g., the first coloring layer **367R**).

The input/output unit **300** includes an anti-reflective layer **367p** positioned in a region overlapping with the display portion **301**. As the anti-reflective layer **367p**, a circular polarizing plate can be used, for example.

The input/output unit **300** includes an insulating film **321**. The insulating film **321** covers the transistor **302t**. Note that the insulating film **321** can be used as a layer for planarizing unevenness caused by the pixel circuits. An insulating film on which a layer that can prevent diffusion of impurities to the transistor **302t** and the like is stacked can be used as the insulating film **321**.

The input/output unit **300** includes the light-emitting elements (e.g., the first light-emitting element **350R**) over the insulating film **321**.

The input/output unit **300** includes, over the insulating film **321**, a partition wall **328** that overlaps with an end portion of the first lower electrode **351R** (see FIG. **8C**). In addition, a spacer **329** that controls the distance between the substrate **310** and the counter substrate **370** is provided on the partition wall **328**.

<<Structure of Image Signal Line Driver Circuit>>

The image signal line driver circuit **303s(1)** includes a transistor **303t** and a capacitor **303c**. Note that the image signal line driver circuit **303s(1)** can be formed in the same process and over the same substrate as those of the pixel circuits.

<<Structure of Imaging Pixel>>

The imaging pixels **308** each include the photoelectric conversion element **308p** and an imaging pixel circuit for sensing light received by the photoelectric conversion element **308p**. The imaging pixel circuit includes a transistor **308t**.

For example, a PIN photodiode can be used as the photoelectric conversion element **308p**.

<<Other Structures>>

The input/output unit **300** includes a wiring **311** through which a signal can be supplied. The wiring **311** is provided with a terminal **319**. Note that an FPC **309(1)** through which a signal such as an image signal or a synchronization signal can be supplied is electrically connected to the terminal **319**. The FPC **309(1)** is preferably placed in a portion other than a bendable portion of the input/output unit **300**. Moreover, the FPC **309(1)** is preferably placed at almost the center of one side of a region surrounding the display portion **301**, especially a side which is folded (a longer side in FIG. **8A**). Accordingly, the distance between an external circuit for driving the input/output unit **300** and the input/output unit **300** can be made short, resulting in easy connection. Furthermore, the center of gravity of the external circuit can be made almost the same as that of the input/output unit **300**. As a result, the data processing device can be treated easily and mistakes such as dropping can be prevented.

Note that a printed wiring board (PWB) may be attached to the FPC **309(1)**.

This embodiment can be combined as appropriate with any of the other embodiments in this specification.

#### Embodiment 5

In this embodiment, a structure of a foldable touch panel in which a touch sensor (a contact sensor device) as an input means is provided to overlap with a display portion is described with reference to FIGS. **9A** and **9B** and FIG. **10**.

FIG. **9A** is a schematic perspective view of a touch panel **500** described as an example in this embodiment. Note that FIGS. **9A** and **9B** illustrate only main components for simplicity. FIG. **9B** is a developed view of the schematic perspective view of the touch panel **500**.

FIG. **10** is a cross-sectional view of the touch panel **500** taken along line X1-X2 in FIG. **9A**.

The touch panel **500** includes a display portion **501** and a touch sensor **595** (see FIG. **9B**). Furthermore, the touch panel **500** includes a substrate **510**, a substrate **570**, and a substrate **590**. Note that the substrate **510**, the substrate **570**, and the substrate **590** each have flexibility.

The display portion **501** includes the substrate **510**, a plurality of pixels over the substrate **510**, and a plurality of wirings **511** through which signals are supplied to the pixels. The plurality of wirings **511** are led to a peripheral portion of the substrate **510**, and part of the plurality of wirings **511** form a terminal **519**. The terminal **519** is electrically connected to an FPC **509(1)**.

<Touch Sensor>

The substrate **590** includes the touch sensor **595** and a plurality of wirings **598** electrically connected to the touch sensor **595**. The plurality of wirings **598** are led to the periphery of the substrate **590**, and part of the wirings **598** form part of a terminal for electrical connection to an FPC **509(2)**. Note that in FIG. **9B**, electrodes, wirings, and the like of the touch sensor **595** which are provided on the rear side of the substrate **590** (the rear side of the diagram) are indicated by solid lines for clarity.

As a touch sensor used as the touch sensor **595**, a capacitive touch sensor is preferably used. Examples of the capacitive touch sensor are of a surface capacitive type, of a projected capacitive type, and the like. Furthermore, examples of the projected capacitive type are of a self capacitive type, a mutual capacitive type, and the like mainly in accordance with the difference in the driving method. The use of a mutual capacitive type is preferable because multiple points can be sensed simultaneously.

An example of using a projected capacitive touch sensor is described below with reference to FIG. **9B**. Note that a variety of sensors that can sense the closeness or the contact of a sensing target such as a finger can be used.

The projected capacitive touch sensor **595** includes electrodes **591** and electrodes **592**. The electrodes **591** are electrically connected to any of the plurality of wirings **598**, and the electrodes **592** are electrically connected to any of the other wirings **598**.

The electrode **592** is in the form of a series of quadrangles arranged in one direction as illustrated in FIGS. **9A** and **9B**. Each of the electrodes **591** is in the form of a quadrangle. A wiring **594** electrically connects two electrodes **591** arranged in a direction intersecting with the direction in which the electrode **592** extends. The intersecting area of the electrode **592** and the wiring **594** is preferably as small as possible. Such a structure allows a reduction in the area of a region where the electrodes are not provided, reducing unevenness in transmittance. As a result, unevenness in luminance of light from the touch sensor **595** can be reduced.

Note that the shapes of the electrode **591** and the electrode **592** are not limited thereto and can be any of a variety of shapes. For example, a structure may be employed in which the plurality of electrodes **591** are arranged so that gaps between the electrodes **591** are reduced as much as possible, and the electrode **592** is spaced apart from the electrodes **591** with an insulating layer interposed therebetween to have regions not overlapping with the electrodes **591**. In this case, it is preferable to provide, between two adjacent electrodes **592**, a dummy electrode electrically insulated from these electrodes because the area of regions having different transmittances can be reduced.

The structure of the touch panel **500** is described with reference to FIG. **10**.

The touch sensor **595** includes the substrate **590**, the electrodes **591** and the electrodes **592** provided in a staggered arrangement on the substrate **590**, an insulating layer **593** covering the electrodes **591** and the electrodes **592**, and the wiring **594** that electrically connects the adjacent electrodes **591** to each other.

An adhesive layer **597** attaches the substrate **590** to the substrate **570** so that the touch sensor **595** overlaps with the display portion **501**.

The electrodes **591** and the electrodes **592** are formed using a light-transmitting conductive material. As a light-transmitting conductive material, a conductive oxide such as indium oxide, indium tin oxide, indium zinc oxide, zinc oxide, or zinc oxide to which gallium is added can be used.

The electrodes **591** and the electrodes **592** may be formed by depositing a light-transmitting conductive material on the substrate **590** by a sputtering method and then removing an unnecessary portion by any of known patterning techniques such as photolithography.

The insulating layer **593** covers the electrodes **591** and the electrodes **592**. Examples of a material for the insulating layer **593** are a resin such as acrylic or epoxy resin, a resin having a siloxane bond, and an inorganic insulating material such as silicon oxide, silicon oxynitride, or aluminum oxide.

Furthermore, openings reaching the electrodes **591** are formed in the insulating layer **593**, and the wiring **594** electrically connects the adjacent electrodes **591**. The wiring **594** is preferably formed using a light-transmitting conductive material, in which case the aperture ratio of the touch panel can be increased. Moreover, the wiring **594** is preferably formed using a material that has higher conductivity than the electrodes **591** and the electrodes **592**.

One electrode **592** extends in one direction, and a plurality of electrodes **592** are provided in the form of stripes.

The wiring **594** intersects with the electrode **592**.

Adjacent electrodes **591** are provided with one electrode **592** provided therebetween and are electrically connected by the wiring **594**.

Note that the plurality of electrodes **591** are not necessarily arranged in the direction orthogonal to one electrode **592** and may be arranged to intersect with one electrode **592** at an angle of less than 90 degrees.

One wiring **598** is electrically connected to any of the electrodes **591** and **592**. Part of the wiring **598** functions as a terminal. For the wiring **598**, a metal material such as aluminum, gold, platinum, silver, nickel, titanium, tungsten, chromium, molybdenum, iron, cobalt, copper, or palladium or an alloy material containing any of these metal materials can be used.

Note that an insulating layer that covers the insulating layer **593** and the wiring **594** may be provided to protect the touch sensor **595**.

Furthermore, a connection layer **599** electrically connects the wiring **598** to the FPC **509(2)**.

For the connection layer **599**, a known anisotropic conductive film (ACF), a known anisotropic conductive paste (ACP), or the like can be used.

The adhesive layer **597** has a light-transmitting property. For example, a thermosetting resin or an ultraviolet curable resin can be used; specifically, a resin such as acrylic, urethane, epoxy resin, or a resin having a siloxane bond can be used.

<Display Portion>

The touch panel **500** includes a plurality of pixels arranged in a matrix. Each of the pixels includes a display element and a pixel circuit for driving the display element.

In this embodiment, an example of using a white organic electroluminescent element as a display element will be described; however, the display element is not limited to such an element.

As the display element, for example, other than organic electroluminescent elements, any of a variety of display elements such as display elements (electronic ink) that perform display by an electrophoretic method, an electronic liquid powder method, or the like; MEMS shutter display elements; and optical interference type MEMS display elements can be used. Note that a structure suitable for display elements to be used can be selected from known pixel circuit structures.

The substrate **510** is a stacked body in which a substrate **510b** having flexibility, a barrier film **510a** that prevents diffusion of unintentional impurities to the light-emitting elements, and an adhesive layer **510c** that attaches the barrier film **510a** to the substrate **510b** are stacked.

The substrate **570** is a stacked body in which a substrate **570b** having flexibility, a barrier film **570a** that prevents diffusion of unintentional impurities to the light-emitting elements, and an adhesive layer **570c** that attaches the barrier film **570a** to the substrate **570b** are stacked.

A sealant **560** attaches the substrate **570** to the substrate **510**. The sealant **560** also serving as an optical adhesive layer has a refractive index higher than that of air.

The pixel circuits and the light-emitting elements (e.g., a first light-emitting element **550R**) are provided between the substrate **510** and the substrate **570**.

<<Structure of Pixel>>

A pixel includes a sub-pixel **502R**, and the sub-pixel **502R** includes a light-emitting module **580R**.

The sub-pixel **502R** includes the first light-emitting element **550R** and the pixel circuit that can supply electric power to the first light-emitting element **550R** and includes a transistor **502t**. Furthermore, the light-emitting module **580R** includes the first light-emitting element **550R** and an optical element (e.g., a first coloring layer **567R**).

The first light-emitting element **550R** includes a lower electrode, an upper electrode, and a layer containing a light-emitting organic compound between the lower electrode and the upper electrode.

The light-emitting module **580R** includes the first coloring layer **567R** on the substrate **570**. The coloring layer transmits light of a particular wavelength and is, for example, a layer that selectively transmits light of red, green, or blue color. A region that transmits light emitted from the light-emitting element as it is may be provided as well.

The light-emitting module **580R**, for example, includes the sealant **560** that is in contact with the first light-emitting element **550R** and the first coloring layer **567R**.

The first coloring layer **567R** is positioned in a region overlapping with the first light-emitting element **550R**. Accordingly, part of light emitted from the first light-emitting element **550R** passes through the sealant **560** that also serves as an optical adhesive layer and through the first coloring layer **567R** and is emitted to the outside of the light-emitting module **580R** as indicated by arrows in FIG. **10**.

<<Structure of Display Portion>>

The display portion **501** includes a light-blocking layer **567BM** on the substrate **570**. The light-blocking layer **567BM** is provided so as to surround the coloring layer (e.g., the first coloring layer **567R**).

The display portion **501** includes an anti-reflective layer **567p** positioned in a region overlapping with pixels. As the anti-reflective layer **567p**, a circular polarizing plate can be used, for example.

The display portion **501** includes an insulating film **521**. The insulating film **521** covers the transistor **502t**. Note that the insulating film **521** can be used as a layer for planarizing unevenness caused by the pixel circuits. An insulating film on which a layer that can prevent diffusion of impurities to the transistor **502t** and the like is stacked can be used as the insulating film **521**.

The display portion **501** includes the light-emitting elements (e.g., the first light-emitting element **550R**) over the insulating film **521**.

The display portion **501** includes, over the insulating film **521**, a partition wall **528** that overlaps with an end portion of the first lower electrode. In addition, a spacer that controls the distance between the substrate **510** and the substrate **570** is provided on the partition wall **528**.

<<Structure of Image Signal Line Driver Circuit>>

The image signal line driver circuit **503s(1)** includes a transistor **503t** and a capacitor **503c**. Note that the image signal line driver circuit **503s(1)** can be formed in the same process and over the same substrate as those of the pixel circuits.

<<Other Structures>>

The display portion **501** includes the wiring **511** through which a signal can be supplied. The wiring **511** is provided with the terminal **519**. Note that the FPC **509(1)** through which a signal such as an image signal or a synchronization signal can be supplied is electrically connected to the terminal **519**.

Note that a printed wiring board (PWB) may be attached to the FPC **509(1)**.

This embodiment can be combined as appropriate with any of the other embodiments in this specification.

## REFERENCE NUMERALS

**100**: data processing device, **110**: arithmetic unit, **111**: arithmetic portion, **112**: memory portion, **114**: transmission path, **115**: input/output interface, **120**: input/output unit, **121**: input means, **121B**: control button, **121C**: camera, **121K**: keyboard, **122**: display portion, **123**: sensor portion, **123L**: sensor, **123R**: sensor, **123U**: sensor, **125**: communication portion, **129**: sign, **200**: data processing device, **211**: link, **212**: link, **222**: display portion, **300**: input/output unit, **301**: display portion, **302**: pixel, **302B**: sub-pixel, **302G**: sub-pixel, **302R**: sub-pixel, **302t**: transistor, **303c**: capacitor, **303g(1)**: scan line driver circuit, **303g(2)**: imaging pixel driver circuit, **303s(1)**: image signal line driver circuit, **303s(2)**: imaging signal line driver circuit, **303t**: transistor, **308**: imaging pixel, **308p**: photoelectric conversion element. **308t**: transistor, **309**: FPC, **310**: substrate, **310a**: barrier film. **310b**: substrate, **310c**: adhesive layer, **311**: wiring, **319**: terminal, **321**: insulating film, **328**: partition wall, **329**: spacer, **350R**: light-emitting element, **351R**: lower electrode, **352**: upper electrode, **353**: layer, **353a**: light-emitting unit, **353b**: light-emitting unit. **354**: intermediate layer, **360**: sealant, **367BM**: light-blocking layer, **367p**: anti-reflective layer, **367R**: coloring layer, **370**: counter substrate, **370a**: barrier film, **370b**: substrate, **370c**: adhesive layer, **380B**: light-emitting module, **380G**: light-emitting module. **380R**: light-emitting module, **500**: touch panel, **501**: display portion, **502R**: sub-pixel, **502t**: transistor, **503c**: capacitor, **503s**: image signal line driver circuit, **503t**: transistor, **509**: FPC, **510**: substrate, **510a**: barrier film, **510b**: substrate, **510c**: adhesive layer, **511**: wiring, **519**: terminal, **521**: insulating film, **528**: partition wall, **550R**: light-emitting element, **560**: sealant, **567BM**: light-blocking layer, **567p**: anti-reflective layer, **567R**: coloring layer, **570**: substrate, **570a**: barrier film, **570b**: substrate, **570c**: adhesive layer, **580R**: light-emitting module, **590**: substrate, **591**: electrode, **592**: electrode, **593**: insulating layer, **594**: wiring, **595**: touch sensor. **597**: adhesive layer, **598**: wiring, **599**: connection layer, C: connection housing, L: first housing, R: second housing.

This application is based on Japanese Patent Application serial no. 2013-138895 filed with Japan Patent Office on Jul. 2, 2013, the entire contents of which are hereby incorporated by reference.

The invention claimed is:

**1.** A data processing device comprising:

a display portion being foldable and having a first region, a second region being adjacent to the first region, and a third region being adjacent to the second region, wherein each of the first region, the second region, and the third region comprises a light-emitting element, wherein when the display portion is folded to face inward, a part of the display portion which does not face a user of the data processing device is configured to stop displaying, wherein the part of the display portion includes at least the second region,

wherein the display portion comprises:

a first substrate having flexibility;  
a first adhesive layer over the first substrate;  
a transistor over the first adhesive layer;

an insulating layer over the transistor;  
a lower electrode of a light-emitting element over the insulating layer;  
a partition having a region overlapping with a first part of the lower electrode;  
a layer containing a light-emitting organic compound, the layer overlapping with a second part of the lower electrode;  
an upper electrode of the light-emitting element over the layer;  
a photodiode below the light-emitting element;  
a coloring layer over the upper electrode;  
a second adhesive layer over the coloring layer; and  
a second substrate having flexibility, and

wherein the photodiode is not overlapped with the light-emitting element, the partition, and the coloring layer.

**2.** The data processing device according to claim **1**, wherein one of a source and a drain of the transistor is electrically connected to the lower electrode through a conductive layer.

**3.** The data processing device according to claim **1**, wherein the photodiode does not overlap with a channel formation region of the transistor.

**4.** A data processing device comprising:

a display portion being foldable and having a first region, a second region being adjacent to the first region, and a third region being adjacent to the second region, wherein each of the first region, the second region, and the third region comprises a light-emitting element, wherein when the display portion is folded to face inward, a part of the display portion which does not face a user of the data processing device is configured to stop displaying,

wherein the part of the display portion includes at least the second region,

wherein the display portion comprises:

a first substrate having flexibility;  
a first adhesive layer over the first substrate;  
a transistor over the first adhesive layer;  
an insulating layer over the transistor;  
a lower electrode of a light-emitting element over the insulating layer;  
a partition having a region overlapping with a first part of the lower electrode;  
a layer containing a light-emitting organic compound, the layer overlapping with a second part of the lower electrode;  
an upper electrode of the light-emitting element over the layer;  
a photodiode below the light-emitting element;  
a coloring layer over the upper electrode;  
a second adhesive layer over the coloring layer; and  
a second substrate having flexibility,

wherein the photodiode is not overlapped with the light-emitting element, the partition, and the coloring layer, and

wherein the light-emitting element is configured to emit light to an outside of the second substrate through the coloring layer.

**5.** The data processing device according to claim **4**, wherein one of a source and a drain of the transistor is electrically connected to the lower electrode through a conductive layer.

**6.** The data processing device according to claim **4**, wherein the photodiode does not overlap with a channel formation region of the transistor.