

US012085707B2

(12) **United States Patent**
Ichikawa et al.

(10) **Patent No.:** **US 12,085,707 B2**
(45) **Date of Patent:** **Sep. 10, 2024**

(54) **WIDE-ANGLE OPTICAL SYSTEM AND
IMAGE PICKUP APPARATUS USING THE
SAME**

(71) Applicant: **OLYMPUS CORPORATION,**
Hachioji (JP)

(72) Inventors: **Keisuke Ichikawa,** Tama (JP); **Takashi
Fujikura,** Hamura (JP); **Shinichi
Mihara,** Tama (JP); **Yoshihiro Uchida,**
Hachioji (JP)

(73) Assignee: **OLYMPUS CORPORATION,** Tokyo
(JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 853 days.

(21) Appl. No.: **17/189,353**

(22) Filed: **Mar. 2, 2021**

(65) **Prior Publication Data**
US 2021/0255440 A1 Aug. 19, 2021

Related U.S. Application Data
(63) Continuation of application No.
PCT/JP2019/008033, filed on Mar. 1, 2019.

(51) **Int. Cl.**
G02B 15/14 (2006.01)
G02B 23/24 (2006.01)

(52) **U.S. Cl.**
CPC ... **G02B 23/243** (2013.01); **G02B 15/143507**
(2019.08)

(58) **Field of Classification Search**
CPC G02B 23/243; G02B 15/143507
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,949,589 A 9/1999 Nakazawa
6,246,529 B1 6/2001 Sensui
6,317,270 B2 11/2001 Nagaoka
7,016,120 B2 3/2006 Achtner et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP H10260346 A 9/1998
JP 2000131606 A 5/2000

(Continued)

OTHER PUBLICATIONS

JP 2016184136, translation (Year: 2016).*

(Continued)

Primary Examiner — Wen Huang


(74) *Attorney, Agent, or Firm* — Holtz, Holtz & Volek PC

(57) **ABSTRACT**

A wide-angle optical system is a wide-angle optical system having a lens component, and includes in order from an object side, a first lens unit having a negative refractive power, a second lens unit having a negative refractive power, and a third lens unit having a positive refractive power. At the time of carrying out a focal-position adjustment from a far point to a near point, the second lens unit is moved from a first position toward a second position. The third lens unit includes not less than three lens components. Not less than three lens components include a first lens component and a second lens component. Each of the first lens component and the second lens component has a positive refractive power, and following conditional expression (1) is satisfied:

$$0.8 < f_{L12}/f_L < 6.0 \quad (1).$$

34 Claims, 33 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,203,793	B2	6/2012	Wada et al.
8,345,357	B2	1/2013	Imoka
8,665,537	B2	3/2014	Roth et al.
8,717,684	B2	5/2014	Sano et al.
8,824,059	B2	9/2014	Kato et al.
8,867,147	B2	10/2014	Kimura
8,908,273	B2	12/2014	Fujimoto
8,934,176	B2	1/2015	Yamagami et al.
9,097,881	B2	8/2015	Yamagami
9,110,278	B2	8/2015	Sugita
9,459,443	B2	10/2016	Uzawa et al.
9,766,437	B2	9/2017	Sato
9,952,416	B2	4/2018	Ichikawa
9,958,653	B2	5/2018	Ichikawa
9,958,656	B2	5/2018	Kawamura et al.
10,095,012	B2	10/2018	Yamagami
10,114,200	B2	10/2018	Ichikawa
10,191,253	B2	1/2019	Ichikawa et al.
10,191,258	B2	1/2019	Ichikawa et al.
10,197,768	B2	2/2019	Ichikawa et al.
10,197,769	B2	2/2019	Ichikawa et al.
10,274,705	B2	4/2019	Ichikawa et al.
10,288,856	B2	5/2019	Fujikura et al.
10,656,399	B2	5/2020	Fujikura et al.
10,663,705	B2	5/2020	Ichikawa et al.
10,768,396	B2	9/2020	Kawamura et al.
10,830,991	B2	11/2020	Ichikawa et al.
2003/0189767	A1	10/2003	Achtner et al.
2010/0290133	A1	11/2010	Sano et al.
2011/0002046	A1	1/2011	Wada et al.
2011/0032606	A1	2/2011	Imaoka
2011/0116172	A1	5/2011	Yamagami et al.
2011/0317282	A1	12/2011	Kimura
2012/0019926	A1	1/2012	Yamagami
2012/0069441	A1	3/2012	Fujimoto et al.
2012/0307374	A1	12/2012	Kato et al.
2013/0265653	A1	10/2013	Kimura
2014/0002910	A1	1/2014	Roth et al.
2014/0125858	A1	5/2014	Sugita
2015/0042773	A1	2/2015	Uzawa et al.
2015/0268460	A1	9/2015	Takada
2015/0293353	A1	10/2015	Chin et al.
2017/0038563	A1	2/2017	Sato
2017/0068079	A1	3/2017	Kawamura et al.
2017/0168281	A1	6/2017	Furuya et al.
2018/0052311	A1	2/2018	Machida
2018/0210179	A1	7/2018	Kawamura et al.
2019/0079269	A1	3/2019	Kimura
2019/0086658	A1	3/2019	Takato
2019/0302432	A1	10/2019	Iwasawa et al.
2020/0018947	A1	1/2020	Tsuyuki

FOREIGN PATENT DOCUMENTS

JP	2003307672	A	10/2003
JP	2004233797	A	8/2004
JP	2010266577	A	11/2010
JP	2011013469	A	1/2011
JP	2011053663	A	3/2011
JP	2011107267	A	6/2011
JP	2012027309	A	2/2012
JP	2012027451	A	2/2012
JP	2012068303	A	4/2012
JP	2012247689	A	12/2012
JP	2013015621	A	1/2013
JP	2014056133	A	3/2014
JP	2014092728	A	5/2014
JP	2015114509	A	6/2015
JP	2016139087	A	8/2016
JP	2016184136	A	10/2016
JP	2017068114	A	4/2017
JP	2017122743	A	7/2017
JP	2018004726	A	1/2018
JP	2018040948	A	3/2018
JP	2018045097	A	3/2018

JP	2018189733	A	11/2018
JP	2019015958	A	1/2019
JP	2019184733	A	10/2019
WO	2014129089	A1	8/2014
WO	2016067838	A1	5/2016
WO	2017199614	A1	11/2017
WO	2018173412	A1	9/2018
WO	2020178883	A1	9/2020
WO	2020178884	A1	9/2020
WO	2020178885	A1	9/2020
WO	2020178886	A1	9/2020

OTHER PUBLICATIONS

International Preliminary Report on Patentability (IPRP) (and English language translation thereof) dated Sep. 16, 2021, issued in counterpart International Application No. PCT/JP2019/008032 which is an International counterpart of related U.S. Appl. No. 17/184,784.

International Preliminary Report on Patentability (IPRP) (and English language translation thereof) dated Sep. 16, 2021, issued in International Application No. PCT/JP2019/008034 (which is an International counterpart of related U.S. Appl. No. 17/189,679).

International Search Report (ISR) (and English language translation thereof) dated Jun. 4, 2019, issued in International Application No. PCT/JP2019/008028.

International Search Report (ISR) (and English translation thereof) dated Apr. 23, 2019 issued in International Application No. PCT/JP2019/008032.

International Search Report (ISR) (and English translation thereof) dated Jun. 4, 2019, issued in International Application No. PCT/JP2019/008034.

U.S. Appl. No. 17/184,784, First Named Inventor: Keisuke Ichikawa; Title: "Wide-Angle Optical System and Image Pickup Apparatus Using the Same"; Filed: Feb. 25, 2021.

U.S. Appl. No. 17/189,679, First Named Inventor: Takashi Fujikura; Title: "Wide-Angle Optical System and Image Pickup Apparatus Using the Same"; Filed: Mar. 2, 2021.

U.S. Appl. No. 17/190,453, First Named Inventor: Takashi Fujikura; Title: "Wide-Angle Optical System and Imaging Device Comprising Same"; Filed: Mar. 3, 2021.

Written Opinion dated Apr. 23, 2019 issued in International Application No. PCT/JP2019/008032.

Written Opinion dated Jun. 4, 2019, issued in International Application No. PCT/JP2019/008028.

Written Opinion dated Jun. 4, 2019, issued in International Application No. PCT/JP2019/008034.

Chinese Office Action (and English language translation thereof) dated Feb. 14, 2022, issued in counterpart. Chinese Application No. 201980056977.6.

International Preliminary Report on Patentability (IPRP) (and English language translation thereof) dated Sep. 16, 2021 issued in International Application No. PCT/JP2019/008028 (which is an International counterpart of related U.S. Appl. No. 17/190,453).

1 Non-Final Office Action dated Feb. 6, 2024, issued in related U.S. Appl. No. 17/189,679.

Japanese Office Action (and English language translation thereof) dated Apr. 20, 2022, issued in counterpart Japanese Application No. 2021-503242.

U.S. Appl. No. 17/184,784, filed Mar. 2, 2021.

U.S. Appl. No. 17/189,679, filed Mar. 2, 2021.

U.S. Appl. No. 17/190,453, filed Mar. 3, 2021.

International Preliminary Report on Patentability (IPRP) (and English language translation thereof) dated Sep. 16, 2021 issued in counterpart International Application No. PCT/JP2019/008033.

Japanese Office Action (and English language translation thereof) dated Mar. 30, 2022, issued in Japanese Application No. 2021-503240 (which is a Japanese counterpart of related U.S. Appl. No. 17/190,453).

Chinese Office Action (and English language translation thereof) dated Feb. 14, 2022, issued in Chinese Application No. 201980056267.3 (which is a counterpart of related U.S. Appl. No. 17/190,453).

Office Action (Non-Final Rejection) dated May 25, 2023, issued in related U.S. Appl. No. 17/190,453.

(56)

References Cited

OTHER PUBLICATIONS

International Search Report (ISR) (and English translation thereof) dated May 14, 2019 issued in International Application No. PCT/JP2019/008033.

Written Opinion dated May 14, 2019 issued in International Application No. PCT/JP2019/008033.

Notice of Allowance dated Apr. 10, 2024, issued in related U.S. Appl. No. 17/184,784.

* cited by examiner

FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15A FIG. 15B FIG. 15C FIG. 15D





FIG. 15E FIG. 15F FIG. 15G FIG. 15H



435.84 -----
486.13 -----
587.56 -----
656.27 -----

FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 16E




FIG. 16F




FIG. 16G




FIG. 16H




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 17D




FIG. 17E




FIG. 17F




FIG. 17G




FIG. 17H




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 18E




FIG. 18F




FIG. 18G




FIG. 18H




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D




FIG. 19E




FIG. 19F




FIG. 19G




FIG. 19H




FIG. 20A

SA
FNO 3.821




FIG. 20

AS
FIY 1.14




FIG. 20C

CC
FIY 1.14




FIG. 20D

DT
FIY 1.14




FIG. 20E

SA
FNO 3.775




FIG. 20F

AS
FIY 1.14




FIG. 20G

CC
FIY 1.14




FIG. 20H

DT
FIY 1.14




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 21D




FIG. 21E




FIG. 21F




FIG. 21G




FIG. 21H




FIG. 22A




FIG. 22B




FIG. 22C




FIG. 22D




FIG. 22E




FIG. 22F




FIG. 22G




FIG. 22H




FIG. 23A




FIG. 23B




FIG. 23C




FIG. 23D




FIG. 23E




FIG. 23F




FIG. 23G





FIG. 23H







FIG. 25A




FIG. 25B




FIG. 25C




FIG. 25D




FIG. 25E




FIG. 25F




FIG. 25G




FIG. 25H




FIG. 26A




FIG. 26B




FIG. 26C




FIG. 26D




FIG. 26E




FIG. 26F




FIG. 26G




FIG. 26H




FIG. 27A




FIG. 27B




FIG. 27C




FIG. 27D




FIG. 27E




FIG. 27F




FIG. 27G




FIG. 27H




FIG. 28A




FIG. 28B




FIG. 28C




FIG. 28D




FIG. 28E




FIG. 28F




FIG. 28G




FIG. 28H




FIG. 29




FIG. 30




FIG. 31




FIG. 32A




FIG. 32B





FIG. 33



1

**WIDE-ANGLE OPTICAL SYSTEM AND
IMAGE PICKUP APPARATUS USING THE
SAME**

CROSS-REFERENCE TO RELATED
APPLICATION

The present application is a continuation application of International Application No. PCT/JP2019/008033 filed on Mar. 1, 2019, the entire contents of which are incorporated herein by reference.

BACKGROUND

Technical Field

The present disclosure relates to a wide-angle optical system and an image pickup apparatus using the same.

As an optical system having a wide angle of view, an objective optical system for endoscope has been known. In the objective optical system for endoscope, a wide-angle optical system with the angle of view of more than 100 degrees has been used.

In conventional endoscopes, an image sensor with a small number of pixels was used. Therefore, in an objective optical system for endoscope, an optical system with a fixed focus was used. Even when the optical system with a fixed focus was used, it was possible to cover a range of an object distance required to be observed (observation depth), by a depth of field.

However, in recent years, for improving a quality of an observed image, an image sensor with a large number of pixels has been used. In an endoscope in which the image sensor with a large number of pixels is used, a high resolution is sought even for the optical system.

When an optical system is made to have a high resolution, the depth of field becomes narrower than the required observation depth. Consequently, it becomes difficult to observe the required observation depth in a focused state. For such reasons, a need arose to impart a function of adjusting a focal position to an optical system.

An objective optical system for endoscope which enables to adjust the focal position has been known. In this objective optical system for endoscope, an inner focusing has been used for adjusting the focal position. For carrying out the inner focusing, an actuator is provided around an optical system.

An optical unit, for instance, includes an optical system and an actuator. In an endoscope, it is necessary to seal the optical unit. Moreover, the angle of view is 140° or more, and there are restrictions on a size and an output of the actuator. Therefore, in the focal-position adjustment, it is difficult to move the optical system. A light-weight and space-saving inner focusing is necessary.

Objective optical systems for endoscope in which, the inner focusing is used, have been disclosed in International Unexamined Patent Application Publication No. 2014/129089 and International Unexamined Patent Application Publication No. 2016/067838.

Description of the Related Art

SUMMARY

A wide-angle optical system according to at least some embodiments of the present disclosure is a wide-angle optical system having a lens component,

2

the lens component has a plurality of optical surfaces, and in the lens component, two optical surfaces are in contact with air, and at least one optical surface is a curved surface, includes in order from an object side:

a first lens unit having a negative refractive power, a second lens unit having a positive refractive power, and a third lens unit having a positive refractive power, wherein

at the time of carrying out a focal-position adjustment from a far point to a near point, the second lens unit is moved from a first position toward a second position, the first position is a position at which a distance between the first lens unit and the second lens unit becomes the minimum, and the second position is a position at which a distance between the second lens unit and the third lens unit becomes the minimum, the third lens unit includes not less than three lens components,

not less than three lens components include a first lens component and a second lens component, the first lens component is a lens component located nearest to an object in the third lens unit, and the second lens component is a lens component located second from the object side in the third lens unit,

each of the first lens component and the second lens component has a positive refractive power, and following conditional expression (1) is satisfied:

$$0.8 < f3L12/fL < 6.0 \quad (1)$$

where,

f3L12 denotes a combined focal length of the first lens component and the second lens component, and fL denotes a focal length of the wide-angle optical system at the first position. surface.

Moreover, an image pickup apparatus of the present disclosure includes:

an optical system, and

an image sensor which is disposed on an image plane, wherein

the image sensor has an image pickup surface, and converts an image formed on the image pickup surface by the optical system to an electric signal, and the optical system is the abovementioned wide-angle optical system.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A and FIG. 1B are lens cross-sectional views of a wide-angle optical system of an example 1;

FIG. 2A and FIG. 2B are lens cross-sectional views of a wide-angle optical system of an example 2;

FIG. 3A and FIG. 3B are lens cross-sectional views of a wide-angle optical system of an example 3;

FIG. 4A and FIG. 4B are lens cross-sectional views of a wide-angle optical system of an example 4;

FIG. 5A and FIG. 5B are lens cross-sectional views of a wide-angle optical system of an example 5;

FIG. 6A and FIG. 6B are lens cross-sectional views of a wide-angle optical system of an example 6;

FIG. 7A and FIG. 7B are lens cross-sectional views of a wide-angle optical system of an example 7;

FIG. 8A and FIG. 8B are lens cross-sectional views of a wide-angle optical system of an example 8;

FIG. 9A and FIG. 9B are lens cross-sectional views of a wide-angle optical system of an example 9;

FIG. 10A and FIG. 10B are lens cross-sectional views of a wide-angle optical system of an example 10;

FIG. 11A and FIG. 11B are lens cross-sectional views of a wide-angle optical system of an example 11;

FIG. 12A and FIG. 12B are lens cross-sectional views of a wide-angle optical system of an example 12;

FIG. 13A and FIG. 13B are lens cross-sectional views of a wide-angle optical system of an example 13;

FIG. 14A and FIG. 14B are lens cross-sectional views of a wide-angle optical system of an example 14;

FIG. 15A, FIG. 15B, FIG. 15C, FIG. 15D, FIG. 15E, FIG. 15F, FIG. 15G, and FIG. 15H are aberration diagrams of the wide-angle optical system of the example 1;

FIG. 16A, FIG. 16B, FIG. 16C, FIG. 16D, FIG. 16E, FIG. 16F, FIG. 16G, and FIG. 16H are aberration diagrams of the wide-angle optical system of the example 2;

FIG. 17A, FIG. 17B, FIG. 17C, FIG. 17D, FIG. 17E, FIG. 17F, FIG. 17G, and FIG. 17H are aberration diagrams of the wide-angle optical system of the example 3;

FIG. 18A, FIG. 18B, FIG. 18C, FIG. 18D, FIG. 18E, FIG. 18F, FIG. 18G, and FIG. 18H are aberration diagrams of the wide-angle optical system of the example 4;

FIG. 19A, FIG. 19B, FIG. 19C, FIG. 19D, FIG. 19E, FIG. 19F, FIG. 19G, and FIG. 19H are aberration diagrams of the wide-angle optical system of the example 5;

FIG. 20A, FIG. 20B, FIG. 20C, FIG. 20D, FIG. 20E, FIG. 20F, FIG. 20G, and FIG. 20H are aberration diagrams of the wide-angle optical system of the example 6;

FIG. 21A, FIG. 21B, FIG. 21C, FIG. 21D, FIG. 21E, FIG. 21F, FIG. 21G, and FIG. 21H are aberration diagrams of the wide-angle optical system of the example 7;

FIG. 22A, FIG. 22B, FIG. 22C, FIG. 22D, FIG. 22E, FIG. 22F, FIG. 22G, and FIG. 22H are aberration diagrams of the wide-angle optical system of the example 8;

FIG. 23A, FIG. 23B, FIG. 23C, FIG. 23D, FIG. 23E, FIG. 23F, FIG. 23G, and FIG. 23H are aberration diagrams of the wide-angle optical system of the example 9;

FIG. 24A, FIG. 24B, FIG. 24C, FIG. 24D, FIG. 24E, FIG. 24F, FIG. 24G, and FIG. 24H are aberration diagrams of the wide-angle optical system of the example 10;

FIG. 25A, FIG. 25B, FIG. 25C, FIG. 25D, FIG. 25E, FIG. 25F, FIG. 25G, and FIG. 25H are aberration diagrams of the wide-angle optical system of the example 11;

FIG. 26A, FIG. 26B, FIG. 26C, FIG. 26D, FIG. 26E, FIG. 26F, FIG. 26G, and FIG. 26H are aberration diagrams of the wide-angle optical system of the example 12;

FIG. 27A, FIG. 27B, FIG. 27C, FIG. 27D, FIG. 27E, FIG. 27F, FIG. 27G, and FIG. 27H are aberration diagrams of the wide-angle optical system of the example 13;

FIG. 28A, FIG. 28B, FIG. 28C, FIG. 28D, FIG. 28E, FIG. 28F, FIG. 28G, and FIG. 28H are aberration diagrams of the wide-angle optical system of the example 14;

FIG. 29 is a diagram showing a schematic configuration of an endoscope system;

FIG. 30 is a diagram showing an arrangement of an optical system of an endoscope;

FIG. 31 is a diagram showing an arrangement of an optical system of an image pickup apparatus;

FIG. 32A is a diagram showing a schematic configuration of an image pickup apparatus;

FIG. 32B is a diagram showing orientations of images on an image sensor; and

FIG. 33 is a diagram showing a positional relationship of an object, an objective optical system, and an optical-path splitting element.

DETAILED DESCRIPTION

Prior to the explanation of examples, action and effect of embodiments according to certain aspects of the present

disclosure will be described below. In the explanation of the action and effect of the embodiments concretely, the explanation will be made by citing concrete examples. However, similar to a case of the examples to be described later, aspects exemplified thereof are only some of the aspects included in the present disclosure, and there exists a large number of variations in these aspects. Consequently, the present disclosure is not restricted to the aspects that will be exemplified.

A wide-angle optical system of the present embodiment is a wide-angle optical system having a lens component. The lens component has a plurality of optical surfaces, and in the lens component, two optical surfaces are in contact with air, and at least one optical surface is a curved surface. The wide-angle optical system includes in order from an object side, a first lens unit having a negative refractive power, a second lens unit having a positive refractive power, and a third lens unit having a positive refractive power. At the time of adjusting a focal-position from a far point to a near point, the second lens unit is moved from a first position toward a second position. The first position is a position at which a distance between the first lens unit and the second lens unit becomes the minimum, and the second position is a position at which a distance between the second lens unit and the third lens unit becomes the minimum. The third lens unit includes not less than three lens components, and not less than three lens components include a first lens component and a second lens component. The first lens component is a lens component located nearest to an object in the third lens unit, and the second lens component is a lens component located second from the object side in the third lens unit. Each of the first lens component and the second lens component has a positive refractive power, and following conditional expression (1) is satisfied:

$$0.8 < f_{3L12}/f_L < 6.0 \quad (1)$$

where,

f_{3L12} denotes a combined focal length of the first lens component and the second lens component, and

f_L denotes a focal length of the wide-angle optical system at the first position.

The wide-angle optical system of the present embodiment, for instance, is about a wide-angle optical system with an angle of view of more than 100 degrees. In recent years, with the debut of a high-resolution monitor and the like, regarding an image quality at the time of observation, a high image quality is being sought. The wide-angle optical system of the present embodiment is a wide-angle optical system which is capable of dealing with such requirement.

Moreover, the wide-angle optical system of the present embodiment is an optical system in which an inner focusing is used. Therefore, an actuator is disposed around an inner-focusing lens. In the wide-angle optical system of the present embodiment, even with the actuator disposed around the optical system, an outer diameter of the overall optical system is small. The wide-angle optical system of the present embodiment, while being an optical system having a wide angle of view, is an optical system in which a light-ray height is suppressed to be low over a long range of a central portion of the optical system.

The wide-angle optical system of the present embodiment is a wide-angle optical system having the lens component. The lens component has the plurality of optical surfaces. In the lens component, the two optical surfaces are in contact with air, and at least one optical surface is a curved surface. The lens component includes a single lens and a cemented lens for example.

5

Moreover, in the lens component, a lens and a plane parallel plate may have been cemented. In this case, one optical surface in contact with air is a lens surface, and the other optical surface in contact with air is a flat surface. A lens component in which a single lens and a plane parallel plate are cemented, is to be deemed as a single lens. A lens component in which a cemented lens and a plane parallel plate are cemented, is to be deemed as a cemented lens.

Moreover, a planoconvex lens and a planoconcave lens may have been cemented. In this case, a cemented surface is a curved surface and an optical surface in contact with air is a flat surface.

The surface on the object side of the lens component, out of the two optical surfaces in contact with air, is an optical surface located on the object side. A surface on an image side of the lens component, out of the two optical surfaces in contact with air, is an optical surface located on the image side. In a case in which the lens component is a cemented lens, a cemented surface is located between the surface on the object side and the surface on the image side.

The wide-angle optical system of the present embodiment includes in order from the object side, the first lens unit having a negative refractive power, the second lens unit having a positive refractive power, and the third lens unit having a positive refractive power. At the time of carrying out the focal-position adjustment from the far point to the near point, the second lens unit is moved from the first position toward the second position. The movement from the first position toward the second position is a movement in a direction in which the distance between the first lens unit and the second lens unit widens, and is a movement in a direction in which the distance between the second lens unit and the third lens unit shortens.

The first position is a position at which the distance between the first lens unit and the second lens unit becomes the minimum. At the first position, the second lens unit is located nearest to the object in a range of movement. At the first position, it is possible to focus to an object located at a far point.

The second position is a position at which the distance between the second lens unit and the third lens unit becomes the minimum. At the second position, the second lens unit is located nearest to an image in a range of movement. At the second position, it is possible to focus to an object located at a near point.

The third lens unit includes not less than three lens components. Not less than three lens components include the first lens component and the second lens component. The first lens component is a lens component located nearest to the object in the third lens unit. The second lens component is a lens component located second from the object side in the third lens unit.

In the wide-angle optical system of the present embodiment, each of the first lens component and the second lens component has a positive refractive power. Moreover, the wide-angle optical system of the present embodiment has an image-side lens component. Accordingly, it is possible to realize a wide-angle optical system in which an angle of view is large, and an aberration within a range of adjustment of the focal-position is corrected favorably, and which has a high resolution. Moreover, by the optical system having the high resolution, even when an image sensor with a large number of pixels is used, it is possible to acquire a sharp image corresponding to the large number of pixels.

The second lens unit is moved for the focal-position adjustment. An actuator is used for moving the second lens unit. The actuator is disposed near the second lens unit or

6

near the third lens unit. Therefore, it is necessary to provide a space for disposing the actuator near the second lens unit or near the third lens unit.

By disposing two lens components having a positive refractive power in the third lens unit, it is possible to lower a light-ray height over a wide range from the object side of the second lens unit up to a vicinity of a center of the third lens unit (hereinafter, referred to as 'predetermined range').

By satisfying conditional expression (1), it is possible to lower the light-ray height in the predetermined range. Consequently, it is possible to make small an outer diameter of the second lens unit and an outer diameter of a part of the third lens unit. As a result, it is possible to suppress an increase in an outer diameter of an optical unit even when the actuator is disposed.

By making the combined focal length of the first lens component and the second component small, it is possible to suppress the light-ray height to be low in the predetermined range. However, since a combined refractive power of the first lens component and the second lens component becomes large, an aberration becomes large. Therefore, it is preferable to set appropriately the combined focal length of the first lens component and the second lens component.

In a case in which a value exceeds an upper limit value of conditional expression (1), it becomes difficult to suppress the light-ray height to be low in the predetermined range. In a case in which the value falls below a lower limit value of conditional expression (1), correction of a spherical aberration and correction of a coma become difficult.

It is preferable that following conditional expression (1') be satisfied instead of conditional expression (1).

$$1.0 < f_{3L12}/f_L < 5.2 \quad (1')$$

Moreover, it is more preferable that following conditional expression (1'') be satisfied instead of conditional expression (1).

$$1.2 < f_{3L12}/f_L < 4.8 \quad (1'')$$

The wide-angle optical system of the present embodiment may have an image-side lens component. The image-side lens component, among the plurality of lens components, is a lens component located nearest to an image. The image-side lens component may be a single lens, and may be a lens component which is located nearest to the image among the plurality of lens components.

In a case in which the wide-angle optical system of the present embodiment includes the first lens unit, the second lens unit, and the third lens unit, the image-side lens component is a lens component located nearest to the image in the third lens unit.

In the wide-angle optical system of the present embodiment, it is preferable that not less than two diverging surfaces be disposed between a surface nearest to the object of the first lens component and a surface nearest to the image of the second lens component.

By making such arrangement, it is possible to maintain favorably the imaging performance while maintaining the light-ray height in the predetermined range low.

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit include not less than three cemented surfaces, and a value of a difference between refractive indices be not less than 0.25 at not less than three cemented surfaces respectively.

Here, the difference in refractive indices is a difference between an object-side refractive index and an image-side refractive index,

the object-side refractive index is a refractive index for a d-line of a medium which is located on an object side of the cemented surface, and which is adjacent to the cemented surface, and

the image-side refractive index is a refractive index for a d-line of a medium which is located on an image side of the cemented surface, and which is adjacent to the cemented surface.

By making such arrangement, it is possible to maintain favorably the imaging performance while maintaining the light-ray height in the predetermined range low.

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit include not less than four lens components, and have not less than two cemented surfaces for which a value of a difference in refractive index is not less than 0.25.

Here, the difference in refractive index is a difference between an object-side refractive index and an image-side refractive index, and

the object-side refractive index is a refractive index for the d-line of a medium which is located on the object side of a cemented surface, and which is adjacent to the cemented surface, and

the image-side refractive index is a refractive index for the d-line of a medium which is located on the image side of the cemented surface, and which is adjacent to the cemented surface.

By making such arrangement, it is possible to maintain favorably the imaging performance while maintaining the light-ray height in the predetermined range low.

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit include three, four, or five lens components having a positive refractive power.

By making such arrangement, it is possible to maintain favorably the imaging performance while maintaining the light-ray height in the predetermined range low.

In the wide-angle optical system of the present embodiment, it is preferable that a cemented lens located nearest to an image in the third lens unit include in order from the object side, a positive lens and a negative lens.

By making such arrangement, it is possible to maintain favorably the imaging performance while maintaining the light-ray height in the predetermined range low.

In the wide-angle optical system of the present embodiment, it is preferable that a single lens unit be disposed nearest to the image in the third lens unit, the single lens unit include two single lenses or three single lenses, a cemented lens be disposed adjacent to the single lens unit, on the object side of the single lens unit, and the cemented lens include in order from the object side, a positive lens and a negative lens.

By making such arrangement, it is possible to maintain favorably the imaging performance while maintaining the light-ray height in the predetermined range low.

In the wide-angle optical system of the present embodiment, it is preferable that one single lens be disposed nearest to the image in the third lens unit, a cemented lens be disposed adjacent to the single lens, on the object side of the single lens, and the cemented lens include in order from the object side, a positive lens and a negative lens.

By making such arrangement, it is possible to maintain favorably the imaging performance while maintaining the light-ray height in the third

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (2) be satisfied:

$$0.05 < fL/R31F < 1.20 \quad (2)$$

where,

R31F denotes a radius of curvature of a surface on the object side of the first lens component, and

fL denotes the focal length of the wide angle-optical system at the first position.

Conditional expression (2) is a conditional expression in which a convergence of a surface nearest to the object in the third lens unit is regulated. The first lens component is located nearest to the object in the third lens unit. Accordingly, conditional expression (2) is a conditional expression in which the convergence of a surface on the object side of the first lens component is regulated.

The larger the curvature of a lens surface, the stronger is the convergence of light rays at the lens surface. The surface on the object side of the first lens component is located nearest to the object in the third lens unit. By making a curvature of the surface on the object side of the first lens component of an appropriate size, it is possible to suppress the light-ray height at the third lens unit to be low.

In a case in which a value exceeds an upper limit value of conditional expression (2), the spherical aberration and the coma are susceptible to occur, or a manufacturing error sensitivity is susceptible to become high. Even when an image sensor with a large number of pixels is used, acquiring a sharp image corresponding to the large number of pixels becomes difficult. Moreover, securing the desired back focus also becomes difficult. In a case in which the value falls below a lower limit value of conditional expression (2), the light-ray height becomes high. Consequently, in a case in which the wide-angle optical system of the present embodiment is used for an optical system of an endoscope, a diameter of an insertion portion becomes large.

It is preferable that following conditional expression (2') be satisfied instead of conditional expression (2).

$$0.07 < fL/R31F < 0.85 \quad (2')$$

It is more preferable that following conditional expression (2'') be satisfied instead of conditional expression (2).

$$0.08 < fL/R31F < 0.75 \quad (2'')$$

An optical system which satisfies conditional expression (2) has a value smaller than an upper limit value. As the value for the optical system becomes smaller, it becomes easier to correct an aberration or it becomes easier to secure a desired back focus in that optical system.

For conditional expression (2), it is possible to set a favorable upper limit value. It is preferable to set the upper limit value to any of 0.60252, 0.55, 0.50, and 0.45. By making such arrangement, it is possible to carry out a favorable aberration correction.

In a case in which favorable aberration correction is to be prioritized, or in a case in which securing the desired back focus is to be prioritized, from 0.10 up to 0.40 can be said to the most appropriate range for conditional expression (2).

In a case in which securing a low light-ray height in the predetermined range is to be prioritized, from 0.35 up to 0.65 can be said to be the most appropriate range for conditional expression (2).

It is preferable that the wide-angle optical system of the present embodiment include an image-side lens component, the image-side lens component, among the plurality of lens components, be a lens component located nearest to the

image, the third lens unit include N number of cemented surfaces S_{Ni} ($i=1, 2, \dots, N$) between the first lens component and the image-side lens component, and following conditional expression (3) be satisfied:

$$-1.0 < fL \times \Sigma P_{SNi} < -0.05 \quad (3)$$

where,

P_{SNi} denotes a refractive power of the cemented surface S_{Ni} , and is expressed by following conditional expression (4)

$$P_{SNi} = (n_{SNi}' - n_{SNi}) / r_{SNi} \quad (4)$$

where,

n_{SNi} denotes a refractive index for the d-line of a medium located on the object side of the cemented surface S_{Ni} ,

n_{SNi}' denotes a refractive index for the d-line of a medium located on the image side of the cemented surface S_{Ni} ,

r_{SNi} denotes a radius of curvature near an optical axis of the cemented surface S_{Ni} , and

fL denotes the focal length of the wide-angle optical system at the first position.

Conditional expression (3) is a conditional expression in which the refractive power of the cemented surface in the third lens unit is regulated. In the predetermined range, it is necessary to maintain a state in which a light-beam diameter is thinned. On the other hand, securing a paraxial amount, such as, securing the focal length or securing the back focus, is significant.

For lowering the light-ray height in the predetermined range, in the third lens unit, the lens component located on the object side is made to have a strong convergence. For securing the paraxial amount, it is preferable to dispose a lens component having a strong divergence on an image side of the lens component located on the object side.

In the wide-angle optical system of the present embodiment, the third lens unit includes N number of cemented surfaces S_{Ni} . The cemented surface S_{Ni} has a strong divergence. Therefore, conditional expression (3) can be said to be a conditional expression in which the divergence of a light ray on the image side of the predetermined range is regulated.

In a case in which a value exceeds an upper limit value of conditional expression (3), the divergence of a light ray on the image side of the predetermined range becomes weak. Consequently, securing the desired paraxial amount becomes difficult or securing the low light-ray height in the predetermined range becomes difficult.

On the other hand, in a case in which the value falls below a lower limit value of conditional expression (3), a spherical aberration and a coma are susceptible to occur or a manufacturing error sensitivity is susceptible to become high. Even when an image sensor with a large number of pixels is used, it becomes difficult to acquire a sharp image corresponding to the large number of pixels.

It is preferable that following conditional expression (3') be satisfied instead of conditional expression (3).

$$-0.85 < fL \times \Sigma P_{SNi} < -0.1 \quad (3')$$

Moreover, it is more preferable that following conditional expression (3'') be satisfied instead of conditional expression (3).

$$-0.75 < fL \times \Sigma P_{SNi} < -0.1 \quad (3'')$$

For conditional expression (3), it is possible to set a favorable lower limit value. It is preferable to set the lower limit value to any of -0.71861 , -0.65 , -0.60 , and -0.55 . By

making such arrangement, it is possible to carry out a favorable aberration correction.

In a case in which favorable aberration correction is to be prioritized, from -0.50 up to -0.20 can be said to be the most appropriate range for conditional expression (3). In a case in which securing the low light-ray height in the predetermined range is to be prioritized, from -0.70 up to -0.40 can be said to be the most appropriate range for conditional expression (3).

By satisfying conditional expression (2) or by satisfying conditional expression (3), it is possible to secure the low light-ray height in the predetermined range or to secure the desired paraxial amount easily. It is even more preferable that both of conditional expression (2) and conditional expression (3) be satisfied.

However, when both of conditional expression (2) and conditional expression (3) are satisfied, correction of an astigmatism is susceptible to be difficult. Therefore, in the third lens unit, it is necessary to correct favorably the astigmatism as well.

As mentioned above, n_{SNi} and n_{SNi}' denote the refractive index. More elaborately, n_{SNi} denotes the refractive index for the d-line of the medium which is located on the object side of the cemented surface S_{Ni} and which is adjacent to the cemented surface S_{Ni} , and n_{SNi}' denotes the refractive index for the d-line of the medium which is located on the image side of the cemented surface S_{Ni} and which is adjacent to the cemented surface S_{Ni} .

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit include a cemented lens which is located nearest to the image among the cemented lenses, and a positive single lens which is located nearest to the image, the cemented lens which is located nearest to the image have a positive refractive power, and the positive single lens satisfy following conditional expression (5):

$$-2 < (R_{3R1} + R_{3R2}) / (R_{3R1} - R_{3R2}) < 2 \quad (5)$$

where,

R_{3R1} denotes a radius of curvature of a surface on the object side of the positive single lens, and

R_{3R2} denotes a radius of curvature of a surface on the image side of the positive single lens.

The third lens unit has the cemented lens which is located nearest to image (hereinafter, referred to as 'cemented lens A'). In a case in which there is one cemented lens disposed in the third lens unit, the cemented lens corresponds to the cemented lens A.

When an optical system is divided into two, an object side and an image side, with a center of the optical system as a boundary between the two, the cemented lens A is located on the image side. In a case in which significance is to be placed on securing an appropriate back focus, the refractive power of the cemented lens A may be made a positive refractive power.

In this case, not only in the object side of the optical system but also in the image side of the optical system, a large positive refractive power is required. For this, it is preferable to make the lens component located nearest to the image a positive single lens, as well as to satisfy conditional expression (5). By making such arrangement, it is possible to suppress the occurrence of astigmatism.

It is preferable that following conditional expression (5') be satisfied instead of conditional expression (5).

$$-1.5 < (R_{3R1} + R_{3R2}) / (R_{3R1} - R_{3R2}) < 1.0 \quad (5')$$

11

It is more preferable that following conditional expression (5'') be satisfied instead of conditional expression (5).

$$-1.1 < (R_{3R1} + R_{3R2}) / (R_{3R1} - R_{3R2}) < 0.0 \quad (5'')$$

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit include a cemented lens which is located nearest to the image among the cemented lenses, and a positive single lens which is located nearest to the image, the cemented lens which is located nearest to the image have a negative refractive power, and the positive single lens satisfy following conditional expression (6) be satisfied:

$$-5 < (R_{3R1} + R_{3R2}) / (R_{3R1} - R_{3R2}) < 1 \quad (6)$$

where,

R_{3R1} denotes a radius of curvature of a surface on the object side of the positive single lens, and

R_{3R2} denotes a radius of curvature of a surface on the image side of the positive single lens.

There is case in which significance is to be placed on shortening an overall length of the optical system, rather than on securing the appropriate back focus. In this case, since a large positive refractive power becomes necessary on the object side of the optical system, a large negative refractive power becomes necessary on the image side of the optical system.

The cemented lens A, among the cemented lenses, is located nearest to the image. Therefore, by making the refractive power of the cemented lens A a negative refractive power, it is possible to achieve a large negative refractive power on the image side. However, when such an arrangement is made, the astigmatism is susceptible to occur or an angle of emergence of an off-axis light ray is susceptible to become large.

In this case, it is preferable to make the lens component located nearest to the image a positive single lens, and to satisfy conditional expression (6). By making such arrangement, the positive single lens is disposed on a rear side of the cemented lens having a negative refractive power. Consequently, it is possible to cancel an increase in the astigmatism or to cancel an increase in the angle of emergence of the off-axis light ray.

In a case in which a value exceeds an upper limit value of conditional expression (6), the abovementioned cancellation effect is susceptible to become weak. In a case in which the value falls below a lower limit value of conditional expression (6), there is an increase in the occurrence of astigmatism or it is not possible to secure adequately an effective diameter of the positive single lens. When an attempt is made to secure adequately the effective diameter of the positive single lens, the back focus becomes excessively long. Consequently, the overall length of the optical system becomes long.

At the lens component located nearest to the image in the third lens unit, a light-ray height of the off-axis light ray is high. Consequently, when a cemented lens is used for this lens component, a thickness as a lens component is susceptible to increase. As a result, securing an adequate back focus or shortening the overall length of the optical system becomes difficult.

It is preferable that following conditional expression (6') be satisfied instead of conditional expression (6).

$$-4.7 < (R_{3R1} + R_{3R2}) / (R_{3R1} - R_{3R2}) < 0.8 \quad (6')$$

12

Moreover, it is more preferable that following conditional expression (6'') be satisfied instead of conditional expression (6).

$$-4.5 < (R_{3R1} + R_{3R2}) / (R_{3R1} - R_{3R2}) < 0.6 \quad (6'')$$

In the wide-angle optical system of the present embodiment, it is preferable that a cemented surface located nearest to the image in the third lens unit satisfy following conditional expression (7):

$$-2.0 < fL / r_{SNr} < 1.56 \quad (7)$$

where,

r_{SNr} denotes a radius of curvature near the optical axis of the cemented surface located nearest to the image, and

fL denotes the focal length of the wide-angle optical system at the first position.

On the image side of the predetermined range, it is preferable that the divergence of a light ray be strong. When the divergence of a light ray is strong, a light-ray height of an off-axis light ray is relatively high with respect to a light-ray height of an axial light ray.

When the light-ray height of an off-axis light ray becomes high, an astigmatism is susceptible to become large. For suppressing an increase in the astigmatism, it is preferable to make a cemented surface located nearest to the image in the third lens unit a shape concentric with respect to a pupil of an optical system. By satisfying conditional expression (7), it is possible to suppress the increase in the astigmatism.

In a case in which a value exceeds an upper limit value of conditional expression (7), it becomes difficult to carry out the correction of the astigmatism. In a case in which the value falls below a lower limit value of conditional expression (7), it becomes difficult to carry out the correction of the spherical aberration.

It is preferable that following conditional expression (7') be satisfied instead of conditional expression (7).

$$-1.2 < fL / r_{SNr} < 1.0 \quad (7')$$

Moreover, it is more preferable that following conditional expression (7'') be satisfied instead of conditional expression (7).

$$-0.9 < fL / r_{SNr} < 0.6 \quad (7'')$$

An optical system which satisfies conditional expression (7) has a value smaller than the upper limit value. As the value in the optical system becomes smaller, it becomes easy to correct the astigmatism in that optical system.

For conditional expression (7), it is possible to set a favorable upper limit value. It is preferable to set the upper limit value to any of -0.32190 , -0.35 , -0.40 , and -0.45 . By making such arrangement, it is possible to correct the astigmatism favorably.

In a case in which the correction of the astigmatism is to be prioritized, from -0.80 up to -0.50 can be said to be the most appropriate range for conditional expression (7). In a case in which the correction of the spherical aberration is to be prioritized, from -0.60 up to -0.30 can be said to be the most appropriate range for conditional expression (7).

At the cemented surface located nearest to the image in the third lens unit, it is preferable that a positive lens be located on the object side of the cemented surface, and a negative lens be located on the image side of the cemented surface.

As a means for simultaneously realizing suppression of the light-ray height in the predetermined range, aberration correction at the time of designing, and prevention of aberration deterioration at the time of manufacturing, improvement of the degree of freedom of a chromatic-

aberration correction is given. For improving the degree of freedom of the chromatic-aberration correction, an appropriate medium is to be used for the medium of a lens.

By setting appropriately a curvature and a thickness of a lens, it is possible to correct the spherical aberration, the coma, and the astigmatism favorably, and by selecting an appropriate glass for the medium of a lens, it is possible to correct the chromatic aberration favorably.

For instance, in an endoscope optical system, a thickness of each lens is large with respect to a focal length of the optical system. In such optical system, it is difficult to achieve both of the correction of longitudinal chromatic aberration and the correction of chromatic aberration of magnification, together.

However, in the wide-angle optical system of the present embodiment, the plurality of lens components is disposed in the third lens unit. Accordingly, it is possible to set appropriately the medium of the lens component located on the object side and the medium of the lens component located on the image side. As a result, it is possible to achieve both of the correction of the longitudinal chromatic aberration and the correction of the chromatic aberration of magnification, together.

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit include a plurality of positive lenses, the plurality of positive lenses include a first positive lens and a second positive lens, the first positive lens, among the plurality of positive lenses, be a positive lens located nearest to the object, the second positive lens, among the plurality of positive lenses, be a positive lens located second from the object, and following conditional expression (8) be satisfied:

$$-70 < v_{31P} - v_{32P} < 20 \quad (8)$$

where,

v_{31P} denotes an Abbe number for the first positive lens, and

v_{32P} denotes an Abbe number for the second positive lens.

Conditional expression (8) is a conditional expression in which a relationship of Abbe number for the first positive lens and Abbe number for the second positive lens is regulated. In a case of satisfying conditional expression (8), in a state of both the correction of the longitudinal chromatic aberration and the correction of the chromatic aberration of magnification achieved together, it becomes easy to satisfy various design conditions of an optical system.

In a case in which a value becomes large on a plus side, for instance, in a case in which the value exceeds an upper limit value of conditional expression (8), the longitudinal chromatic aberration varies in a direction of being corrected excessively, and the chromatic aberration of magnification varies in a direction of being corrected inadequately.

It is preferable that following conditional expression (8') be satisfied instead of conditional expression (8).

$$-65 < v_{31P} - v_{32P} < 15 \quad (8')$$

Moreover, it is more preferable that following conditional expression (8'') be satisfied instead of conditional expression (8).

$$-60 < v_{31P} - v_{32P} < 10 \quad (8'')$$

An optical system which satisfies conditional expression (8) has a value smaller than the upper limit value. As the value in the optical system becomes smaller, it becomes easy to correct the longitudinal chromatic aberration and the chromatic aberration of magnification in that optical system.

For conditional expression (8), it is possible to set a favorable upper limit value. It is preferable to set the upper limit value to any of 0, -5.0, -10.0, and -15.0. By making such arrangement, it is possible to correct the longitudinal chromatic aberration and the chromatic aberration of magnification favorably. Moreover, from -60.0 up to -20.0 can be said to be the most suitable range from conditional expression (8).

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit include a plurality of positive lenses, the plurality of positive lenses include a first positive lens, a second positive lens, and a third positive lens, the first positive lens, among the plurality of positive lenses, be a positive lens located nearest to the object, the second positive lens, among the plurality of positive lenses, be a positive lens located second from the object, the third positive lens, among the plurality of positive lenses, be a positive lens located third from the object, and following conditional expression (9) be satisfied:

$$-50 < v_{33P} - (v_{31P} + v_{32P}) / 2 < 80 \quad (9)$$

where,

v_{31P} denotes the Abbe number for the first positive lens, v_{32P} denotes the Abbe number for the second positive lens, and

v_{33P} denotes an Abbe number for the third positive lens.

Conditional expression (9) is a conditional expression in which a relationship between an average value of Abbe number for the first positive lens and Abbe number for the second positive lens, and Abbe number for the third positive lens is regulated. In a case of satisfying conditional expression (9), in a state of both the correction of the longitudinal chromatic aberration and the correction of the chromatic aberration of magnification achieved together, it becomes easy to satisfy various design conditions of an optical systems.

In a case in which a value becomes large on a minus side, for instance, in a case in which the value falls below a lower limit value of conditional expression (9), the longitudinal chromatic aberration varies in a direction of being corrected excessively, and the chromatic aberration of magnification varies in a direction of being corrected inadequately.

It is preferable that following conditional expression (9') be satisfied instead of conditional expression (9).

$$-40 < v_{33P} - (v_{31P} + v_{32P}) / 2 < 70 \quad (9')$$

Moreover, it is more preferable that following conditional expression (9'') be satisfied instead of conditional expression (9).

$$-35 \leq v_{33P} - (v_{31P} + v_{32P}) / 2 < 60 \quad (9'')$$

For conditional expression (9), it is possible to set a favorable lower limit value. It is preferable to set the lower limit value to any of -22.99, -15.0, -10.0 and -5.0. By making such arrangement, it is possible to correct the longitudinal chromatic aberration and the chromatic aberration of magnification favorably. Moreover, from 0.4 up to 40.0 can be said to be the most suitable range from conditional expression (9).

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit include a plurality of negative lenses, the plurality of negative lenses include a first negative lens and a second negative lens, the first negative lens, among the plurality of negative lenses, be a negative lens located nearest to the object, the second negative lens, among the plurality of negative lenses, be a

15

negative lens located second from the object, and following conditional expression (10) be satisfied:

$$-40 < v_{31N} - v_{32N} < 50 \quad (10)$$

where,

v_{31N} denotes an Abbe number for the first negative lens,
and

v_{32N} denotes an Abbe number for the second negative lens.

Conditional expression (10) is a conditional expression in which a relationship of Abbe number for the first negative lens and Abbe number for the second negative lens is regulated. In case of satisfying conditional expression (10), in a state of both the correction of the longitudinal chromatic aberration and the correction of the chromatic aberration of magnification achieved together, it becomes easy to satisfy various design conditions of an optical systems.

In a case in which a value becomes large on a minus side, for instance, in a case in which the value falls below a lower limit value of conditional expression (10), the longitudinal chromatic aberration varies in a direction of being corrected excessively, and the chromatic aberration of magnification varies in a direction of being corrected inadequately.

It is preferable that following conditional expression (10') be satisfied instead of conditional expression (10).

$$-25 < v_{31N} - v_{32N} < 40 \quad (10')$$

Moreover, it is more preferable that following conditional expression (10'') be satisfied instead of conditional expression (10).

$$-20 < v_{31N} - v_{32N} < 30 \quad (10'')$$

For conditional expression (10), it is possible to set a favorable lower limit value. It is preferable to set the lower limit value to any of -15.34, -12.0, -8.0, and -4.0. By making such arrangement, it is possible to correct the longitudinal chromatic aberration and the chromatic aberration of magnification favorably. Moreover, from 0.0 up to 20.0 can be said to be the most suitable range from conditional expression (10).

In a case in which there is one negative lens in the third lens unit, it is preferable that following conditional expression be satisfied:

$$-40 < v_N < 50$$

where,

v_N denotes Abbe's number for the negative lens.

In the wide-angle optical system of the present embodiment, it is preferable that the third lens unit be fixed at the time of carrying out the focal-position adjustment.

In the third lens unit, with respect to an aberration variation, a tendency of a manufacturing error sensitivity becoming high is strong. Even for a small manufacturing error, the aberration varies largely. Therefore, it is preferable to keep the third lens unit fixed at the time of carrying out the focal-position adjustment.

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (11) be satisfied:

$$-60 < (R21F + R21R) / (R21F - R21R) < 1 \quad (11)$$

where,

R21F denotes a radius of curvature of a surface on the object side of a predetermined lens component,

R21R denotes a radius of curvature of a surface on the image side of the predetermined lens component, and the predetermined lens component is a lens component located nearest to the object in the second lens unit.

16

In a case in which a value exceeds an upper limit value of conditional expression (11), a variation in the spherical aberration at the time of focal-position adjustment or a variation in the astigmatism is susceptible to become large.

In a case in which the value falls below a lower limit value of conditional expression (11), a deterioration of the astigmatism and a deterioration of the coma due to decentering are susceptible to occur. As mentioned above, the decentering occurs due to a movement of the second lens unit.

It is preferable that following conditional expression (11') be satisfied instead of conditional expression (11).

$$-40 < (R21F + R21R) / (R21F - R21R) < -1 \quad (11')$$

Moreover, it is more preferable that following conditional expression (11'') be satisfied instead of conditional expression (11).

$$-30 < (R21F + R21R) / (R21F - R21R) < -2 \quad (11'')$$

An optical system which satisfies conditional expression (11) has a value smaller than the upper limit value. As the value in the optical system becomes smaller, it becomes easier to correct the spherical aberration or the astigmatism at the time of focal-position adjustment more favorably in that optical system.

For conditional expression (11), it is possible to set a favorable upper limit value. It is preferable to set the upper limit value to any of 5.33106, 1.0, 0.0, and -1.0. Moreover, from -15.0 up to -2.0 can be said to be the most suitable range from conditional expression (11).

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (12) be satisfied:

$$0.2 < D21 / fL < 3.0 \quad (12)$$

where,

D21 denotes a distance on an optical axis between a surface nearest to the object and a surface nearest to the image of the second lens unit, and

fL denotes the focal length of the wide-angle optical system at the first position.

In a case in which a value exceeds an upper limit value of conditional expression (12), a weight of the second lens unit increases or the light-ray height becomes high. As just described, it is susceptible to become disadvantageous from a viewpoint of suppressing the increase in the weight of the second lens unit or suppressing the increase in the light-ray height.

In a case in which the value falls below a lower limit value of conditional expression (12), it becomes difficult to achieve two controls. One control is suppressing the variation in the spherical aberration at the time of focal-position adjustment or suppressing the variation in the astigmatism. The other control is suppressing the deterioration of the coma due to decentering or suppressing the deterioration of the astigmatism. The decentering occurs due to a movement of a moving unit at the time of focal-position adjustment.

It is preferable that following conditional expression (12') be satisfied instead of conditional expression (12).

$$0.3 < D21 / fL < 2.5 \quad (12')$$

Moreover, it is more preferable that following conditional expression (12'') be satisfied instead of conditional expression (12).

$$0.4 < D21 / fL < 2.0 \quad (12'')$$

An optical system which satisfies conditional expression (12) has a value larger than the lower limit value. As the

value in the optical system becomes larger, it becomes easier to achieve both of the abovementioned controls in that optical system.

For conditional expression (12), it is possible to set a favorable lower limit value. It is preferable to set the lower limit value to any of 0.54857, 0.56, 0.58, and 0.60. Moreover, from 0.60 up to 1.5 can be said to be the most appropriate range for conditional expression (12).

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (13) be satisfied:

$$1.01 < \beta 2F < 1.35 \quad (13)$$

where,

$\beta 2F$ denotes a magnification of the second lens unit at the first position.

In a case in which a value exceeds an upper limit value of conditional expression (13), an amount of focus movement with respect to the amount of movement of the second lens unit (hereinafter, referred to as 'focusing sensitivity') becomes excessively high. In this case, an accuracy at the time of stopping the second lens unit (hereinafter, referred to as 'stopping accuracy') becomes excessively high. Consequently, a moving mechanism becomes complicated.

In a case in which a value falls below a lower limit value of conditional expression (13), the focusing sensitivity is susceptible to become low. In this case, since the amount of movement of the second lens unit increases, a space for the movement has to be made wide. Consequently, an optical unit becomes large.

It is preferable that following conditional expression (13') be satisfied instead of conditional expression (13).

$$1.03 < \beta 2F < 1.30 \quad (13')$$

Moreover, it is more preferable that following conditional expression (13'') be satisfied instead of conditional expression (13').

$$1.05 < \beta 2F < 1.25 \quad (13'')$$

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (14) be satisfied:

$$1.01 < \beta 2N / \beta 2F < 1.15 \quad (14)$$

where,

$\beta 2F$ denotes the magnification of the second lens unit at the first position, and

$\beta 2N$ denotes a magnification of the second lens unit at the second position.

In a case in which conditional expression (14) is satisfied, since a focal length at a far point becomes short, it is possible to secure a wide angle of view at a far point. Moreover, since a focal length at a near point becomes long, it is possible to achieve a high magnification at a near point.

An optical system having a wide angle of view at a far point and a high magnification at a near point is appropriate for an optical system of an endoscope. Therefore, it is possible to use the wide-angle optical system of the present embodiment as an optical system for an endoscope.

In an endoscope, for instance, by observing a wide range, it is checked if there is a lesion part. Moreover, when it is confirmed that there is a lesion part, the lesion part is magnified and observed in detail. Therefore, it is preferable that an optical system of an endoscope have a wide angle of view for a far-point observation, and have a high magnification for a near-point observation.

Moreover, in the near-point observation, it is necessary to observe a lesion part in detail. Therefore, in an optical system for an endoscope, it is preferable to have an ability to focus with a high accuracy.

In a case in which a value exceeds an upper limit value of conditional expression (14), the focusing sensitivity at a near-point side becomes high. In this case, the stopping accuracy at the near-point side becomes high. Consequently, it becomes difficult to focus with high accuracy. In a case in which the value falls below a lower limit value of conditional expression (14), securing a wide-angle of view in the far-point observation and securing a high magnification in the near-point observation become difficult. Consequently, it becomes inappropriate for an optical system of an endoscope.

It is preferable that following conditional expression (14') be satisfied instead of conditional expression (14).

$$1.02 < \beta 2N / \beta 2F < 1.12 \quad (14')$$

Moreover, it is more preferable that following conditional expression (14'') be satisfied instead of conditional expression (14').

$$1.03 < \beta 2N / \beta 2F < 1.09 \quad (14'')$$

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (15) be satisfied:

$$0.08 < (1 - \beta 2F^2) \times \beta 3F^2 < 0.45 \quad (15)$$

where,

$\beta 2F$ denotes the magnification of the second lens unit at the first position, and

$\beta 3F$ denotes a magnification of the third lens unit at the first position.

In a case in which a value exceeds an upper limit value of conditional expression (15), the focusing sensitivity at the far-point side becomes excessively high. In this case, the stopping accuracy at the far-point side becomes high. In a case in which the value falls below a lower limit value of conditional expression (15), the focusing sensitivity at the far-point side is susceptible to become low. In this case, since the amount of movement of the second lens unit increases, the space for the movement has to be made wide. Consequently, the optical unit becomes large.

It is preferable that following conditional expression (15') be satisfied instead of conditional expression (15).

$$0.11 < (1 - \beta 2F^2) \times \beta 3F^2 < 0.35 \quad (15')$$

Moreover, it is more preferable that following conditional expression (15'') be satisfied instead of conditional expression (15').

$$0.13 < (1 - \beta 2F^2) \times \beta 3F^2 < 0.30 \quad (15'')$$

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (16) be satisfied:

$$0.15 < (1 - \beta 2N^2) \times \beta 3N^2 < 0.55 \quad (16)$$

where,

$\beta 2N$ denotes the magnification of the second lens unit at the second position, and

$\beta 3N$ denotes a magnification of the third lens unit at the second position.

In a case in which a value exceeds an upper limit value of conditional expression (16), the focusing sensitivity at the near-point side becomes excessively high. In this case, the stopping accuracy at the near-point side becomes high. In a case in which the value falls below a lower limit value of

19

conditional expression (16), the focusing sensitivity at the near-point side is susceptible to become low. In this case, since the amount of movement of the second lens unit increases, the space for the movement has to be made wide.

It is preferable that following conditional expression (16') be satisfied instead of conditional expression (16).

$$0.20 < (1 - \beta 2N^2) \times \beta 3N^2 < 0.45 \quad (16')$$

Moreover, it is more preferable that following conditional expression (16'') be satisfied instead of conditional expression (16).

$$0.22 < (1 - \beta 2N^2) \times \beta 3N^2 < 0.40 \quad (16'')$$

In the wide-angle optical system of the present embodiment, it is preferable that the second lens unit include only a positive lens.

By making such arrangement, it is possible to reduce the variation in the astigmatism at the time of focal-position adjustment.

In the wide-angle optical system of the present embodiment, it is preferable that the first lens unit include only a negative lens, and the negative lens have Abbe number larger than Abbe number for a positive lens nearest to the object in the third lens unit

It is not necessary to dispose an actuator in the first lens unit. However, for securing a wide angle of view, an outer diameter of the first lens unit is susceptible to become large. For making the outer diameter of the first lens unit small, a negative refractive power of the first lens unit is to be made large. When the negative refractive power of the first lens unit is made large, an off-axis aberration, particularly the astigmatism, is susceptible to occur.

By disposing the plurality of negative lenses in the first lens unit, it is possible to distribute the negative refractive power of the first lens unit to the plurality of negative lenses. As a result, even when the negative refractive power of the first lens unit is made large, it is possible to correct the off-axis aberration, particularly the astigmatism, favorably.

For making the light-ray height low in an optical system having an extremely wide angle of view, shortening a distance from a surface of incidence up to an entrance-pupil position as much as possible is effective. For this, not disposing a lens which corrects a chromatic aberration in the first lens unit may be one of the options. In a case in which a lens which corrects the chromatic aberration is not disposed in the first lens unit, the first lens unit includes only the single lens.

In this case, the chromatic aberration of magnification is susceptible to occur in the first lens unit. However, it is possible to correct the chromatic aberration of magnification which occurred in the first lens unit, in the third lens unit. At this time, Abbe number for the negative single lens in the first lens unit is to be made larger than Abbe number for the positive lens nearest to the object in the third lens unit.

The positive lens nearest to the object in the third lens unit is located at a distance closest from the negative lens in the first lens unit. Consequently, correction of the chromatic aberration of magnification becomes possible without the longitudinal chromatic aberration being deteriorated. In a case in which Abbe number for the negative lens in the first lens unit is smaller than Abbe number for the positive lens nearest to the object in the third lens unit, it becomes difficult to carry out correction of the longitudinal chromatic aberration and correction of the chromatic aberration of magnification simultaneously.

In the wide-angle optical system of the present embodiment, it is preferable that first lens unit include a plurality of

20

negative lens components, the plurality of negative lens components include a first negative lens component and a second negative lens component, the second negative lens component, among the plurality of negative lens components, be a negative lens component located second from the object, and following conditional expression (17) be satisfied:

$$-2.0 < fL/R12F_a < 5.0 \quad (17)$$

where,

R12F_a denotes a radius of curvature of a surface on the object side of the second negative lens component, and fL denotes the focal length of the wide-angle optical system at the first position.

Since the wide-angle optical system of the present embodiment has a wide angle of view, it is possible to use it for an optical system of an endoscope. In an optical system of an endoscope, from the viewpoint of securing the angle of view, constraints of the aberration correction, and constraints of cleaning, a surface nearest to the object becomes a flat surface or a surface convex toward the object side. Therefore, in the negative lens which is located second from the object side, it is preferable to make an object-side surface a strong diverging surface.

In a case in which a value exceeds an upper limit value of conditional expression (17), the light-ray height in the first lens unit is susceptible to become high. In a case in which the value falls below a lower limit value of conditional expression (17), the astigmatism is susceptible to occur.

The second negative lens component, for instance, is a single lens having a negative refractive power located second from the object or a cemented lens having a negative refractive power located second from the object. In a case in which the second negative lens component is a cemented lens, the cemented lens is formed by a positive lens and a negative lens. The positive lens may be located on the object side and the negative lens may be located on the object side.

It is preferable that following conditional expression (17') be satisfied instead of conditional expression (17).

$$-0.8 < fL/R12F_a < 0.2 \quad (17')$$

Moreover, it is more preferable that following conditional expression (17'') be satisfied instead of conditional expression (17).

$$-0.6 < fL/R12F_a < 0.0 \quad (17'')$$

In the wide-angle optical system of the present embodiment, it is preferable that the first lens unit include a fourth lens component and a fifth lens component, the fourth lens component be a lens component located nearest to the object in the first lens unit, the fifth lens component be a lens component located second from the object side in the first lens unit, the fourth lens component include a negative lens component, the fifth lens component include a cemented lens, and following conditional expression (18) be satisfied:

$$-1.0 < fL/R12F_b < 0.5 \quad (18)$$

where,

R12F_b denotes a radius of curvature of a surface on the object side of the fifth lens component, and

fL denotes the focal length of the wide-angle optical system at the first position.

As mentioned above, in an optical system of an endoscope, the surface located nearest to the object becomes a flat surface or a surface convex toward the object side. Therefore, in the negative lens which located third from the object side, it is preferable to make an object-side surface a strong diverging surface.

21

In a case in which a value exceeds an upper limit value of conditional expression (18), the light-ray height in the first lens unit is susceptible to become high. In a case in which the value falls below a lower limit value of conditional expression (18), the astigmatism is susceptible to occur.

It is preferable that following conditional expression (18') be satisfied instead of conditional expression (18).

$$-0.8 < fL/R12F_b < 0.2 \quad (18')$$

Moreover, it is more preferable that following conditional expression (18'') be satisfied instead of conditional expression (18).

$$-0.6 < fL/R12F_b < 0.0 \quad (18'')$$

In the wide-angle optical system of the present embodiment, it is preferable that the first lens unit include a fourth lens component, a fifth lens component, and a sixth lens component, the fourth lens component be a lens component located nearest to the object in the first lens unit, the fifth lens component be a lens component located second from the object side in the first lens unit, the sixth lens component be a lens component located third from the object side in the first lens unit, the fourth lens component include a negative lens component, the fifth lens component include a negative lens component, and the sixth lens component include a positive lens component, and following conditional expression (19) be satisfied:

$$-1.0 < fL/R12F_e < 0.4 \quad (19)$$

where,

R12F_e denotes a radius of curvature of a surface on the object side of the fifth lens component, and fL denotes the focal length of the wide-angle optical system at the first position.

As mentioned above, in an optical system for an endoscope, the surface located nearest to the object becomes a flat surface or a surface convex toward the object side. Therefore, in the negative lens which is located second from the object side, it is preferable to make an object-side surface a strong diverging surface.

In a case in which a value exceeds an upper limit value of conditional expression (19), the light-ray height in the first lens unit is susceptible to become high. In a case in which the value falls below a lower limit value of conditional expression (19), the astigmatism is susceptible to occur.

It is preferable that following conditional expression (19') be satisfied instead of conditional expression (19).

$$-0.8 < fL/R12F_e < 0.2 \quad (19')$$

Moreover, it is more preferable that following conditional expression (19'') be satisfied instead of conditional expression (19).

$$-0.6 < fL/R12F_e < 0.0 \quad (19'')$$

In the wide-angle optical system of the present embodiment, it is preferable that the first lens unit include a fourth lens component, a fifth lens component, and a sixth lens component, the fourth lens component be a lens component located nearest to the object in the first lens unit, the fifth lens component be a lens component located second from the object side in the first lens unit, the sixth lens component be a lens component located third from the object side in the first lens unit, the fourth lens component include a negative lens component, the fifth lens component include a lens component for which an absolute value of refractive power is smaller than an absolute value of a refractive power of the

22

fourth lens component, the sixth lens component include a cemented lens, and following conditional expression (20) be satisfied:

$$-1.2 < fL/R12F_a < 0.2 \quad (20)$$

where,

R12F_a denotes a radius of curvature of a surface on the object side of the sixth lens component, and

fL denotes the focal length of the wide-angle optical system at the first position.

As mentioned above, in an optical system of an endoscope, the surface located nearest to the object becomes a flat surface or a surface convex toward the object side. Therefore, in the negative lens which located third from the object side, it is preferable to make an object-side surface a strong diverging surface.

In a case in which a value exceeds an upper limit value of conditional expression (20), the light-ray height in the first lens unit is susceptible to become high. In a case in which the value falls below a lower limit value of conditional expression (20), the astigmatism is susceptible to occur.

It is preferable that following conditional expression (20') be satisfied instead of conditional expression (20).

$$-0.9 < fL/R12F_a < 0.0 \quad (20')$$

Moreover, it is more preferable that following conditional expression (20'') be satisfied instead of conditional expression (20).

$$-0.6 < fL/R12F_a < -0.2 \quad (20'')$$

In the wide-angle optical system of the present embodiment, it is preferable that the first lens unit include a fourth lens component and a fifth lens component, the fourth lens component be a lens component located nearest to the object in the first lens unit, the fifth lens component be a lens component located second from the object side in the first lens unit, and following conditional expression (21) be satisfied:

$$-1.0 < fL/fL12 < 0.4 \quad (21)$$

where,

fL12 denotes a focal length of the fifth lens component, and

fL denotes the focal length of the wide-angle optical system at the first position.

In a case in which a value exceeds an upper limit value of conditional expression (21), it is not possible to achieve much effect of size reduction of the fourth component. In a case in which the value falls below a lower limit value of conditional expression (21), it is not possible to achieve much effect of correction of the off-axis aberration.

It is preferable that following conditional expression (21') be satisfied instead of conditional expression (21).

$$-0.7 < fL/fL12 < 0.2 \quad (21')$$

Moreover, it is more preferable that following conditional expression (21'') be satisfied instead of conditional expression (21).

$$-0.6 < fL/fL12 < 0.16 \quad (21'')$$

It is preferable that the wide-angle optical system of the present embodiment include an image-side lens component, the image-side lens component, among the plurality of lens components, be a lens component located nearest to an image, and following conditional expression (22) be satisfied:

$$100 \times |f_{fm}| < |R_{fm}| \quad (22)$$

where,

f_{in} denotes a focal length of an image-side lens component, and

R_{fin} denotes a radius of curvature of a surface on the image side of the image-side lens component.

In an optical system, an optical element having a zero refractive power is disposed between an image-side lens component and an image plane in many cases. An optical element having zero refractive power is an optical filter or a prism, for example. In a case in which conditional expression (22) is satisfied, it becomes easier both of securing a space for disposing the optical element having a zero refractive power and favorable correction of ng achieve both of the astigmatism.

In conditional expression (5) and conditional expression (6), for the lens component located nearest to the image, the radius of curvature of the surface is regulated. In conditional expression (22), for the image-side lens component, the radius of curvature of the surface is regulated. The image-side lens component is a lens component located nearest to the image. Accordingly, conditional expression (22), practically, can be said to be a conditional expression regulating conditional expression (5) and conditional expression (6).

It is preferable that the wide-angle optical system of the present embodiment include the image-side lens component and an optical element having zero refractive power, wherein the image-side lens component, among the plurality of lens components, be a lens component located nearest to the image, the optical element be located on the image side of the image-side lens component, and the image-side lens component and the optical element be cemented.

In an optical system, an optical element having a zero refractive power is disposed between an image-side lens component and an image plane in many cases. An optical element having zero refractive power is an optical filter or a prism, for example. By cementing the image-side lens component and the optical element, it is possible to prevent degradation of an imaging performance due to decentering.

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (23) be satisfied:

$$2 \times y_{max} < fL \times \tan \omega_{max} \quad (23)$$

where,

y_{max} denotes a maximum image height,

ω_{max} denotes an angle of view corresponding to the maximum image height, and

fL denotes the focal length of the wide-angle optical system at the first position.

The wide-angle optical system of the present embodiment is an optical system which has a high resolution and a small outer diameter, and an actuator necessary for the focal-position adjustment disposed therein. Accordingly, it is possible to use the wide-angle optical system of the present embodiment for an optical system of an endoscope.

For using the wide-angle optical system of the present embodiment for an optical system of an endoscope, it is preferable that an angle of view of not less than 100 degrees be secured, for instance. In an optical system having an angle of view of not less than 100 degrees, an occurrence of a distortion is acceptable. Accordingly, such optical system does not satisfy following expression (A). Expression (A) is a condition with no distortion.

$$Y_{max} = fL \times \tan \omega_{max} \quad (A)$$

Instead, the wide-angle optical system of the present embodiment satisfies conditional expression (23). By satis-

fying conditional expression (23), it is possible to make an outer diameter of an optical unit small while securing a wide angle of view. Accordingly, it is possible to use the wide-angle optical system of the present embodiment for an optical system of an endoscope.

In the wide-angle optical system of the present embodiment, it is preferable that following conditional expression (24) be satisfied:

$$ER2 < 4 \times fL / F_{EX} \quad (24)$$

where,

ER2 denotes an effective radius of a surface nearest to the image of the second lens component,

F_{EX} denotes an effective F-value at the first position, and fL denotes the focal length of the wide-angle optical system at the first position.

Conditional expression (24) is a conditional expression related to the light-ray height. By satisfying conditional expression (24), it is possible to use the wide-angle optical system of the present embodiment for an optical system of an endoscope. The effective radius is determined by the height of an outermost light ray in a plane.

An image pickup apparatus of the present embodiment includes an optical system, and an image sensor which is disposed on an image plane, wherein the image sensor has an image pickup surface, and converts an image formed on the image pickup surface by the optical system to an electric signal, and the optical system is the abovementioned wide-angle optical system.

According to the image pickup apparatus of the present embodiment, even when an image sensor with a large number of pixels is used, it is possible to acquire a sharp image corresponding to the large number of pixels.

Embodiments and examples of a wide-angle optical system will be described below in detail by referring to the accompanying diagrams. However, the present disclosure is not restricted to the embodiments and the examples described below.

Lens cross-sectional views of each example will be described below.

FIG. 1A, FIG. 2A, FIG. 3A, FIG. 4A, FIG. 5A, FIG. 6A, FIG. 7A, FIG. 8A, FIG. 9A, FIG. 10A, FIG. 11A, FIG. 12A, FIG. 13A, and FIG. 14A are cross-sectional views at a far point.

FIG. 1B, FIG. 2B, FIG. 3B, FIG. 4B, FIG. 5B, FIG. 6B, FIG. 7B, FIG. 8B, FIG. 9B, FIG. 10B, FIG. 11B, FIG. 12B, FIG. 13B, and FIG. 14B are cross-sectional views at a near point.

A first lens unit is denoted by G1, a second lens unit is denoted by G2, a third lens unit is denoted by G3, an aperture stop is denoted by S, a filter is denoted by F, a cover glass is denoted by C, a prism is denoted by P, and an image plane (image pickup surface) is denoted by I.

Aberration diagrams of each example will be described below. Aberration diagrams are shown in order of aberration diagrams at a far point and aberration diagrams at a near point.

Aberration diagrams at a far point are as follow.

FIG. 15A, FIG. 16A, FIG. 17A, FIG. 18A, FIG. 19A, FIG. 20A, FIG. 21A, FIG. 22A, FIG. 23A, FIG. 24A, FIG. 25A, FIG. 26A, FIG. 27A, and FIG. 28A show a spherical aberration (SA).

FIG. 15B, FIG. 16B, FIG. 17B, FIG. 18B, FIG. 19B, FIG. 20B, FIG. 21B, FIG. 22B, FIG. 23B, FIG. 24B, FIG. 25B, FIG. 26B, FIG. 27B, and FIG. 28B show an astigmatism (AS).

25

FIG. 15C, FIG. 16C, FIG. 17C, FIG. 18C, FIG. 19C, FIG. 20C, FIG. 21C, FIG. 22C, FIG. 23C, FIG. 24C, FIG. 25C, FIG. 26C, FIG. 27C, and FIG. 28C show a chromatic aberration of magnification (CC).

FIG. 15D, FIG. 16D, FIG. 17D, FIG. 18D, FIG. 19D, FIG. 20D, FIG. 21D, FIG. 22D, FIG. 23D, FIG. 24D, FIG. 25D, FIG. 26D, FIG. 27D, and FIG. 28D show a distortion (DT).

Aberration diagrams at a near point are as follow.

FIG. 15E, FIG. 16E, FIG. 17E, FIG. 18E, FIG. 19E, FIG. 20E, FIG. 21E, FIG. 22E, FIG. 23E, FIG. 24E, FIG. 25E, FIG. 26E, FIG. 27E, and FIG. 28E show a spherical aberration (SA).

FIG. 15F, FIG. 16F, FIG. 17F, FIG. 18F, FIG. 19F, FIG. 20F, FIG. 21F, FIG. 22F, FIG. 23F, FIG. 24F, FIG. 25F, FIG. 26F, FIG. 27F, and FIG. 28F show an astigmatism (AS).

FIG. 15G, FIG. 16G, FIG. 17G, FIG. 18G, FIG. 19G, FIG. 20G, FIG. 21G, FIG. 22G, FIG. 23G, FIG. 24G, FIG. 25G, FIG. 26G, FIG. 27G, and FIG. 28G show a chromatic aberration of magnification (CC).

FIG. 15H, FIG. 16H, FIG. 17H, FIG. 18H, FIG. 19H, FIG. 20H, FIG. 21H, FIG. 22H, FIG. 23H, FIG. 24H, FIG. 25H, FIG. 26H, FIG. 27H, and FIG. 28H show a distortion (DT).

A wide-angle optical system of an example 1 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a biconcave negative lens L2, and a biconvex positive lens L3.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a biconvex positive lens L5, a negative meniscus lens L6 having a convex surface directed toward an image side, a biconvex positive lens L7, a biconcave negative lens L8, a negative meniscus lens L9 having a convex surface directed toward the object side, a biconvex positive lens L10, a biconvex positive lens L11, and a negative meniscus lens L12 having a convex surface directed toward the image side.

The biconvex positive lens L5 and the negative meniscus lens L6 are cemented. The biconvex positive lens L11 and the negative meniscus lens L12 are cemented.

A filter F is disposed in the first lens unit G1. An aperture stop S is disposed between the second lens unit G2 and the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 2 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a biconcave negative lens L2, and a positive meniscus lens L3 having a convex surface directed toward the object side.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a positive meniscus lens L5 having a convex surface directed toward the object side, a negative meniscus lens L6 having a convex surface

26

directed toward the object side, a biconvex positive lens L7, a positive meniscus lens L8 having a convex surface directed toward an image side, a biconcave negative lens L9, a positive meniscus lens L10 having a convex surface directed toward the image side, and a biconvex positive lens L11.

The negative meniscus lens L6 and the biconvex positive lens L7 are cemented. The positive meniscus lens L8 and the biconcave negative lens L9 are cemented.

A filter F is disposed in the first lens unit G1. An aperture stop S is disposed between the second lens unit G2 and the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 3 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a negative meniscus lens L1 having a convex surface directed toward the object side, a biconcave negative lens L2, and a positive meniscus lens L3 having a convex surface directed toward the object side.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a positive meniscus lens L5 having a convex surface directed toward the object side, a biconcave negative lens L6, a biconvex positive lens L7, a positive meniscus lens L8 having a convex surface directed toward an image side, a biconcave negative lens L9, a biconvex positive lens L10, and a positive meniscus lens L11 having a convex surface directed toward the object side.

The biconcave negative lens L6 and the biconvex positive lens L7 are cemented. The positive meniscus lens L8 and the biconcave negative lens L9 are cemented.

A filter F is disposed in the first lens unit G1. An aperture stop S is disposed between the second lens unit G2 and the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 4 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a negative meniscus lens L1 having a convex surface directed toward the object side, a biconcave negative lens L2, and a positive meniscus lens L3 having a convex surface directed toward the object side.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a positive meniscus lens L5 having a convex surface directed toward the object side, a negative meniscus lens L6 having a convex surface directed toward the object side, a biconvex positive lens L7, a biconvex positive lens L8, a biconcave negative lens L9, a biconvex positive lens L10, and a positive meniscus lens L11 having a convex surface directed toward the object side.

The negative meniscus lens L6 and the biconvex positive lens L7 are cemented. The biconvex positive lens L8 and the biconcave negative lens L9 are cemented.

A filter F is disposed in the first lens unit G1. An aperture stop S is disposed between the second lens unit G2 and the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 5 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a negative meniscus lens L1 having a convex surface directed toward the object side, a biconcave negative lens L2, and a positive meniscus lens L3 having a convex surface directed toward the object side.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a positive meniscus lens L5 having a convex surface directed toward the object side, a biconvex positive lens L6, a negative meniscus lens L7 having a convex surface directed toward an image side, a biconvex positive lens L8, a biconcave negative lens L9, a positive meniscus lens L10 having a convex surface directed toward the image side, a biconvex positive lens L11, and a planoconvex positive lens L12.

The biconvex positive lens L6 and the negative meniscus lens L7 are cemented. The biconvex positive lens L8 and the biconcave negative lens L9 are cemented.

A filter F is disposed between the first lens unit G1 and the second lens unit G2. An aperture stop S is disposed in the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3. The planoconvex positive lens L12 and the cover glass C are cemented.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 6 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a negative meniscus lens L1 having a convex surface directed toward the object side, a negative meniscus lens L2 having a convex surface directed toward an image side, and a positive meniscus lens L3 having a convex surface directed toward the image side.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a biconvex positive lens L5, a negative meniscus lens L6 having a convex surface directed toward the image side, a biconvex positive lens L7, a negative meniscus lens L8 having a convex surface directed toward the object side, a positive meniscus lens L9 having a convex surface directed toward the object side, a biconvex positive lens L10, a negative meniscus lens L11 having a convex surface directed toward the image side, a negative meniscus lens L12 having a convex surface directed toward the image side, a negative meniscus lens L13 having a convex surface directed toward the object side, and a planoconvex positive lens L14.

The biconvex positive lens L5 and the negative meniscus lens L6 are cemented. The negative meniscus lens L8 and

the positive meniscus lens L9 are cemented. The biconvex positive lens L10 and the negative meniscus lens L11 are cemented.

A filter F is disposed in the first lens unit G1. An aperture stop S is disposed in the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3. The planoconvex positive lens L14 and the cover glass C are cemented.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 7 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a biconcave negative lens L2, and a positive meniscus lens L3 having a convex surface directed toward the object side. The biconcave negative lens L2 and the positive meniscus lens L3 are cemented.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a negative meniscus lens L5 having a convex surface directed toward the object side, a biconvex positive lens L6, a negative meniscus lens L7 having a convex surface directed toward the object side, a biconvex positive lens L8, a biconcave negative lens L9, a biconvex positive lens L10, a biconvex positive lens L11, and a negative meniscus lens L12 having a convex surface directed toward the object side.

The negative meniscus lens L5 and the biconvex positive lens L6 are cemented. The negative meniscus lens L7 and the biconvex positive lens L8 are cemented. The biconcave negative lens L9 and the biconvex positive lens L10 are cemented.

A filter F is disposed in the first lens unit G1. An aperture stop S is disposed in the third lens unit G3. A cover glass C and a prism P are disposed on an image side of the third lens unit G3.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 8 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a planoconvex positive lens L2, a biconcave negative lens L3, and a biconvex positive lens L4. The biconcave negative lens L3 and the biconvex positive lens L4 are cemented.

The second lens unit G2 includes a positive meniscus lens L5 having a convex surface directed toward the object side.

The third lens unit G3 includes a biconvex positive lens L6, a negative meniscus lens L7 having a convex surface directed toward an image side, a negative meniscus lens L8 having a convex surface directed toward the object side, a positive meniscus lens L9 having a convex surface directed toward the object side, a biconvex positive lens L10, a negative meniscus lens L11 having a convex surface directed toward the image side, and a planoconvex positive lens L12.

The biconvex positive lens L6 and the negative meniscus lens L7 are cemented. The negative meniscus lens L8 and the positive meniscus lens L9 are cemented. The biconvex positive lens L10 and the negative meniscus lens L11 are cemented.

An aperture stop S and a filter F are disposed in the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3. The planoconvex positive lens L12 and the cover glass C are cemented.

In an adjustment of a focal-position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 9 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a positive meniscus lens L2 having a convex surface directed toward an image side, a biconcave negative lens L3, and a biconvex positive lens L4. The biconcave negative lens L3 and the biconvex positive lens L4 are cemented.

The second lens unit G2 includes a positive meniscus lens L5 having a convex surface directed toward the object side.

The third lens unit G3 includes a biconvex positive lens L6, a biconcave negative lens L7, a negative meniscus lens L8 having a convex surface directed toward the object side, a positive meniscus lens L9 having a convex surface directed toward the object side, a biconvex positive lens L10, a negative meniscus lens L11 having a convex surface directed toward the image side, and a planoconvex positive lens L12.

The biconvex positive lens L6 and the biconcave negative lens L7 are cemented. The negative meniscus lens L8 and the positive meniscus lens L9 are cemented. The biconvex positive lens L10 and the negative meniscus lens L11 are cemented.

An aperture stop S and a filter F are disposed in the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3. The planoconvex positive lens L12 and the cover glass C are cemented.

In an adjustment of a focal-position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 10 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a biconcave negative lens L2, and a positive meniscus lens L3 having a convex surface directed toward the object side. The biconcave negative lens L2 and the positive meniscus lens L3 are cemented.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a positive meniscus lens L5 having a convex surface directed toward the object side, a negative meniscus lens L6 having a convex surface directed toward the object side, a biconvex positive lens L7, a negative meniscus lens L8 having a convex surface directed toward the object side, a biconvex positive lens L9, and a planoconvex positive lens L10.

The negative meniscus lens L6 and the biconvex positive lens L7 are cemented. The negative meniscus lens L8 and the biconvex positive lens L9 are cemented.

A filter F is disposed in the first lens unit G1. An aperture stop S is disposed in the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3. The planoconvex positive lens L10 and the cover glass C are cemented.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward an image side.

A wide-angle optical system of an example 11 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a biconcave negative lens L2, and a biconvex positive lens L3. The biconcave negative lens L2 and the biconvex positive lens L3 are cemented.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a negative meniscus lens L5 having a convex surface directed toward the object side, a biconvex positive lens L6, a negative meniscus lens L7 having a convex surface directed toward the object side, a biconvex positive lens L8, a negative meniscus lens L9 having a convex surface directed toward the object side, a biconvex positive lens L10, and a planoconvex positive lens L11.

The negative meniscus lens L5 and the biconvex positive lens L6 are cemented. The negative meniscus lens L7 and the biconvex positive lens L8 are cemented. The negative meniscus lens L9 and the biconvex positive lens L10 are cemented.

An aperture stop S and a filter F are disposed in the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3. The planoconvex positive lens L11 and the cover glass C are cemented.

In an adjustment of a focal-position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward an image side.

A wide-angle optical system of an example 12 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1.

The second lens unit G2 includes a positive meniscus lens L2 having a convex surface directed toward the object side.

The third lens unit G3 includes a biconvex positive lens L3, a negative meniscus lens L4 having a convex surface directed toward an image side, a biconvex positive lens L5, a biconcave negative lens L6, a biconvex positive lens L7, and a biconvex positive lens L8.

The biconvex positive lens L3 and the negative meniscus lens L4 are cemented. The biconvex positive lens L5, the biconcave negative lens L6, and the biconvex positive lens L7 are cemented.

A filter F is disposed between the first lens unit G1 and the second lens unit G2. An aperture stop S is disposed in the third lens unit G3. A prism P and a cover glass C are disposed on an image side of the third lens unit G3.

31

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 13 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a biconcave negative lens L2, and a biconvex positive lens L3. The biconcave negative lens L2 and the biconvex positive lens L3 are cemented.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a biconvex positive lens L5, a biconvex positive lens 6, a negative meniscus lens L7 having a convex surface directed toward an image side, and a planoconvex positive lens L8. The biconvex positive lens L6 and the negative meniscus lens L7 are cemented.

An aperture stop S is disposed between the second lens unit G2 and the third lens unit G3. A filter F is disposed in the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3. The planoconvex positive lens L8 and the cover glass C are cemented.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

A wide-angle optical system of an example 14 includes in order from an object side, a first lens unit G1 having a negative refractive power, a second lens unit G2 having a positive refractive power, and a third lens unit G3 having a positive refractive power.

The first lens unit G1 includes a planoconcave negative lens L1, a biconcave negative lens L2, and a biconvex positive lens L3. The biconcave negative lens L2 and the biconvex positive lens L3 are cemented.

The second lens unit G2 includes a positive meniscus lens L4 having a convex surface directed toward the object side.

The third lens unit G3 includes a planoconvex positive lens L5, a negative meniscus lens L6 having a convex surface directed toward the object side, a planoconvex positive lens L7, a biconvex positive lens L8, a negative meniscus lens L9 having a convex surface directed toward an image side, and a planoconvex positive lens L10.

The negative meniscus lens L6 and the planoconvex positive lens L7 are cemented. The biconvex positive lens L8 and the negative meniscus lens L9 are cemented.

An aperture stop S and a filter F are disposed in the third lens unit G3. A cover glass C is disposed on an image side of the third lens unit G3. The planoconvex positive lens L10 and the cover glass C are cemented.

In an adjustment of a focal position, the second lens unit G2 is moved. At the time of adjustment from a far point to a near point, the second lens unit G2 is moved toward the image side.

Numerical data of each example described above is shown below. In Surface data, r denotes radius of curvature of each lens surface, d denotes a distance between respective lens surfaces, nd denotes a refractive index of each lens for a d-line, vd denotes an Abbe number for each lens and * denotes an aspherical surface. A stop is an aperture stop.

Moreover, in Various data, OBJ denotes an object distance, FL denotes a focal length of the entire system, MG denotes a magnification of the entire system, NAI denotes a numerical aperture, FNO. denotes an F number, FIY and

32

FIM denote an image height, LTL denotes a lens total length of the optical system, and FB denotes a back focus.

The back focus is a unit which is expressed upon air conversion of a distance from a rearmost lens surface to a paraxial image surface. The lens total length is a distance from a frontmost lens surface to the rearmost lens surface plus back focus. Moreover, β_1 denotes a magnification of the first lens unit, β_2 denotes a magnification of the second lens unit, β_3 denotes a magnification of the third lens unit.

Further, in Unit focal length, each of f1, f2 . . . is a focal length of each lens unit.

A shape of an aspherical surface is defined by the following expression where the direction of the optical axis is represented by z, the direction orthogonal to the optical axis is represented by y, a conical coefficient is represented by K, aspherical surface coefficients are represented by A4, A6, A8, A10, A12. . .

$$Z=(y^2/r)/[1+\{1-(1+k)(y/r)^2\}^{1/2}]+A4 y^4+A6 y^6+A8 y^8+A10 y^{10}+A12 y^{12}+. . .$$

Further, in the aspherical surface coefficients, 'E -n' (where, n is an integral number) indicates '10⁻ⁿ'. Moreover, these symbols are commonly used in the following numerical data for each example.

Example 1

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	21.0000	1.		
1	∞	0.3700	1.88300	40.76	1.598
2	1.3365	0.7000	1.		1.054
3	∞	0.4000	1.51633	64.14	1.020
4	∞	0.2000	1.		0.970
5	-2.4149	0.2932	1.88300	40.76	0.971
6	11.5245	0.0905	1.		1.030
7	9.8202	0.6960	1.78472	25.68	1.061
8	-3.2386	d8	1.		1.110
9	1.7471	0.5591	1.49700	81.54	1.033
10	1.8893	d10	1.		0.904
11(Stop)	∞	0.1000	1.		0.570
12	1.6617	0.8323	1.58913	61.14	0.648
13	-1.3612	0.2948	1.83400	37.16	0.665
14	-4.5054	0.0944	1.		0.706
15	2.3887	0.7740	1.58913	61.14	0.720
16	-1.6464	0.0861	1.		0.676
17	-1.3548	0.2847	1.88300	40.76	0.642
18	1.6199	0.0148	1.		0.669
19	1.5740	0.2830	1.69895	30.13	0.689
20	1.8348	0.0446	1.		0.712
21	1.9198	0.8306	1.51742	52.43	0.739
22	-3.6617	0.0887	1.		0.828
23	9.6091	0.8470	1.51633	64.14	0.852
24	-1.4071	0.2937	1.88300	40.76	0.873
25	-4.5032	0.0856	1.		0.961
26	∞	1.5000	1.51633	64.14	0.988
27	∞	0.0700	1.		1.129
Image plane	∞	0.			

Various data

	Far Point	Near point
OBJ	21.0000	2.9000
FL	1.08640	1.03636
MG	-0.049360	-0.266448
NAI	0.1264	0.1262
FIY	1.140	1.140

-continued

Various data		
	Far Point	Near point
LTL	12.4438	12.4438
FB	0.01637	-0.20614
d8	0.36201	1.95324
d10	2.24872	0.65748
β_1	0.06727	0.33940
β_2	1.12363	1.20217
β_3	-0.65304	-0.65304

Unit focal length

$$f_1 = -1.51854, f_2 = 20.26060, f_3 = 2.68873$$

Example 2

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	21.0000	1.		
1	∞	0.3700	1.88300	40.76	1.881
2	1.8089	0.6000	1.		1.306
3	∞	0.4000	1.51633	64.14	1.293
4	∞	0.1633	1.		1.209
5	-7.7140	0.2984	1.88300	40.76	1.185
6	3.9041	0.0965	1.		1.135
7	2.4546	0.8446	1.92286	18.90	1.157
8	3.1566	d8	1.		1.013
9	2.2403	1.5268	1.49700	81.54	0.981
10	3.3915	d10	1.		0.697
11(Stop)	∞	0.0783	1.		0.460
12*	4.0614	0.3192	1.88300	40.76	0.485
13*	11.1597	0.0830	1.		0.526
14	2.0140	0.3000	1.88300	40.76	0.578
15	1.5060	0.8356	1.51742	52.43	0.586
16	-1.5170	0.0934	1.		0.663
17	-10.3264	1.2276	1.51633	64.14	0.654
18	-1.3625	0.2968	1.84666	23.78	0.649
19	1.8989	0.2849	1.		0.704
20	-48.9192	0.5397	1.72916	54.68	0.805
21	-2.6727	0.0956	1.		0.941
22	3.6698	0.5463	1.88300	40.76	1.093
23	-86.8018	0.3500	1.		1.101
24	∞	1.4000	1.51633	64.14	1.111
25	∞	0.0757	1.		1.137
Image plane	∞	0.			

Aspherical surface data

12th surface

K=0.

$$A_2 = 0.0000E+00, A_4 = 2.2626E-02, A_6 = -1.5521E-01, A_8 = 7.9970E-01,$$

$$A_{10} = -1.6090E+00, A_{12} = -1.8424E-01, A_{14} = 1.3225E+00,$$

$$A_{16} = 0.0000E+00, A_{18} = 0.0000E+00, A_{20} = 0.0000E+00$$

13th surface

K=0.

$$A_2 = 0.0000E+00, A_4 = 5.9775E-02, A_6 = -3.6261E-02, A_8 = 2.2828E-01,$$

$$A_{10} = -3.7908E-01, A_{12} = 7.3652E-02, A_{14} = -4.9792E-01,$$

$$A_{16} = 0.0000E+00, A_{18} = 0.0000E+00, A_{20} = 0.0000E+00$$

Various data			
	Far Point	Near point	
5	OBJ	21.0000	2.9000
	FL	0.95940	0.97543
	MG	-0.042789	-0.227651
	FNO	3.9659	3.8809
	FIY	1.140	1.140
	LTL	12.4974	12.4974
10	FB	0.03465	-0.14635
	d8	0.37036	1.16143
	d10	1.30128	0.51021
	β_1	0.04739	0.23415
	β_2	1.11562	1.20142
	β_3	-0.80926	-0.80926

Unit focal length

$$f_1 = -1.07556, f_2 = 9.21973, f_3 = 2.80485$$

Example 3

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
25	Object plane	∞	17.0000	1.	
	1	20.0000	0.3700	1.88300	40.76 2.170
	2	1.8355	0.6000	1.	1.438
	3	∞	0.4000	1.51633	64.14 1.482
	4	∞	0.3651	1.	1.367
30	5	-6.0073	0.7484	1.88300	40.76 1.260
	6	3.8110	0.5388	1.	1.141
	7	2.9102	0.4410	1.92286	18.90 1.179
	8	4.0476	d8	1.	1.118
	9	2.4287	1.7001	1.49700	81.54 1.088
	10	3.4681	d10	1.	0.763
35	11(Stop)	∞	0.0944	1.	0.501
	12*	1.7041	0.3825	1.88300	40.76 0.600
	13*	5.1778	0.2781	1.	0.590
	14	-29.8880	0.3000	1.88300	40.76 0.629
	15	2.9929	0.6826	1.51633	64.14 0.668
	16	-1.6314	0.1268	1.	0.749
40	17	-8.7698	1.5571	1.51633	64.14 0.757
	18	-1.4188	0.3403	1.84666	23.78 0.820
	19	4.3711	0.6288	1.	0.933
	20	264.1515	0.7659	1.72916	54.68 1.240
	21	-2.7702	0.1844	1.	1.362
	22	2.3631	0.6206	1.88300	40.76 1.495
45	23	3.9331	0.4000	1.	1.392
	24	∞	1.4000	1.51633	64.14 1.358
	25	∞	0.0411	1.	1.147
	Image plane	∞	0.		

Image plane ∞ 0.

Aspherical surface data

12th surface

K=0.

$$A_2 = 0.0000E+00, A_4 = 5.2580E-02, A_6 = 5.3691E-02, A_8 = -3.8939E-03,$$

55 A₁₀=0.0000E+00 13th surface

K=0.

$$A_2 = 0.0000E+00, A_4 = 1.2458E-01, A_6 = 7.6091E-02, A_8 = 4.8603E-02,$$

$$A_{10} = 0.0000E+00$$

60

Various data			
	Far Point	Near point	
65	OBJ	17.0000	3.0000
	FL	0.96374	0.99290

-continued

Various data		
	Far Point	Near point
MG	-0.051712	-0.215244
FNO	3.8797	3.8945
FIY	1.140	1.140
LTL	14.5440	14.5440
FB	-0.00878	-0.17266
d8	0.28712	1.03089
d10	1.29110	0.54733
β1	0.06071	0.23796
β2	1.13728	1.20767
β3	-0.74900	-0.74900

Unit focal length

f1=-1.14099, f2=10.56718, f3=4.20765

Example 4

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	17.0000	1.		
1	18.6062	0.3700	1.88300	40.76	1.550
2	1.1634	0.6000	1.		0.954
3	∞	0.4000	1.51633	64.14	0.921
4	∞	0.2106	1.		0.839
5	-2.9012	0.2987	1.88300	40.76	0.816
6	6.6566	0.0969	1.		0.825
7	2.2651	0.4862	1.67270	32.10	0.857
8	7.9728	d8	1.		0.830
9	2.1192	0.9855	1.49700	81.54	0.806
10	2.7662	d10	1.		0.651
11(Stop)	∞	0.0820	1.		0.510
12*	1.5966	0.3119	1.88300	40.76	0.557
13*	1.8942	0.0923	1.		0.547
14	1.2718	0.3000	1.88300	40.76	0.588
15	0.8534	1.2563	1.51742	52.43	0.549
16	-2.5219	0.2499	1.		0.650
17	263.2306	0.8622	1.49700	81.54	0.650
18	-1.3145	0.3172	1.92286	18.90	0.650
19	2.8013	0.1794	1.		0.733
20	17.9648	0.6025	1.78472	25.68	0.806
21	-2.5539	0.0985	1.		0.937
22	4.4647	0.4767	1.78472	25.68	1.044
23	837.6148	0.3500	1.		1.056
24	∞	1.5000	1.51633	64.14	1.078
25	∞	0.0239	1.		1.140
Image plane	∞	0.			

Aspherical surface data

12th surface

K=0.

A2=0.0000E+00, A4=5.4679E-02, A6=-7.3153E-02, A8=1.8821E-01,

A10=-2.6187E-01

13th surface

K=0.

A2=0.0000E+00, A4=1.1151E-01, A6=-2.3505E-02, A8=4.5913E-02,

A10=-1.4874E-01

Various data			
		Far Point	Near point
5	OBJ	17.0000	3.0000
	FL	0.95516	0.95802
	MG	-0.052812	-0.235620
	FNO	3.9309	3.8269
	FIY	1.140	1.140
	LTL	11.7045	11.7045
10	FB	-0.02656	-0.20184
	d8	0.28665	1.04021
	d10	1.26710	0.51353
	β1	0.05086	0.21466
	β2	1.08934	1.15157
15	β3	-0.95317	-0.95317

Unit focal length

f1=-0.93319, f2=12.10818, f3=2.86916

Example 5

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
30	Object plane	∞	17.0000	1.	
	1	167.9781	0.3000	1.88300	40.76 1.564
	2	1.6545	0.7012	1.	1.131
	3	-5.5183	0.3000	1.88300	40.76 1.082
	4	3.1744	0.0871	1.	1.041
	5	2.5804	0.7814	1.84666	23.78 1.066
	6	6.9505	0.1577	1.	0.996
35	7	∞	0.4000	1.51633	64.14 0.988
	8	∞	d8	1.	0.965
	9	1.8888	0.4616	1.49700	81.54 0.928
	10	2.1977	d10	1.	0.836
	11*	1.8361	0.5888	1.80625	40.91 0.610
	12*	6.3888	0.1529	1.	0.483
40	13(Stop)	∞	0.1033	1.	0.434
	14	7.9548	0.7137	1.49700	81.54 0.462
	15	-0.9463	0.2804	1.88300	50.15 0.534
	16	-1.4714	0.0811	1.	0.610
	17	7.9058	1.2449	1.49700	81.54 0.624
	18	-1.8551	0.2802	1.84666	23.78 0.640
45	19	1.8960	0.2604	1.	0.682
	20	-28.2916	0.5750	1.69895	40.19 0.759
	21	-3.3461	0.0701	1.	0.916
	22	6.3282	0.5457	1.69895	30.13 1.024
	23	-12.4763	0.3661	1.	1.083
	24	5.0000	1.0000	1.88300	40.76 1.182
50	25	∞	0.6000	1.51633	64.14 1.162
	26	∞	0.0441	1.	1.145
	Image plane	∞	0.		

Aspherical surface data

11th surface

K=0.4228

A2=0.0000E+00, A4=1.9118E-02, A6=0.0000E+00, A8=0.0000E+00,

A10=0.0000E+00

12th surface

K=0.

A2=0.0000E+00, A4=8.0725E-02, A6=0.0000E+00, A8=0.0000E+00,

A10=0.0000E+00

Various data		
	Far Point	Near point
OBJ	17.0000	3.0000
FL	1.01557	1.01923
MG	-0.055562	-0.239423
FNO	3.9399	3.9046
FIY	1.140	1.140
LTL	11.7980	11.7980
FB	-0.01230	-0.19990
d8	0.18900	1.30877
d10	1.51315	0.39339
β_1	0.06224	0.25370
β_2	1.08568	1.14764
β_3	-0.82231	-0.82231

Unit focal length
 $f_1=-1.15452, f_2=18.07196, f_3=3.62238$

Example 6

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	23.0000	1.		
1	23.3351	0.3000	1.88300	40.76	1.615
2	1.3180	1.0918	1.		1.065
3	-2.3725	0.3000	1.72916	54.68	0.965
4	-14.0022	0.0758	1.		0.981
5	∞	0.4000	1.51633	64.14	0.983
6	∞	0.1000	1.		0.985
7	-7.2570	0.5313	1.84666	23.78	0.986
8	-4.6300	d8	1.		1.019
9	1.5542	0.4753	1.49700	81.61	0.973
10	1.7441	d10	1.		0.867
11	6.3417	0.8343	1.69895	30.13	0.700
12	-1.2695	0.2967	1.84666	23.78	0.632
13	-8.2452	0.0892	1.		0.610
14(Stop)	∞	0.0900	1.		0.544
15	3.3742	1.3677	1.84666	23.78	0.628
16	-37.5413	0.0916	1.		0.687
17	3.4999	0.8220	1.92286	18.90	0.698
18	1.4223	0.3889	1.49700	81.61	0.663
19	1.9638	0.0578	1.		0.700
20	2.2850	1.0027	1.49700	81.61	0.718
21	-1.2509	0.2904	1.84666	23.78	0.794
22	-2.1469	0.0769	1.		0.887
23	-2.2922	0.5036	1.80610	40.92	0.894
24	-2.7798	0.0825	1.		1.007
25	2.0361	0.2532	1.72825	28.46	1.067
26	1.6933	0.7456	1.		1.011
27	5.5337	1.0000	1.88300	40.76	1.122
28	∞	0.6000	1.51633	64.14	1.131
29	∞	0.0451	1.		1.138
Image plane	∞	0.			

Various data		
	Far Point	Near point
OBJ	23.0000	3.5000
FL	1.01803	1.00996
MG	-0.042133	-0.217390
FNO	3.8210	3.7550
FIY	1.140	1.140
LTL	13.4982	13.4982
FB	0.00220	-0.17446
d8	0.26049	1.10362
d10	1.32512	0.48199
β_1	0.04971	0.24508

-continued

Various data		
	Far Point	Near point
β_2	1.15340	1.20715
β_3	-0.73482	-0.73482

Unit focal length
 $f_1=-1.21606, f_2=15.68585, f_3=3.50719$

Example 7

Unit mm

Surface data						
Surface no.	r	d	nd	vd	ER	
20	Object plane	∞	13.0000	1.		
1	∞	0.2500	1.88300	40.76	1.404	
2*	0.9721	0.5998	1.		0.965	
3	∞	0.4000	1.49400	75.01	0.945	
4	∞	0.1025	1.		0.891	
5	-7.4090	0.3000	1.81600	46.62	0.881	
25	6	1.0886	0.7980	1.80518	25.42	0.840
7	76.4205	d7	1.		0.820	
8*	2.2208	0.4521	1.49700	81.54	0.786	
9*	2.9006	d9	1.		0.722	
10	6.3327	0.3000	1.83400	37.16	0.650	
11	1.1384	1.1031	1.64769	33.79	0.614	
30	12	-9.1597	0.1000	1.	0.598	
13(Stop)	∞	0.1000	1.		0.590	
14	2.4331	0.4109	1.81600	46.62	0.624	
15	1.4835	0.6873	1.49700	81.54	0.615	
16	-1.5523	0.1000	1.		0.650	
17	-1.7693	0.3000	1.81600	46.62	0.643	
35	18	4.9222	0.5112	1.49700	81.54	0.711
19	-5.5507	0.1000	1.		0.795	
20*	5.0297	0.6920	1.49700	81.54	0.850	
21*	-1.8981	0.1000	1.		0.907	
22	16.7852	0.5780	1.83400	37.16	0.902	
23	9.3753	0.4930	1.		0.882	
40	24	∞	0.2000	1.51633	64.14	0.890
25	∞	0.1000	1.		0.892	
26	∞	5.3000	1.63854	55.38	0.894	
27	∞	0.0856	1.		0.950	
Image plane	∞	0.				

Aspherical surface data

2nd surface

$K=-1.0000$

$A_2=0.0000E+00, A_4=-1.6360E-02, A_6=4.6266E-02,$

$A_8=0.0000E+00,$

$A_{10}=0.0000E+00$

8th surface

$K=0.$

$A_2=0.0000E+00, A_4=-5.2700E-02, A_6=5.4101E-02,$

55 $A_8=4.5765E-03,$

$A_{10}=0.0000E+00$

9th surface

$K=0.$

$A_2=0.0000E+00, A_4=-4.9134E-02, A_6=6.3791E-02,$

60 $A_8=0.0000E+00,$

$A_{10}=0.0000E+00$

20th surface

$K=0.$

65 $A_2=0.0000E+00, A_4=-5.9779E-03, A_6=1.4095E-03,$

$A_8=0.0000E+00,$

$A_{10}=0.0000E+00$

21st surface
 K=0.
 A2=0.0000E+00, A4=2.2880E-02, A6=3.2241E-03,
 A8=0.0000E+00,
 A10=0.0000E+00

Various data		
	Far Point	Near point
OBJ	13.0000	2.4000
FL	0.80002	0.79259
MG	-0.057538	-0.240455
FNO	3.6407	3.5879
FIM	0.948	0.948
LTL	15.7036	15.7037
FB	0.03958	-0.10492
d7	0.30000	0.98746
d9	1.24011	0.55265
β1	0.06093	0.24500
β2	1.11789	1.16191
β3	-0.84467	-0.84469

Unit focal length
 f1=-0.85974, f2=15.61736, f3=2.99266

Example 8

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	11.5000	1.		
1	∞	0.2500	1.88300	40.76	1.436
2*	0.8505	0.6529	1.		0.953
3	13.6043	0.5102	1.62004	36.26	0.919
4	-4.6021	0.2426	1.		0.852
5	-1.5808	0.2500	1.80400	46.57	0.809
6	3.0801	0.6314	1.80518	25.42	0.852
7	-3.5286	d7	1.		0.880
8*	1.7682	0.5533	1.51633	64.14	0.833
9	2.1000	d9	1.		0.727
10	2.0695	0.8114	1.63854	55.38	0.600
11	-1.3646	0.2500	1.80100	34.97	0.507
12	-26.3432	0.1000	1.		0.487
13 (Stop)	∞	0.1000	1.		0.475
14	1.5941	0.8544	1.80100	34.97	0.526
15	0.7801	0.6500	1.49700	81.54	0.508
16*	2.2277	0.2000	1.		0.600
17	1.4012	0.8500	1.49700	81.54	0.770
18	-1.6518	0.3000	1.81600	46.62	0.785
19	-6.6118	0.2000	1.		0.840
20	∞	0.4000	1.49400	75.01	0.870
21	∞	0.6001	1.		0.901
22	3.9388	0.5256	1.76182	26.52	0.987
23	∞	0.3000	1.51633	64.14	0.968
24	∞	0.0263	1.		0.952
Image plane	∞	0.			

Aspherical surface data

2nd surface
 K=-0.7649
 A2=0.0000E+00, A4=-7.8745E-02, A6=2.3040E-02,
 A8=5.7998E-03,
 A10=0.0000E+00
 8th surface
 K=-0.5166
 A2=0.0000E+00, A4=-5.0786E-04, A6=9.9993E-03,
 A8=0.0000E+00,
 A10=0.0000E+00

16th surface
 K=0.
 A2=0.0000E+00, A4=1.0123E-01, A6=-6.6182E-02,
 A8=9.6241E-02,
 A10=0.0000E+00

Various data		
	Far Point	Near point
OBJ	11.5000	2.0000
FL	0.77283	0.76709
MG	-0.062553	-0.269761
FNO	3.6083	3.5385
FIM	0.948	0.948
LTL	10.8109	10.8109
FB	-0.02202	-0.18060
d7	0.29000	1.05123
d9	1.26273	0.50150
β1	0.07260	0.29872
β2	1.14373	1.19879
β3	-0.75331	-0.75331

Unit focal length
 f1=-0.91119, f2=13.82488, f3=3.05955

Example 9

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	12.5000	1.		
1	∞	0.2500	1.88300	40.76	1.290
2 *	0.8666	0.5899	1.		0.874
3	-67.8910	0.4204	1.62004	36.26	0.850
4	-11.6480	0.2250	1.		0.805
5	-1.9029	0.2500	1.80400	46.57	0.786
6	2.7315	0.6194	1.80518	25.42	0.830
7	-3.0429	d7	1.		0.860
8 *	1.7618	0.4866	1.51633	64.14	0.805
9	2.1000	d9	1.		0.719
10	1.8693	0.8282	1.63854	55.38	0.600
11	-1.2660	0.2500	1.80100	34.97	0.496
12	255.5774	0.1000	1.		0.472
13	∞	0.1000	1.		0.460
14	1.5979	0.8190	1.80100	34.97	0.508
15	0.7863	0.6500	1.49700	81.54	0.496
16*	2.2032	0.2000	1.		0.600
17	1.4729	0.8500	1.49700	81.54	0.747
18	-2.4872	0.3000	1.81600	46.62	0.783
19	-9.6848	0.2000	1.		0.828
20	∞	0.4000	1.49400	75.01	0.860
21	∞	0.6000	1.		0.897
22	3.1860	0.5610	1.76182	26.52	1.001
23	∞	0.3000	1.51633	64.14	0.975
24	∞	0.0259	1.		0.951
Image plane	∞	0.			

Aspherical surface data

2nd surface
 K=-0.4408
 A2=0.0000E+00, A4=-1.1358E-01, A6=1.3043E-02,
 A8=-2.8998E-02,
 A10=0.0000E+00
 8th surface
 K=0.2651
 A2=0.0000E+00, A4=-1.5431E-02, A6=6.8384E-03,
 A8=0.0000E+00,
 A10=0.0000E+00

16th surface
 K=0.
 A2=0.0000E+00, A4=1.2142E-01, A6=0.0000E+00,
 A8=0.0000E+00,
 A10=0.0000E+00

Various data		
	Far Point	Near point
OBJ	12.5000	2.1000
FL	0.80064	0.79640
MG	-0.059913	-0.269809
FNO	3.6030	3.5550
FIM	0.948	0.948
LTL	10.5879	10.5879
FB	-0.02210	-0.18901
d7	0.29400	1.08080
d9	1.26851	0.48171
β 1	0.07161	0.30780
β 2	1.16057	1.21589
β 3	-0.72092	-0.72092

Unit focal length
 f1=-0.97051, f2=14.22153, f3=3.39668

Example 10

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	12.5000	1.		
1	∞	0.2500	1.88300	40.76	1.337
2*	0.8692	0.5880	1.		0.900
3	∞	0.4000	1.49400	75.01	0.887
4	∞	0.0878	1.		0.848
5	-9.0618	0.2500	1.81600	46.62	0.841
6	1.0427	0.7558	1.80518	25.42	0.815
7	17.0221	d7	1.		0.801
8*	3.0758	0.4338	1.80610	40.92	0.798
9	3.6580	d9	1.		0.740
10*	2.1247	0.6051	1.72916	54.68	0.650
11*	9.8770	0.1000	1.		0.523
12	∞	0.1000	1.		0.505
(Stop)					
13	2.4630	0.3572	1.74951	35.33	0.520
14	0.9957	1.5342	1.49700	81.54	0.517
15	-4.3095	0.4000	1.		0.650
16	3.5884	0.3000	1.83400	37.16	0.735
17	1.5227	0.5851	1.49700	81.54	0.731
18*	-405.9130	0.6000	1.		0.777
19	3.5202	0.6000	1.53172	48.84	0.901
20	∞	2.4000	1.51633	64.14	0.910
21	∞	0.0260	1.		0.950
Image plane	∞	0.			

Aspherical surface data

2nd surface
 K=-0 0.9776
 A2=0.0000E+00, A4=-8.8118E-03, A6=6.8995E-02,
 A8=0.0000E+00,
 A10=0.0000E+00 8th surface
 K=0.
 A2=0.0000E+00, A4=-9.1674E-04, A6=3.1219E-02,
 A8=-8.5050E-03,
 A10=0.0000E+00

10th surface
 K=0.
 A2=0.0000E+00, A4=-1.0574E-02, A6=-6.0806E-02,
 A8=0.0000E+00,
 A10=0.0000E+00
 5 11th surface
 K=0.
 A2=0.0000E+00, A4=2.6851E-03, A6=-6.5815E-02,
 A8=0.0000E+00,
 A10=0.0000E+00
 10 18th surface
 K=0.
 A2=0.0000E+00, A4=9.0488E-03, A6=-1.1887E-02,
 A8=0.0000E+00,
 A10=0.0000E+00
 15

Various data		
	Far Point	Near point
OBJ	12.5000	2.1000
FL	0.79078	0.78170
MG	-0.059423	-0.269569
FNO	3.6685	3.5909
FIM	0.948	0.948
LTL	11.9080	11.9080
FB	-0.02102	-0.18476
d7	0.23000	1.06652
d9	1.30502	0.46850
β 1	0.05531	0.24046
β 2	1.07157	1.11807
β 3	-1.00267	-1.00267

Unit focal length
 f1=-0.74700, f2=17.99209, f3=2.73069

Example 11

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	10.0000	1.		
1	∞	0.2500	1.88300	40.76	1.380
2*	1.0031	0.9611	1.		0.964
3	-3.9828	0.2500	1.81600	46.62	0.840
4	1.2000	0.7325	1.69895	30.13	0.803
5	-11.8723	d5	1.		0.801
6*	1.7685	0.4535	1.49700	81.54	0.781
7*	2.1000	d7	1.		0.710
8	3.0533	0.3263	1.80400	46.58	0.650
9	1.0971	0.5783	1.67003	47.23	0.576
10	-10.8438	0.1000	1.		0.544
12 (Stop)	∞	0.1000	1.		0.525
12	3.6361	1.0893	1.83400	37.16	0.557
13	3.2493	0.4833	1.49700	81.54	0.604
14	-7.5585	0.3269	1.		0.650
15	7.6519	0.3000	1.80518	25.42	0.709
16	1.5170	0.7129	1.49700	81.54	0.727
17*	-2.4421	0.1000	1.		0.795
18	∞	0.4000	1.49400	75.01	0.816
19	∞	0.6000	1.		0.840
20	6.8695	0.6732	1.49700	81.54	0.901
21	∞	2.4000	1.51633	64.14	0.911
22	∞	0.0265	1.		0.951
Image plane	∞	0.			

Image plane ∞ 0.
 Aspherical surface data
 2nd surface
 K=-1 0.9630

43

A2=0.0000E+00, A4=8.3944E-02, A6=-1.6945E-03,
 A8=0.0000E+00,
 A10=0.0000E+00 6th surface
 K=0.
 A2=0.0000E+00, A4=-3.6151E-02, A6=1.9453E-02, 5
 A8=-5.8053E-03,
 A10=0.0000E+00
 7th surface
 K=0.
 A2=0.0000E+00, A4=-2.3622E-02, A6=0.0000E+00, 10
 A8=0.0000E+00,
 A10=0.0000E+00
 17th surface
 K=0.
 A2=0.0000E+00, A4=1.2915E-02, A6=-8.6587E-03, 15
 A8=0.0000E+00,
 A10=0.0000E+00

Various data		
	Far Point	Near point
OBJ	10.0000	2.0000
FL	0.77489	0.77102
MG	-0.071294	-0.269683
FNO	3.6407	3.5703
FIM	0.948	0.948
LTL	12.4265	12.4265
FB	-0.02879	-0.18148
d5	0.25000	1.03523
d7	1.31256	0.52733
β1	0.06956	0.25131
β2	1.07800	1.12865
β3	-0.95078	-0.95078

Unit focal length
 f1=-0.76944, f2=15.50141, f3=2.75593

Example 12

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	15.0000	1.		
1	∞	0.2500	1.88300	40.76	1.270
2*	0.7856	0.6500	1.		0.838
3	∞	0.4000	1.49400	75.01	0.824
4	∞	d4	1.		0.800
5*	1.9309	0.4597	1.49700	81.54	0.766
6	2.8631	d6	1.		0.685
7	8.2193	0.5563	1.72825	28.46	0.492
8	-0.8058	0.3000	1.81600	46.62	0.453
9	-2.4732	0.1000	1.		0.430
10 (Stop)	∞	0.6013	1.		0.395
11	9.1375	0.4871	1.49700	81.54	0.517
12	-2.2107	0.2570	1.80518	25.42	0.562
13	1.6710	0.6818	1.49700	81.54	0.623
14	-1.7198	0.1000	1.		0.728
15*	2.9755	0.5709	1.49700	81.54	0.800
16	-5.8213	0.6000	1.		0.818
17	∞	3.2000	1.88300	40.76	0.816
18	∞	0.3000	1.51633	64.14	0.812
19	∞	0.0263	1.		0.812
Image plane	∞	0.			

Aspherical surface data
 2nd surface
 K=-1.0000
 A2=0.0000E+00, A4=3.5380E-02, A6=2.5784E-02,
 A8=7.1050E-02,

44

A10=0.0000E+00
 5th surface
 K=0.
 A2=0.0000E+00, A4=-1.5830E-02, A6=4.2282E-02,
 A8=1.6255E-02,
 A10=0.0000E+00
 15th surface
 K=0.
 A2=0.0000E+00, A4=2.1314E-03, A6=1.0242E-02,
 A8=0.0000E+00,
 A10=0.0000E+00

Various data		
	Far Point	Near point
OBJ	15.0000	1.7300
FL	0.70373	0.69457
MG	-0.044525	-0.275741
FNO	3.6056	3.5439
FIM	0.812	0.812
LTL	11.0387	11.0387
FB	-0.00508	-0.16527
d4	0.26500	1.03032
d6	1.23330	0.46798
β1	0.05553	0.32325
β2	1.16820	1.24284
β3	-0.68635	-0.68635

Unit focal length
 f1=-0.88975, f2=10.25404, f3=2.38964

Example 13

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	12.0000	1.		
1	∞	0.2500	1.88300	40.76	0.959
2*	0.5867	0.7292	1.		0.604
3	-2.9628	0.2500	1.77250	49.60	0.580
4	1.8141	0.6400	1.84666	23.78	0.598
5	-3.6936	d5	1.		0.611
6	1.4089	0.5984	1.65160	58.55	0.568
7	1.5806	d7	1.		0.446
8 (Stop)	∞	0.1000	1.		0.320
9	3.0016	0.3300	1.49700	81.54	0.363
10	-2.8548	0.2000	1.		0.415
11	3.2270	0.5193	1.49700	81.54	0.469
12	-0.9500	0.5877	1.84666	23.78	0.498
13	-1.9860	0.2000	1.		0.611
14	∞	0.4000	1.51633	64.14	0.629
15	∞	1.8314	1.		0.645
16	1.4990	0.4755	1.65160	58.55	0.769
17	∞	0.3000	1.51633	64.14	0.719
18	∞	0.0256	1.		0.656
Image plane	∞	0.			

Aspherical surface data
 2nd surface
 K=-3 0.9151
 A2=0.0000E+00, A4=1.8116E+00, A6=-3.8819E+00,
 A8=7.7408E+00,
 A10=-6.1502E+00, A12=-1.6103E-08, A14=0.0000E+
 00,
 A16=0.0000E+00, A18=0.0000E+00, A20=0.0000E+00

Various data		
	Far Point	Near point
OBJ	12.0000	2.3000
FL	0.57445	0.58774
MG	-0.045069	-0.193515
FNO	3.7639	3.8219
FIM	0.644	0.644
LTL	8.5877	8.5877
FB	-0.00025	-0.08809
d5	0.31000	0.75760
d7	0.84053	0.39293
β_1	0.06232	0.25629
β_2	1.21026	1.26367
β_3	-0.59752	-0.59752

Unit focal length

$$f1=-0.79876, f2=8.38077, f3=3.42474$$

Example 14

Unit mm

Surface data					
Surface no.	r	d	nd	vd	ER
Object plane	∞	12.0000	1.		
1	∞	0.3000	1.88300	40.76	0.956
2*	0.6059	0.5726	1.		0.590
3	-2.2791	0.3000	1.77250	49.60	0.568
4	2.2000	0.6000	1.84666	23.78	0.588
5	-5.1712	d5	1.		0.611
6*	1.1177	0.5146	1.51633	64.14	0.582
7*	1.2614	d7	1.		0.492
8	2.4878	0.3800	1.72916	54.68	0.408
9	∞	0.1000	1.		0.378
10 (Stop)	∞	0.1000	1.		0.370
11	1.7000	0.2500	1.80518	25.42	0.385
12	1.0712	0.5000	1.49700	81.54	0.381
13	∞	0.2000	1.		0.408
14	1.4815	0.7000	1.49700	81.54	0.456
15	-0.9675	0.4036	1.88300	40.76	0.458
16	-9.2037	0.2000	1.		0.515
17	∞	0.4000	1.49400	75.01	0.550
18	∞	0.7801	1.		0.593
19	1.6195	0.6259	1.69680	55.53	0.749

-continued

Surface data					
Surface no.	r	d	nd	vd	ER
5					
20	∞	0.3000	1.51633	64.14	0.695
21	∞	0.0264	1.		0.654
Image plane	∞	0.			
10					
2nd surface					
K=-3.9794					
A2=0.0000E+00, A4=1.7134E+00, A6=-3.7300E+00,					
A8=7.5080E+00,					
A10=-5.6418E+00, A12=-1.6099E-08, A14=0.0000E+					
15					
00,					
A16=0.0000E+00, A18=0.0000E+00, A20=0.0000E+00					
6th surface					
K=0.					
A2=0.0000E+00, A4=-1.2803E-01, A6=0.0000E+00,					
A8=0.0000E+00,					
20					
A10=0.0000E+00					
7th surface					
K=0.					
A2=0.0000E+00, A4=-1.0352E-01, A6=0.0000E+00,					
A8=0.0000E+00,					
25					
A10=0.0000E+00					

Various data					
	Far Point	Near point			
30					
OBJ	12.0000	2.3000			
FL	0.59329	0.60659			
MG	-0.046655	-0.201619			
FNO	3.6591	3.6799			
FIM	0.644	0.644			
35					
LTL	8.4232	8.4232			
FB	-0.00123	-0.09585			
d5	0.30000	0.73415			
d7	0.87000	0.43585			
β_1	0.05072	0.20971			
β_2	1.12026	1.17095			
40					
β_3	-0.82104	-0.82104			

Unit focal length

$$f1=-0.64900, f2=8.56357, f3=3.24456$$

Next, values of conditional expressions in each example are given below. '-' (hyphen) indicates that there is no corresponding arrangement.

	Example1	Example2	Example3
(1) f3L12/fL	1.294826951	1.804565353	2.308091394
(2) fL/R31F	0.65378829	0.23622396	0.56554193
(3) fL \times ΣP_{SNi}	-0.4785357	-0.4654942	-0.3424523
(5) (R _{3R1} + R _{3R2})/ (R _{3R1} - R _{3R2})	—	—	—
(6) (R _{3R1} + R _{3R2})/ (R _{3R1} - R _{3R2})	-0.3120846	-0.918874	-4.0103185
(7) fL/I _{SNr}	-0.7720844	-0.7041468	-0.6792642
(8) v _{31P} - v _{32P}	0	-11.67	-23.38
(9) v _{33P} - (v _{31P} + v _{32P})/2	-31.01	17.545	11.69
(10) v _{31N} - v _{32N}	-3.6	16.98	16.98
(11) (R21F + R21R)/ (R21F - R21R)	-25.572433	-4.8921126	-5.673273
(12) D21/fL	0.51463549	1.5914113	1.764065
(13) β_2F	1.12363	1.11562	1.13728
(14) β_2N/β_2F	1.06989845	1.07690791	1.06189329
(15) (1 - β_2F^2) \times β_3F^2	0.17145198	0.19795146	0.21976094

-continued

(16) $(1 - \beta 2N^2) \times \beta 3N^2$	0.29074171	0.35883399	0.34339165
(17) $fL/R12F_a$	-0.4498737	-0.1243713	-0.1604281
(18) $fL/R12F_b$	—	—	—
(19) $fL/R12F_c$	-0.4498737	-0.1243713	-0.1604281
(20) $fL/R12F_d$	—	—	—
(21) $fL/FL12$	-0.4852166	-0.3307478	-0.3779965
(22) $ R_{fm} / f_{fm} $	0.012346397	21.70696209	0.695422317
(23) $fL \times \tan \omega_{max}$	6.28466714	7.38281509	5.57185721
$2y_{max}$	2.28	2.28	2.28
(24) ER2	0.676	0.663	0.749
$4 \times fL/F_{EX}$	1.09848332	0.96373682	0.99482839

	Example4	Example5	Example6
(1) $f3L12/fL$	2.06321454	2.049095582	2.841763013
(2) $fL/R31F$	0.59824627	0.55311258	0.16052951
(3) $fL \times \Sigma EP_{SNi}$	-0.7186162	-0.6056761	-0.7078323
(5) $(R_{3R1} + R_{3R2})/$ $(R_{3R1} - R_{3R2})$	—	—	-1.0000011
(6) $(R_{3R1} + R_{3R2})/$ $(R_{3R1} - R_{3R2})$	-1.0107176	-1.0000001	—
(7) fL/Γ_{SNr}	-0.7266337	-0.5474476	-0.813838
(8) $v_{31P} - v_{32P}$	-11.67	-40.63	6.35
(9) $v_{33P} -$ $(v_{31P} + v_{32P})/2$	34.945	20.315	54.655
(10) $v_{31N} - v_{32N}$	21.86	26.37	4.88
(11) $(R21F + R21R)/$ $(R21F - R21R)$	-7.5508501	-13.2292	-17.368615
(12) $D21/fL$	1.03176431	0.45452308	0.46688212
(13) $\beta 2F$	1.08934	1.08568	1.1534
(14) $\beta 2N/\beta 2F$	1.05712633	1.05707022	1.04660135
(15) $(1 - \beta 2F^2) \times$ $\beta 3F^2$	0.17792027	0.14694767	0.24273424
(16) $(1 - \beta 2N^2) \times$ $\beta 3N^2$	0.31084157	0.26073606	0.33596788
(17) $fL/R12F_a$	-0.3292293	-0.1840368	-0.4290959
(18) $fL/R12F_b$	—	—	—
(19) $fL/R12F_c$	-0.3292293	-0.1840368	-0.4290959
(20) $fL/R12F_d$	—	—	—
(21) $fL/FL12$	-0.4235367	-0.4522086	-0.2570458
(22) $ R_{fm} / f_{fm} $	146.472004	17660044.0	15956852.5
(23) $fL \times \tan \omega_{max}$	5.542921362	2.74763805	4.27016993
$2y_{max}$	2.28	2.28	2.28
(24) ER2	0.65	0.610	0.687
$4 \times fL/F_{EX}$	0.96676113	1.02842532	1.06183051

	Example7	Example8	Example9
(1) $f3L12/fL$	2.82442939	3.49882898	3.46073141
(2) $fL/R31F$	0.12633158	0.37343803	0.42831006
(3) $fL \times \Sigma EP_{SNi}$	-0.3548088	-0.5424258	-0.514974
(5) $(R_{3R1} + R_{3R2})/$ $(R_{3R1} - R_{3R2})$	—	-1.0000001	-1.0000001
(6) $(R_{3R1} + R_{3R2})/$ $(R_{3R1} - R_{3R2})$	0.45203383	—	—
(7) fL/Γ_{SNr}	0.16253301	-0.4678714	-0.3219041
(8) $v_{31P} - v_{32P}$	-47.75	-26.16	-26.16
(9) $v_{33P} -$ $(v_{31P} + v_{32P})/2$	23.875	13.08	13.08
(10) $v_{31N} - v_{32N}$	-9.46	0	0
(11) $(R21F + R21R)/$ $(R21F - R21R)$	-7.5336864	-11.658228	-11.418687
(12) $D21/fL$	0.56511087	0.71594012	0.60776379
(13) $\beta 2F$	1.11789	1.14373	1.16057
(14) $\beta 2N/\beta 2F$	1.03937776	1.04814073	1.04766623
(15) $(1 - \beta 2F^2) \times$ $\beta 3F^2$	0.21089556	0.23210861	0.25010353
(16) $(1 - \beta 2N^2) \times$ $\beta 3N^2$	0.29567094	0.32926989	0.34487983
(17) $fL/R12F_a$	-0.1079795	—	—
(18) $fL/R12F_b$	-0.1079795	—	—
(19) $fL/R12F_c$	—	—	—
(20) $fL/R12F_d$	—	-0.4888854	-0.4207473
(21) $fL/FL12$	-0.1052367	0.13785028	0.03540806
(22) $ R_{fm} / f_{fm} $	0.35511155	19341611.3	23911431.8

-continued

(23) $fL \times \tan\omega_{max}$	2.46301838	4.37275453	2.4579755
$2y_{max}$	1.896	1.896	1.896
(24) ER2	0.650	0.6	0.6
$4 \times fL/F_{EX}$	0.87409997	0.85160331	0.88541886
	Example10	Example11	Example12
(1) $f3L12/fL$	3.25109386	3.49339906	4.72851804
(2) $fL/R31F$	0.37218431	0.25378771	0.08561921
(3) $fL \times \Sigma EP_{SNi}$	-0.3755556	-0.3324111	-0.3045253
(5) $(R_{3R1} + R_{3R2})/$ $(R_{3R1} - R_{3R2})$	-1.0000001	-1.0000001	-0.323504
(6) $(R_{3R1} + R_{3R2})/$ $(R_{3R1} - R_{3R2})$	—	—	—
(7) fL/Γ_{SNr}	0.51932751	0.51080422	0.42114303
(8) $v_{31P} - v_{32P}$	-26.86	-34.31	-53.08
(9) $v_{33P} -$ $(v_{31P} + v_{32P})/2$	13.43	17.155	26.54
(10) $v_{31N} - v_{32N}$	-1.83	9.42	21.2
(11) $(R21F + R21R)/$ $(R21F - R21R)$	-11.566128	-11.669683	-5.1426732
(12) $D21/fL$	0.5485723	0.58524436	0.65323348
(13) $\beta2F$	1.07157	1.078	1.1682
(14) $\beta2N/\beta2F$	1.04339427	1.04698516	1.06389317
(15) $(1 - \beta2F^2) \times$ $\beta3F^2$	0.14865813	0.15410623	0.25030583
(16) $(1 - \beta2N^2) \times$ $\beta3N^2$	0.25074824	0.26037189	0.3738214
(17) $fL/R12F_a$	-0.0872652	-0.1945591	—
(18) $fL/R12F_b$	-0.0872652	-0.1945591	—
(19) $fL/R12F_c$	—	—	—
(20) $fL/R12F_d$	—	—	—
(21) $fL/FL12$	-0.118959	-0.183571	0.0686298
(22) $ R_{fm} / f_{fm} $	15104827.4	7234895.27	1.437642
(23) $fL \times \tan\omega_{max}$	2.41626746	2.38641257	2.15048988
$2y_{max}$	1.896	1.896	1.624
(24) ER2	0.65	0.65	0.728
$4 \times fL/F_{EX}$	0.85698185	0.84479695	0.77760221
	Example13	Example14	
(1) $f3L12/fL$	3.57594221	3.47974852	
(2) $fL/R31F$	0.19138126	0.23847978	
(3) $fL \times \Sigma EP_{SNi}$	-0.2114339	-0.40739	
(5) $(R_{3R1} + R_{3R2})/$ $(R_{3R1} - R_{3R2})$	-1	-1	
(6) $(R_{3R1} + R_{3R2})/$ $(R_{3R1} - R_{3R2})$	—	—	
(7) fL/Γ_{SNr}	-0.6046842	-0.6132196	
(8) $v_{31P} - v_{32P}$	0	-26.86	
(9) $v_{33P} -$ $(v_{31P} + v_{32P})/2$	-22.99	13.43	
(10) $v_{31N} - v_{32N}$	—	-15.34	
(11) $(R21F + R21R)/$ $(R21F - R21R)$	-17.411182	-16.556019	
(12) $D21/fL$	1.04169205	0.86736672	
(13) $\beta2F$	1.21026	1.12026	
(14) $\beta2N/\beta2F$	1.04413101	1.04524842	
(15) $(1 - \beta2F^2) \times$ $\beta3F^2$	0.27768503	0.20935081	
(16) $(1 - \beta2N^2) \times$ $\beta3N^2$	0.3566369	0.30470757	
(17) $fL/R12F_a$	—	-0.2603177	
(18) $fL/R12F_b$	-0.1938875	-0.2603177	
(19) $fL/R12F_c$	—	—	
(20) $fL/R12F_d$	—	—	
(21) $fL/FL12$	0.02105524	-0.0676638	
(22) $ R_{fm} / f_{fm} $	43468810.7	43025556.8	
(23) $fL \times \tan\omega_{max}$	1.76552611	1.84324927	
$2y_{max}$	1.288	1.288	
(24) ER2	0.611	0.408	
$4 \times fL/F_{EX}$	0.61372863	0.64929138	

FIG. 29 is an example of an image pickup apparatus. In this example, the image pickup apparatus is an endoscope system. FIG. 29 is a diagram showing a schematic configuration of an endoscope system.

An endoscope system 300 is an observation system in which an electronic endoscope is used. The endoscope system 300 includes an electronic endoscope 310 and an image processing unit 320. The electronic endoscope 310

51

includes a scope section **310a** and a connecting cord section **310b**. Moreover, a display unit **330** is connected to the image processing unit **320**.

The scope section **310a** is mainly divided into an operating portion **340** and an inserting portion **341**. The inserting portion **341** is long and slender, and can be inserted into a body cavity of a patient. Moreover, the inserting portion **341** is formed of a flexible member. An observer can carry out various operations by an angle knob that is provided to the operating portion **340**.

Moreover, the connecting cord section **310 b** is extended from the operating portion **340**. The connecting cord section **301b** includes a universal cord **350**. The universal cord **350** is connected to the image processing unit **320** via a connector **360**.

The universal cord **350** is used for transceiving of various types of signals. Various types of signals include signals such as a power-supply voltage signal and a CCD (charge coupled device) driving signal. These signals are transmitted from a power supply unit and a video processor to the scope section **310a**. Moreover, various types of signals include a video signal. This signal is transmitted from the scope section **310a** to the video processor.

Peripheral equipment such as a VTR (video tape recorder) deck and a video printer can be connected to the video processor inside the image processing unit **320**. The video processor carries out signal processing on a video signal from the scope section **310a**. On the basis of the video signal, an endoscope image is displayed on a display screen of the display unit **330**.

An optical system is disposed at a front-end portion **342** of the inserting portion **341**. FIG. **30** is a diagram showing an arrangement of the optical system of the endoscope. An optical system **400** includes an illuminating section and an observation section.

The illuminating section includes a light guide **401** and an illuminating lens **402**. The light guide **401** transmits illumination light to the front-end portion **342** of the inserting portion **341**. The transmitted light is emerged from a front-end surface of the light guide **401**.

At the front-end portion **342**, the illuminating lens **402** is disposed. The illuminating lens **402** is disposed at a position of facing the front-end surface of the light guide **401**. The illumination light passes through the illuminating lens **402** and is emerged from an illumination window **403**. As a result, an observation object region **404** of an inside of an object (hereinafter, referred to as 'observation region **404**') is illuminated.

At the front-end portion **342**, an observation window **405** is disposed next to the illumination window **403**. Light from the observation region **404** is incident on the front-end portion **342** through the observation window **405**. An observation portion is disposed behind the observation window **405**.

The observation portion includes a wide-angle optical system **406** and an image sensor **407**. The wide-angle optical system of the example 1 is used for the wide-angle optical system **406**, for instance.

Reflected light from the observation region **404** passes through the wide-angle optical system **406** and is incident on the image sensor **407**. On an image pickup surface of the image sensor **407**, an image (an optical image) of the observation region **404** is formed. The image of the observation region **404** is converted photoelectrically by the image sensor **407**, and thereby an image of the observation region **404** is acquired. The image of the observation region

52

404 is displayed on the display unit **330**. By doing so, it is possible to observe the image of the observation region **404**.

In the wide-angle optical system **406**, an image plane is curved shape. The image sensor **407** has a curved-shape light receiving surface (an image pickup surface) same as an shape of the image plane. By using the image sensor **407**, it is possible to improve an image quality of the acquired image.

FIG. **31** is a diagram showing an arrangement of an optical system of an image pickup apparatus. The optical system includes an objective optical system OBJ, a cover glass C, and a prism P. The cover glass C is disposed between the objective optical system OBJ and the prism P. The wide-angle optical system of the example 7 is used for the objective optical system OBJ. An optical filter may be disposed instead of the cover glass C. Or, the cover glass C may not be disposed.

The prism P includes a prism P1 and a prism P2. Both the prism P1 and the prism P2 are triangular prisms. An optical-path splitting element is formed by the prism P1 and the prism P2.

The prism P1 has an optical surface S1, an optical surface S2, and an optical surface S3. The prism P2 has an optical surface S3, an optical surface S4, and an optical surface S5. The prism P1 is cemented to the prism P2. A cemented surface is formed by the prism P1 and the prism P2. The optical surface S3 is a cemented surface.

Light emerged from the objective optical system OBJ (hereinafter, referred to as 'imaging light') passes through the cover glass C, and is incident on the optical surface S1. The optical surface S1 being a transmitting surface, the imaging light is transmitted through the optical surface S1.

Next, the imaging light is incident on the optical surface S3. The optical surface S3 is disposed so that a normal of the surface is at 45 degrees with respect to an optical axis. The imaging light incident on the optical surface S3 is divided into light transmitted through the optical surface S3 (hereinafter, referred to as 'imaging light 1') and light reflected at the optical surface S3 (hereinafter, referred to as 'imaging light 2').

The imaging light 1 and the imaging light 2 travel in mutually different directions. When an optical path through which the imaging light 1 travels is a first optical path and an optical path through which the imaging light 2 travels is a second optical path, the first optical path and the second optical path are formed by the optical surface S3. As just described, the optical surface S3 functions as an optical-path splitting surface.

The first optical path is formed on an extension line of an optical path of the objective optical system OBJ. The second optical path is formed to intersect the first optical path. In FIG. **31**, the second optical path is orthogonal to the first optical path.

The optical surface S3, the optical surface S4, and the optical surface S5 are located in the first optical path. The imaging light 1 transmitted through the optical surface S3 is incident on the optical surface S4. The optical surface S4 is a reflecting surface. The imaging light 1 is reflected at the optical surface S4, and is incident on the optical surface S5. The optical surface S5 is a transmitting surface. The imaging light 1 is transmitted through the optical surface S5, and is converged on an image plane I near the optical surface S5. An optical image by the imaging light 1 is formed on the image plane I.

The optical surface S3, the optical surface S2, the optical surface S3, and the optical surface S5 are located in the second optical path. The imaging light 2 reflected at the

optical surface S3 is incident on the optical surface S2. The optical surface S2 is a reflecting surface. The imaging light 2 is reflected at the optical surface S2, and is incident on the optical surface S3. At the optical surface S3, the imaging light 2 is divided into light transmitted through the optical surface S3 and light reflected at the optical surface S3.

The imaging light 2 transmitted through the optical surface S3 is incident on the optical surface S5. The imaging light 2 is transmitted through the optical surface S5, and is converged on the image plane I near the optical surface S5. An optical image by the imaging light 2 is formed on the image plane I.

Since two optical paths are formed in the optical system shown in FIG. 31, two optical images are formed on the same plane. The same plane is the image plane I in the two optical paths.

In a case in which an optical-path length of the first optical path and an optical-path length of the second optical path are same, two focused optical images are formed at different positions on the same plane. The two optical images are optical images when the same object is focused. Accordingly, a position of an object plane for one optical image and a position of an object plane for the other optical image are same.

Whereas, even in a case in which the optical-path length of the first optical path and the optical-path length of the second optical path are different, two focused optical images are formed at different positions on the same plane. However, the two optical images are optical images when different objects are focused.

Accordingly, a position of an object plane for one optical image and a position of an object plane for the other optical image are different.

For instance, it is assumed that the optical-path length of the first optical path is shorter than the optical-path length of the second optical path. In this case, the object plane of the optical image formed by the imaging light 1 is positioned far from the object plane of the optical image formed by the imaging light 2. As just described, the focus is adjusted for each of the two object planes in which distance from the objective optical system (hereinafter, referred to as 'object distance') differs from each other. Even when the object distance differs for two object planes, the two optical images are formed at different locations in on the same plane.

The objective optical system OBJ has a section which is focused (hereinafter, referred to as 'focusing section'). The focusing section is a section expressed by the object distance, and corresponds to a depth of field of the objective optical system OBJ. In the focusing section, wherever the object plane is positioned, a focused optical image is formed.

In a case in which the object distance differs for two object planes, there occurs a shift between a position of the focusing section for one object plane and a position of the focusing section for the other object plane. By setting appropriately the distance of the two object planes, it is possible to overlap a part of the focusing section for the one object plane and a part of the focusing section for the other object plane.

Thus, two optical images having the focusing section shifted are captured, and accordingly, two images are acquired. Moreover, only a focused area (an image area of a range corresponding to the depth of field) is extracted from the two images that were acquired, and the areas extracted are combined. By doing so, it is possible to acquire an image with a large depth of field.

For the optical surface S3, it is possible to use a half-mirror surface or a polarizing-beam splitter surface for example.

In a case in which the optical surface S3 is a half-mirror surface, a half of a quantity of imaging light is reflected at the optical surface S3 and the remaining half of the quantity of imaging light is transmitted through the optical surface S3. Accordingly, a quantity of the imaging light 2 becomes half of the quantity of the imaging light. The imaging light 2 is reflected at the optical surface S2. The imaging light 2 reflected at the optical surface S2 is transmitted through the optical surface S3. At the optical surface S3, only half of the quantity of the imaging light 2 can be transmitted.

In a case in which the optical surface S3 is a polarizing-beam splitter surface, a depolarization plate or a wavelength plate may be used instead of the cover glass C. Moreover, the optical surface S2 is not a reflecting surface but is a transmitting surface. A reflecting surface is disposed at a position away from the optical surface S2. Furthermore, a quarter-wave plate is disposed between the optical surface S2 and the reflecting surface.

P-polarized light is polarized light having an amplitude of light in a paper plane, and S-polarized light is polarized light having an amplitude in a plane orthogonal to the paper plane. When it is assumed that the P-polarized light is transmitted through the optical surface S3 and the S-polarized light is reflected at the optical surface S3, the P-polarized light corresponds to the imaging light 1 and the S-polarized light corresponds to the imaging light 2.

For instance, when the depolarization plate is used instead of the cover glass C, the imaging light passes through the depolarization plate. Consequently, in the imaging light emerged from the depolarization plate, a proportion of the P-polarized light and the S-polarized light in the imaging light becomes substantially half. The imaging light incident on the optical surface S3 is divided into the P-polarized light and the S-polarized light at the optical surface S3. Accordingly, the quantity of the imaging light 2 becomes half of the quantity of the imaging light.

The imaging light 2, when directed from the optical surface S3 toward the optical surface S2, is S-polarized light. In a case in which the optical surface S2 is a reflecting surface, the imaging light 2 is reflected toward the optical surface 3 as the S-polarized light as it has been. The imaging light 2 directed from the optical surface S2 toward the optical surface S3 being the S-polarized light, cannot be transmitted through the optical surface S3.

Whereas, in a case in which the optical surface S2 is a transmitting surface, the imaging light 2 is reflected at the reflecting surface. The $\lambda/4$ plate is disposed between the optical surface S2 and the reflecting surface. By the imaging light 2 travelling to and from between the optical surface S2 and the reflecting surface, a direction of polarization for the imaging light 2 rotates 90 degrees. Accordingly, it is possible to convert the S-polarized light to the P-polarized light. As a result, the imaging light directed from the optical surface S2 toward the optical surface S3 becomes the P-polarized light.

The imaging light 2 converted to the P-polarized light reaches the optical surface S3. Accordingly, the imaging light 2 is not reflected at the optical surface S3. In other words, at the optical surface S3, almost whole of the amount of the imaging light 2 can be transmitted through.

FIG. 32A and FIG. 32B are diagrams showing a schematic configuration of an image pickup apparatus. FIG. 32A is a diagram showing an overall configuration, and FIG. 32B is a diagram showing an orientation of an object.

As shown in FIG. 32A, an image pickup apparatus 500 includes an objective optical system 501, a depolarization plate 502, a first prism 503, a second prism 504, a third prism 505, a wavelength plate 506, a mirror 507, an image sensor 508, an image processor 511, and an image display unit 512.

In the image pickup apparatus 500, an optical-path splitting element is formed by the first prism 503, the second prism 504, and the third prism 505.

The objective optical system 501 forms an image of an object. The depolarization plate 502 is disposed between the objective optical system 501 and the first prism 503.

The first prism 503 and the second prism 504 are cemented. A cemented surface 509 is formed by the first prism 503 and the second prism 504. Light incident on the cemented surface 509 is divided into light reflected at the cemented surface 509 and light transmitted through the cemented surface 509.

It is possible to use a polarizing-beam splitter surface for the cemented surface 509. In this case, P-polarized light is transmitted through the cemented surface 509 and S-polarized light is reflected at the cemented surface 509.

The P-polarized light transmitted through the cemented surface 509 emerges from the second prism 504. The P-polarized light is incident on the third prism 505 and reaches an optical surface 510. The optical surface 510, for instance, is a mirror surface. Accordingly, the P-polarized light is reflected at the optical surface 510.

The P-polarized light reflected at the optical surface 510 emerges from the third prism 505 and is incident on the image sensor 508. As shown in FIG. 32B, the image sensor 508 has a first area 513 and a second area 514. The P-polarized light reflected at the optical surface 510 is incident on the first area 513. Accordingly, an optical image is formed on the first area 513.

On the other hand, the S-polarized light reflected at the cemented surface 509 emerges from the first prism 503. The S-polarized light is incident on the wavelength plate 506. A quarter-wave plate is used for the wavelength plate 506. Consequently, the S-polarized light is converted to circularly-polarized light at the wavelength plate 506. As a result, the circularly-polarized light emerges from the wavelength plate 506.

The circularly-polarized light is reflected at the mirror 507 and is incident once again on the wavelength plate 506. Light emerged from the wavelength plate 506 is incident on the first prism 503 and reaches the cemented surface 509. The circularly-polarized light incident on the wavelength plate 506 is converted to P-polarized light at the wavelength plate 506. The light reached the cemented surface 509 being the P-polarized light, the light reached the cemented surface 509 is transmitted through the cemented surface 509.

The P-polarized light which is transmitted through the cemented surface 509 emerges from the second prism 504 and is incident on the image sensor 508. As mentioned above, the image sensor 508 has the first area 513 and the second area 514. The P-polarized light transmitted through the cemented surface 509 is incident on the second area 514. As a result, an optical image is formed on the second surface 514.

For instance, a rolling shutter system is adopted for the image sensor 508. In the rolling shutter system, image information for a line is read for each line one-by-one. The image sensor 508 is connected to the image processor 511. Image information which is read is input to the image processor 511.

The image processor 511 includes a second image processing section 511b. In the second image processing section

511b, it is possible to select a focused image as an image for display by using the image information that has been read for each line one-by-one. Images for each line selected by the second image processing section 511b are combined and displayed on the image display unit 512.

The image processor 511 will be described below. The image processor 511 is provided to a central processing unit (not shown in the diagram). The image processor 511 includes a first image processing section 511a, the second image processing section 511b, a third image processing section 511c, a fourth image processing section 511d, and a fifth image processing section 511e.

In the first image processing section 511a, an orientation of an image acquired from the first area 513 (hereinafter, referred to as 'first image') and an orientation of an image acquired from the second area 514 (hereinafter, referred to as 'second image') are corrected. In correction of the orientation of the image, the image is rotated for example.

The orientation of the first image and the orientation of the second image are determined by an orientation of the optical image formed in the first area 513 (hereinafter, referred to as 'first optical image') and an orientation of the optical image formed in the second area 514 (hereinafter, referred to as 'second optical image') respectively.

FIG. 33 is a diagram showing a positional relationship of an object, an objective optical system, and an optical-path splitting element. For instance, a case of observing a character 'F' as shown in FIG. 33 will be described below. Each of the orientation of the first optical image and the orientation of the second optical image is an orientation as shown in FIG. 32B.

As shown in FIG. 32B, the first optical image and the second optical image are mirror images of each other. Furthermore, when a vertical orientation of a paper surface is an upright direction, the first optical image and the second optical image are rotated 90 degrees from the upright direction.

Therefore, in a case of displaying an image of an object on the image display unit 512, in the first image processing section 511a, the first image is rotated 90 degrees with a central point of the first area 513 as a center. Even regarding the second image, the second image is rotated 90 degrees with a central point of the area 514 as a center. Moreover, regarding the second image, the second image is inverted, and a mirror image is corrected.

As the processing by the first image processing section 511a is terminated, processing by the second image processing unit 511b is executed. However, according to the requirement, processing by at least one of the third image processing section 511c, the fourth image processing section 511d, and the fifth image processing section 511e may be executed before executing the processing by the second image processing section 511b.

The third image processing section 511c is configured so that a white balance of the first image and a white balance of the second image are adjustable. The fourth image processing section 511d is configured so that a center position of the first image and a center position of the second image are movable or selectable. The fifth image processing section 511e is configured so that a display range of the first image and a display range of the second image are adjustable. Moreover, the fifth image processing section 511e may be configured so that a display magnification is adjustable instead of the display range.

The second image processing section 511b is configured to compare the first image and the second image, and to select an image of a focused area as an image for display.

57

The second image processing section **511b** has a high-pass filter, a comparator, and a switch. The high-pass filter is connected to each of the first area **513** and the second area **514**. In the high-pass filter, a high component is extracted from each of the first image and the second image.

Outputs of the two high-pass filters are input to the comparator. The high components extracted in the two high-pass filters are compared in the comparator. A comparison result is input to the switch. Moreover, the first area **513** and the second area **514** are connected to the switch. Accordingly, the comparison result, a signal of the first image, and a signal of the second image are input to the switch.

In the switch, an area with many high component in the first image and an area with many high component in the second image are selected on the basis of the comparison result.

The image display unit **512** has a display area. An image selected by the second processing section **511b** is displayed in the display area. The image display unit **512** may have display areas displaying the first image and the second image.

According to the present disclosure, it is possible to provide a wide-angle optical system in which various aberrations are corrected favorably, and which an outer diameter of a lens which moves and an outer diameter of a lens located near a lens unit that moves are adequately small, and an image pickup apparatus in which the wide-angle optical system is used.

As described heretofore, the present disclosure is suitable for a wide-angle optical system in which various aberrations are corrected favorably, and which an outer diameter of a lens which moves and an outer diameter of a lens located near a lens unit that moves are adequately small, and an image pickup apparatus in which the wide-angle optical system is used.

What is claimed is:

1. A wide-angle optical system having a lens component which has a plurality of optical surfaces, and in the lens component, two optical surfaces are in contact with air, and at least one optical surface is a curved surface, the wide-angle optical system comprising, in order from an object side:

a first lens unit having a negative refractive power;
a second lens unit having a positive refractive power; and
a third lens unit having a positive refractive power,
wherein:

at a time of carrying out a focal-position adjustment from a far point to a near point, the second lens unit is moved from a first position toward a second position, the first position being a position at which a distance between the first lens unit and the second lens unit becomes minimum, and the second position being a position at which a distance between the second lens unit and the third lens unit becomes minimum,

the third lens unit includes at least three lens components, the at least three lens components including a first lens component and a second lens component, the first lens component being a lens component located nearest to an object in the third lens unit, and the second lens component being a lens component located second from the object side in the third lens unit, each of the first lens component and the second lens component has a positive refractive power, the third lens unit includes at least three cemented surfaces,

58

a value of a difference in refractive indices is not less than 0.25 at each of the at least three cemented surfaces, and the following conditional expression (1) is satisfied:

$$0.8 < \beta L_{12} / fL < 6.0 \quad (1)$$

where,

fL_{12} denotes a combined focal length of the first lens component and the second lens component,

fL denotes a focal length of the wide-angle optical system at the first position,

the difference in refractive indices is a difference between an object-side refractive index and an image-side refractive index,

the object-side refractive index is a refractive index for a d-line of a medium which is located on an object side of the cemented surface, and which is adjacent to the cemented surface, and

the image-side refractive index is a refractive index for a d-line of a medium which is located on an image side of the cemented surface, and which is adjacent to the cemented surface.

2. The wide-angle optical system according to claim **1**, wherein at least two diverging surfaces are disposed between a surface nearest to the object of the first lens component and a surface nearest to an image of the second lens component.

3. The wide-angle optical system according to claim **1**, wherein the third lens unit includes at least four lens components.

4. The wide-angle optical system according to claim **1**, wherein the third lens unit includes three, four, or five lens components having a positive refractive power.

5. The wide-angle optical system according to claim **1**, wherein a cemented lens located nearest to an image in the third lens unit includes, in order from the object side, a positive lens and a negative lens.

6. The wide-angle optical system according to claim **1**, wherein

a single lens unit is disposed nearest to an image in the third lens unit,

the single lens unit includes two single lenses or three single lenses,

a cemented lens is disposed adjacent to the single lens unit, on the object side of the single lens unit, and the cemented lens includes, in order from the object side, a positive lens and a negative lens.

7. The wide-angle optical system according to claim **1**, wherein:

one single lens is disposed nearest to an image in the third lens unit,

a cemented lens is disposed adjacent to the single lens, on the object side of the single lens, and the cemented lens includes, in order from the object side, a positive lens and a negative lens.

8. The wide-angle optical system according to claim **1**, wherein the following conditional expression (2) is satisfied:

$$0.05 < fL / R_{31F} < 1.20 \quad (2)$$

where R_{31F} denotes a radius of curvature of a surface on the object side of the first lens component.

9. The wide-angle optical system according to claim **1**, further comprising:

an image-side lens component,

wherein:

the image-side lens component, among a plurality of lens components of the wide-angle optical system, is a lens component located nearest to an image,

59

the third lens unit includes N number of cemented surfaces S_{Ni} ($i=1, 2, \dots, N$) between the first lens component and the image-side lens component, and the following conditional expression (3) is satisfied:

$$-1.0 < fL \times \sum P_{SNi} < -0.05 \quad (3)$$

where,

P_{SNi} denotes a refractive power of the cemented surface S_{Ni} , and is expressed by the following expression (4):

$$P_{SNi} = (n_{SNi} - n_{SNi}') / r_{SNi} \quad (4)$$

where,

n_{SNi} denotes a refractive index for a d-line of a medium located on the object side of the cemented surface S_{Ni} ,

n_{SNi}' denotes a refractive index for the d-line of a medium located on the image side of the cemented surface S_{Ni} , and

r_{SNi} denotes a radius of curvature near an optical axis of the cemented surface S_{Ni} .

10. The wide-angle optical system according to claim 1, wherein:

the third lens unit includes a cemented lens which is located nearest to an image among a plurality of cemented lenses, and a lens component which is located nearest to the image,

the cemented lens which is located nearest to the image has a positive refractive power,

the lens component which is located nearest to the image is a positive single lens, and

the following conditional expression (5) is satisfied:

$$-2 < (R_{3R1} + R_{3R2}) / (R_{3R1} - R_{3R2}) < 2 \quad (5)$$

where,

R_{3R1} denotes a radius of curvature of a surface on the object side of the positive single lens, and

R_{3R2} denotes a radius of curvature of a surface on the image side of the positive single lens.

11. The wide-angle optical system according to claim 1, wherein:

the third lens unit includes a cemented lens which is located nearest to an image among a plurality of cemented lenses, and a positive single lens satisfy which is located nearest to the image,

the cemented lens which is located nearest to the image has a negative refractive power, and

the following conditional expression (6) is satisfied:

$$-5 < (R_{3R1} + R_{3R2}) / (R_{3R1} - R_{3R2}) < 1 \quad (6)$$

where,

R_{3R1} denotes a radius of curvature of a surface on the object side of the positive single lens, and

R_{3R2} denotes a radius of curvature of a surface on the image side of the positive single lens.

12. The wide-angle optical system according to claim 1, wherein a cemented surface located nearest to an image in the third lens unit satisfies the following conditional expression (7)

$$-2.0 < fL / r_{SNr} < 1.5 \quad (7)$$

where,

r_{SNr} denotes a radius of curvature near an optical axis of the cemented surface located nearest to the image.

13. The wide-angle optical system according to claim 1, wherein:

the third lens unit includes a plurality of positive lenses, the plurality of positive lenses include a first positive lens and a second positive lens,

60

the first positive lens, among the plurality of positive lenses, is a positive lens located nearest to the object, the second positive lens, among the plurality of positive lenses, is a positive lens located second from the object, and

the following conditional expression (8) is satisfied:

$$-70 < v_{31P} - v_{32P} < 20 \quad (8)$$

where,

v_{31P} denotes an Abbe number for the first positive lens, and

v_{32P} denotes an Abbe number for the second positive lens.

14. The wide-angle optical system according to claim 1, wherein:

the third lens unit includes a plurality of positive lenses, the plurality of positive lenses include a first positive lens, a second positive lens, and a third positive lens,

the first positive lens, among the plurality of positive lenses, is a positive lens located nearest to the object,

the second positive lens, among the plurality of positive lenses, is a positive lens located second from the object,

the third positive lens, among the plurality of positive lenses, is a positive lens located third from the object, and

the following conditional expression (9) is satisfied:

$$-50 < v_{33P} - (v_{31P} + v_{32P}) / 2 < 80 \quad (9)$$

where,

v_{31P} denotes an Abbe number for the first positive lens, v_{32P} denotes an Abbe number for the second positive lens, and

v_{33P} denotes an Abbe number for the third positive lens.

15. The wide-angle optical system according to claim 1, wherein:

the third lens unit includes a plurality of negative lenses, the plurality of negative lenses include a first negative lens and a second negative lens,

the first negative lens, among the plurality of negative lenses, is a negative lens located nearest to the object,

the second negative lens, among the plurality of negative lenses, is a negative lens located second from the object, and

the following conditional expression (10) is satisfied:

$$-40 < v_{31N} - v_{32N} < 50 \quad (10)$$

where,

v_{31N} denotes an Abbe number for the first negative lens, and

v_{32N} denotes an Abbe number for the second negative lens.

16. The wide-angle optical system according to claim 1, wherein the third lens unit is fixed at the time of carrying out the focal-position adjustment.

17. The wide-angle optical system according to claim 1, wherein the following conditional expression (11) is satisfied:

$$-60 < (R_{21F} + R_{21R}) / (R_{21F} - R_{21R}) < 1 \quad (11)$$

where,

R_{21F} denotes a radius of curvature of a surface on the object side of a predetermined lens component,

R_{21R} denotes a radius of curvature of a surface on the image side of the predetermined lens component, and

the predetermined lens component is a lens component located nearest to the object in the second lens unit.

61

18. The wide-angle optical system according to claim 1, wherein the following conditional expression (12) is satisfied:

$$0.2 < D21/fL < 3.0 \quad (12)$$

where D21 denotes a distance on an optical axis between a surface nearest to the object and a surface nearest to an image of the second lens unit.

19. The wide-angle optical system according to claim 1, wherein the following conditional expression (13) is satisfied:

$$1.01 < \beta 2F < 1.35 \quad (13)$$

where $\beta 2F$ denotes a magnification of the second lens unit at the first position.

20. The wide-angle optical system according to claim 1, wherein the following conditional expression (14) is satisfied:

$$1.01 < \beta 2N/\beta 2F < 1.15 \quad (14)$$

where,

$\beta 2F$ denotes a magnification of the second lens unit at the first position, and

$\beta 2N$ denotes a magnification of the second lens unit at the second position.

21. The wide-angle optical system according to claim 1, wherein the following conditional expression (15) is satisfied:

$$0.08 < (1 - \beta 2F^2) \times \beta 3F^2 < 0.45 \quad (15)$$

where,

$\beta 2F$ denotes a magnification of the second lens unit at the first position, and

$\beta 3F$ denotes a magnification of the third lens unit at the first position.

22. The wide-angle optical system according to claim 1, wherein the following conditional expression (16) is satisfied:

$$0.15 < (1 - \beta 2N^2) \times \beta 3N^2 < 0.55 \quad (16)$$

where,

$\beta 2N$ denotes a magnification of the second lens unit at the second position, and

$\beta 3N$ denotes a magnification of the third lens unit at the second position.

23. The wide-angle optical system according to claim 1, wherein the second lens unit includes only a positive lens.

24. A wide-angle optical system having a lens component which has a plurality of optical surfaces, and in the lens component, two optical surfaces are in contact with air, and at least one optical surface is a curved surface, the wide-angle optical system comprising, in order from an object side:

a first lens unit having a negative refractive power;
a second lens unit having a positive refractive power; and
a third lens unit having a positive refractive power,
wherein:

at a time of carrying out a focal-position adjustment from a far point to a near point, the second lens unit is moved from a first position toward a second position, the first position being a position at which a distance between the first lens unit and the second lens unit becomes minimum, and the second position being a position at which a distance between the second lens unit and the third lens unit becomes minimum,

the third lens unit includes at least three lens components, the at least three lens components including a first lens component and a second lens component, the first lens

62

component being a lens component located nearest to an object in the third lens unit, and the second lens component being a lens component located second from the object side in the third lens unit,
each of the first lens component and the second lens component has a positive refractive power,
the first lens unit includes only a negative lens,
the negative lens has an Abbe number larger than an Abbe number for a positive lens nearest to the object in the third lens unit and
the following conditional expression (1) is satisfied:

$$0.8 < f3L12/fL < 6.0 \quad (1)$$

where,

f3L12 denotes a combined focal length of the first lens component and the second lens component, and
fL denotes a focal length of the wide-angle optical system at the first position.

25. The wide-angle optical system according to claim 1, wherein:

the first lens unit includes a plurality of negative lens components,

the plurality of negative lens components include a first negative lens component and a second negative lens component,

the second negative lens component, among the plurality of negative lens components, is a negative lens component located second from the object, and

the following conditional expression (17) is satisfied:

$$-2.0 < fL/R12F_a < 5.0 \quad (17)$$

where R12F_a denotes a radius of curvature of a surface on the object side of the second negative lens component.

26. The wide-angle optical system according to claim 1, wherein:

the first lens unit includes a fourth lens component and a fifth lens component,

the fourth lens component is a lens component located nearest to the object in the first lens unit,

the fifth lens component is a lens component located second from the object side in the first lens unit,
the fourth lens component includes a negative lens component,

the fifth lens component includes a cemented lens, and
the following conditional expression (18) is satisfied:

$$-1.0 < fL/R12F_b < 0.5 \quad (18)$$

where R12F_b denotes a radius of curvature of a surface on the object side of the fifth lens component.

27. The wide-angle optical system according to claim 1, wherein:

the first lens unit includes a fourth lens component, a fifth lens component, and a sixth lens component,

the fourth lens component is a lens component located nearest to the object in the first lens unit,

the fifth lens component is a lens component located second from the object side in the first lens unit,

the sixth lens component is a lens component located third from the object side in the first lens unit,

the fourth lens component includes a negative lens component,

the fifth lens component includes a negative lens component,

the sixth lens component includes a positive lens component, and the following conditional expression (19) is satisfied:

$$-1.0 < fL/R12F_c < 0.4 \quad (19)$$

63

where R_{12F_c} denotes a radius of curvature of a surface on the object side of the fifth lens component.

28. The wide-angle optical system according to claim 1, wherein:

the first lens unit includes a fourth lens component, a fifth lens component, and a sixth lens component, the fourth lens component is a lens component located nearest to the object in the first lens unit, the fifth lens component is a lens component located second from the object side in the first lens unit, the sixth lens component is a lens component located third from the object side in the first lens unit, the fourth lens component includes a negative lens component, the fifth lens component includes a lens component for which an absolute value of a refractive power is smaller than an absolute value of a refractive power of the fourth lens component, the sixth lens component includes a cemented lens, and the following conditional expression (20) is satisfied:

$$-1.2 < fL/R_{12F_d} < 0.2 \quad (20)$$

where R_{12F_d} denotes a radius of curvature of a surface on the object side of the sixth lens component.

29. The wide-angle optical system according to claim 1, wherein:

the first lens unit includes a fourth lens component and a fifth lens component, the fourth lens component is a lens component located nearest to the object in the first lens unit, the fifth lens component is a lens component located second from the object side in the first lens unit, and the following conditional expression (21) is satisfied:

$$-1.0 < fL/fL_{12} < 0.4 \quad (21)$$

where fL_{12} denotes a focal length of the fifth lens component.

30. The wide-angle optical system according to claim 1, further comprising:

an image-side lens component, wherein:

the image-side lens component, among a plurality of lens components of the wide-angle optical system, is a lens component located nearest to an image, and the following conditional expression (22) is satisfied:

$$100 \times |f_{fin}| < |R_{fin}| \quad (22)$$

64

where,

f_{fin} denotes a focal length of an image-side lens component, and

R_{fin} denotes a radius of curvature of a surface on the image side of the image-side lens component.

31. The wide-angle optical system according to claim 1, further comprising:

an image-side lens component; and an optical element having zero refractive power,

wherein:

the image-side lens component, among a plurality of lens components of the wide-angle optical system, is a lens component located nearest to an image, the optical element is located on the image side of the image-side lens component, and the image-side lens component and the optical element are cemented.

32. The wide-angle optical system according to claim 1, wherein the following conditional expression (23) is satisfied:

$$2 \times y_{max} < fL \times \tan \omega_{max} \quad (23)$$

where,

y_{max} denotes a maximum image height, and

ω_{max} denotes an angle of view corresponding to the maximum image height.

33. The wide-angle optical system according to claim 1, wherein the following conditional expression (24) is satisfied:

$$ER2 < 4 \times fL/F_{EX} \quad (24)$$

where,

ER2 denotes an effective radius of a surface nearest to an image of the second lens component, and

F_{EX} denotes an effective F-value at the first position.

34. An image pickup apparatus comprising:

an optical system; and

an image sensor which is disposed on an image plane,

wherein:

the image sensor has an image pickup surface, and converts an image formed on the image pickup surface by the optical system to an electric signal, and the optical system is the wide-angle optical system according to claim 1.

* * * * *