



US012095589B1

(12) **United States Patent**
Bryant et al.

(10) **Patent No.:** **US 12,095,589 B1**
(45) **Date of Patent:** ***Sep. 17, 2024**

(54) **METHOD FOR MULTICHANNEL ACQUISITION OF GEOPHYSICAL DATA AND SYSTEM IMPLEMENTATION**

(58) **Field of Classification Search**
CPC H04L 12/40013; H04L 12/40019; H04L 7/008; H04L 61/1552; G06F 13/28; G01V 8/20; G01V 8/38
See application file for complete search history.

(71) Applicant: **Earthsystems Technologies, Inc.**,
Carrollton, TX (US)

(56) **References Cited**

(72) Inventors: **John Bryant**, Dallas, TX (US);
Frederick Hershel Savage, Austin, TX (US); **Timothy Beets**, Austin, TX (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Earthsystems Technologies, Inc.**,
Carrollton, TX (US)

2,172,778 A 9/1939 Taylor
2,307,887 A 1/1943 Haynes
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

This patent is subject to a terminal disclaimer.

JP 3944335 B2 7/2007
KR 101274251 B1 6/2013
(Continued)

(21) Appl. No.: **18/328,723**

OTHER PUBLICATIONS

(22) Filed: **Jun. 3, 2023**

Tanaka, Hiroyuki KM. "Muographic mapping of the subsurface density structures in Miura, Boso and Izu peninsulas, Japan." Scientific reports 5 (2015): 8305.

(Continued)

Related U.S. Application Data

Primary Examiner — Dung B Huynh

(63) Continuation of application No. 18/321,510, filed on May 22, 2023, which is a continuation of application
(Continued)

(74) *Attorney, Agent, or Firm* — Schultz & Associates, P.C.


(51) **Int. Cl.**
H04L 12/40 (2006.01)
G01V 3/20 (2006.01)
(Continued)

(57) **ABSTRACT**

A method for a multichannel geophysical data acquisition system is provided in the field of electrical resistivity tomography. Individual and autonomous node operating systems are provided. Separate communication channels for upstream and downstream data transfer, high voltage transfer and synchronization signals are provided. A novel use of high voltage isolation barriers is also provided. A direct memory access data transfer process is provided.

(52) **U.S. Cl.**
CPC **H04L 12/40013** (2013.01); **G01V 3/20** (2013.01); **G01V 3/38** (2013.01);
(Continued)

15 Claims, 42 Drawing Sheets



Related U.S. Application Data

No. 18/321,462, filed on May 22, 2023, which is a continuation of application No. 17/662,605, filed on May 9, 2022, now Pat. No. 11,671,277, which is a continuation of application No. 17/661,896, filed on May 3, 2022, now Pat. No. 11,658,844, which is a continuation of application No. 17/658,407, filed on Apr. 7, 2022, which is a continuation-in-part of application No. 16/948,062, filed on Aug. 28, 2020, which is a continuation of application No. 16/948,061, filed on Aug. 28, 2020, now Pat. No. 11,329,843, which is a continuation of application No. 16/948,059, filed on Aug. 28, 2020, now Pat. No. 11,323,285.

(51) **Int. Cl.**

G01V 3/38 (2006.01)
G06F 13/28 (2006.01)
H04L 7/00 (2006.01)
H04L 61/4552 (2022.01)

(52) **U.S. Cl.**

CPC **G06F 13/28** (2013.01); **H04L 7/0008** (2013.01); **H04L 12/40019** (2013.01); **H04L 61/4552** (2022.05)

(56)

References Cited

U.S. PATENT DOCUMENTS

3,735,249	A	5/1973	Stoll	
3,968,428	A	7/1976	Numoto	
4,023,140	A	5/1977	Siems et al.	
4,210,813	A	7/1980	Romanovsky et al.	
4,319,347	A	3/1982	Savit	
5,357,202	A	10/1994	Henderson	
5,537,045	A	7/1996	Henderson	
5,920,828	A	7/1999	Norris et al.	
6,226,601	B1	5/2001	Longaker	
6,332,109	B1 *	12/2001	Sheard	G01V 1/24 324/357
6,359,438	B1	3/2002	Bittar	
6,404,203	B1	6/2002	Lagmanson	
6,549,012	B2	4/2003	Stolarczyk	
6,674,286	B2	1/2004	Lagmanson	
6,804,625	B1	10/2004	Bryant	
6,865,177	B1 *	3/2005	Park	H04J 13/0025 370/514
6,916,983	B2	7/2005	Orsini et al.	
6,977,867	B2	12/2005	Chamberlain	
7,069,780	B2	7/2006	Ander	
7,158,048	B2	1/2007	Abdelhadi	
7,239,154	B2	7/2007	Lundstrom	
7,269,095	B2	9/2007	Chamberlain et al.	
7,299,133	B2	11/2007	Duncan et al.	
7,353,132	B2	4/2008	Sheard et al.	
7,386,402	B2	6/2008	Bryant	
7,388,382	B2	6/2008	Strack et al.	
7,633,296	B2	12/2009	Safinya et al.	
7,663,973	B2	2/2010	Chamberlain	
7,689,364	B2	3/2010	Lagmanson et al.	
7,788,049	B2	8/2010	Bryant et al.	
7,813,883	B2	10/2010	Bryant	
7,939,751	B2 *	5/2011	Asplund	H01R 4/66 204/196.01
8,019,547	B2	9/2011	Bryant	
8,148,992	B2 *	4/2012	Kowalczyk	G01V 3/104 324/365
8,209,125	B2	6/2012	Berkovitch et al.	
8,321,160	B2	11/2012	Bryant et al.	
8,380,439	B2	2/2013	Lagmanson et al.	
8,483,965	B2	7/2013	Bradley et al.	
8,892,410	B2	11/2014	Krohn	
8,965,705	B2	2/2015	Lagmanson et al.	
9,051,832	B2	6/2015	Ahler et al.	

9,151,861	B2	10/2015	Labrecque	
9,158,022	B2	10/2015	Park et al.	
9,293,843	B2	3/2016	Lu	
9,551,210	B2 *	1/2017	Bartel	E21B 47/002
9,638,821	B2	5/2017	Meyer	
9,700,893	B2	7/2017	Moeny	
9,921,330	B2	3/2018	Berglund	
9,952,345	B1	4/2018	Harro	
9,995,838	B2	6/2018	Labrecque	
10,012,063	B2	7/2018	Storslett et al.	
10,310,118	B2	6/2019	Willis	
10,408,960	B2	9/2019	Berglund	
10,901,117	B2 *	1/2021	Sale	H04Q 9/00
11,329,843	B1 *	5/2022	Bryant	H04L 12/40013
11,671,277	B1 *	6/2023	Bryant	H04L 7/0008 709/253
2001/0005407	A1 *	6/2001	Kaewell, Jr.	H04W 88/02 375/356
2002/0043977	A1 *	4/2002	Vail, III	G01V 3/24 324/368
2003/0071604	A1 *	4/2003	Lee	G01R 27/08 324/72.5
2003/0207681	A1 *	11/2003	Rowitch	G01S 19/07 370/335
2004/0039758	A1 *	2/2004	Li	G06F 12/0269
2005/0043046	A1 *	2/2005	Lee	H04W 36/0072 455/502
2006/0193305	A1 *	8/2006	Litwin	H04B 1/70735 370/503
2006/0238200	A1 *	10/2006	Johnstad	G01V 1/38 324/337
2007/0255891	A1 *	11/2007	Chow	G06F 13/161 711/103
2008/0005457	A1 *	1/2008	Flake	G06F 3/0625 711/112
2008/0115082	A1 *	5/2008	Simmons	G06F 16/29 707/999.003
2008/0253085	A1 *	10/2008	Soffer	H05K 1/185 361/679.46
2008/0298120	A1 *	12/2008	Chow	G11C 13/0004 365/163
2009/0043932	A1 *	2/2009	Bernardi	G11C 5/04 710/110
2009/0248309	A1 *	10/2009	Neville	G01V 5/107 250/269.4
2010/0029268	A1	2/2010	Myer et al.	
2010/0083136	A1 *	4/2010	Komine	G06F 9/52 715/255
2010/0194396	A1 *	8/2010	Bryant	G01V 3/04 324/357
2011/0158043	A1 *	6/2011	Johnstad	G01V 3/12 324/365
2012/0112753	A1	5/2012	Wittle	
2012/0169352	A1 *	7/2012	Helwig	G01V 3/083 324/601
2012/0223718	A1	9/2012	Peppe et al.	
2012/0242343	A1 *	9/2012	Lindqvist	G01V 3/083 324/365
2012/0243375	A1 *	9/2012	Melvin, II	G01S 15/876 367/118
2013/0094332	A1 *	4/2013	Harrick	A01K 79/02 367/139
2013/0124736	A1 *	5/2013	Park	H04L 67/12 709/227
2013/0304990	A1 *	11/2013	Bass	G06F 12/0835 711/E12.017
2014/0008968	A1	1/2014	Money	
2014/0253132	A1 *	9/2014	Juhasz	G01C 13/00 324/365
2014/0254317	A1	9/2014	Thompson et al.	
2015/0050902	A1	2/2015	Umeki et al.	
2015/0167440	A1	6/2015	Kasevich et al.	
2015/0178243	A1 *	6/2015	Lowery	G06F 12/0653 709/212
2015/0229511	A1	8/2015	Le Pallec et al.	
2015/0233242	A1	8/2015	Li et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0131791 A1* 5/2016 Wu G01V 3/38
702/7
2016/0239025 A1* 8/2016 van der Merwe F16K 31/082
2016/0252640 A1* 9/2016 Chubak G01V 3/02
324/357
2016/0282496 A1* 9/2016 Yuan G01V 3/02
2016/0349405 A1 12/2016 Martin et al.
2017/0126390 A1 5/2017 Akahane
2017/0153277 A1 6/2017 Dragt et al.
2017/0235510 A1* 8/2017 Hu G06F 13/32
710/308
2017/0257238 A1* 9/2017 Qian H04L 25/03834
2017/0315655 A1 11/2017 Weinerth
2018/0003559 A1* 1/2018 Smith H04N 25/745
2018/0267191 A1 9/2018 Schmidt et al.
2018/0307636 A1* 10/2018 Mahalingam G06F 9/45558
2018/0348038 A1* 12/2018 Kleman G01F 23/284
2019/0001839 A1 1/2019 Masuda
2019/0126290 A1 5/2019 Takahashi et al.
2019/0130550 A1* 5/2019 Mitsubayashi G06T 5/50
2019/0148940 A1 5/2019 Itaya
2019/0302149 A1 10/2019 Kerr
2020/0001091 A1 1/2020 Marnfeldt
2020/0069355 A1 3/2020 Keidar
2020/0110185 A1 4/2020 Xu et al.
2020/0128615 A1* 4/2020 Bonnett H04W 84/18
2020/0305004 A1* 9/2020 Ansley H04L 12/2801
2020/0309641 A1 10/2020 Balboni et al.
2020/0322726 A1* 10/2020 Wang G08C 23/04
2020/0351693 A1* 11/2020 Jung H04W 24/08
2020/0393395 A1 12/2020 James et al.
2021/0044314 A1 2/2021 Rodriguez et al.
2021/0088571 A1 3/2021 Peng et al.
2021/0109250 A1* 4/2021 Sale G01F 23/14
2021/0137408 A1 5/2021 Ben-Haim et al.
2021/0208899 A1* 7/2021 Bornemann G07C 5/08
2021/0231907 A1 7/2021 Park
2021/0241971 A1 8/2021 Bajai et al.
2022/0121607 A1* 4/2022 Wu G06F 13/28
2022/0286887 A1* 9/2022 Zheng H04W 24/10

2022/0414271 A1* 12/2022 Gunyuzlu G06F 21/31
2023/0083651 A1* 3/2023 Tian G01V 1/307
702/14
2024/0117467 A1* 4/2024 Li E21B 43/28

FOREIGN PATENT DOCUMENTS

WO 9429752 A1 12/1994
WO 2011158103 A1 12/2011
WO 2015062327 A1 5/2015
WO 2015002558 A2 9/2015

OTHER PUBLICATIONS

Liaw, Alfred L., et al. "Microseisms in geothermal exploration studies in Grass Valley, Nevada." *Geophysics* 44.6 (1979): 1097-1115.
Guffanti, Marianne, et al. "Volcano-monitoring instrumentation in the United States, 2008." US Geological Survey Open-File Report 1165 (2009).
Jordan, R., et al. "The Mars express MARSIS sounder instrument." *Planetary and Space Science* 57.14-15 (2009): 1975-1986.
Loke, M.H. "Electrical imaging surveys for environmental and engineering studies: A practical guide to 2-D and 3-D surveys." (1997).
Batayneh, Awni T. "2D Electrical Imaging of an LNAPL Contamination, Al Amiriyya Station, Jordan." *Journal of Applied Sciences* 5(1) : 52-59, 2005.
Cook, John C. "An Electrical Crevasse Detector" *Geophysics*, vol. 21, No. 4, 1956, p. 1055-70, 9 figs. *Journal of Glaciology* 3(22): 146-147. doi: 10.3189/S0022143000024485.
Schuster, C. L., et al. "Natural gas massive hydraulic fracturerearch and advanced technology project." Quarterly report: Feb. 1977-Apr. 1977 (1977) doi: 10.2172/7318329.
Athanasίου, E.N. et al. "Non-destructive DC resistivity surveying using flat-base electrodes." *Near Surface Geophysics* 5. (2007): doi: 10.3997/1873-0604.2007008.
Kiflu, H. G. "Improved 2D and 3D resistivity surveys using buried electrodes and optimized arrays: The multi-electrode resistivity implant technique (MERIT)." Graduate Theses and Dissertations. University of South Florida. (2016).

* cited by examiner




FIG. 1




FIG. 3




FIG. 2




FIG. 4A




FIG. 4B




FIG. 4C





FIG. 4D







FIG. 5B-2







FIG. 6A-1





FIG. 6A-2

FROM FIG. 6A-1

TO FIG. 6A-3

FIG. 6A-3








FIG. 6B-2

TO FIG. 6B-4

FIG. 6B-3









FIG. 8



TO FIG. 9B

FIG. 9A





FIG. 9B



TO FIG. 10B
FIG. 10A





FIG. 10B



TO FIG. 11B

FIG. 11A

FROM FIG. 11A




FIG. 11B





FIG. 11C



TO FIG. 11E

FIG. 11D

FROM FIG. 11D




FIG. 11E

A dipole-dipole shot commences by sending messages sent down the communication link, informing nodes what role to play -A, B, M, or N.

Each M-N pair is a channel. When the channels are chained together, then the shot proceeds in "multi channel mode". A channel chain looks like this:

Chan 1: M = 3, N = 4
 Chan 2: M = 4, N = 5
 etc.

Chains may go forward or backwards from the current injection nodes, A and B. The chain length (number of channels) is only limited by the total current draw of the array.

In pseudo-code, here's how a dipole survey works:

```
for (A=2, B=1; A < nodes-3; A++, B++) { /* On PC */
  create_a_chain_of_M_N_pairs; /* done by control board, based on msgs*/
  /* received from PC */
  do_shot(); /* CB operates power supply and drives node state machines */
  /* with 1 bit pulses on RS-485 to processor GPIO */
  gather_data(); /* CB reads data from nodes, forwards to PC */
  end_of_data(); /* Tell PC shot is complete. */
}
```

The loop above may also be performed backwards, with A and B starting at the end of the array.

In order to remove voltage offset from the resistivity data, and to only do one shot per AB location, we do "4 phase sampling". There is a positive and negative voltage phase. These phases are split in two to allow both even and odd numbered channels to perform sampling when the voltage is positive and negative.

The code that accomplishes this is shown below, in function do_shot().

```
/*
 * voltage: voltage limit
 * current: target current
 * multi: do multi-channel shot. If this value is 0, shot will
 * be single channel, which means that M and N nodes
 * do not change identity during a shot.
 */
int16_t do_shot(uint16_t voltage, uint16_t current, uint16_t multi)
{
```

TO FIG. 11G

FIG. 11F

FROM FIG. 11F

```
/* Apply current/voltage settings in power supply */
modbus_set_current(current);
modbus_set_voltage(voltage);
modbus_set_runstop(0);

/* SYNC 1 -- Send sync signal. A and B nodes will connect to +/-power */
sync_signal();
vTaskDelay(2);      /* wait 20 msec*/
CURRENT_ON;        /* Turn on power supply */

/* Start task that monitors rising current level */
gRamping= 1;
xTaskNotifyGive(iTaskHandle);

/* Wait here till monitor task says current at target level */
xSemaphoreTake(rampSem, portMAX_DELAY);
gRamping= 0;

/* SYNC 2 --Tells N nodes to start sampling */
sync_signal();

/* At the same time, read the source current and voltage */
/* This is done by two independent tasks */
xTaskNotifyGive(iTaskHandle);
xTaskNotifyGive(sTaskHandle);

/* Wait here until sampling period expires */
vTaskDelay(SAMPLING_TIMEA);

if (multi) {
    /* Sync 2.5: Send signal telling M and N nodes to swap roles */
    sync_signal();
    /* Wait for new N nodes to take sample */
    vTaskDelay(SAMPLING_TIMEB);
}
```

TO FIG. 11H

FIG. 11G

FROM FIG. 11G

```
CURRENT_OFF;

vTaskDelay(2); /* 20 msec*/

/* Sync 3: Tell nodes A and B to release the power lines */
sync_signal(); /* release pins, SYNC 3 */

vTaskDelay(50); /* sleep for .5 sec */
/* Sync 4: A and B swap roles, this will create a negative voltage source */
/* M and N nodes return to their originally assigned roles */
sync_signal(); /* A and B connect, SYNC 4 */
vTaskDelay(50); /* sleep for .5 sec */

CURRENT_ON;

/* Wait for current to ramp up again, for negative part of cycle */
gRamping= 1;
xTaskNotifyGive(iTaskHandle);
xSemaphoreTake(rampSem, portMAX_DELAY);
gRamping= 0;

/* Sync 5: Tell the N nodes to take samples */
sync_signal();

/* At the same time, measure the source current and voltage */
xTaskNotifyGive(iTaskHandle);
xTaskNotifyGive(sTaskHandle);

vTaskDelay(SAMPLING_TIMEA); /* sleep for 1 sec */

if (multi) {
    /* Sync 5b: M nodes become N nodes, N nodes become M nodes */
    sync_signal();
    /* Wait while new N nodes take measurements */
    vTaskDelay(SAMPLING_TIMEB);
}

/* Shot is done, turn off the current */
CURRENT_OFF;
vTaskDelay(20);

/* SYNC 6: Tell the A and B nodes to release power lines */
sync_signal();
vTaskDelay(50);

return (0);
}
```

FIG. 11H




FIG. 12

FIG. 13A




FIG. 13B




FIG. 13C





FIG. 13D






FIG. 14




FIG. 15




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 17A




FIG. 17B




FIG. 17C

1**METHOD FOR MULTICHANNEL
ACQUISITION OF GEOPHYSICAL DATA
AND SYSTEM IMPLEMENTATION****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 18/321,510, filed on May 22, 2023, which is a continuation of U.S. application Ser. No. 18/321,462 filed on May 22, 2023, which is a continuation of U.S. application Ser. No. 17/662,605 filed on May 9, 2022, now U.S. Pat. No. 11,671,277, granted on Jun. 6, 2023, which is a continuation of U.S. application Ser. No. 17/661,896 filed on May 3, 2022, now U.S. Pat. No. 11,658,844, granted on May 23, 2023, which is a continuation of U.S. application Ser. No. 17/658,407 filed on Apr. 7, 2022, which is a continuation-in-part of U.S. application Ser. No. 16/948,062 filed on Aug. 28, 2020, which is a continuation of U.S. application Ser. No. 16/948,061 filed on Aug. 28, 2020, now U.S. Pat. No. 11,329,843 granted on May 10, 2022 which is a continuation of U.S. application Ser. No. 16/948,059 filed on Aug. 28, 2020, now U.S. Pat. No. 11,323,285 granted on May 3, 2022. The patent applications identified above are incorporated herein by reference in their entirety to provide continuity of disclosure.

FIELD OF THE INVENTION

The field of the invention is electrical resistivity tomography (ERT) systems

for locating subsurface anomalies, such as variations in density and the presence of groundwater. Raw resistivity data is collected by a reconfigurable network of sensors that distributes current into the ground and measures resulting voltages.

BACKGROUND OF THE INVENTION

ERT is a geophysical technique for imaging subsurface structures using electrical resistivity measurements made by electrodes impressed in the ground.

Resistivity can be computed if the intensity of a current injected into the ground, and the resulting potential difference established between measurement electrodes are known. Resistivity depends on the geometry of the electric field, the nature of the soil and the method used to measure the injected current and the resulting potential difference between the electrodes.

In practice, a system of electrodes is placed in the ground in a predetermined geometry. Current is then introduced into the ground through a pair of the electrodes. An electric field results and the current is measured. Voltage measurements are taken at various other pairs of electrodes in the system. Resistivity values at various depths in the ground can then be determined from the measured current and the voltages.

A resistivity model is created using a least squares data inversion on the resistivity values that minimizes the error in the data. The resistivity model is then subjected to geostatistical analysis, using kriging or other methods to derive a resistivity map. The resistivity map includes equipotential lines indicating varying bands of resistivity at varying depths in the soil. The bands can be used to locate subsurface moisture and other anomalies.

Many topologies are known for electrode placement in an ERT survey. Among them are the Wenner, Wenner-Schlumberger Pole-dipole and dipole-dipole arrangements.

2

Referring to FIG. 1, a dipole-dipole topology **100** will be described. In the dipole-dipole topology, the spacing between the current injection probes **105** and the voltage measurement probes **107** is the same. The distance between current injection probes **105** and voltage measurement probes **107**, is typically a whole number multiplier “n” of the distance “a”.

Referring to FIG. 2, an example of a channel of test data in a dipole-dipole arrangement **200** will be described. Electrodes **202, 204, 206, 208, 210, 212, 214, 216, 218, 220** and **222** are inserted in ground **224** at an equidistant spacing “a” in a straight line. A known current is injected at current injection probes **230**, the resulting differential voltage at electrode pairs **237, 239, 241, 243, 245, 247, 249** and **251**, is measured to obtain the apparent resistivity of the subsurface can be determined at different depths forming a two-dimensional matrix of resistivity values. In this example, impressing a current injection probes **230** and taking a voltage reading at electrode pairs **237** results in a resistivity value for position **280** at depth **260** and horizontal distance **268**. Similarly, a voltage reading at electrode pairs **239** results in a resistivity value for position **281** at depth **261** and distance **269**. Likewise, a voltage reading at electrode pairs **241** results in a resistivity value for position **282** at depth **262** and distance **270**. A voltage reading at electrode pairs **243** results in a resistivity value for position **283** at depth **263** and distance **271**. A voltage reading at electrode pairs **245** results in a resistivity value for position **284** at depth **264** and distance **272**. A voltage reading at electrode pairs **247** results in a resistivity value for position **285** at depth **265** and distance **273**. A voltage reading at electrode pairs **249** results in a resistivity value for position **286** at depth **266** and distance **274**. A voltage reading at electrode pairs **251** results in a resistivity value for position **287** at depth **267** and distance **275**. As can be seen, the farther away the voltage electrodes are from the current injection electrodes, the deeper into the earth the resistivity values are taken. The string of resistivity values for this single placement of the current injection probes can be termed a “channel” of resistivity data.

In a dipole-dipole topography, resistivity can be calculated from the following equation:

$$P_A = \frac{V}{I} \pi A n(n+1)(n+2) \quad \text{Eq. 1}$$

Where:

n=the integer value representing the spacing distance from the current injection electrodes to the measurement electrodes

T=a constant

A=internode spacing

P_A=resistivity

V=voltage potential measured across neighboring measurement electrodes

I=current impressed at the injector electrodes.

Referring to FIG. 3, in order to complete an ERT survey, several (or many) diagonal channels of data are required. After each set of voltage measurements is taken, the current injection probes are typically advanced from left to right from position **302** to positions **304, 306, 308, 310, 312** and **314**, in sequence. As additional voltage differential measurements are taken, separate channels of resistivity readings are derived and advanced in the same sequence from channel **320**, channel **322**, to channel **324**, to channel **328**, to channel

330 and to channel 332. The channels form linear diagonal lines at approximately 45° from an interstitial position between the current injection nodes. The result is a set of differential resistivity values associated with a set of sub-surface points directly below the electrodes. The set of differential resistivity values is then subjected to curve smoothing routines which result in a set of continuous equipotential lines that can be interpreted to discover sub-surface anomalies.

Many systems currently exist for employing ERT in the field. One very typical system is the Super Sting System available from Advanced Geosciences, Inc. of Austin, Texas. The Super Sting System provides a continuous cable with multiple cylindrical electrodes which may be configured as either transmitters or receivers. Each electrode typically contacts the ground with a single metal stake contact. One of the main drawbacks to this type of system, is that the cable segments must be connected with very careful attention to the order in which they are connected. This makes them time consuming to use. Further, the cable sections and nodes can potentially fail during use, resulting in unintelligible or useless data. Further, the data collection provided by these systems can be limited because of the relatively slow speed of the mechanical relays in each survey node and data contention on the single communication line.

Another known system is described in U.S. Pat. No. 8,019,547 to Bryant. The invention of the '547 patent employs reconfigurable nodes located at the stakes. The nodes may be set as either a current impression nodes or a voltage measurement nodes. Programming of the nodes is carried out by a single controller. One potential drawback to this type system is that the various controllers all share a common ground with the high voltage supply line. The common ground makes data acquisition and communication difficult due to noise created by the high voltage and current values necessary to impress current into the injection probes.

A similar known system is described in U.S. Pat. No. 8,380,439 to Lagmanson. This system likewise includes a series of nodes which are remotely reconfigurable. The nodes have individual unique addresses which are discovered by a single controller. The process used by the controller requires a communication with each node and so is relatively time consuming. Once discovered, the controller can set the probes to a current injection or a voltage measurement function. Data acquisition in this system is relatively slow due to the communication protocols used which can cause faulty data. Further, voltage measurement by the probes requires a physical disconnection from the power circuit which considerably lengthens the time necessary to achieve all the required voltage measurements.

U.S. Pat. No. 6,332,109 to Sheard similarly discloses a geological data acquisition system which includes a plurality of nodes for obtaining measurement signals. The nodes are connected on a 4-channel cable connection which necessarily limits the speed at which the data can be transmitted before and after excitation pulses are employed. The 4-channel system also suffers from inherent noise problems resulting in potentially unreliable data.

U.S. Pat. Nos. 5,357,202 and 5,537,045 to Henderson both disclose directly monitoring the soil subjacent to a fluid containment area by burying electrodes. Henderson '202 discloses a plurality of four-plate electrode systems. A voltage and a known current are applied across the outer pair of plates. The resulting potential difference is measured across the inner pair of plates. Henderson '045 also discloses a system of individual electrodes that, by impressing a current into the ground and varying the spacing of the

potential measurement electrodes, can indirectly measure the resistivity at a calculated depth. One problem in using in the system(s) disclosed by Henderson is electrode galvanization. Electrode galvanization occurs when a consistent current of the same plurality is impressed into the ground over a long period of time. The result is a resistive barrier on the electrodes which causes erroneous readings and useless data.

U.S. Pat. No. 6,804,625 to Bryant, discloses a method and apparatus for creating an electrical resistivity map of the volume beneath a slab foundation by placing electrodes through a foundation, and applying a current through them. The invention employs an array of electrodes to impress a known current in the soil and measure the resulting electrical potential of the electrodes. Bryant '625 further discloses a method for converting the measured potential to a resistivity value, assigning the resistivity value to a spatial coordinate, and storing a plurality of values in computer files.

In all cases, the current state of the art is unsatisfactory because it does not adequately isolate the high voltage current signal from the measurement instruments creating incorrect readings and unreadable data. The systems of the prior art also suffer from slow data transfer and slow system configuration times. The prior art is also unsatisfactory because it fails to provide adequate temperature control for required instrumentation leading to further unreliable data. Moreover, the state of the art does not provide for adequate memory management or communication speed. The current state of the art is also unsatisfactory because it fails to account for electrode galvanization.

SUMMARY OF THE INVENTION

The preferred embodiment provides a system for impressing current into the ground and gathering resistivity data from a set of nodes that operate independently of one another but in synchronization to carry out an ERT survey. A preferred embodiment also provides for individual and autonomous operating systems running on each processor in each node. Separate communication channels are provided for upstream and downstream data transfer, high voltage transfer and synchronization signals. A novel set of high voltage isolation barriers is also provided in both the master control board and each node in the array. High voltage isolation is also provided by a triple-ground reference circuit topology. A preferred embodiment also provides for a rapid means of isolated data transfer by employing a novel form of direct memory access between the processors of the nodes and the master control board. Near instantaneous and error free packet transfer is achieved, greatly increasing the speed and accuracy of the ERT survey.

The preferred embodiment provides an alternating waveform of the injected current during the sequence of geophysical test in order to maximize the precision of data readings. The preferred embodiment also provides measurement node type assignments that are interleaved to compress survey time.

The preferred embodiment also provides for a novel method of self-calibration of the nodes to quickly and exactly calibrate the precision measurement devices required for voltage measurements.

The preferred system further comprises a novel set of nodes that have are identical and un-serialized at system start up, but then are independently self-addressed by each node to maximize system flexibility to reduce maintenance time.

The preferred system also provides a set of survey programming that does away with node programming tables in favor of faster looped survey algorithms.

The preferred system further provides a novel cabling system which isolates the high voltage supply channel from a synchronization channel, an independent measurement channel and a memory bus channel for quiet and error free command and measurement data packet transmission.

In the event of damage to a sensor or damage to an interconnecting cable, a replacement sensor or cable may be added to the array of sensors without excessive downtime and expensive field repairs because all of the nodes are identical and are un-serialized. Further, provisions are made for single channel testing which eliminates the necessity for repeating an electrode survey after a node malfunction.

A preferred embodiment system further comprises a novel enclosure cooling system, including strategically placed ducting and insulation, which maintains proper and consistent controller temperature in elevated temperature ambient environments, which greatly enhances the precision of the current and voltage measurements.

A preferred embodiment of the system further comprises a novel node enclosure which includes a failsafe four bar linkage toggle to each ground stake which enhances physical stability of the nodes during the testing and increases the reliability of electrical connectivity to the stake, thereby reducing measurement error and decreasing both setup and survey times.

A preferred embodiment further provides for a novel automatic polarity reversal during the survey routine which substantially reduces or eliminates electrode galvanization.

BRIEF DESCRIPTION OF THE DRAWINGS

In the detailed description of the preferred embodiments presented below, reference is made to the accompanying drawings.

FIG. 1 is a schematic diagram of a dipole-dipole arrangement topology.

FIG. 2 is a schematic diagram of a typical dipole-dipole test data channel.

FIG. 3 is a schematic diagram of a set current injection probes traversing a dipole-dipole topology.

FIG. 4A is a schematic diagram of a preferred embodiment of the system.

FIG. 4B is a schematic diagram of a control box of a preferred embodiment.

FIG. 4C is a schematic diagram of a data cable of a preferred embodiment.

FIG. 4D is a schematic diagram of a data cable of a preferred embodiment.

FIG. 5A-1-5A-2 is a schematic diagram of a preferred embodiment of a master control board.

FIG. 5B-1-5B-2 is a schematic diagram of a preferred embodiment of a master control board.

FIG. 6A-1-6A-3 is a schematic diagram of a preferred embodiment of a measurement node.

FIG. 6B-1-6B-4 is a schematic diagram of a preferred embodiment of a measurement node.

FIG. 7 is a schematic diagram of a preferred embodiment of a measurement voltage divider network.

FIG. 8 is a preferred embodiment of an ERT survey method.

FIG. 9A is a preferred embodiment of a method of node self-enumeration.

FIG. 9B is a preferred embodiment of a method of node self-enumeration.

FIG. 10A is a preferred embodiment of a method of formatting an ERT test topology.

FIG. 10B is a preferred embodiment of a method of formatting an ERT test topology.

FIG. 11A is a preferred embodiment of a method of taking ERT test data.

FIG. 11B is a preferred embodiment of a method of taking ERT test data.

FIG. 11C is a preferred embodiment of a method of self-calibration.

FIG. 11D is a preferred embodiment of a method of taking ERT test data.

FIG. 11E is a preferred embodiment of a method of taking ERT test data.

FIGS. 11F, 11G and 11H is an example of a software routine for survey looping.

FIG. 12 is a signal timing chart for taking ERT test data of a preferred embodiment.

FIG. 13A is a schematic diagram of a method of node interleaving.

FIG. 13B is a schematic diagram of a method of node interleaving.

FIG. 13C is a schematic diagram of a method of node interleaving.

FIG. 13D is a schematic diagram of a method of node interleaving.

FIG. 14 is a schematic diagram of a data communication packet.

FIG. 15 is a test result ERT map resulting from a field test of a preferred embodiment.

FIG. 16A is an isometric view of a node housing for a preferred embodiment.

FIG. 16B is an isometric view of a node housing for a preferred embodiment.

FIG. 16C is a partial section view of a node housing along lines C-C.

FIG. 16D is an exploded view of a node housing for a preferred embodiment.

FIG. 17A is an isometric exploded view of a preferred system enclosure.

FIG. 17B is an isometric exploded view of a preferred system enclosure.

FIG. 17C is an isometric view of a preferred system enclosure.

DETAILED DESCRIPTION OF THE INVENTION

In the description that follows, like parts are marked throughout the specification and figures with the same numerals, respectively. The figures are not necessarily drawn to scale and may be shown in exaggerated or generalized form in the interest of clarity and conciseness.

Referring to FIG. 4A, a schematic diagram of a preferred embodiment will be described. System 400 includes control box 401 connected to an upstream set of nodes 404, 406, 408 and 410. The system may have any number of nodes as indicated by the ellipses in the drawing. Node 404 is connected to control box 401 and node 406. Node 406 is connected downstream to node 408 and upstream to node 404. Node 408 is connected downstream to node 410 and upstream to node 406. Node 408 is also operatively connected to auxiliary 12V DC source 412b. Auxiliary 12V DC source 412b is provided to extend the maximum number of nodes in the array to approximately 50. However, though use of an auxiliary 12V DC source at approximately every 25 nodes, the number of nodes in the array can be extended to

approximately 100, given a node spacing of about 4 meters. Extending the maximum number of nodes is important because it vastly extends the distance over which a survey may be conducted over the prior art. Node **410** is in the terminal position in this example system and is only connected downstream to node **408**. Each of nodes **404**, **406**, **408** and **410** is mechanically and electrically connected to a metallic stake **421**, **423**, **425** and **427**, respectively, that is driven into ground **430**.

The control box and the nodes are connected to each other via separate system communication cables **403**, **405**, **407**, **409** and **411**, as will be further described. Control box **401** is connected to PC controller **414** via standard USB cable **420**. Control box **401** is also connected to main 12V DC power source **412a** via dual 50 Amp connector cable **415**.

PC controller **414** is typically a laptop computer operating a Windows® operating system and a control application used for coordinating system functions and displaying graphical resistivity maps.

Referring to FIG. 4B, a schematic architecture diagram of control box **401** will be described.

Control box **401** includes inverter **452**, high voltage power supply **454**, master control board **402**, and regulated 12V DC power source **412a**.

12V DC power source **412a** supplies 12V DC power to power master control board **402** through a separate isolated DC-DC converter **461**, eliminating any electrical connection to the high voltage circuitry return. DC-DC converter **461** is the Cincon Electronics CQB150 W-24S28. 12V DC power source **412a** in a preferred embodiment is a 12V DC battery. In a preferred embodiment, the battery is an automotive lead acid battery capable of storing 800 cold cranking Amps. In other embodiments, 12V DC power source **412a** can also be provided by a solid-state power supply.

Inverter **452** is connected to 12V DC power source **412a** and is activated by push switch **456**. Inverter **452** preferably has an input voltage of 12V, an output voltage of 220V and an output frequency of 50 Hz. The output of the inverter is a pure sine wave with an actual power of 1500 W and a peak power of OW. Inverter **452** is preferably Part No. CJ-3000Q available from Banggood.com of Hong Kong.

Inverter **452** supplies power to the high voltage power supply. Relay **458** is controlled by master control board **402**. High voltage power supply **454** is further connected to master control board **402** to supply high voltage to the nodes of the system. High voltage power supply **454** in a preferred embodiment is a precision programable DC power supply with a temperature drift of less than 50 ppm, 0.1% accuracy and resolution of 10 mV and 1 μ A with an adjustable voltage range from 0 to 1000V and an adjustable current range from 0 to 1 A. Equivalent command interface is possible for a 0 to 500V supply with current adjustable from 0 to 2 A. Output power is preferably 100 W. Low ripple is a preferred attribute of the high voltage power supply including a voltage ripple of less than 5 mV RMS and a current ripple of less than 3 mV and a read back value temperature coefficient of 50 ppm. In a preferred embodiment, high voltage power supply **454** is Part No. HSPY-600, available from aliexpress.com.

Activation of the high voltage power supply is accomplished by pressing the power button on inverter **452** which generates the AC voltage required for the power supply. Control signals are sent from master control board **402** to high voltage power supply **454** using an RS232 interface.

12V DC power source **412a** is further connected to thermoelectric cooler **1760** through actuating relay **458**. Master control board **402** controls the thermoelectric cooler

based on temperature data from thermostat **417**. In a preferred embodiment, thermoelectric cooler **1760** is the TEC Air Cooler available from TE Technologies, Inc. of Traverse City, Michigan. Preferably, thermoelectric cooler **1760** operates at a supply voltage of 12V DC, Model No. AC-027 requiring approximately 27 W operating power at a 0° temperature difference, available from TE Technologies, Inc.

Referring to FIG. 4C, an example of system communication cable **403** will be further described.

Line **460** includes the high voltage positive signal. Line **462** includes the high voltage negative signal. Together lines **460** and **462** comprise a high power bus **464**. High power bus **464** delivers a high voltage high current signal for injection by the nodes.

Line **466** comprises a positive 28V DC power signal. Line **468** comprises a ground for the positive 28V DC power signal. Together lines **466** and **468** comprise supply power bus **470**. Supply power bus **470** is used to provide operational current for each of the nodes and, in one embodiment, also for synchronization signaling, as will be further described.

Line **472** comprises the positive voltage measurement line. Line **474** comprises the negative voltage measurement line. Together lines **472** and **474** comprise isolated voltage measurement bus **476**. Lines **472** and **474** form a twisted pair. All voltage measurements taken at the various nodes are communicated on the isolated voltage measurement bus. The twisted pair configuration is important because it reduces noise and increases the isolation of the communications channels.

Line **478** comprises the positive RS485 transmit line. Line **480** comprises the negative RS485 transmit line. Together lines **478** and **480** comprise upstream communication bus **482**. Lines **478** and **480** form a twisted pair. All upstream communications between the master control board and the nodes takes place on the respective point to point upstream communications bus.

Line **484** comprises the positive RS485 receive line. Line **486** comprises the negative RS485 receive line. Together lines **484** and **486** comprise respective point to point downstream communication bus **488**. Lines **484** and **486** form a twisted pair. All downstream communications between the nodes and the master control board take place on the downstream communication bus.

The nodes are connected through a “daisy chain” configuration using the isolated RS485 upstream and downstream communication busses. The RS485 implementation is full duplex. In a preferred embodiment, the communications feed runs at 1 MBd. The band rate is an important improvement over the prior art because it substantially shortens the time required for system communications and greatly reduces errors in the data packets sent and received.

Referring to FIG. 4D, an alternate embodiment of system communication cable **403** will be described. Line **490** comprises the sync positive signal. Line **492** comprises the sync negative signal. Together lines **490** and **492** comprise synchronization bus (or sync line) **494**. In one embodiment, the sync line is used for sending node configurations and measurement timing commands across the entire array.

Referring to FIG. 5A, a schematic diagram of master control board **402** will be described.

The functions of master control board **402** are provided by microcontroller **502**. Microcontroller **502** in a preferred embodiment is a RISC CPU microprocessor including 16 bit registers and a dedicated DMA controller. In a preferred

embodiment, the microcontroller is Part No. MSP430F149 available from Texas Instruments of Dallas, Texas.

The microcontroller operates on a Free RTOS operating system for embedded devices. The operating system provides for multiple threads and tasks. Thread priorities are used to control a direct memory access functions of the system. Data is passed using direct memory access to local memory on the master control board and each node microcontroller. In each case, the local CPU of the microprocessor initiates data transfer and then conducts other operations until it receives an interrupt from the local DMA controller when the transfer operation is complete. In this way, much less CPU overhead is used for data transfer because each processor can transfer data from its local memory without occupying processor time thus allowing computation and data transfer to proceed in parallel. Moreover, since the data rate for DMA is extremely fast compared to the sync pulse transmitters, the transfer of measurement and system communication packets can be considered to be nearly instantaneous.

Internode communication is packetized serial over UART/RS-485. UARTs are capable of high data rates (e.g. 1 Megabaud), provided that the processor is sufficiently quick to handle transmit and receive interrupts. The master control board sets up a DMA channel between the UART and memory. As data characters arrive in the UART receive register, the DMA controller transfers them to system memory sequentially. When a predetermined number of characters has been received, the DMA controller then interrupts the microcontroller, which stores the characters in memory. The microcontroller then reinitializes the DMA channel to receive the next data packet.

Serial transmission of data can be accomplished by the same mechanism. A DMA channel is prepared by the microcontroller, it puts data at a predetermined memory location, and the DMA controller moves the data from memory to the transmit register of the UART. Data is transferred upstream through the array of nodes to the master control board by chaining the DMAs together. When a packet arrives from a downstream facing port, the node CPU is interrupted by the DMA controller. The CPU then starts a DMA channel for the upstream port, to transfer the data from memory to the UART, and so on to the next node.

UART alone cannot be used to transmit the data to the next node. Therefore, at the board edge, there is a UART to RS485 bridge, which transmits the UART data as RS485, along the twisted pair to the next bridge chip, which does the inverse process, namely, it transforms RS485 signals to UART signals, which are then received by the UART module and DMA controller of the processor, as will be further described.

Microcontroller **502** supports a UART connection through lines **537** and **539**. Lines **537** and **539** are connected to USB to UART interface **538**. The USB to UART interface is provided to allow asynchronous data transfer between the microcontroller and PC controller **414** through USB connector **514**. Data transfer rates can range from 300 Bd to 3 MBd. Microcontroller **502** also supports Jtag interface **542** for debugging.

Microcontroller **502** is further connected to relay driver **540**. Relay driver **540** is used to activate the high voltage power supply. Relay driver **540** is further connected to high voltage power connector **510** through fuse **511**. Relay driver **540** is further connected to relay **536**. Relay **536** is a general purpose single pole double throw 12V activated relay. Relay **536** is further connected to high voltage power supply relay power connector **512** through fuse **513**.

Microcontroller **502** is further connected to SPI flash supervisor **544**. The flash supervisor provides microcontroller initialization and timing supervision. In a preferred embodiment, SPI flash supervisor includes boot instructions and initial programming for the microcontroller. In a preferred embodiment, the SPI flash supervisor is the TPS 3838 chip available from Texas Instruments of Dallas, Texas. Microcontroller **502** is further connected to reset IC **546**. In a preferred embodiment, the reset IC is provided in the TPS 3838 chip.

Microcontroller **502** is further connected to RS485 transceiver **558** through UART upstream connection **559** and UART downstream connection **574**. RS485 transceiver **558** provides full duplex RS485 communications support to the upstream nodes. RS485 transceiver **558** provides downstream channel **561** and upstream channel **563**. Both channels are connected to the upstream nodes through ten pin node connector **556**. In a preferred embodiment, the transceiver combines a differential driver and differential receiver which operate from a single power supply. In a preferred embodiment, the transceiver supports a wide common mode voltage range making it suitable for connection to multiple ports over long cable runs. In a preferred embodiment, RS485 transceiver **558** is the SN65HVD1792 transceiver chip available from Texas Instruments of Dallas, Texas. Both transceivers are terminated by appropriate resistor networks (not shown) as the master control board is the upstream termination point for both RS485 communication channels.

Microcontroller **502** is further connected to 24 bit analog to digital converter (“ADC”) **572** through line **571**. ADC **572** accepts external differential reference voltage of 1.25V from voltage reference **570**. In a preferred embodiment, the voltage reference is Part No. LTC2415 available from Analog Devices, Inc. of Norwood, Massachusetts.

ADC **572** is further connected to op amp **566**. Op amp **566** is preferably a low power, differential input output amplifier driver with an adjustable gain. In a preferred embodiment, the gain is fixed at a gain of 2. Op amp **566** provides a 3.5 ppm/^o C. gain temperature coefficient and 5 ppm gain long term stability. Op amp **566** is a preferably Part No. LTC1992 available from Analog Devices.

Op amp **566** is further connected to voltage divider **568**. Voltage divider **568** provides a 1:2 voltage divider resistor network connected between voltage reference **570** and op amp **566**.

Voltage reference **570** is further connected to switch network **569**. Switch network **569** is designed to alternately connect voltage reference **570** either to ADC **572** or positive voltage measurement line **567** for self calibration, as will be further described.

Op amp **566** is further connected to instrumentation amplifier (IA) **564**. IA **564** is preferably a precision instrumentation amplifier with an extremely low gain error of 0.08% maximum and 10 ppm maximum non-linearity. IA **564** is further connected to voltage divider **560** and voltage divider **562**.

Both voltage divider **560** and voltage divider **562** are preferably a six lead voltage divider resistor network array of 10K, 9.99 MΩ±0.1% 31 mw±30 ppm/^o C. 15-SIP. The voltage divider networks are provided to condition to signal from the voltage measurement bus for the instrumentation amplifier.

Voltage divider **560** is further connected to negative voltage measurement line **565** which communicates with the upstream nodes through ten pin node connector **556**. Voltage divider **562** is further connected to positive voltage mea-

surement line **567** and communicates with the upstream nodes through ten pin node connector **556**.

Microcontroller **502** is further connected to voltage divider **554**. Voltage divider **554** is provided to condition the signal from positive high voltage supply line **505** before connecting to microcontroller **502** for monitoring.

High voltage input connector **504** is connected to voltage divider **554** and also to positive high voltage supply line **505**. Positive high voltage supply line **505** communicates to the upstream nodes through ten pin node connector **556**. High voltage input connector **504** is further connected to current sense amplifier **552**. Current sense amplifier **552** is further connected to negative high voltage supply line **503** which communicates with the upstream nodes through ten pin node connector **556**. Current sense amplifier **552** is also connected to microcontroller **502**. Importantly, all current measurements for the system are taken through the current sense amplifier by microcontroller **502**. In a preferred embodiment, the current sense amplifier is Part No. INA194 available from Texas Instruments.

Microcontroller **502** is further connected to analog to digital converter (“DAC”) **550**. In a preferred embodiment, DAC **550** is Part No. AD5620 available from Mouser Electronics of Mansfield, Texas. DAC **550** is further connected to op amp **548**. Op amp **548** is a precision operational amplifier with a large maximum dynamic range and high signal to noise ratio adapted for operation at low voltages. Op amp **548** is further connected to high voltage input connector **504**. DAC **550** and op amp **548** allow the microprocessor to program the high voltage power supply as required.

12V DC power is supplied to the circuit either through AC/DC connector **507** or battery connector **508**. Battery connector **508** is connected to hot swap controller **534**. Hot swap controller **534** provides inrush current control to limit system voltage droop and transients when the battery is activated or replaced. In a preferred embodiment, the hot swap controller is Part No. LM5069 available from Texas Instruments of Dallas, Texas.

Hot swap controller **534** is further connected to switch **535** through fuse **541**. Switch **535** is likewise connected to AC/DC connector **507** through fuse **543** and controls power to the master control board and the nodes. The 12V supply is further connected to the upstream nodes through ten pin node connector **556**. The 12V supply is further supplied to step down switching regulator **532**. In a preferred embodiment, the step down switching regulator is Part No. LT3481 from Analog Devices. The regulator supplies 5V DC to charger **530** and to low drop out regulator **528**. Low drop out regulator **528** provides clean 3.3V DC to the circuit through FET switch **526**. In a preferred embodiment, low drop out regulator **528** is Part No. ADM7171ACPZ-3.3-R7 available from Analog Devices.

Charger **530** is further connected to battery **516** through battery connector **518**. Charger **530** is preferably a single input, single cell lithium ion battery charger, Part No. BQ24040 available from Texas Instruments. Battery **516** is preferably the 400 mAmp hour lithium ion battery companion Part No. PRT-13851 available from SparkFun Electronics of Boulder, Colorado.

Charger **530** is further connected to low drop out regulator **520** through battery connector **518**. Low drop out regulator **520** is further connected to P-channel transistor **522** and Schottky diode **524**. The output of the P-channel transistor and Schottky diode are provided to stabilize power to the system when switching from charging mode to battery power mode, as will be further described.

Positive 28V DC supply line **555** is further connected to ten pin node connector **556** for communication with upstream nodes. Similarly, ground line **557** is connected to ten pin node connector **556** for communication to further downstream nodes.

Referring to FIG. 5B, a schematic diagram of an alternate embodiment of master control board **402** will be described.

The functions of master control board **402** are preferably provided by microcontroller **5002**.

Microcontroller **5002** in a preferred embodiment, includes a 16 bit risc architecture running a 16 megahertz. In a preferred embodiment, the microcontroller is Part No. MSP430FR5994IPNR, available from Texas Instruments of Dallas, Texas.

Microcontroller **5002** supports UART connection to USB to UART interface **5038** to PC controller **414** through connector **5039**. Microcontroller **5002** further supports debugging through USB to UART interface **5040** through connection to PC controller **414** through connector **5041**.

Microcontroller **5002** further supports JTAG connector **5042** for debugging.

Microcontroller **5002** is further connected to SPI flash supervisor **5044**. In a preferred embodiment, the SPI flash supervisor is Part No. WT5Q80DVSSIG available from Winbond of Taichung City, Taiwan. The SPI supervisor functions as previously described.

Microcontroller **5002** is further provided with reset supervisor **5046**, which controls reset functions of the microprocessor.

Microcontroller **5002** is further operatively connected to RS485 transceivers **5053**, **5057** and **5058**. RS485 transceiver **5053** is responsible for coordinating transmission of data signals to upstream nodes. RS485 transceiver **5057** is responsible for receiving communications from upstream nodes. RS485 transceiver **5058** is responsible for transmitting synchronization signal to downstream nodes. Each of RS485 transceivers **5053**, **5057** and **5058** are operatively connected to connector **5056** for connection to upstream nodes.

Microcontroller **5002** is further operatively connected to temperature sensor **5003**. Temperature sensor **5003** is used to obtain a reference temperature for operation of thermoelectric cooler **1760**, as will be further described.

Current sense resistor **5052** is operatively connected to high voltage power supply connector **5051** and high voltage power supply connector **5059**. High voltage power supply connector **5051** is connected to the high voltage input from the control box. High voltage power supply connector **5059** is connected to other upstream nodes.

Current sense resistor **5052** is operatively connected to high voltage current measurement amplifier **5071**. In a preferred embodiment, the high voltage current measurement amplifier is Part No. AD8606 available from Analog Devices. Preferably, the high voltage current measurement amplifier is a precision amplifier is a high speed, low noise circuit, single supply amplifier. High voltage current measurement amplifier **5071** is operatively connected to ADC converter **5072**, which incorporates current reference **5070**, as previously described.

ADC converter **5072** is further connected to isolation transceiver **5066**. Isolation transceiver **5066** is a general purpose digital isolator Part No. ADUM1401BRWZ available from Digikey. The isolator is provided to electrically isolate the microprocessor from the high common mode voltage of the high voltage signal from the current sense resistor, thereby avoiding ground current circulation and injection of noise into the measurement.

Isolation transceiver **5066** is operatively connected to microcontroller **5002** in order to transmit measurements from the current sense resistor.

Voltage resistor divider **5054** is operatively connected to the positive high voltage supply line. Voltage resistor divider **5054** is further connected to high voltage measurement amplifier **5073**, which monitor the high voltage signal. High voltage measurement amplifier **5073** is operatively connected to ADC **5077**, as previously described. ADC **5077** draws its voltage reference from reference chip **5075**. Reference chip **5075** is preferably Part No. LT6657 available from Linear Technology, which provides a precision voltage reference with low drift and predictable temperature behavior. ADC **5077** is operatively connected to isolation transceiver **5079**. Isolation transceiver **5079** is operatively connected to microcontroller **5002** and transmits a digital signal related to the high voltage value.

High voltage power supply analog adjust connector **5087** is operatively connected to high voltage power supply **454** for minor corrections to the high voltage output. In order to condition the analog signal, microcontroller **5002** communicates a digital signal to DAC **5083** through isolation transceiver **5081**. DAC **5083**, in a preferred embodiment, is Part No. 56GSA/S, which is an 8 bit analog to digital converter with low power consumption. The digital analog converter communicates with the high voltage power supply through output amplifier **5085**.

Isolation transceiver **5066**, isolation transceiver **5079**, and isolation transceiver **5081**, together, form a high voltage isolation barrier between the master control board 28V isolated converter ground referenced circuitry and the high voltage power supply ground referenced circuitry. The isolation barrier insulates the microcontroller and associated circuits from any potential undesired transient signals through a common ground or other electrical connection to the high voltage power supply.

Microcontroller **5002** receives 28V power from isolated DC-DC converter **5080**. The DC-DC converter is operatively connected to step down resistor **5082** and low dropout regulator **5084**. The DC-DC converter is activated by enable switch **5086**. The DC-DC converter is directly connected to 12V battery **5088**.

Microcontroller **5002** is further operatively connected to TEC relay **5090**. TEC relay **5090** is further connected to thermoelectric cooler **1760** through connector **5092**.

Isolated DC-DC converter **5080** and TEC relay **5090** form a battery isolation barrier between the battery return ground referenced circuitry and the 28V isolated converter ground referenced circuitry. The isolation barrier insulates the microcontroller and associated circuits from any potential undesired transient signals communicated through a common ground or other electrical connection to the 12V battery.

Connector **5056** further supplies 28V power to upstream nodes from the DC-DC converter.

Referring to FIG. 6A, an example of node **404** will be further described.

Node **404** includes microcontroller **602**. In a preferred embodiment, microcontroller, **602** is Part No. MSP430F149 available from Texas Instruments. Microcontroller **602** is provided with transmit UART port **605** and receive UART port **603**. UART port **605** and UART port **603** are further connected to RS485 transceiver **604**. RS485 transceiver **604** is a three state differential line driver and differential input line receiver operating at 3.3V. Preferably the transceiver is Part No. SN658HVD30 available from Texas Instruments. RS485 transceiver **604** has separate input and output pins for

full duplex bus communication at distances of up to 1,500 meters. RS485 transceiver **604** is further connected to downstream receive line **607** and upstream transmit line **609**. Receive line **607** and transmit line **609** are connected to input ten pin connector **606** for communication with further upstream nodes or the downstream master control board.

Microcontroller **602** is provided with the same RTOS as microcontroller **502** and operates with the same direct memory access format.

Microcontroller **602** is further connected to SPI flash **608**. SPI flash **608** provides circuit initialization, initial programming, and timing supervision for the microprocessor. In a preferred embodiment, the SPI flash supervisor is the TPS 3838 chip available from Texas Instruments of Dallas, Texas. Microcontroller **602** is further connected to reset IC **610**. In a preferred embodiment, the reset IC is provided in the TPS 3838 chip.

Microcontroller **602** is further connected to RS485 transceiver **612**. RS485 transceiver **612** is connected to the microcontroller via receiver UART line **611** and transmit UART line **613**. RS485 transceiver **612** is further connected to RS485 receive lines **615** and RS485 transmit lines **617**. Transmit lines **617** and receive lines **615** are connected to upstream nodes through output ten pin connector **614**. RS485 transceiver **612** is an identical part in a preferred embodiment to RS485 transceiver **604**.

Microcontroller **602** provides serial peripheral interface **619**. Serial peripheral interface **619** is connected to 24 bit analog to digital converter ("ADC") **616**. ADC **616** is preferably Part No. LTC2415-1 available from Analog Devices.

ADC **616** is further connected to switch network **627**. Switch network **627** is further connected to reed relay **630**, positive voltage measurement line **567** and voltage reference **628**. The switch network is designed to alternatively connect voltage reference **628** to either ADC **616** or reed relay **630**. Likewise, switch network **627** is designed to alternatively connect positive voltage measurement line **567** to voltage reference pin **677** of ADC **616** or reed relay **630**, as will be further described. Voltage reference **628** typically provides a controlled 1.25V. In a preferred embodiment, voltage reference **628** is Part No. LT6657 available from Analog Devices.

Voltage reference **628** is further connected to 1:2 voltage divider **626**. Voltage divider **626** supplies approximately 0.625V to differential op amp **618**. Differential op amp **618** is connected to ADC **616**. Signals to differential op amp **618** are provided by instrumentation amplifier **620**. In a preferred embodiment, the instrumentation amplifier is Part No. LT1157 available from Analog Devices.

Input to the instrumentation amplifier is provided by divider network **622** and divider network **624**. Each of divider networks **622** and **624** is a power per element voltage divider resistor network 100K, 9.9 Mohm \pm 1% 31 MW, \pm 30 ppm/ $^{\circ}$ C. 15-SIP, 6 lead resistor network. Preferably, Part No. HVD5-B10M-050-05-ND available from Digi-Key Corporation of Thief River Falls, Minnesota.

Microcontroller **602** further provides general purpose input output port **657**. Port **657** is connected to MOSFET gate driver **658**. MOSFET gate driver **658** controls the application of the high voltage signal. MOSFET gate driver **658** is preferably is a high power, high speed driver with independent high and low side reference output channels, including a floating channel. MOSFET gate driver **658** includes gate high line **659** and gate low line **661**. Gate high line **659** is connected to MOSFET **654**. Gate low line **661** is connected to MOSFET **656**. In a preferred embodiment,

MOSFET gate driver **658** is Part No. IR2011(S)PBF available from Infineon Technologies of Neubiberg, Germany.

Positive high voltage supply line **505** and negative high voltage supply line **506** are supplied through input ten pin connector from the closet downstream node. Likewise, positive high voltage supply line **505** and negative high voltage supply line **506** flow through to the upstream nodes through output ten pin connector **614**. Positive high voltage supply line **505** is connected to MOSFET **654**. Negative high voltage supply line **506** is connected to MOSFET **656**. Both MOSFETs **654** and **656** are high speed switching low capacitance MOSFETs, preferably Part No. C2M0080120D available from Mouser Electronics. Each of MOSFETs **654** and **656** are connected to and controlled by general purpose input output port **657** of microcontroller **602**.

MOSFET **654** is further connected to stake connection **646**. Likewise, MOSFET **656** is connected to stake connection **646**. Stake connection **646** is a rigid mechanical linkage to a durable metal rod, as will be further described.

Positive voltage measurement line **567** and negative voltage measurement line **565** are provided to the node through input ten pin connector **606** from the nearest downstream node. Positive voltage measurement line **567** is connected to reed relay **636**. Negative voltage measurement line **565** is further connected to reed relay **634**. Reed relay **636** is connected to reed relay **640**, reed relay **642** and reed relay **632**. Reed relay **634** is further connected to reed relay **638**, reed relay **630** and switch network **627**. Reed relay **644** is connected between stake connection **646**. Reed relay **630** provides positive voltage measurement output **629** to the next upstream node via output ten pin connector **614**. Likewise, reed relay **632** provides negative voltage measurement output **631** to the next upstream node via output ten pin connector **614**.

In a preferred embodiment, each of reed relays **630**, **632**, **634**, **636**, **638**, **640**, **642** and **644** is a high voltage relay Part No. KT12-1A-40L-SMD available from Digi-Key. Each of reed relays **630**, **632**, **634**, **636**, **638**, **640**, **642**, and **644** are connected to general purpose input output port **699** of microcontroller **602**. The microcontroller opens or closes the relays to configure the node to various node configuration types, as will be further described.

Reed relay **642** is connected to divider network **622**. Reed relay **644** is also connected to divider network **624**. Divider network **622** and divider network **624** provide the input voltage to instrumentation amplifier **620**.

28V DC supply line **555** and ground line **557** are provided to the node through input ten pin connector **606** from a downstream node. 28V DC supply line **555** and ground line **557** flow through to the upstream nodes through output ten pin connector **614**. 28V DC supply line **555** and ground line **557** are connected to step down switching regulator **670**. Switching regulator **670** is preferably Part No. LT3481 available from Analog Devices. Switching regulator **670** provides a 5V signal to low drop out regulator **672**. Regulator **672** is preferably Part No. ADM7171ACP-3.3-R7 available from Digi-Key. Regulator **672** provides an output voltage of 3.3V to field effect transistor **668**. Field effect transistor **668** operates as a switch to supply line **665**, which supplies operating voltage to the microcontroller and the remaining components of the node.

Switching regulator **670** further provides 5V operating voltage to charger **674**. Charger **674** is connected to battery **660** through battery connector **676**. Low drop out regulator **662** is also connected to battery **660** and charger **674** through battery connector **676**. Battery charger **674** is preferably Part

No. BQ24040. Battery **660** is preferably Part No. PRT1-113851. Regulator **662** is preferably Part No. ADM7171ACP-3.3-R7.

Regulator **662** is further connected to P-channel field effect transistor **664** and Schottky diode **666**. Schottky diode **666** and P-channel field effect transistor **664** are connected to 3.3V supply line **665** and are provided to smooth transitions between circuit operation between 28V DC supply line **555** and battery **660**.

Lightning protection is provided through gas discharge tube **648** for positive high voltage connection, gas discharge tube **650** for negative high voltage connection and gas discharge tube **652** for the ground connection.

Microcontroller **602** is further connected to programmable transceiver termination resistors network **680** through GPIO port **681**. Termination resistors network **680** is operatively connected to transceiver **612**. Termination resistor network **680** is provided to selectively terminate the communication channel in the case where the node is the last upstream measurement node in the system, as will be further described.

Referring to FIG. 6B, an alternate embodiment of node **404** will be described.

Node **404** includes microcontroller **6002**. In a preferred embodiment, microcontroller **6002** is Part No. MSP430FR5994IPNR, available from Texas Instruments as previously described.

Microcontroller **6002** is operatively connected to RS485 transceiver **6003** and RS transceiver **6005**. RS485 transceiver **6003** is responsible for transmit functions to the next upstream node. RS485 transceiver **6005** is responsible for receive operations for data from the next upstream node. RS485 transceivers **6003** and **6005** are operatively connected to connector **6006**, for further connection to an upstream node. RS485 transceiver **6003** is responsible for sending upstream communications of synchronization pulses, as will be further described. RS485 transceiver **6005** is responsible for receiving upstream communications of synchronization pulses, as will be further described. RS485 transceiver **6007** is responsible for communications of synchronization pulses, as will be further described.

Microcontroller **6002** is further operatively connected to RS485 transceiver **6011** and **6013**. RS485 transceiver **6011** operates to send transmissions from the microcontroller to the downstream node or control box. RS485 transceiver **6013** operates to receive data signals from the downstream node or the control box and transmitting them to microcontroller **6002**. RS485 transceivers **6011** and **6013** are operatively connected to connector **6014** for further connection to an upstream node or the control box.

Microcontroller **6002** is further connected to termination relay **6080** through buffer **6081**. Termination relay **6080** includes termination resistors which are provided to terminate the RS485 communication channels in case the node is the last upstream measurement node in the array, as will be further described. Termination relay **6080** is operatively connected to connector **6014** for connection to the next downstream node or the control box.

Microcontroller **6002** is further provided with SPI flash supervisor **6008** and reset IC **6010**, as previously described. Microcontroller **6002** is further connected to RGB LED **6009**, for visual communication of various states of the microprocessor, as will be further described.

Microcontroller **6002** controls injection current to stake connection **6046** through FET enable circuit **6045** connected to the microcontroller through general-purpose input output pin **6043** through line **6082**. FET enable circuit **6045** enables

isolated DC-DC converters **6047** and **6049**, which provide electrical separation between the microcontroller and the high voltage supply. In a preferred embodiment, isolated DC-DC converters **6047** and **6049** are Part Nos. PDS1S available from CUI, Inc.

Isolated DC-DC converter **6047** is connected to floating gate driver circuit **6051**, which provides appropriate voltage and current for high voltage MOSFET **6055**.

High voltage MOSFET **6055** is connected between high voltage positive power supply line **6061** and high voltage relay **6059**. High voltage relay **6059** is operatively connected to stake connection **6046**. A high voltage relay is enabled through GPIO line **6065**, which is operatively connected to microcontroller **6002**.

Likewise, isolated DC-DC converter **6049** is connected to floating gate driver circuit **6053** which supplies the appropriate voltage and current to high voltage MOSFET **6057**. High voltage MOSFET **6057** is connected between high voltage negative power supply line **6063** and high voltage relay **6059**.

In order to prevent cross conduction between high voltage MOSFET **6055** and **6057**, cross conduction logic **6067** is provided. Cross conduction logic **6067** provides a buffer enable line to each of buffers **6069** and **6071**. Buffer **6069** is further connected to opto-isolator **6073**. Opto-isolator **6073** provides further isolation between buffer **6069** and high voltage MOSFET **6055**. Opto-isolator **6073** is further connected to floating gate driver circuit **6051** which controls switching of high voltage MOSFET **6055**.

Likewise, buffer **6071** is operatively connected to opto-isolator **6075**. Opto-isolator **6075** is operatively connected to floating gate driver circuit **6053**. Microcontroller **6002** controls switching of high voltage MOSFET **6057**, through the buffer circuit, the opto-isolator and the floating gate driver.

Stake connection **6046** is further connected to relay **6048**, relay **6052**, and relay **6068**. Relay **6048** is further connected to positive voltage measurement input line **6070** and controlled by microcontroller **6002** through buffer circuit **6050**.

Relay **6052** is further connected to negative voltage measurement input line **6072**. Relay **6052** is controlled by microcontroller **6002** through buffer circuits **6054**.

Relay **6056** is connected between positive voltage measurement input line **6070** and the positive voltage measurement output line **6074**. Relay **6056** is controlled by microcontroller **6002** through buffer circuit **6058**.

Relay **6060** is connected between negative voltage measurement input line **6072** and negative voltage measurement output line **6076**. Relay **6060** is controlled by microcontroller **6002** through buffer circuit **6062**.

Relay **6068** is connected to the 0.55V calibration line **6078**. Microcontroller **6002** controls sending the calibration signal to the stake connection through buffer circuit **6064**.

Isolated DC-DC converter **6047**, isolated DC-DC converter **6049**, opto-isolator **6073**, opto-isolator **6075** and relays **6048**, **6052**, **6056**, **6060** and **6068** form a high voltage isolation barrier between the node 28V isolated converter ground referenced circuitry and the high voltage power supply ground referenced circuitry. The isolation barrier insulates the microcontroller and associated circuits from potential undesired signaling through a common ground or other electrical connections to the high voltage power supply.

Microcontroller **6002** controls resistor divider network **6104** through buffer circuit **6120** through solid-state relay **6108**. Solid-state relay **6108** is connected to positive voltage measurement input line **6070** and resistor divider network **6104**. Resistor divider network **6104** is further connected to

solid-state relay **6100**. Microcontroller **6002** controls solid-state relay **6100** through buffer circuit **6116**. Solid-state relay **6100** is connected to positive voltage measurement line **6122**.

Microcontroller **6002** controls resistor divider network **6106** through buffer circuit **6125** and solid-state relay **6110**. Solid-state relay **6110** is connected between negative voltage measurement input line **6072** and resistor divider network **6106**. Resistor divider network **6106** is connected to solid-state relay **6102**. Solid-state relay **6102** is controlled by microcontroller **6002** through buffer circuit **6118**. Solid-state relay **6102** is further connected to negative voltage measurement line **6121**.

Buffer circuit **6124** is connected between microcontroller **6002** and solid-state relay **6112**. Solid-state relay **6112** is further connected to positive voltage measurement input line **6070** and positive voltage measurement line **6122**.

Buffer circuit **6126** is connected between microcontroller **6002** and solid-state relay **6114**. Solid-state relay **6114** is further connected to negative voltage measurement input line **6072** and negative voltage measurement line **6121**.

Positive voltage measurement line **6122** is further connected to variable gain amplifier **6130**. Variable gain amplifier **6130** is further connected to voltage divider network **6132**. Voltage divider network **6132** is connected to buffer amplifier **6134**. Buffer amplifier **6134** is connected to the positive side of differential amplifier **6136**. Differential amplifier **6136** is connected through analog to digital converter **6138** to microcontroller **6002**. Analog to digital converter **6138** communicates the voltage mounted measurement at the stake connection, as will be further described.

Solid-state relays **6108** and **6110**, in combination with resistor divider networks **6104** and **6106**, and solid-state relays **6100** and **6102** provide an alternate embodiment of “auto scaling” voltage divider circuit **700** and replaces like components in alternate embodiments for use in a measurement node, as previously described.

Negative voltage measurement line **6121** is connected to variable gain amplifier **6140**. Variable gain amplifier **6140** is further connected to voltage divider network **6142**. Voltage divider network **6142** is connected to buffer amplifier **6144**. Buffer amplifier **6144** is further connected to differential amplifier **6136** and supplies the negative voltage measurement signal to analog to digital converter **6138**.

Variable gain amplifiers **6130** and **6140** are switched resistors into the feedback loop of each amplifier channel to generate a gain closed loop. Voltage divider networks **6132** and **6142** operate similarly except at the output of the operation amplifier so as not to interfere with feedback paths.

Positive voltage measurement output line **6074** and negative voltage measurement output line **6076** are connected to upstream connector **6006** for communication to the next upstream node. Positive voltage measurement input line **6070** and negative voltage measurement input line **6072** are connected to connector **6014** for communication to the previous node or the control box. High voltage positive power supply line **6061** and high voltage negative power supply line **6063** are both connected to connector **6006** for communication to the next upstream node and connector **6014** for connection to the next downstream node or the control box.

28V power supply line **6180** and 28V ground line **6182** are connected to both connectors **6006** and **6014** for communication to the next node downstream or the control box, respectively. Step down transformer **6152** is connected to 28V supply line **6150**. Stepdown transformer **6152** is further

connected to low dropout regulator **6154** for conversion to 3.3V, and low dropout regulator **6156** for conversion to 3.3V. Regulator **6156** is further connected to resistor divider network **6158** and known voltage buffer **6160** for production of a controlled 0.55V calibration signal, which is connected to relay **6068** and used to calibrate the node voltage measurement functions.

Step down transformer **6152** is further connected to regulator **6162**. Regulator **6162** is further connected to regulator **6164** for production of a 14V signal **6166**.

Regulator **6162** is further connected to charge pump **6168**. Charge pump **6168** provides a negative 15V signal to regulators **6170** and **6172** for production of a negative 3.3V signal and a negative 14V signal, respectively.

Microcontroller **6002** is further connected to DC-DC converter **6099**. DC-DC converter **6099** is further connected to auxiliary 12V DC source **412b**. DC-DC converter **6099** operates to supply a 28V signal which is connected to the next upstream node through connector **6014**. Presence of the auxiliary 12V DC source is sensed by microcontroller **6002** through sense line **6098**. In a preferred embodiment, DC-DC converter **6099** is Part No. CBQ150 W-24S48 available from Cincon.

Referring to FIG. 7, an alternate embodiment of “auto scaling” voltage divider circuit **700** will be described. The circuit replaces like components in alternate embodiments of a measurement node.

Positive voltage measurement line **567** is connected to passthrough reed switch **716**, voltage divider reed switch **712**, passthrough reed switch **708** and passthrough reed switch **704**. Negative voltage measurement line **565** is connected to passthrough reed switch **714**, voltage divider reed switch **710**, passthrough reed switch **706** and passthrough reed switch **702**. In a preferred embodiment, each voltage divider reed switches **712** and **710** are further connected to a 500:1 voltage divider network **711**. Voltage divider network **711** is employed to condition extremely large measurement signals.

Passthrough reed switch **716** is further connected to variable gain amplifier **718**. Variable gain amplifier **718** is employed to amplify extremely small measurement signals. In a preferred embodiment, variable gain amplifier **718** is a combination of two low noise amplifiers whose gain is controlled by a series of switched resistor networks. In a preferred embodiment, the op amps are Part No. OPA2140 low powered J-FET amplifiers available from Texas Instruments. Passthrough reed switch **714** is connected to variable gain amplifier **718**. Voltage divider reed switch **712** is likewise connected to variable gain amplifier **718**. Voltage divider reed switch **710** is also connected to variable gain amplifier **718**.

Passthrough reed switch **708** is connected to upstream positive voltage measurement output **629**. Passthrough reed switch **706** is connected to upstream negative voltage measurement output **631**.

Passthrough reed switch **704** is connected to stake connection **646**. Passthrough reed switch **702** is connected to stake connection **646**.

MOSFET **654** is connected to relay **726**. Relay **726** is connected to stake connection **646**. MOSFET **656** is connected to relay **728**. Relay **728** is further connected to stake connection **646**. The relays are provided in the circuit to eliminate leakage current through the MOSFETs to the stake as a result of the high voltage bias between the high voltage line and the ground.

Variable gain amplifier **718** is connected to variable gain multiplexer **720**. The variable gain multiplexer is an active

voltage divider which is capable of attenuating large signals of up to 12.5V down to the acquisition level of ADC **724**. In a preferred embodiment, variable gain multiplexer **720** employs a pair of op amps through a switched resistor network. In a preferred embodiment, each of the op amps is Part No. OPA2140 available from Texas Instruments.

Variable gain multiplexer **720** is connected to differential amplifier **722**. The differential amplifier is used to condition the signal to a midpoint voltage activation level for ADC **724**.

Differential amplifier **722** is connected to ADC **724**. ADC **724** is likewise connected to microcontroller **602**. In a preferred embodiment, ADC **724** demonstrates a very precise 2.5 ppm gain error and 0.23 ppm noise to produce a 24 bit differential analog to digital conversion with a range of 2.7 to 5.5 supply voltage. The full scale differential input range is from $-0.5V$ referenced to $0.5V$ reference. In a preferred embodiment, calibration of the ADC is not necessary because measurements are taken on alternating positive and negative high voltage waveforms which cancel any offset present. In a preferred embodiment, ADC **724** is the LTC241 5-series analog to digital converter, is available from Linear Technology Corporation.

Each of switches **702**, **704**, **706**, **708**, **710**, **712**, **714**, and **716**, and relays **728** and **726** are connected to the general purpose input output port of microcontroller **602** and are controlled thereby.

The voltage divider circuit is useful in situations where very large voltage measurements are required. The divider circuit employs an “auto scaling” feature to precondition the voltage measurement for the ADC. When a large voltage is detected at the stake, ADC **724** automatically indicates an overflow condition. When this occurs, variable gain multiplexer **720** is automatically switched into the circuit in order to attenuate the signal by a factor of 12. If the overflow condition persists, then voltage divider network **711** is automatically switched into the circuit to attenuate the signal by a factor of 500.

Referring to FIG. 8, method **800** for obtaining test data will be described. At step **802**, PC controller **414** receives a start test from the graphic user interface. The start test command includes a test format, and a file name for test data to be recorded. The start test command is sent to the master control board.

At step **804**, the master control board initiates a self-enumeration process at the nodes, as will be further described.

At step **806**, the master control board formats the test protocol, as will be further described.

At step **808**, the master control board initiates the test procedure, as will be further described.

At step **810**, the various nodes take voltage readings, as will be further described.

At step **812**, the nodes report test data, as will be further described. To report test data, testing, the CPU of each node places one packet of test data in the DMA pipeline which is then moved to the master control board, along the downstream communication bus in order, without further intervention. In a preferred embodiment, each packet passed through direct memory access includes an 8 byte payload with a hardware cyclic redundancy check, CRC16, at each node.

At step **814**, the master control board formats the reported test data and forwards it to PC controller **414**. Once the master control board receives a packet of test data from each node, the test data packets are assembled into a table of the appropriate format which is then forwarded to the PC

controller through UART transmission lines **539** and **537**. In a preferred embodiment, the master control board assembles the data into a pre-universal resistivity file (PURF) type format, including measurements of A, B, M, N, V/I, I, error percent, and chargeability, C, in microvolts/volts.

At step **816**, the PC controller processes the data into an intelligible graphic format. In a preferred embodiment, processing the data includes conducting a regression correlation on the raw resistivity data to create a resistivity model. The resistivity model is converted into a graphical form which can then be analyzed to detect and locate subsurface soil anomalies.

Referring to FIGS. **9A** and **9B**, the node self-enumeration process of step **804** will be further described. In this example, two nodes, **404** and **406** are shown. However, as the ellipsis in the drawing indicates, any number of nodes may exist in the system limited only by a signal to noise ratio. Each measurement node in the array is identical to its upstream and downstream neighbors.

At step **902**, PC controller **412** generates a start test message. The start test message, in a preferred embodiment, includes a test protocol and an array type. At step **903**, the PC controller sends the start test message to the master control board.

At step **904**, master control board **402** generates an enumerate data packet. In a preferred embodiment, the enumerate data packet includes a single 8 byte payload. 4 bites of the payload represent the source address of the master control board, in this example 0000. The 4 byte destination address in the data packet is also set to 0000, as none of the nodes has an address. The source address of the master control board is arbitrary and may take on other values. The source address and the destination address of the enumeration packet should be the same value.

At step **906**, master control board **402** sends the enumeration data packet to node **404** using direct memory access. At step **908**, node **404** determines whether or not it has an address. If not, then node **404** proceeds to step **909**. If so, node **404** proceeds to step **920**.

At step **909**, node **404** increments the destination address by 0001. At step **910**, node **404** assigns itself the incremented address.

At step **920**, node **404** generates an enumeration data packet. The enumeration data packet includes the source address of node **404**. In this example, the source address is the packet is 0001, and the destination address 0000, as the next upstream node has no address. At step **922**, node **404** forwards the enumeration data packet to upstream node **406** using the upstream communications channel.

At step **924**, node **406** generates a handshake code. In a preferred embodiment, the handshake code is any arbitrary 4 byte number. At step **926**, node **406** sends the handshake code to node **404**.

At step **928**, node **404** determines whether or not a handshake code has been received within a predetermined timeout period. If so, the method moves to step **930**. If not, the method moves to step **933**.

At step **930**, node **404** generates an acknowledgment to the handshake code. At step **931**, node **404** sends the acknowledgment to node **406**. At step **932**, upon receipt of the acknowledgment from node **404**, node **406** undertakes steps **908**, **909**, **910**, **920**, **922**, **924**, **926**, **928**, **930** and **931**, as previously described, with the next upstream node in the array. The process is repeated recursively at each node until all the nodes in the array have self-enumerated, and the last upstream node has set its termination resistors.

At step **933**, node **404** calculates the maximum number of nodes in the array. In a preferred embodiment, the number of nodes in the array is calculated by the last upstream node in the array by subtracting the source address from its newly self-assigned destination address. The result is the number of nodes in the array. At step **934**, node **404** assembles the max node packet. The max node packet includes a single 4-byte value indicating the calculated number of nodes in the array.

At step **935**, node **404** sets its RS485 termination resistors indicating that it is the terminal node on RS485 communications channels.

At step **936**, node **404** sends the max node packet to master control board **402** using the downstream RS485 communications channel. Node **406** submits the acknowledgment packet to the DMA controller which uses the upstream communications channel to automatically place the acknowledgement packet in the appropriate location in the memory of the master control board. The DMA controller of the master control board automatically generates an interrupt to the CPU of the master control board when the acknowledgement packet is received.

At step **937**, master control board **402** sets the number of nodes to match the number of nodes indicated in the max node packet. At step **938**, master control board **402** sends the number of nodes to PC controller **412**.

At step **939**, master control board **402** builds a table of node addresses starting with its own address and incrementing the address once for each node in the array as indicated in the max node packet. At step **940**, PC controller **412** displays the number of nodes in the array.

Advantageously, neither the measurement nodes, nor the master control board, nor the PC controller does, or is required to, determine a relative ordering or repetitively send addresses of the nodes back to the master control board. Eliminating the necessities of discovering node addresses and a relative position of the nodes in the array makes the survey process far faster than the prior art. Further, since none of the nodes has a unique identifier, it is easier, faster and far less error prone to change the nodes in the field in case of malfunction. Still further, eliminating the requirement to transfer node identifiers in data packets vastly reduces the possibility of address errors occurring in the system.

Referring to FIGS. **10A** and **10B**, a preferred method of formatting the nodes for test of step **806** will be further described.

At step **1002**, PC controller **412** generates a series of node assignment messages.

Each node may be assigned one of the following states:

- A—Inject node +
- B—Inject node −
- P—Pass through node
- M—Measurement +
- N—Measurement −
- LM—M type but does not react to a second transition sync pulse
- LN—N type but does not react to a second transition sync pulse
- SM—M type at first transition sync pulse, N type at second transition sync pulse
- SN—N type at first transition sync pulse, M type at second transition sync pulse
- S—Skip Node (high z, all switches off).

The node assignment messages comprise a separate “channel assignment message” for each node, for each desired channel of test data. The channel assignment messages are enumerated from 0 to n, where (n−2) is the highest

In the case where the voltage divider network 711 is employed to auto scale the node, the reed switches and relays are set according to Table 4 below.

TABLE 4

Node Type	702	704	706	708	710	712	714	716	726	728	654	656
A	O	O	O	O	O	O	O	O	C	O	C	O
B	O	O	O	O	O	O	O	O	O	C	O	C
P	O	O	C	C	O	O	O	O	O	O	O	O
M	O	C	O	C	O	O	O	O	O	O	O	O
N	C	O	O	O	C	C	O	O	O	O	O	O
LM	O/C/C	C/O/O	O	C/O/O	O/C/C	O/O/C	O	O	O	O	O	O
LN	C/O/O	O/C/C	O	O/C/C	C/O/O	C/C/O	O	O	O	O	O	O
SM	O/O/C	C/C/O	O	C/C/O	O/O/C	O/O/C	O	O	O	O	O	O
SN	C/C/O	O/O/C	O	O/O/C	C/C/O	C/C/O	O	O	O	O	O	O
S	O	O	O	O	O	O	O	O	O	O	O	O

Where:

“O” denotes off

“C” denotes on

The “/” slash denotes a sync pulse transition, as will be further described.

At step 1020, node 404 generates an acknowledgment packet. At step 1022, node 404 sends the acknowledgment packet to master control board 402 via direct memory access.

If, at step 1016 the address of the type assignment packet does not match the address of node 404, then node 404 proceeds to step 1024. At step 1024, node 404 forwards the node type assignment packet to the next upstream node on the communications channel, in this example node 406.

At step 1025, node 406 repeats steps 1014, 1016, 1018, 1020, 1022 and 1024, as previously described, either setting its switches and relays, or forwarding the node assignment packet to the next upstream node. The process continues recursively at all upstream nodes until all nodes are configured according to their node assignment packets.

At step 1026, node 404 waits for a synchronization pulse on 28V DC supply line 555, as will be further described.

At step 1028, master control board 402 waits for acknowledgment packets from all enumerated nodes.

At step 1030, once it has received acknowledgement packets from all nodes, master control board 402 generates a “test ready” message. At step 1032, master control board 402 forwards the test ready message to PC controller 412. At step 1034, PC controller 412 displays the test ready message on the GUI, and waits for further instructions.

Referring to FIGS. 11A and 11B, a preferred method of taking data by a node string of step 810, will be further described. In this example, node 404 is configured as node type “A”, node 406 is configured as node type “B”, and node 408 is configured as a measurement node type. In this example, the circuits of FIGS. 5A and 6A are employed.

At step 1102, PC controller 412 generates an “initiate test” message. At step 1104, PC controller 412 sends the initiate test message to master control board 402. At step 1105, the master control board executes a self calibration routine, as will be further described. At step 1106, master control board 402 checks the status of the positive high voltage supply line 505 and negative high voltage supply line 506.

At step 1108, master control board 402 waits for the current level to reach a predetermined value by monitoring current sense amplifier 552. In a preferred embodiment, a 2 Amp current limit setting is used. In an alternate embodiment, master control board 402 waits for a preset time

period, or until the current reaches a railed value, before proceeding. In this way, the circuit advantageously monitors the current delivery only until it reaches a high limit preset

or becomes unchanging so as not to delay a test procedure due to low current injection into the soil.

At optional step 1110, the master control board deactivates the 28V DC power supply to the upstream nodes by shutting down switch 535. At optional step 1112, master control board 402 switches to battery power through regulator 520, P-channel transistor 522 and Schottky diode 524. Schottky diode 524 smooths the transition from the power supply to the battery to avoid supply voltage noise.

Likewise, at optional step 1113, node 404 switches to battery supply power through regulator 662, P-channel field effect transistor 664 and Schottky diode 666. In the same way, at optional step 1114, node 406 switches to battery power. Likewise, at optional step 1115, node 408 switches to battery power.

At step 1116, master control board 402 sends a high voltage state 1 pulse on the 28V supply line.

At step 1121, node 404 switches to high voltage state 1 by activating MOSFET 654 and relay 726. Activating MOSFET 654 and relay 726 connects positive high voltage supply line 505 to stake connection 646.

At step 1122, node 406 activates high voltage state 2. In a preferred embodiment, node 406 activates MOSFET 656 and relay 728, thereby connecting negative high voltage supply line 506 to stake connection 646.

At step 1123, node 408 participates in taking two measurement samples in its original node type configuration. In this example, node 408 would be set to a “LM” node type assignment and so would direct its stake connection to the next upstream node for measurement.

At step 1126, master control board 402 transmits a transition sync pulse to the nodes by pulsing 28V DC supply line 555, or a pulse on the RS485 sync line, as will be further described.

At step 1130, node 408, in response to the transition sync pulse toggles its node type assignment. For example, if node 408 is assigned as an “M” state, it toggles to an “N” state. If the node is assigned an “LM” node type it toggles to an “S” node type. If the node is assigned a “LN” type it toggles to an “S” node type. If the node is assigned a “SM” node type, it toggles from an “M” node type to an “N” node type. If the node is assigned a “SN” node type, then it toggles from an “N” node type to a “M” node type. If the node is assigned “S” node type then no change takes place. Table 5 below shows the node response to a sync pulse.

27

TABLE 5

Prior State		Next State
	M	N
	N	M
	LM	S
	LN	S
SM	M	N
SN	N	M
	S	S

At step 1131, node 408 participates in taking two samples in its new node type configuration.

At step 1132, master control board 402 sends a zero high voltage sync pulse on the 28V DC supply line 555, or a pulse on the RS485 sync channel. As a result, at step 1133, node 404 disconnects the high voltage. Likewise, node 406, at step 1134, disconnects the high voltage. At step 1135, node 408 toggles back to its original node type configuration, as previously described.

At step 1140, master control board 402 sends a high voltage state 2 sync pulse on 28V DC supply line 555, or a pulse on the RS485 sync channel. As a result, node 404, at step 1147, activates MOSFET 656 and relay 728 to supply negative high voltage to stake connection 646. At step 1148, node 406 activates MOSFET 654 and closes relay 726 to supply high voltage to stake connection 646.

At step 1149, node 408 participates in taking two measurement samples in its original node type configuration.

At step 1152, master control board 402 sends a second transition sync pulse to the nodes. At step 1153, node 408 switches its node state to its new node type configuration. At step 1154, node 408 participates in taking measurement samples in its new node type configuration. At step 1155, master control board 402 sends a zero high voltage sync pulse to the nodes. As a result, at step 1165, node 404 disconnects the high voltage from the stake connection by turning off MOSFET 656 and opening relay 728. Likewise, at step 1166, node 406 disconnects the high voltage from the stake connection by turning off MOSFET 654 and opening relay 726. At step 1167, node 408 returns to its original node type configuration.

28

At step 1169, master control board 402 reformats all nodes for the next upstream test channel in the survey by calculating and sending a new set of channel assignment messages. At step 1170, master control board 402 restarts the test procedure by returning to step 1116 and repeating the following steps until the survey is complete.

Referring to FIGS. 11D and 11E, an alternate method of taking data by a node string of step 810, will be further described. In this example, node 404 is configured as a node type "A", node 406 is configured as node type "B" and node 408 is configured as a measurement node type. In this example, the circuits of FIGS. 5B and 6B are employed.

At step 11002, PC controller 412 generates an initiate test message. At step 11004, PC controller 412 sends the initiate test message to master control board 402.

At step 11006, master control board 402 verifies the current and voltage levels present at the high voltage supply by reading current sense resistor 5052 and voltage resistor divider 5054, respectively. At step 11008, master control board 402 waits for the current level to reach a predetermined value, as previously.

At step 11016, master control board 402 sends a high voltage state 1 sync pulse on the RS485 sync line. In each connection to the high voltage supply line, cross conduction logic 6067 delays connection by a sufficient time to allow discharge of each MOSFET.

At step 11021, node 404 activates high voltage state 1. In a preferred embodiment, node 404 activates high voltage MOSFET 6055 and high voltage relay 6059 to connect to the positive high voltage signal to stake connection 6046.

At step 11022, node 406 activates high voltage state 2. In a preferred embodiment, node 406 activates high voltage MOSFET 6057 and high voltage relay 6059 to connect to the negative high voltage signal to stake connection 6046.

At step 11023, node 408 participates in taking two measurement samples in its original node type configuration. In this example, node 408 would be set to an "LM" node type assignment and so direct its stake connection to the next upstream node for measurement.

Referring again to FIG. 6B, switch and relay settings for the various node type assignments are shown in Table 6 below.

TABLE 6

Node Type	6055	6057	6048	6052	6056	6060	6112	6114	6059
A	C	O	O	O	O	O	O	O	C
B	O	C	O	O	O	O	O	O	C
P	O	O	O	O	C	C	C	C	O
M	O	O	C	O	O	O	O	O	O
N	O	O	O	C	O	O	C	C	O
LM	O	O	C/O/O	O/C/C	O	O	O/C/C	O/C/C	O
LN	O	O	O/C/C	C/O/O	O	O	C/O/O	C/O/O	O
SM	O	O	C/C/O	O/O/C	O	O	O/O/C	O/O/C	O
SN	O	O	O/O/C	C/C/O	O	O	C/C/O	C/C/O	O
S	O	O	O	O	O	O	O	O	O

At step 1168, master control board 402 advances the A and B node position upstream, to gather data from the next test channel, as will be further described.

When the auto scaling resistor divider networks 6104 and 6106 are used, switch and relay settings for the various node type assignments are shown in Table 7 below:

TABLE 7

Node Type	6055	6057	6048	6052	6056	6060	6108	6110	6100	6102	6112	6114	6059
A	C	O	O	O	O	O	O	O	O	O	O	O	C
B	O	C	O	O	O	O	O	O	O	O	O	O	C
P	O	O	O	O	C	C	O	O	O	O	C	C	O
M	O	O	C	O	O	O	O	O	O	O	O	O	O
N	O	O	O	C	O	O	C	C	C	C	O	O	O
LM	O	O	C/O/O	O/C/C	O	O	O/C/C	O/C/C	O/C/C	O/C/C	O	O	O
LN	O	O	O	C/O/O	O	O	C/O/O	C/O/O	C/O/O	C/O/O	O	O	O
SM	O	O	C/C/O	O/O/C	O	O	O/O/C	O/O/C	O/O/C	O/O/C	O	O	O
SN	O	O	O/O/C	C/C/O	O	O	C/C/O	C/C/O	C/C/O	C/C/O	O	O	O
S	O	O	O	O	O	O	O	O	O	O	O	O	O

At step 11026, master control board 402 transmits a transition sync pulse to the nodes on the RS485 sync line.

At step 11030, node 408, in response to the transition sync pulse toggles its node type assignment, as previously described.

At step 11031, node 408 participates in taking two samples in its new node type configuration.

At step 11032, master control board 402 sends a zero high voltage sync pulse on the RS485 sync line. As a result, at step 11033, node 404 disconnects the high voltage. Likewise, common node 406, at step 11034 disconnects the high voltage. At step 11035, node 408 toggles back to its original node type configuration, as previously described.

At step 11040, master control board 402 sends a high voltage state 2 sync pulse on the RS485 sync line. As a result, at step 11047 activates high voltage MOSFET 6057 and high voltage relay 6059 to supply negative high voltage to stake connection 6046. At step 11048, node 406 activate high voltage MOSFET 6055 and closes high voltage relay 6059 to supply high voltage to stake connection 6046.

At step 11049, node 408 participates in taking two measurement samples in its original node type configuration.

At step 11052, master control board 402 sends a second transition sync pulse to the node, as previously described. At step 11053, node 408 switches its node state to its new node state node type configuration. At step 11054, node 408 participates in taking measurement samples and its new node type configuration.

At step 11055, master control board 402 sends a zero high voltage sync pulse to the nodes. As a result, at step 11065, node 404 disconnects the high voltage from the state connection by turning off high voltage MOSFET 6057 and opening high voltage relay 6059. Likewise, at step 11066, node 406 disconnects the high voltage from the stake connection by turning off high voltage MOSFET 6055 and opening high voltage relay 6059. At step 11067, node 408 returns to its original node type configuration.

At step 11068, master control board 402 advances the "A" and "B" node position upstream, to gather data for the next test channel, as will be further described.

At step 11069, master control board 402 reformats all nodes for the next upstream test channel in the survey, as previously described. At step 11070, master control board 402 restarts the test procedure returning to step 11016 and repeating 11006-11069 steps until the survey is complete.

Referring to FIG. 11C, a method of self-calibration, of step 1105 will be further described.

At step 1171, master control board 402 sets switch network 569 to its "calibrate" position. In the calibrate position, switch network 569 is disconnected from voltage reference 570 and ADC 572 and connects voltage reference 570 to outbound positive voltage measurement line 567.

At step 1172, master control board 402 generates a calibrate command data packet, addressed to the first upstream node.

At step 1173, master control board 402 sends the calibrate command data packet to node 404.

At step 1174, node 404 opens the calibrate command data packet and confirms that it is the node to which the packet is addressed. If so, it then sets its calibrate switch positions. In practice, switch network 627 is set to disconnect voltage reference 628 from ADC 616. Switch network 627 is then set to connect positive voltage measurement line 567 to voltage reference pin 677 of ADC 616. This effectively connects voltage reference 570 of the master control board to voltage reference pin 677 of ADC 616 in node 404.

At step 1175, node 404 calibrates its ADC from the voltage reference pin 677. Once calibrated, node 404 generates acknowledge packet at step 1176. At step 1177, node 404 sends the acknowledge packet to master control board 402.

At step 1178, master control board 402 generates a second calibrate command data packet instructing node 404 to reset its calibration switch positions. At step 1179, master control board 402 forwards the calibrate command packet to node 404. At step 1180, node 404 resets its calibration switch positions. In practice, node 404 sets switch network 627 to connect voltage reference 628 to reed relay 630. Node 404 further closes reed relay 630 effectively connecting voltage reference 628 to outbound positive voltage measurement output 629.

At step 1181, node 404 advances the address in the command packet to the next upstream node and changes the payload to indicate proper calibration switch positions for node 406. At step 1182, node 404 forwards the command packet to node 406. At step 1183, node 406 receives the command packet and sets its calibration switch positions. In practice, node 406 sets switch network 627 to disconnect voltage reference 628 from voltage reference pin 677 of ADC 616. Node 406 then sets switch network 627 to connect positive voltage measurement line 567 to voltage reference pin 677 of ADC 616. This effectively connects the voltage reference of node 404 to the voltage reference pin of ADC 616 in node 406.

At step 1184, node 406 calibrates its ADC. At step 1185, node 406 generates an acknowledgment packet. At step 1186, node 406 forwards the acknowledge packet to node 404. At step 1187, node 404 forwards the acknowledge packet to master control board 402 using DMA.

At step 1188, master control board 402 compares the original address of the acknowledge packet to the address of the maximum node. If the address does not match, the master control board returns to step 1178 and repeats the

process until all nodes are calibrated. If the address does match, then the master control board moves to step **1189** where it returns.

The self-calibration routine is important because it enables the tolerance of each downstream device to be translated through the measurement system to the adjoining upstream device which then can mathematically compensate the measured values to the exact voltage injected. In this way, a known value with a very low ppm tolerance can be sent into the adjoining node and used to scale the resistive divider of each ADC exactly.

FIGS. **11F**, **11G** and **11H** show an example of a method of taking data by a node string in pseudocode.

Referring to FIG. **12**, a sync pulse timing diagram will be described. The sync pulses are triggered by the master control board and take place on 28V DC supply line **555** or by the master control board sending a sync signal on the dedicated RS485 sync line.

With reference to axis **1202**, the sync pulse train will be described. With reference to axis **1204** the positive high voltage and negative high voltage waveforms at the "A" type node configuration will be described. With reference to axis **1206**, the positive high voltage and negative high voltage waveforms at the "B" type node configuration will be described. With reference to axis **1208**, node actions responsive to the sync pulses at a measurement node will be described.

High voltage state 1 sync pulse **1210** triggers high voltage pulse **1222** at the "A" node and negative high voltage pulse **1224** on the "B" node. Likewise, high voltage state 1 sync pulse **1210** triggers two measurements, **1230**, at node state 1 at the measurement node.

Transition sync pulse **1212** causes no change at the A node or the B node, but triggers a toggle at the measurement node at **1232**. In a toggle, the measurement node resets its measurement switches and relays to change from a first node type configuration to a second node type configuration. In this example, node type configuration "1" is an "M" node type configuration and node type "2" is an "N" node type configuration. However, any pairing of node type configurations is possible. Likewise, two measurements in state 2, **1234**, at the measurement node are triggered.

At zero high voltage sync pulse **1214**, high voltage pulse **1222** is terminated at the A node, as is negative high voltage pulse **1224** at the B node. The measurement node, in response, toggles at **1236** back to node state 1.

At high voltage state 2 sync pulse **1216**, the A node produces negative high voltage waveform **1226**. The B node produces positive high voltage waveform **1228**. The measurement node takes two measurements in state 1 at **1238**.

At transition sync pulse **1218**, no change occurs at node A or node B. However, the measure node toggles at **1240** back to node state 2. Likewise, the measurement takes two measurements, at **1242**.

At zero high voltage sync pulse **1220**, the A node terminates negative high voltage waveform **1226**. Likewise, the B node terminates positive high voltage waveform **1228**. The measurement node toggles at **1243**, back to node state 1.

In a preferred embodiment, the sync pulses are 0.5 seconds apart, thereby conducting an entire channel test in approximately 2.5 seconds. Those of skill in the art will recognize that a complete survey of ten test channels can now be conducted in about 25 seconds. This a vast improvement over the prior art. Further, since the test data is sent independently by the nodes using the DMA memory model and an isolated upstream communications channel, there is no delay in transmission or contention for data channel use.

Referring to FIGS. **13A** through **13D**, an example of interleaving a set of nodes during transition toggling will be further described.

Referring to FIG. **13A**, the nodes at positions 1 and 2 are assigned to A and B types respectively. The nodes at positions 3 and 4 are assigned node types LM and N respectively. The nodes at positions 5 and 6 are assigned node types M and N, respectively. The nodes at positions 7 and 8 are assigned node types M and N, respectively. The nodes at positions 9 and 10 are assigned node types M and N, respectively.

In the high voltage state 1, measurements will be taken at all N type nodes. In this example, measurements will be taken at node positions 4, 6, 8 and 10, resulting in measurements at positions **1302**, **1304**, **1306** and **1308**, respectively.

Referring to FIG. **13B**, node assignments after the first transition sync pulse will be described.

The nodes at positions 1 and 2, remain assigned node types A and B, respectively, at the first transition sync pulse. However, each of the measurement nodes have toggled to a different state. The nodes at position 4 and 5 has toggled to states M and N, respectively. The nodes at position 6 and 7 have toggled to states M and N, respectively. The nodes at position 8 and 9 have toggled to states M and N, respectively. Likewise, the node at position 10 has toggled from an N to an M state.

In the high voltage state 1, measurements will be taken at all N type nodes. In this example, measurements will be taken at node positions 5, 7 and 9, resulting in measurements at positions **1312**, **1314** and **1316**, respectively.

Referring to FIG. **13C**, the node type assignments after the HV state 2 sync pulse will be described. The nodes at position 1 and 2 are assigned to B and A types, respectively. The nodes at positions 3 and 4 are assigned node types LM and N, respectively. The nodes at positions 5 and 6 are assigned node types M and N, respectively. The nodes at positions 7 and 8 are assigned node types M and N, respectively. The nodes at positions 9 and 10 are assigned node types M and N, respectively.

In the high voltage state 2, measurements will be taken at all N type nodes. In this example, measurements will be taken at node positions 4, 6, 8 and 10, resulting in measurements at positions **1318**, **1320**, **1322** and **1324**, respectively.

Referring to FIG. **13D**, the node assignments after the second transition sync pulse will be described.

The nodes at positions 1 and 2, remain assigned node types B and A, respectively. However, each of the measurement nodes has toggled to a different state. The nodes at position 4 and 5 have toggled to states M and N, respectively. The nodes at position 6 and 7 have toggled to states M and N, respectively. The nodes at position 8 and 9 have toggled to states M and N, respectively. Likewise, the node at position 10 has toggled from an N to an M state.

In the high voltage state 2, measurements will be taken at all N type nodes. In this example, measurements will be taken at node positions 5, 7 and 9, resulting in measurements at positions **1328**, **1330** and **1332**, respectively.

The method of interleaving is important because it increases the amount of data that can be taken in each channel test. The method of switching polarity at the current injection nodes is important because it aids in deionizing the soil.

FIG. **14** shows a memory model for each packet of measurement data sent from the N type nodes to the master control board by DMA.

Packet **1400** includes destination **1402**, source section **1404**, payload section **1406**, and CRC section **1408**. The

destination section includes a 4 byte address of the processor to which the node is sending the packet. Source section **1404** includes a 4 byte address of the node sending the packet. Payload section **1406** includes a 2 byte payload which includes a measurement section **1410** and a sample node under section **1412**. Measurement section **1410** includes the digital measurement taken from ADC **616** during the measurement step. Section **1412** includes a 4 byte sample number. In a preferred embodiment, the sample numbers include 1 through 4. CRC section **1408** includes a 4 byte summation of the destination source and payload sections.

Referring to FIG. **15**, potential map **1500** will be described.

PC controller **412** processes the data received from the master control board at step **816**. After processing, as previously described, potential map **1500** results. Potential map **1500** is a result of the survey that has eighteen nodes at positions 1 through 19. Equipotential lines **1502**, **1504**, **1506**, **1508**, **1510**, **1512**, **1514**, **1516**, **1518** and **1520** indicate electrical resistivity profiles ranging from about 18 Ohms/meter to about and 200 Ohms/meter, at depths ranging from about 0 to about 5 meters below the surface. Each of the nodes is placed at an internode spacing of about 1 meter. Low resistivity readings at **1550** and **1555** indicate potential moisture in the soil. High resistivity readings at position **1560** and **1565** indicate high resistivity readings indicating high density anomalies such as rocks or concrete.

Referring to FIGS. **16A**, **16B**, **16C** and **16D**, preferred node housing **1600** will be described.

Housing **1600** comprises front panel **1604** and rear panel **1602**. Rear panel **1602** supports PCB **1603** by appropriate standoffs. Front panel **1604** is removably secured to rear panel **1602** by a plurality of screws **1607**, or a suitable industrial adhesive.

Gasket **1605** is positioned between rear panel **1602** and front panel **1604** and provides a watertight seal for the interior of the housing. Downstream cable connector **1612** and upstream cable connector **1610** are provided at the base of the container with appropriate watertight connections to the interior for further connection to PCB **1603**.

Front panel **1604** further includes indicator lights **1660** and **1662** which are both operatively connected to PCB **1603**, for indication of status. Stake mount bracket **1614** is fitted to rear panel **1602** with mounting screws **1615** and high voltage supply post **1617**. When in use, high voltage supply post **1617** is connected to PCB **1603** for communication of a high voltage signal to the stake mount bracket.

Stake mount bracket **1614** further comprises raised channel **1616** which, in a preferred embodiment, is horizontally positioned across the back of the rear panel. Raised channel **1616** further includes hexagonal clamp channel **1619**. In a preferred embodiment, hexagonal clamp channel **1619** is vertically positioned with respect to housing **1600**. The hexagonal clamp channel is sized to accommodate the diameter of the stake to within $\pm 1/10$ inch tolerance.

The shape of the hexagonal channel is important because it provides a self-centering placement of stake **1608** in the hexagonal channel due to pressure from adjustment bolt head **1621**, thereby creating a positive and secure mechanical and electrical contact at points **1650**, **1652**, **1654** and **1656**. Further, since the stake contacts the hexagonal channel in four (4) places in at least two vertical positions, the hexagonal channel prevents rotation of housing about the longitudinal and latitudinal axes of the stake.

Stake **1608** is positioned within hexagonal clamp channel **1619** and held in position by toggle clamp **1618**.

Toggle clamp **1618** further comprises base bracket **1664**, pivotally connected to engagement link **1665** and crank **1624**. Engagement link **1665** is pivotally connected to crank **1624** by coupler **1613**.

Base bracket **1664**, engagement link **1665**, crank **1624** and coupler **1613** cooperate to form a 4-bar linkage. Base bracket **1664** is rigidly connected to raised channel **1616** with mounting screws **1622**. Engagement link **1665** includes bolt hole **1611**, positioned generally perpendicular with hexagonal clamp channel **1619**. Collar **1623** is seated in bolt hole **1611**. Collar **1623** accommodates adjustment bolt **1620**. Adjustment bolt **1620** includes bolt head **1621**. Adjustment bolt **1620** is held in position by lock nuts **1621a** and **1621b** adjacent collar **1623**.

Adjustment bolt **1620** and lock nuts **1621a** and **1621b** are positioned centrally with respect to the raised channel so as to equalize the pressure exerted by bolt head **1621** on stake **1608** when the toggle clamp is in a closed position.

In a preferred embodiment, toggle clamp **1618** is operated by crank **1624**. Toggle clamp **1618** is closed by depressing crank **1624**, whereby toggle clamp **1618** forces stake **1608** firmly into hexagonal clamp channel **1619**, through force "F", thereby creating an electrical contact between the stake mount bracket, the high voltage supply post and stake **1608**. When crank **1624** is released, the adjustment bolt moves away from stake **1608** allowing housing **1600** to be removed from stake **1608** and disengaging the stake from electrical contact with stake mount bracket **1614** and high voltage supply post **1617**.

Stake **1608** is further provided with gradations **1626**. In a preferred embodiment, gradations **1626** are placed at 6" intervals along the length of the stake to indicate the depth into the ground that the stake has been driven. In a preferred embodiment, the stake is a $3/4$ " diameter round stainless steel rod about 4' long.

Referring to FIGS. **17A**, **17B** and **17C** a preferred embodiment of system housing **1700** will be described.

System housing **1700** includes enclosure **1702**. Enclosure **1702** further comprises base **1703**, removable side panel **1706** and top cover **1704**. The enclosure, the side panel and the top cover is preferably 0.8 mm stainless steel. The interior surface of top cover **1704** includes insulated radiant barrier **1705**. In a preferred embodiment, insulated radiant barrier **1705** is a 90 mil fiberglass and aluminum foil composite applied with a suitable adhesive. Likewise, side panel **1706** includes insulated radiant barrier **1707** applied to its interior surface. Top cover **1704** and side panel **1706** are removable and are affixed to enclosure **1702** through accessible screws.

Side panel **1706** includes side exhaust vent **1708** and side intake vent **1765**. Enclosure **1702** includes front intake vent **1710**, rear intake vent **1724** and rear exhaust vent **1720**.

Enclosure **1702** encloses and mechanically supports inverter **1716**, high voltage supply **1714** and master control board **1718**, as will be further described.

Enclosure **1702** includes rear panel **1713** and spring loaded push rod activation button **1712**. Rear panel **1713** provides visual access to control functions of the inverter and the high voltage supply. Push rod activation button **1712** controls power activation of inverter **1716** while providing for ease of replacement of the inverter. The push rod configuration is important because it electrically isolates the enclosure from the inverter and further allows removal and replacement of the inverter without replacing an electrical switch connection.

The exterior surface of enclosure 1702 further supports USB connector 1754 and upstream node connector 1758, operatively attached to master control board 1718.

Support bracket 1732 is rigidly attached to the interior of the enclosure. Support bracket 1732 further comprises rear support shelf 1723, rear support column 1729, channel base 1767, forward support column 1728 and forward support shelf 1757. In a preferred embodiment, the support bracket is integrally formed for 0.8 mm stainless steel. Channel base 1767 is riveted or spot welded to base 1703. Rear support shelf 1723 is riveted or spot welded to the interior of enclosure 1702. Likewise, forward support shelf 1757 is riveted or spot welded to the interior of enclosure 1702. Card support channel 1759 is riveted or spot welded to forward support shelf 1757 and rear support shelf 1723. Rear support shelf 1723 further supports interior baffle 1722 and interior baffle 1734. Interior baffle 1722 is riveted to the surface of rear support shelf 1723. Interior baffle 1734 is riveted in between base 1703 and the lower surface of rear support shelf 1723. Handles 1790 and 1795 are bolted in place on the exterior of the enclosure adjacent and under forward support shelf 1757 and rear support shelf 1723, respectively.

Interior baffle 1722 includes opening 1721 sufficient to allow protrusion of inverter 1716 and high voltage supply 1714 at the rear of the enclosure. Interior baffle 1722 further includes internal vents 1744, as will be further described.

Interior baffle 1734 further comprises opening 1739 sufficient to allow protrusion of heat rejection fan 1736 of thermoelectric cooler 1760. Rear support column 1729 further comprises opening 1731, sufficient to allow protrusion of cooling heat sink 1730 of thermoelectric cooler 1760.

Forward support column 1728 further comprises opening 1731, sufficient to allow protrusion of cooling intake fan 1726, as will be further described.

Rear support shelf 1723 further comprises insulated radiant barrier 1705 on its upper surface. Insulated radiant barrier 1705, in a preferred embodiment also encompasses the rear surface of interior baffle 1722.

Forward support column 1728, forward support shelf 1757, base 1703 and the interior of side panel 1706 form front intake duct 1711. Front intake duct 1711 is ductedly connected to front intake vent 1710 in the front of enclosure 1702. Likewise, interior baffle 1734, rear support shelf 1723, base 1703 and the interior of side panel 1706 form rear intake duct 1725. Rear intake duct 1725 is ductedly connected with rear intake vent 1724 and side intake vent 1765, as will be further described. Rear intake duct 1725 is also ductedly connected to side exhaust vent 1708 through heat rejection fan 1736 and heat rejection heat sink 1738.

Forward support column 1728 and rear support column 1729 form cooling duct 1733. Cooling duct 1733 is ductedly connected to front intake duct 1711 through cooling intake fan 1726 and cooling heat sink 1730.

Peltier junction 1799 is fixed between cooling heat sink 1730 and heat rejection heat sink 1738.

Forward support shelf 1757, rear support shelf 1723, interior baffle 1722 and top cover 1704 form cooled compartment 1752. Cooled compartment 1752 is ductedly connected with cooling duct 1733 through portal 1797.

Rear support shelf 1723, interior baffle 1722 and top cover 1704 form exhaust compartment 1735. Exhaust compartment 1735 is ductedly connected to rear exhaust vent 1720 and internal vent 1744, as will be further described.

Thermoelectric cooler 1760 is comprised of large Peltier junction 1799 sandwiched between heat rejection heat sink 1738 and cooling heat sink 1730. Cooling intake fan 1726 is

affixed to cooling heat sink 1730. Heat rejection fan 1736 is affixed to heat rejection heat sink 1738.

In use, when current is supplied to Peltier junction 1799, heat is drawn from cooling heat sink 1730 and moved to heat rejection heat sink 1738. Heat rejection fan 1736 and cooling intake fan 1726 are activated. As a result, cooling air is drawn along cool airflow path 1762 through front intake vent 1710 by cooling intake fan 1726. Cooling intake fan 1726 forces incoming air across cooling heat sink 1730 and into cooling duct 1733. Cooling duct 1733 forces air upward through portal 1797 and into cooled compartment 1752, along cool air path 1748, where it draws heat from master control board 1718 and exits through internal vent 1744 into exhaust compartment 1735. Cool air flow path further enters inverter 1716 and high voltage supply 1714 through intake ducts in both components (not shown). Cool airflow path 1762 further flows through these components and exits through inverter heat exhaust fan 1719 and high voltage supply heat exhaust fan 1768. Cool airflow path 1762 then exits through exhaust compartment 1735 forming exhaust air path 1750 through rear exhaust vent 1720.

Heat rejection air path 1740 enters rear intake vent 1724 and side intake vent 1765, and enters rear intake duct 1725.

Heat rejection air path 1740 is drawn into thermoelectric cooler 1760 through heat rejection fan 1736. Heat rejection fan 1736 forces ambient air through heat rejection heat sink 1738 of thermoelectric cooler 1760 which exits through side exhaust vent 1708.

In use, the thermoelectric cooler, reduces the temperature of the components in the cooled compartment by between about 15° F. and 20° F. Maintaining inverter 1716, high voltage supply 1714, and master control board 1718 at a reduced temperature is important when the system is used in elevated outdoor temperatures because it reduces variation in the resistive values of the electrical components thereby decreasing error and increasing precision of the measurements taken by the system.

The invention claimed is:

1. A system for gathering geophysical data comprising:
 - a master processor, having a master processor memory;
 - a plurality of node processors, having a plurality of node processor memories;
 - a communication channel, connecting the master processor and each node processor of the plurality of node processors;
 - a synchronization channel, connecting the master processor and each node processor of the plurality of node processors; and
 - the master processor memory and the plurality of node processor memories containing a set of instructions, that when executed, cause the system to:
 - conduct a self-enumeration process at each node processor of the plurality of node processors, using the communication channel;
 - format the plurality of node processors for a test shot, by the master processor, using the communication channel;
 - acquire a set of geophysical data, by the plurality of node processors, controlled by a set of test shot signals, from the master processor, using the synchronization channel; and
 - report the set of geophysical data, from the plurality of node processors, to the master processor, using the communication channel;

37

wherein conducting the self-enumeration process further comprises:

- generating a first self-enumeration packet, at the master processor, having a blank destination address;
- 5 sending the first self-enumeration packet to a first node processor, of the plurality of node processors, on the communication channel;
- determining, at the first node processor, whether the first node processor has a first destination address;
- 10 if the first node processor does not have the first destination address, then incrementing the blank destination address, to create an incremented address;
- 15 assigning the incremented address as the first destination address;
- calculating a number of node processors of the plurality of node processors; and
- 20 sending the number of node processors, to the master processor, on the communication channel.

2. The system of claim 1, wherein conducting the self-enumeration process further comprises:

- engaging a set of communication channel termination resistors, on the communication channel, by the first node processor.
- 25

3. The system of claim 1, further comprises:

- creating an address table, at the master processor, by incrementing the blank destination address by the number of node processors.

4. The system of claim 1, wherein formatting the plurality of node processors further comprises:

- 30 generating a set of node type assignment packets;
- sending the set of node type assignment packets to a node processor, of the plurality of node processors; and
- 35 setting a configuration of the node processor, of the plurality of node processors, based on a first node type assignment packet of the set of node type assignment packets.

5. The system of claim 4, wherein formatting the plurality of node processors further comprises:

- 40 forwarding a second node type assignment packet, of the set of node type assignment packets, from the first node processor to a second node processor, of the plurality of node processors, using the communication channel.

6. The system of claim 1, wherein reporting the set of geophysical data further comprises:

- 45 sending a first data set, of the set of geophysical data, from a node processor of the plurality of node processors, to the master processor, on the communication channel, using a direct memory access format.
- 50

7. The system of claim 1, wherein:

- the communication channel further comprises a set of RS485 transceivers connected to a node processor, of the plurality of node processors.

8. A system for gathering geophysical data comprising:

- 55 a master processor, having a master processor memory;
- a plurality of node processors, having a plurality of node processor memories;
- a communication channel, connecting the master processor and each node processor of the plurality of node processors;
- 60 a synchronization channel, connecting the master processor and each node processor of the plurality of node processors;
- the master processor memory and the plurality of node processor memories containing a set of instructions, that when executed, cause the system to:
- 65

38

- conduct a self-enumeration process at each node processor of the plurality of node processors, using the communication channel;
- format the plurality of node processors for a test shot, by the master processor, using the communication channel;
- acquire a set of geophysical data, by the plurality of node processors, controlled by a set of test shot signals, from the master processor, using the synchronization channel; and
- report the set of geophysical data, from the plurality of node processors, to the master processor, using the communication channel; and
- a voltage measurement channel, connecting the master processor and each node processor of the plurality of node processors;
- wherein the set of instructions further comprise instructions that when executed cause the system to:
- calibrate the master processor using the voltage measurement channel; and
- calibrate each node processor, of the plurality of node processors, using the voltage measurement channel.

9. A system for gathering geophysical data comprising:

- a master processor, having a master processor memory;
- a plurality of node processors, having a plurality of node processor memories;
- a communication channel, connecting the master processor and each node processor of the plurality of node processors;
- a synchronization channel, connecting the master processor and each node processor of the plurality of node processors;
- the master processor memory and the plurality of node processor memories containing a set of instructions, that when executed, cause the system to:
- conduct a self-enumeration process at each node processor of the plurality of node processors, using the communication channel;
- format the plurality of node processors for a test shot, by the master processor, using the communication channel;
- acquire a set of geophysical data, by the plurality of node processors, controlled by a set of test shot signals, from the master processor, using the synchronization channel; and
- report the set of geophysical data, from the plurality of node processors, to the master processor, using the communication channel;
- a set of electrodes, impressed in a geological surface;
- at least one electrode, of the set of electrodes, connected to each node processor, of the plurality of node processors; and
- a high voltage channel, connecting the master processor and each node processor of the plurality of node processors;
- wherein formatting the plurality of node processors further comprises:
- recursively connecting each first node processor of the plurality of node processors to the high voltage channel.

10. A system for gathering geophysical data comprising:

- a master processor, having a master processor memory;
- a plurality of node processors, having a plurality of node processor memories;
- a communication channel, connecting the master processor and each node processor of the plurality of node processors;

39

a synchronization channel, connecting the master processor and each node processor of the plurality of node processors;

the master processor memory and the plurality of node processor memories containing a set of instructions, that when executed, cause the system to:

conduct a self-enumeration process at each node processor of the plurality of node processors, using the communication channel;

format the plurality of node processors for a test shot, by the master processor, using the communication channel;

acquire a set of geophysical data, by the plurality of node processors, controlled by a set of test shot signals, from the master processor, using the synchronization channel; and

report the set of geophysical data, from the plurality of node processors, to the master processor, using the communication channel;

a set of electrodes, impressed in a geological surface;

at least one electrode, of the set of electrodes, connected to each node processor of the plurality of node processors; and

a voltage measurement channel, connecting the master processor and each node processor of the plurality of node processors;

wherein formatting the plurality of node processors further comprises:

recursively connecting each node processor of the plurality of node processors to the voltage measurement channel.

11. A system for gathering geophysical data comprising:

a master processor, having a master processor memory;

a plurality of node processors, having a plurality of node processor memories;

a communication channel, connecting the master processor and each node processor of the plurality of node processors;

a synchronization channel, connecting the master processor and each node processor of the plurality of node processors;

the master processor memory and the plurality of node processor memories containing a set of instructions, that when executed, cause the system to:

conduct a self-enumeration process at each node processor of the plurality of node processors, using the communication channel;

format the plurality of node processors for a test shot, by the master processor, using the communication channel;

acquire a set of geophysical data, by the plurality of node processors, controlled by a set of test shot signals, from the master processor, using the synchronization channel; and

report the set of geophysical data, from the plurality of node processors, to the master processor, using the communication channel;

a high voltage channel, connecting the master processor and each node processor of the plurality of node processors; and

a voltage measurement channel, connecting the master processor and each node processor of the plurality of node processors;

40

wherein the communication channel, the high voltage channel and the voltage measurement channel cross a high voltage isolation barrier, in each node processor, of the plurality of node processors.

12. A system for gathering geophysical data comprising:

a master processor, having a master processor memory;

a plurality of node processors, having a plurality of node processor memories;

a direct memory access channel, connecting the master processor and each node processor of the plurality of node processors;

a measurement channel, connected to the master processor and the plurality of node processors;

the master processor memory and the plurality of node processor memories containing a set of instructions that when executed cause the system to:

connect a first node processor pair, of the plurality of node processors, to an isolated high voltage source, using the direct memory access channel;

connect a second node processor pair, of the plurality of node processors, to the measurement channel, using the direct memory access channel;

acquire a set of geophysical data, by the second node processor pair, using the measurement channel; and

report the set of geophysical data, from a measurement node of the second node processor pair, to the master processor, using the direct memory access channel;

wherein reporting the set of geophysical data further comprises:

sending a data packet, to the master processor memory, from the measurement node, using the direct memory access channel; and

wherein the data packet further comprises:

an address of the measurement node and a voltage reading;

wherein the set of instructions further comprises instructions that when executed cause the system to:

convert the voltage reading to a resistivity value; and

format the resistivity value into a pre-universal resistivity file.

13. The system of claim **12**, wherein the master processor further comprises:

a first direct memory access controller;

wherein the set of instructions further comprises instructions that when executed cause the system to:

send an interrupt from the first direct memory access controller to the master processor related to the data packet.

14. The system of claim **13**, wherein the set of instructions further comprises instructions that when executed cause the system to:

store the data packet in the master processor memory.

15. The system of claim **12**, wherein the system further comprises:

a display processor, operatively connected to the master processor, having a display processor memory; and

the display processor memory, and the plurality of node processor memories include further instructions that when executed cause the system to:

send, from the master processor to the display processor, the resistivity value; and

generate a graphic, related to the resistivity value, by the display processor.

* * * * *