

US012097125B2

(12) **United States Patent**
Cowan

(10) **Patent No.:** **US 12,097,125 B2**
(45) **Date of Patent:** **Sep. 24, 2024**

(54) **METHOD AND IMPLANT DEVICE FOR GRAFTING ADJACENT VERTEBRAL BODIES**
(71) Applicant: **GLOBUS MEDICAL, INC.**, Audubon, PA (US)
(72) Inventor: **John A. Cowan**, Rome, GA (US)
(73) Assignee: **Globus Medical, Inc.**, Audubon, PA (US)

(2013.01); *A61F 2002/30433* (2013.01); *A61F 2002/30492* (2013.01); *A61F 2002/305* (2013.01); *A61F 2002/30507* (2013.01); *A61F 2002/3055* (2013.01); *A61F 2002/30574* (2013.01); *A61F 2002/30576* (2013.01); *A61F 2002/30578* (2013.01); *A61F 2002/30593* (2013.01); *A61F 2002/30604* (2013.01); *A61F 2002/30607* (2013.01); *A61F 2002/30616* (2013.01); *A61F 2002/3065* (2013.01); *A61F 2002/30662* (2013.01);

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 119 days.

(58) **Field of Classification Search**
CPC *A61F 2/4455*; *A61F 2/4465*; *A61F 2/4425*; *A61F 2002/443*
See application file for complete search history.

(21) Appl. No.: **17/815,970**
(22) Filed: **Jul. 29, 2022**

(56) **References Cited**
U.S. PATENT DOCUMENTS

(65) **Prior Publication Data**
US 2022/0362035 A1 Nov. 17, 2022

2004/0199252 A1* 10/2004 Sears *A61F 2/44*
606/279

* cited by examiner

Primary Examiner — Olivia C Chang

Related U.S. Application Data


(60) Continuation of application No. 16/928,183, filed on Jul. 14, 2020, now Pat. No. 11,413,158, which is a (Continued)

(57) **ABSTRACT**

(51) **Int. Cl.**
A61F 2/44 (2006.01)
A61F 2/28 (2006.01)
(Continued)
(52) **U.S. Cl.**
CPC *A61F 2/4465* (2013.01); *A61F 2/2846* (2013.01); *A61F 2/4425* (2013.01); *A61F 2/4455* (2013.01); *A61F 2/4611* (2013.01); *A61F 2002/2835* (2013.01); *A61F 2002/285* (2013.01); *A61F 2002/30062* (2013.01); *A61F 2002/30224* (2013.01); *A61F 2002/30225* (2013.01); *A61F 2002/30227* (2013.01); *A61F 2002/30233* (2013.01); *A61F 2002/30235*

A methodology for grafting together adjacent bony structures is provided using an implant device having an endplate with an inner disc portion and outer ring portion spaced from the inner disc portion by a connecting wall disposed there between. An endplate interior surface includes a retaining structure for securing the endplate to one of the bony structures, and endplate an exterior surface has an integrally formed socket. A ball-joint rod has a longitudinally extending body and an end, and at least a portion of the ball-joint rod end is curvilinear in shape. The curvilinear ball-joint rod end is rotatably disposed in the endplate socket to fixedly interconnect the bony structures.

12 Claims, 12 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/806,582, filed on Nov. 8, 2017, now Pat. No. 10,758,364, which is a continuation of application No. 15/244,031, filed on Aug. 23, 2016, now Pat. No. 9,839,526, which is a division of application No. 13/866,512, filed on Apr. 19, 2013, now Pat. No. 9,468,537, which is a continuation-in-part of application No. 13/366,890, filed on Feb. 6, 2012, now Pat. No. 8,425,606.

(60) Provisional application No. 61/499,271, filed on Jun. 21, 2011.

(51) **Int. Cl.**

A61F 2/46 (2006.01)

A61F 2/30 (2006.01)

(52) **U.S. Cl.**

CPC *A61F 2002/30663* (2013.01); *A61F 2002/30665* (2013.01); *A61F 2002/30729* (2013.01); *A61F 2002/30777* (2013.01); *A61F 2002/30779* (2013.01); *A61F 2002/30785* (2013.01); *A61F 2002/30787* (2013.01); *A61F 2002/30789* (2013.01); *A61F 2002/30825* (2013.01); *A61F 2002/30841* (2013.01); *A61F 2002/30845* (2013.01); *A61F 2002/30863* (2013.01); *A61F 2002/30884* (2013.01); *A61F 2002/30891* (2013.01); *A61F 2002/30894* (2013.01); *A61F 2002/443* (2013.01); *A61F 2220/0016* (2013.01); *A61F 2310/00023* (2013.01)








FIG - 2










FIG - 7






FIG - 9






FIG - 11













FIG - 13










FIG. 21




FIG. 22




FIG. 23

METHOD AND IMPLANT DEVICE FOR GRAFTING ADJACENT VERTEBRAL BODIES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application a continuation of U.S. patent application Ser. No. 16/928,183, filed Jul. 14, 2020, which is a continuation of U.S. patent application Ser. No. 15/806,582, filed Nov. 8, 2017, which is a continuation of U.S. patent application Ser. No. 15/244,031, filed Aug. 23, 2016, which is a divisional of U.S. patent application Ser. No. 13/866,512, filed Apr. 19, 2013, now U.S. Pat. No. 9,468,537, which is a continuation-in-part of U.S. patent application Ser. No. 13/366,890, filed Feb. 6, 2012, now U.S. Pat. No. 8,425,606, which claims the benefit of U.S. Provisional Application No. 61/499,271, filed on Jun. 21, 2011, the contents of which are hereby incorporated by reference in their entireties for all purposes.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present disclosure relates generally to a vertebral implant device, and more particularly, to a method and implant device for grafting together adjacent vertebral bodies.

2. Description of Related Art

Diseases and injury to bone structures, such as the vertebral column, and conditions requiring surgical intervention are relatively common. A variety of conventional implant or graft devices are presently available for use in specific areas. The devices vary in size, shape, materials used, and insertion techniques. For example, in the vertebral column, grafts may provide restoration, decompression, or stabilization of the spine. Typically these devices include a member that is inserted in the vertebral column to replace an injured portion. An example of such a procedure is a corpectomy, which involves the replacement of a vertebral body with an implant or graft. The graft is secured to the adjacent vertebrae via a plurality of fasteners to maintain the position of the implant in situ.

While these conventional devices may generally provide adequate results, they have several disadvantages. For example, conventional graft devices utilized in a corpectomy procedure typically have a relatively bulky all-in-one construction and include several components. Such an implant construction limits surgery flexibility, including the approach to the spine. The instrument utilized for insertion is likewise limited due to the constraints of existing implant devices.

Thus, there is a need in the art for a graft device that has a modular construction such that components can be interconnected when and as needed to enhance surgery flexibility and offer increased adaptability to individual patient anatomy.

Other features and advantages of the present disclosure will be readily appreciated, as the same becomes better understood after reading the subsequent description taken in conjunction with the accompanying drawings.

SUMMARY OF THE INVENTION

Accordingly, the present disclosure relates to an implant device for grafting together adjacent bony structures. The

implant device has an endplate with an inner disc portion and outer ring portion spaced from the inner disc portion by a connecting wall disposed therebetween. An endplate interior surface includes a retaining structure for securing the endplate to one of the bony structures, and endplate an exterior surface has an integrally formed socket. A ball-joint rod has a longitudinally extending body and an end, and at least a portion of the ball-joint rod end is curvilinear in shape. The curvilinear ball-joint rod end is rotatably disposed in the endplate socket to fixedly interconnect the bony structures. The methodology includes the steps of securing an endplate to each of the vertebral bodies and interconnecting each endplate using a ball-joint rod.

One advantage of the present disclosure is that an improved implant device is provided that is modular in construction and enhances surgery flexibility allowing for minimally invasive approaches. Another advantage of the present disclosure is that the implant device is a vertebral graft that is easy to assemble and insert from a lateral or lateral extracavity approach. Yet another advantage of the present disclosure is that a vertebral implant device is provided that facilitates bone grafting. Still another advantage of the present disclosure is that the vertebral implant device includes a bristle post to help support bone growth. A further advantage of the present disclosure is that the vertebral implant device provides for strong and stable endplate gripping. Yet a further advantage of the present disclosure is that the vertebral implant device provides for modular in situ insertion for easier placement. Still a further advantage of the present disclosure is that the vertebral implant device provides for larger endplates which results in less "pistoning" and more aggressive distraction for enhanced performance. Still yet a further advantage of the present disclosure is that the vertebral implant device provides a snap-in ball-joint rod that enables variation in endplate alignment and angulation. Still yet another advantage of the present disclosure is that the vertebral implant device may include a snap-on bristle cage that enables generous and stable packing of bone graft. Still another advantage of the present disclosure is that the vertebral implant device provides may include a snap-on allograft strut. Yet another advantage of the present disclosure is that the vertebral implant device provides for motion preservation due to a ball-joint construct.

Other features and advantages of the present disclosure will be readily appreciated, as the same becomes better understood after reading the subsequent description taken in conjunction with the accompanying drawings.

Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred embodiment of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

FIG. 1 is a perspective view of a vertebral implant device, according to an exemplary embodiment.

FIG. 2 is a top view of an endplate of the vertebral implant device of FIG. 1.

FIG. 3 is a side view of the endplate of the vertebral implant device of FIG. 2.

3

FIG. 4 is a side view of the endplate of the vertebral implant device of FIG. 3 including a fastener.

FIG. 5a is an elevational side view of a ball-joint rod of the vertebral implant device of FIG. 1.

FIG. 5b is an elevational side view of a ball-joint rod having a plurality of spikes, according to another embodiment.

FIG. 6 is a perspective view of a vertebral implant device having a bristle post fusion shaft member.

FIG. 7 is an enlarged side view of the bristle post fusion shaft member of FIG. 6.

FIG. 8 is a top view of the ball-joint rod and bristle shaft member of FIG. 6.

FIG. 9 is a perspective view of a vertebral implant device having a ring fusion shaft member.

FIG. 10 is an enlarged side view of the ring fusion shaft member of FIG. 9.

FIG. 11 is a top view of the ball-joint rod of FIG. 9.

FIG. 12 is a perspective view of a device for inserting a vertebral implant into a vertebral region, according to an exemplary embodiment.

FIG. 13 is a flowchart of a method of inserting a vertebral implant device into a vertebral region, using the vertebral implant device of FIG. 1.

FIG. 14 is a side view illustrating a vertebral region having undergone a corpectomy according to the method of FIG. 13.

FIG. 15 is a side view illustrating a pair of endplates inserted between two vertebrae, according to the method of FIG. 13.

FIG. 16 is a side view of the endplates of FIG. 15 illustrating attachment of the endplates to the vertebrae.

FIG. 17 is a side view illustrating attachment of a ball-joint rod to the endplates.

FIG. 18 is a side view of a bristle fusion shaft member attached to the ball-joint rod of FIG. 17, according to an exemplary embodiment.

FIG. 19 is a sectional view of the vertebral implant device of FIG. 6 secured to two adjacent vertebral bodies.

FIG. 20 is an elevational view of the vertebral implant device set at a predetermined angle.

FIG. 21 is a side view illustrating an end plate having a poly axial head that allows for attachment of a ride at various angles.

FIG. 22 is a side view of an alternative embodiment illustrating attachment of a ball-joint rod to an endplate.

FIG. 23 is a top view of the alternative embodiment according to FIG. 22.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following description of the preferred embodiment(s) is merely exemplary in nature and is in no way intended to limit the invention, its application, or uses.

Referring to FIGS. 1-20, an implant device 10 for use between adjacent bone structures is shown. In this example, the implant device 10 is a vertebral implant device 10 designed to be implanted in regions of the spine 12, such as the cervical, thoracic, and lumbar spine, although the location of implantation is non-limiting. For example, the vertebral implant device 10 can be used in the lateral extracavity, anterolateral, or direct anterior regions of the thoracolumbar spine to address indications relating to trauma, tumors, and degenerative issues such as scoliosis, or the like. The vertebral implant device 10 may serve as a modular mechanical graft to support eventual bone growth.

4

The vertebral implant device 10 and its individual components can be fabricated from various materials, such as, plastic, metal, alloys, a bio-absorbable polymer, or the like, and the selection is non-limiting. The selected material may be magnetic resonance imaging (MRI) compatible. Implantation of the vertebral implant device 10 may be via lateral or lateral extracavitary approaches, in a manner to be described.

Referring now to FIGS. 2-4, the vertebral implant device 10 of this example is illustrated. The vertebral implant device 10 generally includes an endplate 14 that provides a direct attachment mechanism to the adjacent remaining vertebra 16 and distributes forces across the vertebra 16. In this example there is a first endplate 14 and a second endplate 14 that is spaced apart from the first endplate by a rod 18 or shaft. The endplate 14 may be about mm thick and range from 20-40 mm in diameter. The endplate 14 can be made of various materials, such as titanium, PEEK, a bio-absorbable polymer, or the like. The endplate 14 includes an exterior surface 20 and an interior surface 22, and the endplate interior surface 22 is in direct contact with the adjacent vertebral body 16. The endplate interior surface 22 may have a variety of profiles, such as a concentric rings of varying thickness, or the like, to mimic anatomic doming of the vertebrae.

The endplate 14 has a generally circular disc-shaped profile. The endplate 14 includes an inner disc portion 24 that is spaced apart from a generally planar outer ring portion 26 by a connecting wall 28. A generally planar collar 30 extends away from an outer edge of the outer ring portion 26.

The endplate inner disc portion 24 is concave to form a socket 32 for receiving a portion of the ball-joint rod 18 in a manner to be described. The wall of the socket 32 may include apertures 34 so that bone marrow may pass there-through from the passageways 36 formed within the vertebral implant device 10. Further, the wall of the socket may include another aperture (not shown) for receiving a locking set screw to prevent angular movement of the formed ball-socket joint from a final position. In another example, the wall of the socket 32 may include a structural formation, such as a circumferentially extending indentations, groves or the like, to facilitate grasping of corresponding spikes or protrusions on the ball joint rod end. This would allow gripping of the ball joint rod end at various angles but would prevent slipping from that predetermined angle, in a manner to be described.

FIGS. 22-23 illustrates another or alternative embodiment of the present invention wherein the inner disc 24 is formed of two separate sections 24a, 24b. As illustrated, the ball-joint body end 56 is placed in the socket 32 wherein the second section 24b is then positioned adjacent the first section 24a to capture and retain the ball-joint rod 18 to endplate 14. As illustrated a pair of fasteners 100 extend through the second section 24b and are received in threaded apertures 102 located in first section 24a. Further, while the socket 32 is shown extending into the collar 30, the depth of the socket 32 can be limited to the length of the wall 28 whereby the ball-joint body end 56 can be slid laterally or sideways above the top surface of the concentric ring portion 26 and into the socket 32. Since the second section 24b has a complementary or identical configuration placing it adjacent the first section 24a secures the ball-joint rod 18 to the endplate 14. In this way, the half dome shaped socket 32 is formed from the respective sections 24a, 24b which cooperate together to complete or form a full socket 32. While shown herein as secured by threaded fasteners, other mecha-

5

nisms could be used to secure the respective sections **24a**, **24b** to one another including various types of snap fit arrangements including detent tabs, bayonet and other push type fastener systems.

In addition, as illustrated in FIG. **21** the ball-joint rod **18** may be formed in two separate portions wherein the ball-joint body portion **54** is separate from the ball-joint body end **56** shown engaged or connected to the endplate **14**. Thus, the ball-joint body end **56** forms a poly-axial head **106** configured to receive a fusion shaft **108** of the ball-joint body portion **54**. As illustrated a pin **110** extends through the poly-axial head **106** and fusion shaft **108** to couple the two together. While the pin **110** is shown, other mechanisms or fastening means, such as set screws, can be used to couple or attached the ball-joint body end **56** to the ball-joint body portion **54**. Accordingly, multiple endplates **14** can be secured with their respective ball-joint body ends **56** already attached after which a ball-joint body portion **54** is used to connect selected endplates **14**.

The endplate **14** may also include a retaining structure **40** for securing the endplate **14** to the adjacent vertebral body **16**. Further, the endplate **14** may include a plurality of retaining structures **40** that are concentrically arranged within the endplate interior surface **22** to form an inner ring wall. Additionally, the endplate **12** may include one or more concentric inner ring walls **42**. Each concentric ring well **42** may have an increasing diameter to correspond to anatomic endplate surfaces of the adjacent vertebral bodies **16**. An example of a retaining structure **40** is a cleat **44** extending outwardly from the endplate interior surface **22**. Each cleat **44** may have a predetermined shape. In this example, cleat **44** has an upper surface that is angled/curved/actuate to conform to or mirror the dome- or bowl-like shape of the upper surface of the endplate. The cleat **44** may be hollow as shown at **45** to form another passageway **36** for bone graft material to travel through, and may connect with other passageways **36** formed in the endplate interior portion **22**. The endplate **12** may also include a plurality of integrally formed apertures **46**, and the apertures **46** may assume various shapes, such as circular or as a notch or the like. The openings formed between the retaining structures **40** similarly form a connection to passageways **36** that facilitate the transfer of bone growth therethrough.

Another example of a retaining structure **40** is a spike **48**, such as a central spike as shown at **48a** extending from the center of the endplate inner disc **24** for impactation into an object, such as the adjacent vertebral body **16** or the like. The central spike **48a** can likewise have apertures **48b** leading to an interior channel **48c** to allow for autograft or bone marrow to seep through and support bone growth therein.

The endplate **12** also includes an opening **34** for receiving a fastener **38**, such as a screw or the like, for either tacking or fixedly securing the endplate **14** to the adjacent vertebral body **16** or the like. In an example, the opening **34** is located in the endplate outer ring **26**. If a temporary fixation of the endplate **14** to the anatomic endplate **98** of the adjacent vertebral body is desired, the fastener **38** may be a tack screw having a predetermined length, such as 3 mm. Similarly, the fastener **38** may be a screw having another predetermined length, such as 10 mm, although other types of fasteners **52** may be utilized.

Referring now to FIG. **5a**, a ball-joint rod **18** that interconnects the endplates **14** and provides structural support to the removed vertebral body **16** is illustrated. The ball-joint rod **18** has a generally cylindrical body portion **54**, with a first end **56** and an opposed second end **56**. The ball-joint body portion **54** may vary in length depending on specific

6

anatomical characteristics. The ball-joint body ends **56** each have a semi-spherical shape. Similarly, the ball-joint body end **56** may have a spherical shape, or a similar combination. The ball-joint end **56** is received in the socket **32** formed in the endplate **14**, and thus corresponds in shape and dimension to mate with the endplate socket **32**. For example, the ball-joint rod **18** may be between 5 mm to 30 mm in diameter.

The ball-joint rod **18** may also include other features, such as an integrally formed groove **58** positioned adjacent the ball joint end and extending circumferentially around the ball-joint body **54**. The ball-joint rod groove **58** and the ball-joint body **54** operatively work in conjunction with each other to engage the socket **32** formed in the endplate **14** to create a snap-fit ball-joint **60** to retain the ball-joint rod **18** to the endplate **14**. The ball-joint end **56** may be engaged in the end plate socket **32** using a variety of techniques, such as by using a spring loaded ring/washer, set screw, fastener, nitrile ring, or the like. For example, a locking device (not shown), such as a spring washer, may be inserted in the groove **58** to prevent the ball-joint rod **54** from disengaging from the endplate socket **32**. The second ball-joint end, a second ball-joint groove and likewise are engaged with the socket formed in the second endplate to also create a snap-fit joint. This type of universal joint enables each of the endplates **14** to freely move independently from each other, as shown in FIG. **20**. This flexibility enables variation in endplate alignment and angulation for improved insertion, attachment, and performance of the device **10**. The ball-joint rod **14** body **54** can be of various sizes. In this example, the ball-joint body can range from 5 mm to 30 mm in length. The ball-joint rod body can be made of various materials, such as, titanium, PEEK, or the like.

The ball-joint rod **18** can also have a variety of other features to enhance performance, such as perforations, a hollow interior/core, extensions, spikes, or the like, to facilitate bone marrow growth and transit in, through, around passageways formed relative to the device **10**. For example, the ball-joint end **56** may have apertures **62** connecting with passageways **36** extending through the endplate for transmitting bone marrow or graft material **82** therethrough passageways **64** formed in the ball-joint rod **18**. Likewise, the ball-joint body **54** may have apertures **62** to connect with passageways **64**.

In another example, an exterior surface of the ball-joint rod body **54** can have a plurality of outwardly extending spikes **66**, as shown in FIG. **5b**. The spaces between the spikes **66** may delineate channels **68** for bone growth. In an example, the spikes **66** can be arranged on the ball-joint rod end **56**, such that the spikes **60** engage corresponding openings **34** in the endplates **12** to initially lock that ball-joint shaft into the endplate **14** at a selected position or angle **70**. The ball-joint rod **18** can then be further locked in the selected position or angle by fasteners, such as screws, or the like.

Referring now to FIGS. **6-8** the vertebral implant device **10** may include another member removeably attached thereto. In an example, the vertebral implant device **10** includes a fusion shaft member **80** that can be attached to the ball-joint rod body **54**, and that acts as a carrier, support, and/or container for bone grafting tissue, bone growth, or the like. Examples of various potential pathways for bone marrow transit are depicted in FIG. **19** at **82**. The fusion shaft member **80** has a circumferentially shaped body portion **84** that is placed over the ball-joint shaft body **54**. The fusion shaft member body portion **84** may have an opening **86** for engaging the ball-joint shaft body **54**. The fusion shaft

7

member body **84** also includes a plurality of extension members **88** or bristles that further facilitate bone growth and support of the graft. For example, the bristles **88** may contain a bone growth enhancement material such as allograft and/or autograft. The fusion shaft member **80** can have a variety of dimensions, sizes, shapes, or the like. In an example, the fusion shaft member **80** is a partial ring having a C-shape profile and having a circumference of approximately 270 degrees and includes a plurality of bristles extending outwardly therefrom, such as perpendicularly, or the like. The fusion shaft member **80** can be clipped in a snap-fit manner onto the ball-joint rod body portion. In another example, multiple fusion shaft members **80** can be stacked adjacent to one another on the ball-joint rod body **54** for additional coverage and to help bind the joint. For example, the fusion shaft members **80** may be positioned so that the opening of each is staggered. The fusion shaft member **80** can be made from a variety of materials, such as, vicryl, PEEK, or the like. Similarly, the bristles **88** may be a microfiber material.

Referring now to FIGS. 9-11, another example of an additional member is illustrated. In this example, the vertebral implant device **10** includes a ring member **90**, such as an allograft ring or strut, that can be attached to ball-joint rod body **54** to act as a carrier, support, and/or container for bone grafting tissue, bone growth, or the like. The ring member has an inner surface **92** that is placed adjacent to the ball-joint rod **54** and an outer surface **94** that further facilitates bone growth and support. The ring member **90** can have a variety of dimensions, sizes, shapes, or the like. In this example, the ring **90** has an opening shown at **96** to form a C-shaped profile, having a circumference of approximately 270 degrees and inferior and superior curvatures to span between the endplates. The ring member **90** can be clipped in a snap-fit manner onto the ball-joint rod body **54**. Multiple rings **90** can be placed adjacent to each other on the ball-joint rod body **54**, such as for additional coverage or to help bind the joint, or the like. The ring **54** can be made from a variety of materials, such as, vicryl, PEEK, or the like.

Referring now to FIG. 12, an insertion device **400** for implantation of the vertebral implant device **10** within the vertebrae **16** of a patient is shown. The insertion device **400** is generally Y-shaped and includes a first arm **402** having a first gripping portion **402a** and a first handle portion **402b**. The insertion device **400** also includes a second arm **404** having a first gripping portion **404a** and a second handle portion **404b**. The first arm and second arm **400**, **404** are pivotably attached at a pivot point **406**, above which defines the gripping portion and below which defines the handle portion. The arms **402**, **404** move relative to each other in scissor-like fashion above the pivot point **406**. The first arm and second arm gripping portion **408** operatively grips the vertebral implant device **10**. The gripping portion **408** of the insertion device **400** includes a ball-joint **410** to mimic the ball-joint shaft while inserting the device **10**. The insertion device **400** also includes a central guide member **412** for aligning and installing a fastener, such as a lock screw or the like. In operation, when the insertion device **400** is opened, the endplates **12** toggle on the insertion guide.

Referring now to FIG. 13, a flowchart outlining a method of implanting a vertebral implant device **10**, such as in a corpectomy procedure, is illustrated. The methodology demonstrates the potential for hollowed components which would facilitate bone marrow or other bone matrix transit. The methodology begins in block **500** with the step of preparing the site for the graft. For example, a partial or complete corpectomy involving the removal of a vertebral

8

body **16** or a portion of a vertebral body is performed on a patient. One or more vertebral bodies **16** may be removed, as shown in FIG. 14.

The method advances to block **510**, which includes the step of inserting an endplate **14** onto an anatomic **98** endplate of an adjacent vertebral body **16**. The size of the endplate **14** may be preselected using a gauge, such as an endplate sizer. Relevant dimensions include the diameter and length of the endplate **14**. In this example, the insertion guide **400** is utilized to position the endplate **12** on the respective anatomic endplate **98**. The first endplate and an opposed second endplate are positioned as shown in FIG. 15. The concentric inner rings **42** of the endplate **14** assist in the retention of the endplate **14** on the anatomic endplate **98**. The retaining members, such as the centrally located spike **48** allows the endplate ring well **42** to be impacted into the anatomical endplate. Similarly, the cleats may also assist in temporarily tacking the endplate **12** in the desired position. As described, the interior portion of the endplate fits over the anatomic endplate **98**, such as the cranial and caudal rings. A tack screw may be utilized to hold the endplate firmly against the vertebral body.

The method proceeds to block **520** which includes the step of securing the first endplate and the second endplate to an adjacent vertebral body, as shown in FIG. 16. In this step, pilot holes can be drilled using the guide portion **412** of the insertion device **400** and screws placed therein while the insertion device **400** is holding the endplates **14** fixedly in position.

The method then proceeds to block **530** which includes the step of measuring the distance between the endplates, such as using a caliper. An appropriately sized ball joint rod **18** is selected and using the insertion device **100**, the spherical ends **56** of the selected ball-joint rod **18** are disposed within the socket **32** formed in each endplate **14**, as shown in FIG. 17. In this step, the ball-joint rod is snapped in position while the insertion device is over-distracting the endplates. The socket joint is open on one side to all the ball joints to facilitate snapping in place. The ball-joint rod **18** may be secured to the endplate **14**. For example, a collar or groove portion **88** of the spherical end of the ball-joint rod may engage the socket **82** to form the ball and socket joint **60**. The collar may be threaded to secure in place, or a lock screw, as previously described, may be utilized. The locking set screw may be utilized to keep the ball socket joint **60** from pivoting on implantation, until alignment is complete. If a ball-joint rod such as that described in FIG. 5b is utilized, that the relative angular position of the anatomical vertebral body with respect to the ball-joint rod may be set as shown in FIG. 20, such as by snap-tilting the bristle ends into a corresponding aperture in the socket. Advantageously, a positive fit is achieved and the snap-in fit makes assembly easier.

If it is desired to preserve the functionality of the joint, then the methodology ends. The ball and socket arrangement of the graft allows for relative movement of the adjacent vertebrae. If functionality of the joint is to be limited, the method proceeds to block **540** which includes the step of selecting and attaching a second member to the ball-joint rod. In an example, the mobility of the joint is limited using a locking screw as a cam to lock the angular position between the graft and an upper or lower vertebral body, such as between 15-20 degrees of angulation or the like. Further each endplate can be set at a different angle. In another example, a fusion member **80** such as a bristle post member and/or an allograft strut may be located onto the ball-joint rod body **54**, as shown in FIG. 18. The bristle post member

80 may be snap fit onto the ball-joint rod body **54**. These secondary devices promote bone growth around the graft, so that the adjacent vertebral bodies are fused together.

The method can be modified in various manners, such as by adding steps, removing steps, rearranging steps, or the like. For example, the endplates may be further customized by heating the endplate and molding around the anatomical endplate to improve the bond therebetween. Advantageously, the device **10** may be assembly in situ and is readily customizable.

The present disclosure has been described in an illustrative manner. It is to be understood that the terminology which has been used is intended to be in the nature of words of description rather than of limitation. Many modifications and variations of the present disclosure are possible in light of the above teachings. Therefore, within the scope of the appended claim, the present disclosure may be practiced other than as specifically described.

The present disclosure has been described in an illustrative manner. It is to be understood that the terminology which has been used is intended to be in the nature of words of description rather than of limitation. Many modifications and variations of the present disclosure are possible in light of the above teachings. Therefore, within the scope of the appended claim, the present disclosure may be practiced other than as specifically described.

The description of the invention is merely exemplary in nature and, thus, variations that do not depart from the gist of the invention are intended to be within the scope of the invention. Such variations are not to be regarded as a departure from the spirit and scope of the invention.

What is claimed is:

1. A method of implanting an implant device for grafting together adjacent bony structures of a body comprising:
 - attaching a first endplate having a first socket to a first vertebral body;
 - attaching a second endplate having a second socket to a second vertebral body; and
 - selecting one of a plurality of rods based on spacing between the attached endplates, the selected rod having first and second opposite ends;
 - inserting the first and second ends of the selected rod to the respective first and second sockets of the attached endplates,
 - wherein after inserting the selected rod to the attached endplates, further comprising attaching a fusion shaft to the selected rod in a snap-fit manner.
2. The method of claim 1, wherein attaching the first endplate includes drilling a pilot hole in the first vertebral

body and inserting a bone screw through the drilled pilot hole to secure the first endplate to the first vertebral body.

3. The method of claim 1, wherein measuring a distance includes measuring the distance using a caliper.

4. The method of claim 1, wherein attaching the fusion shaft includes attaching a bristle post fusion shaft in a snap-fit manner.

5. The method of claim 1, wherein attaching the fusion shaft includes attaching a ring fusion shaft in a snap-fit manner.

6. The method of claim 1, wherein the selected rod is a ball joint rod with each end having a curvilinear shape.

7. The method of claim 6, wherein inserting the first and second ends of the selected rod includes inserting the first and second ends of the selected rod to the respective first and second sockets of the attached endplates in a snap-fit manner.

8. A method of implanting an implant device for grafting together adjacent bony structures of a body comprising:

attaching a first endplate having a first socket to a first vertebral body;

attaching a second endplate having a second socket to a second vertebral body; and

selecting a ball joint rod based on spacing between the attached endplates, the selected rod having first and second opposite ends with each end having a curvilinear shape;

inserting the first and second ends of the selected rod to the respective first and second sockets of the attached endplates in a snap-fit manner

wherein after inserting the selected rod to the attached endplates, further comprising attaching a fusion shaft to the selected rod in a snap-fit manner.

9. The method of claim 8, wherein attaching the first endplate includes drilling a pilot hole in the first vertebral body and inserting a bone screw through the drilled pilot hole to secure the first endplate to the first vertebral body.

10. The method of claim 8, wherein attaching the fusion shaft includes attaching a bristle post fusion shaft in a snap-fit manner.

11. The method of claim 8, wherein attaching the fusion shaft includes attaching a ring fusion shaft in a snap-fit manner.

12. The method of claim 8, wherein the selected ball joint rod includes a circumferential groove near the first end which engages with the first socket in the snap-fit manner, wherein the first end is rotatably disposed in the first socket to allow angular adjustment of the selected rod relative to the first attached endplate.

* * * * *