



US012102473B2

(12) **United States Patent**  
**Barthe et al.**

(10) **Patent No.:** **US 12,102,473 B2**  
(45) **Date of Patent:** **\*Oct. 1, 2024**

(54) **SYSTEMS FOR ULTRASOUND TREATMENT**

(56)

**References Cited**

(71) Applicant: **Ulthera, Inc.**, Mesa, AZ (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Peter G. Barthe**, Phoenix, AZ (US);  
**Michael H. Slayton**, Phoenix, AZ (US);  
**Inder Raj S. Makin**, Mesa, AZ (US)

2,427,348 A 9/1947 Bond et al.  
2,792,829 A 2/1952 Calosi  
(Continued)

(73) Assignee: **Ulthera, Inc.**, Mesa, AZ (US)

FOREIGN PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CN 2460061 11/2001  
CN 1734284 12/2009  
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

US 10,398,895 B2, 09/2019, Schwarz (withdrawn)  
(Continued)

(21) Appl. No.: **18/214,851**

(22) Filed: **Jun. 27, 2023**

(65) **Prior Publication Data**

US 2023/0338005 A1 Oct. 26, 2023

*Primary Examiner* — Shahdeep Mohammed  
(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

**Related U.S. Application Data**

(63) Continuation of application No. 17/410,780, filed on Aug. 24, 2021, now Pat. No. 11,723,622, which is a  
(Continued)

(51) **Int. Cl.**  
*A61B 8/08* (2006.01)  
*A45D 19/00* (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... *A61B 8/0858* (2013.01); *A45D 44/005* (2013.01); *A61B 8/4209* (2013.01);  
(Continued)

(58) **Field of Classification Search**


None  
See application file for complete search history.

(57)

**ABSTRACT**

Embodiments provide an ultrasound treatment system. In some embodiments, the system includes a removable transducer module having an ultrasound transducer. In some embodiments, the system can include a hand wand and a control module that is coupled to the hand wand and has a graphical user interface for controlling the removable transducer module, and an interface coupling the hand wand to the control module. The interface may provide power to the hand wand or may transfer a signal from the hand wand to the control module. In some embodiments, the treatment system may be used in cosmetic procedures on at least a portion of a face, head, neck, and/or other part of a patient.

**20 Claims, 16 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 16/703,019, filed on Dec. 4, 2019, now Pat. No. 11,123,039, which is a continuation of application No. 12/996,616, filed as application No. PCT/US2009/046475 on Jun. 5, 2009, now Pat. No. 10,537,304.

(60) Provisional application No. 61/059,477, filed on Jun. 6, 2008.

(51) **Int. Cl.**

*A45D 44/00* (2006.01)  
*A61B 5/00* (2006.01)  
*A61B 8/00* (2006.01)  
*A61B 90/00* (2016.01)  
*A61N 7/00* (2006.01)  
*G10K 11/35* (2006.01)

(52) **U.S. Cl.**

CPC ..... *A61B 8/4411* (2013.01); *A61B 8/4438* (2013.01); *A61B 8/4455* (2013.01); *A61B 8/4461* (2013.01); *A61B 8/461* (2013.01); *A61B 8/465* (2013.01); *A61B 8/467* (2013.01); *A61N 7/00* (2013.01); *A45D 2019/0033* (2013.01); *A45D 2044/007* (2013.01); *A45D 2200/207* (2013.01); *A61B 5/441* (2013.01); *A61B 5/6843* (2013.01); *A61B 8/4254* (2013.01); *A61B 8/4281* (2013.01); *A61B 8/429* (2013.01); *A61B 8/4472* (2013.01); *A61B 8/468* (2013.01); *A61B 8/469* (2013.01); *A61B 2090/378* (2016.02); *A61N 2007/0008* (2013.01); *A61N 2007/0034* (2013.01); *G10K 11/352* (2013.01)

(56)

**References Cited**

U.S. PATENT DOCUMENTS

3,913,386 A 10/1975 Saglio  
 3,965,455 A 6/1976 Hurwitz  
 3,992,925 A 11/1976 Perilhou  
 4,039,312 A 8/1977 Patru  
 4,059,098 A 11/1977 Murdock  
 4,101,795 A 7/1978 Fukumoto  
 4,151,834 A 5/1979 Sato et al.  
 4,166,967 A 9/1979 Benes et al.  
 4,211,948 A 7/1980 Smith et al.  
 4,211,949 A 7/1980 Brisken et al.  
 4,213,344 A 7/1980 Rose  
 4,276,491 A 6/1981 Daniel  
 4,315,514 A 2/1982 Drewes et al.  
 4,325,381 A 4/1982 Glenn  
 4,343,301 A 8/1982 Indech  
 4,372,296 A 2/1983 Fahim  
 4,379,145 A 4/1983 Masuho et al.  
 4,381,007 A 4/1983 Doss  
 4,381,787 A 5/1983 Hottinger  
 4,397,314 A 8/1983 Vaguine  
 4,409,839 A 10/1983 Taenzer  
 4,417,170 A 11/1983 Benisncasa  
 4,431,008 A 2/1984 Wanner et al.  
 4,441,486 A 4/1984 Pounds  
 4,452,084 A 6/1984 Taenzer  
 4,484,569 A 11/1984 Driller  
 4,507,582 A 3/1985 Glenn  
 4,513,749 A 4/1985 Kino  
 4,513,750 A 4/1985 Heyman et al.  
 4,527,550 A 7/1985 Ruggera et al.  
 4,528,979 A 7/1985 Marchenko  
 4,534,221 A 8/1985 Fife et al.  
 4,566,459 A 1/1986 Umemura et al.  
 4,567,895 A 2/1986 Putzke  
 4,586,512 A 5/1986 Do-Huu

4,587,971 A 5/1986 Stolfi  
 4,601,296 A 7/1986 Yerushalmi  
 4,620,546 A 11/1986 Aida et al.  
 4,637,256 A 1/1987 Sugiyama et al.  
 4,646,756 A 3/1987 Watmough  
 4,663,358 A 5/1987 Hyon  
 4,668,516 A 5/1987 Duraffourd et al.  
 4,672,591 A 6/1987 Breimesser et al.  
 4,680,499 A 7/1987 Umemura et al.  
 4,697,588 A 10/1987 Reichenberger  
 4,754,760 A 7/1988 Fukukita et al.  
 4,757,820 A 7/1988 Itoh  
 4,771,205 A 9/1988 Mequio  
 4,801,459 A 1/1989 Liburdy  
 4,803,625 A 2/1989 Fu et al.  
 4,807,633 A 2/1989 Fry  
 4,817,615 A 4/1989 Fukukita et al.  
 4,858,613 A 8/1989 Fry  
 4,860,732 A 8/1989 Hasegawa et al.  
 4,865,041 A 9/1989 Hassler  
 4,865,042 A 9/1989 Umemura  
 4,867,169 A 9/1989 Machida  
 4,874,562 A 10/1989 Hyon  
 4,875,487 A 10/1989 Seppi  
 4,881,212 A 11/1989 Takeuchi  
 4,891,043 A 1/1990 Zeimer et al.  
 4,893,624 A 1/1990 Lele  
 4,896,673 A 1/1990 Rose  
 4,900,540 A 2/1990 Ryan et al.  
 4,901,729 A 2/1990 Saitoh  
 4,917,096 A 4/1990 Englehart  
 4,932,414 A 6/1990 Coleman et al.  
 4,938,216 A 7/1990 Lele  
 4,938,217 A 7/1990 Lele  
 4,947,046 A 8/1990 Kawabata et al.  
 4,951,653 A 8/1990 Fry  
 4,955,365 A 9/1990 Fry  
 4,958,626 A 9/1990 Nambu  
 4,976,709 A 12/1990 Sand  
 4,979,501 A 12/1990 Valchanov  
 4,992,989 A 2/1991 Watanabe et al.  
 5,012,797 A 5/1991 Liang  
 5,018,508 A 5/1991 Fry et al.  
 5,030,874 A 7/1991 Saito et al.  
 5,036,855 A 8/1991 Fry  
 5,040,537 A 8/1991 Katakura  
 5,054,310 A 10/1991 Flynn  
 5,054,470 A 10/1991 Fry  
 5,054,491 A 10/1991 Saito et al.  
 5,070,879 A 12/1991 Herres  
 5,088,495 A 2/1992 Miyagawa  
 5,115,814 A 5/1992 Griffith  
 5,117,832 A 6/1992 Sanghvi  
 5,123,418 A 6/1992 Saurel  
 5,142,511 A 8/1992 Kanai et al.  
 5,143,063 A 9/1992 Fellner  
 5,143,074 A 9/1992 Dory  
 5,149,319 A 9/1992 Unger  
 5,150,711 A 9/1992 Dory  
 5,150,714 A 9/1992 Green  
 5,152,294 A 10/1992 Mochizuki et al.  
 5,156,144 A 10/1992 Iwasaki  
 5,158,536 A 10/1992 Sekins  
 5,159,931 A 11/1992 Pini  
 5,163,421 A 11/1992 Bernstein  
 5,163,436 A 11/1992 Saitoh et al.  
 5,178,135 A 1/1993 Uchiyama et al.  
 5,190,518 A 3/1993 Takasu  
 5,190,766 A 3/1993 Ishihara  
 5,191,880 A 3/1993 McLeod  
 5,205,287 A 4/1993 Erbel et al.  
 5,209,720 A 5/1993 Unger  
 5,212,671 A 5/1993 Fujii et al.  
 5,215,680 A 6/1993 D'Arrigo  
 5,224,467 A 7/1993 Oku  
 5,230,334 A 7/1993 Klopotek  
 5,230,338 A 7/1993 Allen et al.  
 5,247,924 A 9/1993 Suzuki et al.  
 5,255,681 A 10/1993 Ishimura et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,257,970 A	11/1993	Dougherty	5,603,323 A	2/1997	Pflugrath et al.
5,265,614 A	11/1993	Hayakawa	5,605,154 A	2/1997	Ries et al.
5,267,985 A	12/1993	Shimada	5,609,562 A	3/1997	Kaali
5,269,297 A	12/1993	Weng	5,615,091 A	3/1997	Palatnik
5,282,797 A	2/1994	Chess	5,618,275 A	4/1997	Bock
5,295,484 A	3/1994	Marcus	5,620,479 A	4/1997	Diederich
5,295,486 A	3/1994	Wollschlager et al.	5,622,175 A	4/1997	Sudol et al.
5,304,169 A	4/1994	Sand	5,617,858 A	5/1997	Taverna et al.
5,305,756 A	4/1994	Entrekin et al.	5,638,819 A	6/1997	Manwaring et al.
5,321,520 A	6/1994	Inga et al.	5,644,085 A	7/1997	Lorraine et al.
5,323,779 A	6/1994	Hardy et al.	5,647,373 A	7/1997	Paltieli
5,327,895 A	7/1994	Hashimoto et al.	5,655,535 A	8/1997	Frlemel et al.
5,329,202 A	7/1994	Garlick et al.	5,655,538 A	8/1997	Lorraine
5,348,016 A	9/1994	Unger et al.	5,657,760 A	8/1997	Ying
5,358,466 A	10/1994	Aida et al.	5,658,328 A	8/1997	Johnson
5,360,268 A	11/1994	Hayashi	5,660,836 A	8/1997	Knowlton
5,370,121 A	12/1994	Reichenberger	5,662,116 A	9/1997	Kondo
5,370,122 A	12/1994	Kunig	5,665,053 A	9/1997	Jacobs
5,371,483 A	12/1994	Bhardwaj	5,665,141 A	9/1997	Vago
5,375,602 A	12/1994	Lancee et al.	5,671,746 A	9/1997	Dreschel et al.
5,379,773 A	1/1995	Hornsby	5,673,699 A	10/1997	Trahey et al.
5,380,280 A	1/1995	Peterson	5,676,692 A	10/1997	Sanghvi
5,380,519 A	1/1995	Schneider et al.	5,685,820 A	11/1997	Riek et al.
5,383,917 A	1/1995	Desai et al.	5,690,608 A	11/1997	Watanabe
5,391,140 A	2/1995	Schaetzle et al.	5,694,936 A	12/1997	Fujimoto
5,391,197 A	2/1995	Burdette et al.	5,697,897 A	12/1997	Buchholtz
5,392,259 A	2/1995	Bolorforosh	5,701,900 A	12/1997	Shehada et al.
5,396,143 A	3/1995	Seyed-Bolorforosh et al.	5,704,361 A	1/1998	Seward et al.
5,398,689 A	3/1995	Connor et al.	5,706,252 A	1/1998	Le Verrier et al.
5,406,503 A	4/1995	Williams	5,706,564 A	1/1998	Rhyne
5,413,550 A	5/1995	Castel	5,715,823 A	2/1998	Wood et al.
5,417,216 A	5/1995	Tanaka	5,720,287 A	2/1998	Chapelon et al.
5,423,220 A	6/1995	Finsterwald et al.	5,722,411 A	3/1998	Suzuki
5,435,311 A	7/1995	Umamura	5,727,554 A	3/1998	Kalend et al.
5,438,998 A	8/1995	Hanafy	5,735,280 A	4/1998	Sherman et al.
5,443,068 A	8/1995	Cline et al.	5,740,804 A	4/1998	Cerofolini
5,445,611 A	8/1995	Eppstein et al.	5,743,863 A	4/1998	Chapelon
5,458,596 A	10/1995	Lax	5,746,005 A	5/1998	Steinberg
5,460,179 A	10/1995	Okunuki et al.	5,746,762 A	5/1998	Bass
5,460,595 A	10/1995	Hall et al.	5,748,767 A	5/1998	Raab
5,419,327 A	11/1995	Rohwedder	5,749,364 A	5/1998	Sliwa et al.
5,469,854 A	11/1995	Unger et al.	5,755,228 A	5/1998	Wilson et al.
5,471,488 A	12/1995	Fujio	5,755,753 A	5/1998	Knowlton
5,472,405 A	12/1995	Buchholtz et al.	5,762,066 A	6/1998	Law
5,487,388 A	1/1996	Rello et al.	5,763,886 A	6/1998	Schulte
5,492,126 A	2/1996	Hennige	5,769,790 A	6/1998	Watkins
5,496,256 A	3/1996	Bock	5,779,644 A	7/1998	Eberle et al.
5,501,655 A	3/1996	Rolt	5,792,058 A	8/1998	Lee
5,503,152 A	4/1996	Oakley et al.	5,795,297 A	8/1998	Daigle
5,503,320 A	4/1996	Webster et al.	5,795,311 A	8/1998	Wess
5,507,790 A	4/1996	Weiss	5,810,009 A	9/1998	Mine et al.
5,511,296 A	4/1996	Dias et al.	5,810,888 A	9/1998	Fenn
5,520,188 A	5/1996	Hennige	5,814,599 A	9/1998	Mitragotri et al.
5,522,869 A	6/1996	Burdette	5,817,013 A	10/1998	Ginn et al.
5,523,058 A	6/1996	Umamura et al.	5,817,021 A	10/1998	Reichenberger
5,524,620 A	6/1996	Rosenchein	5,820,564 A	10/1998	Slayton
5,524,624 A	6/1996	Tepper	5,823,962 A	10/1998	Schaetzle
5,524,625 A	6/1996	Okazaki	5,827,204 A	10/1998	Grandia et al.
5,526,624 A	6/1996	Berg	5,840,032 A	11/1998	Hatfield et al.
5,526,812 A	6/1996	Dumoulin et al.	5,844,140 A	12/1998	Seale
5,526,814 A	6/1996	Cline et al.	5,853,367 A	12/1998	Chalek et al.
5,526,815 A	6/1996	Granz	5,866,024 A	2/1999	de Villeneuve
5,529,070 A	6/1996	Augustine et al.	5,869,751 A	2/1999	Bonin
5,540,235 A	7/1996	Wilson	5,871,524 A	2/1999	Knowlton
5,558,092 A	9/1996	Unger	5,873,902 A	2/1999	Sanghvi
5,560,362 A	10/1996	Sliwa et al.	5,876,341 A	3/1999	Wang et al.
5,573,497 A	11/1996	Chapelon	5,879,303 A	3/1999	Averkiou et al.
5,575,291 A	11/1996	Hayakawa	5,882,557 A	3/1999	Hayakawa
5,575,807 A	11/1996	Faller	5,884,627 A	3/1999	Wakabayashi et al.
5,577,502 A	11/1996	Darrow et al.	5,891,034 A	4/1999	Bucholz
5,577,507 A	11/1996	Snyder et al.	5,895,356 A	4/1999	Andrus et al.
5,577,991 A	11/1996	Akui et al.	5,899,861 A	5/1999	Friemel et al.
5,580,575 A	12/1996	Unger et al.	5,904,659 A	5/1999	Duarte
5,643,179 A	1/1997	Fujimoto	5,919,219 A	7/1999	Knowlton
5,601,526 A	2/1997	Chapelon	5,923,099 A	7/1999	Bili
			5,924,989 A	7/1999	Polz
			5,928,169 A	7/1999	Schatzle et al.
			5,931,805 A	8/1999	Briskin
			5,938,606 A	8/1999	Bonnefous

(56)

References Cited

U.S. PATENT DOCUMENTS

5,938,612	A	8/1999	Kline-Schoder	6,296,619	B1	10/2001	Brisken
5,948,011	A	9/1999	Knowlton	6,301,989	B1	10/2001	Brown et al.
5,957,844	A	9/1999	Dekel	6,307,302	B1	10/2001	Toda
5,957,882	A	9/1999	Nita et al.	6,309,355	B1	10/2001	Cain et al.
5,957,941	A	9/1999	Ream	6,311,090	B1	10/2001	Knowlton
5,964,707	A	10/1999	Fenster et al.	6,315,741	B1	11/2001	Martin
5,967,980	A	10/1999	Ferre et al.	6,322,509	B1	11/2001	Pan et al.
5,968,034	A	10/1999	Fullmer	6,322,532	B1	11/2001	D'Sa
5,971,949	A	10/1999	Levin	6,325,540	B1	12/2001	Lounsberry et al.
5,977,538	A	11/1999	Unger et al.	6,325,758	B1	12/2001	Carol et al.
5,984,881	A	11/1999	Ishibashi et al.	6,325,769	B1	12/2001	Klopotek
5,984,882	A	11/1999	Rosenchein	6,325,798	B1	12/2001	Edwards et al.
5,990,598	A	11/1999	Sudol et al.	6,350,276	B1	2/2002	Knowlton
5,997,471	A	12/1999	Gumb et al.	6,356,780	B1	3/2002	Licato et al.
5,997,497	A	12/1999	Nita et al.	6,361,531	B1	3/2002	Hissong
5,999,843	A	12/1999	Anbar	6,370,411	B1	4/2002	Osadchy et al.
6,004,262	A	12/1999	Putz et al.	6,375,672	B1	4/2002	Aksan
6,007,499	A	12/1999	Martin et al.	6,377,854	B1	4/2002	Knowlton
6,013,032	A	1/2000	Savord	6,377,855	B1	4/2002	Knowlton
6,014,473	A	1/2000	Hossack et al.	6,381,497	B1	4/2002	Knowlton
6,016,255	A	1/2000	Bolan et al.	6,381,498	B1	4/2002	Knowlton
6,019,724	A	2/2000	Gronningsaeter et al.	6,387,380	B1	5/2002	Knowlton
6,022,308	A	2/2000	Williams	6,390,982	B1	5/2002	Bova et al.
6,022,317	A	2/2000	Cruanas et al.	6,405,090	B1	6/2002	Knowlton
6,022,327	A	2/2000	Chang	6,409,720	B1	6/2002	Hissong
6,030,374	A	2/2000	McDaniel	6,413,216	B1	7/2002	Cain et al.
6,036,646	A	3/2000	Barthe	6,413,253	B1	7/2002	Koop
6,039,048	A	3/2000	Silberg	6,413,254	B1 *	7/2002	Hissong ..... A61N 7/022 601/3
6,039,689	A	3/2000	Lizzi	6,419,648	B1	7/2002	Vitek
6,042,556	A	3/2000	Beach	6,423,007	B2	7/2002	Lizzi et al.
6,049,159	A	4/2000	Barthe	6,425,865	B1	7/2002	Salcudean
6,050,943	A	4/2000	Slayton	6,425,867	B1	7/2002	Vaezy
6,059,727	A	5/2000	Fowlkes	6,425,912	B1	7/2002	Knowlton
6,071,239	A	6/2000	Cribbs	6,428,477	B1	8/2002	Mason
6,080,108	A	6/2000	Dunham	6,428,532	B1	8/2002	Doukas
6,083,148	A	7/2000	Williams	6,430,446	B1	8/2002	Knowlton
6,086,535	A	7/2000	Ishibashi	6,432,057	B1	8/2002	Mazess et al.
6,086,580	A	7/2000	Mordon et al.	6,432,067	B1	8/2002	Martin
6,090,054	A	7/2000	Tagishi	6,432,101	B1	8/2002	Weber
6,093,148	A	7/2000	Fujimoto	6,436,061	B1	8/2002	Costantino
6,093,883	A	7/2000	Sanghvi	6,438,424	B1	8/2002	Knowlton
6,100,626	A	8/2000	Frey et al.	6,440,071	B1	8/2002	Slayton
6,101,407	A	8/2000	Groezinger	6,440,121	B1	8/2002	Weber
6,106,469	A	8/2000	Suzuki et al.	6,443,914	B1	9/2002	Costantino
6,113,558	A	9/2000	Rosenchein	6,447,443	B1	9/2002	Keogh et al.
6,113,559	A	9/2000	Klopotek	6,450,979	B1	9/2002	Miwa et al.
6,120,452	A	9/2000	Barthe	6,451,013	B1	9/2002	Bays et al.
6,123,081	A	9/2000	Durette	6,453,202	B1	9/2002	Knowlton
6,126,619	A	10/2000	Peterson et al.	6,461,304	B1	10/2002	Tanaka et al.
6,135,971	A	10/2000	Hutchinson	6,461,378	B1	10/2002	Knowlton
6,139,499	A	10/2000	Wilk	6,470,216	B1	10/2002	Knowlton
6,159,150	A	12/2000	Yale et al.	6,338,716	B1	11/2002	Hossack
6,171,244	B1	1/2001	Finger et al.	6,485,420	B1	11/2002	Bullis
6,176,840	B1	1/2001	Nishimura	6,488,626	B1	12/2002	Lizzi
6,183,426	B1	2/2001	Akisada	6,491,657	B2	12/2002	Rowe
6,183,502	B1	2/2001	Takeuchi	6,500,121	B1	12/2002	Slayton
6,183,773	B1	2/2001	Anderson	6,500,141	B1	12/2002	Irion
6,190,323	B1	2/2001	Dias	6,506,171	B1	1/2003	Vitek et al.
6,190,336	B1	2/2001	Duarte	6,508,774	B1	1/2003	Acker
6,193,658	B1	2/2001	Wendelken	6,511,427	B1	1/2003	Sliwa, Jr. et al.
6,198,956	B1	3/2001	Dunne	6,511,428	B1	1/2003	Azuma
6,210,327	B1	4/2001	Brackett et al.	6,514,244	B2	2/2003	Pope
6,213,948	B1	4/2001	Barthe	6,517,484	B1	2/2003	Wilk
6,216,029	B1	4/2001	Paltieli	6,524,250	B1	2/2003	Weber
6,233,476	B1	5/2001	Strommer et al.	6,666,835	B2	3/2003	Martin
6,234,990	B1	5/2001	Rowe et al.	6,540,679	B2	4/2003	Slayton
6,241,753	B1	6/2001	Knowlton	6,540,685	B1	4/2003	Rhoads et al.
6,246,898	B1	6/2001	Vesely et al.	6,540,700	B1	4/2003	Fujimoto et al.
6,251,074	B1	6/2001	Averkou et al.	6,547,788	B1	4/2003	Maguire et al.
6,251,088	B1	6/2001	Kaufman et al.	6,554,771	B1	4/2003	Buil et al.
6,268,405	B1	7/2001	Yao	6,569,099	B1	5/2003	Babaev
6,273,864	B1	8/2001	Duarte	6,569,108	B2	5/2003	Sarvazyan et al.
6,280,402	B1	8/2001	Ishibashi et al.	6,572,552	B2	6/2003	Fukukita
6,287,257	B1	9/2001	Matichuk	6,575,956	B1	6/2003	Brisken et al.
6,287,304	B1	9/2001	Eggers et al.	6,595,934	B1	7/2003	Hissong
				6,599,256	B1	7/2003	Acker
				6,605,043	B1	8/2003	Dreschel
				6,605,080	B1	8/2003	Altshuler et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,607,498 B2	8/2003	Eshel	7,294,125 B2	11/2007	Phalen et al.
6,618,620 B1	9/2003	Freundlich et al.	7,297,117 B2	11/2007	Trucco
6,623,430 B1	9/2003	Slayton	7,303,555 B2	12/2007	Makin et al.
6,626,854 B2	9/2003	Friedman	7,311,679 B2	12/2007	Desilets et al.
6,626,855 B1	9/2003	Weng	7,327,071 B2	2/2008	Nishiyama et al.
6,638,226 B2	10/2003	He et al.	7,331,951 B2	2/2008	Eshel et al.
6,645,145 B1	11/2003	Dreschel et al.	7,332,985 B2	2/2008	Larson et al.
6,645,150 B2	11/2003	Angelsen et al.	7,338,434 B1	3/2008	Haarstad et al.
6,645,162 B2	11/2003	Friedman	7,347,855 B2	3/2008	Eshel
6,662,054 B2	12/2003	Kreindel	RE40,403 E	6/2008	Cho et al.
6,663,627 B2	12/2003	Francischelli	7,393,325 B2	7/2008	Barthe
6,665,806 B1	12/2003	Shimizu	7,398,116 B2	7/2008	Edwards
6,669,638 B1	12/2003	Miller	7,399,279 B2	7/2008	Abend et al.
6,673,017 B1	1/2004	Jackson	7,491,171 B2	2/2009	Barthe et al.
6,685,639 B1	2/2004	Wang et al.	7,507,235 B2	3/2009	Keogh et al.
6,685,640 B1	2/2004	Fry	7,510,536 B2	3/2009	Foley et al.
6,692,450 B1	2/2004	Coleman	7,517,315 B2	4/2009	Willis
6,699,237 B2	3/2004	Weber	7,530,356 B2	5/2009	Slayton
6,716,184 B2	4/2004	Vaezy et al.	7,530,958 B2	5/2009	Slayton
6,719,449 B1	4/2004	Laughlin	7,532,201 B2	5/2009	Quistgaard et al.
6,719,694 B2	4/2004	Weng	7,571,336 B2	8/2009	Barthe
6,726,627 B1	4/2004	Lizzi et al.	7,601,120 B2	10/2009	Moilanen et al.
6,733,449 B1	5/2004	Krishnamurthy et al.	7,615,015 B2	11/2009	Coleman
6,749,624 B2	6/2004	Knowlton	7,615,016 B2	11/2009	Barthe
6,772,490 B2	8/2004	Toda	7,652,411 B2	1/2010	Crunkilton et al.
6,773,409 B2	8/2004	Truckai et al.	7,662,114 B2	2/2010	Seip et al.
6,775,404 B1	8/2004	Pagoulatos et al.	7,674,257 B2	3/2010	Pless et al.
6,790,187 B2	9/2004	Thompson et al.	7,686,763 B2	3/2010	Vaezy et al.
6,824,516 B2	11/2004	Batten et al.	7,713,203 B2	3/2010	Lacoste et al.
6,825,176 B2	11/2004	White et al.	7,694,406 B2	4/2010	Wildes et al.
6,835,940 B2	12/2004	Morikawa et al.	7,695,437 B2	4/2010	Quistgaard et al.
6,846,290 B2	1/2005	Lizzi et al.	7,727,156 B2	6/2010	Angelsen et al.
6,875,176 B2	4/2005	Mourad et al.	7,758,524 B2	7/2010	Barthe
6,882,884 B1	4/2005	Mosk et al.	7,766,848 B2	8/2010	Desilets et al.
6,887,239 B2	5/2005	Elstrom	7,789,841 B2	9/2010	Huckle et al.
6,887,260 B1	5/2005	McDaniel	7,806,839 B2	10/2010	Mast et al.
6,889,089 B2	5/2005	Behl	7,815,570 B2	10/2010	Eshel et al.
6,896,657 B2	5/2005	Willis	7,819,826 B2	10/2010	Diederich et al.
6,902,536 B2	6/2005	Manna	7,828,734 B2	10/2010	Azhari et al.
6,905,466 B2	6/2005	Salgo	7,824,348 B2	11/2010	Barthe
6,918,907 B2	7/2005	Kelly	7,833,162 B2	11/2010	Hasegawa et al.
6,920,883 B2	7/2005	Bessette	7,841,984 B2	11/2010	Cribbs et al.
6,921,371 B2	7/2005	Wilson	7,846,096 B2	12/2010	Mast et al.
6,932,771 B2	8/2005	Whitmore	7,857,773 B2	12/2010	Desilets et al.
6,932,814 B2	8/2005	Wood	7,875,023 B2	1/2011	Eshel et al.
6,936,044 B2	8/2005	McDaniel	7,901,359 B2	3/2011	Mandrusov et al.
6,936,046 B2	8/2005	Hissong	7,905,007 B2	3/2011	Calisti et al.
6,945,937 B2	9/2005	Culp et al.	7,905,844 B2	3/2011	Desilets et al.
6,948,843 B2	9/2005	Laugharn et al.	7,914,453 B2	3/2011	Slayton et al.
6,953,941 B2	10/2005	Nakano et al.	7,914,469 B2	3/2011	Torbati
6,958,043 B2	10/2005	Hissong	7,955,281 B2	6/2011	Pedersen et al.
6,971,994 B1	12/2005	Young et al.	7,967,764 B2	6/2011	Lidgren et al.
6,974,417 B2	12/2005	Lockwood	7,967,839 B2	6/2011	Flock et al.
6,976,492 B2	12/2005	Ingle	7,955,262 B2	7/2011	Rosenberg
6,992,305 B2	1/2006	Maezawa et al.	7,993,289 B2	8/2011	Quistgaard et al.
6,997,923 B2	2/2006	Anderson	8,057,465 B2	9/2011	Sliwa, Jr. et al.
7,006,874 B2	2/2006	Knowlton	8,057,389 B2	11/2011	Barthe et al.
7,020,528 B2	3/2006	Neev	8,066,641 B2	11/2011	Barthe et al.
7,022,089 B2	4/2006	Ooba	8,123,707 B2	2/2012	Huckle et al.
7,058,440 B2	6/2006	Heuscher et al.	8,128,618 B2	3/2012	Gliklich et al.
7,063,666 B2	6/2006	Weng	8,133,180 B2	3/2012	Slayton et al.
7,070,565 B2	7/2006	Vaezy et al.	8,133,191 B2	3/2012	Rosenberg et al.
7,074,218 B2	7/2006	Washington et al.	8,142,200 B2	3/2012	Crunkilton et al.
7,094,252 B2	8/2006	Koop	8,152,904 B2	4/2012	Slobodzian et al.
7,108,663 B2	9/2006	Talish et al.	8,162,858 B2	4/2012	Manna et al.
7,115,123 B2	10/2006	Knowlton	8,166,332 B2	4/2012	Barthe et al.
7,122,029 B2	10/2006	Koop et al.	8,182,428 B2	5/2012	Angelsen et al.
7,142,905 B2	11/2006	Slayton	8,197,409 B2	6/2012	Foley et al.
7,165,451 B1	1/2007	Brooks et al.	8,206,299 B2	6/2012	Foley et al.
7,179,238 B2	2/2007	Hissong	8,208,346 B2	6/2012	Crunkilton
7,189,230 B2	3/2007	Knowlton	8,211,017 B2	7/2012	Foley et al.
7,229,411 B2	6/2007	Slayton	8,262,591 B2	9/2012	Pedersen et al.
7,235,592 B2	6/2007	Muratoglu	8,262,650 B2	9/2012	Zanelli et al.
7,258,674 B2	8/2007	Cribbs	8,264,126 B2	9/2012	Toda et al.
7,273,459 B2	9/2007	Desilets	8,273,037 B2	9/2012	Kreindel et al.
			8,282,554 B2	10/2012	Makin et al.
			8,292,835 B1	10/2012	Cimino
			8,298,163 B1	10/2012	Cimino
			8,333,700 B1	12/2012	Barthe et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,334,637 B2	12/2012	Crunkilton et al.	9,492,686 B2	11/2016	Da Silva
8,337,407 B2	12/2012	Quistgaard et al.	9,498,651 B2	11/2016	Sapozhnikov et al.
8,343,051 B2	1/2013	Desilets et al.	9,510,802 B2	12/2016	Barthe et al.
8,454,540 B2	1/2013	Eshel et al.	9,522,290 B2	12/2016	Slayton et al.
8,366,622 B2	2/2013	Slayton et al.	9,532,832 B2	1/2017	Ron Edoute et al.
8,398,549 B2	3/2013	Palmeri et al.	9,533,174 B2	1/2017	Barthe et al.
8,409,097 B2	4/2013	Slayton et al.	9,533,175 B2	1/2017	Slayton et al.
8,425,435 B2	4/2013	Wing et al.	9,545,529 B2	1/2017	Britva et al.
8,388,535 B2	5/2013	Weng et al.	9,566,454 B2	2/2017	Barthe et al.
8,444,562 B2	5/2013	Barthe et al.	9,623,267 B2	4/2017	Ulric et al.
8,460,193 B2	6/2013	Barthe et al.	9,694,211 B2	7/2017	Barthe et al.
8,480,585 B2	7/2013	Slayton et al.	9,694,212 B2	7/2017	Barthe et al.
8,486,001 B2	7/2013	Weyant	9,700,340 B2	7/2017	Barthe et al.
8,506,486 B2	8/2013	Slayton et al.	9,707,412 B2	7/2017	Slayton et al.
8,512,250 B2	8/2013	Quistgaard et al.	9,710,607 B2	7/2017	Ramdas et al.
8,523,775 B2	9/2013	Barthe et al.	9,713,731 B2	7/2017	Slayton et al.
8,523,849 B2	9/2013	Liu et al.	9,802,063 B2	10/2017	Barthe et al.
8,535,228 B2	9/2013	Slayton et al.	9,827,449 B2	11/2017	Barthe et al.
8,570,837 B2	10/2013	Toda et al.	9,827,450 B2	11/2017	Slayton et al.
8,573,392 B2	11/2013	Bennett et al.	9,833,639 B2	12/2017	Slayton et al.
8,583,211 B2	11/2013	Salomir et al.	9,833,640 B2	12/2017	Barthe et al.
8,585,618 B2	11/2013	Hunziker et al.	9,895,560 B2	2/2018	Barthe et al.
8,604,672 B2	12/2013	Toda et al.	9,907,535 B2	3/2018	Barthe et al.
8,622,937 B2	1/2014	Weng et al.	9,919,167 B2	3/2018	Domankevitz
8,636,665 B2	1/2014	Slayton et al.	9,974,982 B2	5/2018	Slayton et al.
8,641,622 B2	2/2014	Barthe et al.	9,993,664 B2	6/2018	Aviad et al.
8,663,112 B2	3/2014	Slayton et al.	10,010,721 B2	7/2018	Slayton et al.
8,672,848 B2	3/2014	Slayton et al.	10,010,724 B2	7/2018	Barthe et al.
8,690,778 B2	4/2014	Slayton et al.	10,010,725 B2	7/2018	Slayton et al.
8,690,779 B2	4/2014	Slayton et al.	10,010,726 B2	7/2018	Barthe et al.
8,690,780 B2	4/2014	Slayton et al.	10,016,626 B2	7/2018	Zovrin et al.
8,708,935 B2	4/2014	Barthe et al.	10,046,181 B2	8/2018	Barthe et al.
8,715,186 B2	5/2014	Slayton et al.	10,046,182 B2	8/2018	Barthe et al.
8,726,781 B2	5/2014	Eckhoff et al.	10,070,883 B2	9/2018	Barthe et al.
8,728,071 B2	5/2014	Lischinsky et al.	10,183,183 B2	1/2019	Burdette
8,753,295 B2	6/2014	Thierman	10,226,645 B2	3/2019	Barthe
8,758,253 B2	6/2014	Sano et al.	10,238,894 B2	3/2019	Slayton et al.
8,836,203 B2	9/2014	Nobles et al.	10,245,450 B2	4/2019	Slayton et al.
8,857,438 B2	10/2014	Barthe et al.	10,252,086 B2	4/2019	Barthe et al.
8,858,471 B2	10/2014	Barthe et al.	10,265,550 B2	4/2019	Barthe et al.
8,915,853 B2	12/2014	Barthe et al.	10,272,272 B2	4/2019	Lee et al.
8,915,854 B2	12/2014	Slayton et al.	10,300,308 B2	5/2019	Seip et al.
8,915,870 B2	12/2014	Barthe et al.	10,328,289 B2	6/2019	Barthe et al.
8,920,320 B2	12/2014	Stecco et al.	10,363,440 B2	6/2019	Cho et al.
8,920,324 B2	12/2014	Slayton et al.	10,406,383 B2	9/2019	Luebcke
8,926,533 B2	1/2015	Bockenstedt et al.	10,420,960 B2	9/2019	Emery
8,932,224 B2	1/2015	Barthe et al.	10,420,961 B2	9/2019	Lacoste
8,932,238 B2	1/2015	Wing et al.	10,485,573 B2	11/2019	Clark, III et al.
8,968,205 B2	3/2015	Zeng et al.	10,492,862 B2	12/2019	Domankevitz
9,011,336 B2	4/2015	Slayton et al.	10,525,288 B2	1/2020	Slayton et al.
9,039,617 B2	5/2015	Slayton et al.	10,532,230 B2	1/2020	Barthe et al.
9,039,619 B2	5/2015	Barthe et al.	10,537,304 B2	1/2020	Barthe et al.
9,050,116 B2	6/2015	Homer	10,556,123 B2	2/2020	Altshuler et al.
9,095,697 B2	8/2015	Barthe et al.	10,583,287 B2	3/2020	Schwarz
9,107,798 B2	8/2015	Azhari et al.	10,603,519 B2	3/2020	Slayton et al.
9,114,247 B2	8/2015	Barthe et al.	10,603,521 B2	3/2020	Emery et al.
9,180,314 B2	11/2015	Desilets et al.	10,603,523 B2	3/2020	Slayton et al.
9,216,276 B2	12/2015	Slayton et al.	10,610,705 B2	4/2020	Barthe et al.
9,220,915 B2	12/2015	Liu et al.	10,610,706 B2	4/2020	Barthe et al.
9,272,162 B2	3/2016	Slayton et al.	10,639,006 B2	5/2020	Choi et al.
9,283,409 B2	3/2016	Slayton et al.	10,639,504 B2	5/2020	Kim
9,283,410 B2	3/2016	Slayton et al.	10,751,246 B2	8/2020	Kaila
9,295,607 B2	3/2016	Rosenberg	10,772,646 B2	9/2020	Lu et al.
9,308,390 B2	4/2016	Youngquist	10,780,298 B2	9/2020	Cain et al.
9,308,391 B2	4/2016	Liu et al.	10,888,716 B2	1/2021	Slayton et al.
9,314,650 B2	4/2016	Rosenberg et al.	10,888,717 B2	1/2021	Slayton et al.
9,320,537 B2	4/2016	Slayton et al.	10,888,718 B2	1/2021	Barthe et al.
9,345,910 B2	5/2016	Slayton et al.	10,960,235 B2	3/2021	Barthe et al.
9,421,029 B2	8/2016	Barthe et al.	10,960,236 B2	3/2021	Slayton et al.
9,427,600 B2	8/2016	Barthe et al.	11,123,039 B2	9/2021	Barthe et al.
9,427,601 B2	8/2016	Barthe et al.	11,167,155 B2	11/2021	Barthe et al.
9,433,803 B2	9/2016	Lin et al.	11,179,580 B2	11/2021	Slayton et al.
9,440,093 B2	9/2016	Homer	11,207,547 B2	12/2021	Slayton et al.
9,440,096 B2	9/2016	Barthe et al.	11,207,548 B2	12/2021	Barthe et al.
9,492,645 B2	11/2016	Zhou et al.	11,224,895 B2	1/2022	Brown et al.
			11,235,179 B2	2/2022	Barthe et al.
			11,235,180 B2	2/2022	Slayton et al.
			11,241,218 B2	2/2022	Emery et al.
			2001/0009997 A1	7/2001	Pope

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2001/0009999 A1	7/2001	Kaufman et al.	2003/0233085 A1	12/2003	Giammarusti
2001/0014780 A1	8/2001	Martin	2003/0236487 A1	12/2003	Knowlton
2001/0014819 A1	8/2001	Ingle	2004/0000316 A1	1/2004	Knowlton
2001/0031922 A1	10/2001	Weng	2004/0001809 A1	1/2004	Brisken
2001/0039380 A1	11/2001	Larson et al.	2004/0002658 A1	1/2004	Marian, Jr.
2001/0041880 A1	11/2001	Brisken	2004/0002705 A1	1/2004	Knowlton
2002/0000763 A1	1/2002	Jones	2004/0010222 A1	1/2004	Nunomura et al.
2002/0002345 A1	1/2002	Marlinghaus	2004/0015079 A1	1/2004	Berger et al.
2002/0040199 A1	4/2002	Klopotek	2004/0015106 A1	1/2004	Coleman
2002/0040442 A1	4/2002	Ishidera	2004/0030227 A1	2/2004	Littrup
2002/0055702 A1	5/2002	Atala	2004/0030268 A1	2/2004	Weng et al.
2002/0062077 A1	5/2002	Emmenegger	2004/0039312 A1	2/2004	Hillstead
2002/0062142 A1	5/2002	Knowlton	2004/0039418 A1	2/2004	Elstrom
2002/0072691 A1	6/2002	Thompson et al.	2004/0041563 A1	3/2004	Lewin et al.
2002/0082528 A1	6/2002	Friedman	2004/0041880 A1	3/2004	Ikeda et al.
2002/0082529 A1	6/2002	Suorsa et al.	2004/0042168 A1	3/2004	Yang et al.
2002/0082589 A1	6/2002	Friedman	2004/0044375 A1	3/2004	Diederich et al.
2002/0087080 A1	7/2002	Slayton	2004/0049134 A1	3/2004	Tosaya et al.
2002/0095143 A1	7/2002	Key	2004/0049734 A1	3/2004	Tosaya et al.
2002/0099094 A1	7/2002	Anderson	2004/0059266 A1	3/2004	Fry
2002/0111569 A1	8/2002	Rosenschien et al.	2004/0068186 A1	4/2004	Ishida et al.
2002/0115917 A1	8/2002	Honda et al.	2004/0073079 A1	4/2004	Altshuler et al.
2002/0128639 A1	8/2002	Pless et al.	2004/0073113 A1	4/2004	Salgo
2002/0128648 A1	9/2002	Weber	2004/0073115 A1	4/2004	Horzewski et al.
2002/0143252 A1	10/2002	Dunne et al.	2004/0073116 A1	4/2004	Smith
2002/0156400 A1	10/2002	Babaev	2004/0073204 A1	4/2004	Ryan et al.
2002/0161357 A1	10/2002	Anderson	2004/0077977 A1	4/2004	Ella et al.
2002/0165529 A1	11/2002	Danek	2004/0082857 A1	4/2004	Schonenberger
2002/0168049 A1	11/2002	Schriever	2004/0082859 A1	4/2004	Schaer
2002/0169394 A1	11/2002	Eppstein et al.	2004/0102697 A1	5/2004	Evron
2002/0169442 A1	11/2002	Neev	2004/0105559 A1	6/2004	Aylward et al.
2002/0173721 A1	11/2002	Grunwald et al.	2004/0106867 A1	6/2004	Eshel et al.
2002/0193784 A1	12/2002	McHale et al.	2004/0122323 A1	6/2004	Vortman et al.
2002/0193831 A1	12/2002	Smith	2004/0122493 A1	6/2004	Ishibashi et al.
2003/0009153 A1	1/2003	Brisken et al.	2004/0143297 A1	7/2004	Ramsey
2003/0014039 A1	1/2003	Barzell et al.	2004/0152982 A1	8/2004	Hwang et al.
2003/0018255 A1	1/2003	Martin	2004/0158150 A1	8/2004	Rabiner et al.
2003/0018270 A1	1/2003	Makin et al.	2004/0186535 A1	9/2004	Knowlton
2003/0023283 A1	1/2003	McDaniel	2004/0189155 A1	9/2004	Funakubo
2003/0028111 A1	2/2003	Vaezy et al.	2004/0206365 A1	10/2004	Knowlton
2003/0028113 A1	2/2003	Gilbert et al.	2004/0210214 A1	10/2004	Knowlton
2003/0032900 A1	2/2003	Ella	2004/0217675 A1	11/2004	Desilets
2003/0036706 A1	2/2003	Slayton et al.	2004/0249318 A1	12/2004	Tanaka
2003/0040739 A1	2/2003	Koop	2004/0254620 A1	12/2004	Lacoste
2003/0050678 A1	3/2003	Sierra	2004/0267252 A1	12/2004	Washington et al.
2003/0055308 A1	3/2003	Friemel et al.	2005/0007879 A1	1/2005	Nishida
2003/0055417 A1	3/2003	Truckai et al.	2005/0033201 A1	2/2005	Takahashi
2003/0060736 A1	3/2003	Martin et al.	2005/0033316 A1	2/2005	Kertz
2003/0065313 A1	4/2003	Koop	2005/0038340 A1	2/2005	Vaezy et al.
2003/0066708 A1	4/2003	Allison et al.	2005/0055018 A1	3/2005	Kreindel
2003/0073907 A1	4/2003	Taylor	2005/0055073 A1	3/2005	Weber
2003/0074023 A1	4/2003	Kaplan	2005/0061834 A1	3/2005	Garcia et al.
2003/0083536 A1	5/2003	Eshel	2005/0070961 A1	3/2005	Maki
2003/0092988 A1	5/2003	Makin	2005/0074407 A1	4/2005	Smith
2003/0097071 A1	5/2003	Halmann et al.	2005/0080469 A1	4/2005	Larson
2003/0099383 A1	5/2003	Lefebvre	2005/0085731 A1	4/2005	Miller et al.
2003/0125629 A1	7/2003	Ustuner	2005/0091770 A1	5/2005	Mourad et al.
2003/0135135 A1	7/2003	Miwa et al.	2005/0096542 A1	5/2005	Weng et al.
2003/0139790 A1	7/2003	Ingle et al.	2005/0104690 A1	5/2005	Larson et al.
2003/0149366 A1	8/2003	Stringer et al.	2005/0113689 A1	5/2005	Gritzky
2003/0153961 A1	8/2003	Babaev	2005/0131302 A1	6/2005	Poland
2003/0171678 A1	9/2003	Batten et al.	2005/0137656 A1	6/2005	Malak
2003/0171701 A1	9/2003	Babaev	2005/0143677 A1	6/2005	Young et al.
2003/0176790 A1	9/2003	Slayton	2005/0154313 A1	7/2005	Desilets
2003/0191396 A1	10/2003	Sanghvi	2005/0154314 A1	7/2005	Quistgaard
2003/0199794 A1	10/2003	Sakurai et al.	2005/0154332 A1	7/2005	Zanelli
2003/0200481 A1	10/2003	Stanley	2005/0154431 A1	7/2005	Quistgaard
2003/0212129 A1	11/2003	Liu et al.	2005/0187495 A1	8/2005	Quistgaard
2003/0212351 A1	11/2003	Hissong	2005/0191252 A1	9/2005	Mitsui
2003/0212393 A1	11/2003	Knowlton	2005/0193451 A1	9/2005	Quistgaard
2003/0216648 A1	11/2003	Lizzi et al.	2005/0193820 A1	9/2005	Sheljaskow et al.
2003/0216795 A1	11/2003	Harth	2005/0197681 A1	9/2005	Barolet et al.
2003/0220536 A1	11/2003	Hissong	2005/0228281 A1	10/2005	Nefos
2003/0220585 A1	11/2003	Hissong	2005/0240127 A1	10/2005	Seip et al.
2003/0229331 A1	12/2003	Brisken et al.	2005/0240170 A1	10/2005	Zhang et al.
			2005/0251120 A1	11/2005	Anderson et al.
			2005/0251125 A1	11/2005	Pless et al.
			2005/0256406 A1	11/2005	Barthe
			2005/0261584 A1	11/2005	Eshel

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0261585	A1	11/2005	Makin et al.	2008/0097253	A1	4/2008	Pedersen et al.
2005/0267454	A1	12/2005	Hissong	2008/0114251	A1	5/2008	Weymer
2005/0288748	A1	12/2005	Li et al.	2008/0139943	A1	6/2008	Deng et al.
2006/0004306	A1	1/2006	Altshuler	2008/0139974	A1	6/2008	Da Silva
2006/0020260	A1	1/2006	Dover et al.	2008/0146970	A1	6/2008	Litman et al.
2006/0025756	A1	2/2006	Francischelli	2008/0167556	A1	7/2008	Thompson
2006/0042201	A1	3/2006	Curry	2008/0183077	A1	7/2008	Moreau-Gobard et al.
2006/0058664	A1	3/2006	Barthe	2008/0183110	A1	7/2008	Davenport et al.
2006/0058671	A1	3/2006	Vitek et al.	2008/0188745	A1	8/2008	Chen et al.
2006/0058707	A1	3/2006	Barthe	2008/0194964	A1	8/2008	Randall et al.
2006/0058712	A1	3/2006	Altshuler et al.	2008/0195000	A1	8/2008	Spooner et al.
2006/0074309	A1	4/2006	Bonnefous	2008/0200810	A1	8/2008	Buchalter
2006/0074313	A1	4/2006	Slayton et al.	2008/0200813	A1	8/2008	Quistgaard
2006/0074314	A1	4/2006	Slayton	2008/0214966	A1	9/2008	Slayton
2006/0074355	A1	4/2006	Slayton	2008/0214988	A1	9/2008	Altshuler et al.
2006/0079816	A1	4/2006	Barthe	2008/0221491	A1	9/2008	Slayton
2006/0079868	A1	4/2006	Makin	2008/0223379	A1	9/2008	Stuker
2006/0084891	A1	4/2006	Barthe	2008/0242991	A1	10/2008	Moon et al.
2006/0089632	A1	4/2006	Barthe	2008/0243035	A1	10/2008	Crunkilton
2006/0089688	A1	4/2006	Panescu	2008/0269608	A1	10/2008	Anderson et al.
2006/0094988	A1	5/2006	Tosaya	2008/0275342	A1	11/2008	Barthe
2006/0106325	A1	5/2006	Perrier	2008/0281206	A1	11/2008	Bartlett et al.
2006/0111744	A1	5/2006	Makin	2008/0281236	A1	11/2008	Eshel et al.
2006/0116583	A1	6/2006	Ogasawara et al.	2008/0281237	A1	11/2008	Slayton
2006/0116671	A1	6/2006	Slayton	2008/0281255	A1	11/2008	Slayton
2006/0122508	A1	6/2006	Slayton	2008/0294072	A1	11/2008	Crutchfield, III
2006/0122509	A1	6/2006	Desilets	2008/0294073	A1	11/2008	Barthe
2006/0161062	A1	7/2006	Arditi et al.	2008/0319356	A1	12/2008	Cain
2006/0184069	A1	8/2006	Vaitekunas	2009/0005680	A1	1/2009	Jones et al.
2006/0184071	A1	8/2006	Klopotek	2009/0012394	A1	1/2009	Hobelsberger et al.
2006/0189972	A1	8/2006	Grossman	2009/0043198	A1	2/2009	Milner et al.
2006/0206105	A1	9/2006	Chopra	2009/0043293	A1	2/2009	Pankratov et al.
2006/0224090	A1	10/2006	Ostrovsky et al.	2009/0048514	A1	2/2009	Azhari et al.
2006/0229514	A1	10/2006	Wiener	2009/0069677	A1	3/2009	Chen et al.
2006/0238068	A1	10/2006	May et al.	2009/0093737	A1	4/2009	Chomas et al.
2006/0241440	A1	10/2006	Eshel	2009/0156969	A1	6/2009	Santangelo
2006/0241442	A1	10/2006	Barthe	2009/0163807	A1	6/2009	Sliwa
2006/0241470	A1	10/2006	Novak et al.	2009/0171252	A1	7/2009	Bockenstedt et al.
2006/0241576	A1	10/2006	Diederich et al.	2009/0171266	A1	7/2009	Harris
2006/0250046	A1	11/2006	Koizumi et al.	2009/0177122	A1	7/2009	Peterson
2006/0282691	A1	12/2006	Barthe	2009/0177123	A1	7/2009	Peterson
2006/0291710	A1	12/2006	Wang et al.	2009/0182231	A1	7/2009	Barthe et al.
2007/0016039	A1	1/2007	Vortman et al.	2009/0198157	A1	8/2009	Babaev et al.
2007/0032784	A1	2/2007	Gilklich et al.	2009/0216159	A1	8/2009	Slayton et al.
2007/0035201	A1	2/2007	Desilets	2009/0226424	A1	9/2009	Hsu
2007/0055154	A1	3/2007	Torbati	2009/0227910	A1	9/2009	Pedersen et al.
2007/0055155	A1	3/2007	Owen et al.	2009/0230823	A1	9/2009	Kushculey et al.
2007/0055156	A1	3/2007	Desilets et al.	2009/0240146	A1*	9/2009	Bockenstedt ..... A61N 7/02 600/459
2007/0065420	A1	3/2007	Johnson	2009/0253988	A1	10/2009	Slayton et al.
2007/0078290	A1	4/2007	Esenaliev	2009/0281463	A1	11/2009	Chapelon et al.
2007/0083120	A1	4/2007	Cain et al.	2009/0312693	A1	12/2009	Thapliyal et al.
2007/0087060	A1	4/2007	Dietrich	2009/0318909	A1	12/2009	Debenedictis et al.
2007/0088245	A1	4/2007	Babaev et al.	2009/0326420	A1	12/2009	Moonen et al.
2007/0088346	A1	4/2007	Mirizzi et al.	2010/0011236	A1	1/2010	Barthe et al.
2007/0161902	A1	7/2007	Dan	2010/0022919	A1	1/2010	Peterson
2007/0166357	A1	7/2007	Shaffer et al.	2010/0022921	A1	1/2010	Seip et al.
2007/0167709	A1	7/2007	Slayton	2010/0022922	A1	1/2010	Barthe et al.
2007/0018553	A1	8/2007	Kennedy	2010/0030076	A1	2/2010	Vortman et al.
2007/0208253	A1	9/2007	Slayton	2010/0042020	A1	2/2010	Ben-Ezra
2007/0219448	A1	9/2007	Seip et al.	2010/0049178	A1	2/2010	Deem et al.
2007/0219604	A1	9/2007	Yaroslavsky et al.	2010/0056925	A1	3/2010	Zhang et al.
2007/0219605	A1	9/2007	Yaroslavsky et al.	2010/0056962	A1	3/2010	Vortman et al.
2007/0238994	A1	10/2007	Stecco et al.	2010/0100014	A1	4/2010	Eshel et al.
2007/0239075	A1	10/2007	Rosenberg	2010/0113983	A1	5/2010	Heckerman et al.
2007/0239077	A1	10/2007	Azhari et al.	2010/0130891	A1	5/2010	Taggart et al.
2007/0239079	A1	10/2007	Manstein et al.	2010/0160782	A1	6/2010	Slayton et al.
2007/0239142	A1	10/2007	Altshuler	2010/0160837	A1	6/2010	Hunziker et al.
2008/0015435	A1	1/2008	Cribbs et al.	2010/0168576	A1	7/2010	Poland et al.
2008/0027328	A1	1/2008	Klopotek	2010/0191120	A1	7/2010	Kraus et al.
2008/0033458	A1	2/2008	McLean et al.	2010/0241035	A1	9/2010	Barthe et al.
2008/0039724	A1	2/2008	Seip et al.	2010/0249602	A1	9/2010	Buckley et al.
2008/0071255	A1	3/2008	Barthe	2010/0249669	A1	9/2010	Ulric et al.
2008/0086054	A1	4/2008	Slayton	2010/0256489	A1	10/2010	Pedersen et al.
2008/0086056	A1	4/2008	Chang et al.	2010/0274161	A1	10/2010	Azhari et al.
2008/0097214	A1	4/2008	Meyers et al.	2010/0280420	A1	11/2010	Barthe et al.
				2010/0286518	A1	11/2010	Lee et al.
				2010/0312150	A1	12/2010	Douglas et al.
				2011/0040171	A1	2/2011	Foley et al.



(56)

## References Cited

## U.S. PATENT DOCUMENTS

2011/0040190	A1	2/2011	Jahnke et al.	2013/0274603	A1	10/2013	Barthe et al.
2011/0040213	A1	2/2011	Dietz et al.	2013/0278111	A1	10/2013	Sammoura
2011/0040214	A1	2/2011	Foley et al.	2013/0281853	A1	10/2013	Slayton et al.
2011/0066084	A1	3/2011	Desilets et al.	2013/0281891	A1	10/2013	Slayton et al.
2011/0072970	A1	3/2011	Slobodzian et al.	2013/0296697	A1	11/2013	Slayton et al.
2011/0077514	A1	3/2011	Ulric et al.	2013/0296700	A1	11/2013	Slayton et al.
2011/0079083	A1	4/2011	Yoo et al.	2013/0296743	A1	11/2013	Lee et al.
2011/0087099	A1	4/2011	Eshel et al.	2013/0303904	A1	11/2013	Barthe et al.
2011/0087255	A1	4/2011	McCormack et al.	2013/0303905	A1	11/2013	Barthe et al.
2011/0112405	A1	5/2011	Barthe et al.	2013/0310714	A1	11/2013	Eshel et al.
2011/0144490	A1	6/2011	Davis et al.	2013/0310863	A1	11/2013	Makin et al.
2011/0178444	A1	7/2011	Slayton et al.	2013/0345562	A1	12/2013	Barthe et al.
2011/0178541	A1	7/2011	Azhari	2014/0024974	A1	1/2014	Slayton et al.
2011/0190745	A1	8/2011	Uebelhoer et al.	2014/0050054	A1	2/2014	Toda et al.
2011/0201976	A1	8/2011	Sanghvi et al.	2014/0081300	A1	3/2014	Melodelima et al.
2011/0251524	A1	10/2011	Azhari et al.	2014/0082907	A1	3/2014	Barthe et al.
2011/0251527	A1	10/2011	Kushculey et al.	2014/0117814	A1	5/2014	Toda et al.
2011/0270137	A1	11/2011	Goren et al.	2014/0142430	A1	5/2014	Slayton et al.
2011/0319793	A1	12/2011	Henrik et al.	2014/0148834	A1	5/2014	Barthe et al.
2011/0319794	A1	12/2011	Gertner	2014/0155747	A1	6/2014	Bennett
2012/0004549	A1	1/2012	Barthe et al.	2014/0180174	A1	6/2014	Slayton et al.
2012/0016239	A1	1/2012	Barthe et al.	2014/0187944	A1	7/2014	Slayton et al.
2012/0029353	A1	2/2012	Slayton et al.	2014/0188015	A1	7/2014	Slayton et al.
2012/0035473	A1	2/2012	Sanghvi et al.	2014/0188145	A1	7/2014	Slayton et al.
2012/0035475	A1	2/2012	Barthe et al.	2014/0194723	A1	7/2014	Herzog et al.
2012/0035476	A1	2/2012	Barthe et al.	2014/0208856	A1	7/2014	Schmid
2012/0046547	A1	2/2012	Barthe et al.	2014/0221823	A1	8/2014	Keogh et al.
2012/0053458	A1	3/2012	Barthe et al.	2014/0236049	A1	8/2014	Barthe et al.
2012/0059288	A1	3/2012	Barthe et al.	2014/0236061	A1	8/2014	Lee et al.
2012/0111339	A1	5/2012	Barthe et al.	2014/0243713	A1	8/2014	Slayton et al.
2012/0123304	A1	5/2012	Rybyanets et al.	2014/0257145	A1	9/2014	Emery
2012/0136280	A1	5/2012	Rosenberg et al.	2014/0276055	A1	9/2014	Barthe et al.
2012/0136282	A1	5/2012	Rosenberg et al.	2014/0316269	A1	10/2014	Zhang et al.
2012/0143056	A1	6/2012	Slayton et al.	2015/0000674	A1	1/2015	Barthe et al.
2012/0143100	A1	6/2012	Jeong et al.	2015/0025420	A1	1/2015	Slayton et al.
2012/0165668	A1	6/2012	Slayton et al.	2015/0031995	A1	1/2015	Guracar
2012/0165848	A1	6/2012	Slayton et al.	2015/0064165	A1	3/2015	Perry et al.
2012/0191019	A1	7/2012	Desilets et al.	2015/0080723	A1	3/2015	Barthe et al.
2012/0191020	A1	7/2012	Vitek et al.	2015/0080771	A1	3/2015	Barthe et al.
2012/0197120	A1	8/2012	Makin et al.	2015/0080874	A1	3/2015	Slayton et al.
2012/0197121	A1	8/2012	Slayton et al.	2015/0088182	A1	3/2015	Slayton et al.
2012/0203108	A1	8/2012	Tsujita	2015/0141734	A1	5/2015	Chapelon et al.
2012/0209150	A1	8/2012	Zeng et al.	2015/0164734	A1	6/2015	Slayton et al.
2012/0215105	A1	8/2012	Slayton et al.	2015/0165238	A1	6/2015	Slayton et al.
2012/0271202	A1	10/2012	Wisdom	2015/0165243	A1	6/2015	Slayton et al.
2012/0271294	A1	10/2012	Barthe et al.	2015/0174388	A1	6/2015	Slayton
2012/0277587	A1	11/2012	Adanny et al.	2015/0202468	A1	7/2015	Slayton et al.
2012/0277639	A1	11/2012	Pollock et al.	2015/0217141	A1	8/2015	Barthe et al.
2012/0296240	A1	11/2012	Azhari et al.	2015/0238258	A1	8/2015	Palero et al.
2012/0302883	A1	11/2012	Kong et al.	2015/0297188	A1	10/2015	Konofagou
2012/0316426	A1	12/2012	Foley et al.	2015/0321026	A1	11/2015	Branson et al.
2012/0330197	A1	12/2012	Makin et al.	2015/0360058	A1	12/2015	Barthe et al.
2012/0330222	A1	12/2012	Makin et al.	2015/0374333	A1	12/2015	Barthe et al.
2012/0330223	A1	12/2012	Makin et al.	2015/0375014	A1	12/2015	Slayton et al.
2012/0330283	A1	12/2012	Hyde et al.	2016/0001097	A1	1/2016	Cho et al.
2012/0330284	A1	12/2012	Hyde et al.	2016/0016015	A1	1/2016	Slayton et al.
2013/0012755	A1	1/2013	Slayton	2016/0027994	A1	1/2016	Toda et al.
2013/0012816	A1	1/2013	Slayton et al.	2016/0151618	A1	6/2016	Powers et al.
2013/0012838	A1	1/2013	Jaeger et al.	2016/0158580	A1	6/2016	Slayton et al.
2013/0012842	A1	1/2013	Barthe	2016/0175619	A1	6/2016	Lee et al.
2013/0018285	A1	1/2013	Park et al.	2016/0206335	A1	7/2016	Slayton
2013/0018286	A1	1/2013	Slayton et al.	2016/0206341	A1	7/2016	Slayton
2013/0046209	A1	2/2013	Slayton et al.	2016/0256675	A1	9/2016	Slayton
2013/0051178	A1	2/2013	Rybyanets	2016/0296769	A1	10/2016	Barthe et al.
2013/0060170	A1	3/2013	Lee et al.	2016/0310444	A1	10/2016	Dobak, III
2013/0066208	A1	3/2013	Barthe et al.	2016/0361571	A1	12/2016	Bernabei
2013/0066237	A1	3/2013	Smotrich et al.	2016/0361572	A1	12/2016	Slayton
2013/0072826	A1	3/2013	Slayton et al.	2017/0028227	A1	2/2017	Emery et al.
2013/0073001	A1	3/2013	Campbell	2017/0043190	A1	2/2017	Barthe et al.
2013/0096471	A1	4/2013	Slayton et al.	2017/0050019	A1	2/2017	Ron Edoute et al.
2013/0096596	A1	4/2013	Schafer	2017/0080257	A1	3/2017	Paunescu et al.
2013/0190659	A1	7/2013	Slayton et al.	2017/0090507	A1	3/2017	Weiner et al.
2013/0211293	A1	8/2013	Auboiroux et al.	2017/0100585	A1	4/2017	Hall et al.
2013/0225994	A1	8/2013	Hsu et al.	2017/0119345	A1	5/2017	Levien et al.
2013/0268032	A1	10/2013	Neev	2017/0136263	A1	5/2017	Reil
				2017/0209201	A1	7/2017	Slayton et al.
				2017/0209202	A1	7/2017	Friedrichs et al.
				2017/0304654	A1	10/2017	Blanche et al.
				2017/0368574	A1	12/2017	Sammoura

(56)

## References Cited

U.S. PATENT DOCUMENTS						
2018/0001113	A1	1/2018	Streeter	EP	1262160	12/2002
2018/0015308	A1	1/2018	Reed et al.	EP	1283690	2/2003
2018/0043147	A1	2/2018	Slayton	EP	0659387	4/2003
2018/0099162	A1	4/2018	Bernabei	EP	1374944	1/2004
2018/0099163	A1	4/2018	Bernabei	EP	1479412	11/2004
2018/0126190	A1	5/2018	Aviad et al.	EP	1028660	1/2008
2018/0154184	A1	6/2018	Kong et al.	EP	1874241	1/2008
2018/0177912	A1	6/2018	Kaioptas et al.	EP	1362223	5/2008
2018/0207450	A1	7/2018	Sanchez et al.	EP	1750804	7/2008
2018/0272156	A1	9/2018	Slayton et al.	EP	1811901	4/2009
2018/0272157	A1	9/2018	Barthe et al.	EP	1785164	8/2009
2018/0272158	A1	9/2018	Barthe et al.	EP	2230904	9/2010
2018/0272159	A1	9/2018	Slayton et al.	EP	1501331	6/2011
2018/0317884	A1	11/2018	Chapelon et al.	EP	2066405	11/2011
2018/0333595	A1	11/2018	Barthe et al.	EP	2474050	7/2012
2018/0360420	A1	12/2018	Vortman et al.	EP	2527828	11/2012
2019/0000498	A1	1/2019	Barthe et al.	EP	2897547	7/2015
2019/0009110	A1	1/2019	Gross et al.	EP	2709726	11/2015
2019/0009111	A1	1/2019	Myhr et al.	EP	1538980	1/2017
2019/0022405	A1	1/2019	Greenbaum et al.	EP	3124047	1/2017
2019/0038921	A1	2/2019	Domankevitz	EP	2173261	B1 8/2018
2019/0060675	A1	2/2019	Krone et al.	EP	3417911	12/2018
2019/0091490	A1	3/2019	Alexander et al.	FR	2532851	9/1983
2019/0142380	A1	5/2019	Emery et al.	FR	2685872	1/1992
2019/0143148	A1	5/2019	Slayton	FR	2672486	8/1992
2019/0184202	A1	6/2019	Zereshkian et al.	FR	2703254	3/1994
2019/0184203	A1	6/2019	Slayton et al.	GB	2113099	8/1983
2019/0184205	A1	6/2019	Slayton et al.	IL	102516	1/1996
2019/0184207	A1	6/2019	Barthe et al.	IL	112369	8/1999
2019/0184208	A1	6/2019	Barthe et al.	IL	120079	3/2001
2019/0224501	A1	7/2019	Burdette	JP	63036171	2/1988
2019/0262634	A1	8/2019	Barthe et al.	JP	03048299	3/1991
2019/0282834	A1	9/2019	Zawada et al.	JP	3123559	5/1991
2019/0290939	A1	9/2019	Watson et al.	JP	03136642	6/1991
2019/0350562	A1	11/2019	Slayton et al.	JP	4089058	3/1992
2019/0366126	A1	12/2019	Pahk et al.	JP	04150847	5/1992
2019/0366127	A1	12/2019	Emery	JP	7080087	3/1995
2019/0366128	A1	12/2019	Slayton et al.	JP	07505793	6/1995
2020/0008779	A1	1/2020	Göksel et al.	JP	7184907	7/1995
2020/0094083	A1	3/2020	Slayton et al.	JP	7222782	8/1995
2020/0100762	A1	4/2020	Barthe et al.	JP	09047458	2/1997
2020/0129759	A1	4/2020	Schwarz	JP	9108288	4/1997
2020/0171330	A1	6/2020	Barthe et al.	JP	9503926	4/1997
2020/0179727	A1	6/2020	Slayton et al.	JP	3053069	10/1998
2020/0179729	A1	6/2020	Slayton et al.	JP	11123226	5/1999
2020/0188703	A1	6/2020	Barthe et al.	JP	11505440	5/1999
2020/0188704	A1	6/2020	Barthe et al.	JP	11506636	6/1999
2020/0188705	A1	6/2020	Emery et al.	JP	10248850	9/1999
2020/0206072	A1	7/2020	Capelli et al.	JP	2000126310	5/2000
2020/0222728	A1	7/2020	Khokhlova et al.	JP	2000166940	6/2000
2021/0038925	A1	2/2021	Emery	JP	2000233009	8/2000
2021/0378630	A1	12/2021	Slayton et al.	JP	2001-46387	2/2001
				JP	2001136599	A 5/2001
				JP	2001170068	6/2001
				JP	2002505596	2/2002
				JP	2002078764	3/2002
				JP	2002515786	5/2002
				JP	2002537013	5/2002
				JP	2002521118	7/2002
				JP	2002537939	11/2002
				JP	2003050298	7/2003
				JP	2003204982	7/2003
				JP	2004-504898	2/2004
				JP	2004-507280	3/2004
				JP	2004154256	3/2004
				JP	2004-509671	4/2004
				JP	2004-512856	4/2004
				JP	2004130145	4/2004
				JP	2004147719	5/2004
				JP	2005503388	2/2005
				JP	2005527336	9/2005
				JP	2005323213	11/2005
				JP	2006520247	9/2006
				JP	2008515559	5/2008
				JP	2009518126	5/2009
				JP	2010517695	5/2010
				KR	2001-0019317	3/2001
				KR	1020010024871	3/2001
				KR	2002-0038547	5/2002
FOREIGN PATENT DOCUMENTS						
CN	102112059	6/2011				
CN	102573648	7/2012				
CN	104027893	9/2014				
CN	106994041	8/2017				
CN	108023552	5/2018				
DE	4029175	3/1992				
DE	10140064	3/2003				
DE	10219297	11/2003				
DE	10219217	12/2004				
DE	20314479	12/2004				
EP	0142215	5/1984				
EP	0344773	12/1989				
EP	0473553	4/1992				
EP	670147	2/1995				
EP	0661029	7/1995				
EP	724894	2/1996				
EP	763371	11/1996				
EP	1044038	10/2000				
EP	1050322	11/2000				
EP	1234566	8/2002				

(56)

## References Cited

FOREIGN PATENT DOCUMENTS		
KR	100400870	10/2003
KR	1020060113930	11/2006
KR	1020070065332	6/2007
KR	1020070070161	7/2007
KR	1020070098856	10/2007
KR	1020000059516	4/2012
KR	10-1365946	2/2014
TW	386883	9/2000
TW	201208734 A	3/2012
WO	WO9312742	7/1993
WO	WO9524159	9/1995
WO	WO9625888	8/1996
WO	WO9634568	11/1996
WO	WO9639079	12/1996
WO	WO9735518	10/1997
WO	WO9832379	7/1998
WO	WO9852465	11/1998
WO	WO9933520	7/1999
WO	WO9939677	8/1999
WO	WO9949788	10/1999
WO	WO200006032	2/2000
WO	WO0015300	3/2000
WO	WO0021612	4/2000
WO	WO0048518	8/2000
WO	WO0053113	9/2000
WO	WO200071021	11/2000
WO	WO0128623	4/2001
WO	WO01045550	6/2001
WO	WO0182777	11/2001
WO	WO0182778	11/2001
WO	WO0187161	11/2001
WO	WO01080709	11/2001
WO	WO2001087161	11/2001
WO	WO0209812	2/2002
WO	WO0209813	2/2002
WO	WO02015768	2/2002
WO	WO0224050	3/2002
WO	WO200149194	7/2002
WO	WO2002054018	7/2002
WO	WO02092168	11/2002
WO	WO03053266	7/2003
WO	WO03065347	8/2003
WO	WO03070105	8/2003
WO	WO03077833	9/2003
WO	WO03086215	10/2003
WO	WO03096883	11/2003
WO	WO03099177	12/2003
WO	WO03099382	12/2003
WO	WO03101530	12/2003
WO	WO2004000116	12/2003
WO	WO2004080147	9/2004
WO	WO2004110558	12/2004
WO	WO2005/011804	2/2005
WO	WO2005065408	7/2005
WO	WO2005065409	7/2005
WO	WO2005090978	9/2005
WO	WO2005113068	12/2005
WO	WO2006/042163	4/2006
WO	WO2006036870	4/2006
WO	WO2006042168	4/2006
WO	WO2006042201	4/2006
WO	WO2006065671	6/2006
WO	WO2006082573	8/2006
WO	WO2006104568	10/2006
WO	WO2006110388	10/2006
WO	WO2007067563	6/2007
WO	WO2008036479	3/2008
WO	WO2008036622	3/2008
WO	WO2008144274	11/2008
WO	WO2009013729	1/2009
WO	WO2009149390	12/2009
WO	WO2010006293	1/2010
WO	WO2010102128	9/2010
WO	WO2012134645	10/2012
WO	WO2013048912	4/2013

WO	WO2013178830	12/2013
WO	WO2014043206	3/2014
WO	WO2014045216	3/2014
WO	WO2014055708	4/2014
WO	WO2014057388	4/2014
WO	WO2014127091	8/2014
WO	WO 2014/137835	9/2014
WO	WO2015160708	10/2015
WO	WO2016054155	4/2016
WO	WO2016115363	7/2016
WO	WO2017127328	7/2017
WO	WO2017149506	9/2017
WO	WO2017165595	9/2017
WO	WO2017212489	12/2017
WO	WO2017223312	12/2017
WO	WO2018035012	2/2018
WO	WO2018158355	9/2018
WO	WO2019008573	1/2019
WO	WO 2019147596	8/2019
WO	WO2019164836	8/2019
WO	WO2020009324	1/2020
WO	WO2020075906	4/2020
WO	WO2020080730	4/2020
WO	WO2020121307	6/2020
WO	WO2022240843	11/2022

## OTHER PUBLICATIONS

Adams et al., "High Intensity Focused Ultrasound Ablation of Rabbit Kidney Tumors" Sonablate High-Intensity Focused Ultrasound device; *Journal of Endourology* vol. 10, No. 1, (Feb. 1996).

Agren, Magnus S. et al., Collagenase in Wound Healing: Effect of Wound Age and Type. *The Journal of Investigative Dermatology*, vol. 99/No. 6, (Dec. 1992).

Alam, M., "The future of noninvasive procedural dermatology". *Semin Cutan Med Surg.* Mar. 2013; 32(1):59-61.

Alam, M., et al., "Ultrasound tightening of facial and neck skin: a rater-blinded prospective cohort study". *J Am Acad Dermatol*, 2010. 62(2): p. 262-9.

Alexiades-Armenakas, M., "Ultrasound Technologies for Dermatologic Techniques". *J Drugs Derm.* 2014. 12 (11): p. 1305.

Alster, T.S., et al., "Noninvasive lifting of arm, thigh, and knee skin with transcutaneous intense focused ultrasound". *Dermatol Surg*, 2012. 38(5): p. 754-9.

Alster, Tinas S., Tanzi, Elizabeth L., "Cellulite Treatment using a Novel Combination Radiofrequency, Infrared Light, and Mechanical Tissue Manipulation Device," *Journal of Cosmetic & Laser Therapy*, Jun. 2005, vol. 7, Issue 2, pp. 81-85.

Arosarena, O., "Options and Challenges for Facial Rejuvenation in Patients With Higher Fitzpatrick Skin Phototypes". *JAMA Facial Plastic Surgery*, 2015.

Arthur et al., "Non-invasive estimation of hyperthermia temperatures with ultrasound," *Int. J. Hyperthermia*, Sep. 2005, 21(6), pp. 589-600.

Barthe et al., "Ultrasound therapy system and ablation results utilizing miniature imaging/therapy arrays," *Ultrasonics Symposium*, 2004 IEEE, Aug. 23, 2004, pp. 1792-1795, vol. 3.

Bozec, Laurent et al., Thermal Denaturation Studies of Collagen by Microthermal Analysis and Atomic Force Microscopy, *Biophysical Journal*, vol. 101, pp. 228-236. (Jul. 2001).

Brobst, R.W., et al., "Noninvasive Treatment of the Neck". *Facial Plast Surg Clin North Am*, 2014. 22(2): p. 191-202.

Brobst, R.W., et al., "Ulthera: initial and six month results". *Facial Plast Surg Clin North Am*, 2012. 20(2): p. 163-76.

Brown J A et al: "Fabrication and performance of 40-60 MHz annular arrays", 2003 IEEE Ultrasonics Symposium Proceedings. Honolulu, Hawaii, Oct. 5-8, 2003; [IEEE Ultrasonics Symposium Proceedings], New York, NY : IEEE, US, vol. 1, Oct. 5, 2003 (Oct. 5, 2003), pp. 869-872.

Calderhead et al., "One Mechanism Behind LED Photo-Therapy for Wound Healing and Skin Rejuvenation: Key Role of the Mast Cell" *Laser Therapy* 17.3: 141-148 (2008).

(56)

## References Cited

## OTHER PUBLICATIONS

- Carruthers et al., "Consensus Recommendations for Combined Aesthetic Interventions in the Face Using Botulinum Toxin, Fillers, and Energy-Based Devices" *Dermatol Surg* 2016 (pp. 1-12).
- Casabona, G., et al., "Microfocused Ultrasound with Visualization and Calcium Hydroxylapatite for Improving Skin Laxity and Cellulite Appearance"; *Plast Reconstr Surg Glob Open*. Jul. 25, 2017;5(7):e1388, 8 pages.
- Casabona, G., et al., "Microfocused Ultrasound With Visualization and Fillers for Increased Neocollagenesis: Clinical and Histological Evaluation". *Dermatol Surg* 2014;40:S194-S198.
- Chan, N.P., et al., "Safety study of transcutaneous focused ultrasound for non-invasive skin tightening in Asians". *Lasers Surg Med*, 2011. 43(5): p. 366-75.
- Chapelon et al., "Effects of Cavitation In the High Intensity Therapeutic Ultrasound", *Ultrasonics Symposium—1357* (1991).
- Chapelon, et al., "Thresholds for Tissue Ablation by Focused Ultrasound" (1990).
- Chen, L. et al., "Effect of Blood Perfusion on the ablation of liver parenchyma with high intensity focused ultrasound," *Phys. Med. Biol*; 38:1661-1673; 1993b.
- Coon, Joshua et al., "Protein identification using sequential ion/ion reactions and tandem mass spectrometry" *Proceedings of the National Academy of Sciences of the USA*, vol. 102, No. 27, Jul. 27, 2005, pp. 9463-9468.
- Corry, Peter M., et al., "Human Cancer Treatment with Ultrasound", *IEEE Transactions on Sonics and Ultrasonics*, vol. SU-31, No. 5, Sep. 1984, pp. 444, 456.
- Damianou et al., "Application of the Thermal Dose Concept for Predicting the Necrosed Tissue vol. During Ultrasound Surgery," 1993 *IEEE Ultrasound Symposium*, pp. 1199-1202.
- Daum et al., Design and Evaluation of a Feedback Based Phased Array System for Ultrasound Surgery, *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, vol. 45, No. 2, Mar. 1998, pp. 431-438.
- Davis, Brian J., et al., "An Acoustic Phase Shift Technique for the Non-Invasive Measurement of Temperature Changes in Tissues", 1985 *Ultrasonics Symposium*, pp. 921-924.
- Dayan, S.H., et al., "Prospective, Multi-Center, Pivotal Trial Evaluating the Safety and Effectiveness of Micro-Focused Ultrasound with Visualization (MFU-V) for Improvement in Lines and Wrinkles of the Decolletage". *Plast Reconstr Surg*. Oct. 2014; 134(4 Suppl 1):123-4.
- Decision of the Korean Intellectual Property Tribunal dated Jun. 28, 2013 regarding Korean Patent No. 10-1142108, which is related to the pending application and/or an application identified in the Table on pp. 1-4 of the Information Disclosure Statement herein (English translation, English translation certification, and Korean decision included).
- Delon Martin, C., et al., "Venous Thrombosis Generation By Means of High-Intensity Focused Ultrasound" *Ultrasound in Med. & Biol.*, vol. 21, No. 1, pp. 113-119 (1995).
- Dierickx, Christine C., "The Role of Deep Heating for Noninvasive Skin Rejuvenation" *Lasers in Surgery and Medicine* 38:799-807 (2006).
- Dobke, M.K., et al., "Tissue restructuring by energy-based surgical tools". *Clin Plast Surg*, 2012. 39(4): p. 399-408.
- Dong, Yuan-Lin et al., "Effect of Ibuprofen on the Inflammatory Response to Surgical Wounds" *The Journal of Trauma*, vol. 35, No. 3. (1993).
- Driller et al., "Therapeutic Applications of Ultrasound: A Review" *IEEE Engineering in Medicine and Biology*; (Dec. 1987) pp. 33-40.
- Dvivedi, Sanjay, et al. "Effect of Ibuprofen and diclofenac sodium on experimental wound healing" *Indian Journal of Experimental Biology*, vol. 35, pp. 1243-1245. (Nov. 1997).
- Fabi, S.G., "Microfocused Ultrasound With Visualization for Skin Tightening and Lifting: My Experience and a Review of the Literature". *Dermatol Surg*. Dec. 2014; 40 Suppl 12:S164-7.
- Fabi, S.G., "Noninvasive skin tightening: focus on new ultrasound techniques". *Clin Cosmet Invest Dermatol*. Feb. 5, 2015; 8:47-52.
- Fabi, S.G., et al., "A prospective multicenter pilot study of the safety and efficacy of microfocused ultrasound with visualization for improving lines and wrinkles of the décolleté". *Dermatol Surg*. Mar. 2015; 41(3):327-35.
- Fabi, S.G., et al., "Evaluation of microfocused ultrasound with visualization for lifting, tightening, and wrinkle reduction of the décolletage". *J Am Acad Dermatol*, 2013. 69(6): p. 965-71.
- Fabi, S.G., et al., "Future directions in cutaneous laser surgery". *Dermatol Clin*, 2014. 32(1): p. 61-9.
- Fabi, S.G., et al., "Retrospective Evaluation of Micro-focused Ultrasound for Lifting and Tightening the Face and Neck". *Dermatol Surg*, 2014.
- Friedmann D.P., "Comments on evaluation of microfocused ultrasound system for improving skin laxity and tightening in the lower face". *Aesthet Surg J*. Mar. 2015;35(3):NP81-2.
- Friedmann, D.P., et al., "Combination of intense pulsed light, Sculptra, and Ultherapy for treatment of the aging face". *J Cosmet Dermatol*, 2014. 13(2): p. 109-18.
- Fry, W.J. et al., "Production of Focal Destructive Lesions in the Central Nervous System with Ultrasound," *J. Neurosurg.*, 11:471-478; 1954.
- Fujimoto, et al., "A New Cavitation Suppression Technique for Local Ablation Using High-Intensity Focused Ultrasound" *Ultrasonics Symposium—1629* (1995).
- Gliklich et al., Clinical Pilot Study of Intense Ultrasound therapy to Deep Dermal Facial Skin and Subcutaneous Tissues, *Arch Facial Plastic Surgery*, Mar. 1, 2007, vol. 9, No. 1.
- Gold, M.H., et al., "Use of Micro-Focused Ultrasound with Visualization to Lift and Tighten Lax Knee Skin". *J Cosmet Laser Ther*, 2014: p. 1-15.
- Goldberg, D.J., et al., "Safety and Efficacy of Microfocused Ultrasound to Lift, Tighten, and Smooth the Buttocks". *Dermatol Surg* 2014; 40:1113-1117.
- Greene, R.M., et al., "Skin tightening technologies". *Facial Plast Surg*. Feb. 2014; 30(1):62-7.
- Greenhalgh, David G., "Wound healing and diabetes mellitus" *Clinics in Plastic Surgery* 30; 37-45. (2003).
- Guo, S. et al., "Factors Affecting Wound Healing" *Critical Reviews in Oral Biology & Medicine*, *J Dent Res* 89(3), pp. 219-229. (2010).
- Haar, G.R. et al., "Tissue Destruction with Focused Ultrasound in Vivo," *Eur. Urol.* 23 (suppl. 1):8-11; 1993.
- Hantash, Basil M. et al., "Bipolar Fractional Radiofrequency Treatment Induces Neocollagenesis and Neocollagenesis" *Lasers in Surgery and Medicine* 41:1-9 (2009).
- Hantash, Basil M. et al., "In Vivo Histological Evaluation of a Novel Ablative Fractional Resurfacing Device" *Lasers in Surgery and Medicine* 39:96-107 (2007).
- Harris, M.O., "Safety of Microfocused Ultrasound With Visualization in Patients With Fitzpatrick Skin Phototypes III to VI". *Jama Facial Plast. Surg*, 2015.
- Hart, et al., "Current Concepts in the Use of PLLA: Clinical Synergy Noted with Combined Use of Microfocused Ultrasound and Poly-L-Lactic Acid on the Face, Neck, and Décolletage". *Amer. Soc. Plast. Surg*. 2015. 136; 180-187S.
- Hassan et al., "Structure and Applications of Poly(vinyl alcohol) Hydrogels Produced by Conventional Crosslinking or by Freezing/Thawing Methods," *advanced in Polymer Science*, 2000, pp. 37-65, vol. 153.
- Hassan et al., "Structure and Morphology of Freeze/Thawed PVA Hydrogels," *Macromolecules*, Mar. 11, 2000, pp. 2472-2479, vol. 33, No. 7.
- Hexsel et al., "A Validated Photonumeric Cellulite Severity Scale"; *J Eur Acad Dermatol Venereol*. May 2009; 23(5):523-8, 6 pages.
- Hitchcock, T.M. et al., "Review of the safety profile for microfocused ultrasound with visualization". *Journal of Cosmetic Dermatology*, 13, 329-335. (2014).
- Husseini et al., "The Role of Cavitation in Acoustically Activated Drug Delivery," *J. Control Release*, Oct. 3, 2005, pp. 253-261, vol. 107(2).
- Husseini et al. "Investigating the mechanism of acoustically activated uptake of drugs from Pluronic micelles," *BMD Cancer* 2002, 2:20k, Aug. 30, 2002, pp. 1-6.

(56)

## References Cited

## OTHER PUBLICATIONS

- Hynynen et al., Temperature Distributions During Local Ultrasound Induced Hyperthermia In Vivo, Ultrasonics Symposium—745 (1982).
- Jeffers et al., “Evaluation of the Effect of Cavitation Activity on Drug-Ultrasound Synergisms,” 1993 IEEE Ultrasonics Symposium, pp. 925-928.
- Jenne, J., et al., “Temperature Mapping for High Energy US-Therapy”, 1994 Ultrasonics Symposium, pp. 1879-1882.
- Jeong, K.H., et al., “Neurologic complication associated with intense focused ultrasound”. *J Cosmet Laser Ther*, 2013.
- Johnson, S.A., et al., “Non-Intrusive Measurement of Microwave and Ultrasound-Induced Hyperthermia by Acoustic Temperature Tomography”, Ultrasonics Symposium Proceedings, pp. 977-982. (1977).
- Ketterling J. A. et al.: “Design and fabrication of a 40-MHz annular array transducer”, IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control, IEEE, US, vol. 52, No. 4, Apr. 1, 2005 (Apr. 1, 2005), pp. 672-681.
- Kim, H.J., et al., “Coagulation and ablation patterns of high-intensity focused ultrasound on a tissue mimicking phantom and cadaveric skin”. *Laser Med Sci*. Sep. 4, 2015.
- Kornstein, A.N., “Ulthera for silicone lip correction”. *Plast Reconstr Surg*, 2012. 129(6): p. 1014e-1015e.
- Kornstein, A.N., “Ultherapy shrinks nasal skin after rhinoplasty following failure of conservative measures”. *Plast Reconstr Surg*, 2013. 131(4): p. 664e-6e.
- Krischak, G.D., et al., “The effects of non-steroidal anti-inflammatory drug application on incisional wound healing in rats” *Journal of Wound Care*, vol. 6, No. 2, (Feb. 2007).
- Laubach, H.J., et al., “Confined Thermal Damage with Intense Ultrasound (IUS)” [abstr.] American Society for Laser Medicine and Surgery Abstracts, p. 15 #43 (Apr. 2006).
- Laubach, H.J., et al., “Intense focused ultrasound: evaluation of a new treatment modality for precise microcoagulation within the skin”. *Dermatol Surg*, 2008. 34(5): p. 727-34.
- Lee, H.J., et al., “The efficacy and safety of intense focused ultrasound in the treatment of enlarged facial pores in Asian skin”. *J Dermatolog Treat*, 2014.
- Lee, H.S., et al., “Multiple Pass Ultrasound Tightening of Skin Laxity of the Lower Face and Neck”. *Dermatol Surg*, 2011.
- Lin, Sung-Jan, et al., “Monitoring the thermally induced structural transitions of collagen by use of second-harmonic generation microscopy” *Optics Letters*, vol. 30, No. 6, (Mar. 15, 2005).
- MacGregor J.L., et al., “Microfocused Ultrasound for Skin Tightening”. *Semin Cutan Med Surg* 32:18-25. (2013).
- Madersbacher, S. et al., “Tissue Ablation in Benign Prostatic Hyperplasia with High Intensity Focused Ultrasound,” *Dur. Urol.*, 23 (suppl. 1):39-43; 1993.
- Makin et al., “B-Scan Imaging and Thermal Lesion Monitoring Using Miniaturized Dual-Functionality Ultrasound Arrays,” Ultrasonics Symposium, 2004 IEEE, Aug. 23, 2004, pp. 1788-1791, vol. 3.
- Makin et al., “Confirmed Bulk Ablation and Therapy Monitoring Using Intracorporeal Image-Treat Ultrasound Arrays,” 4th International Symposium on Therapeutic Ultrasound, Sep. 19, 2004.
- Makin et al., “Miniaturized Ultrasound Arrays for Interstitial Ablation and Imaging,” *UltraSound Med. Biol.* 2005, Nov. 1, 2005, pp. 1539-1550, vol. 31(11).
- Manohar et al., “Photoacoustic mammography laboratory prototype: imaging of breast tissue phantoms,” *Journal of Biomedical Optics*, Nov./Dec. 2004, pp. 1172-1181, vol. 9, No. 6.
- Mast et al., “Bulk Ablation of Soft Tissue with Intense Ultrasound; Modeling and Experiments,” *J. Acoust. Soc. Am.*, Oct. 1, 2005, pp. 2715-2724, vol. 118(4).
- Meshkinpour, Azin, et al., “Treatment of Hypertrophic Scars and Keloids With a Radiofrequency Device: A Study of Collagen Effects” *Lasers in Surgery and Medicine* 37:343-349 (2005).
- Microchip microID 125 kHz RFID System Design Guide, Microchip Technology Inc. (2004).
- Minkis, K., et al., “Ultrasound skin tightening”. *Dermatol Clin*, 2014. 32(1): p. 71-7.
- Mitragotri, S., “Healing sound: the use of ultrasound in drug delivery and other therapeutic applications,” *Nature Reviews; Drug Delivery*, pp. 255-260, vol. 4 (Mar. 2005).
- Mosser, David M. et al., “Exploring the full spectrum of macrophage activation” *Nat Rev Immunol*; 8(12): 958-969. (Dec. 2008).
- Murota, Sei-Itsu, et al., “Stimulatory Effect of Prostaglandins on the Production of Hexosamine-Containing Substances by Cultured Fibroblasts (3) Induction of Hyaluronic Acid Synthetase by Prostaglandin” Department of Pharmacology, Tokyo Metropolitan Institute of Gerontology, Itabashiku, Tokyo—173, Japan. (Nov. 1977, vol. 14, No. 5).
- Murota, Sei-Itsu, et al., “The Stimulatory Effect of Prostaglandins on Production of Hexosamine-Containing Substances by Cultured Fibroblasts” Department of Pharmacology, Tokyo Metropolitan Institute of Gerontology, Itabashiku, Tokyo—173, Japan. (Aug. 1976, vol. 12, No. 2).
- Narayanasamy et al., “Spatial registration of temporally separated whole breast 3D ultrasound images” *Med Phys*. Sep. 2009;36(9):4288-300. doi: 10.1118/1.3193678. PMID: 19810503; PMCID: PMC2749445 (2009).
- Nestor, M.S. et al., “Safety and Efficacy of Micro-focused Ultrasound Plus Visualization for the Treatment of Axillary Hyperhidrosis”. *J Clin Aesthet Dermatol*, 2014. 7(4): p. 14-21.
- Oni, G., et al. “Response to ‘comments on evaluation of microfocused ultrasound system for improving skin laxity and tightening in the lower face’”. *Aesthet Surg J*. Mar. 2015;35(3):NP83-4.
- Oni, G., et al., “Evaluation of a Microfocused Ultrasound System for Improving Skin Laxity and Tightening in the Lower Face”. *Aesthet Surg J*, 2014. 38:861-868.
- Pak, C.S., et al., “Safety and Efficacy of Ulthera in the Rejuvenation of Aging Lower Eyelids: A Pivotal Clinical Trial”. *Aesthetic Plast Surg*, 2014.
- Paradossi et al., “Poly(vinyl alcohol) as versatile biomaterial for potential biomedical applications,” *Journal of Materials Science: Materials in Medicine*, 2003, pp. 687-691, vol. 14.
- Pritzker, R.N., et al., “Updates in noninvasive and minimally invasive skin tightening”. *Semin Cutan Med Surg*. Dec. 2014;33(4):182-7.
- Pritzker, R.N., et al., “Comparison of different technologies for noninvasive skin tightening”. *Journal of Cosmetic Dermatology*, 13, 315-323. (2014).
- Rappolee, Daniel A., et al., “Wound Macrophages Express TGF and Other Growth Factors in Vivo: Analysis by mRNA Phenotyping” *Science*, vol. 241, No. 4866 (Aug. 1988).
- Reid, Gavin, et al., “Tandem Mass spectrometry of ribonuclease A and B: N-linked glycosylation site analysis of whole protein ions,” *Analytical Chemistry*. Feb. 1, 2002, vol. 74, No. 3, pp. 577-583.
- Righetti et al., “Elastographic Characterization of HIFU-Induced Lesions in Canine Livers,” 1999, *Ultrasound in Med & Bio*, vol. 25, No. 7, pp. 1099-1113.
- Rokhsar, C., et al., “Safety and efficacy of microfocused ultrasound in tightening of lax elbow skin”. *Dermatol Surg*. 2015; 41(7):821-6.
- Rosenberg, Carol S. “Wound Healing in the Patient with Diabetes Mellitus” *Nursing Clinics of North America*, vol. 25, No. 1, (Mar. 1990).
- Saad et al., “Ultrasound-Enhanced Effects of Adriamycin Against Murine Tumors,” *Ultrasound in Med. & Biol.* Vol. 18, No. 8, pp. 715-723 (1992).
- Sabet-Peyman, E.J. et al., “Complications Using Intense Ultrasound Therapy to Treat Deep Dermal Facial Skin and Subcutaneous Tissues”. *Dermatol Surg* 2014; 40:1108-1112.
- Sandulache, Vlad C. et al., “Prostaglandin E2 inhibition of keloid fibroblast migration, contraction, and transforming growth factor (TGF)- $\beta$ 1-induced collagen synthesis” *Wound Rep Reg* 15 122-133, 2007. (2007).
- Sanghvi, N.T., et al., “Transrectal Ablation of Prostate Tissue Using Focused Ultrasound,” 1993 Ultrasonics Symposium, IEEE, pp. 1207-1210.
- Sasaki, G.H. et al., “Clinical Efficacy and Safety of Focused-Image Ultrasonography: A 2-Year Experience”. *Aesthet Surg J*, 2012.
- Sasaki, G.H. et al., “Microfocused Ultrasound for Nonablative Skin and Subdermal Tightening to the Periorbitum and Body Sites:

(56)

## References Cited

## OTHER PUBLICATIONS

- Preliminary Report on Eighty-Two Patients". *Journal of Cosmetics, Dermatological Sciences and Applications*, 2012, 2, 108-116.
- Sassen, Sander, "ATI's R520 architecture, the new king of the hill?" <http://www.hardwareanalysis.com/content/article/1813>, Sep. 16, 2005, 2 pages.
- Seip, Ralf, et al., "Noninvasive Detection of Thermal Effects Due to Highly Focused Ultrasonic Fields," *IEEE Symposium*, pp. 1229-1232, vol. 2, Oct. 3-Nov. 1993.
- Seip, Ralf, et al., "Noninvasive Estimation of Tissue Temperature Response to Heating Fields Using Diagnostic Ultrasound," *IEEE Transactions on Biomedical Engineering*, vol. 42, No. 8, Aug. 1995, pp. 828-839.
- Simon et al., "Applications of Lipid-Coated Microbubble Ultrasonic Contrast to Tumor Therapy," *Ultrasound in Med. & Biol.* Vol. 19, No. 2, pp. 123-125 (1993).
- Sklar, L.R., et al., "Use of transcutaneous ultrasound for lipolysis and skin tightening: a review". *Aesthetic Plast Surg*, 2014. 38(2): p. 429-41.
- Smith, Nadine Barrie, et al., "Non-invasive In Vivo Temperature Mapping of Ultrasound Heating Using Magnetic Resonance Techniques", 1994 *Ultrasonics Symposium*, pp. 1829-1832, vol. 3.
- Sonocare, Inc. *Therapeutic Ultrasound System Model CST-100 Instruction Manual* (1985).
- Suh, D.H., et al., "A intense-focused ultrasound tightening for the treatment of infraorbital laxity". *J Cosmet Laser Ther*, 2012. 14(6): p. 290-5.
- Suh, D.H., et al., "Comparative histometric analysis of the effects of high-intensity focused ultrasound and radiofrequency on skin". *J Cosmet Laser Ther*. Mar. 24, 2015:1-7.
- Suh, D.H., et al., "Intense Focused Ultrasound Tightening in Asian Skin: Clinical and Pathologic Results" *American Society for Dermatologic Surgery, Inc.*; 37:1595-1602. (2011).
- Surry et al., "Poly(vinyl alcohol) cryogel phantoms for use in ultrasound and MR imaging," *Phys. Med. Biol.*, Dec. 6, 2004, pp. 5529-5546, vol. 49.
- Syka J. E. P. et al., "Peptide and Protein Sequence Analysis by Electron Transfer Dissociation Mass Spectrometry," *Proceedings of the National Academy of Sciences of USA, National Academy of Science*, Washington, DC, vol. 101, No. 26, Jun. 29, 2004, pp. 9528-9533.
- Talbert, D. G., "An Add-On Modification for Linear Array Real-Time Ultrasound Scanners to Produce 3D Displays," *UTS Int'l 1977 Brighton, England* (Jun. 28-30, 1977) pp. 57-67.
- Tata et al., "Interaction of Ultrasound and Model Membrane Systems: Analyses and Predictions," *American Chemical Society, Phys. Chem.* 1992, 96, pp. 3548-3555.
- Ueno, S., et al., "Ultrasound Thermometry in Hyperthermia", 1990 *Ultrasonic Symposium*, pp. 1645-1652.
- Verhofstad, Michiel H.J. et al., "Collagen Synthesis in rat skin and ileum fibroblasts is affected differently by diabetes-related factors" *Int. J. Exp. Path.* (1998), 79, 321-328.
- Wang, H., et al., "Limits on Focused Ultrasound for Deep Hyperthermia", 1994 *Ultrasonic Symposium*, Nov. 1-4, 1994, pp. 1869-1872, vol. 3.
- Wasson, Scott, "NVIDIA's GeForce 7800 GTX graphics processor Power MADD," <http://techreport.com/reviews/2005q2/geforce-7800gtx/index.x?pg=1>, Jun. 22, 2005, 4 pages.
- Webster et al. "The role of ultrasound-induced cavitation in the 'in vitro' stimulation of collagen synthesis in human fibroblasts"; *Ultrasonics* pp. 33-37 (Jan. 1980).
- Weiss, M., "Commentary: noninvasive skin tightening: ultrasound and other technologies: where are we in 2011?" *Dermatol Surg*, 2012. 38(1): p. 28-30.
- White et al. "Selective Creating of Thermal Injury Zones in the Superficial Musculoaponeurotic System Using Intense Ultrasound Therapy," *Arch Facial Plastic Surgery*, Jan./Feb. 2007, vol. 9, No. 1 (pp. 22-29).
- White, W. M., et al., "Selective Transcutaneous Delivery of Energy to Facial Subdermal Tissues Using the Ultrasound Therapy System" [abstr]. *American Society for Laser Medicine and Surgery Abstracts*, p. 37 #113 (Apr. 2006).
- White, W. Matthew, et al., "Selective Transcutaneous Delivery of Energy to Porcine Soft Tissues Using Intense Ultrasound (IUS)" *Lasers in Surgery and Medicine* 40:67-75 (2008).
- Woodward, J.A., et al. "Safety and Efficacy of Combining Microfocused Ultrasound With Fractional CO2 Laser Resurfacing for Lifting and Tightening the Face and Neck". *Dermatol Surg*, Dec. 2014 400:S190-S193.
- Zelickson, Brian D. et al., "Histological and Ultrastructural Evaluation of the Effects of a Radiofrequency-Based Nonablative Dermal Remodeling Device, A Pilot Study" *Arch Dermatol*, vol. 140, (Feb. 2004).
- Ulthera, Inc., Petition for Inter Partes Review filed Jul. 19, 2016 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 63 pages (Filed Jul. 19, 2016).
- Ulthera Exhibit 1001, U.S. Pat. No. 6,113,559 to Klopotek, filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1002, Patent file history of U.S. Pat. No. 6,113,559 Klopotek filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1003, Declaration of Expert Witness Mark E. Schafer, Ph.D. filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1004, Curriculum Vitae of Mark E. Schafer, Ph.D. filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1005, International PCT Publication WO96/34568 Knowlton filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1006, French Patent No. 2,672,486, Technomed patent filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1007, English translation of French Patent No. 2,672,486, Technomed filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1008, International PCT Publication WO93/12742, Technomed PCT filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1009, English translation of International PCT Publication WO93/12742, Technomed PCT filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1010, U.S. Pat. No. 5,601,526, which claims priority to Technomed PCT filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1011, Patent file history for European Patent Application No. 98964890.2, Klopotek filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1012, Translator Declaration filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1013, U.S. Pat. No. 5,230,334 to Klopotek filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1014, U.S. Pat. No. 5,755,753 to Knowlton filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1015, Excerpts from The American Medical Association Encyclopedia of Medicine (1989) filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1016, The Simultaneous Study of Light Emissions and Shock Waves Produced by Cavitation Bubbles, G. Gimenez, J. Acoust. Soc. Am. 71(4), Apr. 1982, pp. 839-847 (filed Jul. 19, 2016 in re IPR2016-01459).
- ULThERA Exhibit 1017, Excerpts from Gray's Anatomy (1995) (filed Jul. 19, 2016 in re IPR2016-01459).
- Ulthera Exhibit 1018, Anatomy of the Superficial Venous System, Comjen G.M., *Dermatol. Surg.*, 1995; 21:35-45 (filed Jul. 19, 2016 in re IPR2016-01459).
- Ulthera Exhibit 1019, Section 2.6 from *Ultrasonics Theory and Application*, by G.L. Gooberman (Hart Publishing Co., 1969) (filed Jul. 19, 2016 in re IPR2016-01459).
- Ulthera Exhibit 1020, *Deep Local Hyperthermia for Cancer Therapy: External Electromagnetic and Ultrasound Techniques*, A.Y. Cheung and A. Neyzari, *Cancer Research (Suppl.)*, vol. 44, pp. 4736-4744 (1984) (filed Jul. 19, 2016 in re IPR2016-01459).
- Decision on Institution of Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 20 pages [011] (Dated Jan. 23, 2017).
- Dermafocus Response to Institution of Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 73 pages [018] (Dated Apr. 26, 2017).

(56)

**References Cited**

## OTHER PUBLICATIONS

Dermafocus Exhibit List in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 5 pages [019] (Dated Apr. 26, 2017).

Dermafocus Exhibit 2002, Declaration of Mark Palmeri, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 136 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2003, Deposition of Dr. Mark Schafer, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 327 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2004, Amendment No. 4 to Ulthera Form S-1, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 308 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2005, Excerpt from Churchill Livingstone, Gray's Anatomy (38th ed. 1995), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2006, Bo Eklof et al., "Revision of the CEAP Classification for Chronic Venous Disorders: Consensus Statement," *Acta Fac Med Naiss*, vol. 25, No. 1 (2008), 3-10 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2007, WebMD, "Varicose Veins and Spider Veins" downloaded from <http://www.webmd.com/skin-problems-and-treatments/guide/varicose-spider-veins#1> in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 3 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2008, John M. Porter et al., "Reporting Standards in Venous Disease: An Update," *Journal of Vascular Surgery*, vol. 21, No. 4 (1995), 635-645 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 11 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2009, Kullervo Hynynen, "Review of Ultrasound Therapy," 1997 Ultrasonics Symposium (1997), 1305-1313, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 9 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2010, A.G. Visioli et al., "Preliminary Results of a Phase I Dose Escalation Clinical Trial Using Focused Ultrasound in the Treatment of Localised Tumours," *European Journal of Ultrasound*, vol. 9 (1999), 11-18, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 8 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2011, U.S. Pat. No. 5,143,063, issued on Sep. 1, 1992, Fellner, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2012, Hugh G. Beebe et al., "Consensus Statement: Classification and Grading of Chronic Venous Disease in the Lower Limbs," *European Journal of Vascular and Endovascular Surgery*, vol. 12 (1996), 487-492, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2013, Excerpt from Mosby's Medical Dictionary (3rd ed. 1990), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2014, Excerpt from Miller-Keane Encyclopedia & Dictionary of Medicine, Nursing, & Allied Health (5th ed. 1992), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2015, David J. Tibbs et al., *Varicose Veins, Venous Disorders, and Lymphatic Problems in the Lower Limbs* (1997), Chapter 4: Clinical Patterns of Venous Disorder I, 47-67, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 24 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2016, Mitchel P. Goldman et al., *Varicose Veins and Telangiectasias* (2nd ed. 1999), Chapter 22: Treatment of Leg Telangiectasias with Laser and High-Intensity Pulsed Light, 470-497, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 31 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2017, Email from Anderson to Klotek dated May 25, 2004, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 1 page (Filed Apr. 26, 2017).

Dermafocus Exhibit 2018, List of Klotek Patents, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 411 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2019, Declaration of Peter Klotek Civil Action 15-cv-654-SLR, dated Nov. 2, 2016, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 1 page (Filed Apr. 26, 2017).

Dermafocus Exhibit 2020, "Our Technology," downloaded from <http://jobs.ulthera.com/about> on Apr. 10, 2017, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2021, C. Damianou and K. Hynynen, "Focal Spacing and Near-Field Heating During Pulsed High Temperature Ultrasound Therapy," *Ultrasound in Medicine & Biology*, vol. 19, No. 9 (1993), 777-787, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 11 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2022, Excerpt from Mosby's Medical Dictionary (5th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 5 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2023, Excerpt from Miller-Keane Encyclopedia & Dictionary of Medicine, Nursing, & Allied Health (6th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2024, Excerpt from Stedman's Concise Medical Dictionary (3rd ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2025, Excerpt from Taber's Cyclopedic Medical Dictionary (18th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 9 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2026, Bo Eklof et al., "Revision of the CEAP Classification for Chronic Venous Disorders: Consensus Statement," *Journal of Vascular Surgery*, vol. 40, No. 6 (2004), 1248-1252.e1, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).

Ulthera, Inc., Reply in Support of Petition for Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 33 pages (Filed Aug. 2, 2017).

Ulthera Exhibit 1022, Use of the Argon and Carbon Dioxide Lasers for Treatment of Superficial Venous Varicosities of the Lower Extremity, D. Apfelberg et al., *Lasers in Surgery and Medicine*, vol. 4.3, pp. 221-231 (1984) (filed Aug. 2, 2017 in re IPR2016-01459).

Ulthera Exhibit 1023, 532-Nanometer Green Laser Beam Treatment of Superficial Varicosities of the Lower Extremities, T. Smith et al., *Lasers in Surgery and Medicine*, vol. 8.2, pp. 130-134 (1988) (filed Aug. 2, 2017 in re IPR2016-01459).

Ulthera Exhibit 1024, Deposition Transcript of Dr. Mark Palmeri on Jul. 11, 2017 (filed Aug. 2, 2017 in re IPR2016-01459).

Ulthera Exhibit 1025, Ulthera Oral Proceeding Demonstrative Slides (filed Oct. 2, 2017 in re IPR2016-01459).

Dermafocus Exhibit 2027, DermaFocus Oral Proceeding Demonstrative Slides (filed Oct. 2, 2017 in re IPR2016-01459).

PTAB Record of Oral Hearing held Oct. 4, 2017 in U.S. Pat. No. 6,113,559; IPR2016-01459; 67 pages (PTAB Document sent to Ulthera on Nov. 1, 2017).

Final Written Decision of Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 37 pages [030] (Entered Jan. 19, 2018).

Ulthera, Inc., Petitioner Notice of Appeal to Federal Circuit 2018-1542 re: IPR2016-01459; 4 pages from [001] (no appendices) (Filed Feb. 9, 2018).

Federal Circuit Order Granting Ulthera Motion to Remand, re: 2018-1542; 4 pages [022] (Dated May 25, 2018).


Ulthera Brief (Corrected), Fed. Cir. Appeal Case 19-1006 from re: IPR2016-01459; 136 pages [030] (Dated Apr. 3, 2019).

DermaFocus Brief (Corrected), Fed. Cir. Appeal Case 19-1006 from re: IPR2016-01459; 73 pages [032] (Dated Apr. 4, 2019).

Pavicic et al., Microfocused ultrasound with visualization: Consensus on safety and review of energy-based devices, *J Cosmet Dermatol* Feb. 2022, vol. 21, Issue 2: pp. 636-647, published online Dec. 24, 2021.

\* cited by examiner

FIG. 1








FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9






FIG. 10



**FIG. 11**



**FIG. 12**






FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18






FIG. 19



*FIG. 20*



*FIG. 21*




FIG. 22

## SYSTEMS FOR ULTRASOUND TREATMENT

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/410,780, filed Aug. 24, 2021 and issued as U.S. Pat. No. 10,537,304, which is a continuation of U.S. patent application Ser. No. 16/703,019, filed Dec. 4, 2019 and issued as U.S. Pat. No. 11,123,039, which is a continuation of U.S. patent application Ser. No. 12/996,616, filed Jan. 12, 2011 and issued as U.S. Pat. No. 10,537,304, which is a U.S. National Phase under 35 U.S.C. 371 of International Application No. PCT/US2009/046475, filed Jun. 5, 2009 and published in English on Dec. 10, 2009, which claims the benefit of priority from U.S. Provisional No. 61/059,477 filed Jun. 6, 2008, each of which is incorporated in its entirety by reference, herein. Any and all priority claims identified in the Application Data Sheet, or any correction thereto, are hereby incorporated by reference under 37 CFR 1.57.

## BACKGROUND

Embodiments of the present invention generally relate to ultrasound treatment and imaging devices and more specifically relate to ultrasound devices having a transducer probe operable to emit and receive ultrasound energy for cosmetic treatment and imaging.

In general, a popular cosmetic procedure for reducing wrinkles on the brow region of a patient's face is a brow lift, during which portions of muscle, fat, fascia and other tissues in the brow region are invasively cut, removed, and/or paralyzed to help reduce or eliminate wrinkles from the brow. Traditionally, the brow lift requires an incision beginning at one ear and continuing around the forehead at the hair line to the other ear. A less invasive brow lift procedure is known as an endoscopic lift during which smaller incisions are made along the forehead and an endoscope and surgical cutting tools are inserted within the incisions to cut, remove, manipulate, or paralyze tissue to reduce or eliminate wrinkles from the brow.

Even less invasive cosmetic treatments are designed to inject a neurotoxin in the brow. This procedure paralyzes muscles within the brow which can assist in reducing wrinkles. However, such procedures are temporary, can require chronic usage to sustain the intended effects, and can have deleterious effects.

## SUMMARY

There is a need for non-invasive cosmetic procedures for reducing wrinkles in the head and neck, such as in a brow region, and in other regions. In addition, there is a need for non-invasive cosmetic procedures that result in a tightening of skin in the head and neck, including the brow region, and other regions. Further, there is a need to effectively and efficiently image the region of the skin that is targeted for treatment. In several of the embodiments described herein, the procedure is entirely cosmetic and not a medical act.

Accordingly, several embodiments of the present invention provide a system and method for cosmetic treatment and imaging. In various embodiments the treatment system includes a hand wand with at least one finger activated control, or controller, and a removable transducer module having at least one ultrasound transducer. In one embodiment, the system includes a control module that is coupled

to the hand wand and has a graphic user interface for controlling the removable transducer module that has an interface coupling the hand wand to the control module. In an aspect of the embodiment, the interface provides power to the hand wand and/or transfers a signal from the hand wand to the control module. In various embodiments of the present invention, the cosmetic treatment and imaging system is used in aesthetic procedures on a portion of a head of patient, including the face, scalp, neck and/or ears of a patient.

In accordance with one embodiment of an aesthetic imaging system, the aesthetic imaging system includes a hand wand, a removable transducer module, a control module, and an interface coupling the hand wand and the control module. The hand wand includes at least one finger activated controller. The removable transducer module includes an ultrasound transducer and at least one interface coupleable to the hand wand. The control module is coupled to the hand wand and includes a graphical user interface for controlling the removable transducer module. In one embodiment, the interface couples the hand wand to the control module, and provides at least power to the hand wand. In one embodiment, the interface transfers one or more signals between the hand wand and the control module. In one embodiment, at least one signal (e.g., 1, 2, 3, 4, 5 or more signals) is communicated from the wand to the control module. In another embodiment, at least one signal (e.g., 1, 2, 3, 4, 5 or more signals) is communicated from the control module to the wand. In several embodiments, at least one signal (e.g., 1, 2, 3, 4, 5 or more signals) is communicated to, from, or between the wand and control module. In one embodiment, the aesthetic imaging system also includes a printer coupled to the control module and the control module provides an output signal and power to the printer. In one embodiment, the aesthetic imaging system also includes a key operable to unlock the control module for controlling the removable transducer module. In one embodiment of an aesthetic imaging system, the hand wand includes a movement mechanism, operable to move the ultrasound transducer within the transducer module. In one embodiment, the aesthetic imaging system also includes at least one sensor coupled to the hand wand and/or the removable transducer module.

In accordance with one embodiment of a hand wand for use in cosmetic treatment, the wand includes a first controlling device operably controlling an imaging function, a second controlling device operably controlling a treatment function, a status indicator, an input for power, an output for at least one signal, a movement mechanism and a removable transducer module operably coupled to at least one of the first controlling device, the second controlling device and the movement mechanism. In one embodiment, the hand wand includes a latch mechanism removably holding the transducer module in the wand. In one embodiment, the hand wand includes a cable for communicating at least one of the input and the output. In one embodiment, the hand wand includes a controller operably interfacing with a cable, where the controller has a graphical user interface for controlling the removable transducer module. In one embodiment, the hand wand includes a first transducer module coupled to the first controlling device and a second transducer module coupled to the second controlling device.

In accordance with one embodiment of a device for cosmetic imaging and treatment, the device includes a removable transducer module and a controller. In one embodiment, the transducer module is not removable. In one embodiment, the transducer module is integrated, or perma-



nently attached. The removable transducer module is interfaced to a hand enclosure having at least one controller button such that the transducer module and button is operable using one hand. The transducer module provides ultrasound energy for at least one of an imaging function and a treatment function. The controller is coupled to the hand enclosure and is interfaced to the transducer module. The controller controls the ultrasound energy and receives at least one signal from the transducer module. The controller has a power supply operably providing power for at least the ultrasound energy. In one embodiment, the device also includes a graphical user interface for controlling the transducer module and for viewing the at least one signal from the transducer module. In one embodiment, the device has a hand enclosure that also includes a movement mechanism operably moving a transducer in the transducer module, where the movement mechanism is controlled by the controller. In one embodiment, the device has at least one controller button as a first controller button controlling the imaging function and a second controlling button controlling the treatment function. In various embodiments, the device has a treatment function that is one of face lift, a brow lift, a chin lift, a wrinkle reduction, a scar reduction, a tattoo removal, a vein removal, sun spot removal, and pimple removal. In another embodiment the device may be used on adipose tissue.

In accordance with one embodiment of a method of performing cosmetic treatment on a facial (or other) area of a subject, the method includes inserting a transducer module into a hand controller, coupling the transducer module to the subject, activating a first switch on the hand controller operably initiating an imaging sequence of a portion of tissue below the dermal layer, collecting data from the imaging sequence, calculating a treatment sequence from the data, and activating a second switch on the hand controller operably initiating the treatment sequence. In one embodiment, the method also includes emitting a first ultrasound energy from a first transducer in the transducer module operably providing a source for the imaging sequence. In one embodiment, the method also includes emitting a second ultrasound energy from a second transducer in the transducer module operably providing a source for the treatment sequence. In one embodiment, the method also includes tightening a portion of the dermal layer on a facial area of a subject. In one embodiment, the method provides for the transducer module to permit the treatment sequence at a fixed depth below the dermal layer.

In accordance with one embodiment of a hand wand for use in cosmetic treatment, the wand includes a first controlling device operably controlling an ultrasonic imaging function, a second controlling device operably controlling an ultrasonic treatment function, a movement mechanism configured for travel through a liquid-tight seal, and a fluid-filled transducer module. In one embodiment, the fluid-filled transducer module is operably coupled to at least one of the first controlling, the second controlling device and the movement mechanism. In one embodiment, the fluid-filled transducer module is mechanically and electrically separable from at least one of the first controlling, the second controlling device and the movement mechanism. In one embodiment, the fluid-filled transducer module includes an acoustic liquid. In one embodiment, the fluid-filled transducer module includes a gel adapted to enhance transmission of an ultrasonic signal. In one embodiment, a gel adapted to enhance transmission of an ultrasonic signal is placed between the transducer and the patient's skin.

In accordance with one embodiment of a hand wand for use in cosmetic treatment, the wand includes a first controlling device operably controlling an ultrasonic imaging function, a second controlling device operably controlling an ultrasonic treatment function, and a movement mechanism configured to create a linear sequence of individual thermal lesions with the second controlling device. In one embodiment, the movement mechanism is configured to be automated and programmable by a user. In one embodiment, the wand includes a transducer module operably coupled to at least one of the first controlling device, the second controlling device and the movement mechanism. In one embodiment, the linear sequence of individual thermal lesions has a treatment spacing in a range from about 0.01 mm to about 25 mm. In one embodiment, the movement mechanism is configured to be programmed to provide variable spacing between the individual thermal lesions. In one embodiment the individual thermal lesions are discrete. In one embodiment the individual thermal lesions are overlapping.

In accordance with one embodiment of a variable ultrasonic parameter ultrasonic system for use in cosmetic treatment, the system includes a first controlling device, a second controlling device, a movement mechanism, and one or more removable transducer modules. In various embodiments, the one or more removable transducer modules includes two, three, four, five, six, or more removable transducer modules. In various embodiments, the different numbers of removable transducer modules can be configured for different or variable ultrasonic parameters. For example, in various non-limiting embodiments, the ultrasonic parameter can relate to transducer geometry, size, timing, spatial configuration, frequency, variations in spatial parameters, variations in temporal parameters, coagulation formation, depth, width, absorption coefficient, refraction coefficient, tissue depths, and/or other tissue characteristics. In various embodiments, a variable ultrasonic parameter may be altered, or varied, in order to effect the formation of a lesion for the desired cosmetic approach. In various embodiments, a variable ultrasonic parameter may be altered, or varied, in order to effect the formation of a lesion for the desired clinical approach. By way of example, one variable ultrasonic parameter relates to aspects of configurations associated with tissue depth. For example, some non-limiting embodiments of removable transducer modules can be configured for a tissue depth of 3 mm, 4.5 mm, 6 mm, less than 3 mm, between 3 mm and 4.5 mm, more than more than 4.5 mm, more than 6 mm, and anywhere in the ranges of 0-3 mm, 0-4.5 mm, 0-25 mm, 0-100 mm, and any depths therein. In one embodiment, an ultrasonic system is provided with two transducer modules, in which the first module applies treatment at a depth of about 4.5 mm and the second module applies treatment at a depth of about 3 mm. An optional third module that applies treatment at a depth of about 1.5-2 mm is also provided. A combination of two or more treatment modules is particularly advantageous because it permits treatment of a patient at varied tissue depths, thus providing synergistic results and maximizing the clinical results of a single treatment session. For example, treatment at multiple depths under a single surface region permits a larger overall volume of tissue treatment, which results in enhanced collagen formation and tightening. Additionally, treatment at different depths affects different types of tissue, thereby producing different clinical effects that together provide an enhanced overall cosmetic result. For example, superficial treatment may reduce the visibility of wrinkles and deeper treatment may induce formation of more collagen growth.

Although treatment of a subject at different depths in one session may be advantageous in some embodiments, sequential treatment over time may be beneficial in other embodiments. For example, a subject may be treated under the same surface region at one depth in week 1, a second depth in week 2, etc. The new collagen produced by the first treatment may be more sensitive to subsequent treatments, which may be desired for some indications. Alternatively, multiple depth treatment under the same surface region in a single session may be advantageous because treatment at one depth may synergistically enhance or supplement treatment at another depth (due to, for example, enhanced blood flow, stimulation of growth factors, hormonal stimulation, etc.).

In several embodiments, different transducer modules provide treatment at different depths. In several embodiments, a system comprising different transducers, each having a different depth, is particularly advantageous because it reduces the risk that a user will inadvertently select an incorrect depth. In one embodiment, a single transducer module can be adjusted or controlled for varied depths. Safety features to minimize the risk that an incorrect depth will be selected can be used in conjunction with the single module system.

In several embodiments, a method of treating the lower face and neck area (e.g., the submental area) is provided. In several embodiments, a method of treating (e.g., softening) mentolabial folds is provided. In other embodiments, a method of treating the eye region is provided. Upper lid laxity improvement and periorbital lines and texture improvement will be achieved by several embodiments by treating at variable depths. In one embodiment, a subject is treated with about 40-50 lines at depths of 4.5 and 3 mm. The subject is optionally treated with about 40-50 lines at a depth of about 1.5-2 mm. The subject is optionally treated with about 40-50 lines at a depth of about 6 mm. By treating at varied depths in a single treatment session, optimal clinical effects (e.g., softening, tightening) can be achieved.

In several embodiments, the treatment methods described herein are non-invasive cosmetic procedures. In some embodiments, the methods can be used in conjunction with invasive procedures, such as surgical facelifts or liposuction, where skin tightening is desired.

In accordance with one embodiment of a variable ultrasonic parameter system for use in cosmetic treatment, the system includes a first controlling device, a second controlling device, a movement mechanism, a first removable transducer module and a second removable transducer module. The first controlling device operably controls an ultrasonic imaging function. The second controlling device operably controls an ultrasonic treatment function. The movement mechanism is configured to create a linear sequence of individual thermal lesions for treatment purposes. The first removable transducer module is configured to treat tissue at a first tissue depth. The second removable transducer module is configured to treat tissue at a second tissue depth. The first and second transducer modules are interchangeably coupled to a hand wand. The first and second transducer modules are operably coupled to at least one of the first controlling device, the second controlling device and the movement mechanism. Rapid interchangeability and exchange of multiple modules on a single unit facilitates treatment in several embodiments. In one embodiment the individual thermal lesions are discrete. In one embodiment the individual thermal lesions are overlapping, merged, etc.

In accordance with one embodiment of an aesthetic imaging and treatment system includes a hand wand, a removable transducer module, a control module and an interface coupling the hand wand to the control module. The hand wand includes at least one finger activated controller. The removable transducer module includes an ultrasound transducer and at least one interface coupleable to the hand wand. The control module is coupled to the hand wand and includes a graphical user interface for controlling the removable transducer module. The interface coupling the hand wand to the control module transfers at least a signal between the hand wand and the control module. In one embodiment, the system also includes a printer coupled to the control module, with the control module providing an output signal and power to the printer. In one embodiment, the system also includes a key operable to unlock the control module for controlling the removable transducer module. In one embodiment, the hand wand also includes a movement mechanism, the movement mechanism operable to move the ultrasound transducer within the transducer module. In one embodiment, the system also includes at least one sensor coupled to one of the hand wand and the removable transducer module.

In accordance with one embodiment of a hand wand for use in cosmetic treatment, the wand includes a first controlling device operably controlling an imaging function, a second controlling device operably controlling a treatment function, a status indicator, an input for power, an output for at least one signal, a movement mechanism, and a removable transducer module operably coupled to at least one of the first controlling device, the second controlling device and the movement mechanism. In one embodiment, the system also includes a latch mechanism removably holding the transducer module in the wand. In one embodiment, the system also includes a cable for communicating at least one of the input and the output. In one embodiment, the system also includes a controller operably interfacing with the cable, the controller having a graphical user interface for controlling the removable transducer module. In one embodiment, the transducer module has a first transducer coupled to the first controlling device and a second transducer coupled to the second controlling device.

In accordance with one embodiment of a device for cosmetic treatment, the device includes a removable transducer module interfaced to a hand enclosure and a controller coupled to the hand enclosure and interfaced to the transducer module. The removable transducer module has at least one controller button such that the transducer module and button are operable using one hand. The transducer module provides ultrasound energy for a treatment function. The controller controls the ultrasound energy and receives at least one signal from the transducer module. The controller has a power supply operably providing power for at least the ultrasound energy. In one embodiment, the controller also includes a graphical user interface for controlling the transducer module and for viewing the at least one signal from the transducer. In one embodiment, the hand enclosure also includes a movement mechanism operably moving a transducer in the transducer module, the movement mechanism being controlled by the controller. In one embodiment, the at least one controller button includes a first controller button controlling the imaging function and a second controlling button controlling the treatment function. In one embodiment, the treatment function is at least one of face lift, a brow lift, a chin lift, a wrinkle reduction, a scar reduction, a tattoo removal, a vein removal, sun spot removal, and acne treatment

In accordance with one embodiment of a method of performing cosmetic treatment a facial area of a subject, the method includes inserting a transducer module into a hand controller, coupling the transducer module to the facial area of the subject, activating a first switch on the hand controller operably initiating an imaging sequence of a portion of tissue below the dermal layer, collecting data from the imaging sequence, calculating a treatment sequence from the data, and activating a second switch on the hand controller operably initiating the treatment sequence. In one embodiment, the method also includes emitting a first ultrasound energy from a first transducer in the transducer module operably providing a source for the imaging sequence. In one embodiment, the method also includes emitting a second ultrasound energy from a second transducer in the transducer module operably providing a source for the treatment sequence. In one embodiment, the method also includes tightening a portion of the dermal layer on a facial area of a subject. In one embodiment, the transducer module permits the treatment sequence at a fixed depth below the dermal layer.

In several embodiments, the invention comprises a hand wand for use in cosmetic treatment. In one embodiment, the wand comprises a first controlling device operably controlling an ultrasonic imaging function for providing ultrasonic imaging and a second controlling device operably controlling an ultrasonic treatment function for providing ultrasonic treatment. The controlling devices, in some embodiments, are finger/thumb operated buttons or keys that communicate with a computer processor. The wand also comprises a movement mechanism configured to direct ultrasonic treatment in a linear sequence of individual thermal lesions. In one embodiment, the linear sequence of individual thermal lesions has a treatment spacing in a range from about 0.01 mm to about 25 mm. In one embodiment the individual thermal lesions are discrete. In one embodiment the individual thermal lesions are overlapping. The movement mechanism is configured to be programmed to provide variable spacing between the individual thermal lesions. First and second removable transducer modules are also provided. Each of the first and second transducer modules are configured for both ultrasonic imaging and ultrasonic treatment. The first and second transducer modules are configured for interchangeable coupling to the hand wand. The first transducer module is configured to apply ultrasonic therapy to a first layer of tissue, while the second transducer module is configured to apply ultrasonic therapy to a second layer of tissue. The second layer of tissue is at a different depth than the first layer of tissue. The first and second transducer modules are configured to be operably coupled to at least one of the first controlling device, the second controlling device and the movement mechanism.

In one embodiment, a third transducer module is provided. The third transducer module is configured to apply ultrasonic therapy to a third layer of tissue, wherein the third layer of tissue is at a different depth than the first or second layers of tissue. Fourth and fifth modules are provided in additional embodiments. The transducer modules are configured to provide variable depth treatment and the movement mechanism is configured to provide variable treatment along a single depth level.

In one embodiment, at least one of the first controlling device and the second controlling device is activated by a control. The control module comprises a processor and a graphical user interface for controlling the first and second transducer modules.

A method of performing a cosmetic procedure on a subject using a hand wand as described herein is provided in several embodiments. In one embodiment, the method comprises ultrasonically imaging a first target region on the subject with the first transducer module and ultrasonically treating the first target region on the subject with the first transducer module at the first tissue depth. The treatment comprises multiple treatment lines across the first target region that are automatically selected (e.g., programmed, pre-set, etc.) by the movement mechanism. In one embodiment, the method further comprises exchanging the first transducer module with the second transducer module; ultrasonically imaging a second target region on the subject with the second transducer module; and ultrasonically treating the second target region on the subject with the second transducer module at the second tissue depth. The treatment comprises multiple treatment lines across the second target region that are automatically selected (e.g., programmed, pre-set, etc.) by the movement mechanism. In one embodiment, the first and second target regions are located under a single surface of the subject.

In several embodiments, the invention comprises a hand wand for use in cosmetic treatment. In accordance with one embodiment, the hand wand comprises a first controlling device, a second controlling device, a movement mechanism, and a transducer module. The first controlling device operably controls an ultrasonic imaging function for providing ultrasonic imaging. The second controlling device operably controls an ultrasonic treatment function for providing ultrasonic treatment. The movement mechanism is configured to direct ultrasonic treatment in a sequence of individual thermal lesions. The removable transducer module is configured for both ultrasonic imaging and ultrasonic treatment. The removable transducer module is configured for interchangeable coupling to the hand wand. The removable transducer module is configured to be operably coupled to at least one of said first controlling device, said second controlling device and said movement mechanism. The removable transducer module is configured to apply ultrasonic therapy to at a first variable ultrasonic parameter to tissue.

In one embodiment, the hand wand is configured to apply ultrasonic therapy to at a second variable ultrasonic parameter to tissue. In one embodiment, the removable transducer module is configured to apply ultrasonic therapy to at a second variable ultrasonic parameter to tissue. In one embodiment, the hand wand further comprises a second removable transducer module, wherein the second removable transducer module is configured to apply ultrasonic therapy to at the second variable ultrasonic parameter to tissue. In one embodiment, the variable ultrasonic parameter is tissue depth. In one embodiment, the variable ultrasonic parameter is frequency. In one embodiment, the variable ultrasonic parameter is timing. In one embodiment, the variable ultrasonic parameter is geometry.

In several embodiments, the invention comprises a hand wand for use in cosmetic treatment. In one embodiment, the wand comprises at least one controlling device, movement mechanism and transducer module. In one embodiment, the wand comprises at least one controlling device operably controlling an ultrasonic imaging function for providing ultrasonic imaging and operably controlling an ultrasonic treatment function for providing ultrasonic treatment. One, two or more controlling devices may be used. A movement mechanism configured to direct ultrasonic treatment in a sequence of individual thermal lesions is provided. The transducer module is configured for both ultrasonic imaging

and ultrasonic treatment and is operably coupled to at least one controlling device and a movement mechanism. The transducer module is configured to apply ultrasonic therapy at a first ultrasonic parameter and a second ultrasonic parameter. In various embodiments, the first and second ultrasonic parameters are selected from the group consisting of: variable depth, variable frequency, and variable geometry. For example, in one embodiment, a single transducer module delivers ultrasonic therapy at two or more depths. In another embodiment, two or more interchangeable transducer modules each provide a different depth (e.g., one module treats at 3 mm depth while the other treats at a 4.5 mm depth). In yet another embodiment, a single transducer module delivers ultrasonic therapy at two or more frequencies, geometries, amplitudes, velocities, wave types, and/or wavelengths. In other embodiments, two or more interchangeable transducer modules each provide a different parameter value. In one embodiment, a single transducer may provide at least two different depths and at least two different frequencies (or other parameter). Variable parameter options are particularly advantageous in certain embodiments because they offer enhanced control of tissue treatment and optimize lesion formation, tissue coagulation, treatment volume, etc.

Further areas of applicability will become apparent from the description provided herein. It should be understood that the description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the embodiments disclosed herein.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The drawings described herein are for illustration purposes only and are not intended to limit the scope of the present disclosure in any way. Embodiments of the present invention will become more fully understood from the detailed description and the accompanying drawings wherein:

FIG. 1 is an illustration depicting a cosmetic treatment system according to various embodiments of the present invention;

FIG. 2 is a top view illustrating a hand wand according to various embodiments of the present invention;

FIG. 3 is a side view illustrating a hand wand according to various embodiments of the present invention;

FIG. 4 is a side view illustrating an emitter-receiver module according to various embodiments of the present invention;

FIG. 5 is another side view illustrating an emitter-receiver module according to various embodiments of the present invention;

FIG. 6 is a block diagram illustrating an emitter-receiver module according to various embodiments of the present invention;

FIG. 7 is an illustration depicting a movement mechanism according to various embodiments of the present invention;

FIG. 8 is a block diagram illustrating a cosmetic treatment system according to various embodiments of the present invention;

FIG. 9 is an electronic block diagram illustrating a cosmetic treatment system according to various embodiments of the present invention;

FIG. 10 is a schematic illustration of a hand wand and an emitter-receiver module according to various embodiments of the present invention;

FIG. 11 is an illustration depicting one possible area of interest of a subject according to various embodiments of the present invention;

FIG. 12 is an illustration depicting one possible area of interest of a subject according to various embodiments of the present invention;

FIG. 13 is an illustration depicting an area of interest of a subject according to various embodiments of the present invention;

FIG. 14 is a cross-sectional illustration of a portion of an area of interest according to various embodiments of the present invention;

FIG. 15 is a cross-sectional illustration depicting an apparatus and a method according to one embodiment of the present invention;

FIG. 16 is a cross-sectional illustration depicting a treatment region according to various embodiments of the present invention;

FIG. 17 is an illustration depicting the cosmetic treatment system coupled to the region of interest according to various embodiments of the present invention;

FIG. 18 is a flow chart depicting a method according to various embodiments of the present invention;

FIG. 19 is a flow chart depicting another method according to various embodiments of the present invention.

FIG. 20 is a front view illustrating a controller according to various embodiments of the present invention;

FIG. 21 is a side view illustrating a controller according to various embodiments of the present invention;

FIG. 22 is a representation of an interactive graphical display on a controller according one embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The following description sets forth examples of embodiments, and is not intended to limit the present invention or its teachings, applications, or uses thereof. It should be understood that throughout the drawings, corresponding reference numerals indicate like or corresponding parts and features. The description of specific examples indicated in various embodiments of the present invention are intended for purposes of illustration only and are not intended to limit the scope of the invention disclosed herein. Moreover, recitation of multiple embodiments having stated features is not intended to exclude other embodiments having additional features or other embodiments incorporating different combinations of the stated features. Further, features in one embodiment (such as in one figure) may be combined with descriptions (and figures) of other embodiments.

In accordance with one embodiment of the present invention, methods and systems for ultrasound treatment of tissue are configured to provide cosmetic treatment. In various embodiments of the present invention, tissue below or even at a skin surface such as epidermis, dermis, fascia, and superficial muscular aponeurotic system (“SMAS”), are treated non-invasively with ultrasound energy. The ultrasound energy can be focused, unfocused or defocused and applied to a region of interest containing at least one of epidermis, dermis, hypodermis, fascia, and SMAS to achieve a therapeutic effect. In one embodiment, the present invention provides non-invasive dermatological treatment to produce eyebrow lift through tissue coagulation and tightening. In one embodiment, the present invention provides imaging of skin and sub-dermal tissue. Ultrasound energy can be focused, unfocused or defocused, and applied to any

desired region of interest, including adipose tissue. In one embodiment, adipose tissue is specifically targeted.

In various embodiments of the present invention, certain cosmetic procedures that are traditionally performed through invasive techniques are accomplished by targeting energy, such as ultrasound energy, at specific subcutaneous tissues. In several embodiments, methods and systems for non-invasively treating subcutaneous tissues to perform a brow lift are provided; however, various other cosmetic treatment applications, such as face lifts, acne treatment and/or any other cosmetic treatment application, can also be performed with the cosmetic treatment system. In one embodiment, a system integrates the capabilities of high resolution ultrasound imaging with that of ultrasound therapy, providing an imaging feature that allows the user to visualize the skin and sub-dermal regions of interest before treatment. In one embodiment, the system allows the user to place a transducer module at optimal locations on the skin and provides feedback information to assure proper skin contact. In one embodiment, the therapeutic system provides an ultrasonic transducer module that directs acoustic waves to the treatment area. This acoustic energy heats tissue as a result of frictional losses during energy absorption, producing a discrete zone of coagulation.

In various embodiments, the device includes a removable transducer module interfaced to a hand enclosure having at least one controller button such that the transducer module and the controller button is operable using only one hand. In an aspect of the embodiments, the transducer module provides ultrasound energy for an imaging function and/or a treatment function. In another aspect of the embodiments, the device includes a controller coupled to the hand-held enclosure and interfaced to the transducer module. In a further aspect of the embodiments, the controller controls the ultrasound energy and receives a signal from the transducer module. The controller can have a power supply and driver circuits providing power for the ultrasound energy. In still another aspect of the embodiments, the device is used in cosmetic imaging and treatment of a patient, or simply treatment of the patient, such as on a brow of a patient.

In accordance with one embodiment for a method of performing a brow lift on a patient, the method includes coupling a probe to a brow region of the patient and imaging at least a portion of subcutaneous tissue of the brow region to determine a target area in the subcutaneous tissue. In one embodiment, the method includes administering ultrasound energy into the target area in the subcutaneous tissue to ablate or coagulate the subcutaneous tissue in the target area, which causes tightening of a dermal layer above or below the subcutaneous tissue of the brow region.

Moreover, several embodiments of the present invention provide a method of tightening a portion of a dermal layer on a facial area of a patient. In various embodiments, the method includes inserting a transducer module into a hand controller and then coupling the transducer module to a facial area of the patient. In one embodiment, the method includes activating a first switch on the hand to initiate an imaging sequence of a portion of tissue below a dermal layer, then collecting data from the imaging sequence. In these embodiments, the method includes calculating a treatment sequence from the collected data, and then activating a second switch on the hand to initiate the treatment sequence. In an aspect of the embodiments, the method can be useful on a portion of a face, head, neck and/or other part of the body of a patient.

In some embodiments, the system includes a hand wand with at least one finger activated controller, and a removable

transducer module having an ultrasound transducer. In one embodiment, the system includes a control module that is coupled to the hand wand and has a graphic user interface for controlling the removable transducer module with an interface coupling the hand wand to the control module. In one embodiment, the interface provides power to the hand wand. In one embodiment, the interface transfers at least one signal between the hand wand and the control module. In one embodiment, the aesthetic imaging system is used in cosmetic procedures on a portion of a face, head, neck and/or other part of the body of a patient.

In addition, several embodiments of the present invention provide a hand wand for use in aesthetic treatment. In some embodiments, the hand wand includes a first controlling device operably controlling an imaging function, a second controlling device operably controlling a treatment function, a status indicator, an input for power, an output for at least one signal, and a movement mechanism. A removable transducer module can be coupled to the hand wand. The removable transducer module can be interfaced with the first controlling device, the second controlling device and/or the movement mechanism. In one embodiment, the hand wand is used in cosmetic procedures on a face, head, neck and/or other part of the body of a patient.

Several embodiments of the present invention may be described herein in terms of various components and processing steps. It should be appreciated that such components and steps may be realized by any number of hardware components configured to perform the specified functions. For example, some embodiments of the present invention may employ various medical treatment devices, visual imaging and display devices, input terminals and the like, which may carry out a variety of functions under the control of one or more control systems or other control devices. Several embodiments of the present invention may be practiced in any number of medical contexts. For example, the principles, features and methods discussed may be applied to any medical application.

To further explain in more detail various aspects of embodiments of the present invention, several examples of a cosmetic treatment system as used with a control system and an ultrasonic probe system will be provided. However, it should be noted that the following embodiments are for illustrative purposes, and that embodiments of the present invention can comprise various other configurations for a cosmetic treatment. In addition, although not illustrated in the drawing figures, the cosmetic treatment system can further include components associated with imaging, diagnostic, and/or treatment systems, such as any required power sources, system control electronics, electronic connections, and/or additional memory locations.

With reference to the illustration in FIG. 1, an embodiment of the present invention is depicted as a cosmetic treatment system 20. In various embodiments of the present invention, the cosmetic treatment system 20 (hereinafter "CTS 20") includes a hand wand 100, an emitter-receiver module 200, and a controller 300. The hand wand 100 can be coupled to the controller 300 by an interface 130. In one embodiment the interface is a cord. In one embodiment, the cord is a two way interface between the hand wand 100 and the controller 300. In various embodiments the interface 130 can be, for example, any multi-conductor cable or wireless interface. In one embodiment, the interface 130 is coupled to the hand wand 100 by a flexible connection 145. In one embodiment, the flexible connection 145 is a strain relief. The distal end of the interface 130 is connected to a controller connector on a flex circuit 345. In various embodi-

ments the flexible connector **145** can be rigid or may be flexible, for example, including a device such as an elastic sleeve, a spring, a quick connect, a reinforced cord, a combination thereof, and the like. In one embodiment, the flexible connection **145** and the controller connection on the flex circuit **345** can include an antenna and receiver for communications wirelessly between the hand wand **100** and the controller **300**. In one embodiment, the interface **130** can transmit controllable power from the controller **300** to the hand wand **100**.

In various embodiments, the controller **300** can be configured for operation with the hand wand **100** and the emitter-receiver module **200**, as well as the overall CTS **20** functionality. In various embodiments, multiple controllers **300**, **300'**, **300"**, etc. can be configured for operation with multiple hand wands **100**, **100'**, **100"**, etc. and or multiple emitter-receiver modules **200**, **200'**, **200"**, etc. In various embodiments, a second embodiment of a reference can be indicated with a reference number with one or more primes ('). For example, in one embodiment a first module **200** may be used with or as an alternative to a second module **200'**, third module **200"**, fourth module **200'"**, etc. Likewise, in various embodiments, any part with multiples can have a reference number with one or more primes attached to the reference number in order to indicate that embodiment. For example, in one embodiment a first transducer **280** can be indicated with the **280** reference number, and a second transducer **280'** uses the prime. In one embodiment, controller **300** houses an interactive graphical display **310**, which can include a touch screen monitor and Graphic User Interface (GUI) that allows the user to interact with the CTS **20**. In various embodiments, this display **310** sets and displays the operating conditions, including equipment activation status, treatment parameters, system messages and prompts and ultrasound images. In various embodiments, the controller **300** can be configured to include, for example, a microprocessor with software and input/output devices, systems and devices for controlling electronic and/or mechanical scanning and/or multiplexing of transducers and/or multiplexing of transducer modules, a system for power delivery, systems for monitoring, systems for sensing the spatial position of the probe and/or transducers and/or multiplexing of transducer modules, and/or systems for handling user input and recording treatment results, among others. In various embodiments, the controller **300** can comprise a system processor and various digital control logic, such as one or more of microcontrollers, microprocessors, field-programmable gate arrays, computer boards, and associated components, including firmware and control software, which may be capable of interfacing with user controls and interfacing circuits as well as input/output circuits and systems for communications, displays, interfacing, storage, documentation, and other useful functions. System software may be capable of controlling all initialization, timing, level setting, monitoring, safety monitoring, and all other system functions required to accomplish user-defined treatment objectives. Further, the controller **300** can include various control switches that may also be suitably configured to control operation of the CTS **20**. In one embodiment, the controller **300** includes an interactive graphical display **310** for conveying information to user. In one embodiment, the controller **300** includes one or more data ports **390**. In one embodiment, the data port **390** is a USB port, and can be located on the front, side, and/or back of the controller **300** for access to storage, a printer **391**, devices, or be used for other purposes. In various embodiments the CTS **20** includes a lock **395**, and in one embodi-

ment the lock **395** can be connectable to the controller **300** via a USB port. In one embodiment, in order to operate CTS **20**, lock **395** must be unlocked so that power switch **393** may be activated. In another embodiment lock **395** must be unlocked insertion of USB access key or hardware dongle and associated software so that the interactive graphical display **310** can execute. In one embodiment, an emergency stop button **392** is readily accessible for emergency deactivation.

In various embodiments, an aesthetic imaging system or CTS **20** includes a hand wand **100** with at least one finger activated controller (**150** and/or **160**), and a removable emitter-receiver module **200** having an ultrasound transducer. Other embodiments may include non-removable emitter-receiver modules, imaging-only emitter-receiver modules, treatment-only emitter-receiver modules, and imaging-and-treatment emitter-receiver modules. In one embodiment, the CTS **20** includes a control module **300** that is coupled to the hand wand **100** and has a graphic user interface **310** for controlling the removable transducer module **200** with an interface **130**, such as in one embodiment, a cord coupling the hand wand **100** to the control module **300**. In one embodiment, the interface **130** provides power to the hand wand **100**. In one embodiment, the interface **130** transfers at least one signal between the hand wand **100** and the control module **300**. In an aspect of this embodiment, the aesthetic imaging system of CTS **20** is used in aesthetic procedures on a portion of a head of a patient. In one embodiment, the CTS **20** is used in aesthetic procedures on a portion of a face, head, neck and/or other part of the body of a patient.

In addition, certain embodiments of the present invention provide a hand wand **100** for use in aesthetic treatment. In some embodiments, the hand wand **100** includes a first controlling device **150** operably controlling an imaging function, a second controlling device **160** operably controlling a treatment function, a status indicator **155**, an input for power, an output for at least one signal (for example to a controller **300**), a movement mechanism **400**, and a removable transducer module **200** in communication with the first controlling device **150**, the second controlling device **160** and/or the movement mechanism **400**. In an aspect of the embodiments, the hand wand **100** is used in cosmetic procedures on a face, head, neck and/or other part of the body of a patient.

In accordance to various embodiments of the present invention, an emitter-receiver module **200** can be coupled to the hand wand **100**. In some embodiments an emitter-receiver module **200** can emit and receive energy, such as ultrasonic energy. In one embodiment, an emitter-receiver module **200** can be configured to only emit energy, such as ultrasonic energy. In one embodiment, the emitter-receiver module **200** is permanently attachable to the hand wand **100**. In one embodiment, the emitter-receiver module **200** is attachable to and detachable from the hand wand **100**. The emitter-receiver module **200** can be mechanically coupled to the hand wand **100** using a latch or coupler **140**. An interface guide **235** can be useful in assisting the coupling of the emitter-receiver module **200** to the hand wand **100**. In addition, the emitter-receiver module **200** can be electronically coupled to the hand wand **100** and such coupling may include an interface which is in communication with the controller **300**. In one embodiment, an electric coupler at the interface guide **235**, located at a proximal end of an emitter-receiver module **200** provides for electronic communication between the emitter-receiver module **200** and the hand wand **100**, which can both be in electric communication with a

controller 300. The emitter-receiver module 200 can comprise various probe and/or transducer configurations. For example, the emitter-receiver module 200 can be configured for a combined dual-mode imaging/therapy transducer, coupled or co-housed imaging/therapy transducers, or simply a separate therapy probe and an imaging probe. In one embodiment, the hand wand 100 includes a handle with an integrated receptacle for insertion of an emitter-receiver module 200 containing at least a transducer on one end and an electrical cable for attachment to the controller 200 on the other end.

With additional reference to the illustrations in FIGS. 2 and 3, the hand wand 100 can be designed for ergonomic considerations to improve comfort, functionality and/or ease of use of the hand wand 100 by a user, such as, for example, a practitioner or medical professional. The hand wand 100 can be designed to be used ambidextrously. In one embodiment, the use of the hand wand 100 is not diminished by whether it is in a right hand or a left hand. In one embodiment, of the hand wand 100 includes an imaging button 150, a treatment button 160, and an indicator 155 on a top portion of the hand wand 100. Other arrangements of buttons and/or indicators are possible in various embodiments. In one embodiment the hand wand 100 includes a hand rest 148 on a bottom portion and a coupler 140 distal to the flexible connector 145. In one embodiment, the hand rest 148 includes a clearance pocket molded into the hand wand 100 housing which allows a magnet-tipped clutch rod (433 and 432 of FIG. 7) to move back and forth to drive the transducer module's rectilinear motion without hitting the hand wand's housing. According to these aspects, the hand wand 100 can be operated by the user either in a right hand or a left hand. Further to these aspects, the user can control the imaging button 150 and the treatment button 160 with a thumb or finger, such as an index finger. An interior portion of the hand wand 100 can include electronics as well as software, connections, and/or couplings for interfacing to and from the electronics. In one embodiment, the hand wand 100 contains an electronic interface 175 (not illustrated here, but see other figures) in communication with at least one of the imaging button 150 and the treatment button 160. In accordance with one embodiment, the electronic interface 175 can interface with an outside source such as, for example, the controller 300. In various embodiments, the indicator 145 can be an LED, a light, an audio signal, and combinations thereof. In one aspect of the embodiments, the indicator 155 is a LED which can change colors based on different states of the CTS 20. For example the indicator 155 can be one color (or off) in a standby mode, a second color in an imaging mode and a third color in a treatment mode.

In one embodiment, the emitter-receiver module 200 is configured to removably attach both electronically and mechanically with a hand wand 100. In one embodiment, a motion mechanism 400 (see FIG. 7) is configured to move an ultrasonic transducer 280 in an emitter-receiver module 200 such as is illustrated in various embodiments in FIGS. 4-6. A user can remove the indicated transducer module from its protective, resealable pouch, setting aside the pouch for storing the transducer module between procedures, if necessary. In one embodiment, a hand wand 100 and an emitter-receiver module 200 can be connected by pushing the coupler 140 upwards and sliding the emitter-receiver module 200 into the hand wand 100 as shown in FIG. 1. In one embodiment, when the emitter-receiver module 200 is inserted, the controller 300 automatically detects it and updates the interactive graphical display 310. In one embodiment, the emitter-receiver module 200 locked into

the hand wand 100 once the emitter-receiver module 200 is fully inserted and the coupler 140 at the tip of the hand wand 100 is pushed down. To disconnect the emitter-receiver module 200, the user can lift the coupler 140 at the tip of the hand wand 100 and slide the emitter-receiver module 200 out of the hand wand 100.

FIGS. 4 and 5 illustrate two opposing side views of an embodiment of an emitter-receiver module 200 comprising a housing 220 and an acoustically transparent member 230. In one embodiment, the housing 220 may include a cap 222 that is removable or permanently attachable to the housing 220. In one embodiment, the emitter-receiver module 200 includes an interface guide 235 and/or one or more side guides 240 that can be useful in assisting the coupling of the emitter-receiver module 200 to the hand wand 100. The emitter-receiver module 200 can include a transducer 280 which can emit energy through an acoustically transparent member 230. The acoustically transparent member 230 can be a window, a filter and/or a lens. The acoustically transparent member 230 can be made of any material that is transparent to the energy that is emitted by the transducer 280. In one embodiment, the acoustically transparent member 230 is transparent to ultrasound energy.

In various embodiments, the transducer 280 is in communication with the controller 300. In one embodiment, the transducer 280 is electronically coupled to the hand wand 100 and/or the controller 300. In one embodiment, the housing 220 is sealed by the cap 222 and the structure of the combination of the housing 220 and the cap 222 can hold a liquid (not shown). As illustrated in FIG. 6, an embodiment of the emitter-receiver module 200 housing 220 can have a port 275 which allows interfacing from the hand wand 100 into the transducer module 200 without affecting the integrity of the sealed structure of the housing 220 and the cap 222. Further, the cap 222 can include one or more ports. For example, a first port 292, a second port 293 and a third port 294. The ports in the cap 222 can be useful for electronically coupling the transducer 280 to the hand wand 100 and/or the controller 300. In one embodiment, at least one of the ports in the cap 222 may be used to interface a sensor 201 that may be useful in the emitter-receiver module 200. The sensor 201 can be in communication with the controller 300. More than one sensor 201 is used in some embodiments.

In various embodiments, as illustrated in the block diagram of FIG. 6, the transducer 280 is movable within the emitter-receiver module 200. The transducer 280 is held by a transducer holder 289. In one embodiment, the transducer holder 289 includes a sleeve 287 which is moved along motion constraining bearings, such as linear bearings, namely, a bar (or shaft) 282 to ensure a repeatable linear movement of the transducer 280. In one embodiment, sleeve 287 is a spline bushing which prevents rotation about a spline shaft 282, but any guide to maintain the path of motion is appropriate. In one embodiment, the transducer holder 289 is driven by a motion mechanism 400, which may be located in the hand wand 100 or in the emitter-receiver module 200. The motion mechanism 400, as is discussed below in relation to FIG. 7, includes a scotch yoke 403 with a movement member 432 and a magnetic coupling 433 on a distal end of the movement member 432. The magnet coupling 433 helps move the transducer 280. One benefit of a motion mechanism such as motion mechanism 400 is that it provides for a more efficient, accurate and precise use of an ultrasound transducer 280, for both imaging and for therapy purposes. One advantage this type of motion mechanism has over conventional fixed arrays of multiple transducers fixed in space in a housing is that the

fixed arrays are a fixed distance apart. By placing transducer **280** on a linear track under controller **300** control, embodiments of the system and device provide for adaptability and flexibility in addition to the previously mentioned efficiency, accuracy and precision. Real time and near real time adjustments can be made to imaging and treatment positioning along the controlled motion by the motion mechanism **400**. In addition to the ability to select nearly any resolution based on the incremental adjustments made possible by the motion mechanism **400**, adjustments can be made if imaging detects abnormalities or conditions meriting a change in treatment spacing and targeting.

In one embodiment, one or more sensors **201** may be included in the emitter-receiver module **200**. In one embodiment, one or more sensors **201** may be included in the emitter-receiver module **200** to ensure that a mechanical coupling between the movement member **432** and the transducer holder **289** is indeed coupled. In one embodiment, an encoder **283** may be positioned on top of the transducer holder **289** and a sensor **201** may be located in a dry portion of the emitter-receiver module **200**, or vice versa (swapped). In various embodiments the sensor **201** is a magnetic sensor, such as a giant magnetoresistive effect (GMR) or Hall Effect sensor, and the encoder a magnet, collection of magnets, or multi-pole magnetic strip. The sensor may be positioned as a transducer module home position. In one embodiment, the sensor **201** is a contact pressure sensor. In one embodiment, the sensor **201** is a contact pressure sensor on a surface of the device to sense the position of the device or the transducer on the patient. In various embodiments, the sensor **201** can be used to map the position of the device or a component in the device in one, two, or three dimensions. In one embodiment the sensor **201** is configured to sense the position, angle, tilt, orientation, placement, elevation, or other relationship between the device (or a component therein) and the patient. In one embodiment, the sensor **201** comprises an optical sensor. In one embodiment, the sensor **201** comprises a roller ball sensor. In one embodiment, the sensor **201** is configured to map a position in one, two and/or three dimensions to compute a distance between areas or lines of treatment on the skin or tissue on a patient. Motion mechanism **400** can be any motion mechanism that may be found to be useful for movement of the transducer **280**. Other embodiments of motion mechanisms useful herein can include worm gears and the like. In various embodiments of the present invention, the motion mechanism is located in the emitter-receiver module **200**. In various embodiments, the motion mechanism can provide for linear, rotational, multi-dimensional motion or actuation, and the motion can include any collection of points and/or orientations in space. Various embodiments for motion can be used in accordance with several embodiments, including but not limited to rectilinear, circular, elliptical, arc-like, spiral, a collection of one or more points in space, or any other 1-D, 2-D, or 3-D positional and attitudinal motional embodiments. The speed of the motion mechanism **400** may be fixed or may be adjustably controlled by a user. One embodiment, a speed of the motion mechanism **400** for an image sequence may be different than that for a treatment sequence. In one embodiment, the speed of the motion mechanism **400** is controllable by the controller **300**.

Transducer **280** can have a travel distance **272** such that an emitted energy **50** is able to be emitted through the acoustically transparent member **230**. In one embodiment, the travel **272** is described as end-to-end range of travel of the transducer **280**. In one embodiment, the travel **272** of the transducer **280** can be between about 100 mm and about 1

mm. In one embodiment, the length of the travel **272** can be about 25 mm. In one embodiment, the length of the travel **272** can be about 15 mm. In one embodiment, the length of the travel **272** can be about 10 mm. In various embodiments the length of the travel **272** can be about between 0-25 mm, 0-15 mm, 0-10 mm.

The transducer **280** can have an offset distance **270**, which is the distance between the transducer **280** and the acoustically transparent member **230**. In various embodiments of the present invention, the transducer **280** can image and treat a region of interest of about 25 mm and can image a depth less than about 10 mm. In one embodiment, the emitter-receiver module **200** has an offset distance **270** for a treatment at a depth **278** of about 4.5 mm below the skin surface **501** (see FIG. 15).

In various embodiments, transducer modules **200** can be configured for different or variable ultrasonic parameters. For example, in various non-limiting embodiments, the ultrasonic parameter can relate to aspects of the transducer **280**, such as geometry, size, timing, spatial configuration, frequency, variations in spatial parameters, variations in temporal parameters, coagulation formation, depth, width, absorption coefficient, refraction coefficient, tissue depths, and/or other tissue characteristics. In various embodiments, a variable ultrasonic parameter may be altered, or varied, in order to effect the formation of a lesion for the desired cosmetic approach. In various embodiments, a variable ultrasonic parameter may be altered, or varied, in order to effect the formation of a lesion for the desired clinical approach. By way of example, one variable ultrasonic parameter relates to configurations associated with tissue depth **278**. In several embodiments, the transducer module **200** is configured for both ultrasonic imaging and ultrasonic treatment and is operably coupled to at least one controlling device **150**, **160** and a movement mechanism **400**. The transducer module **200** is configured to apply ultrasonic therapy at a first ultrasonic parameter and a second ultrasonic parameter. In various embodiments, the first and second ultrasonic parameters are selected from the group consisting of: variable depth, variable frequency, and variable geometry. For example, in one embodiment, a single transducer module **200** delivers ultrasonic therapy at two or more depths **278**, **278'**. In another embodiment, two or more interchangeable transducer modules **200** each provide a different depth **278** (e.g., one module treats at 3 mm depth while the other treats at a 4.5 mm depth). In yet another embodiment, a single transducer module **200** delivers ultrasonic therapy at two or more frequencies, geometries, amplitudes, velocities, wave types, and/or wavelengths. In other embodiments, two or more interchangeable transducer modules **200** each provide a different parameter value. In one embodiment, a single transducer module **200** may provide at least two different depths **278**, **278'** and at least two different frequencies (or other parameter). Variable parameter options are particularly advantageous in certain embodiments because they offer enhanced control of tissue treatment and optimize lesion formation, tissue coagulation, treatment volume, etc.

FIG. 15 illustrates one embodiment of a depth **278** that corresponds to a muscle depth. In various embodiments, the depth **278** can correspond to any tissue, tissue layer, skin, dermis, fat, SMAS, muscle, or other tissue. In some embodiments, different types of tissue are treated to provide synergistic effects, thus optimizing clinical results. In another embodiment, the emitter-receiver module has an offset distance **270** for a treatment at a depth **278** of about 3.0 mm below the surface **501**. In various embodiments, this offset



distance may be varied such that the transducer **280** can emit energy to a desired depth **278** below a surface **501**. In various embodiments, in a treatment mode, bursts of acoustic energy from the transducer **280** can create a linear sequence of individual thermal lesions **550**. In one embodiment the individual thermal lesions **550** are discrete. In one embodiment the individual thermal lesions **550** are overlapping. In various embodiments, the transducer **280** can image to a depth roughly between 1 and 100 mm. In one embodiment, the transducer imaging depth can be approximately 20 mm. In one embodiment, the transducer **280** can treat to a depth of between about zero (0) to 25 mm. In one embodiment, the transducer treatment depth can be approximately 4.5 mm.

In any of the embodiments described herein, the transducer treatment depth can be approximately 0.5 mm, 1 mm, 1.5 mm, 2 mm, 3 mm, 4 mm, 4.5 mm, 5 mm, 6 mm, 10 mm, 15 mm, 20 mm, 25 mm, or any other depth in the range of 0-100 mm. Varied depth treatment, including treatment of the same tissue at different depths or treatment of different tissues, can increase clinical results by providing synergistic effects.

In various embodiments of the present invention, a transducer **280** is capable of emitting ultrasound energy for imaging, diagnostics, or treating and combinations thereof. In one embodiment, the transducer **280** is configured to emit ultrasound energy at a specific depth in a region of interest to target a region of interest of a specific tissue such as a corrugator supercillii muscle as described below. In this embodiment, the transducer **280** may be capable of emitting unfocused or defocused ultrasound energy over a wide area of the region of interest **65** for treatment purposes (see FIGS. **12** and **22**). In one embodiment, the emitter-receiver module **200** contains a transducer **280** that can image and treat a region of tissue up to 25 mm long and can image a depth of up to 8 millimeters. Treatment occurs along a line less than or equal to the transducer's active length, which is indicated in one embodiment by guide marks (not illustrated here) on the sides of the emitter-receiver module **200** near an acoustically transparent member **230** along the surface adjacent to the patient's skin. In one embodiment, a marked guide at the front tip of the transducer **280** represents the center of the treatment line. In one embodiment of a treatment mode, bursts of sound energy create a linear sequence of individual thermal coagulation zones. In one embodiment the individual thermal coagulation zones are discrete. In one embodiment the individual thermal coagulation zones are overlapping. A label (not illustrated here) may be applied or etched on a side or top surface of the emitter-receiver module **200** to provide the transducer **280** type, expiration date, and other information. In one embodiment, an emitter-receiver module **200** can be configured with a label for tracking the type transducer **280** used, treatment frequency and treatment depth, a unique serial number, a part number, and date of manufacture. In one embodiment, the emitter-receiver modules **200** are disposable. In one embodiment, the system tracks use of the emitter-receiver modules **200** in order to determine the remaining life of the emitter-receiver module **200** as transducer life diminishes over time and/or usage. Once a transducer **280** has diminished capacity, the emitter-receiver module **200** may work less effectively in performing its functions. In one embodiment, the emitter-receiver module **200** or controller **300** will track usage and prevent additional usage of an emitter-receiver module **200** beyond a recommended usage life in order to preserve the safety and effectiveness of the device. This safety feature can be configured based on test data.

In one embodiment, an emitter-receiver module **200** is configured with a treatment frequency of approximately 4 MHz, a treatment depth of approximately 4.5 mm and an imaging depth range of roughly 0-8 mm. In one embodiment, an emitter-receiver module **200** is configured with a treatment frequency of approximately 7 MHz, a treatment depth of approximately 3.0 mm and an imaging depth range of roughly 0-8 mm. In one embodiment, an emitter-receiver module **200** is configured with a treatment frequency of approximately 7 MHz, a treatment depth of approximately 4.5 mm and an imaging depth range of roughly 0-8 mm.

Transducer **280** may comprise one or more transducers for facilitating imaging and/or treatment. The transducer **280** may comprise a piezoelectrically active material, such as, for example, lead zirconate titanate, or other piezoelectrically active materials such as, but not limited to, a piezoelectric ceramic, crystal, plastic, and/or composite materials, as well as lithium niobate, lead titanate, barium titanate, and/or lead metaniobate, including piezoelectric, electrically conductive, and plastic film layers deposited on spherically focused backing material. In addition to, or instead of, a piezoelectrically active material, the transducer **280** may comprise any other materials configured for generating radiation and/or acoustical energy. The transducer **280** may also comprise one or more matching and/or backing layers coupled to the piezoelectrically active material. The transducer **280** may also be configured with single or multiple damping elements.

In one embodiment, the thickness of a transduction element of the transducer **280** may be configured to be uniform. That is, the transduction element may be configured to have a thickness that is generally substantially the same throughout. In another embodiment, the transduction element may also be configured with a variable thickness, and/or as a multiple damped device. For example, the transduction element of the transducer **280** may be configured to have a first thickness selected to provide a center operating frequency of a lower range, for example from about 1 MHz to about 10 MHz. The transduction element may also be configured with a second thickness selected to provide a center operating frequency of a higher range, for example from about 10 MHz to greater than 100 MHz.

In yet another embodiment, the transducer **280** is configured as a single broadband transducer excited with two or more frequencies to provide an adequate output for raising a temperature within a treatment area of the region of interest to the desired level as discussed herein. The transducer **280** may be configured as two or more individual transducers, such that each transducer **280** may comprise a transduction element. The thickness of the transduction elements may be configured to provide center-operating frequencies in a desired treatment range. For example, in one embodiment, the transducer **280** may comprise a first transducer configured with a first transduction element having a thickness corresponding to a center frequency range of about 1 MHz to about 10 MHz, and a second transducer configured with a second transduction element having a thickness corresponding to a center frequency range of about 10 MHz to greater than 100 MHz. Various other combinations and ranges of thickness for a first and/or second transduction element can be designed to focus at specific depths below a surface **501**, for specific frequency ranges, and/or specific energy emissions.

The transduction elements of the transducer **280** can be configured to be concave, convex, and/or planar. In one embodiment, the transduction elements are configured to be concave in order to provide focused energy for treatment of

the region of interest. Additional embodiments of transducers are disclosed in U.S. patent application Ser. No. 10/944, 500, entitled "System and Method for Variable Depth Ultrasound Treatment," incorporated in its entirety herein by reference.

Moreover, the transducer **280** can be any distance from the surface **501**. In that regard, it can be far away from the surface **501** disposed within a long transducer or it can be just a few millimeters from the surface **501**. This distance can be determined by design using the offset distance **270** as described herein. In certain embodiments, positioning the transducer **280** closer to the surface **501** is better for emitting ultrasound at higher frequencies. Moreover, both two and three dimensional arrays of elements can be used in the present invention. Furthermore, the transducer **280** may comprise a reflective surface, tip, or area at the end of the transducer **280** that emits ultrasound energy. This reflective surface may enhance, magnify, or otherwise change ultrasound energy emitted from the CTS **20**.

In various embodiments any set of one or more transducers **280** can be used for various functions, such as separate treat/image or dual-mode (both treat/image) transducers or a treat-only version. In various embodiments the imaging element(s) can be on the side (adjacent to) or at any relative position, attitude, and/or height, or even within the therapy element(s). One or more therapy depths and frequencies can be used and one or more imaging elements or one or more dual-mode elements. In various embodiments any controllable means of moving the active transduction element(s) within the emitter-receiver module **200** housing constitute viable embodiments.

In various embodiments, the emitter-receiver module **200** can also be configured in various manners and comprise a number of reusable and/or disposable components and parts in various embodiments to facilitate its operation. For example, the emitter-receiver module **200** can be configured within any type of transducer probe housing or arrangement for facilitating the coupling of the transducer **280** to a tissue interface, with such housing comprising various shapes, contours and configurations. The emitter-receiver module **200** can comprise any type of matching, such as for example, electric matching, which may be electrically switchable, multiplexer circuits and/or aperture/element selection circuits, and/or probe identification devices, to certify probe handle, electric matching, transducer usage history and calibration, such as one or more serial EEPROM (memories).

In various embodiments, the emitter-receiver module **200** may also comprise cables and connectors, motion mechanisms, motion sensors and encoders, thermal monitoring sensors, and/or user control and status related switches, and indicators such as LEDs. In one embodiment, a motion mechanism similar to the motion mechanism **400** described in the hand wand **100** may be used to drive the emitter-receiver module **200** from within the emitter-receiver module **200**. In one embodiment, a hand wand **100** is electrically connectable to the emitter-receiver module **200** to drive the emitter-receiver module **200** from within itself. In various embodiments, a motion mechanism (in any of the embodiments described herein) may be used to controllably create multiple lesions, or sensing of probe motion itself may be used to controllably create multiple lesions and/or stop creation of lesions **550**, as discussed herein. For example in one embodiment, for safety reasons if the emitter-receiver module **200** is suddenly jerked or is dropped, a sensor can relay this action to the controller **300** to initiate a corrective action or shut down the emitter-receiver module **200**. In

addition, an external motion encoder arm may be used to hold the probe during use, whereby the spatial position and attitude of the emitter-receiver module **200** is sent to the controller **300** to help controllably create lesions **550**. Furthermore, other sensing functionality such as profilometers or other imaging modalities may be integrated into the emitter-receiver module **200** in accordance with various embodiments. In one embodiment, pulse-echo signals to and from the emitter/receiver module **200** are utilized for tissue parameter monitoring of the treatment region **550**.

Coupling components can comprise various devices to facilitate coupling of the emitter-receiver module **200** to a region of interest. For example, coupling components can comprise cooling and acoustic coupling system configured for acoustic coupling of ultrasound energy and signals. Acoustic cooling/coupling system with possible connections such as manifolds may be utilized to couple sound into the region-of-interest, control temperature at the interface and deeper into tissue, provide liquid-filled lens focusing, and/or to remove transducer waste heat. The coupling system may facilitate such coupling through use of one or more coupling mediums, including air, gases, water, liquids, fluids, gels, solids, and/or any combination thereof, or any other medium that allows for signals to be transmitted between the transducer **280** and a region of interest. In one embodiment one or more coupling media is provided inside a transducer. In one embodiment a fluid-filled emitter-receiver module **200** contains one or more coupling media inside a housing. In one embodiment a fluid-filled emitter-receiver module **200** contains one or more coupling media inside a sealed housing, which is separable from a dry portion of an ultrasonic device.

In addition to providing a coupling function, in accordance with one embodiment, the coupling system can also be configured for providing temperature control during the treatment application. For example, the coupling system can be configured for controlled cooling of an interface surface or region between the emitter-receiver module **200** and a region of interest and beyond by suitably controlling the temperature of the coupling medium. The suitable temperature for such coupling medium can be achieved in various manners, and utilize various feedback systems, such as thermocouples, thermistors or any other device or system configured for temperature measurement of a coupling medium. Such controlled cooling can be configured to further facilitate spatial and/or thermal energy control of the emitter-receiver module **200**.

In one embodiment, the emitter-receiver module **200** is connected to a motion mechanism **400** in the hand wand **100**. In one embodiment, the motion mechanism **400** may be in the emitter-receiver module **200**. One embodiment of a motion mechanism **400** is illustrated in FIG. 7, which depicts a two phase stepper motor **402** and a scotch yoke **403** to produce a linear motion. The stepper motor **402** rotates as indicated by arrow **405** which moves a pin **404** in a circular path. The pin **404** slides in a slot **406** of the scotch yoke **403**. This causes the scotch yoke **403** to move in a linear fashion. The scotch yoke **403** is held by guides **410** and glide members **412** may be between the scotch yoke **403** and guide **410**. In one embodiment, a guide **410** is a shoulder screw. Embodiments of the glide member **412** may include any material or mechanical device that lowers a coefficient of friction between the guide **410** and the scotch yoke **403**, or any linear bearings. For example, in various embodiments the glide member **412** can be at least one of an elastomeric

material, a lubricant, ball bearings, a polished surface, a magnetic device, pressurized gas, or any other material or device useful for gliding.

A sensor **425** operates as one embodiment of a position sensor by reading an encoder **430** which is mounted on the scotch yoke **403**. In one embodiment, the encoder strip **430** is an optical encoder which has a pitch in a range from about 1.0 mm to about 0.01 mm. In one embodiment, the pitch may be about 0.1 mm. The encoder strip **430** can include index marks at each end of its travel. The direction of travel of the encoder strip **430** can be determined by comparing phases of two separate channels in the optical sensor **425**. In one embodiment, the encoder strip **430** has one, two or more home positions which may be useful in calibrating for a position and travel of the scotch yoke **403**.

In one embodiment, the movement of the scotch yoke **403** is transferred through the movement mechanism **432** such that the transducer **280** moves in a linear fashion inside of the emitter-receiver module **200**. In one embodiment, the scotch yoke **403** includes a movement member **432** and a magnetic coupling **433** on a distal end of the movement member **432**. The movement member **432** can be sized to travel through or within a liquid-tight seal.

Transducer **280** can have a travel distance **272**. The coupling system may facilitate such coupling. With reference to FIG. **8**, a block diagram illustrates various embodiments of the CTS **20**. In one embodiment, the controller **300** includes a controller subsystem **340**, a therapy subsystem **320**, an imaging subsystem **350**, an embedded host **330** (with software) and an interactive graphical display **310**. In one embodiment, the therapy subsystem **320**, the controller subsystem **340**, and/or the imaging subsystem **350** is interfaced with the hand wand **100** and/or the emitter-receiver module **200**. In various embodiments, the CTS **20** has built into the controller **300** limits as to an amount of energy **50** that can be emitted from the emitter-receiver module **200**. These limits can be determined by time of emission, frequency of the energy emitted, power of energy, a temperature, and/or combinations thereof. The temperature may be from monitoring the surface **501** and/or monitoring the emitter-receiver module **200**. According to one embodiment the limits may be preset and cannot be changed by the user.

According to various embodiments, when the emitter-receiver module **200** is coupled to the surface **501**, which may be a skin surface of the subject, the CTS **20** can image and/or treat a treatment area **272**. In some aspects of these embodiments, the imaging by the CTS **20** can be over essentially the entire treatment area **272** at specified depths **278** below the surface **501**. In some aspects of these embodiments, the treatment can include discrete energy emissions **50** to create lesion **550** at intervals along the treatment area **272** and at specified depths **278**. In one embodiment the intervals are discrete. In one embodiment the intervals are overlapping.

In various embodiments the imaging subsystem **350** may be operated in a B-mode. The imaging subsystem **350** can provide support to the emitter-receiver module **200** such that the emitter-receiver module **200** can have emission energy **50** from a frequency of about 10 MHz to greater than 100 MHz. In one embodiment, the frequency is about 18 MHz. In one embodiment, the frequency is about 25 MHz. The imaging subsystem **350** can support any frame rate that may be useful for the applications. In some embodiments, the frame rate may be in a range from about 1 frames per second (hereinafter "FPS") to about 100 FPS, or from about 5 FPS to about 50 FPS or from about 5 FPS to about 20 FPS nominal. An image field of view may be controlled by the

image area of the transducer **280** in a focus of the transducer **280** at a specific depth **278** below the surface **501** as discussed herein. In various embodiments, the field of view can be less than 20 mm in depth and 100 mm in width or less than 10 mm in depth and less than 50 mm in width. In one embodiment, a particularly useful image field of view is about 8 mm in depth by about 25 mm in width.

A resolution of the field of view can be controlled by the graduation of the movement mechanism **400**. As such, any pitch may be useful based on the graduation of the motion mechanism **400**. In one embodiment, the resolution of the field of view may be controlled by the resolution of an encoder **430** and sensor **425**. In one embodiment the image field of view can have a pitch in the range of 0.01 mm to 0.5 mm or from about 0.05 mm to about 0.2 mm. In one embodiment, a particularly useful line pitch for the image field of view is about 0.1 mm.

According to various embodiments, the imaging subsystem **350** can include one or more functions. In one embodiment, the one or more functions can include any of the following B-mode, scan image, freeze image, image brightness, distance calipers, text annotation for image, save image, print image, and/or combinations thereof. In various embodiments of the present invention, the imaging subsystem **350** contains pulse echo imaging electronics.

Various embodiments of the therapy subsystem **320** comprise a radio frequency (hereinafter "RF") driver circuit which can deliver and/or monitor power going to the transducer **280**. In one embodiment, the therapy subsystem **320** can control an acoustic power of the transducer **280**. In one embodiment, the acoustic power can be from a range of 1 watt (hereinafter "W") to about 100 W in a frequency range from about 1 MHz to about 10 MHz, or from about 10 W to about 50 W at a frequency range from about 3 MHz to about 8 MHz. In one embodiment, the acoustic power and frequencies are about 40 W at about 4.3 MHz and about 30 W at about 7.5 MHz. An acoustic energy produced by this acoustic power can be between about 0.01 joule (hereinafter "J") to about 10 J or about 2 J to about 5 J. In one embodiment, the acoustic energy is in a range less than about 3 J.

In various embodiments the therapy subsystem **320** can control a time on for the transducer **280**. In one embodiment, the time on can be from about 1 millisecond (hereinafter "ms") to about 100 ms or about 10 ms to about 50 ms. In one embodiment, time on periods can be about 30 ms for a 4.3 MHz emission and about 30 ms for a 7.5 MHz emission.

In various embodiments, the therapy subsystem **320** can control the drive frequency of the transducer **280** moving across the travel **272**. In various embodiments, the frequency of the transducer **280** is based on the emitter/receiver **200** connected to the hand wand **100**. According to some embodiments, the frequency of this movement may be in a range from about 1 MHz to about 10 MHz, or about 4 MHz to about 8 MHz. In one embodiment, the frequencies of this movement are about 4.3 MHz or about 7.5 MHz. As discussed herein, the length of the travel **272** can be varied, and in one embodiment, the travel **272** has a length of about 25 mm.

According to various embodiments, the therapy subsystem **320** can control the line scan along the travel **272** and this line scan can range from 0 to the length of the distal of the travel **272**. In one embodiment, the line scan can be in a range from about 0 to about 25 mm. According to one embodiment, the line scan can have incremental energy emissions **50** having a treatment spacing **295** and this treatment spacing can range from about 0.01 mm to about 25

mm or from 0.2 mm to about 2.0 mm. In one embodiment, treatment spacing **295** is about 1.5 mm. In various embodiments, the treatment spacing **295** can be predetermined, constant, variable, programmable, and/or changed at any point before, during or after a treatment line. The resolution of the line scan is proportional to the resolution of the motion mechanism **400**. In various embodiments, the resolution that is controllable by the therapy subsystem **320** is equivalent to the resolution controllable by the imaging subsystem **350** and, as such, can be in the same range as discussed for the imaging subsystem **350**.

In various embodiments, the therapy subsystem **320** can have one or more functions. In one embodiment, the one or more functions can include any of the following: emission energy control, treatment spacing, travel length, treatment ready, treatment, treatment stop, save record, print record, display treatment, and/or combinations thereof.

In various embodiments, the control subsystem **340** includes electronic hardware which mechanically scans the transducer **280** for one or more functions. In one embodiment, one or more functions that can be scanned by the controller subsystem **340** can include scanning the transducer **280** for imaging, a position of the transducer **280** for imaging, scan slip positions of the transducer **280** at locations for therapy, controls therapy hardware settings, provides other control functions, interfacing with the embedded host **330**, and/or combinations thereof. In one embodiment the locations are discrete. In one embodiment the locations are overlapping.

In various embodiments, an embedded host **330** is in two-way communication with the controller **340** and the graphical interface **310**. In one embodiment, data from the controller **340** can be converted to a graphical format by the embedded host **330** and then transferred to the graphical interface **310** for displaying imaging and/or treatment data.

In one embodiment, commands can be entered by a user employing the graphical interface **310**. The commands entered by use of the graphical interface **310** can be communicated to embedded host **330** and then communicated to controller **340** for control and operation of the therapy subsystem **320**, the imaging subsystem **350**, the hand wand **100**, and/or the emitter-receiver module **200**. In various embodiments, the embedded host **330** can include a processing unit, memory, and/or software.

In various embodiments, when the imaging button **150** is pressed the CTS **20** enters an imaging sequence in which the imaging subsystem **350** acquires scan lines which are transferred to the embedded host **330** for data conversion and/or graphical conversion which is then communicated to the graphical interface **310**. While the system is operating in the imaging sequence, the imaging button **150** may be pressed again which puts the CTS **20** into a ready state. In an aspect of this embodiment, an audio warning or visual display such as the indicator **155** may be initiated to alert the user that the CTS **20** is in the ready state. In the ready state, the controller subsystem **340** communicates with the embedded host **330** to acquire users entered treatment settings. These treatment settings can be checked and can be verified and converted to hardware parameter in the controller subsystem **340**. In one embodiment, such set hardware parameters can include treatment timing, cadence, time on, time off, RF driver power, voltage levels, acoustic power output, oscillator frequency, therapy transducer frequency, treatment spacing, travel, motion mechanism speed, and/or combinations thereof. The CTS **20** may remain in the ready state indefinitely or may be timed out after a set time period.

In various embodiments of the present invention, when the CTS **20** is in the ready state, the treatment button **160** may be activated. This activation of the treatment button **160** commences a treatment sequence. The treatment sequence is controllable by the therapy subsystem **320** which executes the treatment sequence along with the controller subsystem **340** and independently of the embedded host **330**. The treatment sequence is delivered in real time and last one of the length of the activating of the treatment button **160** or a programmed time downloaded from the embedded host **330** into the controller subsystem **340** and/or the therapy subsystem **320**.

In various embodiments, safety features can be designed in the CTS **20** to ensure safe use, imaging, and treatment. In various embodiments, the embedded host **330** is in communication with data port **390** which can comprise either one-way or two-way communication between the data port **390** and the embedded host **330**. The data port **390** can interface any electronic storage device, for example, the data port **390** can be interfaced for one or more of a USB drive, a compact flash drive, a secured digital card, a compact disc, and the like. In one embodiment, a storage device through data port **390** to the embedded host **330** can download treatment records or software updates. In another aspect of these embodiments, the storage device can be a two-way communication through data port **390** to the embedded host **330** such that a treatment protocol can be downloaded to the embedded host **330** and CTS **20**. A treatment protocol can include parameters, imaging data, treatment data, date/time, treatment duration, subject information, treatment location, and combinations thereof, and the like which can be uploaded by and/or downloaded from the embedded host **330** to the storage device via the data port **390**. In one embodiment, a second data port (not shown) may be located on the back of the controller. The second data port may provide power and/or data to a printer.

In various embodiments, the CTS **20** includes a lock **395**. In one embodiment, in order to operate CTS **20**, lock **395** must be unlocked so that power switch **393** may be activated. In one embodiment, the power may remain on as the lock **395** is unlocked and locked successively and different parameters are entered. A key **396** (not illustrated) may be needed to unlock the lock **395**. Examples of keys **396** useful herein include a standard metal tooth and groove key, or an electronic key. In some embodiments, an electronic key **396** may be digitally encoded to include user information and collect data and/or time usage of CTS **20**. In one embodiment, an electronic key is particularly useful with CTS **20** may be a USB drive with encryption such that inserting the USB drive key into lock **395** the CTS **20** may be activated. In various embodiments, a software key can be configured to indicate a condition or status to the user, lock the system, interrupt the system, or other feature.

With reference to FIG. **9**, a CTS **20** layout block diagram is illustrated according to various embodiments of the present invention. In accordance with the aspects of these embodiments, the controller **300** can include several electronic sections. Included in these electronic sections can be a power supply **350** which provides power to CTS **20** including the controller **300**, the hand wand **100**, and/or the emitter-receiver module **200**. In one embodiment, the power supply **350** can supply power to a printer or other data output device. The controller **300** can include the controller subsystem **340** as described herein, the host **330**, a graphical interface **310**, an RF driver **352** and a front panel flex circuit **345**. The RF driver **352** can provide power to the transducer **280**. The embedded host **330** can be a host computer which

may be used collecting user input, transferring it to the controller subsystem **340** and for displaying images and system statuses on the graphical interface **310**. The power supply **350** can be convertible for use internationally based on different voltage inputs and typically is a medical grade power supply. The power supply may be plugged into a standard wall socket to draw power or may draw power from a battery or any other alternative source that may be available.

The graphical interface **310** displays images and systems status as well as facilitates the user interface for entering commands to control the CTS **20**. The controller subsystem **340** can control the imaging subsystem **350**, the therapy subsystem **320**, as well as interfacing and communicating treatment protocol to the hand wand **100** and the emitter-receiver module **200**, as described herein. In one embodiment, the controller subsystem **340** not only sets treatment parameters but also monitors the status of such treatment and transfers such status to the host **330** for display on display/touch screen **310**. The front panel flex circuit **345** can be a printed circuit cable that connects the controller **300** to the interface cable **130**. In one embodiment, the cable **130** can include a quick connect or release, multi-pin connector plug which interfaces to the front panel flex circuit **345** as described herein. The cable **130** allows for interfacing of the controller **300** with the hand wand **100** and the emitter-receiver module **200** as described herein.

Now with reference to FIG. **10**, the hand wand **100** includes the hand piece imaging sub-circuits **110**, encoder **420**, sensor **425**, image **150** and treat **160** switches, motor **402**, status light **155**, and interconnect and flex interconnect **420**. The hand wand **100** interfaces with spring pin flex **106** and spring pin connector **422** which can be used for hardware, software and/or power interface from the hand wand **100** to the emitter-receiver module **200**.

In various embodiments of the present invention, the emitter-receiver module **200** can include a probe ID and connector PCB **224**. The probe ID and connector PCB can include a secure EEPROM. The probe ID and connector PCB **224** can be interfaced with a PCB located in a dry portion of the emitter-receiver module **200** and interfaced with the transducer **280**. The transducer **280** is typically located in the liquid portion of the emitter-receiver module **200**. In one embodiment, the emitter-receiver module **200** can be connected to the hand wand **100** via the spring pin flex **106** and spring pin connector **422** which can be a twelve contact spring pin connector that is recessed in the hand wand **100**. The spring pin flex **106** with its twelve contact spring pin connector can be connected to the probe ID and connector PCB **224** which can include gold plated contacts. In one embodiment, the probe ID and connector PCB **224** can include a usage counter that disables the emitter-receiver module **200** after a pre-set usage. In various embodiments, the pre-set usage can range from a single treatment sequence to multiple treatment sequences. In one embodiment, the pre-set usage is determined by a pre-set time on of the transducer **280**. In one embodiment, the pre-set usage is a single cycle of treatment sequences. In this aspect, essentially the emitter-receiver module **200** is disposable after each use. In one embodiment, the system automatically shuts off or otherwise indicates to a user that the emitter-receiver module **200** should be replaced. The system may be programmed to shut off or otherwise indicate replacement based on at least one of usage time, energy delivered, shelf time, or a combination thereof.

With further reference to FIG. **10**, a block diagram illustrates an interconnection of the hand wand **100** and the

emitter-receiver module **200**. The hand wand **100** can include a therapy protection switch which can provide a electric isolation between treat and image functions. A transducer pulse generated by the controller subsystem **340** can be received by matching network **173**. In one embodiment, a single transducer **280** can be used for therapy without imaging. In another embodiment one dual-mode transducer can be used for therapy and imaging. In another embodiment, two transducers **280** can be used for therapy and imaging. In yet another embodiment, therapy is done at relatively low frequencies (such as, in one embodiment, nominally 4 and 7 MHz) with a first transducer **280**, and a second higher frequency transducer for imaging (such as, in one embodiment, 18-40 MHz or more).

The imaging sub-circuits **110** can include a time gain control amplifier and tunable bypass filter which can receive echoes produced by the imaging portion of the transducer **280**. The imaging can be controlled by imaging switch **150**. Power can be transferred from the controller **300** via cable **130**. Such power can be directed to the imaging sub-circuits **110**, the image switch **150** and the treatment switch **160**. Such power can also be provided to the stepper motor **402**, the encoder **425**, the probe IO switch **181**, the hand wand temperature sensor **183**, and a hand wand ID EEPROM **169**. All of the electronics described in FIG. **10** for the hand wand **100** can be mounted on the circuit board with an interface to cable **130** and/or an interface to the emitter-receiver module **200**.

The emitter-receiver module **200** includes an interface connectable to the hand wand **100** as described in FIG. **9**. The emitter-receiver module **200** can include any type of storage device **249**. In one embodiment, the storage device **249** is part of the electric interface mating circuit board **224** and electric matching **243** circuit board. In one embodiment, the storage device **249** is a permanent storage device. In one embodiment, the storage device **249** is a non-volatile member. In one embodiment, the storage device **249** is an EEPROM. In one embodiment, the storage device **249** is a secure EEPROM. In one embodiment, a transducer PCB can contain calibration data and information storage in the secure EEPROM. Further in this aspect, the emitter-receiver module **200** includes a sensor which measures a fluid temperature of the fluid portion of the emitter-receiver module **200**, a matching network **243** interfaced to the treatment portion of the transducer **280**. In various embodiments, the storage device **249** can contain digital security information, build date, transducer focus depth, transducer power requirements, and the like. In one embodiment, the storage device **249** can include a timer which inactivates the emitter-receiver module **200** for use with CTS **20** after a predetermined shelf life has expired. The emitter-receiver module **200** can include a position encoder **283**, such as a magnet, connected to the transducer **280** and a sensor **241**, such as a Hall sensor, connected to the stationary emitter/receiver housing **220** via circuit board. The position encoder **283** and the position sensor **241** can act as a sensor for determining a transducer **280** home position and/or movement as described herein. The imaging portion of the transducer **280** can receive a transducer RF signal from the controller **300**.

Since it is possible for a user to potentially touch the spring pin flex contacts **422** when an emitter-receiver module **200** is not attached, the current must be able to be turned off in this situation to provide safety to the user. To provide such safety, contact pins **422** on opposite ends of the spring pin flex **106** can be used to detect an attachment of the emitter-receiver module **200** to the hand wand **100**. As

discussed above, motion mechanism **400** can be connected to the transducer **280** to provide linear movement of the transducer along the travel **272**.

In various embodiments, the CTS **20** can include various safety features to provide a safe environment for the user and/or the subject that receives treatment. One embodiment, the CTS **20** can include at least one of calibration data, safe operating area, high mismatch detect, high current detect, RF driver supply voltage monitoring, forward and reverse electric power monitoring, acoustic coupling detection, acoustic coupling complete, treatment position sensing, and combinations thereof.

For example, calibration data can include certain characteristics for a given emitter-receiver module **200** that reside on the storage device **249**. Such characteristics can include but are not limited to unique and traceable serial numbers, probe identification, frequency setting, acoustic power versus voltage lookup table, electric power versus voltage lookup table, maximum power levels, date codes, usage, other information, and/or combinations thereof. For example, a safe operating area safety feature limits energy output for a given emitter-receiver module **200** is limited to a safe operating area. Such a limitation may include for a given emitter-receiver module **200**, the acoustic power level supplied by the power supply voltage and the time On may be limited in the hardware and/or software of the controller **300** and/or the emitter-receiver module **200**.

An example of a high mismatch detect safety feature can include if a fault occurs in reflective power from the load of the emitter-receiver module **200** is large as compared a forward power such as the emitter-receiver module **200** failure, open circuit, or high reflective energy, then a system Stop state would automatically and indefinitely be invoked by comparator circuit latched in the hardware of the controller **300** and a notification of such fault would appear on the display/touch screen **310** to alert the user. An example of a high current detect safety feature can include if a driver fault or load fault occurs such that a large current draw is detected such as for example a short circuit or electrical component failure, then a Stop state would be automatically and immediately invoked as located in the hardware of the controller **300** and a notice would be displayed on the display/touch screen **310** to alert the user.

An example of RF driver supply voltage monitoring safety feature can include the CTS **20** measuring the RF driver power supply voltage setting before, during and after treatment to assure that the voltage is at the correct level. If it is determined that the voltage is outside the correct level, then a Stop state would be automatically and immediately invoked and a notice would be displayed on the display/touch screen **310** to alert the user. An example of a safety feature includes monitoring the stepper motor **402** during treatment and determining if it is in an acceptable range such that the transducer **280** is properly moving along the travel **272** at a predetermined rate or frequency. If it is determined that the stepper motor **402** is not at an expected position, a notification is issued to alert the user.

An example of an acoustic coupling safety feature includes an imaging sequence that indicates to the user that the emitter-receiver module **200** is acoustically coupled to the surface **501** before and after treatment. An image sequence confirms that the transducer **280** is scanning a treatment area.

Still further, other safety features may be included such as thermal monitoring, use of a stop switch, a probe sensor, or a combination thereof. An example of thermal monitoring can include monitoring the temperature of the liquid portion

of the emitter-receiver module **200**, monitoring the temperature of the hand wand **100**, monitoring the temperature of the controller **300**, monitoring the temperature of the controller subsystem **340** and/or monitoring the temperature of the RF driver **352**. Such temperature monitoring assures that the devices described operate within temperatures that are acceptable and will provide notification if a temperature is outside an acceptable range thus alerting the user.

A stop switch can be included in CTS **20** such that when a user hits the stop switch the system moves to a safe and inactive state upon activation of the stop switch. An example of a probe sense fail safe can include immediately stopping imaging and/or treatment if the emitter-receiver module **200** is disconnected from the hand wand **100** while in use. In one embodiment, the CTS **20** can include a system diagnostic which can include software checks for errors, unexpected events and usage. The system diagnostics may also include maintenance indicator that tracks the usage of the CTS **20** and notifies the user that maintenance is needed for the system. Other safety features may be included in the CTS **20** that are well known in the art such as fuses, system power supply over voltage and over current limiting, as well as standardized protections such as fire safety ratings, electrical safety ratings, ISO/EN 60601 compliance and the like.

In various embodiments, the CTS **20** includes a removable transducer module **200** interfaced to a hand enclosure **100** having at least one controller button (**150** and/or **160**) such that the transducer module **200** and the controller button (**150** and/or **160**) is operable using only one hand. In an aspect of the embodiments, the transducer module **200** provides ultrasound energy for an imaging function and/or a treatment function. In another aspect of the embodiments, the device includes a controller **300** coupled to the hand-held enclosure **100** and interfaced to the transducer module **200**. In a further aspect of these embodiments, the controller **300** controls the ultrasound energy of and receives a signal from the transducer module **200**. The controller **300** can have a power supply providing power for the ultrasound energy. In still another aspect of the embodiments, the device is used in aesthetic imaging and treatment on a brow of a patient.

FIG. **11** illustrates a schematic drawing of anatomical features of interest in the head and face region of a patient **500**, including a trigeminal nerve **502**, a facial nerve **504**, a parotid gland **506** and a facial artery **508**. In one embodiment, the anatomical features of interest are areas to be treated with care or to be noted, treated with care, or even avoided during treatment. FIGS. **12-14** illustrate one region of interest **65** (hereinafter "ROI **65**") and a cross-sectional tissue portion **10** along the line **23-23** of the ROI **65** on a subject **500**, such as may be used for example when performing a brow lift. This cross-sectional tissue portion **10** can be located anywhere in the ROI **65** and can in any direction or of any length with in the ROI **65**. Of course, the subject **500** can be a patient that may be treated with a brow lift. The cross-sectional portion tissue **10** includes a surface **501** in a dermal layer **503**, a fat layer **505**, a superficial muscular aponeurotic system **507** (hereinafter "SMAS **507**"), and a facial muscle layer **509**. The combination of these layers in total may be known as subcutaneous tissue **510**. Also illustrated in FIG. **14** is a treatment zone **525** which is below the surface **501**. In one embodiment, the surface **501** can be a surface of the skin of a subject **500**. Although the term facial muscle may be used herein as an example, the inventors have contemplated application of the device to any tissue in the body. In various embodiments, the

device and/or methods may be used on muscles (or other tissue) of the face, neck, head, arms, legs, or any other location in the body.

Facial muscle tissue is capable of contraction and expansion. Skeletal muscle is a fibrous tissue used to generate stress and strain. For example, skeletal muscles in the forehead region can produce frowning and wrinkles. There are several facial muscles within the brow or forehead including the epicranium muscle, the corrugator supercilii muscle, and the procerus muscle. These facial muscles are responsible for movement of the forehead and various facial expressions. Besides facial muscles, other tissues exist in the brow region that also can lead to wrinkles on the brow.

In accordance with one embodiment of the present invention, methods for ultrasound cosmetic treatment of tissue using one cosmetic treatment system are provided. The ultrasound energy can be focused, unfocused or defocused and is applied to a ROI 65 containing one of facial muscle tissue or dermal layers or fascia to achieve a therapeutic effect, such as a tighten of a brow of a subject 500.

In various embodiments, certain cosmetic procedures that are traditionally performed through invasive techniques are accomplished by targeting energy such as ultrasound energy at specific subcutaneous tissues 510. In one embodiment, methods for non-invasively treating subcutaneous tissues 510 to perform a brow lift are provided. In one embodiment, a non-invasive brow lift is performed by applying ultrasound energy at specific depths 278 along the brow to ablatively cut, cause tissue to be reabsorbed into the body, coagulate, remove, manipulate, or paralyze subcutaneous tissue 510 such as the facial muscle 509, for example, the corrugator supercilii muscle, the epicranium muscle, and the procerus muscle within the brow to reduce wrinkles.

In some embodiments, ultrasound energy is applied at a ROI 65 along a patient's forehead. The ultrasound energy can be applied at specific depths and is capable of targeting certain subcutaneous tissues within the brow such as with reference to FIGS. 12-14, SMAS 507 and/or facial muscle 509. The ultrasound energy targets these tissues and cuts, ablates, coagulates, micro-ablates, manipulates and/or causes the subcutaneous tissue 510 to be reabsorbed into the subject's body which effectuates a brow lift non-invasively.

For example, the corrugator supercilii muscle in a target zone 525, can be targeted and treated by the application of ultrasound energy at specific depths 278. This facial muscle 509 or other subcutaneous facial muscles can be ablated, coagulated, micro-ablated, shaped or otherwise manipulated by the application of ultrasound energy in a non-invasive manner. Specifically, instead of cutting a corrugator supercilii muscle during a classic or endoscopic brow lift, the targeted muscle 509 such as the corrugator supercilii can be ablated, micro-ablated, or coagulated by applying ultrasound energy at the forehead without the need for traditional invasive techniques.

One method is configured for targeted treatment of subcutaneous tissue 510 in the forehead region 65 in various manners such as through the use of therapy only, therapy and monitoring, imaging and therapy, or therapy, imaging and monitoring. Targeted therapy of tissue can be provided through ultrasound energy delivered at desired depths 278 and locations via various spatial and temporal energy settings. In one embodiment, the tissues of interest are viewed in motion in real time by utilizing ultrasound imaging to clearly view the moving tissue to aid in targeting and treatment of a ROI 65 on the patient's forehead. Therefore, the practitioner or user performing the non-invasive brow

lift can visually observe the movement and changes occurring to the subcutaneous tissue 510 during treatment.

FIGS. 15-17 illustrate an embodiment of a method of administering a brow lift. Other embodiments include multiple treatment depths, three dimensional (3-D) treatment, and use of multiple treatment sessions over time. The CTS 20 can be coupled to a tissue portion 10 of the ROI 65 that is to be treated. In one embodiment, a treatment zone 525 is first imaged and then treated. In one embodiment, a user activates the imaging button 150 to initiate the imaging sequence. Imaging can be displayed on the graphical interface 310. In one embodiment, the imaging sequence can be controlled on a touchscreen 315 that is part of the graphical interface 310. After the imaging sequence is started, the treatment sequence can be initiated at any time. The user can activate treatment button 160 at any time to initiate the treatment sequence. Treatment and imaging can occur simultaneously or occur sequentially. For example, a user can image, treat, image, treat, etc. As schematically illustrated in FIG. 15, the treatment sequence activates the treatment portion of the transducer 280 to create voids or lesions 550 below the surface 105. Note that FIG. 15 illustrates one embodiment of a depth 278 that corresponds to a muscle depth. In various embodiments, the depth 278 can correspond to any tissue, tissue layer, skin, dermis, fat, SMAS, muscle, or other tissue. Note that as illustrated, the energy 50 represented is for illustration purposes only. Certain figures including FIGS. 15-17 show energy 50 emanating from the entire length of the transducer housing (its entire opening such as corresponding to travel distance 272); however the actual energy is emitted from a sub-length of that, e.g., the actual transduction element of the transducer 280. In one embodiment, the transduction element of the transducer 280 is scanned in a linear motion to cover the region of interest, such that at any time the energy is not coming out of the entire transducer housing's length at once.

In one embodiment, CTS 20 generates ultrasound energy which is directed to and focused below the surface 501. This controlled and focused ultrasound energy creates the lesion 550 which may be a thermally coagulated zone or void in subcutaneous tissue 510. In one embodiment, the emitted energy 50 raises a temperature of the tissue at a specified depth 278 below the surface 501. The temperature of the tissue can be raised from about 1° C. to about 100° C. above an ambient temperature of the tissue, or about 5° C. to about 60° C. above an ambient temperature of the tissue or above 10° C. to about 50° C. above the ambient temperature of the tissue. In some embodiments, the emitted energy 50 targets the tissue below the surface 501 which cuts, ablates, coagulates, micro-ablates, manipulates, and/or causes a lesion 550 in the tissue portion 10 below the surface 501 at a specified depth 278. In one embodiment, during the treatment sequence, the transducer 280 moves in a direction denoted by the arrow marked 290 at specified intervals 295 to create a series of treatment zones 254 each of which receives an emitted energy 50 to create a lesion 550. For example, the emitted energy 50 creates a series of lesions 550 in the facial muscle layer 509 of tissue portion 10.

In various embodiments, delivery of emitted energy 50 at a suitable depth 278, distribution, timing, and energy level is provided by the emitter-receiver module 200 through controlled operation by the control system 300 to achieve the desired therapeutic effect of controlled thermal injury to treat at least one of the dermis layer 503, fat layer 505, the SMAS layer 507 and the facial muscle layer 509. During operation, the emitter-receiver module 200 and/or the transducer 280 can also be mechanically and/or electronically

scanned along the surface **501** to treat an extended area. In addition, spatial control of a treatment depth **278** can be suitably adjusted in various ranges, such as between a wide range of about 0 mm to about 25 mm, suitably fixed to a few discrete depths, with an adjustment limited to a fine range, for example, approximately between about 3 mm to about 9 mm, and/or dynamically adjusted during treatment, to treat at least one of the dermis layer **503**, fat layer **505**, the SMAS layer **507** and the facial muscle layer **509**. Before, during, and after the delivery of ultrasound energy **50** to at least one of the dermis layer **503**, fat layer **505**, the SMAS layer **507** and the facial muscle layer **509**, monitoring of the treatment area and surrounding structures can be provided to plan and assess the results and/or provide feedback to the controller **300** and the user via the graphical interface **310**.

As to the treatment of the SMAS layer **507** and similar fascia, connective tissue can be permanently tightened by thermal treatment to temperatures about 60° C. or higher. Upon ablating, collagen fibers shrink immediately by approximately 30% of their length. The shrunken fibers can produce tightening of the tissue, wherein the shrinkage should occur along the dominant direction of the collagen fibers. Throughout the body, collagen fibers are laid down in connective tissues along the lines of chronic stress (tension). On the aged face, the collagen fibers of the SMAS **507** region are predominantly oriented along the lines of gravitational tension. Shrinkage of these fibers results in tightening of the SMAS **507** in the direction desired for correction of laxity and sagging due to aging. The treatment includes the ablation of specific regions of the SMAS **507** region and similar suspensory connective tissues.

In addition, the SMAS layer **507** varies in depth and thickness at different locations, for example from about 0.5 mm to about 5 mm or more. On the face, important structures such as nerves, parotid gland, arteries and veins are present over, under or near the SMAS **507** region. Treating through localized heating of regions of the SMAS **507** layer or other suspensory subcutaneous tissue **510** to temperatures of about 60° C. to about 90° C., without significant damage to overlying or distal/underlying tissue, or proximal tissue, as well as the precise delivery of therapeutic energy to the SMAS layer **507**, and obtaining feedback from the region of interest before, during, and after treatment can be suitably accomplished through the CTS **20**.

In various embodiments, a method is provided for performing a brow lift on a patient. In some embodiments, the method includes coupling a probe **200** to a brow region **65** of the patient **60** and imaging at least a portion of subcutaneous tissue **510** of the brow region to determine a target area in the subcutaneous tissue **510**. In an aspect of the embodiment, the method includes administering ultrasound energy **50** into the target area **525** in the subcutaneous tissue **510** to ablate the subcutaneous tissue **510** in the target area **525**, which causes tightening of a dermal layer **503** above the subcutaneous tissue **510** of the brow region **65**.

In various embodiments, a method is provided for tightening a portion of a dermal layer **503** on a facial area of a patient **60**. In some embodiments, the method includes inserting a transducer module **200** into a hand controller **100** and then coupling the transducer module **200** to a facial area of the patient **60**. In one embodiment, the method includes activating a first switch **150** on the hand controller **100** to initiate an imaging sequence of a portion of tissue **10** below the dermal layer **503**, then collecting data from the imaging sequence. In this embodiment, the method includes calculating a treatment sequence from the collected data, and activating a second switch **160** on the hand controller **100** to

initiate the treatment sequence. In an aspect of the embodiments, the method can be useful on a portion of a face, head, neck and/or other part of the body of a patient **60**.

With reference to FIG. **16**, after the emitted energy has created lesions **550**, healing and/or tightening of the portion of tissue **10** begins. In one embodiment, the void or lesion **550** can dissipate in the facial muscle layer **509** of the portion of tissue **10**. For example, the facial muscle layer **509** has movement **560** around the lesion **550** to shrink the lesion **550**. Eventually, the body essentially eliminates the lesion **550** through resorption, and can enhance the growth of tissue. This movement **560** causes upper layers such as the SMAS **507** to have movement **570** above where the lesion **550** was located. This in turn causes movement **580** at the surface **501** which tightens surface **501**. This surface movement **580** at the surface **501** is the goal of any brow lift. The surface movement **580** creates a tightening effect across the skin surface **501** which can provide a more youthful look for the subject **500**. In various embodiments, a medicant can be applied during the coupling of the CTS **20** to the portion of tissue **10**. This medicant can be activated in the target zone **525** by the emitted energy **50** and can assist, accelerate, and/or treat the void or lesion **550** during the dissipation and/or healing of the void or lesion **550**. Medicants include, but are not limited to, hyaluronic acid, retinol, vitamins (e.g., vitamin c), minerals (e.g., copper) and other compounds or pharmaceuticals that can be activated by energy and/or would benefit from deeper penetration into the skin.

Turning to FIG. **18**, a flow chart illustrates a method according to various embodiments of the present invention. A method **800** can include a first step **801** which is a coupling of a probe to a brow region. For example, step **801** can include the coupling of the emitter-receiver module **200** to a portion of tissue **10** in a ROI **65** of the subject **500**. This step **801** can include a gel located between the emitter-receiver module **200** and the portion of tissue **10** that assists in the coupling of a probe to the brow region. Step **801** can move to step **802** which is imaging subcutaneous tissue **510** in the brow region. Step **802** can include imaging the portion of tissue **10** using the CTS **20** as discussed herein. Optionally, a step **810** can be included between steps **801** and **802**. Step **810** is the applying a medicant to the brow region. The medicant can be any substance or material that has an active ingredient that may be helpful in the tightening of the surface **501** and/or in the healing and/or dissipation of the void or lesion **550** in a portion of tissue **10** below the surface **501**. In one embodiment, the medicant can also act as a coupling gel useful in step **801**. Step **802** moves to step **803** which is determining a target zone **525**. Step **803** can include reviewing an image that was created in step **802** to help determine the target zone **525**.

Step **803** moves to step **804** which is the administering of energy to the target zone **525**. For example, step **804** can be illustrated in, for example, FIG. **15**. Note that FIG. **15** illustrates one embodiment of a depth **278** that corresponds to a muscle depth. In various embodiments, the depth **278** can correspond to any tissue, tissue layer, skin, dermis, fat, SMAS, muscle, or other tissue. Step **804** moves to step **805** which is ablating the tissue in the target zone **525**. In various embodiments, this “ablating” may be coagulation instead of ablation. Ablation is more or less instantaneous physical removal, analogous to sublimation or vaporization, while thermal coagulation is milder in that it is killing tissue but leaving it in place. Step **805** is illustrated in FIG. **15**. Note that FIG. **15** illustrates one embodiment of a depth **278** that corresponds to a muscle depth. In various embodiments, the depth **278** can correspond to any tissue, tissue layer, skin,



dermis, fat, SMAS, muscle, or other tissue. In step **805**, the void or lesion **550** is created in a portion of tissue **10** below the surface **501**. Step **805** moves to step **806** which is tightening a dermal layer **503** above or below the treated tissue. In the illustrated embodiment, step **806** is merely 5 tightening a dermal layer above the tissue, but the broader step described is possible in various embodiments. Step **806** is illustrated in FIG. **17**. For example, one of the surface **501** in the dermal layer **503** is tightened due to the void or lesion **505** being dissipated or healed. Between step **505** and **506**, 10 an optional step **812** may be used. Typically, for step **812** to be used, optional step **810** must also be used. In step **812**, the medicant is activated in the target zone **525**. This activation of the medicant can allow active ingredient to assist in tightening the dermal layer **503** above the ablate tissue. For 15 example, the active ingredient may assist in the healing or dissipating of the void or lesion **550**. In another example, the medicant may be activated at the surface **501** or in the dermal layer **503** to assist tightening.

With reference to FIG. **19** a method **900** is illustrated 20 according to various embodiments of the present invention. Method **900** begins with inserting a transducer module to the hand controller. For example, method **900** can include the inserting of the emitter-receiver module **200** into the hand wand **100**. Step **901** moves to step **902** which is the coupling 25 of the module to a facial area of the subject. For example, step **902** can include coupling the emitter-receiver module **200** to a region of interest **65** of a subject **63**. Step **902** moves to step **903** which is activating a first switch on the hand controller. For example, step **903** can include activating an 30 imaging button **150** on the hand wand **100**. Step **903** moves to step **904** which is initiating the imaging sequence. For example, step **904** can include imaging sequence that can be collected by the CTS **20** as discussed herein. Step **904** moves to step **905** which is collecting imaging data. Step **905** 35 moves to step **906** which is calculating a treatment sequence. In various embodiments, "calculating" as used with respect to step **906** can be determining, selecting, selecting a pre-determined treatment sequence, and/or selecting a desired 40 treatment sequence. For example, step **906** can include the controller **300** downloading a treatment sequence to the hand wand **100** and the emitter-receiver module **200**. Step **906** moves to step **907** which is the activating of a second switch on the hand controller. For example, step **907** can be 45 the activating of the treatment button **160** on the hand wand **100**. Step **907** moves to step **908** which is executing the treatment sequence. For example, step **908** can be any treatment sequence as discussed herein. In other embodiments, the illustrated method may be broader to include 50 generalized activating of switches anywhere and anyhow, such as with foot switches or switches on the controller **300**, in various non-limiting embodiments.

FIGS. **20-21** illustrate a front and side view of one embodiment of a controller **300** as previously described herein. FIG. **22** illustrates one embodiment of an interactive 55 graphical display **310**, which can include a touch screen monitor and Graphic User Interface (GUI) that allows the user to interact with the CTS **20**. FIG. **22** illustrates a general example of an embodiment of an interactive graphical display **310**, which may include system function tabs **1000**, 60 therapy controls **1010**, imaging controls **1020**, region control **1030**, patient total line count **1040**, treat zone line count **1050**, system status **1060**, probe information area **1070**, header information **1080** and/or image-treat region **1090**.

The system function tabs **1000** reflect aspects of the 65 system function. In one embodiment, the interactive graphical display **310** has one or more general functions. In various

embodiments the interactive graphical display **310** has two, three, four or more general functions. In one embodiment, an interactive graphical display **310** has three general functions: a planning function, a imaging/treatment function, and a 5 settings function. In one embodiment, the planning function contains the controls and information instrumental in planning a treatment, which can automatically set therapy controls. In one embodiment, the planning function can display an overview of the various treatment regions with recom- 10 mended treatment parameters for each. For example, parameters for treating such regions as the forehead, left or right temple, left or right preauricular, left or right neck, submental, and left or right cheek can show a recommended emitter-receiver module **200** listing energy levels and recom- 15 mended numbers of lines of treatment. Certain areas can include a protocol listing for selection of treatment protocols, a protocol allowed treat regions listing, and disallowed regions that can not be selected due to an incorrect transducer, which can be grayed out. In one embodiment, the 20 imaging/treatment function contains the controls and protocol information needed for imaging soft tissue and for treating pertinent soft tissue. In various embodiments, a start up screen can include patient and/or facility data. In one embodiment the imaging/treatment function can include a main startup screen. In one embodiment a imaging/treatment 25 function can be configured for a forehead. The settings function allows the user to input, track, store and/or print patient treatment information outside the scanning function, and can include such information as patient and facility information, end treatment, treatment records, images, help, 30 volume, and system shutdown controls and dialogs.

The therapy controls **1010** can set acoustic energy level, spacing for setting the distance between micro-coagulative zones, and length which can set the maximum distance of 35 the treatment line and similar information.

The imaging controls **1020** can include marker (not scanning), display (scanning), image and scan information. The marker can include a distance icon to show calipers and text for annotation. The display can increase or decrease 40 brightness or other display related characteristics. The image icon can toggle a treat ruler, or save an image. The scan buttons can start or stop scanning for imaging purposes and similar information.

The region control **1030** launches a dialog below the 45 image to select tissue region. The patient total line count **1040** keeps track of the cumulative number of treatment lines delivered and similar information. The treat zone line count **1050** indicates a zone of treatment, such as forehead or submental, etc. and can display the lines delivered to a 50 zone or a protocol for recommended lines and similar information. The system status **1060** can display that the system is ready, treating, or other mode-dependent system messages and similar information. The probe information area **1070** can display the name of the attached transducer, 55 the treatment depth of the transducer, and the number of lines spent/(vs.) total line capacity of transducer and similar information. The header information **1080** can include the facility, clinician, patient name and patient identification, date and time and similar information. The image-treat 60 region **1090** can include an ultrasound image, horizontal and vertical (depth) rulers with 1 mm tick marks or other measuring dimensions, a treatment ruler indicating spacing, length and depth of treatment, and other similar information.

One benefit or advantage of using a treatment system that 65 also allows imaging is that a user can verify that there sufficient coupling between the transducer and the skin (such as by applying coupling gel between the emitter-receiver

module **200** and skin) by ensuring there are not dark, vertical bars, as indicative of air pockets between the face of the transducer and patient. A lack of coupling may result in a region that is improperly treated. Corrective action might include placing more coupling ultrasound gel to ensure proper contact and communication between the device and the patient.

Therapeutic treatment can be initiated by pressing the treatment button **160** on the hand wand **100**. In one embodiment, an indicator **155** will display a yellow light to indicate the system is in the "treating" state. As the energy **50** is delivered a continuous tone is sounded and a yellow 'treating' line will advance over the green 'ready' treatment line on the screen. To deliver the next line of energy in the same treatment area, the user can advance the transducer roughly 1-6 mm, or roughly 2-3 mm (depending on the treatment, region, etc.) to adjacent tissue and press the treatment button **160** again. In various embodiments, a time period can elapse between delivering a previous line of energy **50**. In various embodiments, the time period can be 1 second, 5 seconds, 10 seconds, or any other duration. In one embodiment, if five or ten seconds (or some other duration) have elapsed between delivering the previous line of energy **50**, the user can press the imaging button **150** on the hand wand **100** to restore the "ready" state, and then press the treatment button **160** next to it. Treatment can continue in this fashion until the recommended number of lines (as shown on the bottom/center of the screen) has been delivered. In one embodiment, when the correct number of lines is delivered, the line count color turns from orange to white.

In one embodiment, the settings function allows a user to export images. Stored images are listed in the bottom dialog box and the most recently user-selected image is displayed above it. If an external storage device and/or printer is attached then image file export and/or printing is enabled, respectively. In one embodiment, the settings function allows a user to export records.

In certain embodiments, the interactive graphical display **310** can display error messages to direct appropriate user responses, such as in one embodiment of an error message.

The citation of references herein does not constitute admission that those references are prior art or have relevance to the patentability of the teachings disclosed herein. All references cited in the Description section of the specification are hereby incorporated by reference in their entirety for all purposes. In the event that one or more of the incorporated references, literature, and similar materials differs from or contradicts this application, including, but not limited to, defined terms, term usage, described techniques, or the like, this application controls.

Some embodiments and the examples described herein are examples and not intended to be limiting in describing the full scope of compositions and methods of these invention. Equivalent changes, modifications and variations of some embodiments, materials, compositions and methods can be made within the scope of the present invention, with substantially similar results.

What is claimed is:

**1.** A transducer module for use in an ultrasound treatment, comprising:

a sealed housing comprising an acoustic fluid and an acoustically transparent window,

a circuit board configured for direct electrical connection to a pin connector comprising one or more pins, wherein the circuit board is configured to be operably coupled to a detachable hand wand at a circuit board

interface, wherein the circuit board interface is on an external surface of the transducer module,

an ultrasonic treatment piezoelectric element configured to focus ultrasound energy at a depth in a range between 3 mm and 9 mm below a skin surface with a treatment frequency in a range of 1 MHz to 10 MHz at an acoustic power,

wherein the ultrasonic treatment piezoelectric element is acoustically coupled to the acoustically transparent window via the acoustic fluid in the sealed housing, and a movement mechanism comprising a shaft,

wherein the movement mechanism is configured to attach to a motor operably coupled to the detachable hand wand,

wherein the movement mechanism is configured to linearly move the ultrasonic treatment piezoelectric element along the shaft within the sealed housing to direct the ultrasound treatment in a linear sequence of spaced thermal lesions at the depth below the skin surface,

wherein the ultrasonic treatment piezoelectric element is configured to focus the ultrasound energy at the depth for treatment in at least one of the group consisting of: a dermis tissue, a fascia tissue, a muscle tissue, and a fat tissue,

wherein the transducer module is configured to detach from the detachable hand wand via the circuit board interface, which thereby permits a second transducer module to interchangeably attach to the hand wand after detachment from the transducer module.

**2.** The transducer module of claim **1**, wherein the movement mechanism further comprises any one or more of the group consisting of: a scotch yoke, a magnetic coupling, and a screw.

**3.** The transducer module of claim **1**, further comprising an ultrasound imaging piezoelectric element configured for attachment to a display for providing an ultrasonic image.

**4.** The transducer module of claim **1**, wherein the ultrasonic treatment piezoelectric element and the movement mechanism are configured for operation via electrical communication with an electronic key.

**5.** The transducer module of claim **1**, wherein the circuit board interface is configured for removable insertion and detachment from an integrated receptacle of the detachable hand wand.

**6.** The transducer module of claim **5**, wherein the integrated receptacle is configured for interchangeable attachment to the second transducer module, wherein the second transducer module comprises a second sealed housing comprising a second acoustic fluid and a second acoustically transparent window, a second ultrasonic treatment piezoelectric element configured to focus ultrasound energy at a second depth in a range of 3 mm to 4.5 mm below the skin surface with a second treatment frequency in a range of 1 MHz to 10 MHz at a second acoustic power, wherein the second ultrasonic treatment piezoelectric element is acoustically coupled to the second acoustically transparent window via the second acoustic fluid in the second sealed housing.

**7.** The transducer module of claim **5** wherein the integrated receptacle is configured for interchangeable attachment to the second transducer module, wherein the second transducer module comprises:

a second sealed housing comprising a second acoustic fluid and a second acoustically transparent window,

a second ultrasonic treatment piezoelectric element configured to focus ultrasound at a second depth in a range of 1.5 mm to 3 mm below the skin surface with a

second treatment frequency in a range of 1 MHz to 10 MHz at a second acoustic power, and wherein the second ultrasonic treatment piezoelectric element is acoustically coupled to the second acoustically transparent window via the second acoustic fluid in the second sealed housing, wherein the transducer module and second transducer module are configured to provide treatment at different depths below the skin surface.

**8.** A transducer module for use in an ultrasound treatment, comprising:

a sealed housing comprising an ultrasonic treatment piezoelectric element, an acoustic fluid, and a circuit board,

wherein the circuit board is configured for direct electrical connection to a pin connector comprising one or more pins, wherein the circuit board is configured to be operably coupled to a detachable hand wand at a circuit board interface, wherein the circuit board interface is on an external surface of the transducer module,

wherein the ultrasonic treatment piezoelectric element is configured to focus ultrasound at a depth in a range between 3 mm and 9 mm below a skin surface with a treatment frequency in a range of 1 MHz to 10 MHz at an acoustic power,

a storage device configured for containing calibration data or storage data, and

a movement mechanism comprising a shaft, the movement mechanism being configured to attach to a motor operably coupled to the detachable hand wand,

wherein the movement mechanism is configured to linearly move the ultrasonic treatment piezoelectric element along the shaft to direct the ultrasound treatment in a linear sequence of spaced thermal lesions,

wherein the ultrasonic treatment piezoelectric element is configured to provide the ultrasound treatment at the depth for treatment in at least one of the group consisting of: a skin tissue, a fascia tissue, a muscle tissue, and a fat tissue,

wherein the transducer module is configured to detach from the detachable hand wand via the circuit board interface, which thereby permits a second transducer module to interchangeably attach to the detachable hand wand.

**9.** The transducer module of claim **8**, wherein the ultrasonic treatment piezoelectric element is connected to a microprocessor for controlling the ultrasound treatment.

**10.** The transducer module of claim **8**, wherein the movement mechanism comprises one or more of a sleeve, a bearing, a screw, a scotch yoke, or a magnetic coupling, wherein the movement mechanism is operably attached to the motor to linearly move the ultrasonic treatment piezoelectric element when the motor is operated.

**11.** The transducer module of claim **8**, wherein the movement mechanism comprises a magnetic coupling.

**12.** The transducer module of claim **8**, further comprising an ultrasound imaging piezoelectric element configured for providing an ultrasonic image on a display of the at least one of the group consisting of: the skin tissue, the fascia tissue, the muscle tissue, and the fat tissue.

**13.** A transducer module for use in an ultrasound treatment, comprising:

a sealed housing comprising an ultrasonic treatment piezoelectric element and an acoustically transparent window,

the ultrasonic treatment piezoelectric element being configured for acoustic coupling to the acoustically transparent window to focus ultrasound in a linear sequence of individual thermal lesions at a depth in a range between 3 mm and 9 mm below a skin surface with a treatment frequency in a range of 1 MHz to 10 MHz at an acoustic power,

wherein the ultrasonic treatment piezoelectric element is configured to provide the ultrasound treatment at the depth for treatment in at least one of the group consisting of: a skin tissue, a fascia tissue, a muscle tissue, and a fat tissue,

a circuit board configured for direct electrical connection to a pin connector comprising one or more pins, wherein the circuit board is configured to be operably coupled to a detachable hand wand at a circuit board interface, wherein the circuit board interface is on an external surface of the transducer module,

a movement mechanism, wherein the movement mechanism is configured for operable connection to a motor in the detachable hand wand, the motor configured to linearly move the ultrasonic treatment piezoelectric element inside the sealed housing,

wherein the transducer module is configured to detach from the detachable hand wand via the circuit board interface, which thereby permits a second transducer module to removably attach to the detachable hand wand.

**14.** The transducer module according to claim **13**, further comprising a latch mechanism configured for removably holding the transducer module to the detachable hand wand.

**15.** The transducer module according to claim **13**, wherein the movement mechanism comprises one or more of a shaft, a sleeve, a bearing, a screw, a scotch yoke, or a magnetic coupling, wherein the movement mechanism is configured to linearly move the ultrasonic treatment piezoelectric element within the sealed housing to create a series of separated ablative lesions under the skin surface.

**16.** The transducer module according to claim **13**, configured for connection to a graphical user interface for controlling the ultrasound treatment.

**17.** The transducer module according to claim **13**, wherein the ultrasound treatment is at least one of face lift, a wrinkle reduction, a skin tightening, and a scar reduction.

**18.** The transducer module according to claim **13**, wherein the ultrasonic treatment piezoelectric element in the transducer module is electronically coupled to a treatment button of the detachable hand wand, the treatment button configured for operably controlling the ultrasonic treatment piezoelectric element when the sealed housing is coupled to an integrated receptacle at the circuit board interface.

**19.** The transducer module of claim **13**, wherein the circuit board interface is configured for interchangeable coupling to the detachable hand wand at the circuit board interface via at least one pin at the pin connector, the circuit board interface configured for removable insertion of the transducer module from the circuit board interface.

**20.** The transducer module according to claim **13**, further comprising an ultrasound imaging piezoelectric element configured for providing an ultrasonic image on a display.