

(10) **Patent No.:** US 12,110,878 B2
(45) **Date of Patent:** *Oct. 8, 2024

(58) **Field of Classification Search**
CPC F03G 4/00-074; F03G 7/04-045
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,982,745 A 12/1934 Koenemann
3,517,208 A 6/1970 Williams et al.
(Continued)

AU	2007204830	A1	7/2007
AU	2009238733	B2	8/2013

(Continued)

OTHER PUBLICATIONS

Li et al., “Thermodynamic analysis of subcritical/transcritical ORCs with metal-organic heat carriers for efficient power generation from low-grade thermal energy”, *Energy* 255 (2022) 124519.

(Continued)

Primary Examiner — Laert Dounis

(74) *Attorney, Agent, or Firm* — Womble Bond Dickinson
(US) LLP

(57) **ABSTRACT**

Embodiments of systems and methods for generating power in the vicinity of a drilling rig are disclosed. During a drilling operation, heat generated by drilling fluid flowing from a borehole, exhaust from an engine, and/or fluid from an engine's water (or other fluid) jacket, for example, may be utilized by corresponding heat exchangers to facilitate heat transfer to a working fluid. The heated working fluid may cause an ORC unit to generate electrical power.

16 Claims, 17 Drawing Sheets

Related U.S. Application Data

continuation of application No. 17/657,015, filed on Mar. 29, 2022, now Pat. No. 11,592,009, which is a continuation-in-part of application No. 17/682,126, filed on Feb. 28, 2022, now Pat. No. 11,359,612, and a continuation-in-part of application No. 17/670,827, filed on Feb. 14, 2022, now Pat. No. 11,421,663, and a continuation-in-part of application No. 17/650,811, filed on Feb. 11, 2022, now Pat. No. 11,578,706, and a continuation-in-part of application No. 17/578,550, filed on Jan. 19, 2022, and a continuation-in-part of application No. 17/578,520, filed on Jan. 19, 2022, now Pat. No. 11,326,550, and a continuation-in-part of application No. 17/578,542, filed on Jan. 19, 2022, now Pat. No. 11,359,576, and a continuation-in-part of application No. 17/578,528, filed on Jan. 19, 2022, now Pat. No. 11,480,074, said application No. 17/682,126 is a continuation of application No. 17/494,936, filed on Oct. 6, 2021, now Pat. No. 11,293,414, said application No. 17/670,827 is a continuation-in-part of application No. 17/305,296, filed on Jul. 2, 2021, now Pat. No. 11,255,315, said application No. 17/494,936 is a continuation-in-part of application No. 17/305,296, filed on Jul. 2, 2021, now Pat. No. 11,255,315, said application No. 17/650,811 is a continuation of application No. 17/305,298, filed on Jul. 2, 2021, now Pat. No. 11,280,322, said application No. 17/657,015 is a continuation-in-part of application No. 17/305,297, filed on Jul. 2, 2021, now Pat. No. 12,060,867.

- (60) Provisional application No. 63/269,862, filed on Mar. 24, 2022, provisional application No. 63/269,572, filed on Mar. 18, 2022, provisional application No. 63/261,601, filed on Sep. 24, 2021, provisional application No. 63/200,908, filed on Apr. 2, 2021.

(51) **Int. Cl.**

E21B 34/06 (2006.01)
E21B 36/00 (2006.01)
E21B 41/00 (2006.01)
E21B 47/07 (2012.01)
F01K 11/02 (2006.01)
F01K 17/02 (2006.01)
F01K 25/08 (2006.01)
F03G 4/00 (2006.01)
F03G 4/06 (2006.01)

(52) **U.S. Cl.**

CPC *E21B 41/0085* (2013.01); *E21B 47/07* (2020.05); *F01K 11/02* (2013.01); *F01K 17/02* (2013.01); *F01K 25/08* (2013.01); *F03G 4/023* (2021.08); *F03G 4/035* (2021.08); *F03G 4/06* (2021.08); *F03G 4/072* (2021.08)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,757,516 A 9/1973 McCabe
 3,808,794 A 5/1974 Wood
 3,875,749 A 4/1975 Baciú
 3,908,381 A 9/1975 Barber et al.
 3,988,895 A 11/1976 Sheinbaum
 4,063,417 A 12/1977 Shields
 4,079,590 A 3/1978 Sheinbaum
 4,112,687 A 9/1978 Dixon
 4,112,745 A 9/1978 McCabe
 4,149,385 A 4/1979 Sheinbaum

4,157,730 A 6/1979 Despois et al.
 4,191,021 A 3/1980 Nakamura
 4,224,796 A 9/1980 Stiel et al.
 4,228,657 A 10/1980 Leo
 4,275,563 A 6/1981 Kuroda
 4,292,808 A 10/1981 Lohmiller
 4,356,401 A 10/1982 Santi
 4,369,373 A 1/1983 Wiseman
 4,484,446 A 11/1984 Goldsberry
 4,542,625 A 9/1985 Bronicki
 4,558,568 A 12/1985 Hoshino et al.
 4,576,005 A 3/1986 Force
 4,590,384 A 5/1986 Bronicki
 4,982,568 A 1/1991 Kalina
 4,996,846 A 3/1991 Bronicki
 5,038,567 A 8/1991 Mortiz
 5,117,908 A 6/1992 Hofmann
 5,131,231 A 7/1992 Trimble
 5,199,507 A 4/1993 Westmoreland
 5,311,741 A 5/1994 Blaize
 5,421,157 A 6/1995 Rosenblatt
 5,440,882 A 8/1995 Kalina
 5,483,797 A 1/1996 Rigal et al.
 5,497,624 A 3/1996 Amir et al.
 5,517,822 A 5/1996 Haws et al.
 5,526,646 A 6/1996 Bronicki et al.
 5,555,731 A 9/1996 Rosenblatt
 5,570,579 A 11/1996 Larjola
 5,595,059 A 1/1997 Huber et al.
 5,598,706 A 2/1997 Bronicki et al.
 5,660,042 A 8/1997 Bronicki et al.
 5,661,977 A 9/1997 Shnell
 5,671,601 A 9/1997 Bronicki et al.
 5,685,362 A 11/1997 Brown
 5,816,048 A 10/1998 Bronicki et al.
 5,839,282 A 11/1998 Bronicki et al.
 5,860,279 A 1/1999 Bronicki et al.
 RE36,282 E 8/1999 Nitschke
 5,970,714 A 10/1999 Bronicki et al.
 5,974,804 A 11/1999 Sterling
 6,073,448 A 6/2000 Lozada
 6,212,890 B1 4/2001 Amir
 6,536,360 B2 3/2003 O'Connor
 6,585,047 B2 7/2003 McClung
 6,691,531 B1 2/2004 Martinez
 6,695,061 B2 2/2004 Fripp et al.
 6,724,687 B1 4/2004 Stephenson et al.
 6,853,798 B1 2/2005 Weiss
 6,857,268 B2 2/2005 Stinger et al.
 6,857,486 B2 2/2005 Chitwood et al.
 6,989,989 B2 1/2006 Brasz et al.
 7,096,665 B2 8/2006 Stinger et al.
 7,174,716 B2 2/2007 Brasz et al.
 7,224,080 B2 5/2007 Smedstad
 7,225,621 B2 6/2007 Zimron et al.
 7,234,314 B1 6/2007 Wiggs
 7,237,383 B2 7/2007 Ahrens-Botzong et al.
 7,254,949 B2 8/2007 Brasz et al.
 7,281,379 B2 10/2007 Brasz
 7,287,381 B1 10/2007 Pierson et al.
 7,289,325 B2 10/2007 Brasz et al.
 7,313,926 B2 1/2008 Gurin
 7,320,221 B2 1/2008 Bronicki
 7,334,410 B2 2/2008 Creighton et al.
 7,337,842 B2 3/2008 Roddy et al.
 7,353,653 B2 4/2008 Bronicki
 7,428,816 B2 9/2008 Singh et al.
 7,472,548 B2 1/2009 Meksvanh
 7,493,768 B2 2/2009 Klaus et al.
 7,753,122 B2 7/2010 Curlett
 7,823,386 B2 11/2010 Zimron et al.
 7,891,187 B2 2/2011 Mohr
 7,891,189 B2 2/2011 Bottger et al.
 7,900,450 B2 3/2011 Gurin
 7,926,276 B1 4/2011 Dunn
 7,934,383 B2 5/2011 Gutierrez et al.
 7,942,001 B2 5/2011 Radcliff et al.
 7,950,230 B2 5/2011 Nishikawa et al.
 8,046,999 B2 11/2011 Doty

(56)

References Cited

U.S. PATENT DOCUMENTS

8,096,128 B2	1/2012	Held et al.	9,441,504 B2	9/2016	Held
8,099,198 B2	1/2012	Gurin	9,458,738 B2	10/2016	Held
8,146,360 B2	4/2012	Myers et al.	9,488,160 B2	11/2016	Fisher et al.
8,166,761 B2	5/2012	Moghtaderi et al.	9,499,732 B2	11/2016	Reddy et al.
8,193,659 B2	6/2012	Bronicki et al.	9,512,348 B2	12/2016	Reyes et al.
8,272,217 B2	9/2012	Lengert	9,512,741 B2	12/2016	Myogan et al.
8,309,498 B2	11/2012	Funkhouser et al.	9,574,551 B2	2/2017	Parrella, Sr. et al.
8,371,099 B2	2/2013	Gutierrez et al.	9,587,161 B2	3/2017	Fisk, Jr.
8,381,523 B2	2/2013	Zadok	9,587,162 B2	3/2017	Fisk, Jr.
8,430,166 B2	4/2013	Danko	9,638,065 B2	5/2017	Vermeersch et al.
8,438,849 B2	5/2013	Kaplan et al.	9,649,582 B2	5/2017	Shnell
8,459,029 B2	6/2013	Lehar	9,671,138 B2	6/2017	Batscha et al.
8,511,085 B2	8/2013	Frey et al.	9,683,463 B2	6/2017	Juchymenko
8,528,333 B2	9/2013	Juchymenko	9,726,157 B2	8/2017	Sweatman et al.
8,534,069 B2	9/2013	Parrella	9,726,441 B2	8/2017	Reissner et al.
8,555,643 B2	10/2013	Kalina	9,732,634 B2	8/2017	Hikichi et al.
8,555,912 B2	10/2013	Woolley et al.	9,745,870 B2	8/2017	Johnson et al.
8,572,970 B2	11/2013	Matteson et al.	9,759,096 B2	9/2017	Vermeersch
8,578,714 B2	11/2013	Nagurny et al.	9,762,460 B2	9/2017	Pawlowski et al.
8,596,066 B2	12/2013	Zimron et al.	9,777,602 B2	10/2017	Juchymenko
8,616,000 B2	12/2013	Parrella	9,784,140 B2	10/2017	Huntington et al.
8,616,001 B2	12/2013	Held et al.	9,784,248 B2	10/2017	Batscha et al.
8,616,323 B1	12/2013	Gurin	9,797,273 B2	10/2017	Nishiguchi et al.
8,656,720 B1	2/2014	Hardgrave	9,803,803 B1	10/2017	Adams
8,667,797 B2	3/2014	Woodland	9,816,402 B2	11/2017	Kauffman et al.
8,667,799 B2	3/2014	Batscha	9,816,443 B2	11/2017	Sheridan et al.
8,674,525 B2	3/2014	Van den Bossche et al.	9,829,194 B2	11/2017	Aumann et al.
8,680,704 B1	3/2014	Rooney	9,840,662 B2	12/2017	Pascarella et al.
8,707,697 B2	4/2014	Nitschke	9,845,423 B2	12/2017	Frantz et al.
8,707,698 B2	4/2014	Conry	9,863,282 B2	1/2018	Hart et al.
8,708,046 B2	4/2014	Montgomery et al.	9,874,112 B2	1/2018	Giegel
8,720,563 B2	5/2014	Joseph et al.	9,932,861 B2	4/2018	Preuss et al.
8,752,382 B2	6/2014	Lehar	9,932,970 B1	4/2018	Jeter
8,756,908 B2	6/2014	Sheridan et al.	9,957,432 B2	5/2018	Galindo et al.
8,771,603 B2	7/2014	Harless et al.	9,994,751 B2	6/2018	Hulse et al.
8,783,034 B2	7/2014	Held	10,005,950 B2	6/2018	Smith et al.
8,791,054 B2	7/2014	Deville	10,024,198 B2	7/2018	Held et al.
8,820,075 B2	9/2014	Kaminsky	10,059,870 B2	8/2018	Joseph et al.
8,820,079 B2	9/2014	Zyhowski et al.	10,060,283 B2	8/2018	Tomigashi et al.
8,839,857 B2	9/2014	Schultz et al.	10,060,302 B2	8/2018	Weng et al.
8,841,041 B2	9/2014	Biederman et al.	10,060,652 B2	8/2018	Tahara
8,850,814 B2	10/2014	Kaplan et al.	10,077,683 B2	9/2018	Close
8,857,186 B2	10/2014	Held	10,082,030 B2	9/2018	Genrup et al.
8,869,531 B2	10/2014	Held	10,113,389 B2	10/2018	Pandey et al.
8,881,805 B2	11/2014	Klemencic	10,113,535 B2	10/2018	Conlon
8,919,123 B2	12/2014	Gibble et al.	10,138,405 B2	11/2018	Kulkarni et al.
8,959,914 B2	2/2015	Kasuya et al.	10,138,560 B2	11/2018	Reyes et al.
8,984,883 B2	3/2015	Riley	10,221,770 B2	3/2019	Sheridan
8,984,884 B2	3/2015	Xu et al.	10,227,893 B2	3/2019	McCune et al.
9,003,798 B2	4/2015	Yanagi	10,234,183 B2	3/2019	Hashimoto
9,014,791 B2	4/2015	Held	10,247,044 B2	4/2019	Barmeier et al.
9,062,898 B2	6/2015	Held	10,247,046 B2	4/2019	Schuster et al.
9,077,220 B2	7/2015	Kyle et al.	10,267,184 B2	4/2019	Bowan et al.
9,080,789 B2	7/2015	Hamstra et al.	10,323,545 B2	6/2019	Johnson
9,091,278 B2	7/2015	Vermeersch	10,352,197 B2	7/2019	Grill et al.
9,109,398 B2	8/2015	Harris et al.	10,357,726 B2	7/2019	Qin et al.
9,115,604 B2	8/2015	Bronicki	10,400,635 B2	9/2019	Johnson et al.
9,118,226 B2	8/2015	Kacludis et al.	10,435,604 B2	10/2019	Kontomaris et al.
9,121,259 B2	9/2015	Bryant et al.	10,458,206 B2	10/2019	Al-Dossary et al.
9,150,774 B2	10/2015	Reddy et al.	10,465,104 B2	11/2019	Ravi et al.
9,181,930 B2	11/2015	Klemencic	10,465,491 B2	11/2019	Moore
9,217,370 B2	12/2015	Wang et al.	10,472,994 B2	11/2019	Avadhanula et al.
9,234,522 B2	1/2016	Jonsson et al.	10,494,897 B2	12/2019	Pandey et al.
9,243,616 B2	1/2016	Lee et al.	10,495,098 B2	12/2019	Preuss et al.
9,297,367 B2	3/2016	Ramaswamy et al.	10,519,814 B2	12/2019	Quoilin
9,316,404 B2	4/2016	Gurin	10,527,026 B2	1/2020	Muir et al.
9,322,300 B2	4/2016	Mirmobin et al.	10,563,927 B2	2/2020	Papadopoulos et al.
9,331,547 B2	5/2016	Bronicki	10,570,777 B2	2/2020	Bowan
9,341,084 B2	5/2016	Xie et al.	10,570,782 B2	2/2020	Lintl et al.
9,341,086 B2	5/2016	Batscha et al.	10,584,660 B2	3/2020	Sheridan et al.
9,359,919 B1	6/2016	Berry	10,590,324 B2	3/2020	Kulkarni et al.
9,376,937 B2	6/2016	Goswami et al.	10,590,802 B2	3/2020	McCune et al.
9,394,764 B2	7/2016	Favilli et al.	10,598,160 B2	3/2020	Sumrall
9,394,771 B2	7/2016	Wiggs	10,619,520 B2	4/2020	Juchymenko
9,403,102 B2	8/2016	Wu et al.	10,626,709 B2	4/2020	Al-Dossary
			10,670,340 B2	6/2020	Batscha et al.
			10,724,805 B2	7/2020	Barmeier et al.
			10,767,904 B2	9/2020	von Düring
			10,788,267 B2	9/2020	Dokic et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

10,794,292 B2	10/2020	Kupratis et al.	2010/0034684 A1	2/2010	Ast
10,883,388 B2	1/2021	Held	2010/0045042 A1	2/2010	Hinders et al.
10,934,895 B2	3/2021	Held et al.	2010/0071366 A1	3/2010	Klemencic
10,947,626 B2	3/2021	Pinder et al.	2010/0071409 A1	3/2010	Kaart
10,947,839 B2	3/2021	Cuthbert et al.	2010/0077752 A1	4/2010	Papile
10,975,279 B2	4/2021	Kontomaris et al.	2010/0077792 A1	4/2010	Gurin
11,022,070 B2	6/2021	Aumann et al.	2010/0187319 A1	7/2010	Isom et al.
11,137,169 B2	10/2021	Buscheck et al.	2010/0192573 A1	8/2010	Hamilton
11,168,673 B2	11/2021	Younes et al.	2010/0194111 A1	8/2010	Van den Bossche et al.
11,174,715 B2	11/2021	Atisele	2010/0218930 A1	9/2010	Proeschel
11,187,112 B2	11/2021	Held	2010/0300093 A1	12/2010	Doty
11,187,212 B1	11/2021	Bodishbaugh et al.	2010/0319354 A1	12/2010	Guidati et al.
11,220,932 B2	1/2022	Kontomaris et al.	2011/0000210 A1	1/2011	Miles
11,236,735 B1	2/2022	Bodishbaugh et al.	2011/0000227 A1	1/2011	Kamiya
11,255,315 B1	2/2022	Bodishbaugh et al.	2011/0030404 A1	2/2011	Gurin et al.
11,255,576 B2	2/2022	Higgins et al.	2011/0041502 A1	2/2011	Zimron et al.
11,274,660 B2	3/2022	Radke	2011/0041505 A1	2/2011	Kasuya et al.
11,274,663 B1	3/2022	Bodishbaugh et al.	2011/0083620 A1	4/2011	Yoon
11,280,322 B1	3/2022	Bodishbaugh et al.	2011/0100003 A1	5/2011	McLeod et al.
11,293,414 B1	4/2022	Bodishbaugh et al.	2011/0126539 A1	6/2011	Ramaswamy et al.
11,326,479 B2	5/2022	Radke	2011/0138809 A1	6/2011	Ramaswamy et al.
11,326,550 B1	5/2022	Bodishbaugh et al.	2011/0272166 A1	11/2011	Hunt
11,359,576 B1	6/2022	Bodishbaugh et al.	2011/0314818 A1	12/2011	Breen et al.
11,359,612 B1	6/2022	Bodishbaugh et al.	2012/0001429 A1	1/2012	Saar et al.
11,365,652 B2	6/2022	Gaia et al.	2012/0042650 A1	2/2012	Ernst et al.
11,396,828 B2	7/2022	Chase	2012/0111004 A1	5/2012	Conry
11,421,625 B1	8/2022	Bodishbaugh et al.	2012/0131918 A1	5/2012	Held
11,421,663 B1	8/2022	Bodishbaugh et al.	2012/0145397 A1	6/2012	Schultz et al.
11,480,074 B1	10/2022	Bodishbaugh et al.	2012/0174581 A1	7/2012	Vaughan et al.
11,486,330 B2	11/2022	Bodishbaugh et al.	2012/0174622 A1	7/2012	Granier
11,486,370 B2	11/2022	Bodishbaugh et al.	2012/0192560 A1	8/2012	Ernst et al.
11,493,029 B2	11/2022	Bodishbaugh et al.	2012/0198844 A1	8/2012	Kaminsky
11,542,888 B2	1/2023	Bodishbaugh et al.	2012/0261092 A1	10/2012	Heath et al.
11,549,402 B2	1/2023	Bodishbaugh et al.	2012/0291433 A1	11/2012	Meng et al.
11,572,849 B1	2/2023	Bodishbaugh et al.	2012/0292112 A1	11/2012	Lakic
11,578,706 B2	2/2023	Bodishbaugh et al.	2012/0292909 A1	11/2012	Erikson
11,592,009 B2	2/2023	Bodishbaugh et al.	2012/0315158 A1	12/2012	Klaus
11,598,320 B2	3/2023	Bodishbaugh et al.	2013/0041068 A1	2/2013	Reddy et al.
11,624,355 B2	4/2023	Bodishbaugh et al.	2013/0067910 A1	3/2013	Ishiguro et al.
11,644,014 B2	5/2023	Bodishbaugh et al.	2013/0091843 A1	4/2013	Zyhowski et al.
11,644,015 B2	5/2023	Bodishbaugh et al.	2013/0129496 A1	5/2013	Eckert
11,668,209 B2	6/2023	Bodishbaugh et al.	2013/0139509 A1	6/2013	Berti
11,680,541 B2	6/2023	Bodishbaugh et al.	2013/0168089 A1	7/2013	Berg et al.
11,732,697 B2	8/2023	Bodishbaugh et al.	2013/0168964 A1	7/2013	Xu et al.
11,761,353 B2	9/2023	Bodishbaugh et al.	2013/0186089 A1	7/2013	Bruckner
11,761,433 B2	9/2023	Bodishbaugh et al.	2013/0217604 A1	8/2013	Fisk, Jr.
11,773,805 B2	10/2023	Bodishbaugh et al.	2013/0227947 A1	9/2013	Bronicki et al.
11,879,409 B2	1/2024	Bodishbaugh et al.	2013/0247569 A1	9/2013	Suter
11,905,934 B2	2/2024	Bodishbaugh et al.	2013/0298568 A1	11/2013	Pierson et al.
11,933,279 B2	3/2024	Bodishbaugh	2013/0299123 A1	11/2013	Matula
11,933,280 B2	3/2024	Bodishbaugh	2013/0299170 A1	11/2013	Joseph et al.
11,946,459 B2	4/2024	Bodishbaugh	2014/0011908 A1	1/2014	Reddy et al.
11,959,466 B2	4/2024	Bodishbaugh	2014/0026574 A1	1/2014	Leibowitz et al.
11,971,019 B2	4/2024	Bodishbaugh	2014/0033713 A1	2/2014	Juchymenko
12,049,875 B2	7/2024	Bodishbaugh	2014/0057810 A1	2/2014	Fisk, Jr.
2002/0178723 A1	12/2002	Bronicki et al.	2014/0087978 A1	3/2014	Deville
2003/0010652 A1	1/2003	Hunt	2014/0102098 A1	4/2014	Bowan et al.
2003/0029169 A1	2/2003	Hanna et al.	2014/0102103 A1	4/2014	Yamamoto
2004/0237890 A1	12/2004	Bour	2014/0123643 A1	5/2014	Ming
2005/0034467 A1	2/2005	Varney	2014/0130498 A1	5/2014	Randolph
2005/0109495 A1	5/2005	Cheng et al.	2014/0158429 A1	6/2014	Kader et al.
2005/0247056 A1	11/2005	Cogswell et al.	2014/0178180 A1	6/2014	Sheridan
2005/0247059 A1	11/2005	Cogswell et al.	2014/0206912 A1	7/2014	Iglesias
2006/0026961 A1	2/2006	Bronicki	2014/0224469 A1	8/2014	Mirmmobin
2006/0130480 A1	6/2006	Lovelace	2014/0296113 A1	10/2014	Reyes et al.
2007/0025854 A1	2/2007	Moore et al.	2014/0305125 A1	10/2014	Wang et al.
2008/0095611 A1	4/2008	Storage	2014/0366540 A1	12/2014	Zyhowski et al.
2008/0168772 A1	7/2008	Radcliff et al.	2015/0021924 A1	1/2015	Parella
2008/0217523 A1	9/2008	O'Sullivan	2015/0047351 A1	2/2015	Ishikawa et al.
2009/0071155 A1	3/2009	Boyapati	2015/0135708 A1	5/2015	Lutz et al.
2009/0211253 A1	8/2009	Radcliff et al.	2015/0192038 A1	7/2015	Sharp et al.
2009/0217664 A1	9/2009	Rapp et al.	2015/0226500 A1	8/2015	Reissner et al.
2009/0313999 A1	12/2009	Hunter	2015/0252653 A1	9/2015	Shelton, Jr.
2009/0320477 A1	12/2009	Juchymenko	2015/0300327 A1	10/2015	Sweatman et al.
2010/0018207 A1	1/2010	Juchymenko	2015/0330261 A1	11/2015	Held
			2015/0345341 A1	12/2015	Kacludis et al.
			2015/0345482 A1	12/2015	Klitzing et al.
			2015/0361831 A1	12/2015	Myers
			2016/0003108 A1	1/2016	Held et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0010512 A1 1/2016 Close
 2016/0017758 A1 1/2016 Vermeersch et al.
 2016/0017759 A1 1/2016 Gayawal et al.
 2016/0040557 A1 2/2016 Vermeersch et al.
 2016/0047540 A1 2/2016 Aumann et al.
 2016/0061055 A1 3/2016 Bowan
 2016/0076405 A1 3/2016 Hashimoto et al.
 2016/0084115 A1 3/2016 Ludewig et al.
 2016/0130985 A1 5/2016 O'Connor et al.
 2016/0160111 A1 6/2016 Smith et al.
 2016/0177887 A1 6/2016 Fischer
 2016/0201521 A1 7/2016 Karthaus
 2016/0222275 A1 8/2016 Galindo et al.
 2016/0257869 A1 9/2016 Kulkarni et al.
 2016/0312646 A1 10/2016 Juano
 2016/0340572 A1 11/2016 Pascarella et al.
 2016/0369408 A1 12/2016 Reyes et al.
 2017/0058181 A1 3/2017 Frantz et al.
 2017/0058722 A1 3/2017 Noureldin et al.
 2017/0130614 A1 5/2017 Held et al.
 2017/0145815 A1 5/2017 Cuthbert et al.
 2017/0159504 A1 6/2017 Ostrom et al.
 2017/0175582 A1 6/2017 McCune et al.
 2017/0175583 A1 6/2017 McCune et al.
 2017/0211829 A1 7/2017 Slack
 2017/0226402 A1 8/2017 Patil et al.
 2017/0233635 A1 8/2017 Pandey et al.
 2017/0240794 A1 8/2017 Iverson et al.
 2017/0254223 A1 9/2017 Goethals et al.
 2017/0254226 A1 9/2017 Heber et al.
 2017/0261268 A1 9/2017 Barmeier et al.
 2017/0276026 A1 9/2017 Barmeier et al.
 2017/0276435 A1 9/2017 Papadopoulos et al.
 2017/0362963 A1 9/2017 Hostler et al.
 2017/0284230 A1 10/2017 Juchymenko
 2017/0314420 A1 11/2017 Bowan et al.
 2017/0321104 A1 11/2017 Ravi et al.
 2017/0321107 A1 11/2017 Joseph et al.
 2017/0370251 A1 12/2017 McGrail
 2018/0094548 A1 4/2018 Jeter
 2018/0128131 A1 5/2018 Zyhowski et al.
 2018/0179960 A1 6/2018 Apte et al.
 2018/0224164 A1 8/2018 Lakic
 2018/0274524 A1 9/2018 Moncarz et al.
 2018/0313232 A1 11/2018 Auciello
 2018/0313340 A1 11/2018 Spadacini et al.
 2018/0328138 A1 11/2018 Pandey et al.
 2018/0340450 A1 11/2018 Avadhanula et al.
 2018/0355703 A1 12/2018 Al-Dossary
 2018/0356044 A1 12/2018 Monti et al.
 2019/0048759 A1 2/2019 Noureldin et al.
 2019/0055445 A1 2/2019 Kulkarni et al.
 2019/0128147 A1 5/2019 Liu
 2019/0128567 A1 5/2019 Redfern
 2019/0390660 A1 12/2019 McBay
 2020/0011426 A1 1/2020 Juchymenko
 2020/0025032 A1 1/2020 McCune et al.
 2020/0095899 A1 3/2020 Merswolke et al.
 2020/0200123 A1 6/2020 Aumann et al.
 2020/0200483 A1 6/2020 Ahlbom
 2020/0217304 A1 7/2020 Sumrall
 2020/0232342 A1 7/2020 McCune et al.
 2020/0248063 A1 8/2020 Stone
 2020/0308992 A1 10/2020 Juchymenko
 2020/0309101 A1 10/2020 Muir et al.
 2020/0354839 A1 11/2020 Pinder et al.
 2020/0386212 A1 12/2020 Atisele
 2020/0399524 A1 12/2020 Pisklak et al.
 2021/0017439 A1 1/2021 Ramirez Angulo et al.
 2021/0047963 A1 2/2021 Conde
 2021/0062682 A1 3/2021 Higgins et al.
 2021/0071063 A1 3/2021 Stone
 2021/0140684 A1 5/2021 Younes et al.
 2021/0172344 A1 6/2021 Juchymenko
 2021/0205738 A1 7/2021 Blomqvist et al.

2021/0285693 A1 9/2021 Gerson
 2021/0372668 A1 12/2021 Buscheck et al.
 2022/0090521 A1 3/2022 Kontomaris et al.
 2022/0186984 A1 6/2022 Gaia et al.
 2024/0026838 A1 1/2024 Bodishbaugh et al.
 2024/0093660 A1 3/2024 Bodishbaugh et al.
 2024/0159225 A1 5/2024 Bodishbaugh
 2024/0191703 A1 6/2024 Bodishbaugh
 2024/0209844 A1 6/2024 Bodishbaugh
 2024/0218772 A1 7/2024 Bodishbaugh
 2024/0254973 A1 8/2024 Bodishbaugh

FOREIGN PATENT DOCUMENTS

AU 2011336831 B2 12/2016
 AU 2012306439 B2 3/2017
 AU 2014225990 B2 7/2018
 CA 2692629 1/2009
 CA 2698334 4/2009
 CA 2676502 A1 2/2011
 CA 2679612 5/2018
 CA 2676502 12/2018
 CA 2952379 C 4/2019
 CN 204661610 U 9/2015
 CN 103174473 10/2015
 CN 102812212 4/2016
 CN 103174475 8/2016
 CN 106517718 3/2017
 CN 107246550 10/2017
 CN 108302946 A 7/2018
 CN 108457609 A 8/2018
 CN 207761721 U 8/2018
 CN 209457990 U 10/2019
 CN 111837006 10/2020
 CN 111911255 11/2020
 CN 113266815 A 8/2021
 CN 113983844 A 1/2022
 DE 10337240 A1 3/2005
 DE 102011006066 A1 9/2012
 DE 102012214907 A1 10/2013
 DE 102012014443 1/2014
 DE 102013009351 1/2014
 DE 102018201172 A1 7/2019
 EP 0652368 5/1995
 EP 1507069 A1 2/2005
 EP 2530255 A2 12/2012
 EP 2201666 3/2013
 EP 1573173 4/2013
 EP 1713877 5/2013
 EP 1869293 5/2013
 EP 2222939 11/2013
 EP 1706667 B1 10/2014
 EP 2167872 2/2016
 EP 2446122 B1 8/2017
 EP 2478201 B1 8/2017
 EP 3102796 B1 1/2018
 EP 3514339 A1 7/2019
 EP 2550436 B1 8/2019
 EP 3464836 4/2020
 EP 3631173 A1 4/2020
 EP 2948649 B1 12/2020
 EP 3540331 B1 12/2020
 FR 2738872 3/1997
 GB 2336943 6/2003
 IN 247090 12/2003
 IN 256000 1/2005
 IN 202111000822 10/2021
 JP 08192150 7/1996
 JP 2001183030 7/2001
 JP 2009127627 A 6/2009
 JP 2010166805 A 7/2010
 JP 2010249501 A 11/2010
 JP 2010249502 A 11/2010
 JP 2011064451 A 3/2011
 JP 4668189 B2 4/2011
 JP 2011069370 A 4/2011
 JP 2011106459 A 6/2011
 JP 2011137449 A 7/2011
 JP 2013151931 A 8/2013

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2013238228	A	11/2013
JP	2014016124	A	1/2014
JP	2014080975	A	5/2014
JP	2014109279	A	6/2014
JP	2015149885	A	8/2015
JP	2016006323	A	1/2016
JP	2016105687	A	6/2016
JP	2016188640	A	11/2016
JP	2021167601	A	10/2021
KR	101126833		3/2012
KR	20120067710		6/2012
KR	20130023578	A	3/2013
KR	1691908		1/2017
KR	2075550		2/2020
KR	2185002		12/2020
NZ	581457		11/2011
RU	2006142350		6/2008
SG	191467		7/2013
SG	191468		7/2013
SG	192327		8/2013
WO	1993/001397		1/1993
WO	1994028298		12/1994
WO	2005014981	A1	2/2005
WO	2005019606	A1	3/2005
WO	2005049975		6/2005
WO	2005100755	A1	10/2005
WO	2006/014609		2/2006
WO	2006/027770		3/2006
WO	2006060253		6/2006
WO	2006/092786		9/2006
WO	2006138459		12/2006
WO	2007048999		5/2007
WO	20070079245		7/2007
WO	2007137373		12/2007
WO	2008052809		5/2008
WO	2008106774	A1	9/2008
WO	2009017471		2/2009
WO	2009017474		2/2009
WO	2009027302	A2	3/2009
WO	2009030283	A2	3/2009
WO	2009/058112		5/2009
WO	2009095127	A2	8/2009
WO	2009/142608		11/2009
WO	2010021618		2/2010
WO	2010/039448		4/2010
WO	2010/065895		6/2010
WO	2009017473		8/2010
WO	2010106089	A2	9/2010
WO	2010127932	A2	11/2010
WO	2010/143046		12/2010
WO	2010/143049		12/2010
WO	2011012047	A1	2/2011
WO	2011/066032		6/2011
WO	2011073469		6/2011
WO	2011/061601		8/2011
WO	2011/103560		8/2011
WO	2011093854		8/2011
WO	2011/137980		11/2011
WO	2012060510		5/2012
WO	2012/079694		6/2012
WO	2012074940	A2	6/2012
WO	2012/112889		8/2012
WO	2012/142765		10/2012
WO	2012/151447		11/2012
WO	2013/014509		1/2013
WO	2013059695		4/2013
WO	2013/082575		6/2013
WO	2013103592		7/2013
WO	2013110375	A2	8/2013
WO	2013115668	A1	8/2013
WO	2013/136131		9/2013
WO	2014019755	A1	2/2014
WO	2014042580		3/2014
WO	2014053292	A2	4/2014
WO	2014059235	A1	4/2014

WO	2014065977	5/2014
WO	2014/124061	8/2014
WO	2014/167795	10/2014
WO	2014154405	A1 10/2014
WO	2014159520	A1 10/2014
WO	2014159587	A1 10/2014
WO	2014160257	A1 10/2014
WO	2014164620	10/2014
WO	2014164620	A1 10/2014
WO	2014165053	10/2014
WO	2014165053	A1 10/2014
WO	2014165144	A1 10/2014
WO	2014191157	A2 12/2014
WO	2015/040279	3/2015
WO	2015034987	A1 3/2015
WO	2015/059069	4/2015
WO	2015078829	A1 6/2015
WO	2015/135796	9/2015
WO	2015131940	A1 9/2015
WO	2015/158600	10/2015
WO	2015192005	A1 12/2015
WO	2016039655	A1 3/2016
WO	2016049712	4/2016
WO	2016050365	A1 4/2016
WO	2016050366	A1 4/2016
WO	2016050367	A1 4/2016
WO	2016050368	A1 4/2016
WO	2016050369	A1 4/2016
WO	2016/069242	5/2016
WO	2013103631	5/2016
WO	2016073245	A1 5/2016
WO	2016/087920	6/2016
WO	2016099975	A1 6/2016
WO	2016147419	9/2016
WO	2016/196144	12/2016
WO	2016204287	12/2016
WO	2017041147	3/2017
WO	2017065683	4/2017
WO	2017123132	7/2017
WO	2017/146712	8/2017
WO	2017/147400	8/2017
WO	2017203447	11/2017
WO	2018/044690	3/2018
WO	2018/107279	6/2018
WO	2018106528	6/2018
WO	2018/210528	11/2018
WO	2018217969	A1 11/2018
WO	2018227068	A1 12/2018
WO	2019004910	1/2019
WO	2019060844	3/2019
WO	2019067618	4/2019
WO	2019086960	A1 5/2019
WO	2019/157341	8/2019
WO	2019155240	8/2019
WO	2019/178447	9/2019
WO	2020152485	7/2020
WO	2020153896	7/2020
WO	2020/186044	9/2020
WO	2020201843	10/2020
WO	2020/229901	11/2020
WO	2020/097714	12/2020
WO	2020239067	12/2020
WO	2020239068	12/2020
WO	2020239069	12/2020
WO	2020251980	A1 12/2020
WO	2021004882	1/2021
WO	2021013465	A1 1/2021
WO	2021096696	A1 5/2021
WO	2021107834	6/2021
WO	2022/061320	3/2022

OTHER PUBLICATIONS

Richter, Alexander, GreenFire Energy and Mitsui Oil Exploration Co. are partnering on a closed-loop geothermal pilot project in Japan, Think GeoEnergy, Apr. 6, 2021.

(56)

References Cited

OTHER PUBLICATIONS

Edwards, Alex, Dallas Innovates, Hunt Energy Network's New Venture Will Put 50 Batteries Across Texas, Giving ERCOT a Portfolio of Energy Generation, Apr. 1, 2021.

Guo, Boyun, Petroleum Engineering, A Computer-Assisted Approach, Dec. 21, 2006.

Li, Tailu et al., Cascade utilization of low temperature geothermal water in oilfield combined power generation, gathering heat tracing and oil recovery, *Applied Thermal Engineering* 40 (2012).

Sherven, Bob, Automation Maximizes performance for shale wells, *Oil&Gas Journal*, 2013.

Hu, Kaiyong et al., A case study of an ORC geothermal power demonstration system under partial load conditions in Huabei Oilfield, China, *ScienceDirect*, 2017.

Liu, Xiaolei et al., A systematic study of harnessing low-temperature geothermal energy from oil and gas reservoirs, *Elsevier, ScienceDirect, Energy*, 2017.

Wang, Kai, et al., A comprehensive review of geothermal energy extraction and utilization in oilfields, *Elsevier, ScienceDirect, Journal of Petroleum Science and Engineering*, 2017.

Cutright, Bruce L., The Transformation of Tight Shale Gas Reservoirs to Geothermal Energy Production, Bureau of Economic Geology University of Texas, Austin Texas, Jun. 14, 2011.

Khennich, Mohammed et al., Optimal Design of ORC Systems with a Low-Temperature Heat Source, *Entropy* 2012, 14, 370-389; doi:10.3390/e14020370.

Dambly, Benjamin W., et al., The Organic Rankine Cycle for Geothermal Power Generation, *Geothermal Energy*, 2007.

Obi, John Besong, State of art on ORC applications for waste heat recovery and micro-cogeneration for installations up to 100kWe, *Elsevier, Energy Procedia* 82 (2015) 994-1001.

Obafunmi, Jaiyeje Sunday, Thermodynamic Analysis of Organic Rankine Cycles, Eastern Mediterranean University Jul. 2014, Gazimağusa, North Cyprus.

Dong, Benshi et al., Potential of low temperature organic Rankine cycle with zeotropic mixtures as working fluid, *Elsevier, ScienceDirect, Energy Procedia* 105 (2017) 1489-1494.

Iqbal, MdArbab et al., Trilateral Flash Cycle (TFC): a promising thermodynamic cycle for low grade heat to power generation, *Elsevier, ScienceDirect, Energy Procedia* 160 (2019) 208-214.

Bao, Junjiang et al., A review of working fluid and expander selections for organic Rankine cycle, *Elsevier, ScienceDirect, Renewable and Sustainable Energy Reviews* 24 (2013) 325-342.

Ajmotokan, Habeeb A. et al., Trilateral Flash Cycle for Recovery of Power from a Finite Low-Grade Heat Source, *Proceedings of the 24th European Symposium on Computer Aided Process Engineering—Escape* 24 Jun. 15-18, 2014, Budapest, Hungary. Copyright © 2014 Elsevier B.V.

Hung Tzu-Chen, et al., The Development and Application of a Small-Scale Organic Rankine Cycle for Waste Heat Recovery, *IntechOpen*, 2019.

Kong, Rithy et al., Thermodynamic performance analysis of a R245fa organic Rankine cycle (ORC) with different kinds of heat sources at evaporator, *Elsevier, ScienceDirect, Case Studies in Thermal Engineering* 13 (2019) 100385.

Lukawski, Maciej Z. et al., Impact of molecular structure of working fluids on performance of organic Rankine cycles (ORCs), *Sustainable Energy Fuels*, 2017, 1, 1098.

Saleh, Bahaa et al., Working fluids for low-temperature organic Rankine cycles, *Elsevier, ScienceDirect, Energy* 32 (2007) 1210-1221.

Brasz, Lars J. et al., Ranking of Working Fluids for Organic Rankine Cycle Applications, *Purdue University, Purdue e-Pubs*, (2004). *International Refrigeration and Air Conditioning Conference*. Paper 722.

Miller, Patrick C., Research uses landfill gas tech for Bakken flaring solution, *The Bakken magazine*, Sep. 16, 2015.

ElectraTherm, Inc., Power+ Generator 4400B & 4400B+, Nov. 24, 2020.

ElectraTherm, Inc., Heat To Power Generation Base Load Renewable Energy, Mar. 2020.

ElectraTherm, Inc., Power+ Generator, Nov. 25, 2020.

ElectraTherm, Inc., Generating Clean Power From Waste Heat, Nov. 2020.

ElectraTherm, Inc., Power+ Generator, May 19, 2020.

Sneary, Loy et al., Gulf Coast Green Energy, Flare Gas Reduction Trial Using an Organic Rankine Cycle Generator, Jan. 11, 2016.

Enertime, ORC for Industrial Waste Heat Recovery, Aug. 2017.

Enogia, Generate power from your waste heat thanks to our ORC, 2019.

UTC Power, PureCycle, 200 Heat-to-Electricity Power System, 2004.

Rank, MT3 machine, Dec. 17, 2018.

Heat Recovery Solutions, Clean Cycle Containerized Solution, 2009.

Triogen BV, Specification: E-Box Engine Application, Feb. 15, 2019.

International Search Report and Written Opinion for PCT/US2022/071327, Aug. 29, 2022.

International Search Report and Written Opinion for PCT/US2022/071328, Sep. 9, 2022.

International Search Report and Written Opinion for PCT/US2022/071329, Aug. 25, 2022.

International Search Report and Written Opinion for PCT/US2022/071480, Aug. 3, 2022.

International Search Report and Written Opinion for PCT/US2022/071482, Aug. 2, 2022.

"From Waste Heat To High Performance", PBOG (Permian Basin Oil and Gas Magazine), Apr. 26, 2013.

"Turning Waste Heat Into Clean Power; GNP's Expander System", Great Northern Power Corporation, 2022.

Ng et al., "Thermo-Economic Performance of an Organic Rankine Cycle System Recovering Waste Heat Onboard an Offshore Service Vessel", *Journal of Marine Science and Engineering*, May 14, 2020.

"First Flare Elimination Demonstration", *ElectraTherm*, 2022.

International Search Report and Written Opinion for PCT/US2022/071472, May 9, 2022.

International Search Report and Written Opinion for PCT/US2022/071475, May 17, 2022.

International Search Report and Written Opinion for PCT/US2022/071474, Jun. 10, 2022.

International Search Report and Written Opinion for PCT/US2022/071486, Jun. 14, 2022.

International Search Report and Written Opinion for PCT/US2022/071323, Jun. 28, 2022.

International Search Report and Written Opinion for PCT/US2022/071325, Jun. 28, 2022.

Invitation to Pay Additional Fees and Communication Relating to Results of Partial International Search for PCT/US2022/071329, mailed Jun. 27, 2022.

Invitation to Pay Additional Fees and Communication Relating to Results of Partial International Search for PCT/US2022/071327, mailed Jul. 4, 2022.

International Search Report and Written Opinion for PCT/US2022/071313, Jul. 5, 2022.

International Search Report and Written Opinion for PCT/US2022/071517, Jun. 27, 2022.

International Search Report and Written Opinion for PCT/US2022/071484, Jun. 27, 2022.

International Search Report and Written Opinion for PCT/US2022/071319, Jul. 12, 2022.








FIG. 1A



**B
1
G.
F**










FIG. 2C




FIG. 2D




FIG. 2E





FIG. 2F






FIG. 2H




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6

SYSTEMS AND METHODS FOR GENERATION OF ELECTRICAL POWER AT A DRILLING RIG

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. Non-Provisional application Ser. No. 18/099,807, filed Jan. 20, 2023, titled “Systems and Methods for Generation of Electrical Power at a Drilling Rig,” which is a continuation of U.S. Non-Provisional application Ser. No. 17/657,015, filed Mar. 29, 2022, titled “Systems and Methods for Generation of Electrical Power at a Drilling Rig,” now U.S. Pat. No. 11,592,009, issued Feb. 28, 2023, which is a non-provisional of and claims priority to and the benefit of U.S. Provisional Application No. 63/269,862, filed Mar. 24, 2022, titled “Systems and Methods for Generation of Electrical Power at a Drilling Rig,” and U.S. Provisional Application No. 63/269,572, filed Mar. 18, 2022, titled “Systems and Methods for Generation of Electrical Power at a Drilling Rig,” U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entirety. U.S. Non-Provisional application Ser. No. 17/657,015 also is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/305,297, filed Jul. 2, 2021, titled “Systems for Generating Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production Based on Working Fluid Temperature,” which claims priority to and the benefit of U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entirety. U.S. Non-Provisional application Ser. No. 17/657,015 further is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/578,520, filed Jan. 19, 2022, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” now U.S. Pat. No. 11,326,550, issued May 10, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entirety. U.S. Non-Provisional application Ser. No. 17/657,015 also further is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/578,528, filed Jan. 19, 2022, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” now U.S. Pat. No. 11,480,074, issued Oct. 25, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entirety. U.S. Non-Provisional application Ser. No. 17/657,015 still further is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/578,542, filed Jan. 19, 2022, titled “Systems and Meth-

ods Utilizing Gas Temperature as a Power Source,” now U.S. Pat. No. 11,480,074, issued Oct. 25, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entirety. U.S. Non-Provisional application Ser. No. 17/657,015 additionally is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/578,550, filed Jan. 19, 2022, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” which claims priority to and the benefit of U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entirety. U.S. Non-Provisional application Ser. No. 17/657,015 is also a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/650,811, filed Feb. 11, 2022, titled “Systems for Generating Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production Based on Well-head Fluid Temperature,” now U.S. Pat. No. 11,578,706, issued Feb. 14, 2023, which is a continuation of U.S. Non-Provisional application Ser. No. 17/305,298, filed Jul. 2, 2021, titled “Controller for Controlling Generation of Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production,” now U.S. Pat. No. 11,280,322, issued Mar. 22, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entirety. U.S. Non-Provisional application Ser. No. 17/657,015 further still is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/670,827, filed Feb. 14, 2022, titled “Systems and Methods for Generation of Electrical Power in an Organic Rankine Cycle Operation,” now U.S. Pat. No. 11,421,663, issued Aug. 23, 2022, which is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/305,296, filed Jul. 2, 2021, titled “Controller for Controlling Generation of Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production,” now U.S. Pat. No. 11,255,315, issued Feb. 22, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entirety. U.S. Non-Provisional application Ser. No. 17/657,015 yet further is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/682,126, filed Feb. 28, 2022, titled “Systems and Methods for Generation of Electrical Power in an Organic Rankine Cycle Operation,” now U.S. Pat. No. 11,359,612, issued Jun. 14, 2022, which is a continuation of U.S. Non-Provisional application Ser. No. 17/494,936, filed Oct. 6, 2021, titled “Systems and Methods for Generation of Electrical Power in an Organic Rankine Cycle Operation,” now U.S. Pat. No. 11,293,414, issued Apr. 5, 2022, which is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/305,296, filed Jul. 2, 2021, titled “Controller for Controlling Generation of Geothermal Power in an Organic Rankine Cycle Operation

During Hydrocarbon Production,” now U.S. Pat. No. 11,255,315, issued Feb. 22, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entireties.

FIELD OF DISCLOSURE

Embodiments of this disclosure relate to generating electrical power from heat generated on, in, at, about, or adjacent a drilling rig, and more particularly, to systems and methods for generating electrical power in an organic Rankine cycle (ORC) operation in the vicinity of a drilling rig during drilling operations to thereby supply electrical power to one or more of operational equipment, a grid power structure, and an energy storage device.

BACKGROUND

In some instances, an organic Rankine cycle (ORC) generator or unit may include a working fluid loop that flows to a heat source, such that the heat from the heat source causes the working fluid in the loop to change phases from a liquid to a vapor. The vaporous working fluid may then flow to a gas expander, causing the gas expander to rotate. The rotation of the gas expander may cause a generator to generate electrical power. The vaporous working fluid may then flow to a condenser or heat sink. The condenser or heat sink may cool the working fluid, causing the working fluid to change phase from the vapor to the liquid. The working fluid may circulate through the loop in such a continuous manner, thus the ORC generator or unit may generate electrical power.

SUMMARY

As noted, for example, organic Rankine cycle (ORC) generators or units may generate electrical power via an ORC operation based on heat transfer to a working fluid. While various types of sources of heat may be utilized, there is currently no system, method, or controller available to utilize heat generated in the vicinity (e.g., at, on, in, about, or adjacent) of a drilling rig and, more particularly, to utilize heated drilling mud and/or to optimize or ensure that drilling fluid or drilling mud is cooled to a preselected or specified level, that the overall energy efficiency of equipment at the drilling rig is increased, that the amount of electrical power utilized at the drilling rig is decreased, and/or that engine performance or efficiency is increased. For example, when drilling fluid or drilling mud is utilized as the source of heat in such operations, then a mud chiller may not be utilized or may consume less electrical power to cool the drilling fluid or drilling mud to a particular, preselected, and/or specified temperature. Further, the mud chiller may utilize electrical power generated by the ORC unit. In other embodiments, working fluid flowing to a heat exchanger corresponding to the drilling fluid or drilling mud may be increased or decreased to adjust generation of electrical power and/or control temperature of the drilling fluid or drilling mud. In other embodiments, engine performance and/or efficiency and/or electrical power generation may be adjusted based on the amount of working fluid flowing to heat exchangers corresponding to heat associated with engine exhaust and/or with fluid from an engine’s water jacket.

Accordingly, Applicants have recognized a need for systems and methods to generate electrical power by use of heat generated in the vicinity of a drilling rig during drilling operations to thereby supply electrical power to one or more of in-field operational equipment, a grid power structure, and an energy storage device, and/or, more particularly to provide electrical power to a mud chiller and/or increase efficiency of a generator and/or engine at the drilling rig. The present disclosure includes embodiments of such systems and methods.

As noted, the present disclosure is generally directed to systems and methods for generating electrical power by use of heat generated at a drilling rig during a drilling operation. During drilling operations, drilling fluid or drilling mud is pumped through a drill string or drill pipe to and through a drill bit positioned or connected to the distal end of the drill string or drill pipe. The drill bit may break apart rock and/or other formations in the subsurface via rotation of the drill string or drill pipe and/or via the flow of drilling fluid through the drill bit (e.g., the flow of drilling fluid to cause the drill bit to rotate) thereby forming a borehole. The drilling fluid may also cool the drill bit. As the drill bit operates, the friction between the drill bit and the rock and/or other formations in the subsurface may generate heat. Such heat may cause the drill bit to exhibit premature wear and/or to not operate properly. Further, the heat may decrease the overall lifetime (e.g., the time that the drill bit is utilized) of the drill bit and/or other bottom-hole assembly components (e.g., drill collars, stabilizers, reamers, shocks, hole-openers, bit subs, etc.). To ensure that the drill bit operates properly and/or to extend the life or use of the drill bit, the drilling fluid may be utilized to cool the drill bit. The drilling fluid may also be utilized to carry cuttings and other debris caused by forming the borehole. The drilling fluid may flow up the borehole above the surface and out of the borehole via a drilling fluid return pipeline. The drilling fluid return pipeline may connect directly to a drilling fluid heat exchanger or may connect to the drilling fluid heat exchanger via a control valve. The control valve may divert a portion or all of the drilling fluid to the drilling fluid heat exchanger.

The drilling rig may include other sources of heat. For example, an engine to drive the drilling fluid pump or mud pump may produce heated fluid via an engine’s water jacket and/or heated exhaust. In such examples, the exhaust may be transported, via an exhaust pipeline to an exhaust heat exchanger. An exhaust control valve may be positioned along the exhaust pipeline to divert a portion or all of the exhaust from the exhaust heat exchanger to the atmosphere when the exhaust is outside a specified operating range.

Another source of heat may include fluid from an engine’s water (or other fluid, e.g., coolant) jacket, for example. As an engine operates, the engine may generate heat. The heat may cause parts and consumables (e.g., oil and/or seals and/or sealants) to wear out or break down faster and/or cause formation of deposits thereby impeding airflow through the engine and decreasing engine performance. As such, an engine may include a water jacket. Water or other coolant may flow through the jacket, absorb heat from the engine, and flow to a heat sink where the absorbed heat may dissipate. In such examples, fluid from the engine’s water jacket may flow through a water jacket pipeline to a water jacket heat exchanger. A water jacket fluid control valve may be positioned along the water jacket fluid pipeline to divert a portion or all of the water or other coolant in the water

5

jacket to a water jacket heat exchanger when the fluid from the engine's water jacket is within a specified operating range.

In such embodiments, a system may include each of these heat exchangers. Each of the heat exchangers may connect to a supply manifold and a return manifold. The amount of working fluid flowing to/from the supply manifold and return manifold, respectively, and/or the amount of working fluid flowing to each heat exchanger from the return manifold may be controlled by one or more flow control devices. Adjusting the flow of working fluid to any of the heat exchangers may be performed based on a number of factors, such as engine performance and/or efficiency and/or electrical power generation may be adjusted based on the amount of working fluid flowing to heat exchangers corresponding to heat associated with engine exhaust and/or with fluid from an engine's water jacket.

Accordingly, an embodiment of the disclosure is directed to a method for generating power in an organic Rankine cycle (ORC) operation in the vicinity of a drilling rig. The method may include, during a drilling operation, pumping, via a pump, drilling fluid from a drilling fluid container to a proximal end of a drill pipe. The pump may be driven by an engine during the drilling operation. Further, the drilling rig may include one or more additional engines to provide electrical power to drilling rig equipment. The drilling fluid may flow through an interior of the drill pipe to the distal end of the drill pipe. The distal end of the drill pipe may be connected to a drill bit. The flow of drilling fluid may cause the drill bit to rotate. The rotation of the drill bit may form a borehole in a subsurface and thereby generate a heated drilling fluid. The heated drilling fluid may flow up the borehole to a drilling fluid return pipe above the subsurface via an annulus defined by a space between an outer surface of the drill pipe and an inner surface of the borehole. The method may include diverting, via a heat exchanger supply valve, the heated drilling fluid from the drilling fluid return pipe to a heat exchanger. The heat exchanger may be positioned to transfer heat from the heated drilling fluid to a flow of a working fluid to generate a cooled drilling fluid and a heated working fluid. The heated working fluid may cause an ORC unit to generate electrical power. The method may include returning the cooled drilling fluid to the drilling fluid container.

An embodiment of a method also may include, prior to returning the cooled drilling fluid to the drilling fluid container, degassing the cooled drilling fluid and removing cuttings included in the cooled drilling fluid from formation of the borehole. The method further may include, prior to diversion of the heated drilling fluid, sensing, via a temperature sensor positioned along the drilling fluid return pipe, a temperature of the heated drilling fluid. The method additionally may include, in response to the temperature of the heated drilling fluid being lower than an ORC operating range, adjusting the heat exchanger supply valve to a closed position to thereby prevent heated drilling fluid to flow therethrough, and in response to the temperature of the heated drilling fluid being within an ORC operating range, adjusting the heat exchanger supply valve to an opened position to thereby divert the heated drilling fluid to the heat exchanger. The transfer of heat from the heated drilling fluid to the flow of the working fluid may extend a time that bottom-hole assembly components are utilized and reduces a total amount of electrical power generated by generator sets of the drilling rig.

In another embodiment, a method may include, during operation of (1) the pump via the engine and (2) the one or

6

more additional engines, transporting exhaust produced by one of the engine or one or more additional engines to a second heat exchanger. The second heat exchanger may indirectly transfer heat from the exhaust to a flow of a second working fluid thereby to cause the ORC unit to generate electrical power. The method may include, prior to transport of the exhaust to the second heat exchanger: sensing, via an exhaust inlet sensor, an exhaust thermal mass of the exhaust produced by one of the one or more engines; and, in response to the exhaust thermal mass being outside of an exhaust thermal mass range, adjusting an exhaust control valve to partially or fully prevent or allow flow of the exhaust from the one of the one or more engines to the second heat exchanger. The one or more additional engines may drive generator sets and each of the generator sets may generate a total of about 2 megawatts to about 10 megawatts of electrical power. The exhaust from the engine and one or more of the additional engines, for example, may be about 500° Fahrenheit (F) to about 1200° F. at about 2000 cubic feet per minute (CFM) to about 20000 CFM.

In another embodiment, a method may include, during operation of (1) the pump via the engine and (2) the one or more additional engines, transporting a flow of heated coolant from a water jacket associated with one of the one or more engines to a third heat exchanger, the third heat exchanger to indirectly transfer heat from the heated coolant to a flow of a third working fluid, thereby to cause the ORC unit to generate electrical power. The method may include, prior to transport of the heated coolant to the second heat exchanger, sensing, via a water jacket inlet temperature sensor, a heated coolant temperature of the flow of heated coolant from the water jacket, and in response to the heated coolant temperature being outside of a water jacket temperature range, adjusting a water jacket control valve to prevent or allow flow of the heated coolant from the water jacket to the second heat exchanger. The heated coolant, for example, may be about 165° F. to about 230° F. at about 70 gallons per minute to about 250 gallons per minute.

In another embodiment, a first heat exchanger, a second heat exchanger, and a third heat exchanger may connect to a working fluid manifold and one or more working fluid flow control devices positioned therebetween. The method may include, in response to a determination that an ambient temperature exceeds an engine operating range, increasing, via a corresponding flow control device, an amount of working fluid flowing from the working fluid manifold to one or more of the second heat exchanger and the third heat exchanger, and in response to a determination that electrical power utilization of a drilling fluid chiller exceeds an operating range, increasing, via a corresponding flow control device, an amount of working fluid flowing from the working fluid manifold to the heat exchanger.

Another embodiment of the disclosure is directed to a method for generating power based on heat generated in the vicinity of a drilling rig. The drilling rig may be one of an on-shore drilling rig or off-shore drilling rig. Such a method may be executed, performed, or operate during a drilling operation. The method may include receiving, via a return pipe positioned above a subsurface, a heated drilling fluid from a fluid channel defined by a space between an outer surface of a drilling pipe and an inner surface of a borehole, and directing the heated drilling fluid from the drilling fluid return pipe to a heat exchanger. The heat exchanger may be positioned to transfer heat from the heated drilling fluid to a flow of a working fluid to generate a cooled drilling fluid, thereby to cause an ORC unit to generate electrical power. The electrical power generated may be one of direct current

(DC) or alternating current (AC) power. On-site equipment at the drilling rig may utilize the electrical power. Such utilization of the electrical power by the on-site equipment may reduce total fuel usage of the drilling rig during the drilling operation. Electrical power may be supplied to one or more of on-site drilling rig equipment (including, but not limited to, a fluid or mud chiller), to the grid, or an energy storage device. The electrical power may be supplied to on-site drilling rig equipment during peak drilling operation hours. In other embodiments, electrical power may be supplied to one or more of the grid, an energy storage device, cryptocurrency miners, or drilling fluid chillers during off-peak drilling operation hours. Finally, the method may include returning the cooled drilling fluid to a drilling fluid container.

Another embodiment of the disclosure is directed to a method for generating power in an organic Rankine cycle (ORC) operation in the vicinity of a drilling rig. Such a method may be executed, performed, or operate during a drilling operation. The method may include pumping, via a pump, drilling fluid from a drilling fluid container to a proximal end of a drill pipe. The drilling fluid may flow through an interior of the drill pipe to the distal end. The distal end of the drill pipe may be connected to a drill bit. The flow of drilling fluid may cause the drill bit to rotate. The rotation of the drill bit may form a borehole in a subsurface and thereby generate a heated drilling fluid. The heated drilling fluid may flow up the borehole to a drilling fluid return pipe above the subsurface via an annulus defined by a space between an outer surface of the drill pipe and an inner surface of the borehole. The method may include receiving, via a return pipe positioned above the subsurface, the heated drilling fluid, and sensing, via a return pipe temperature sensor, a temperature of the heated drilling fluid in the return pipe. The method also may include sensing, via a working fluid temperature sensor, a temperature of a flow of working fluid from a heat exchanger. The flow of working fluid may flow through the heat exchanger to facilitate transfer of heat from heated drilling fluid to the flow of working fluid thereby causing an ORC unit to generate electrical power and generate cooled drilling fluid. The heat exchanger may be connected to the return pipe via a heat exchanger valve and the heated drilling fluid may flow therethrough. The method further may include, in response to one or more of a (1) determination that the temperature of heated drilling fluid in the return pipe is greater than or equal to a threshold or (2) a determination that the temperature of the flow of working fluid from the heat exchanger is within an operating range, adjusting an opened/closed position of a heat exchanger valve to allow continuous diversion of the heated drilling fluid to a heat exchanger to facilitate transfer of heat from heated drilling fluid to a flow of working fluid and generate cooled drilling fluid. Such determinations may occur at pre-determined or pre-selected intervals. The method may include returning the cooled drilling fluid to the drilling fluid container.

Another embodiment of the disclosure is directed to a system for generating power in an organic Rankine cycle (ORC) operation in the vicinity of a drilling rig during drilling operations. The system may include a drilling fluid container to store an amount of drilling fluid. The system may include a container pipe including a first end and a second end. The first end of the container pipe may be in fluid communication with the drilling fluid container. The system may include a drilling fluid pump in fluid communication with the second end of the container pipe. The system may include a drilling fluid pipe including a first end

and a second end. the first end of the drilling fluid pipe may be connected to the drilling fluid pump. The drilling fluid pump may pump drilling fluid therethrough. The system may include a drill string including a proximal end, a distal end, an outer surface, and an inner surface. The proximal end of the drill string may be connected to the second end of the drilling fluid pipe. The drill string inner surface may define a cavity, the drilling fluid to flow therethrough. The system may include a drill bit connected to the distal end of the drill string. The drill bit may rotate based on rotation of the drill string and/or the flow of the drilling fluid. The drill bit may form a borehole in a subsurface geological formation. The system may include a drilling fluid return pipe positioned above the subsurface geological formation and connected to an annulus defined by an inner surface of the borehole and the outer surface of the drill string. The drilling fluid may include aggregate from the drill bit. The system may include a heat exchanger connected to drilling fluid return pipe. The heat exchanger may facilitate heat transfer from the drilling fluid to the to transfer heat to a working fluid flow. The system may include an ORC unit to generate electrical power using heat from the working fluid flow. The ORC unit may include a generator, a gas expander, a condenser, an internal heat exchanger, and a loop for the flow of organic working fluid, the loop defined by a fluid path through the condenser, generator, and a first fluid path of the internal heat exchanger, the internal heat exchanger including a second fluidic path to connect to the heat exchanger and the working fluid flowing therethrough, the internal heat exchanger to indirectly transfer heat from the working fluid to the organic working fluid thereby causing the organic working fluid to change phases from a liquid to a vapor, the flow of the vapor to cause the generator to generate electrical power via rotation of a gas expander as defined by an ORC operation, the condenser to cool the flow of the organic working fluid, and the cooling to cause the organic working fluid to change phases from the vapor to the liquid.

In other embodiments, a system may include a pump engine to drive the drilling pump, one or more generation sets to generate electrical power for use at the drilling rig, and one or more engines connected to and to drive the one or more generation sets. The pump engine and one or more engines may produce exhaust. Each of the pump engine and one or more engines may include exhaust outlets. In such embodiments, the system also may include one or more exhaust conduits including a first end and a second end. Each of the one or more exhaust conduit's first end may be in fluid communication with each of the exhaust outlets of the pump engine and one or more engines. The system may include an exhaust manifold to connect to each of the one or more exhaust conduit's second end, the exhaust from each of the pump engine and one or more engines may aggregate therein one or more exhaust heat exchangers to connect to the exhaust manifold, to receive the aggregated exhaust from each of the pump engine and one or more engines, and configured to facilitate heat transfer from exhaust to a second working fluid.

In other embodiments, a system may include one or more water or other fluid (e.g., coolant) jackets as will be understood by those skilled in the art. Each of the one or more water jackets may corresponding to one of the pump engine and one or more engines and to cool the one of the pump engine and one or more engines during drilling operation. The system may include one or more water jacket heat exchangers each in fluid communication with one of the one

or more water jackets and configured to facilitate heat transfer from fluid within the water jacket to a second working fluid.

Another embodiment of the disclosure is directed to a system for generating power in an organic Rankine cycle (ORC) operation in the vicinity of a drilling rig during drilling operations. The system may include a drilling fluid container to store an amount of drilling fluid. The system may include a container pipe including a first end and a second end. The first end of the container pipe may be in fluid communication with the drilling fluid container. The system also may include a drilling fluid pump in fluid communication with the second end of the container pipe. The system further may include a drilling fluid pipe including a first end and a second end. The first end of the drilling fluid pipe may be connected to the drilling fluid pump, the drilling fluid pump to pump drilling fluid therethrough, and a drill string including a proximal end, a distal end, an outer surface, and an inner surface. The proximal end of the drill string may be connected to the second end of the drilling fluid pipe. The drill string inner surface may define a cavity, the drilling fluid to flow therethrough. The system still further may include a drill bit connected to the distal end of the drill string. The drill bit may rotate based on rotation of the drill string and flow of the drilling fluid. The drill bit may form a borehole in a subsurface geological formation. The system also may include drilling fluid return pipe positioned above the subsurface geological formation and connected to an annulus defined by an inner surface of the borehole and the outer surface of the drill string, the drilling fluid, including aggregate from the drill bit, to flow therethrough. The system still further may include a heat exchanger connected to drilling fluid return pipe. The heat exchanger may facilitate heat transfer from the drilling fluid to the to transfer heat to a working fluid flow. The system also may include an ORC unit to generate electrical power using the heat transferred to the working fluid flow.

Another embodiment of the disclosure is directed to a controller to control electrical power generated in an organic Rankine cycle (ORC) operation in the vicinity of a drilling rig during drilling operations. The controller may include an input in signal communication with a drilling fluid return pipe sensor to provide a temperature of a drilling fluid entering a drilling fluid return pipe. The controller may further include a set of inputs/outputs in signal communication with a heat exchanger valve and a working fluid flow control device. The controller may be configured to, in response to the drilling fluid being within an operating range, transmit one or more signals to (1) to adjust a heat exchanger valve's position to thereby divert drilling fluid to a heat exchanger or (2) to adjust the working fluid flow control device to thereby control an amount of heat transferred to the working fluid flow. The heat exchanger may facilitate transfer of heat from the drilling fluid to a working fluid flow and the heat transferred to the working fluid may cause an ORC unit to generate electricity. The controller may further include a second input in signal communication with a heat exchanger working fluid outlet temperature sensor. The heat exchanger working fluid outlet temperature sensor may provide a working fluid outlet temperature of a working fluid flow from the heat exchanger. Adjustment of the one or more of (1) heat exchanger valve's position or (2) working fluid flow control device may further be based on the working fluid outlet temperature.

Another embodiment of the disclosure is directed to a method to increase, for one or more of an engine, a generator set, or a bottom-hole assembly, performance and lifespan.

Such a method may be executed, performed, or operate during a drilling operation. The method may include sensing, via a drilling fluid return pipe sensor, a temperature of a flow of drilling fluid from a borehole, and sensing, via an ambient temperature sensor, an ambient temperature of a drilling rig. The method also may include determining electrical power utilized by drilling rig equipment and generated by a generator set driven by an engine, and in response to one or more of (a) the temperature of the flow of drilling fluid from the borehole exceeding an operating range, (b) the ambient temperature exceeding an ambient temperature threshold, or (c) the electrical power utilized by the drilling rig equipment exceeding a power requirement threshold: adjusting one or more of (1) a first working fluid flow control device; (2) a second working fluid flow control device; or (3) a third working flow control device. The first working fluid flow control device may control a flow of working fluid to a drilling fluid heat exchanger.

An embodiment of a drilling fluid heat exchanger, for example, may be configured to transfer heat from the drilling fluid to the flow of the working fluid, the transferred heat to cause an ORC unit to generate electrical power. Adjustment of the first working fluid flow control device may cause an increase in working fluid flow to the drilling fluid heat exchanger thereby causing a decrease in the temperature in drilling fluid to thereby decrease cooling via a mud chiller and to further thereby decrease overall electrical power utilized at the drilling rig. The second working fluid flow control device may control a flow of working fluid to an exhaust heat exchanger. The exhaust fluid heat exchanger may be configured to transfer heat from exhaust generated by the engine to the flow of the working fluid, the transferred heat to cause an ORC unit to generate electrical power. Adjustment of the second working fluid flow control device may cause an increase in working fluid flow to the exhaust heat exchanger thereby causing an increase in overall electrical power generated by the ORC unit due to the high heat of the exhaust and to thereby optimize engine and generator set performance. The third working fluid flow control device may control a flow of working fluid to a water jacket heat exchanger. The water jacket fluid heat exchanger may be configured to transfer heat from water jacket fluid of a water jacket, the water jacket configured to cool the engine, to the flow of the working fluid, the transferred heat to cause an ORC unit to generate electrical power. Adjustment of the third working fluid flow control device may cause an increase in working fluid flow to the water jacket heat exchanger thereby causing an increase in engine performance due to increased heat transfer from the engine to the working fluid.

Another embodiment of the disclosure is directed to a method for generating power in an organic Rankine cycle (ORC) operation in the vicinity of a drilling rig. The method may include operating a drilling rig to form a borehole in a subsurface formation. The method may also include, during operation of the drilling rig, selecting one or more fluids from one or more corresponding heat sources. The one or more fluids selected may flow to one or more corresponding heat exchangers. Each of the one or more corresponding heat exchangers may be positioned to transfer heat from the heated drilling fluid to a flow of a working fluid to generate a heated working fluid. The heated working fluid may cause an ORC unit to generate electrical power. The one or more heat sources may include exhaust produced by one of one or more engines positioned in the vicinity of the drilling rig or fluid from a fluid jacket corresponding to one of the one or more engines. Additionally, the one or more heat sources

11

may include drilling fluid utilized during operation of the drilling rig. One or more of the one or more heat sources may be selected based on temperature of fluid from each of the one or more heat sources, the ambient temperature at the drilling rig, engine optimization, electrical power output maximization, or electrical power utilization at the drilling rig.

Another embodiment of the disclosure is directed to a method for generating power in an organic Rankine cycle (ORC) operation in the vicinity of a drilling rig. The method may include, during a drilling operation, selecting, based on one or more of (a) engine optimization, (b) electrical power output maximization, or (c) electrical power utilization at the drilling rig, diversion of an amount of one or more of (1) engine exhaust, via a first heat exchanger supply valve, from an engine exhaust conduit to a first heat exchanger and (2) fluid, via a second heat exchanger supply valve, from an engine fluid jacket to a second heat exchanger. Each of the first heat exchanger and the second heat the heat exchanger may be positioned to transfer heat from the engine exhaust and fluid to a flow of a working fluid to generate a heated working fluid. The heated working fluid may cause an ORC unit to generate electrical power. Selection of diversion of the amount of one or more of engine exhaust and fluid may be further based on ambient temperature at the drilling rig, temperature of the engine exhaust, temperature of the fluid, temperature of working fluid corresponding to the engine exhaust, and temperature of working fluid corresponding to the fluid.

Another embodiment of the disclosure is directed to a method for increasing one or more of engine, generator set, or bottom-hole assembly performance and lifespan. The method may be executed during a drilling operation. The method may include sensing, via an ambient temperature sensor, an ambient temperature of a drilling rig. The method may include determining electrical power utilized by drilling rig equipment and generated by a generator set driven by an engine. The method may include, in response to one or more of (a) the ambient temperature exceeding an ambient temperature threshold or (b) the electrical power utilized by the drilling rig equipment exceeding a power requirement threshold: adjusting one or more of (1) a first working fluid flow control device, or (2) a second working fluid flow control device. The first working fluid flow control device may control a flow of working fluid to an exhaust heat exchanger. The exhaust fluid heat exchanger may be configured to transfer heat from exhaust generated by the engine to the flow of the working fluid. The transferred heat may cause a power generation unit to generate electrical power. the second working fluid flow control device may control a flow of working fluid to a fluid jacket heat exchanger. The fluid jacket fluid heat exchanger may be configured to transfer heat from the fluid of the fluid jacket to the flow of the working fluid. The fluid jacket may be configured to cool the engine. The transferred heat may cause a power generation unit to generate electrical power.

Still other aspects and advantages of these embodiments and other embodiments, are discussed in detail herein. Moreover, it is to be understood that both the foregoing information and the following detailed description provide merely illustrative examples of various aspects and embodiments, and are intended to provide an overview or framework for understanding the nature and character of the claimed aspects and embodiments. Accordingly, these and other objects, along with advantages and features of the present invention herein disclosed, will become apparent through reference to the following description and the

12

accompanying drawings. Furthermore, it is to be understood that the features of the various embodiments described herein are not mutually exclusive and may exist in various combinations and permutations.

BRIEF DESCRIPTION OF DRAWINGS

These and other features, aspects, and advantages of the disclosure will become better understood with regard to the following descriptions, claims, and accompanying drawings. It is to be noted, however, that the drawings illustrate only several embodiments of the disclosure and, therefore, are not to be considered limiting of the scope of the disclosure.

FIG. 1A, FIG. 1B, and FIG. 1C are side-view perspectives of implementations of systems to generate electrical power at a drilling rig, according to one or more embodiments of the disclosure.

FIG. 2A, FIG. 2B, FIG. 2C, FIG. 2D, FIG. 2E, FIG. 2F, FIG. 2G, and FIG. 2H are block diagrams illustrating implementations of systems of an electrical power generation enabled drilling rig to provide electrical power to one or more of in-field equipment, equipment at other sites, energy storage devices, and the grid power structure, according to one or more embodiment of the disclosure.

FIG. 3 is a simplified diagram illustrating a control system for managing electrical power production at a drilling rig, according to one or more embodiments of the disclosure.

FIG. 4A, FIG. 4B, and FIG. 4C are flow diagrams of methods of electrical power generation in which, during a drilling operation, working fluid is heated via one or more of drilling fluid or drilling mud, engine exhaust, and/or water (or other fluid) jacket fluid flow, according to one or more embodiments of the disclosure.

FIG. 5 is a flow diagram of a method of electrical power generation in which, during a drilling operation, working fluid is heated via one or more heat sources, according to one or more embodiments of the disclosure.

FIG. 6 is a flow diagram of a method of electrical power generation in which, during a drilling operation, working fluid is heated via one or more of drilling fluid or drilling mud, engine exhaust, and/or water (or other fluid) jacket fluid flow, according to one or more embodiments of the disclosure.

DETAILED DESCRIPTION

So that the manner in which the features and advantages of the embodiments of the systems and methods disclosed herein, as well as others that will become apparent, may be understood in more detail, a more particular description of embodiments of systems and methods briefly summarized above may be had by reference to the following detailed description of embodiments thereof, in which one or more are further illustrated in the appended drawings, which form a part of this specification. It is to be noted, however, that the drawings illustrate only various embodiments of the systems and methods disclosed herein and are therefore not to be considered limiting of the scope of the systems and methods disclosed herein as it may include other effective embodiments as well.

The present disclosure is directed to embodiments of systems and methods for generating electrical power (e.g., via a power generation unit such as an organic Rankine cycle (ORC) operation or other operations utilizing heat to generate electrical power as will be understood by those skilled in the art) based on heat from a flow of drilling fluid or mud

13

and other sources (e.g., engine exhaust, coolant from an engine's water jacket, other heat generating equipment or devices, etc.) to thereby supply electrical power to one or more of equipment or operational equipment, a grid power structure, an energy storage device, and/or other devices. Drilling rig operations typically include pumping of drilling fluid or drilling mud through a drill string or drill pipe to a drill bit connected to the drill string or drill pipe at the drill string or drill pipe's proximal end. The drilling fluid may cool the drill bit and, in some embodiments, other bottom-hole assembly components or devices. During the drilling operation, the drill bit's temperature may increase due to the friction between the drill bit and the rock and/or other substrate of the subsurface formation. After the drilling fluid cools the drill bit, the drilling fluid may flow or may be pumped or transmitted to the surface (e.g., to a drilling fluid return pipeline) via an annulus defined by a space between the outer surface of the drill string or drill pipe and the surface or inner surface of the borehole. The drilling fluid may flow, via the drilling fluid return pipeline, to a drilling fluid tank, container, or pit. Other equipment or devices may be positioned therebetween. For example, a fluid or mud chiller and/or shale shaker may be positioned prior to the drilling fluid tank, container, or pit. The heat generated or carried by the drilling fluid or drilling mud, as well as the heat produced by the equipment on-site (e.g., engine exhaust and/or cooling fluid in a water jacket of an engine, computing devices or systems, and/or any other equipment which generates heat during drilling operations), may be utilized via either external and/or internal heat exchangers to produce electrical power (e.g., via one or more ORC units or other equipment configured to convert heat to electrical power).

In such examples, ORC generators or units, for example, may use a pipeline in communication with heat sources to allow a working fluid to change phase from liquid to vapor. As the working fluid changes phase from a liquid to a vaporous state, the vaporous state working fluid may flow up the pipe or pipeline to a gas expander. The vaporous state working fluid may flow through and cause the gas expander to rotate. The rotation of the gas expander may cause a generator to generate electrical power, as will be described below. The vaporous state working fluid may flow through the gas expander to a heat sink, condenser, or other cooling apparatus. The heat sink, condenser, or other cooling apparatus may cool the working fluid thereby causing the working fluid to change phases from a vapor to a liquid.

In the present disclosure, a drilling fluid return pipeline may connect directly to an inlet of a drilling fluid heat exchanger or may connect to a secondary supply pipeline via a drilling fluid control valve, the secondary supply pipeline connecting to the inlet of the drilling fluid heat exchanger. In such embodiments, the drilling fluid may flow directly to and through the drilling fluid heat exchanger or the drilling fluid control valve may divert a portion or all of the drilling fluid to the drilling fluid heat exchanger. The drilling fluid may flow through the drilling fluid heat exchanger thereby facilitating transfer of heat from the flow of drilling fluid to a working fluid.

Sensors to sense or determine various characteristics of the drilling fluid and/or other heated fluid from other equipment may be positioned throughout the drilling rig. In such an embodiment, the drilling fluid control valve's position may be adjusted to increase or decrease the amount of drilling fluid flowing to the drilling fluid heat exchanger. Similar valves may be included for each heat source. Further, each heat exchanger may connect to a return manifold

14

and a supply manifold, each manifold positioned between the heat exchangers and the ORC unit. The supply manifold and/or the return manifold may include flow control devices to adjust the amount of working fluid flowing to any particular heat exchanger, thus enabling control of electrical power output and/or other factors.

For example, adjustment of a first working fluid flow control device may cause an increase or decrease in a working fluid flow to the drilling fluid heat exchanger thereby causing a decrease or increase, respectively, in the temperature in drilling fluid. Based on the increase or decrease of working fluid to the drilling fluid heat exchanger and a preselected or predetermined temperature of the drilling fluid, a mud chiller may or may not be utilized to a degree to cool the drilling fluid further. The mud chiller may utilize electrical power. As the temperature of the drilling fluid increases, the electrical power utilized by the mud chiller may increase. In an embodiment, to offset such an increase in utilized electrical power, the ORC unit may supply electrical power to the mud chiller.

As noted, other heat sources may be utilized, for example engine exhaust and/or fluid from an engine's water (or other coolant) jacket. In such embodiments, a second working fluid flow control device may control a flow of working fluid to an exhaust heat exchanger. The exhaust fluid heat exchanger may be configured to transfer heat from exhaust generated by the engine to the flow of the working fluid, the transferred heat to cause an ORC unit to generate electrical power. Adjustment of the second working fluid flow control device may cause an increase or decrease in working fluid flow to the exhaust heat exchanger. An increase in working fluid may cause an increase in overall electrical power generated by the ORC unit due to the high heat of the exhaust. Such an action may be performed to optimize engine and generator set performance (e.g., the engine may be utilized to generate a lesser amount of electrical power). A third working fluid flow control device may control a flow of working fluid to a water jacket heat exchanger (or a heater exchanger that uses another type of coolant, for example). The water jacket fluid heat exchanger may be configured to transfer heat from water jacket fluid of a water jacket, the water jacket configured to cool the engine, to the flow of the working fluid, the transferred heat to cause an ORC unit to generate electrical power. Adjustment of the third working fluid flow control device may cause an increase or decrease in working fluid flow to the water jacket heat exchanger. Increasing flow of working fluid to the water jacket heat exchanger may cause an increase in engine performance due to increased heat transfer from the engine to the working fluid (e.g., extending life of consumables and parts of the engine, as well as increasing engine efficiency and/or output).

After passing through the heat exchanger, the drilling fluid may be cooled for a period of time in the drilling fluid tank or container. After a period of time or preselected or predetermine time interval in the drilling fluid tank the drilling fluid may be cooled radiantly. In other words, as the drilling fluid resides in the tank, over time, the drilling fluid may cool or the drilling fluid temperature may decrease. In such embodiments, as the drilling fluid is pumped from the drilling fluid tank, the drilling fluid may be pumped through a drilling fluid chiller, also known as a mud chiller. The mud chiller, utilizing electrical power, may further cool the drilling fluid. The drilling fluid pumped from the drilling fluid tank may be pumped back through the same fluidic path again (e.g., back to the drill string or drill pipe) and the operation repeated for the duration of the drilling operation.

15

Thus, heat from the flow of drilling fluid, exhaust, fluid from a water jacket (or other coolant jacket), and/or other fluid may be utilized to generate electrical power in a power generation unit such as an ORC unit as will be understood by those skilled in the art, while increasing efficiency of and/or optimizing drilling rig operations.

Such embodiments of systems, for example, may include various components, devices, or apparatuses, such as temperature sensors, pressure sensors or transducers, flow meters, control valves, smart valves, valves actuated via control signal, controllers, a master or supervisory controller, other computing devices, computing systems, user interfaces, in-field equipment, and/or other equipment as will be understood by those skilled in the art. The controller, for example, may monitor and adjust various aspects of the system to ensure that a flow of gas does not drop below the threshold where volatiles may condense in the flow of gas, that the temperature of the flow of gas stays below the threshold where a compressor or pump provides a higher output, that the flow of gas remains within a selected operating range, that the working fluid remains within a selected operating range, and/or that electrical power is generated efficiently and economically.

FIG. 1A, FIG. 1B, and FIG. 1C are side-view perspectives of example implementations of systems to generate electrical power at a drilling rig, according to one or more embodiments of the disclosure. A drilling rig 100, as illustrated in FIG. 1A, may include various equipment and/or devices. The equipment and/or devices may include a drilling fluid tank, also referred to as a drilling fluid pit or drilling fluid container. The drilling fluid tank (e.g., a mud tank 130) may store drilling fluid (e.g., drilling mud). The drilling fluid tank may be comprised of steel or other metal configured to withstand corrosion. The drilling fluid tank may store varying amounts of drilling fluid. The amount of drilling fluid may vary at different time intervals as the length of the borehole increases and/or as additional drilling fluid is added to the drilling fluid tank. The drilling fluid, also referred to as drilling mud, may include a water-based mud (e.g., dispersed or non-dispersed), non-aqueous mud (e.g., oil based mud), and/or a gaseous drilling fluid. During drilling operations, the drilling fluid may be pumped (e.g., via a pump 134 driven by an engine 136) to a drill bit 118 to cool the drill bit 118, carry cuttings, and/or to provide hydrostatic pressure (e.g., preventing formation fluids from entering the borehole 120).

The drilling rig 100, as noted, may include a pump 134 to pump the drilling fluid to a borehole 120. The pump 134 may first pump the drilling fluid from the drilling fluid tank via drilling fluid input pipe 132. The pump 134 may pump such fluid through a stand pipe 104. In other embodiments, the stand pipe 104 may be a goose neck pipe, a kelly hose, another pipeline or hose configured to withstand high pressure, or some combination thereof. The stand pipe 104 may pass through and/or be supported by a swivel 110. The swivel 110 may connect to a travel block 108 and the travel block 108 may connect to a crown block 106. The crown block 106 may be stationary and may be configured to raise and lower the travel block 108 thereby allowing the stand pipe 104 or other pipeline or hose to move in a vertical direction. The stand pipe 104 may pass through a table 114 at the drill floor 112. The stand pipe 104 may then connect to the drill string 116 or drill pipe thereby allowing drilling fluid to be pumped through the stand pipe 104 to an inner cavity of the drill string 116. The inner cavity of the drill string 116 may be defined by the space substantially within the inner surface of the drill string 116.

16

The drill string 116 may include a proximal end and a distal end. The proximal end may connect to the stand pipe 104. The distal end may include or may be connected to a drill bit 118. The drill string 116 may rotate, via the rotary table 114 and/or other equipment or devices, as will be understood by a person skilled in the art. As the drill string rotates 116, the drill bit 118 may rotate. In another embodiment, in addition to or rather than the rotation of the drill string 116 causing rotation of the drill bit 118, the drilling fluid pumped through the drill string 116 may cause the drill bit 118 to rotate. As the drill bit 118 rotates, the drill bit 118 may cut or break apart rock and/or other materials in the subsurface formation. Such an action may create a borehole 120 in the subsurface formation, which may be utilized for various purposes, including, but not limited to, for oil and gas extraction (e.g., via fracturing or a well), water well formation, carbon dioxide sequestration, and/or geothermal well generation.

The pump 134 may be driven by an engine 136. In an embodiment, the rotary table 114 or the rotation of the drill string 116 may be driven by the engine 136 and/or another engine. Further, additional engines and/or generators or generator sets (e.g., to provide electrical power to equipment and/or devices at the drilling rig 100) may be included or positioned at the drilling rig 100. Such additional engines may be utilized to generate electrical power and/or drive other equipment and/or devices. The engine 136 and/or other additional engines at the drilling rig 100 may include a water (or other fluid) jacket as will be understood by those skilled in the art. Further, the engine, during operation, may produce exhaust. In other embodiments, the engine 136 may be an electric engine and, thus, no exhaust may be produced. The pump 134 may be in fluid communication with the mud tank 130, for example, via pipeline 132 (e.g., a tank or container pipe or pipeline). As the pump 134 is driven by the engine 136, the drilling fluid may flow through the pump 134 to the stand pipe 104 and from the stand pipe 104 to the drill string 116. The drilling fluid may flow through and/or around the drill bit 118, thus cooling the drill bit 118 and carrying cuttings up the borehole 120 (e.g., via an annulus defined by a space between an outer surface of the drill string 116 and an inner surface of the borehole 120).

As the drilling fluid flows up the borehole 120, the drilling fluid may reach a drilling fluid return pipeline 122. The drilling fluid return pipeline 122 may, in an embodiment, connect directly to a heat exchanger 124 (e.g., a drilling fluid heat exchanger). In another embodiment, the drilling fluid return pipeline 122 may connect to the mud tank 130 or other equipment (e.g., a shale shaker 128 or filter, a degasser, and/or a mud chiller) positioned therebetween. For example, the drilling fluid return pipeline 122 may connect to a shale shaker 128. The shale shaker 128 may remove any solids from the drilling fluid flowing therethrough. The shale shaker 128 may connect to the heat exchanger 124 and the heat exchanger may connect to the mud tank 130. In another embodiment, a second pipeline may be connected to the drilling fluid return pipeline 122. The second pipeline may include a control valve and the drilling fluid return pipeline 12 may include a control valve. Thus, based on various factors, the amount of drilling fluid flowing to the heat exchanger 124 may be controlled. In the embodiments, the heat exchanger 124 may connect to the mud tank 130 via a third pipeline 126.

In an embodiment, different types of heat exchangers may be utilized at the drilling rig 100. The heat exchanger 124 may be internal to the ORC unit 142 and/or external to the ORC unit 142. In an embodiment, the heat exchanger 124

17

may be a shell and tube heat exchanger, a spiral plate or coil heat exchanger, a heliflow heat exchanger, or another heat exchanger configured to withstand high temperatures, high pressure, and/or corrosive fluids. To prevent damage or corrosion to the heat exchanger **124** over a period of time, the fluid path inside the heat exchanger **124** for the flow of drilling fluid may be configured to withstand damage or corrosion by including a permanent coating, a semi-permanent coating, a temporary anti-corrosive coating, an injection point for anti-corrosive chemical additive injections, and/or some combination thereof. Further, at least one fluid path of the heat exchanger **124** may be comprised of an anti-corrosive material, e.g., anti-corrosive metals or polymers.

The direction of drilling fluid flowing through the heat exchanger **124** may be opposite of the flow of working fluid flowing through the heat exchanger **124**, thereby the heat exchanger **124** facilitates transfer of heat from the drilling fluid to the working fluid. The working fluid may flow from the ORC unit **142** to the heat exchanger via pipeline **140**. After heat transfer within the heat exchanger **124**, the working fluid may flow through pipeline **138** to the ORC unit **142**, thereby causing an ORC operation to occur and electrical power **144** to be generate. In another embodiment, the heat exchanger **124** may be internal to the ORC unit **142** and, in such embodiments, pipeline **140** and pipeline **138** may be internal to the ORC unit **142**.

In an example, the working fluid may be a fluid with a low boiling point and/or high condensation point. In other words, a working fluid may boil at lower temperatures (for example, in relation to water), while condensing at higher temperatures (e.g., in relation to water) as will be understood by a person skilled in the art. The working fluid may be an organic working fluid. The working fluid may be one or more of pentafluoropropane, carbon dioxide, ammonia and water mixtures, tetrafluoroethane, isobutene, propane, pentane, perfluorocarbons, other hydrocarbons, a zeotropic mixture of pentafluoropentane and cyclopentane, other zeotropic mixtures, and/or other fluids or fluid mixtures. The working fluid's boiling point and condensation point may be different depending on the pressure within the working fluid pipelines e.g., the higher the pressure, the higher the boiling point. In another example, the working fluid may be an intermediate working fluid. The intermediate working fluid may be a fluid with a higher boiling point. For example, the intermediate working fluid may be water or a water glycol mixture. In such examples, as heat is transferred from the flow of drilling fluid, the exhaust, the fluid from the water (or other fluid) jacket, and/or from another source, the intermediate working fluid may, rather than exhibiting a vaporous phase change, remain in a liquid phase, while retaining the transferred heat. As a liquid, the higher boiling point intermediate working fluid may be more manageable and/or easier to transport through the pipelines. In such examples, the ORC unit **142** may include an internal heat exchanger.

In an embodiment, the ORC unit **142** may include a generator, a gas expander, a condenser, an internal heat exchanger, a loop for the flow of working fluid, or some combination thereof. As an intermediate working fluid or other fluid flows into the ORC unit **142**, the internal heat exchanger may facilitate transfer of heat in the intermediate working fluid or other fluid to a working fluid of the ORC unit **142**. The heat may cause the working fluid of the ORC unit **142** to exhibit a phase change from a liquid to a vapor. In another embodiment, the working fluid may enter the ORC unit **142** as a vapor or vaporous working fluid (e.g., such an ORC unit **142** may not include an internal heat

18

exchanger). The vaporous working fluid may flow into the gas expander. In an example, the gas expander may be a turbine expander, positive displacement expander, scroll expander, screw expander, twin-screw expander, vane expander, piston expander, other volumetric expander, and/or any other expander suitable for an ORC operation or cycle. As gas flows through the gas expander, a rotor or other component connected to the gas expander may begin to turn, spin, or rotate. The rotor may include an end with windings. The end with windings may correspond to a stator including windings and a magnetic field (e.g., the end with windings and stator with windings being a generator). As the rotor spins within the stator, electricity may be generated. Other generators may be utilized, as will be understood by those skilled in the art. The generator may produce DC power, AC power, single phase power, or three phase power. The vaporous working fluid may then flow from the gas expander to a condenser, where the vaporous working fluid may exhibit a phase change back to the liquid working fluid. The liquid working fluid may then flow back to the internal heat exchanger, the process repeating.

The electrical power **144** may be transferred to or utilized by the equipment at the site **100** (e.g., a mud chiller **176** and/or other equipment), to an energy storage device (e.g., if excess power is available), to equipment at other nearby sites, to the grid or grid power structure (e.g., via a transformer through power lines), to other types of equipment (e.g., cryptographic currency and/or block chain miners, hydrolyzers, carbon capture machines, nearby structures such as residential or business structures or buildings, and/or other power destinations), or some combination thereof. Such electrical power **100** may be utilized at the drilling rig **100** in lieu or in addition too electrical power generate by a generator or generator set driven by additional engines.

Turning to FIG. **1B** and as noted, the engine **136** or one or more engines may produce exhaust exhibiting high heat or temperature. The exhaust may be transported via an exhaust duct **146** or pipeline to a heat exchanger **148** or ORC unit **142** (e.g., via pipeline **152**). After the exhaust flows through the heat exchanger **148** or the ORC unit **140**, the exhaust may be output to the atmosphere, via an exhaust outlet duct **150**. In another embodiment, prior to output of the exhaust to the atmosphere, the exhaust may pass through a filter **156** or catalyst. The filter **156** may remove specific chemicals deemed harmful to the environment. In another embodiment, prior to input into the heat exchanger **148**, the exhaust may be filtered or pass through a catalyst to prevent buildup within the heat exchanger **148**. If additional engines are positioned at the drilling rig **100**, then, in an embodiment, the exhaust from such additional engines may be transported to the heat exchanger **148** or ORC unit **142** or may be transported to one or more additional heat exchangers.

In an embodiment, sensors and/or meters may be disposed throughout the drilling rig **100**. The sensors and/or meters may be temperature sensors, densitometers, density measuring sensors, pressure transducers, pressure sensors, flow meters, turbine flow meters, mass flow meters, Coriolis meters, spectrometers, other measurement sensors to determine a temperature, pressure, flow, composition, density, or other variables as will be understood by those skilled in the art, or some combination thereof. Further, the sensors and/or meters may be in fluid communication with a fluid to measure the temperature, pressure, or flow or may indirectly measure flow (e.g., an ultrasonic sensor). In other words, the

sensors or meters may be a clamp-on device to measure flow indirectly (such as via ultrasound passed through the pipeline to the fluid).

In an embodiment, the exhaust duct **146** or pipeline may include an exhaust valve. In an embodiment, the exhaust from the engine **136** may be at a high temperature or have a high thermal mass (e.g., temperature of the exhaust multiplied by the flow rate of the exhaust). If the temperature or thermal mass of the exhaust (e.g., as measured by a temperature sensor) is outside of a range (e.g., defined by the operating temperature range of the heat exchanger **148**, ORC unit **142**, or other equipment or devices interacting with the exhaust and/or based on thermal mass) or above or below a threshold, the exhaust control valve may close, thereby partially or fully preventing the exhaust from flowing to the heat exchanger **148**. If the exhaust control valve is fully closed, the exhaust may be fully diverted to a typical exhaust output. If the exhaust control valve is partially closed, the exhaust may be partially diverted to a typical exhaust output, while the remaining portion may flow to the heat exchanger **148**. The partial or full prevention of the flow of exhaust to the heat exchanger **148** may prevent interruption of catalyst performance of the engine **136** and/or deposition of particulates in equipment.

In another embodiment, the flow of exhaust, prior to flowing through the heat exchanger **148**, may pass through a filter, converter, or some other device to reduce particulates within the exhaust. As noted, the exhaust may cause scaling and/or deposition of such particulates. The filter or other device may ensure that the heat exchanger **148** may not exhibit such scaling and/or deposition of particulates or may not exhibit the scaling and/or deposition at rates higher than if there were no filter or other device.

The engine **136** or one or more engines may include a water (or other fluid) jacket. As an engine **136** operates, the water or other coolant (i.e., fluid) inside the water jacket may indirectly remove heat from the engine **136**. Heat from the engine **136** may be transferred to the water or other coolant, thereby producing heated water or other coolant. The heated water or other coolant may pass through a radiator, heat sink, or other type of heat exchanger to reduce the temperature of heated water or coolant, the cooled water or coolant then flowing back to the water jacket to cool the engine **136**. In an embodiment, the output of the water jacket may connect to a pipeline **158** to divert the flow of water to the heat exchanger **160**.

In an embodiment, a water jacket control valve may be positioned on the pipeline to control the flow water or coolant from the water jacket. A pipeline **162** may be connected to the input of the water jacket to return the water or other coolant to the water jacket. In such embodiments, rather than or in addition to the water or other coolant passing through the typical radiator or heat exchanger, the heated water or other coolant may pass through heat exchanger **160** thereby transferring heat to a working fluid. The working fluid may flow, in one embodiment, to the ORC unit **142** via pipeline **164** and the working fluid may return to heat exchanger **160** via pipeline **166**. In another embodiment, the engine's **136** water jacket may be configured to transport the water or other coolant directly to the ORC unit **142**. In another embodiment, the water jacket control valve may close if the water or other coolant is outside a selected operating range (e.g., if the water or other coolant is too cool, then, if utilized, water or other coolant may not be sufficient for the ORC unit **142** to generate electrical power, and/or if the water or coolant is too hot, then, if utilized, the heated water or other coolant may damage equipment not

rated for a high temperature) thus preventing fluid from flowing to the heat exchanger **160** and/or the ORC unit **142**. Temperature of the water or coolant may be determined or sensed via one or more temperature sensors. The temperature of the working fluid or intermediate working fluid may be determined or sensed via one or more temperature sensors.

As noted, heat may be transferred from the engine's **136** exhaust, from working fluid, and/or from drilling fluid to an intermediate working fluid or a working fluid. The intermediate working fluid may be stored in another storage tank or expansion tank. The temperature of the intermediate working fluid flowing from the heat exchanger **148** may be determined based on measurements from temperature sensors proximate to the heat exchanger **148**. The temperature of the intermediate working fluid may be measured at various other points, such as after the storage tank or the storage tank control valve or prior to entry into the heat exchanger. Based on these measurements, a storage tank control valve may open or close to prevent or allow the storage tank to fill up and/or to prevent over-filling the storage tank. In an embodiment, the storage tank may be an expansion tank, such as a bladder or diaphragm expansion tank. The expansion tank may accept a varying volume of the intermediate working fluid as the pressure within the working fluid pipeline varies, as will be understood by a person skilled in the art. Thus, the expansion tank may manage any pressure changes exhibited by the intermediate working fluid.

In an embodiment, various temperature sensors and/or other sensors or meters may be disposed and/or positioned throughout the drilling rig **100**. In another embodiment, the heat exchangers and/or ORC unit or units may be added to the site as a kit. In such examples, temperature sensors and/or other sensors or meters, in addition to control valves and/or other devices or equipment, may be included in the added kit (e.g., along added or installed conduits or pipelines) installed at a drilling rig **100**, rather than in existing equipment.

The drilling rig **100**, as shown, utilizes an ORC unit **142** to generate electrical power. In another embodiment, rather than or in addition to the ORC unit **142**, other geothermal-based generators may be utilized to generate electrical power using the heat transferred to the working fluid from the flow of drilling fluid, engine exhaust, and/or fluid from a water jacket. For example, the geothermal-based generator may be another type of binary-cycle generator. In another embodiment, one or more of the one or more heat sources (e.g., the heat from the drilling fluid, engine exhaust, and/or fluid from the water jacket, among other heat sources) may be utilized to generate electrical power in the ORC unit **142** or other geothermal-based generators based on a number of factors, the factors including but not limited to, an amount of electrical power utilized at the drilling rig **100**, engine performance, engine life expectancy, drill bit and/or bottom-hole assembly component life expectancy, ambient temperature, and/or other aspects.

Additionally, as illustrated in FIG. 1B and FIG. 1C, the drilling rig **100** may include additional heat exchangers and a return manifold **174** and supply manifold **172**. In another embodiment, the drilling rig **100** may include additional ORC units. As illustrated in FIG. 1B and FIG. 1C, each heat exchanger may connect to a supply manifold **172** to transport the flow of working fluid to the intake of an ORC unit **142**. Further, each heat exchanger may connect to a return manifold **174** to receive the working fluid from the ORC unit **142**. In another embodiment, the supply manifold **172** and/or

21

return manifold **174** may control, either directly or indirectly (e.g., via another flow control device), the amount or rate of flow of working fluid flowing to the ORC unit **142** and/or to each heat exchanger.

In another embodiment, the drilling rig **100** may include a separate supply manifold and return manifold for hot working fluid supply/return and for cool working fluid supply/return. In such examples, the separate supply manifolds and return manifolds may control the flow of working fluid based on temperature of the working fluid from each source (e.g., each heat exchanger).

In FIG. **1C**, the drilling rig **100** may include a mud chiller **176**. As noted, the drilling fluid may cool the drill bit **118** to extend the life or use of the drill bit **118** and/or other bottom-hole assembly components. As such, the drilling fluid may be cooled further prior to pumping the drilling fluid back to the drill bit **118** (e.g., via the same fluidic path described herein). In some examples, the heat exchanger **124** may sufficiently cool the drilling fluid. In other examples, the drilling fluid may reside in the mud tank **130** for a period of time or a preselected or predetermined time interval sufficient to cause the drilling fluid to radiantly cool to a specified temperature. In other example, a mud chiller **176** may be included to further cool the drilling fluid. The mud chiller **176** may utilize electrical power generated by a generator or generator set. The mud chiller **176** may be positioned prior to (as illustrated in FIG. **1C**) or after the pump **134**. As drilling fluid is pumped from the mud tank **130**, the drilling fluid may pass through the mud chiller **176**, the mud chiller **176** further cooling the drilling fluid. In such examples, to lower reliance on fossil fuel generated electrical power, the mud chiller **176** may utilize electrical power generated by the ORC unit **142**, in addition to or rather than electrical power from a generated by a generator or generator set.

FIG. **2A**, FIG. **2B**, FIG. **2C**, FIG. **2D**, FIG. **2E**, FIG. **2F**, FIG. **2G**, and FIG. **2H** are block diagrams illustrating example implementations of an electrical power generation enabled drilling rig to provide electrical power to one or more of in-field equipment, equipment at other sites, energy storage devices, and the grid power structure, according to one or more embodiment of the disclosure. Turning first to FIG. **2A**, a drilling rig **200** may include one or more heat sources. The one or more heat sources may include drilling fluid from a drilling fluid return pipe **202**, exhaust from an engine exhaust port **204**, water or other coolant from a water jacket **206**, additional engines (e.g., providing additional exhaust and/or fluid from a water jacket) among other sources.

The drilling fluid from the drilling fluid return pipe **202** may, after cooling the drill bit of a drilling rig **200**, be heated to about 100 degrees Fahrenheit to about 500 degrees Fahrenheit, or in some examples, hotter than 500 degrees Fahrenheit. As the heated drilling fluid flows into or from the drilling fluid return pipe **202**, the temperature of the drilling fluid may be determined or sensed (e.g., via sensor **278** as illustrated in FIG. **2G**). If the temperature of the drilling fluid is within a specified or preselected temperature range, control valve **216** may open to a position to allow a portion or all of the drilling fluid to flow therethrough to the heat exchanger **218**. Further, if the temperature of the drilling fluid is above or below the specified or preselected temperature range, then the control valve **216** may close fully or partially and the control valve **214** may open fully or partially, thus drilling fluid is directed directly, at least partially, to a drilling fluid tank **220**. If drilling fluid flows through the heat exchanger **218**, then the heat exchanger **218**

22

may facilitate heat transfer from the drilling fluid to a working fluid. The heated working fluid produced by heat exchanger **218** may flow to the ORC unit A **234A** and may cause the ORC unit A **234A** to generate electrical power **236**.

The exhaust from the engine exhaust port **204** may be heated to about 500 degrees Fahrenheit to about 1200 degrees Fahrenheit. The exhaust may exit the engine at about 2000 cubic feet per minute to about 20000 cubic feet per minute. As the exhaust flows from the engine exhaust port **204**, the temperature and/or thermal mass of the exhaust may be determined or sensed (e.g., via sensor **284** as illustrated in FIG. **2G**). If the temperature of the exhaust is within a specified or preselected temperature or thermal mass range, control valve **222** may open to a position to allow a portion or all of the exhaust to flow therethrough to the heat exchanger **210**. Further, if the temperature of the exhaust is above or below the specified or preselected temperature or thermal mass range, then the control valve **222** may close fully or partially and the control valve **224** may open fully or partially, thus exhaust is directed directly, at least partially, to the atmosphere. If exhaust flows through the heat exchanger **210**, then the heat exchanger **210** may facilitate heat transfer from the exhaust to a working fluid. The heated working fluid may flow to the ORC unit B **234B** and may cause the ORC unit B **234B** to generate electrical power **236**.

The fluid from the water jacket **206** may, after cooling the engine at a drilling rig **200**, be heated to about 165° F. to about 230° F. at rate of about 70 gallons per minute to about 250 gallons per minute. As the fluid flows from the water jacket **206**, the temperature of the fluid may be determined or sensed (e.g., via sensor **292** as illustrated in FIG. **2G**). If the temperature of the fluid is within a specified or preselected temperature range, control valve **228** may open to a position to allow a portion or all of the drilling fluid to flow therethrough to the heat exchanger **212**. Further, if the temperature of the fluid is above or below the specified or preselected temperature range, then the control valve **228** may close fully or partially and the control valve **230** may open fully or partially, thus the fluid is directed directly, at least partially, to a heat sink **232**. If the fluid flows through the heat exchanger **212**, then the heat exchanger **212** may facilitate heat transfer from the fluid to a working fluid. The heated working fluid may flow to the ORC unit C **234C** and may cause the ORC unit C **234C** to generate electrical power **236**.

In an embodiment, one or more of the heat sources may be utilized to generate electrical power **236** in any of the ORC units present at the drilling rig **200**. For example, drilling fluid may be utilized, in addition to engine exhaust, to generate electrical power **236** in ORC unit A **234A** and ORC unit B **234B** (as illustrated in FIG. **2A**), respectively. In such an example, heat from the engine exhaust and drilling fluid may be utilized to maximize the amount of electrical power **236** generated, as the engine exhaust may exhibit high temperatures and a cooled drilling fluid may not be cooled further or be cooled less by a mud chiller thereby less electrical power is utilized at the drilling rig **200** overall. In another example, engine exhaust and/or fluid from the water (or other fluid) jacket **206** may be utilized to generate electrical power **236** in ORC unit **246** (as illustrated in FIG. **2B**). In such an example, heat from the engine exhaust and/or fluid from the water jacket **206** may be utilized to maximize electrical power **236** and engine performance, as the engine exhaust, as noted, may exhibit a high temperature and transferring heat from the fluid from the water jacket **206** may cool such fluid to a temperature lower than normal

23

thereby enabling additional heat to be transferred from the engine to the fluid in the water jacket **206** and causing the engine to operate for longer (e.g., less wear on parts and/or consumables) and operate at higher efficiency.

As illustrated in FIG. 2B, the drilling rig **200** may include a supply manifold **242** and a return manifold **244**. In such examples, the working fluid may coalesce or combine at each manifold (e.g., the supply manifold **242** and the return manifold **244**). For example, the working fluid may flow from each of the heat exchangers **210**, **212**, **218**, and up to **240** and combine at the supply manifold **242**. The working fluid may then flow through the ORC unit **246** then back to the return manifold **244**, where the working fluid may then flow back to each of the heat exchangers **210**, **212**, **218**, and up to **240**. The supply manifold **242** and/or return manifold **244** may each include (e.g., internal to or external and proximate to) flow control devices configured to adjust the amount of working fluid flowing to each heat exchanger, thus various aspects of the drilling rig **200** may be controlled (e.g., electrical power generation, engine performance, drill bit and/or bottom-hole assembly component life span, and/or other aspects). As noted and described herein, the flow drilling fluid, exhaust, and/or fluid from a water jacket, among other fluids from other heat sources, may flow to one of the one or more exchangers **210**, **212**, **218**, and up to **240** via various valves and pipeline. The supply manifold **242**, return manifold **244**, the flow control devices, the sensors, and/or any other devices described in FIGS. 2A-2H may be positioned or disposed at various points in between the ORC units and heat exchangers in FIG. 1A through FIG. 1C.

In FIG. 2C, each pipeline from the heat exchangers **210**, **212**, **218**, and up to **240** to the supply manifold **242** may include a sensor (e.g., sensor **274**, **286**, **294**, and **299** as illustrated in FIG. 2G), such as a temperature sensor, flow meter, or other sensor may measure or sense some characteristic of the working fluid. Each pipeline from the return manifold **244** to the heat exchangers **210**, **212**, **218**, and up to **240** may include a sensor (e.g., sensor **272**, **282**, **290**, and **298** as illustrated in FIG. 2G), such as a temperature sensor, flow meter, or other sensor to measure some characteristic of the working fluid. Further, the pipeline positioned between the return manifold **244** and the ORC unit **246** may include one or more flow control devices **254**, **258**, in addition to one or more sensors **252**, **256** (e.g., temperature sensors or some other suitable sensor), thereby controlling the flow of working fluid from the ORC unit **246** to the return manifold **244**. Each pipeline from the return manifold **244** to the heat exchangers **210**, **212**, **218**, and up to **240** may further include a flow control device **248A**, **248B**, **248C**, and up to **248N** thereby controlling the flow of the working fluid from the return manifold **244** to each of the heat exchangers **210**, **212**, **218**, and up to **240**. Utilizing various combinations of each sensor and each flow control device, the temperature and flow of the working fluid may be concisely controlled. The pipeline from the supply manifold **242** to the ORC unit **246** can include a sensor **250** to measure temperature or some other characteristic of the working fluid. Based on the measurements or determinations of the temperature or other characteristic of the working fluid (e.g., flow, pressure, density, etc.), the flow control devices may adjust the amount of working fluid flowing to each of the one or more heat exchangers ensuring that the proper amount of working fluid flows to each of the one or more exchangers. For example, one of the heat exchangers may not be producing heat for use in the ORC unit **246**. In such examples, the flow

24

control device associated with that particular heat exchanger may prevent further flow of working fluid to the that heat exchanger.

In FIG. 2D, the flow control devices positioned between the return manifold **244** and each of the one or more heat exchangers **210**, **212**, **218**, and up to **240** may be control valves **264A**, **264B**, **264C**, and up to **264N**. The flow control devices between the return manifold **244** and the ORC unit **246** may be a pump **260**, while the flow control device within the ORC unit **246** may be a pump **262**. In FIG. 2E, the flow control devices used throughout the site may be pumps **266A**, **266B**, **266C**, and up to **266N** or variable speed pumps. In FIG. 2F, the flow control devices may include some combination of one or more control valves **264A**, **264B**, **264C**, and up to **264N** and/or one or more pumps **266A**, **266B**, **266C**, and up to **266N**. In an embodiment, the one or more flow control devices **254**, **256**, **248A**, **248B**, **248C**, and up to **248N** may include one or more of a fixed speed pump, a variable speed drive pump, a control valve, an actuated valve, or other suitable device to control flow of a fluid.

In FIG. 2G, the drilling rig **200** may include a controller **268** (e.g., such as the master controller in FIG. 3). The controller **268** may include instructions executable by a processor included in the controller **268**. The controller **268** may receive various aspects of or data related to the drilling rig **200**, such as temperature, pressure, flow rate, and/or other factors from the various sensors disposed or positioned throughout (e.g., sensors **270**, **272**, **274**, **276**, **278**, **280**, **282**, **284**, **286**, **288**, **290**, **292**, **294**, **296**, **297**, **298**, **299**). Based on the aspects or data received, the controller **268** may adjust each of the control valves and/or flow control devices positioned through the drilling rig **200**.

In such embodiments, the flow of working fluid to any of the heat exchangers (e.g., heat exchangers **218**, **210**, **212**, and up to **240**) may be controlled via the flow control devices. The controller **268** may utilize the flow control devices to manage, adjust, or maintain a temperature of the flow of drilling fluid, if a flow of drilling fluid flows therethrough. For example, the total percentage of working fluid flowing to each heat exchanger, for example heat exchangers **218**, **210**, **212**, and up to **240**, may initially be equal. As temperatures vary and the temperature of the flow of drilling fluid rises or falls and/or the temperature of the engine (based on the temperature of the fluid from the water jacket) rises or falls, then the percentage or amount of working fluid to a particular heat exchanger may be increased or decreased to lower or raise, respectively, the temperature of the flow of drilling fluid and/or fluid from the water jacket flowing therethrough.

For example, the controller **268** may include instructions to optimize or maximize the amount of electrical power generated. Based on the temperatures of each fluid received from a heat source and/or the temperature of working fluid flowing from each heat exchanger, the controller **268** may increase (e.g., via control valves or flow control devices) the amount of working fluid flowing to heat exchangers with higher temperatures, thus increasing the overall temperature of the working fluid and thereby generating an increased amount of electrical power in the ORC unit **246**. In another embodiment, the controller **268** may include instructions to increase engine efficiency. In such examples, the controller may increase (e.g., via control valves or flow control devices) the amount of working fluid flowing to heat exchanger **212** associated with the water jacket **206**. In yet another embodiment, the controller **268** may include instructions to lower the temperature of the drilling fluid to the

25

lowest potential temperature by increasing the flow of working fluid to the heat exchanger **218** associated with the drilling fluid borehole return **202**. Such working fluid flow rate adjustments may be made or performed intermittently or continuously. In a further example, an adjustment to a particular working fluid flow rate may be performed and then temperatures, flow rates, and/or other characteristics may be determined. Further adjustments may be performed and temperatures, flow rates, and/or other characteristics may be determined again. Such operations may be performed until the temperature of the flow of gas and/or the working fluid is at a desired temperature, with a selected operating range or window, and/or steady-state temperature.

In FIG. 2H and as noted, the ORC unit **246** may produce electricity based on received heated working fluid. The ORC unit **246**, in an embodiment, may provide electrical power to battery banks **251** or other energy storage devices, to the grid **253**, to a mud chiller **255**, and/or to field equipment or other equipment/loads **257**.

In an embodiment, the site may include a warm supply manifold and a warm return manifold, for controlling the flow of warm working fluid from warm water heat exchangers (e.g., working fluid from the heat exchangers associated with the drilling fluid borehole return **202**, fluid from the water jacket **206**, and/or fluid from another heat source **238**) to a warm fluid intake/outtake of the ORC unit **246**. The site may also include a hot supply manifold and a hot return manifold, for controlling the flow of hot working fluid from hot water heat exchangers (e.g., working fluid from the heat exchangers associated with the drilling fluid borehole return **202**, exhaust from the engine exhaust port **204**, fluid from the water jacket **206**, and/or fluid from another heat source **238**) to a hot fluid intake/outtake of the ORC unit **246**.

FIG. 3 is a simplified diagram illustrating a control system for managing electrical power production at a drilling rig, according to one or more embodiments of the disclosure. A master controller **302** may manage the operations of electrical power generation at a facility during gas compression. The master controller **302** may be one or more controllers, a supervisory controller, programmable logic controller (PLC), a computing device (such as a laptop, desktop computing device, and/or a server), an edge server, a cloud based computing device, and/or other suitable devices. The master controller **302** may be located at or near the drilling rig. The master controller **302** may be located remote from the facility. The master controller **302**, as noted, may be more than one controller. In such cases, the master controller **302** may be located near or at the drilling rig, various facilities and/or at other off-site locations. The master controller **302** may include a processor **304**, or one or more processors, and memory **306**. The memory **306** may include instructions. In an example, the memory **306** may be a non-transitory machine-readable storage medium. As used herein, a “non-transitory machine-readable storage medium” may be any electronic, magnetic, optical, or other physical storage apparatus to contain or store information such as executable instructions, data, and the like. For example, any machine-readable storage medium described herein may be any of random access memory (RAM), volatile memory, non-volatile memory, flash memory, a storage drive (e.g., hard drive), a solid state drive, any type of storage disc, and the like, or a combination thereof. As noted, the memory **306** may store or include instructions executable by the processor **304**. As used herein, a “processor” may include, for example one processor or multiple processors included in a single device or distributed across multiple computing devices. The processor may be at least

26

one of a central processing unit (CPU), a semiconductor-based microprocessor, a graphics processing unit (GPU), a field-programmable gate array (FPGA) to retrieve and execute instructions, a real time processor (RTP), other electronic circuitry suitable for the retrieval and execution instructions stored on a machine-readable storage medium, or a combination thereof.

As used herein, “signal communication” refers to electric communication such as hard wiring two components together or wireless communication for remote monitoring and control/operation, as understood by those skilled in the art. For example, wireless communication may be Wi-Fi®, Bluetooth®, ZigBee, cellular wireless communication, satellite communication, or forms of near field communications. In addition, signal communication may include one or more intermediate controllers or relays disposed between elements that are in signal communication with one another.

The master controller **302** may include instructions **308** to measure the temperature at various points at the drilling rig or at the site. For example, the temperature at the inlet of one or more heat exchangers may be measured or sensed from one or more heat exchanger temperature sensors **320A** and up to **320N**. In another embodiment, the temperature at the outlet of one or more heat exchangers may be measured from one or more heat exchanger temperature sensors **320A** and up to **320N**. In another embodiment, temperature sensors may be positioned at both the inlet and outlet of the heat exchanger. The master controller **302** may further include instructions **312** to measure the amount of electrical power output from the ORC unit **330**. In an embodiment, the drilling rig or at the site may include one or more ORC units and, in such examples, each ORC unit may connect to the master controller **302** to provide, among other information or data, the amount of electrical power output over time.

The master controller **302** may further connect to one or more heat exchanger valves **326A**, **326B**, and up to **326N** and working fluid valves **328A**, **328B**, and up to **328N**. The master controller **302** may include instructions **310** to adjust each of these valves based on various factors. For example, if the temperature measured from one of the heat exchangers is below a threshold or outside of a selected operating temperature range or window and/or if the ambient temperature from the ambient temp sensor **322** is above a preselected threshold, then the master controller **302** may transmit a signal causing one or more of the heat exchanger valves **326A**, **326B**, up to **326N** to close. Such a threshold may be defined by the temperature sufficient to ensure the ORC unit generates an amount of electrical power. The operating temperature range or window may be defined by an operating temperature of the ORC unit and/or by the lowest and highest potential temperature of the flow of drilling fluid. The ambient threshold may be defined by an ambient temperature at which engine performance may degrade and/or drilling fluid may not cool sufficiently. In another example, based on a heat exchanger inlet temperature and an outlet temperature, the master controller **302** may adjust, via a signal transmitted to, one of the one or more of the heat exchanger valves **326A**, **326B**, and up to **326N** and/or working fluid valves **328A**, **328B**, and up to **328N**. The master controller **302** may consider other factors (e.g., temperature, pressure, flow rate, density, composition, etc.) as described herein.

The master controller **302** may include instructions **306** to measure the working fluid temperature via a sensor (e.g., via one or more heat exchanger temperature sensors **322**). The master controller **302** may include instructions **310** to adjust the flow of working fluid to any one of the one or more heat

exchangers based on the measured temperatures. The flow of the working fluid may be adjusted by the master controller **302**, as noted, based on various temperature measurements of the working fluid, via one or more working fluid flow control devices (e.g., working fluid valves **328A**, **328B**, up to **328N**) and/or a master flow control device. In an embodiment, the adjustment of the flow of working fluid may occur to adjust the temperature of the flow of gas through a corresponding heat exchanger.

As noted, the master controller **302** may adjust the amount of working fluid flowing to each of the heat exchangers based on an aspect of the drilling rig to be optimized. For example, adjustment of a working fluid valve (e.g., working fluid valves **328A**, **328B**, and/or up to **328N**) associated with the drilling fluid may cause a decrease in the temperature of the drilling fluid to thereby decrease cooling via a mud chiller and to further thereby decrease overall electrical power utilized at the drilling rig. Adjustment of a second working fluid control valve (e.g., working fluid valves **328A**, **328B**, and/or up to **328N**) may cause an increase in working fluid flow to the heat exchanger associated with the exhaust output from the engine, thereby causing an increase in overall electrical power generated by the ORC unit due to the high heat of the exhaust and to thereby optimize engine and generator set performance. Adjustment of a third working fluid flow control device (e.g., working fluid valves **328A**, **328B**, and/or up to **328N**) may cause an increase in working fluid flow to the water jacket heat exchanger thereby causing an increase in engine performance due to increased heat transfer from the engine to the working fluid. Various adjustments may be made over varying time intervals, the temperatures or other characteristic of the drilling rig to be measured at each interval and further adjustments made. Finally, the master controller **302** may maximize each aspect of the drilling rig or maximize one or more aspect based on other factors. For example, the master controller **302** may maximize the electrical power generated by the ORC unit during peak hours of electrical power usage of the drilling rig. In other words, when the most electrical power is utilized by equipment at the drilling rig, then the master controller **302** may adjust working fluid control valves, such that the most heat is transferred to the working fluid thereby enabling the ORC unit to generate the most electrical power. In another example, during off-peak hours, the master controller **302** may adjust the working fluid to heat exchangers such that enough electrical power is generated to supply the electrical power requirements during such off-peak hours.

In an embodiment, the master controller **302** may connect to a user interface **332**. A user may interact with the master controller **302** via the user interface **332**. The user may manually enter each of the thresholds, the operating temperature ranges or windows, or some aspect to optimize described herein and/or may manually adjust any of the control valves described herein.

FIG. 4A is a flow diagram of electrical power generation in which, during a drilling operation, working fluid is heated via one or more of drilling fluid or drilling mud, engine exhaust, and/or water jacket fluid flow, according to one or more embodiments of the disclosure. The method is detailed with reference to the master controller **302** and the drilling rig **100** of FIGS. 1A through 1C. Unless otherwise specified, the actions of method **400** may be completed within the master controller **302**. Specifically, method **400** may be included in one or more programs, protocols, or instructions loaded into the memory of the master controller **302** and executed on the processor or one or more processors of the master controller **302**. The order in which the operations are

described is not intended to be construed as a limitation, and any number of the described blocks may be combined in any order and/or in parallel to implement the methods.

Turning to FIG. 4A, at block **402**, the master controller **302** may determine whether a drilling operation is occurring. If a drilling operation is not occurring, the master controller **402** may wait and perform such a determination may be performed again. If a drilling operation is occurring or has begun, the master controller **302** may proceed to perform the next operation.

At block **404**, a pump may pump drilling fluid through and around a drill bit thereby cooling the drill bit. The drilling fluid may then flow up a borehole to a drilling fluid return pipe.

At block **406**, the master controller **302** may determine or sense a temperature of the drilling fluid, for example, via a drilling fluid return temperature sensor. In an embodiment, other aspects of the drilling fluid or any other fluid may be determined.

At block **408**, the master controller **302** may determine whether the temperature of the drilling fluid is within a range or window. The range or window may be defined by a maximum operating temperature of the first heat exchanger and a minimum temperature at which ORC equipment generates electricity.

At block **410**, if the temperature is above or below of a range, the master controller **302** may determine if the drilling operation is finished or still occurring. If the temperature is within the range or window, the master controller **302** may adjust a divert a drilling fluid to a drilling fluid heat exchanger via a drilling fluid control valve. The drilling fluid control valve may partially or fully divert a portion of the exhaust produced by the engine. In another embodiment, the exhaust control valve may be adjusted to maintain the first heat exchanger. In another embodiment, other aspects may be considered when adjusting a drilling fluid control valve, such as an amount of electrical power generated, temperature of an engine, temperature of an engine's exhaust, temperature of fluid from a water jacket, and so on. In such embodiments, in addition to adjusting the amount of drilling fluid flowing to a heat exchanger, the amount of working fluid flowing to that particular heat exchanger may be adjusted (e.g., an increase in working fluid causing greater heat transfer from the drilling fluid to the working fluid and a decrease in working fluid causing lesser heat transfer from the drilling fluid to the working fluid). In other words, the temperature of the drilling fluid may be controlled based on the amount of working fluid flowing through the corresponding heat exchanger.

At block **412**, the drilling fluid may be returned to the drilling fluid container from the heat exchanger. At block **414**, the master controller **302** may determine whether the drilling operation is finished. If the drilling operation is finished, the master controller **302** may wait until another drilling operation begins. If the drilling operation is not finished, the master controller **302** may perform method **400** again, for the duration of a drilling operation.

FIGS. 4B and 4C are flow diagrams of electrical power generation in which, during drilling operations, working fluid is heated via engine exhaust and/or water jacket fluid flow, according to one or more embodiment of the disclosure. The method is detailed with reference to the master controller **302** and drilling rig **100** of FIGS. 1A through 1C. Unless otherwise specified, the actions of method **401** may be completed within the master controller **302**. Specifically, method **900** may be included in one or more programs, protocols, or instructions loaded into the memory of the

29

master controller **302** and executed on the processor or one or more processors of the master controller **302**. The order in which the operations are described is not intended to be construed as a limitation, and any number of the described blocks may be combined in any order and/or in parallel to implement the methods.

Turning to FIG. 4B, at block **402**, the master controller **302** may determine whether a drilling operation is occurring. If a drilling operation is not occurring, the master controller **402** may wait and perform such a determination may be performed again. If a drilling operation is occurring or has begun, the master controller **302** may proceed to perform the next operation.

At block **416**, fluid (e.g., exhaust) produced by the engine may be transported to a second heat exchanger. The second heat exchanger may facilitate heat transfer from the fluid (e.g., exhaust) to a working fluid or intermediate work fluid. The heated working fluid or intermediate working fluid may be utilized by an ORC unit to generate electrical power during an ORC operation. The working fluid or intermediate working fluid may be considered warm or hot and may be utilized in a warm or low temperature ORC operation or a hot or high temperature ORC operation, respectively.

At block **418**, the master controller **302** may sense or determine the temperature of the exhaust. The master controller **302** may sense or determine the temperature of the exhaust via a temperature sensor.

At block **420**, the master controller **302** may determine whether the temperature or thermal mass of the exhaust is within a range or window. The range or window may be defined by a maximum operating temperature or thermal mass of the first heat exchanger and a minimum temperature or thermal mass at which ORC equipment generates electricity.

At block **422**, if the temperature or thermal mass is within a range, the master controller **302** may re-execute or perform method **401** again. If the temperature or thermal mass is above or below the range or window, the master controller **302** may adjust an exhaust control valve. The exhaust control valve may partially or fully divert a portion of the exhaust produced by the engine. In another embodiment, the exhaust control valve may be adjusted to maintain the second heat exchanger. Over time, scaling or depositions of particulates in the exhaust may build. As such, the second heat exchanger may be cleaned or maintained to remove the buildup and, during such cleaning or maintenance, the exhaust control valve may be fully closed. Once the second heat exchanger has been maintained, the exhaust control valve may be adjusted to allow the exhaust to flow to the second heat exchanger. In another embodiment, a portion of the exhaust may be diverted (e.g., via the exhaust control valve) from the second heat exchanger to limit the amount of scaling and/or deposition of particulates. In yet another embodiment, the exhaust control valve may be adjusted to prevent interruption of catalyst performance.

In another embodiment, the amount of electricity generated may be adjusted based on adjustment of working fluid flowing to the heat exchanger corresponding to the exhaust. Since the exhaust is output from the engine at a high temperature, the amount of heat transferred to the working fluid may be high. However, a temperature of the working fluid may produce a maximum amount of electrical power. The master controller **302** may, based on such data, adjust the working fluid flowing to the heat exchanger corresponding to the exhaust.

Turning to FIG. 4B, at block **402**, the master controller **302** may determine whether a drilling operation is occurring.

30

If a drilling operation is not occurring, the master controller **402** may wait and perform such a determination may be performed again. If a drilling operation is occurring or has begun, the master controller **302** may proceed to perform the next operation.

At block **424**, fluid from a water jacket may be transported to a third heat exchanger. The third heat exchanger may facilitate heat transfer from the fluid of the water jacket to a working fluid or intermediate work fluid. The heated working fluid or intermediate working fluid may be utilized by an ORC unit to generate electrical power during an ORC operation. The working fluid or intermediate working fluid may be considered warm or hot and may be utilized in a warm or low temperature ORC operation or a hot or high temperature ORC operation, respectively.

At block **426**, the master controller **302** may determine whether the temperature of the fluid from the water jacket is within a range or window. The range or window may be defined by a maximum operating temperature mass of the third heat exchanger and a minimum temperature at which ORC equipment generates electricity.

At block **428**, if the temperature of the fluid from the water jacket is within a range, the master controller **302** may re-execute or perform method **401** again. If the temperature of the fluid from the water jacket is above or below the range or window, the master controller **302** may adjust water jacket control valve. The water jacket control valve may partially or fully divert a portion of the fluid from the water jacket. In another embodiment, the water jacket control valve may be adjusted to maintain the third heat exchanger. In another embodiment, the performance of the engine may be maximized based on adjustment of working fluid flowing to the heat exchanger corresponding to the fluid from the water jacket.

FIG. 5 is a flow diagram of electrical power generation in which, during a drilling operation, working fluid is heated via one or more fluids from heat sources, according to one or more embodiments of the disclosure. The method is detailed with reference to the master controller **302** and the drilling rig **100** of FIGS. 1A through 1C. Unless otherwise specified, the actions of method **500** may be completed within the master controller **302**. Specifically, method **500** may be included in one or more programs, protocols, or instructions loaded into the memory of the master controller **302** and executed on the processor or one or more processors of the master controller **302**. The order in which the operations are described is not intended to be construed as a limitation, and any number of the described blocks may be combined in any order and/or in parallel to implement the methods.

At block **502**, the master controller **302** and/or a user may begin a drilling operation. In an embodiment, when a drilling operation begins, the master controller **302** may receive a signal indicating that the drilling operation has begun. In another embodiment, the activation or use of pumps, control valves, engines, and/or other drilling rig equipment may indicate to the master controller **302** that a drilling rig has begun. In yet another embodiment, a user may indicate that a drilling operation has begun via the user interface **332**.

At block **504**, the master controller **302** may check or determine, at varying points during the drilling operation, whether the drilling operation has finished or has been completed. The master controller **302** may, if the drilling operation is ongoing, proceed to the next block in an operation or process (e.g., block **506**). In another embodiment, the master controller **302** may, if the drilling operation

31

has finished or has been completed, proceed back to block 502 and wait until another or a next drilling operation has begun. The master controller 302 may determine that a drilling operation is complete if one or more different equipment at the drilling rig is not being utilized or not operating. For example, if a drilling fluid or mud pump is not operating, the master controller 302 may determine that the drilling operation has completed or has been paused. In another embodiment, a user may indicate that a drilling operation is complete or paused via the user interface 332. In yet another embodiment, the master controller 302 may determine that a drilling operation is ongoing based on the flow and/or other characteristics of various fluids at the drilling rig (e.g., a flow of drilling fluid, flow of exhaust, a flow of fluid from an engine water or fluid jacket, temperatures of various fluids, etc.).

At block 506, the master controller 302 or a user may select one or more fluids, each of the fluids corresponding to one or more heat sources at a drilling rig. As noted, a drilling rig may include various sources of heat. For example, an engine, during operation, may produce heated exhaust. Further, as the engine operates, the engine's temperature may increase. Such a temperature increase may decrease the overall life of consumables and/or parts of the engine. To prevent such a decrease, the engine may include a water jacket or fluid jacket (e.g., a jacket utilizing a fluid capable of transporting heat from the engine) to cool the engine via circulation of water or fluid within the jacket and a heat sink or other cooling equipment. The drilling rig may include other heat sources, such as heated drilling fluid from a borehole. One or more of the fluids associated with these various heat sources may each flow through added or installed heat exchangers at the site (e.g., a heat exchanger for drilling fluid, one or more heat exchangers corresponding to one or more engines for exhaust, one or more heat exchangers corresponding to one or more engines for fluid from a fluid jacket, and/or heat exchangers for other sources).

The master controller 302 and/or a user may determine which heat source and/or associated or corresponding heat exchanger to utilize for ORC operations (e.g., selecting a heat source). Such a selection may be based on the temperature of the fluid flowing from the heat source and whether the temperature is within an operating range of the ORC unit and/or of a corresponding heat exchanger. The selection may also be based on flow rates of the fluid and whether the flow rate is sufficient to facilitate heat transfer from the fluid to a working fluid in the associated or corresponding heat exchanger. For example, the flow rate may be at such a rate to prevent sufficient heat transfer. The selection may be based on the thermal mass of the fluid and whether the thermal mass is within operating range of the associated or corresponding heat exchanger. Other factors may be utilized in such selections, such as a desired, specified, selected, or pre-selected electrical power output; the ambient temperature at the drilling rig; whether engine optimization, electrical power output maximization, and/or electrical power utilization (e.g., off-setting equipment power use) is sought; a number and type of available heat exchangers at the drilling rig; and/or among other environmental factors at the drilling rig.

In an embodiment, based on the choice of fluid to be utilized for ORC operations, corresponding heat exchanger valves may be opened or closed. For example, if engine exhaust and fluid from the fluid jacket is chosen, then heat exchanger valves configured to divert fluid from normal fluid pathways or pipeline to a corresponding heat exchanger

32

may be opened (e.g., heat exchanger valves corresponding to fluid pathways or pipeline for the exhaust and fluid from the fluid jacket), while other heat exchanger valves may be closed (e.g., a heat exchanger valve corresponding to the fluid pathway or pipeline for the drilling fluid). The heat exchanger valves may be opened or closed based on signals transmitted via the master controller 302 or manually by a user. Other various combinations of heat sources may be selected.

For example, if a user or if the master controller 302 selects one or more fluids based on electrical power utilization, then the master controller 302 may select the drilling fluid, in addition to engine exhaust and/or fluid from a fluid jacket. In such examples, the drilling fluid may be cooled to a specified or preselected temperature via a corresponding heat exchanger and then further cooled via a mud chiller. The mud chiller may utilize electrical power, thus, to ensure electrical power utilization is optimized, the amount of working fluid flowing to the heat exchanger corresponding to the drilling fluid may be increased, the amount of drilling fluid flowing through the heat exchanger may be increased, and/or the electrical power generated by the ORC unit may be directed to or utilized by the mud chiller.

In another example, if a user or if the master controller 302 selects one or more fluids based on engine optimization or performance, then the master controller 302 may select the fluid from the fluid jacket, as well as, in some embodiments, to engine exhaust. In such examples, to ensure that the engine operates efficiently, the fluid from the fluid jacket may pass through a corresponding heat exchanger and the working fluid flowing to that heat exchanger may be increased, thus cooling the fluid in the fluid jacket to a lower than typical temperature. After passing through the heat exchanger the fluid in the fluid jacket may pass through a heat sink or other cooler typically used in such components thereby further cooling the fluid. The cooled fluid may then flow to the fluid jacket and cool the engine. The engine may be cooled more than typical due to the lower temperature fluid in the fluid jacket. Exhaust may be utilized to generate additional electrical power (e.g., additional to the electrical power generated via the fluid in the fluid jacket). The additional electrical power may be utilized by equipment at the drilling rig, thus allowing the engine to operate at lower speeds or operate for a reduced time thereby reducing engine wear, extending or increasing engine life, and/or extending or increasing generator set life.

In another example, if a user or if the master controller 302 selects one or more fluids based on electrical power generated, then the master controller 302 may select the exhaust from the engine, as well any other heat source. Since exhaust typically has a high thermal mass and temperature, the exhaust may be utilized to generate substantial amounts of electrical power. Any other heat source selected may be based on the temperature of the heat source (e.g., higher temperature heat sources being selected first).

In another example, if a user or if the master controller 302 selects one or more fluids based on drilling fluid temperature, then the master controller 302 may select the drilling fluid, as well as engine exhaust and/or fluid from a fluid jacket. In such examples, the drilling fluid may be cooled to a specified or preselected temperature via a corresponding heat exchanger and then further cooled via a mud chiller. The cooled drilling fluid may ensure that bottom-hole assembly components operate longer (e.g., extending the life span of the components).

At block 508, the master controller 302 may sense an ambient temperature at a drilling rig. One or more ambient

temperature sensors may be positioned at various points throughout the drilling rig. For example, an ambient temperature sensor may be positioned proximate to or nearby the engine. Another ambient temperature sensor may be positioned at a preselected distance from the engine and/or at a location where heat is not generated to thereby produce an actual ambient temperature of the environment or atmosphere at the drilling rig. Other ambient temperature sensors may be positioned throughout the drilling rig. Each of the one or more ambient temperature sensors may provide a signal to the master controller 302. The signal may indicate the temperature at the location where the ambient temperature is disposed or positioned.

At block 510, the master controller 302 may sense the temperature of each selected fluid. In such examples, temperature sensors may be positioned nearby, within, or proximate to a pipeline, conduit, or fluid path corresponding to the selected fluid. The temperature sensor may be positioned upstream of the heat exchanger (e.g., prior to where the selected fluid enters the heat exchanger). The master controller 302 may utilize temperature or other characteristics or aspects of the selected fluid from other sensors positioned throughout the drilling rig, such as temperature sensors positioned downstream of the heat exchangers, flow meters positioned upstream and/or downstream of the heat exchangers, pressure sensors or transducers positioned upstream and/or downstream of the heat exchangers, and/or other sensors positioned throughout the drilling rig.

At block 512, the master controller 302 may sense the temperature of working fluid associated with each of the selected fluids. In such examples, temperature sensors may be positioned nearby, within, or proximate to a pipeline, conduit, or fluid path corresponding to working fluid associate with or corresponding to a selected fluid. The temperature sensor may be positioned upstream or downstream of the heat exchanger (e.g., prior to where the working fluid enters the heat exchanger or subsequent to where the working fluid exits the heat exchanger). The master controller 302 may utilize temperature or other aspects or characteristics of the working fluid from other sensors positioned throughout the drilling rig, such as flow meters positioned upstream and/or downstream of the heat exchangers, pressure sensors or transducers positioned upstream and/or downstream of the heat exchangers, and/or other sensors positioned throughout the drilling rig.

At block 514, the master controller 302 may determine an amount electrical power utilized. In an embodiment, one or more ORC units may be positioned at the drilling rig. The ORC units may be configured to generate a range of electrical power. The upper range or maximum amount of electrical power of the ORC unit may be known or may be provided to the master controller 302. Further, the master controller 302 may be in signal communication with each component or equipment at the drilling rig that utilizes electrical power. The master controller 302 may determine the amount of electrical power utilized by each of the components or equipment. As such, the master controller 302 may determine the total amount of electrical power utilized at the drilling rig at an any particular time interval or on an ongoing basis.

At block 516, the master controller 302 may determine whether any selected fluid is outside a specified operating range. The operating range may be defined by the operating temperature of the corresponding heat exchanger (e.g., the highest temperature which a heat exchanger may be able to withstand and/or the lowest temperature at which heat transfer to a working fluid is facilitated) and/or the ORC unit

(e.g., the temperature of fluid at which the ORC unit generates electrical power or the maximum amount of electrical power). The operating range may include or may be defined by temperatures to optimize various aspects of electrical power generation and/or engine performance at the drilling rig. For example, the fluid selected (e.g., at block 506) may be based on optimizing a certain aspect, such as engine optimization or performance, electrical power generated, drilling fluid temperature, and/or electrical power utilization (e.g., off-setting electrical power use at the drilling rig). If any of the selected fluids are outside of the specified operating range, then the method 500 may proceed to block 524, otherwise the method 500 may proceed to block 518.

At block 518, the master controller 302 may determine whether the ambient temperature exceeds a threshold. The threshold may be defined by a temperature at which an engine's performance degrades and/or a temperature at which drilling fluid may not be cooled sufficiently. If the ambient temperature exceeds the threshold, then the method 500 may proceed to block 524, otherwise the method 500 may proceed to block 520.

At block 520, the master controller 302 may determine whether the electrical power utilized at the drilling rig exceeds a threshold. The threshold may be defined by the maximum amount of electrical power generated by the ORC unit. The threshold may be defined by an arbitrary amount of electrical power or by the maximum amount of electrical power generated by the ORC unit plus an amount of electrical power utilized or an amount of electrical power allowable from a fossil fuel based generator set. If the electrical power utilized exceeds the threshold, then the method 500 may proceed to block 524, otherwise the method 500 may proceed to block 522.

At block 522, the master controller 302 may determine whether the working fluid for each selected fluid is within an operating range. The operating range may be defined by a temperature of working fluid at which an ORC unit generates electrical power and a temperature of working fluid at which the ORC unit generates a maximum amount of electrical power. If the working fluid is within the operating range, then the method 500 may proceed to block 504, otherwise the method 500 may proceed to block 524.

At block 524, the master controller 302 may adjust each working fluid flow control device associated with each selected fluid. The working fluid flow control device may control an amount of working fluid flowing to a heat exchanger. The adjustment of the position of each working fluid flow control device may be based on the various temperatures and/or other aspects, as well as whether an aspect exceeds a threshold and/or is within an operating range. For example, if the working fluid associated with a heat exchanger corresponding to drilling fluid is lower than the smallest value of the operating range of the ORC unit, then the corresponding working fluid flow control device may be closed. In such an example and in other examples, an increase in working fluid flowing to a heat exchanger may increase facilitation of heat from a fluid to the working fluid, while a decrease in working fluid flowing to a heat exchanger may decrease the facilitation of heat from a fluid to the working fluid.

At block 526, the master controller 302 may adjust each heat exchanger valve associated with each selected fluid. The valve associated with a specified heat exchanger may control the amount of a selected fluid flowing to a heat exchanger. The adjustment of the position of each valve may be based on the various temperatures and/or other aspects, as

35

well as whether an aspect exceeds a threshold and/or is within an operating range. For example, if the selected fluid associated with a heat exchanger is lower than the least value of the operating range of the ORC unit, then the corresponding valve may be closed. In such an example and in other examples, an increase in a selected fluid flowing to a heat exchanger may increase facilitation of heat transfer from the selected fluid to the working fluid, while a decrease in selected fluid flowing to the heat exchanger may decrease the facilitation of heat from the selected fluid to the working fluid.

In an embodiment, after all adjustments are made the method **500** may be performed again or until the drilling operation has finished. Further, the master controller **302** may wait a preselected interval of time between each sensing or measurement of temperature and/or other aspects or characteristics and adjustment. The preselected interval of time may be sufficient to allow temperatures to stabilize (e.g., after adjustment, temperatures may vary due to such adjustments, thus the master controller **302** may wait until temperatures and/or other aspects are stabilized). The preselected interval of time may be about 30 seconds, about 1 minute, about 5 minutes, about 15 minutes, about 30 minutes, or longer.

FIG. **6** is a flow diagram of electrical power generation in which, during a drilling operation, working fluid is heated via one or more fluids from heat sources, according to one or more embodiments of the disclosure. The method is detailed with reference to the master controller **302** and the drilling rig **100** of FIGS. **1A** through **1C**. Unless otherwise specified, the actions of method **600** may be completed within the master controller **302**. Specifically, method **600** may be included in one or more programs, protocols, or instructions loaded into the memory of the master controller **302** and executed on the processor or one or more processors of the master controller **302**. The order in which the operations are described is not intended to be construed as a limitation, and any number of the described blocks may be combined in any order and/or in parallel to implement the methods.

At block **602**, the master controller **302** and/or a user may begin a drilling operation. In an embodiment, when a drilling operation begins, the master controller **302** may receive a signal indicating that the drilling operation has begun. In another embodiment, the activation or use of pumps, control valves, engines, and/or other drilling rig equipment may indicate to the master controller **302** that a drilling rig has begun. In yet another embodiment, a user may indicate that a drilling operation has begun via the user interface **332**.

At block **604**, the master controller **302** may check or determine, at varying points during the drilling operation, whether the drilling operation has finished or has been completed. The master controller **302** may, if the drilling operation is ongoing, proceed to the next block in an operation or process (e.g., block **506**). In another embodiment, the master controller **302** may, if the drilling operation has finished or has been completed, proceed back to block **502** and wait until another or a next drilling operation has begun. The master controller **302** may determine that a drilling operation is complete if one or more different equipment at the drilling rig is not being utilized or not operating. For example, if a drilling fluid or mud pump is not operating, the master controller **302** may determine that the drilling operation has completed or has been paused. In another embodiment, a user may indicate that a drilling operation is complete or paused via the user interface **332**.

36

In yet another embodiment, the master controller **302** may determine that a drilling operation is ongoing based on the flow of various fluids at the drilling rig (e.g., a flow of drilling fluid, exhaust, fluid from an engine water or fluid jacket, etc.).

At block **606**, the master controller **302** may sense a drilling fluid temperature. In such an embodiment, a temperature sensor may be positioned along a drilling fluid return pipeline. The temperature sensor may provide a signal to the master controller **302** indicating the temperature of the drilling fluid.

At block **608**, the master controller **302** may sense an ambient temperature at a drilling rig. One or more ambient temperature sensors may be positioned at various points throughout the drilling rig. For example, an ambient temperature sensor may be positioned proximate to or nearby the engine. Another ambient temperature sensor may be positioned at a preselected distance from the engine and/or at a location where heat is not generated to thereby produce an actual ambient temperature of the environment or atmosphere at the drilling rig. Other ambient temperature sensors may be positioned throughout the drilling rig. Each of the one or more ambient temperature sensors may provide a signal to the master controller **302**. The signal may indicate the temperature at the location where the ambient temperature is disposed or positioned.

At block **610**, the master controller **302** may determine an amount electrical power utilized at the drilling rig. In an embodiment, one or more ORC units may be positioned at the drilling rig. The ORC units may be configured to generate a range of electrical power. The upper range or maximum amount of electrical power of the ORC unit may be known or may be provided to the master controller **302**. Further, the master controller **302** may be in signal communication with each component or equipment at the drilling rig that utilizes electrical power. The master controller **302** may determine the amount of electrical power utilized by each of the components or equipment. As such, the master controller **302** may determine the total amount of electrical power utilized at the drilling rig at an any particular time interval or on an ongoing basis. In another embodiment, in addition to or rather than the determination of electrical power utilized, the master controller **302** may determine an amount of electrical power generated by a generator set.

At block **612**, may sense a working fluid temperature associated with drilling fluid. In such an embodiment, a temperature sensor may be positioned proximate to an outlet where working fluid exits the heat exchanger. An additional temperature sensor may be positioned at an inlet where working fluid enters the heat exchanger. The temperature sensors may provide signals to the master controller **302** indicating the temperature of the working fluid.

At block **614**, may sense a working fluid temperature associated with exhaust. In such an embodiment, a temperature sensor may be positioned proximate to an outlet where working fluid exits the heat exchanger. An additional temperature sensor may be positioned at an inlet where working fluid enters the heat exchanger. The temperature sensors may provide signals to the master controller **302** indicating the temperature of the working fluid.

At block **616**, may sense a working fluid temperature associated with fluid from the fluid jacket. In such an embodiment, a temperature sensor may be positioned proximate to an outlet where working fluid exits the heat exchanger. An additional temperature sensor may be positioned at an inlet where working fluid enters the heat exchanger.

In an embodiment, additional temperature sensors and/or other types of sensors may be included or positioned throughout the drilling rig. For example, the temperature of the exhaust and/or the fluid from the fluid jacket may be sensed prior to entry into or after exit from the heat exchanger.

At block **618**, the master controller **302** may determine whether the drilling fluid is outside an operating range. The operating range may be defined by a temperature at which heat transferred to working fluid may cause the ORC unit to generate electrical power. Other temperatures of other fluids (e.g., exhaust and/or fluid from the fluid jacket) may be considered. If the temperature of the drilling fluid is outside of the specified operating range, then the method **600** may proceed to block **620**, otherwise the method **600** may proceed to block **626**.

At block **620**, the master controller **302** may determine whether the ambient temperature exceeds a threshold. The threshold may be defined by a temperature at which an engine's performance degrades and/or a temperature at which drilling fluid may not be cooled sufficiently. If the ambient temperature exceeds the threshold, then the method **600** may proceed to block **622**, otherwise the method **600** may proceed to block **626**.

At block **622**, the master controller **302** may determine whether the electrical power utilized at the drilling rig exceeds a threshold. The threshold may be defined by the maximum amount of electrical power generated by the ORC unit. The threshold may be defined by an arbitrary amount of electrical power (e.g., the amount set by a user or the master controller **302**) or by the maximum amount of electrical power generated by the ORC unit plus an amount of electrical power utilized or an amount of electrical power allowable from a fossil fuel based generator set. If the electrical power utilized exceeds the threshold, then the method **500** may proceed to block **524**, otherwise the method **500** may proceed to block **522**.

At block **624**, the master controller **302** may determine whether the working fluid for each heat source (e.g., the drilling fluid, the exhaust, and/or the fluid from a fluid jacket) is within an operating range. The operating range may be defined by a temperature of working fluid at which an ORC unit generates electrical power and a temperature of working fluid at which the ORC unit generates a maximum amount of electrical power. If the working fluid is within the operating range, then the method **600** may proceed to block **604**, otherwise the method **600** may proceed to block **626**.

At block **626**, the master controller **302** may adjust the amount of working fluid flowing to the heat exchanger associated with the drilling fluid and/or the amount of drilling fluid flowing to the heat exchanger. By adjusting the amount of working fluid and drilling fluid flowing through the heat exchanger, the temperature of the working fluid and/or the drilling fluid may be controlled. Such adjustments may occur based on which block of the method precedes block **626**. For example, if the temperature of the drilling fluid is outside of the operating range, such as at a temperature to not sufficiently transfer heat to working fluid to generate electrical power in the ORC unit, then the working fluid flow and the drilling fluid to the heat exchanger may be prevented (e.g., corresponding valves closed).

At block **628**, the master controller **302** may adjust the amount of working fluid flowing to the heat exchanger associated with the fluid from the fluid jacket and/or the amount of fluid from the fluid jacket flowing to the heat exchanger. By adjusting the amount of working fluid and fluid from the fluid jacket flowing through the heat

exchanger, the temperature of the fluid from the fluid jacket and/or the working fluid may be controlled. For example, if engine performance is prioritized and ambient temperature is above a threshold, then working fluid flow to the heat exchanger associated with fluid from the fluid jacket may be increased to thereby further cool the fluid from the fluid jacket.

At block **630**, the master controller **302** may adjust the amount of working fluid flowing to the heat exchanger associated with the exhaust and/or the amount of exhaust flowing to the heat exchanger. By adjusting the amount of working fluid and exhaust flowing through the heat exchanger, the temperature of the working fluid may be controlled. For example, if electrical power generation is prioritized, after checking electrical power utilization and generation, working fluid flow to the heat exchanger associated with exhaust may be increased, thereby increasing the temperature of the working fluid and increasing electrical power output by the ORC unit. The master controller **302** may, after adjustment, perform method **600** until the drilling operation is finished.

This application is a continuation of U.S. Non-Provisional application Ser. No. 18/099,807, filed Jan. 20, 2023, titled "Systems and Methods for Generation of Electrical Power at a Drilling Rig," which is a continuation of U.S. Non-Provisional application Ser. No. 17/657,015, filed Mar. 29, 2022, titled "Systems and Methods for Generation of Electrical Power at a Drilling Rig," now U.S. Pat. No. 11,592,009, issued Feb. 28, 2023, which is a non-provisional of and claims priority to and the benefit of U.S. Provisional Application No. 63/269,862, filed Mar. 24, 2022, titled "Systems and Methods for Generation of Electrical Power at a Drilling Rig," and U.S. Provisional Application No. 63/269,572, filed Mar. 18, 2022, titled "Systems and Methods for Generation of Electrical Power at a Drilling Rig," U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled "Systems and Methods Utilizing Gas Temperature as a Power Source," and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled "Systems and Methods for Generating Geothermal Power During Hydrocarbon Production," the disclosures of all of which are incorporated herein by reference in their entireties. U.S. Non-Provisional application Ser. No. 17/657,015 also is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/305,297, filed Jul. 2, 2021, titled "Systems for Generating Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production Based on Working Fluid Temperature," which claims priority to and the benefit of U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled "Systems and Methods for Generating Geothermal Power During Hydrocarbon Production," the disclosures of all of which are incorporated herein by reference in their entireties. U.S. Non-Provisional application Ser. No. 17/657,015 further is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/578,520, filed Jan. 19, 2022, titled "Systems and Methods Utilizing Gas Temperature as a Power Source," now U.S. Pat. No. 11,326,550, issued May 10, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled "Systems and Methods Utilizing Gas Temperature as a Power Source," and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled "Systems and Methods for Generating Geothermal Power During Hydrocarbon Production," the disclosures of all of which are incorporated herein by reference in their entireties. U.S. Non-Provisional application Ser. No. 17/657,015 also further is a continuation-in-part of U.S. Non-Provisional appli-

cation Ser. No. 17/578,528, filed Jan. 19, 2022, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” now U.S. Pat. No. 11,480,074, issued Oct. 25, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entireties. U.S. Non-Provisional application Ser. No. 17/657,015 still further is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/578,542, filed Jan. 19, 2022, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” now U.S. Pat. No. 11,480,074, issued Oct. 25, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entireties. U.S. Non-Provisional application Ser. No. 17/657,015 additionally is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/578,550, filed Jan. 19, 2022, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” which claims priority to and the benefit of U.S. Provisional Application No. 63/261,601, filed Sep. 24, 2021, titled “Systems and Methods Utilizing Gas Temperature as a Power Source,” and U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entireties. U.S. Non-Provisional application Ser. No. 17/657,015 is also a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/650,811, filed Feb. 11, 2022, titled “Systems for Generating Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production Based on Well-head Fluid Temperature,” now U.S. Pat. No. 11,578,706, issued Feb. 14, 2023, which is a continuation of U.S. Non-Provisional application Ser. No. 17/305,298, filed Jul. 2, 2021, titled “Controller for Controlling Generation of Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production,” now U.S. Pat. No. 11,280,322, issued Mar. 22, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entireties. U.S. Non-Provisional application Ser. No. 17/657,015 further still is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/670,827, filed Feb. 14, 2022, titled “Systems and Methods for Generation of Electrical Power in an Organic Rankine Cycle Operation,” now U.S. Pat. No. 11,421,663, issued Aug. 23, 2022, which is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/305,296, filed Jul. 2, 2021, titled “Controller for Controlling Generation of Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production,” now U.S. Pat. No. 11,255,315, issued Feb. 22, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in

their entireties. U.S. Non-Provisional application Ser. No. 17/657,015 yet further is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/682,126, filed Feb. 28, 2022, titled “Systems and Methods for Generation of Electrical Power in an Organic Rankine Cycle Operation,” now U.S. Pat. No. 11,359,612, issued Jun. 14, 2022, which is a continuation of U.S. Non-Provisional application Ser. No. 17/494,936, filed Oct. 6, 2021, titled “Systems and Methods for Generation of Electrical Power in an Organic Rankine Cycle Operation,” now U.S. Pat. No. 11,293,414, issued Apr. 5, 2022, which is a continuation-in-part of U.S. Non-Provisional application Ser. No. 17/305,296, filed Jul. 2, 2021, titled “Controller for Controlling Generation of Geothermal Power in an Organic Rankine Cycle Operation During Hydrocarbon Production,” now U.S. Pat. No. 11,255,315, issued Feb. 22, 2022, which claims priority to and the benefit of U.S. Provisional Application No. 63/200,908, filed Apr. 2, 2021, titled “Systems and Methods for Generating Geothermal Power During Hydrocarbon Production,” the disclosures of all of which are incorporated herein by reference in their entireties.

In the drawings and specification, several embodiments of systems and methods to provide electrical power from heat of a flow of gas and/or other source have been disclosed, and although specific terms are employed, the terms are used in a descriptive sense only and not for purposes of limitation. Embodiments of systems and methods have been described in considerable detail with specific reference to the illustrated embodiments. However, it will be apparent that various modifications and changes can be made within the spirit and scope of the embodiments of systems and methods as described in the foregoing specification, and such modifications and changes are to be considered equivalents and part of this disclosure.

What is claimed is:

1. A method for increasing performance of one or more of engine, generator set, or bottom-hole assembly, the method comprising:

sensing a temperature of a flow of drilling fluid from a borehole;
determining electrical power utilized by drilling rig equipment and generated by a generator set driven by an engine; and

in response to one or more of (a) a determination that the temperature of the flow of drilling fluid from the borehole exceeds an operating range, (b) a determination that ambient temperature exceeds an ambient temperature threshold of a drilling rig, (c) a determination that the electrical power utilized by the drilling rig equipment exceeds a power requirement threshold, or (d) a determination that ambient temperature exceeds an engine operating range:

adjusting one or more of (1) a first working fluid flow control device to control a flow of working fluid to a drilling fluid heat exchanger, the drilling fluid heat exchanger configured to transfer heat from the drilling fluid to the flow of the working fluid, thereby to cause a power generation unit to generate electrical power, (2) a second working fluid flow control device to control a flow of working fluid to an exhaust heat exchanger, the exhaust fluid heat exchanger configured to transfer heat from exhaust generated by the engine to the flow of the working fluid, thereby to cause a power generation unit to generate electrical power, or (3) a third working fluid flow control device to control a flow of working fluid to a fluid jacket heat exchanger, the fluid jacket fluid

41

heat exchanger configured to transfer heat from the fluid of the fluid jacket to the flow of the working fluid, thereby to cause a power generation unit to generate electrical power.

2. The method of claim 1, wherein adjustment of the first working fluid flow control device to cause an increase in working fluid flow to the drilling fluid heat exchanger causes a decrease in the temperature of drilling fluid.

3. The method of claim 2, wherein the power generation unit comprises an Organic Rankine Cycle (ORC) unit, and wherein adjustment of the second working fluid flow control device to cause an increase in working fluid flow to the exhaust heat exchanger causes an increase in overall electrical power generated by the ORC unit due to the high heat of the exhaust.

4. The method of claim 1, wherein the fluid jacket comprises a water jacket, wherein the fluid jacket heat exchanger comprises a water jacket heat exchanger, and wherein adjustment of the third working fluid flow control device to cause an increase in working fluid flow to the water jacket heat exchanger causes an increase in engine performance.

5. A method for generating power in the vicinity of a drilling rig, the method comprising:

operating a drilling rig to form a borehole in a subsurface formation;

during operation of the drilling rig, selecting one or more fluids from one or more corresponding heat sources based on ambient temperature of the drilling rig, the one or more fluids selected to flow to one or more corresponding heat exchangers, each of the one or more corresponding heat exchangers positioned to transfer heat from one or more corresponding fluids to a flow of a working fluid to generate a heated working fluid, thereby to cause a power generation unit to generate electrical power; and

in response to a determination that ambient temperature of a drilling rig exceeds an engine operating range, adjusting an amount of flow of the one or more fluids to the one or more corresponding heat exchangers.

6. The method of claim 5, wherein the one or more heat sources includes exhaust produced by one of one or more engines positioned in the vicinity of the drilling rig or fluid from a fluid jacket corresponding to one or more engines.

7. The method of claim 5, wherein the one or more heat sources include drilling fluid utilized during operation of the drilling rig, and wherein one or more of the one or more heat sources are selected based on temperature of fluid from each of the one or more heat sources.

8. The method of claim 5, wherein one or more of the one or more heat sources is selected based on one or more of engine optimization, electrical power output maximization, or electrical power utilization at the drilling rig.

9. The method of claim 5, further comprising: supplying, via the power generation unit, generated electrical power to one or more of battery banks, other energy storage devices, a grid, a mud chiller, field equipment, or other equipment.

10. The method of claim 5, wherein one or more fluids from the one or more corresponding heat sources is selected based on whether one or more of a flow rate or temperature of each of the one or more fluids from one or more corresponding heat sources is sufficient to facilitate heat transfer to the working fluid to cause the power generation unit to generate electrical power.

11. The method of claim 5, further comprising: based on the one or more fluids selected, adjusting a position of one or more corresponding heat exchanger valves, the one or

42

more corresponding heat exchanger valves configured to divert, based on adjusted position, an amount of the one or more fluids selected to the one or more corresponding heat exchangers.

12. The method of claim 11, wherein the one or more corresponding heat exchanger valves is controlled by one or more of (1) a controller via signals to indicate adjustment position of each of the one or more corresponding heat exchanger valves or (2) a user located at a drilling rig.

13. A method for generating power in the vicinity of a drilling rig, the method comprising:

sensing a temperature of engine exhaust;

sensing a temperature of a flow of fluid from an engine fluid jacket;

sensing a temperature of a working fluid flowing from each of one or more corresponding heat exchangers; and

selecting, based on one or more of (a) engine optimization, (b) electrical power output maximization, (c) electrical power utilization at the drilling rig (d) the temperature of the engine exhaust, (e) the temperature of the flow of fluid from the engine fluid jacket, or (f) the temperature of the working fluid flowing from each of the one or more corresponding heat exchangers, diversion of an amount of one or more of (1) the engine exhaust, via a first heat exchanger supply valve, from an engine exhaust conduit to a first heat exchanger or (2) fluid, via a second heat exchanger supply valve, from the engine fluid jacket to a second heat exchanger, each of the first heat exchanger and the second heat exchanger positioned to transfer heat from the engine exhaust and fluid to the flow of the working fluid to generate a heated working fluid, thereby to cause a power generation unit to generate electrical power.

14. The method of claim 13, wherein selection of diversion of the amount of one or more engine exhaust and fluid further is based on one or more of ambient temperature at the drilling rig, temperature of the engine exhaust, temperature of the fluid, temperature of working fluid corresponding to the engine exhaust, or temperature of working fluid corresponding to the fluid.

15. A method for increasing performance of one or more of engine, generator set, or bottom-hole assembly, the method comprising:

determining electrical power utilized by drilling rig equipment and generated by a generator set driven by an engine; and

in response to one or more of (a) ambient temperature in the vicinity of a drilling rig exceeding an ambient temperature threshold or (b) the electrical power utilized by the drilling rig equipment exceeding a power requirement threshold:

adjusting one or more of (1) a first working fluid flow control device to control a flow of working fluid to an exhaust heat exchanger, the exhaust fluid heat exchanger configured to transfer heat from exhaust generated by the engine to the flow of the working fluid, thereby to generate electrical power, or (2) a second working fluid flow control device to control a flow of working fluid to a fluid jacket heat exchanger, the fluid jacket fluid heat exchanger configured to transfer heat from the fluid of the fluid jacket to the flow of the working fluid, the fluid jacket configured to cool the one or more engines, the transferred heat to cause a power generation unit to generate electrical power.

16. The method of claim 15, wherein the drilling rig equipment includes a mud chiller, wherein adjustment of the

first working fluid flow control device to cause an increase
in working fluid flow to the drilling fluid heat exchanger
causes a decrease in the temperature in drilling fluid, thereby
to decrease electrical power utilization of the mud chiller,
wherein the power generation unit comprises an Organic 5
Rankine Cycle (ORC) unit, wherein adjustment of the first
working fluid flow control device causes an increase in
working fluid flow to the exhaust heat exchanger, thereby to
increase overall electrical power generated by the ORC unit
due to the high heat of the exhaust, wherein the fluid jacket 10
comprises a water jacket, wherein the fluid jacket heat
exchanger comprises a water jacket heat exchanger, and
wherein adjustment of the second working fluid flow control
device causes an increase in engine performance.

* * * * *