

US012128697B2

(12) **United States Patent**  
**Noda**

(10) **Patent No.:** **US 12,128,697 B2**  
(45) **Date of Patent:** **\*Oct. 29, 2024**

(54) **TAPE CASSETTE**

(71) Applicant: **BROTHER KOGYO KABUSHIKI KAISHA**, Nagoya (JP)

(72) Inventor: **Kengo Noda**, Inazawa (JP)

(73) Assignee: **BROTHER KOGYO KABUSHIKI KAISHA**, Nagoya (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 364 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/464,761**

(22) Filed: **Sep. 2, 2021**

(65) **Prior Publication Data**

US 2022/0055388 A1 Feb. 24, 2022

**Related U.S. Application Data**

(63) Continuation of application No. 16/293,984, filed on Mar. 6, 2019, now Pat. No. 11,135,862, which is a continuation of application No. 14/742,077, filed on Jun. 17, 2015, now Pat. No. 10,265,982, which is a continuation of application No. 13/430,033, filed on Mar. 26, 2012, now Pat. No. 9,656,495, which is a  
(Continued)

(51) **Int. Cl.**

**B41J 15/04** (2006.01)

**B41J 3/407** (2006.01)

**B41J 32/00** (2006.01)

(52) **U.S. Cl.**

CPC ..... **B41J 32/00** (2013.01); **B41J 3/4075** (2013.01); **B41J 15/044** (2013.01)

(58) **Field of Classification Search**

CPC ..... B41J 32/00; B41J 3/4075; B41J 15/044  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,901,372 A 8/1975 Denley  
4,127,883 A 11/1978 Mestdagh  
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2003294971 A1 7/2004  
CA 2108332 A1 4/1994  
(Continued)

OTHER PUBLICATIONS

Nov. 27, 2017—(US) Notice of Allowance—U.S. Appl. No. 15/276,474.  
(Continued)


*Primary Examiner* — Yaovi M Ameh

(74) *Attorney, Agent, or Firm* — KENEALY VAIDYA LLP

(57) **ABSTRACT**

A cassette case includes a bottom case and a top case. A tape is housed in the cassette case. A tape discharge portion discharges, from the cassette case, the tape that has been guided in the cassette case along a predetermined feed path. A first indicator portion indicates a type of the tape. A second indicator portion indicates a type of the tape, which is different from that indicated by the first indicator portion. An indicator member is a member independent from the top case and the bottom case, and is provided with the second indicator portion. An attachment portion is provided on the cassette case. The indicator member is removably attached to the attachment portion.

**20 Claims, 24 Drawing Sheets**



**Related U.S. Application Data**

continuation-in-part of application No. PCT/JP2009/  
071812, filed on Dec. 28, 2009.

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

4,226,547 A	10/1980	Bradshaw et al.	5,533,818 A	7/1996	Bahrabadi
4,360,278 A	11/1982	Paque	5,536,092 A	7/1996	Yamaguchi
D267,330 S	12/1982	Worrell	5,538,352 A	7/1996	Sugiura
4,391,539 A	7/1983	Connoy	5,540,510 A	7/1996	Sims et al.
4,402,619 A	9/1983	Paque et al.	5,541,796 A	7/1996	Sawada
4,557,617 A	12/1985	Richardson et al.	5,553,952 A	9/1996	Umbach
4,567,488 A	1/1986	Moriguchi et al.	5,564,843 A	10/1996	Kawaguchi
4,678,353 A	7/1987	Richardson et al.	5,593,237 A	1/1997	Nozaki et al.
4,725,155 A	2/1988	Kittel et al.	5,595,447 A	1/1997	Takayama et al.
4,773,775 A	9/1988	Bradshaw et al.	5,599,119 A	2/1997	Nunokawa et al.
4,815,871 A	3/1989	McGourty et al.	5,605,404 A	2/1997	Nunokawa et al.
4,815,874 A	3/1989	Richardson et al.	5,620,268 A	4/1997	Yamaguchi et al.
4,815,875 A	3/1989	Richardson et al.	5,634,728 A	6/1997	Nunokawa et al.
4,832,514 A	5/1989	Basile	5,653,542 A	8/1997	Sugimoto et al.
4,844,636 A	7/1989	Paque	5,658,083 A	8/1997	Day et al.
4,880,325 A	11/1989	Ueda et al.	5,659,441 A	8/1997	Eckberg et al.
4,892,425 A	1/1990	Shimizu et al.	5,709,486 A	1/1998	Day
D307,296 S	4/1990	Ivarson et al.	5,727,888 A	3/1998	Sugimoto et al.
4,915,516 A	4/1990	Shimizu et al.	5,730,536 A	3/1998	Yamaguchi
4,917,514 A	4/1990	Richardson et al.	5,739,839 A	4/1998	Iwai et al.
D307,918 S	5/1990	Goda	5,752,777 A	5/1998	Nunokawa et al.
4,927,278 A	5/1990	Kuzuya et al.	5,755,519 A	5/1998	Klinefelter
4,930,913 A	6/1990	Basile	5,765,954 A	6/1998	Nunokawa et al.
D311,416 S	10/1990	Richardson et al.	5,771,803 A	6/1998	Takami
4,966,476 A	10/1990	Kuzuya et al.	5,788,387 A	8/1998	Takayama et al.
4,983,058 A	1/1991	Nagae	5,795,086 A	8/1998	Watanabe et al.
5,022,771 A	6/1991	Paque	5,813,773 A	9/1998	Kawai
D319,070 S	8/1991	Lavander	5,813,779 A	9/1998	Palmer et al.
D320,391 S	10/1991	Paque	5,823,689 A	10/1998	Nehowig et al.
5,056,940 A	10/1991	Basile	5,825,724 A	10/1998	Matsumoto et al.
5,078,523 A	1/1992	McGourty et al.	5,826,995 A	10/1998	Day et al.
5,098,208 A	3/1992	Martinez	5,857,788 A	1/1999	Gutsell et al.
5,104,247 A	4/1992	Ohshima	5,860,752 A	1/1999	Watanabe et al.
5,111,216 A	5/1992	Richardson et al.	5,887,993 A	3/1999	Nunokawa et al.
5,188,469 A	2/1993	Nagao et al.	5,961,225 A	10/1999	Nunokawa et al.
5,193,919 A	3/1993	Godo et al.	5,964,539 A	10/1999	Yamaguchi et al.
5,195,835 A	3/1993	Collins	5,967,678 A	10/1999	Nunokawa et al.
5,203,951 A	4/1993	Hattori et al.	5,997,194 A	12/1999	Nunokawa et al.
5,223,939 A	6/1993	Imaizumi et al.	6,012,860 A	1/2000	Nunokawa et al.
5,227,477 A	7/1993	Auerbach et al.	6,016,749 A	1/2000	Tukahara et al.
5,239,437 A	8/1993	Hoge et al.	6,042,280 A	3/2000	Yamaguchi et al.
D342,275 S	12/1993	Cooper	6,048,118 A	4/2000	Martinez et al.
5,273,272 A	12/1993	Nakamura et al.	6,050,672 A	4/2000	Matsubishi
RE34,521 E	1/1994	Shimizu et al.	6,050,734 A	4/2000	Watanabe et al.
5,277,503 A	1/1994	Nagao	6,059,469 A	5/2000	Hirumi
5,318,370 A	6/1994	Nehowig	6,106,171 A	8/2000	Nunokawa et al.
5,348,406 A	9/1994	Yoshiaki et al.	6,116,796 A	9/2000	Yamaguchi et al.
5,350,243 A	9/1994	Ichinomiya et al.	6,126,344 A	10/2000	Takayama et al.
D352,305 S	11/1994	Cooper	6,132,120 A	10/2000	Yamaguchi et al.
5,374,132 A	12/1994	Kimura	6,146,034 A	11/2000	Watanabe et al.
D356,333 S	3/1995	Pearce et al.	6,149,325 A	11/2000	Nunokawa et al.
5,395,173 A	3/1995	Ueno et al.	6,160,679 A	12/2000	Maekawa et al.
5,399,033 A	3/1995	Putman	6,167,696 B1	1/2001	Maaseidvaag et al.
D357,497 S	4/1995	Gray et al.	6,168,328 B1	1/2001	Ueda et al.
5,411,339 A	5/1995	Bahrabadi et al.	6,190,065 B1	2/2001	Brzuskiwicz
5,419,648 A	5/1995	Nagao et al.	6,190,067 B1	2/2001	Kobayashi et al.
D359,303 S	6/1995	Gray et al.	6,190,069 B1	2/2001	Yamaguchi et al.
5,424,757 A	6/1995	Thom	6,196,740 B1	3/2001	Yamaguchi et al.
5,429,443 A	7/1995	Kobayashi et al.	6,227,477 B1	5/2001	Komatsuzaki et al.
5,431,504 A	7/1995	Beadman et al.	6,232,993 B1	5/2001	Kobayashi et al.
5,435,657 A	7/1995	Pearce et al.	6,247,860 B1	6/2001	Yanagisawa
5,454,650 A	10/1995	Yamaguchi	6,270,269 B1	8/2001	Watanabe et al.
5,466,076 A	11/1995	Kobayashi et al.	6,317,156 B1	11/2001	Nagasaki et al.
5,492,282 A	2/1996	Okuchi et al.	6,334,724 B2	1/2002	Yamaguchi et al.
5,492,420 A	2/1996	Nunokawa et al.	6,366,425 B1	4/2002	Kletzl et al.
5,494,362 A	2/1996	Kobayashi et al.	6,386,774 B1	5/2002	Takayama et al.
5,506,736 A	4/1996	Ota	6,406,202 B1	6/2002	Unno et al.
5,511,891 A	4/1996	Nehowig et al.	6,419,648 B1	7/2002	Vitek et al.
5,518,328 A	5/1996	Okuchi et al.	6,429,443 B1	8/2002	Mankos et al.
D372,044 S	7/1996	Ware et al.	6,435,744 B1	8/2002	Dunn et al.
			6,476,838 B1	11/2002	Italiano
			6,485,206 B1	11/2002	Takahashi
			6,520,696 B2	2/2003	Huss et al.
			6,644,876 B2	11/2003	Carriere et al.
			D486,853 S	2/2004	Wilken et al.
			6,707,571 B1	3/2004	Kurashina
			6,709,179 B2	3/2004	Yamaguchi et al.
			6,910,819 B2	6/2005	Carriere et al.
			6,929,415 B2	8/2005	Wilken



(56)

References Cited

U.S. PATENT DOCUMENTS

6,955,318 B2 10/2005 Nonomura  
 D519,522 S 4/2006 Lee  
 7,070,347 B2 7/2006 Carriere et al.  
 7,070,348 B2 7/2006 Sugimoto et al.  
 7,097,372 B1 8/2006 Heyse et al.  
 7,121,751 B2 10/2006 Harada et al.  
 7,128,483 B2 10/2006 Harada et al.  
 D534,203 S 12/2006 Harada et al.  
 7,201,522 B2 4/2007 Bandholz et al.  
 D542,334 S 5/2007 Harada et al.  
 7,232,268 B2 6/2007 Sugimoto et al.  
 7,251,044 B1 7/2007 Kurashina  
 7,287,715 B2 10/2007 Ban  
 7,296,941 B2 11/2007 Suzuki et al.  
 7,357,585 B2 4/2008 Kurashina  
 7,404,684 B2 7/2008 Sugimoto et al.  
 D579,942 S 11/2008 Terry et al.  
 7,503,714 B2 3/2009 Yamamoto et al.  
 7,841,790 B2 11/2010 Yamaguchi et al.  
 7,942,594 B2 5/2011 Kumazaki et al.  
 7,965,308 B2 6/2011 Jauert et al.  
 8,045,288 B2 10/2011 Ota et al.  
 8,109,684 B2 2/2012 Yamaguchi  
 8,162,553 B2 4/2012 Vandermeulen  
 8,164,609 B2 4/2012 Liu et al.  
 8,382,389 B2 2/2013 Yamaguchi et al.  
 D681,727 S 5/2013 Van Den Broecke  
 8,529,142 B2 9/2013 Tanaka  
 8,540,444 B2 9/2013 Vandermeulen et al.  
 8,550,393 B2 10/2013 Tada  
 8,562,228 B2 10/2013 Yamaguchi et al.  
 8,641,304 B2 2/2014 Yamaguchi et al.  
 8,734,035 B2 5/2014 Suva et al.  
 8,740,482 B2 6/2014 Yamaguchi et al.  
 8,757,907 B2 6/2014 Yamaguchi et al.  
 8,764,326 B2 7/2014 Yamaguchi et al.  
 8,770,877 B2 7/2014 Yamaguchi et al.  
 9,498,998 B2 11/2016 Yamaguchi et al.  
 9,533,522 B2 1/2017 Yamaguchi et al.  
 9,566,808 B2 2/2017 Yamaguchi et al.  
 9,656,495 B2 5/2017 Noda  
 9,802,432 B2 10/2017 Yamaguchi et al.  
 9,855,768 B2 1/2018 Tanizaki  
 9,855,779 B2 1/2018 Yamaguchi et al.  
 10,265,982 B2 4/2019 Noda  
 10,315,442 B2 6/2019 Sato et al.  
 10,391,732 B2 8/2019 Tanaka  
 10,414,176 B2 9/2019 Kawai  
 10,625,527 B2 4/2020 Sato et al.  
 10,675,894 B2 6/2020 Yamaguchi et al.  
 11,052,685 B2 7/2021 Yamaguchi et al.  
 11,135,862 B2\* 10/2021 Noda ..... B41J 32/00  
 2002/0006303 A1 1/2002 Yamaguchi et al.  
 2002/0012558 A1\* 1/2002 Huss ..... B41J 15/04  
 400/191  
 2002/0047063 A1 4/2002 Kaneda et al.  
 2002/0085080 A1 7/2002 Kurashina  
 2002/0135938 A1 9/2002 Hiraguchi et al.  
 2003/0081978 A1 5/2003 Carriere et al.  
 2004/0056143 A1 3/2004 Nonomura  
 2004/0062586 A1 4/2004 Harada et al.  
 2004/0233269 A1 11/2004 Tsubota  
 2004/0265027 A1 12/2004 Hine et al.  
 2005/0036816 A1 2/2005 Carriere et al.  
 2005/0117881 A1 6/2005 Baba et al.  
 2005/0152732 A1 7/2005 Bandholz et al.  
 2005/0172981 A1 8/2005 Byun  
 2006/0008608 A1 1/2006 Kurashina  
 2006/0088802 A1 4/2006 Akaiwa  
 2006/0121229 A1 6/2006 Nagae  
 2006/0182921 A1\* 8/2006 Hioki ..... B41J 15/044  
 428/40.1  
 2006/0193669 A1 8/2006 Takada et al.  
 2006/0204304 A1 9/2006 Hioki et al.  
 2006/0216099 A1 9/2006 Sakano et al.

2006/0216100 A1 9/2006 Minoya et al.  
 2006/0233582 A1 10/2006 Horiuchi  
 2006/0238600 A1 10/2006 Vandermeulen et al.  
 2006/0239743 A1 10/2006 Naito  
 2007/0009302 A1 1/2007 Vandermeulen  
 2007/0009306 A1 1/2007 Harada et al.  
 2007/0031171 A1 2/2007 Heyse et al.  
 2007/0041772 A1 2/2007 Harada et al.  
 2007/0070168 A1 3/2007 Mindler et al.  
 2007/0098473 A1 5/2007 Heyse et al.  
 2007/0172293 A1 7/2007 Vandermeulen  
 2007/0212149 A1 9/2007 Ota et al.  
 2007/0212151 A1 9/2007 Innocenti et al.  
 2007/0231041 A1 10/2007 Ueda et al.  
 2007/0237562 A1 10/2007 Kato et al.  
 2007/0264070 A1 11/2007 Loo et al.  
 2007/0283249 A1 12/2007 Nose et al.  
 2008/0003043 A1 1/2008 Fukui et al.  
 2008/0029530 A1 2/2008 Yuyama et al.  
 2008/0050160 A1 2/2008 Yamaguchi et al.  
 2008/0056793 A1 3/2008 Yokoyama  
 2008/0080922 A1 4/2008 Vandermeulen  
 2008/0165009 A1 7/2008 Hirota  
 2008/0181703 A1 7/2008 Ito et al.  
 2008/0181708 A1 7/2008 Yamaguchi et al.  
 2008/0205958 A1 8/2008 Moriyama et al.  
 2008/0226373 A1 9/2008 Yamaguchi et al.  
 2008/0232886 A1 9/2008 Kato et al.  
 2008/0310904 A1 12/2008 Yamaguchi et al.  
 2009/0016795 A1 1/2009 Caveney et al.  
 2009/0085451 A1 4/2009 Yuyama et al.  
 2009/0190988 A1 7/2009 Vereecken et al.  
 2009/0202283 A1 8/2009 Kumazaki et al.  
 2009/0231607 A1 9/2009 Kurashina  
 2009/0285617 A1 11/2009 Vandermeulen  
 2010/0119280 A1 5/2010 Vandermeulen  
 2010/0119281 A1 5/2010 Ford et al.  
 2010/0166475 A1 7/2010 Yamaguchi et al.  
 2010/0166478 A1 7/2010 Yamaguchi et al.  
 2010/0166479 A1\* 7/2010 Yamaguchi ..... B41J 3/4075  
 400/613  
 2010/0232862 A1 9/2010 Vandermeulen  
 2010/0247208 A1 9/2010 Yamaguchi et al.  
 2010/0247209 A1 9/2010 Yamaguchi et al.  
 2010/0247210 A1 9/2010 Yamaguchi et al.  
 2010/0250233 A1 9/2010 Tanaka  
 2010/0272492 A1 10/2010 Van Britsom et al.  
 2011/0058884 A1 3/2011 Kato et al.  
 2012/0008999 A1 1/2012 Yamaguchi et al.  
 2012/0009001 A1 1/2012 Sago et al.  
 2012/0027485 A1 2/2012 Suva et al.  
 2012/0027486 A1 2/2012 Suva et al.  
 2012/0027487 A1 2/2012 Suva et al.  
 2012/0057917 A1 3/2012 Van Britsom et al.  
 2012/0080550 A1 4/2012 Yamaguchi et al.  
 2012/0170959 A1 7/2012 Vandermeulen et al.  
 2012/0175454 A1 7/2012 Noda  
 2012/0188325 A1 7/2012 Yamaguchi et al.  
 2012/0189366 A1 7/2012 Yamaguchi et al.  
 2012/0201588 A1 8/2012 Yamaguchi et al.  
 2014/0205350 A1 7/2014 Yamaguchi et al.  
 2014/0218458 A1 8/2014 Suva et al.  
 2015/0283837 A1 10/2015 Sakano  
 2017/0100948 A1 4/2017 Yamaguchi et al.  
 2018/0257400 A1 9/2018 Yamaguchi et al.

FOREIGN PATENT DOCUMENTS

CH 121073 6/1927  
 CH 136498 11/1929  
 CN 1063641 A 8/1992  
 CN 1119146 A 3/1996  
 CN 1143928 A 2/1997  
 CN 1146954 A 4/1997  
 CN 1148547 A 4/1997  
 CN 1148548 A 4/1997  
 CN 1166155 A 11/1997  
 CN 1209776 A 3/1999  
 CN 1289293 A 3/2001



(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

CN	1313197	A	9/2001	EP	1829696	A2	9/2007
CN	1313198	A	9/2001	EP	2059396	A1	5/2009
CN	1085151	C	5/2002	EP	2236303	A1	10/2010
CN	1376115	A	10/2002	EP	2236304	A1	10/2010
CN	1385312	A	12/2002	EP	2448762	B1	9/2013
CN	1385313	A	12/2002	IN	1331684	C	8/2007
CN	1385314	A	12/2002	JP	S56-20944	U	2/1981
CN	1397431	A	2/2003	JP	S58-139415	U	9/1983
CN	1415482	A	5/2003	JP	S58-220783	A	12/1983
CN	1415484	A	5/2003	JP	S59-78879	A	5/1984
CN	1415485	A	5/2003	JP	S60-99692	A	6/1985
CN	1469811	A	1/2004	JP	S61-179776	A	8/1986
CN	1493462	A	5/2004	JP	S62-173944	U	11/1987
CN	1636755	A	7/2005	JP	S63-81063	U	5/1988
CN	1642746	A	7/2005	JP	S63-166557	A	7/1988
CN	1663807	A	9/2005	JP	S63-203348	A	8/1988
CN	1744993	A	3/2006	JP	S63-254085	A	10/1988
CN	1744994	A	3/2006	JP	H01-195088	A	8/1989
CN	1762720	A	4/2006	JP	H01-146945	U	10/1989
CN	1785685	A	6/2006	JP	H02-56664	U	4/1990
CN	1799850	A	7/2006	JP	H02-56665	U	4/1990
CN	1799851	A	7/2006	JP	H02-56666	U	4/1990
CN	1820940	A	8/2006	JP	H02-147272	A	6/1990
CN	1827386	A	9/2006	JP	H03-14865	A	1/1991
CN	1829607	A	9/2006	JP	H03-93584	A	4/1991
CN	1835867	A	9/2006	JP	H03-120680	A1	5/1991
CN	1865012	A	11/2006	JP	H03-151261	A	6/1991
CN	1914045	A	2/2007	JP	H03-63155	B2	9/1991
CN	1990261	A	7/2007	JP	H03-118672	U	12/1991
CN	101028771	A	9/2007	JP	H04-16113	U	2/1992
CN	101035683	A	9/2007	JP	H04-37575	A	2/1992
CN	101039807	A	9/2007	JP	H04-133756	A	5/1992
CN	101060985	A	10/2007	JP	H04-168086	A	6/1992
CN	101077664	A	11/2007	JP	H05-16342	U	3/1993
CN	101128324	A	2/2008	JP	H05-18853	U	3/1993
CN	201030694	Y	3/2008	JP	H05-63067	A	3/1993
CN	101229724	A	7/2008	JP	H05-104840	A	4/1993
CN	101264701	A	9/2008	JP	H05-155067	A	6/1993
CN	101264702	A	9/2008	JP	5-51662	U	7/1993
CN	101310989	A	11/2008	JP	H05-54225	U	7/1993
CN	101327696	A	12/2008	JP	H05-78565	U	10/1993
CN	101356061	A	1/2009	JP	H05-80765	U	11/1993
CN	101516628	A	8/2009	JP	H05-294051	A	11/1993
CN	101758676	A	6/2010	JP	H05-301435	A	11/1993
CN	102616025	A	8/2012	JP	H06-12053	U	2/1994
CN	202895934	U	4/2013	JP	H06-52560	A	2/1994
EP	214466	A2	3/1987	JP	H06-21953	U	3/1994
EP	0329369	A2	8/1989	JP	H06-122239	A	5/1994
EP	0511602	A1	11/1992	JP	H06-122249	A	5/1994
EP	0593269	A2	4/1994	JP	H06-124406	A	5/1994
EP	0629509	A2	12/1994	JP	H06-127094	A	5/1994
EP	0635375	A2	1/1995	JP	H06-152907	A	5/1994
EP	0644506	A2	3/1995	JP	H06143761	A	5/1994
EP	0684143	A2	11/1995	JP	H06-53560	U	7/1994
EP	0703089	A1	3/1996	JP	H06-191081	A	7/1994
EP	734878	A2	10/1996	JP	H06183117	A	7/1994
EP	0742103	A1	11/1996	JP	H06-210889	A	8/1994
EP	0555954	B1	3/1997	JP	H06-255145	A	9/1994
EP	0760291	A2	3/1997	JP	H06-74348	U	10/1994
EP	0863021	B1	9/1998	JP	H06-328800	A	11/1994
EP	0644506	B1	4/1999	JP	H07-1782		1/1995
EP	0936076	A2	8/1999	JP	H07-1805	A	1/1995
EP	0940263	A2	9/1999	JP	H07-9743	A	1/1995
EP	0958931	A2	11/1999	JP	H07-25122	A	1/1995
EP	0997300	A2	5/2000	JP	H07-25123	A	1/1995
EP	1167049	A1	1/2002	JP	H07-47737	A	2/1995
EP	1170139	A1	1/2002	JP	H07-20725	B2	3/1995
EP	1199179	A1	4/2002	JP	H07-61009	A	3/1995
EP	1284196	A2	2/2003	JP	H07-68814	A	3/1995
EP	1502758	A1	2/2005	JP	H07-68877	A	3/1995
EP	1516739	A1	3/2005	JP	H07-69497	A	3/1995
EP	1552949	A1	7/2005	JP	H07-89115	A	4/1995
EP	1575781	A1	9/2005	JP	H07-89196	A	4/1995
EP	1700705	A1	9/2006	JP	H07-101133	A	4/1995
EP	1707395	A1	10/2006	JP	H07-108702	A	4/1995
				JP	H07-108730	A	4/1995
				JP	H07-108730	A	4/1995
				JP	H07-137327	A	5/1995
				JP	H07-164680	A	6/1995
				JP	H07-40456	U	7/1995

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

JP	H07-214876	A	8/1995	JP	2002166605	A	6/2002
JP	H07-237314	A	9/1995	JP	2002179300	A	6/2002
JP	H07-251539	A	10/1995	JP	2002192769	A	7/2002
JP	H07-276695	A	10/1995	JP	2002308481	A	10/2002
JP	H07-290803	A	11/1995	JP	2002308518	A	10/2002
JP	H07-314862	A	12/1995	JP	3357128	B2	12/2002
JP	H07-314864	A	12/1995	JP	2002367333	A	12/2002
JP	H07-314865	A	12/1995	JP	2003-011454	A	1/2003
JP	H07-314866	A	12/1995	JP	2003-026164	A	1/2003
JP	H08-25768	A	1/1996	JP	2003-506235	A	2/2003
JP	H08-39909	A	2/1996	JP	3378622	B2	2/2003
JP	H08-058211	A	3/1996	JP	2003048337	A	2/2003
JP	H08-90887		4/1996	JP	2003-072127	A	3/2003
JP	H08-118738	A	5/1996	JP	2003145902	A	5/2003
JP	H08-165035	A	6/1996	JP	3426983	B2	7/2003
JP	H08-216461	A	8/1996	JP	2003-251904	A	9/2003
JP	H08-252964	A	10/1996	JP	2003251902	A	9/2003
JP	H08-267839	A	10/1996	JP	2003285522	A	10/2003
JP	H08-290618	A	11/1996	JP	2004-018077	A	1/2004
JP	H08-290681	A	11/1996	JP	2004-155150	A	6/2004
JP	H09-39347		2/1997	JP	3543659	B2	7/2004
JP	9-76614	A	3/1997	JP	2004-255656	A	9/2004
JP	H09-85928	A	3/1997	JP	3564848	B2	9/2004
JP	2596263	B2	4/1997	JP	3567469	B2	9/2004
JP	H09-109533	A	4/1997	JP	2004291591	A	10/2004
JP	H09-118044	A	5/1997	JP	2004323241	A	11/2004
JP	H09-123579	A	5/1997	JP	3106187	U	12/2004
JP	H09-134557	A	5/1997	JP	2005-059504	A	3/2005
JP	H09-141986	A	6/1997	JP	2005088597	A	4/2005
JP	H09-141997	A	6/1997	JP	2005-178206	A	7/2005
JP	H09-188049	A	7/1997	JP	2005231203	A	9/2005
JP	H09-188050	A	7/1997	JP	2005-298031	A	10/2005
JP	H09-240158	A	9/1997	JP	2005280008	A	10/2005
JP	9-277673	A	10/1997	JP	2005297348	A	10/2005
JP	H10-56604	A	2/1998	JP	2006021432	A	1/2006
JP	H10-181063	A	7/1998	JP	2006-512224	A	4/2006
JP	H10-301701	A	11/1998	JP	2006096030	A	4/2006
JP	H11-78188	A	3/1999	JP	2006142835	A	6/2006
JP	H11-78189	A	3/1999	JP	2006168974	A	6/2006
JP	H11-91144	A	4/1999	JP	2006182034	A	7/2006
JP	H11-105351	A	4/1999	JP	2006224675	A	8/2006
JP	H11-129563	A	5/1999	JP	2006-240310	A	9/2006
JP	H11-263055	A	9/1999	JP	2006248059	A	9/2006
JP	H11-263056	A	9/1999	JP	2006-264337	A	10/2006
JP	2000-006481	A	1/2000	JP	2006272895	A	10/2006
JP	2000-006501	A	1/2000	JP	2006272977	A	10/2006
JP	2000-025316	A	1/2000	JP	2006289991	A	10/2006
JP	2998617	B2	1/2000	JP	2007070028	A	3/2007
JP	2000025251	A	1/2000	JP	2007111863	A	5/2007
JP	2000-043337	A	2/2000	JP	2007196654	A	8/2007
JP	2000043336	A	2/2000	JP	2007-230155		9/2007
JP	2000-076372	A	3/2000	JP	2007-268815	A	10/2007
JP	2000085224	A	3/2000	JP	4003068	B2	11/2007
JP	3031439	B2	4/2000	JP	2007296863	A	11/2007
JP	2000103129	A	4/2000	JP	2007313681	A	12/2007
JP	2000103131	A	4/2000	JP	2008044180	A	2/2008
JP	2000135843	A	5/2000	JP	4061507	B2	3/2008
JP	2000198258	A	7/2000	JP	2008062474		3/2008
JP	2000-211193	A	8/2000	JP	2008080668	A	4/2008
JP	2000-229750	A	8/2000	JP	2008083432	A	4/2008
JP	2001011594	A	1/2001	JP	2008094103	A	4/2008
JP	2001048389	A	2/2001	JP	2008509823	A	4/2008
JP	2001088359	A	4/2001	JP	2008-213462	A	9/2008
JP	2001121797	A	5/2001	JP	2008-229855	A	10/2008
JP	3207860	B2	9/2001	JP	2008254384	A	10/2008
JP	2001310540	A	11/2001	JP	2008-279678	A	11/2008
JP	2001319447	A	11/2001	JP	2008265180	A	11/2008
JP	2002-053248	A	2/2002	JP	2008265278	A	11/2008
JP	2002042441	A	2/2002	JP	2008-307703	A	12/2008
JP	3266736	B2	3/2002	JP	2009001020	A	1/2009
JP	3266739	B2	3/2002	JP	2009028976	A	2/2009
JP	2002-103762	A	4/2002	JP	2009509812	A	3/2009
JP	2002104568	A	4/2002	JP	2009184832	A	8/2009
JP	2002-166606	A	6/2002	JP	2009-214431	A	9/2009
JP	2002-167084	A	6/2002	JP	2009-215083		9/2009
				JP	2010-234697	A	10/2010
				JP	2011-011407	A	1/2011
				JP	2011011401	A	1/2011
				JP	2011110843	A	6/2011



(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

JP	2011110845	A	6/2011
JP	2011110848	A	6/2011
KR	2007-0091073	A	9/2007
RU	2297333	C2	4/2007
TW	200827179	A	7/2008
WO	96/16812	A1	6/1996
WO	2000032401	A1	6/2000
WO	0110649	A1	2/2001
WO	0232680	A1	4/2002
WO	03080350	A1	10/2003
WO	2004/058509	A1	7/2004
WO	2005101306	A1	10/2005
WO	2005/120844	A1	12/2005
WO	20060013466	A2	2/2006
WO	2006024913	A2	3/2006
WO	2006033431	A1	3/2006
WO	2006033432	A1	3/2006
WO	2006090842	A1	8/2006
WO	2008/029931	A1	3/2008
WO	2009107534	A1	9/2009
WO	2010-113782	A1	10/2010
WO	2010113445	A1	10/2010

## OTHER PUBLICATIONS

Jan. 8, 2018—(US) Non-Final Office Action—U.S. Appl. No. 15/226,188.

Sep. 12, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,386.

Sep. 22, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/141,673.

Sep. 24, 2014—(JP) Notification of Rejection—App 2013-142488—Eng Tran.

Sep. 24, 2014—(US) Notice of Allowance—U.S. Appl. No. 13/431,277.

Sep. 25, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,424.

Jan. 3, 2014 (AU) Office Action issued in Australian Patent Application No. 2010231426.

Jan. 17, 2014 (CN) Office Action issued in Chinese Patent Application No. 201210071810.7.

Jan. 22, 2014 (CN) Office Action issued in Chinese Patent Application No. 201010274378.2.

Feb. 5, 2014 (EP) Extended European Search Report issued in European Patent Application No. 09852818.5.

Mar. 10, 2014 (US) Non-Final Office Action issued in U.S. Appl. No. 13/430,080.

Mar. 13, 2014 (CN) Office Action issued in Chinese Application No. 201010150928.

Mar. 25, 2014 (US) Non-Final Office Action issued in U.S. Appl. No. 13/431,371.

Mar. 26, 2014 (US) Final Office Action issued in U.S. Appl. No. 12/732,457.

Mar. 27, 2014 (US) Notice of Allowance issued in U.S. Appl. No. 13/240,266.

Apr. 1, 2014 (JP) Office Action issued in Japanese Patent Application No. 2013-035990.

Apr. 2, 2014 (CN) Office Action issued in Chinese Patent Application No. 201210070968.

Apr. 10, 2014 (CN) Office Action issued in Chinese Application No. 201010150109.

Apr. 11, 2014 (US) Notice of Allowance issued in U.S. Appl. No. 12/644,572.

Apr. 15, 2014 (AU) Office Action issued in Australian Patent Application No. 2009332345.

Apr. 17, 2014 (RU) Office Action issued in Russian Patent Application No. 2011143817.

Apr. 25, 2014 (MX) Mexican Office Action issued in Mexican Application No. MX/a/2011/013553.

May 6, 2014 (CN) Chinese Office Action issued in Chinese Application No. 201010150878.5.

May 6, 2014 (CN) Chinese Office Action issued in Chinese Application No. 201010150087.2.

May 6, 2014 (US) Notice of Allowance issued in U.S. Appl. No. 13/934,512.

May 7, 2014 (US) Final Office Action issued in U.S. Appl. No. 13/240,216.

May 9, 2014 (VN) Office Action issued in Vietnamese Patent Application No. 1-2011-02491.

May 13, 2014 (CN) Chinese Office Action issued in Chinese Application No. 201080013339.5.

May 21, 2014 (EP) Extended European Search Report issued in European Application No. 10758552.3.

May 22, 2014 (US) Non-Final Office Action issued in U.S. Appl. No. 14/226,256.

Jun. 2, 2014 (AU) Office action issued in Australian Patent Application No. 2010231425.

Jun. 6, 2014 (US) Restriction Requirement issued in corresponding U.S. Appl. No. 13/430,033.

Jun. 10, 2014 (JP) Japanese Office Action issued Japanese Application No. 2013-142488.

Jun. 20, 2014 (CN) Office action issued in Chinese Patent Application No. 201210070147.

Jun. 24, 2014 (JP) Japanese Office Action issued Japanese Application No. 2013-153250.

Jun. 24, 2014 (JP) Japanese Office Action issued Japanese Application No. 2013-153340.

Jun. 27, 2014 (AU) Office Action issued in Australian Patent Application No. 2010231426.

Jul. 7, 2014 (US) Final Office Action issued in U.S. Appl. No. 13/430,080.

Jul. 8, 2014 (CA) Office Action issued in Canadian Patent Application No. 2,755,882.

Jul. 8, 2014 (JP) Office Action issued in Japanese Patent Application No. 2013-153421.

Jul. 8, 2014 (JP) Office Action issued in Japanese Patent Application No. 2013-153495.

Jul. 18, 2014 (US) Office Action in U.S. Appl. No. 13/431,350.

Jul. 16, 2013 (US) Office Action in U.S. Appl. No. 12/817,556.

Dec. 16, 2014—(US) Notice of Allowance—U.S. Appl. No. 13/240,216.

Dec. 16, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,259.

Jan. 2, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,262.

Jan. 5, 2015—(US) Non-final Office Action—U.S. Appl. No. 14/226,201.

Jan. 22, 2015—(US) Notice of Allowance—U.S. Appl. No. 12/732,457.

Jan. 16, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,402.

Jan. 20, 2015—(US) Non-Final Office Action—U.S. Appl. No. 13/431,371.

Jan. 28, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/431,277.

Aug. 13, 2015—(US) Final Office Action—U.S. Appl. No. 13/431,371.

Aug. 24, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,402.

Aug. 11, 2015—(AU) Patent Examination Report 1—App 2014221250.

Sep. 1, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,259.

Sep. 9, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,386.

Sep. 8, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/141,673.

Aug. 6, 2015—(CN) Office Action—App 201410046812.X—Eng Tran.

Sep. 8, 2015—(JP) Office Action—App 2014-210427—Eng Tran.

Sep. 22, 2013 (CN) Office Action issued in Chinese Patent Application No. 201010150109.5.

Sep. 25, 2013 (NZ) Office Action issued in New Zealand Patent Application No. 596044.

Sep. 26, 2013 (CN) Office Action issued in Chinese Patent Application No. 201010150090.4.

Sep. 30, 2013 (CN) Office Action issued in Chinese Patent Application No. 201010150088.7.

Oct. 1, 2013 (JP) Office Action issued in Japanese Patent Application No. 2011547222.

Oct. 16, 2013 (US) Non-Final Office Action issued in corresponding U.S. Appl. No. 13/240,266.



(56)

**References Cited**

## OTHER PUBLICATIONS

- Oct. 28, 2013 (CN) Office Action issued in Chinese Patent Application No. 200980158165.9.
- Nov. 1, 2013 (CN) Office Action Issued in Chinese Patent Application No. 200980161405.0.
- Nov. 6, 2013 (EP) European Search Report issued in European Patent Application No. 09842716.4.
- Nov. 8, 2013 (NZ) Office Action issued in New Zealand Patent Application No. 596044.
- Nov. 12, 2013 (EP) European Search Report issued in European Patent Application No. 10758310.6.
- Nov. 13, 2013 (US) Office Action issued in corresponding U.S. Appl. No. 13/240,216.
- Nov. 19, 2013 (US) Office Action issued in corresponding U.S. Appl. No. 13/934,512.
- Dec. 3, 2013 (JP) Office Action issued in Japanese Patent Application No. 2011-507049.
- Dec. 16, 2013 (EP) Extended European Search Report in European Patent Application No. 12160324.5.
- Dec. 18, 2013 (EP) Extended European Search Report in European Patent Application No. 12160192.6.
- Dec. 19, 2013 (CN) Office Action issued in Chinese Patent Application No. 200910262674.8.
- Dec. 20, 2013 (EP) Extended European Search Report issued in European Patent Application No. 12161271.7.
- Dec. 23, 2013 (US) Final Office Action issued in U.S. Appl. No. 13/431,350.
- Dec. 30, 2013 (CN) Office Action issued in Chinese Application No. 201010209208.6.
- Dec. 30, 2013 (CN) Office Action issued in Chinese Patent Application No. 201210070147.9.
- Aug. 12, 2014—(CN) Notice of Second Office Action—App 201210071810.7—Eng Tran.
- Aug. 26, 2014—(CN) Notice of Second Office Action—App 201010274378.2—Eng Tran.
- Aug. 28, 2014—(US) Non-Final Office Action—U.S. Appl. No. 13/240,216.
- Dec. 5, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,325.
- Dec. 1, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,289.
- Feb. 4, 2014 (US) Notice of Allowance issued in U.S. Appl. No. 12/732,404.
- Feb. 19, 2014 (US) Notice of Allowance issued in U.S. Appl. No. 12/732,747.
- Feb. 24, 2014 (US) Notice of Allowance issued in U.S. Appl. No. 12/644,451.
- Jan. 27, 2014 (US) Notice of Allowance issued in U.S. Appl. No. 12/732,828.
- Jul. 16, 2014 (US)—Restriction requirement in U.S. Appl. No. 13/848,750.
- Jul. 22, 2014 (US) Office Action in U.S. Appl. No. 12/732,257.
- Jul. 25, 2014—(CN) Notice of Second Office Action—App 201010150090.4—Eng Tran.
- Jul. 28, 2014—(CN) Notice of Second Office Action—App 201010150088.7—Eng Tran.
- Jun. 26, 2014—(CN) Office Action—App 200980161405.
- Nov. 4, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,367.
- Nov. 4, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,428.
- Nov. 5, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,373.
- Nov. 25, 2014—(US) Notice of Allowance—U.S. Appl. No. 13/934,512.
- Oct. 2, 2014—(US) Non-Final Office Action—U.S. Appl. No. 13/430,033.
- Oct. 10, 2014—(US) Notice of Allowance—U.S. Appl. No. 12/732,457.
- Oct. 27, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/141,576.
- Oct. 30, 2014 (US) Final Office Action App—U.S. Appl. No. 14/226,256.
- Sep. 2, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,165.
- Sep. 9, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,380.
- Sep. 9, 2014—(US) Non-Final Office Action—U.S. Appl. No. 14/226,417.
- Sep. 10, 2014—(US) Notice of Allowance—U.S. Appl. No. 13/934,512.
- Sep. 11, 2014—(US) Election Requirement—U.S. Appl. No. 13/240,322.
- Sep. 11, 2014—(US) Non-Final Office Action—U.S. Appl. No. 13/848,750.
- Sep. 12, 2014—(US) Final Office Action—U.S. Appl. No. 13/431,371. Office Action dated Sep. 22, 2023 received in related U.S. Appl. No. 17/538,254.
- Notice of Allowance dated Sep. 23, 2021, which issued in a related application, namely, U.S. Appl. No. 16/296,132, filed Feb. 5, 2020. Office Action dated Oct. 21, 2021, which issued in related application, namely, U.S. Appl. No. 16/924,874, filed Jul. 9, 2020. Office Action dated Oct. 26, 2022 received in related U.S. Appl. No. 17/538,254.
- Notice of Allowance dated Oct. 26, 2022 received in related U.S. Appl. No. 17/339,374.
- Office Action dated Nov. 9, 2022 received in related U.S. Appl. No. 17/677,455.
- Official Action dated Mar. 24, 2022 in a related application, namely, U.S. Appl. No. 17/339,374, filed Jun. 4, 2021.
- Supplemental List of Patents or Patent Applications Treated as Related dated Sep. 28, 2022.
- Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156357.
- Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156371.
- Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156398.
- Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156403.
- Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-270325.
- Apr. 8, 2013 (EP) European Search Report issued in European Patent Application No. 09852278.2.
- Apr. 15, 2013 (CN) Office Action issued in Chinese Patent Application No. 201080013099.9.
- Apr. 19, 2013 (CN) Office Action issued in Chinese Patent Application No. 200910262678.6.
- Apr. 23, 2013 (JP) Office Action issued in Japanese Patent Application No. 2010-73748.
- Apr. 23, 2013 (JP) Office Action issued in Japanese Patent Application No. 2010-73750.
- Apr. 23, 2013 (US) Office Action in U.S. Appl. No. 13/430,080.
- Apr. 26, 2013 (CN) Office Action issued in Chinese Patent Application No. 200910262676.7.
- Apr. 26, 2013 (US) Office Action in U.S. Appl. No. 13/755,174.
- May 2, 2013 (CN) Office Action issued in Chinese Patent Application No. 200910262677.1.
- May 2, 2013 (CN) Office Action issued in Chinese Patent Application No. 200910262679.0.
- May 2, 2013 (CN) Office Action issued in Chinese Patent Application No. 200910262680.3.
- May 7, 2013 (US) Office Action in U.S. Appl. No. 12/732,404.
- May 14, 2013 (JP) Office Action issued in Japanese Patent Application No. 2010-073747.
- May 14, 2013 (US) Office Action in U.S. Appl. No. 13/431,350.
- May 14, 2013 (US) Office Action in U.S. Appl. No. 13/431,371.
- May 21, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-154698.
- May 21, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-154699.
- May 21, 2013 (JP) Office Action issued in Japanese Patent Application No. 2010-073749.
- May 21, 2013 (JP) Office Action issued in Japanese Patent Application No. 2010-073755.



(56)

**References Cited**

## OTHER PUBLICATIONS

- May 21, 2013 (US) Office Action in U.S. Appl. No. 12/732,257.  
 May 21, 2013 (US) Office Action in U.S. Appl. No. 12/732,828.  
 May 22, 2013 (US) Office Action in U.S. Appl. No. 12/644,413.  
 May 22, 2013 (US) Office Action in U.S. Appl. No. 12/873,633.  
 May 28, 2013 (JP) Office Action issued in Japanese Patent Application No. 2010-073751.  
 May 30, 2013 (US) Office Action in U.S. Appl. No. 12/732,247.  
 Jun. 4, 2013 (CN) Office Action issued in Chinese Patent Application No. 200980161443.6.  
 Jun. 4, 2013 (JP) Office Action issued in Japanese Patent Application No. 2010-073754.  
 Jun. 19, 2013 (US) Office Action in U.S. Appl. No. 12/644,373.  
 Jul. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156281.  
 Jul. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156350.  
 Jul. 10, 2013 (NZ) (Office Action issued in New Zealand Patent Application No. 596044.  
 Jul. 16, 2013 (US) Office Action issued in U.S. Appl. No. 12/817,556.  
 Aug. 1, 2013 (US) Office Action in U.S. Appl. No. 12/732,747.  
 Aug. 7, 2013 (CN) Office Action issued in Chinese Patent Application No. 200910262675.2.  
 Aug. 9, 2013 (US) Office Action in U.S. Appl. No. 13/431,350.  
 Aug. 22, 2013 (CN) Office Action issued in Chinese Patent Application No. 201080013339.5.  
 Aug. 27, 2013 (US) Office Action in U.S. Appl. No. 12/644,451.  
 Aug. 27, 2013 (US) Office Action in U.S. Appl. No. 12/644,572.  
 Sep. 3, 2013 (CN) Office Action issued in Chinese Patent Application No. 201010150928.X.  
 Sep. 3, 2013 (JP) Office Action issued in Japanese Patent Application No. 2011507143.  
 Sep. 9, 2013 (US) Office Action issued in U.S. Appl. No. 12/732,404.  
 Sep. 11, 2013 (US) Office Action in U.S. Appl. No. 13/430,080.  
 Sep. 12, 2013 (US) Office Action in U.S. Appl. No. 12/732,457.  
 Sep. 12, 2013 (US) Office Action in U.S. Appl. No. 12/732,828.  
 Sep. 17, 2013 (US) Office Action in U.S. Appl. No. 12/732,647.  
 Dec. 24, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,380.  
 Nov. 9, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/848,750.  
 Nov. 13, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,289.  
 Nov. 25, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,256.  
 Nov. 27, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,367.  
 Dec. 4, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,325.  
 Dec. 10, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/755,141.  
 Nov. 20, 2015—(KR) Office Action—App 10-2015-7006347.  
 Nov. 20, 2015—(KR) Office Action—App 10-2011-7017238.  
 Dec. 11, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,165.  
 Dec. 17, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/920,398.  
 Dec. 21, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/934,512.  
 Dec. 23, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,417.  
 Oct. 27, 2015—(CN) Office Action—App 201410195767.4.  
 Jul. 4, 2017—(CN) Office Action—App 201510714069.5 with English Translation.  
 Notice of Allowance dated Jun. 10, 2022 in a related application, namely, U.S. Appl. No. 16/924,874, filed Jul. 9, 2020.  
 Apr. 27, 2018—(US) Non-Final Office Action—U.S. Appl. No. 15/832,531.  
 Mar. 5, 2010 (PCT) International Search Report in International Application No. PCT/JP2009/007088.  
 Mar. 16, 2010 (PCT) International Search Report and Written Opinion issued in International Application No. PCT/JP2009/071812.  
 Mar. 16, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/050253.  
 Mar. 23, 2010 (PCT) International Search Report in International Application No. PCT/JP2009/070971.  
 Mar. 23, 2010 (PCT) International Search Report in International Application No. PCT/JP2009/071568.  
 May 20, 2010 (PCT) International Search Report in International Application No. PCT/JP2009/007085.  
 May 20, 2010 (PCT) International Search Report in International Application No. PCT/JP2009/007086.  
 May 20, 2010 (PCT) International Search Report in International Application No. PCT/JP2009/007087.  
 May 21, 2010 (PCT) International Search Report in International Application No. PCT/JP2009/007089.  
 May 21, 2010 Extended European Search Report in European Patent Application No. 09180351.  
 May 21, 2010 Extended European Search Report in European Patent Application No. 09180354.  
 Jun. 22, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/055305.  
 Jun. 22, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/055310.  
 Jun. 22, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/055311.  
 Jun. 22, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/055324.  
 Jun. 22, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/055326.  
 Jun. 28, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/002170.  
 Jul. 2, 2010 Extended European Search Report in European Patent Application No. 10157994.  
 Jul. 12, 2010 Extended European Search Report in European Patent Application No. 10158024.  
 Jul. 30, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/002165.  
 Jul. 30, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/002169.  
 Aug. 3, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/002154.  
 Aug. 3, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/002161.  
 Aug. 24, 2010 (PCT) International Search Report in International Application No. PCT/JP2010/004076.  
 Oct. 12, 2010 Extended European Search Report in European Patent Application No. 10155348.  
 Dec. 3, 2010 Extended European Search Report in European Patent Application No. 10175769.  
 Oct. 11, 2011 (JP) Office Action issued in Japanese Patent Application No. 2008-331634.  
 Oct. 11, 2011 (JP) Office Action issued in Japanese Patent Application No. 2009-088227.  
 Oct. 11, 2011 (JP) Office Action issued in Japanese Patent Application No. 2009-088238.  
 Oct. 11, 2011 (JP) Office Action issued in Japanese Patent Application No. 2009-088441.  
 Oct. 11, 2011 (JP) Office Action issued in Japanese Patent Application No. 2009-088460.  
 Oct. 11, 2011—(JP) Office Action issued in Japanese Patent Application No. 2009-088440.  
 Nov. 15, 2011 (JP) Office Action issued in Japanese Patent Application No. 2009-088241.  
 Nov. 15, 2011 (PCT) International Preliminary Report on Patentability issued in PCT/JP2009/071568.  
 Nov. 15, 2011 (PCT) International Preliminary Report on Patentability issued in PCT/JP2010/050253.  
 Nov. 15, 2011 (PCT) International Preliminary Report on Patentability issued in PCT/JP2010/055324.  
 Nov. 15, 2011 (PCT) International Preliminary Report on Patentability issued in PCT/JP2010/055326.  
 Jan. 17, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-088456.  
 Feb. 14, 2012 (PCT) International Preliminary Report on Patentability in International Application No. PCT/JP2010/055305.  
 Feb. 14, 2012 (PCT) International Preliminary Report on Patentability in International Application No. PCT/JP2010/055311.  
 Mar. 7, 2012 (US) Office Action issued in U.S. Appl. No. 12/732,404.



(56)

**References Cited**

## OTHER PUBLICATIONS

- Mar. 8, 2012 (US) Office Action issued in U.S. Appl. No. 12/732,247.  
 Mar. 9, 2012 (US) Office Action issued in U.S. Appl. No. 12/732,257.  
 Mar. 26, 2012 (US) Office Action issued in U.S. Appl. No. 12/732,457.  
 Mar. 27, 2012 (JP) Office Action issued in Japanese Patent Application No. 2008-331638.  
 Mar. 27, 2012 (JP) Office Action issued in Japanese Patent Application No. 2008-331639.  
 Mar. 27, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-156405.  
 Mar. 27, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-156406.  
 Mar. 27, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-156407.  
 Mar. 27, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-270221.  
 Feb. 16, 2016—(US) Non-Final Office Action—U.S. Appl. No. 14/867,877.  
 Feb. 24, 2016—(US) Non-Final Office Action—U.S. Appl. No. 14/226,262.  
 Feb. 25, 2016—(US) Non-Final Office Action—U.S. Appl. No. 14/141,568.  
 Feb. 22, 2016—(US) Non-Final Office Action—U.S. Appl. No. 14/226,386.  
 Mar. 4, 2016—(US) Notice of Allowance—U.S. Appl. No. 14/643,865.  
 Mar. 29, 2016—(US) Notice of Allowance—U.S. Appl. No. 13/431,350.  
 Mar. 29, 2016—(US) Notice of Allowance—U.S. Appl. No. 14/641,681.  
 Sep. 17, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,424.  
 Sep. 18, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,428.  
 Oct. 1, 2015—(US) Notice of Allowance—U.S. Appl. No. 12/732,457.  
 Oct. 5, 2015—(US) Notice of Allowance—U.S. Appl. No. 12/644,572.  
 Oct. 5, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/141,673.  
 Oct. 7, 2015—(US)—Final Office Action—U.S. Appl. No. 13/240,322.  
 Oct. 13, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/430,033.  
 Oct. 20, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,201.  
 Oct. 22, 2015—(US) Final Office Action—U.S. Appl. No. 14/641,681.  
 Sep. 2, 2015—(CN) Notification of First Office Action—App 201410200475.5.  
 Oct. 23, 2015—(US) Final Office Action—U.S. Appl. No. 13/431,350.  
 Oct. 26, 2015—(US)—Non-Final Office Action—U.S. Appl. No. 14/643,865.  
 Oct. 30, 2015—(US)—Non-Final Office Action—U.S. Appl. No. 14/226,373.  
 Nov. 3, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,259.  
 Nov. 6, 2017—(CN) Office Action—App 201610344359.X with English Translation.  
 Supplemental List of Patents or Patent Applications Treated as Related dated Feb. 23, 2022.  
 Mar. 30, 2012 (US) Office Action issued in U.S. Appl. No. 12/644,451.  
 Apr. 11, 2012 (PCT) International Preliminary Report on Patentability issued in PCT/JP2010/055310.  
 Apr. 11, 2012 (US) Office Action in U.S. Appl. No. 12/644,572.  
 May 8, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-086239.  
 May 10, 2012 (US) Office Action in U.S. Appl. No. 13/431,371.  
 May 22, 2012 (JP) Japanese Office Action issued in Japanese Patent Application No. 2010-041323.  
 Jun. 4, 2012 (US) Office Action in U.S. Appl. No. 13/431,350.  
 Jun. 6, 2012 (US) Office Action in U.S. Appl. No. 12/732,747.  
 Jun. 8, 2012 (US) Office Action in U.S. Appl. No. 13/431,277.  
 Jun. 12, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-086222.  
 Jun. 12, 2012 (JP) Office Action issued in Japanese Patent Application No. 2010-084499.  
 Jun. 12, 2012 (US) Office Action in U.S. Appl. No. 12/732,828.  
 Jun. 15, 2012 (US) Office Action in U.S. Appl. No. 12/732,404.  
 Jul. 3, 2012 (JP) Office Action issued in Japanese Patent Application No. 2010-084500.  
 Jul. 3, 2012 (JP) Office Action issued in Japanese Patent Application No. 2010-084501.  
 Jul. 3, 2012 (JP) Office Action issued in Japanese Patent Application No. 2010-084502.  
 Jul. 10, 2012 (PCT) International Preliminary Report on Patentability issued in PCT/JP2009/070971.  
 Jul. 13, 2012 (US) Office Action in U.S. Appl. No. 12/644,413.  
 Jul. 20, 2012 (US) Office Action in U.S. Appl. No. 12/817,556.  
 Jul. 30, 2012 (US) Final Office Action in U.S. Appl. No. 12/732,247.  
 Aug. 3, 2012 (US) Office Action in U.S. Appl. No. 12/644,373.  
 Aug. 14, 2012 (PCT) International Preliminary Report on Patentability issued in PCT/JP2009/071812.  
 Aug. 27, 2012 (US) Office Action in U.S. Appl. No. 12/644,572.  
 Aug. 28, 2012 (US) Office Action in U.S. Appl. No. 12/644,451.  
 Aug. 28, 2012 (US) Office Action in U.S. Appl. No. 12/732,257.  
 Aug. 28, 2012 (US) Office Action in U.S. Appl. No. 12/732,457.  
 Aug. 30, 2012 (US) Office Action in U.S. Appl. No. 12/732,647.  
 Sep. 6, 2012 (EP) European Communication issued in European Patent Application No. 10711477.9.  
 Sep. 11, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-086172.  
 Sep. 11, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-088449.  
 Sep. 28, 2012 (NZ) Examination Report issued in New Zealand Patent Application No. 596044.  
 Oct. 16, 2012 (US) Office Action in U.S. Appl. No. 12/873,633.  
 Oct. 23, 2012 (US) Office Action in U.S. Appl. No. 12/732,404.  
 Nov. 13, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-270056.  
 Nov. 13, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-297502.  
 Dec. 18, 2012 (JP) Office Action issued in Japanese Patent Application No. 2009-156369.  
 Nov. 22, 2013 (EP) Office Action issued in European Patent Application No. 10711776.4.  
 Nov. 26, 2013 (JP) Office Action issued in Japanese Patent Application No. 2011-507142.  
 Jan. 17, 2013 (US) Office Action in U.S. Appl. No. 12/732,747.  
 Jan. 22, 2013 (US) Office Action in U.S. Appl. No. 12/732,247.  
 Jan. 29, 2013 (JP) Office Action issued in Japanese Patent Application No. 2011-506968.  
 Jan. 30, 2013 (US) Office Action in U.S. Appl. No. 13/431,277.  
 Feb. 28, 2013 (US) Office Action in U.S. Appl. No. 12/817,556.  
 Mar. 1, 2013 (US) Office Action in U.S. Appl. No. 12/732,647.  
 Mar. 8, 2013 (CN) Office Action issued in Chinese Patent Application No. 200980158165.9.  
 Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156399.  
 Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156404.  
 Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156281.  
 Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156350.  
 Apr. 2, 2013 (JP) Office Action issued in Japanese Patent Application No. 2009-156355.  
 Notice of Allowance dated Oct. 7, 2021 received in related application, namely, U.S. Appl. No. 16/923,690.  
 Notice of Allowance dated Nov. 22, 2021 in related application, namely, U.S. Appl. No. 16/782,368, filed Feb. 5, 2020.  
 Supplemental List of Patents or Patent Applications Treated as Related dated Dec. 7, 2021.  
 Sep. 22, 2016—(KR) Notice of Final Rejection—App 10-2011-7021961, Eng Tran.  
 Office Action dated Mar. 7, 2023 received in related U.S. Appl. No. 17/570,849.  
 Office Action dated Mar. 7, 2023 received in related U.S. Appl. No. 17/943,869.  
 U.S. Appl. No. 12/644,373, filed Dec. 22, 2009, Abandoned.  
 U.S. Appl. No. 12/644,413, filed Dec. 22, 2009, Abandoned.  
 U.S. Appl. No. 12/644,451, filed Dec. 22, 2009, Patented.  
 U.S. Appl. No. 12/644,481, filed Dec. 22, 2009, Patented.  
 U.S. Appl. No. 12/644,525, filed Dec. 22, 2009, Patented.



(56)

## References Cited

## OTHER PUBLICATIONS

- U.S. Appl. No. 12/644,555, filed Dec. 22, 2009, Patented.  
 U.S. Appl. No. 12/644,572, filed Dec. 22, 2009, Patented.  
 U.S. Appl. No. 12/718,129, filed Mar. 5, 2010, Patented.  
 U.S. Appl. No. 12/732,247, filed Mar. 26, 2010, Abandoned.  
 U.S. Appl. No. 12/732,257, filed Mar. 26, 2010, Patented.  
 U.S. Appl. No. 12/732,404, filed Mar. 26, 2010, Patented.  
 U.S. Appl. No. 12/732,457, filed Mar. 26, 2010, Patented.  
 U.S. Appl. No. 12/732,647, filed Mar. 26, 2010, Patented.  
 U.S. Appl. No. 12/732,747, filed Mar. 26, 2010, Patented.  
 U.S. Appl. No. 12/732,828, filed Mar. 26, 2010, Patented.  
 U.S. Appl. No. 12/817,556, filed Jun. 17, 2010, Abandoned.  
 U.S. Appl. No. 12/873,633, filed Sep. 1, 2010, Abandoned.  
 U.S. Appl. No. 13/240,216, filed Sep. 22, 2011, Patented.  
 U.S. Appl. No. 13/240,266, filed Sep. 22, 2011, Patented.  
 U.S. Appl. No. 13/240,322, filed Sep. 22, 2011, Patented.  
 U.S. Appl. No. 13/430,033, filed Mar. 26, 2012, Patented.  
 U.S. Appl. No. 13/430,080, filed Mar. 26, 2012, Abandoned.  
 U.S. Appl. No. 13/431,277, filed Mar. 27, 2012, Patented.  
 U.S. Appl. No. 13/431,350, filed Mar. 27, 2012, Patented.  
 U.S. Appl. No. 13/431,371, filed Mar. 27, 2012, Patented.  
 U.S. Appl. No. 13/755,174, filed Jan. 31, 2013, Patented.  
 U.S. Appl. No. 13/848,750, filed Mar. 22, 2013, Patented.  
 U.S. Appl. No. 13/934,512, filed Jul. 3, 2013, Patented.  
 U.S. Appl. No. 14/141,568, filed Dec. 27, 2013, Patented.  
 U.S. Appl. No. 14/141,576, filed Dec. 27, 2013, Patented.  
 U.S. Appl. No. 14/141,673, filed Dec. 27, 2013, Patented.  
 U.S. Appl. No. 14/226,165, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,201, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,256, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,259, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 17/226,262, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,289, filed Mar. 26, 2014, Abandoned.  
 U.S. Appl. No. 14/226,325, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,367, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,373, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,380, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,386, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,402, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,411, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,417, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/226,424, filed Mar. 26, 2014, Abandoned.  
 U.S. Appl. No. 14/226,428, filed Mar. 26, 2014, Patented.  
 U.S. Appl. No. 14/641,681, filed Mar. 9, 2015, Patented.  
 U.S. Appl. No. 14/643,865, filed Mar. 10, 2015, Patented.  
 U.S. Appl. No. 14/742,077, filed Jun. 17, 2015, Patented.  
 U.S. Appl. No. 14/755,141, filed Jun. 30, 2015, Patented.  
 U.S. Appl. No. 14/867,877, filed Sep. 28, 2015, Patented.  
 U.S. Appl. No. 14/920,398, filed Oct. 22, 2015, Patented.  
 U.S. Appl. No. 15/130,109, filed Apr. 15, 2016, Patented.  
 U.S. Appl. No. 15/226,188, filed Aug. 2, 2016, Pending.  
 U.S. Appl. No. 15/250,310, filed Aug. 29, 2016, Patented.  
 U.S. Appl. No. 15/276,474, filed Sep. 26, 2016, Patented.  
 U.S. Appl. No. 15/276,599, filed Sep. 26, 2016, Patented.  
 U.S. Appl. No. 15/357,004, filed Nov. 21, 2016, Patented.  
 U.S. Appl. No. 15/389,497, filed Dec. 23, 2016, Patented.  
 U.S. Appl. No. 15/715,329, filed Sep. 26, 2017, Pending.  
 U.S. Appl. No. 15/832,531, filed Dec. 5, 2017, Allowed.  
 U.S. Appl. No. 15/866,000, filed Jan. 9, 2018, Patented.  
 U.S. Appl. No. 15/981,465, filed May 16, 2018, Allowed.  
 U.S. Appl. No. 16/160,343, filed Oct. 15, 2018, Patented.  
 U.S. Appl. No. 16/256,604, filed Jan. 24, 2019, Allowed.  
 U.S. Appl. No. 16/293,984, filed Mar. 6, 2019, Pending.  
 U.S. Appl. No. 16/286,132, filed Feb. 26, 2019, Pending.  
 U.S. Appl. No. 16/782,368, filed Feb. 5, 2020, Pending.  
 U.S. Appl. No. 16/796,463, filed Feb. 20, 2020, Pending.  
 U.S. Appl. No. 16/866,950, filed May 5, 2020, Pending.  
 U.S. Appl. No. 16/923,690, filed Jul. 8, 2020, Pending.  
 U.S. Appl. No. 16/924,874, filed Jul. 9, 2020, Pending.  
 U.S. Appl. No. 17/339,374, filed Jun. 4, 2021, Pending.  
 Jun. 17, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,325.  
 Jun. 18, 2015—(US) Notice of Allowance—U.S. Appl. No. 12/732,457.  
 Notice of Reasons for Refusal dated Aug. 30, 2022 received in Japanese Patent Application No. JP 2021-156029 together with English language translation.  
 Nov. 27, 2015—(CN) Office Action—App 201410311930.9.  
 Dec. 3, 2015—(CN) Office Action—App 201510088644.5.  
 Jan. 12, 2016—(US) Notice of Allowance—U.S. Appl. No. 13/431,371.  
 Jan. 15, 2016—(US) Notice of Allowance—U.S. Appl. No. 12/732,257.  
 Jan. 29, 2016—(US) Notice of Allowance—U.S. Appl. No. 14/226,411.  
 Dec. 24, 2015—(TW) Decision of Rejection—App 101110368—Eng Tran.  
 Feb. 5, 2016—(US) Non-Final Office Action—U.S. Appl. No. 13/240,322.  
 Explanation of Proofs submitted in Nullification Appeal for JP Patent 5233800 dated Feb. 17, 2022 together with English language translation.  
 Nov. 12, 2014 (MX) Office Action in Application No. MX/a/2011/013553.  
 Dec. 26, 2014—(CN) Office Action in Application No. 201080013339.5.  
 Jan. 22, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,411.  
 Feb. 10, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,380.  
 Feb. 12, 2015—(US) Final Office Action—U.S. Appl. No. 12/732,257.  
 Feb. 12, 2015—(US) Final Office Action—U.S. Appl. No. 13/431,350.  
 Feb. 12, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,417.  
 Feb. 13, 2015—(US) Non-Final Office Action—U.S. Appl. No. 13/240,322.  
 Feb. 17, 2015—(US) Final Office Action—U.S. Appl. No. 14/141,673.  
 Mar. 4, 2015—(US) Final Office Action—U.S. Appl. No. 14/141,576.  
 Mar. 4, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,386.  
 Mar. 6, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,424.  
 Feb. 6, 2015—(EP) Extended Search Report—App. 14189221.6.  
 Jan. 29, 2015—(TW) Office Action—App 099132599.  
 Mar. 17, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/848,750.  
 Apr. 1, 2015—(US) Notice of Allowance—U.S. Appl. No. 12/732,457.  
 Apr. 1, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/430,033.  
 Apr. 10, 2015—(US) Non-Final Office Action—U.S. Appl. No. 13/430,080.  
 Apr. 9, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/431,277.  
 Jan. 23, 2015 (AU) Office Action in Application No. 2010231426.  
 Mar. 6, 2015 (AU) Office Action in Application No. 2010231425.  
 Mar. 10, 2015 (JP) Office Action in Application No. 2014-095027.  
 Mar. 13, 2015 (US) Notice of Allowance in U.S. Appl. No. 14/226,165.  
 Mar. 12, 2015 (EP) Search Report in Application No. 14156840.2.  
 Feb. 19, 2015 (CA) Office Action in Application No. 2755885.  
 Mar. 2, 2015 (TW) Office Action in Application No. 101110368.  
 Mar. 23, 2015 (US) Notice of Allowance in U.S. Appl. No. 13/934,512.  
 Apr. 14, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/240,266.  
 Apr. 9, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/641,681.  
 Apr. 17, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,367.  
 Apr. 21, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,428.  
 May 1, 2015—(US) Notice of Allowance—U.S. Appl. No. 12/644,572.  
 May 6, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,259.  
 May 6, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,373.  
 Apr. 20, 2015 (AU) Office Action in Application No. 2010231426.  
 Apr. 7, 2015 (TW) Office Action in U.S. Appl. No. 99/132,600.  
 Apr. 2, 2015 (EP) Office Action in Application No. 10711776.4.  
 May 19, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,289.  
 May 19, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,201.  
 May 20, 2015—(US) Notice of Allowance—U.S. Appl. No. 13/848,750.  
 May 22, 2015—(US) Non-Final Office Action—U.S. Appl. No. 12/732,257.  
 May 29, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,165.  
 Jun. 2, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,262.  
 Jun. 5, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/226,380.  
 Jun. 2, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,256.



(56)

**References Cited**

## OTHER PUBLICATIONS

Jun. 9, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,256.

Apr. 13, 2015—(CN) Notification of Third Office Action—App 201210071810.7—Eng. Tran.

Apr. 9, 2015—(TW) Office Action—App 099132598—Eng. Tran.

May 26, 2015—(CN) Office Action—App 201310659625.4.

Jun. 25, 2015—(US) Non-Final Office Action—U.S. Appl. No. 13/431,350.

May 29, 2015—(MY) Substantive Examination Adverse Report—App. PI 2013702520—Eng Tran.

Jun. 1, 2015—(CN) Notification of First Office Action—App 201310717842.4—Eng Tran.

Jun. 1, 2015—(CN) Notification of First Office Action—App 201310717871.0—Eng Tran.

Jul. 7, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/141,673.

Jul. 16, 2015—(US) Non-Final Office Action—U.S. Appl. No. 14/226,417.

Jun. 19, 2015 (CN) Notification of First Office Action—App 201310659875.8—Eng Tran.

Aug. 4, 2015—(US) Notice of Allowance—U.S. Appl. No. 14/141,576.

Jul. 31, 2015—(US) Final Office Action—U.S. Appl. No. 14/226,411.

Jan. 6, 1993, figures and photographs of a TX cassette, Ichinomiya et al.

Dec. 28, 1988, figures and photographs of a TC cassette, Kuzuya.

Apr. 20, 2018—(US) Non-Final Office Action—U.S. Appl. No. 14/742,077.

Chinese Office Action dated Jun. 3, 2019 in Chinese Patent Application No. 201711461753.2.

Office Action dated May 20, 2019 received in U.S. Appl. No. 15/226,188.

German Official Action dated Oct. 12, 2020 in a related application 10 2010 012 892.9 together with English language translation.

Office Action dated Jun. 5, 2019 in related application, namely, U.S. Appl. No. 15/981,465, filed May 16, 2018.

Final Office Action dated Jul. 29, 2020 in related application, namely, U.S. Appl. No. 16/286,132, filed Feb. 26, 2019.

Extended European Search Report dated Aug. 29, 2019 received from the European Patent Office in related EP 19173286.6.

Notice of Allowance dated Nov. 5, 2019 in related application, namely, U.S. Appl. No. 16/160,343.

Office Action dated Nov. 12, 2019 in related application, namely, U.S. Appl. No. 15/981,465.

Office Action dated Oct. 24, 2019 in related application, namely, U.S. Appl. No. 15/715,329.

Notification of Reasons for Rejection dated Oct. 29, 2019 received from the Japanese Patent Office in application JP 2018-246396 together with an English language translation.

Notice of Allowance dated Dec. 3, 2019 in related application, namely, U.S. Appl. No. 16/256,604.

Office Action dated Dec. 9, 2019 in related application, namely, U.S. Appl. No. 16/286,132.

Notice of Allowance dated Apr. 8, 2020 in related application, namely, U.S. Appl. No. 16/796,463, filed Feb. 20, 2020.

Final Office Action dated Jul. 1, 2020, received in related U.S. Appl. No. 15/715,329, filed Sep. 26, 2017.

Office Action dated Oct. 6, 2020, received in related U.S. Appl. No. 16/866,950, filed May 5, 2020.

Office Action dated Nov. 24, 2020 received in related U.S. Appl. No. 16/782,368, filed Feb. 5, 2020.

Office Action dated Dec. 14, 2020, received in related U.S. Appl. No. 15/715,329, filed Sep. 26, 2017.

Office Action dated Jan. 7, 2021 received in parent U.S. Appl. No. 16/293,984.

Final Office Action dated Jul. 29, 2020 received in related application, namely, U.S. Appl. No. 16/286,132.

Final Office Action dated Apr. 22, 2021 received in related application, namely, U.S. Appl. No. 15/715,329.

Notice of Allowance dated Jun. 2, 2021 received in parent U.S. Appl. No. 16/293,984.

Final Office Action dated Jul. 1, 2021 received in related application, namely, U.S. Appl. No. 16/782,368.

List of Patents or Patent Applications Treated as Related dated Sep. 2, 2021.

Notice of Allowance dated Mar. 5, 2019 from related application, namely, U.S. Appl. No. 15/832,531.

Notice of Allowance dated Jun. 5, 2019 from related application, namely, U.S. Appl. No. 15/832,531.

Notice of Allowance dated Sep. 30, 2019 from related application, namely, U.S. Appl. No. 15/832,531.

Notice of Allowance dated Jan. 21, 2021 from related application, namely, U.S. Appl. No. 15/832,531.

Notice of Allowance dated Mar. 4, 2021 from related application, namely, U.S. Appl. No. 16/866,950.

Notice of Allowance dated Aug. 31, 2021 from related application, namely, U.S. Appl. No. 15/715,329.

\* cited by examiner



FIG. 1






FIG. 2






FIG. 3






FIG. 4






FIG. 5






FIG. 6






FIG. 7




FIG. 8






FIG. 9




FIG. 10






FIG. 11




FIG. 12






FIG. 13




FIG. 14






FIG. 15




FIG. 16






FIG. 17




FIG. 18






FIG. 19






FIG. 20








FIG. 22






FIG. 23





FIG. 24





**1****TAPE CASSETTE****CROSS-REFERENCE TO RELATED APPLICATION**

This application is a continuation application of U.S. Ser. No. 16/293,984 filed on Mar. 6, 2019, which is a continuation application of U.S. Ser. No. 14/742,077 filed on Jun. 17, 2015, now U.S. Pat. No. 10,265,982 granted on Apr. 23, 2019, which is a continuation application of U.S. Ser. No. 13/430,033, filed on Mar. 26, 2012, now U.S. Pat. No. 9,656,495 granted on May 23, 2017, which is a continuation-in-part of International Application No. PCT/JP2009/071812, filed Dec. 28, 2009. The disclosures of the foregoing applications are hereby incorporated by reference in their entirety.

**BACKGROUND**

The present disclosure relates to a tape cassette that can be freely inserted into and removed from a tape printer.

In related art, a tape cassette is known which is structured to be freely inserted into and removed from a cassette housing portion of a tape printer, and which includes a cassette case in which a tape as a print medium is housed. The cassette case is provided with a bottom case and a top case that is attached to an upper side of the bottom case. Via a print head, the tape printer prints characters, such as letters, on the tape that is pulled out from the cassette case. A plurality of types of tape cassette are prepared corresponding to types (a tape width, a printing format and the like, for example) of the tape that is housed in the cassette case.

A tape cassette is known that, when it is inserted in a cassette housing portion, causes a tape printer to detect a type of a tape housed in the cassette case. In more detail, a cassette detection portion, in which through holes are formed in a pattern corresponding to the type of the tape, is provided in a portion of a lower surface of the tape cassette. A plurality of detection switches that protrude upward are provided in the cassette housing portion. When the tape cassette is inserted in the cassette housing portion, the plurality of detection switches are selectively pressed in accordance with the pattern of the through holes formed in the cassette detection portion. The tape printer detects the type of the tape in accordance with a combination of pressing and non-pressing of the plurality of detection switches.

**SUMMARY**

In related art, the cassette detection portion is formed on the bottom case, and it is therefore necessary to prepare a same number of the bottom cases as the number of types of the tape. In this case, when the tape cassette is manufactured, component management for the bottom cases may become complicated. In addition, since it is necessary to prepare dies that respectively correspond to the plurality of types of bottom cases, there is a possibility that manufacturing costs of the bottom cases are increased.

In addition, the pattern of the through holes and non-through portions provided in the cassette detection portion is a random pattern. Therefore, even if a person visually checks the cassette detection portion, the type of the tape cannot be recognized. For this reason, there is a risk that the type of the tape housed in the cassette case by an operator is different from the type of the tape indicated by the cassette detection portion.

**2**

Various embodiments of the broad principles derived herein provide a tape cassette that can be manufactured accurately at a low cost.

The embodiments provide a tape cassette that includes a cassette case, a tape, a tape discharge portion, a first indicator portion, a second indicator portion, an indicator member, and an attachment portion. The cassette case includes a bottom case and a top case that is attached to an upper side of the bottom case, and includes a top surface, a bottom surface, a front surface and a pair of side surfaces. The tape is housed in the cassette case. The tape is a print medium. The tape discharge portion discharges, from the cassette case, the tape that has been guided in the cassette case along a predetermined feed path, at least part of which extends in parallel with the front surface. The first indicator portion indicates a type of the tape. The second indicator portion indicates a type of the tape, which is different from that indicated by the first indicator portion. The indicator member is a member independent from the top case and the bottom case, and is provided with the second indicator portion. The attachment portion is provided on the cassette case. The indicator member is removably attached to the attachment portion.

The embodiments also provide a tape cassette that is configured to be installed in and removed from a tape printer having a printhead and a plurality of detecting switches. The tape cassette includes a cassette case, a tape, a first indicator portion, a second indicator portion, an indicator member, an attachment portion, a head insertion portion, and an arm portion. The cassette case includes a bottom case and a top case that is attached to an upper side of the bottom case, and includes a top surface, a bottom surface, a front surface and a pair of side surfaces. The tape is housed in the cassette case. The tape is a print medium. The first indicator portion includes at least one hole and indicates a type of the tape. The second indicator portion includes at least one hole and at least one surface portion and indicates a type of the tape, which is different from that indicated by the first indicator portion. The indicator member is a member independent from the top case and the bottom case, and is provided with the second indicator portion. The attachment portion is provided on the cassette case. The indicator member is removably attached to the attachment portion. The head insertion portion is a space extending through the cassette case in a vertical direction. The printhead is inserted into the head insertion portion when the tape cassette is installed in the tape printer. The arm portion includes a part of the front surface, guides feeding of the tape, and discharges the tape toward the printhead that is inserted into the head insertion portion. The first indicator portion is formed in the part of the front surface included in the arm portion. The second indicator portion is formed in the bottom surface, opposes the plurality of detecting switches that protrude toward the bottom surface when the tape cassette is installed in the tape printer, and selectively presses a part of the plurality of detecting switches that oppose to the at least one surface portion without pressing the at least one switch that opposes to the at least one hole of the second indicator portion.

**BRIEF DESCRIPTION OF THE DRAWINGS**

Embodiments will be described below in detail with reference to the accompanying drawings in which:

FIG. 1 is a perspective view of a tape printer 1, as seen from above, when a cassette cover 6 is in a closed state.

FIG. 2 is a perspective view of the tape printer 1, as seen from above, when the cassette cover 6 is in an open state.



## 3

FIG. 3 is a cross-sectional view in a direction of arrows taken along a line I-I in FIG. 2.

FIG. 4 is a plan view of a cassette housing portion 8 in which a tape cassette 30 has been inserted, in a case where a platen holder 12 is in a stand-by position.

FIG. 5 is a plan view of the cassette housing portion 8 in which the tape cassette 30 has been mounted, in a case where the platen holder 12 is in a print position.

FIG. 6 is a partially enlarged view of a cassette-facing surface 12B that is provided with an arm detection portion 200.

FIG. 7 is a cross-sectional view in the direction of arrows taken along a line II-II in FIG. 6.

FIG. 8 is a block diagram showing an electrical configuration of the tape printer 1.

FIG. 9 is a perspective view of the tape cassette 30 according to a first embodiment.

FIG. 10 is a perspective view of a top case 31A.

FIG. 11 is a perspective view of a bottom case 31B.

FIG. 12 is a view in which a first indicator member 900 is attached to an open portion 30D.

FIG. 13 is an enlarged front view of an arm front surface 35.

FIG. 14 is a view in which a first indicator member 920 is attached to a wall portion 235 according to a second embodiment.

FIG. 15 is a perspective view of a top case 331A according to a third embodiment, as seen from the front right side.

FIG. 16 is a perspective view of the top case 331A as seen from the rear right side.

FIG. 17 is a perspective view of a bottom case 331B as seen from the front right side.

FIG. 18 is a perspective view of the bottom case 331B as seen from the rear right side.

FIG. 19 is an exploded perspective view of a tape cassette 330.

FIG. 20 is an exploded perspective view of a tape cassette 430 according to a first modified example.

FIG. 21 is a view in which a first indicator member 940 is attached to an attachment portion 430D.

FIG. 22 is a view in which a first indicator member 935 is attached to an attachment portion 530D according to a second modified example.

FIG. 23 is a view in which a second indicator member 956 is attached to an extended plate portion 442A.

FIG. 24 is a view in which a first indicator member 925 is attached to a wall portion 635 according to a third modified example.

## DETAILED DESCRIPTION

Hereinafter, various embodiments of the present disclosure will be explained with reference to the drawings. Note that in the explanation that follows, a video conference system that includes conference terminal devices that transmit and receive audio data and video data will be explained as an example of a conference system, but the present disclosure can also be applied to an audio conference system that includes conference terminal devices that transmit and receive audio data only.

A tape printer 1 and a tape cassette 30 according to a first embodiment will be explained hereinafter with reference to FIG. 1 to FIG. 13. In the explanation of the present embodiment, the lower left side, the upper right side, the lower right side and the upper left side in FIG. 1 respectively correspond to the front side, the rear side, the right side and the left side of the tape printer 1. The lower right side, the upper left side,

## 4

the upper right side and the lower left side in FIG. 9 respectively correspond to the front side, the rear side, the right side and the left side of the tape cassette 30.

Note that, in FIG. 4 and FIG. 5, although walls that form a periphery around a cassette housing portion 8 are shown, these drawings are simply schematic diagrams, and the walls shown in the drawings are depicted as thicker than they are in actuality. Further, in FIG. 4 and FIG. 5, the states in which the tape cassette 30 is inserted in the cassette housing portion 8 are shown with a top case 31A removed.

First, an outline structure of the tape printer 1 according to the first embodiment will be explained. The tape printer 1 is a general purpose tape printer, in which various types of tape cassette can be used, such as a thermal type, a receptor type, a laminated type and a heat sensitive laminated type. Hereinafter, an example will be described in which a laminated tape having a print surface that is laminated is created.

As shown in FIG. 1 and FIG. 2, the tape printer 1 is provided with a main unit cover 2 that has a rectangular shape in a plan view. A keyboard 3 is provided on the front side of the main unit cover 2, the keyboard 3 including character keys such as characters, symbols and numerals, a variety of function keys and so on. On the rear side of the keyboard 3 is positioned a display 5 that can display input characters and symbols. On the rear side of the display 5 is provided a cassette cover 6 that can be opened and closed when replacing the tape cassette 30 (refer to FIG. 4). A discharge slit 9 is provided to the rear of the left side of the main unit cover 2, from which a printed tape is discharged to the outside. A discharge window 11 is formed on the left side surface of the cassette cover 6, such that, when the cassette cover 6 is in a closed state, the discharge slit 9 is exposed to the outside. A hook shaped engaging lock 4, which protrudes downward from a lower surface, is provided substantially in the center of the front surface of the cassette cover 6. A lock hole 7 is provided in the main unit cover 2, in a position corresponding to the engaging lock 4. When the cassette cover 6 is closed, the engaging lock 4 is latched into the lock hole 7, thus inhibiting the cassette cover 6 from spontaneously opening.

An internal structure of the main unit cover 2 that corresponds to the cassette cover 6 will be explained with reference to FIG. 2 to FIG. 7. As shown in FIG. 2, the cassette housing portion 8, which is an area in which the tape cassette 30 can be freely inserted or removed, is provided inside the main unit cover 2 that corresponds to the cassette cover 6. The cassette housing portions 8 is an area in which the tape cassette 30 can be freely inserted or removed, and includes a cavity 8A and a cassette support portion 8B. The cavity 8A is formed as a depression that substantially corresponds to the shape of a bottom surface 30B (refer to FIG. 9) of a cassette case 31 that will be described later, and has a flat bottom surface. The cassette support portion 8B is a flat surface portion extending horizontally from outer edges of the cavity 8A.

The shape of the cassette support portion 8B in a plan view substantially corresponds to the shape of the tape cassette 30 in a plan view, and is a rectangular shape that is longer in a left-right direction. A rear edge portion of the cavity 8A has such a shape that two arcs are arranged side by side in the left-right direction in a plan view. A portion of the cassette support portion 8B that is located between the two arcs is referred to as a rear support portion 8C. The rear support portion 8C is a portion that faces a rear indicator portion 950 (refer to FIG. 4) of the tape cassette 30 that is inserted in the cassette housing portion 8.



## 5

As shown in FIG. 2, the rear support portion 8C is provided with a rear detection portion 300. The rear detection portion 300 is provided with rear detection switches 310 that are a plurality of detection switches.

A detailed structure of the rear detection switches 310 will be explained with reference to FIG. 3. Each of the rear detection switches 310 is provided with a substantially cylindrically-shaped main body portion 321 that is provided below the rear support portion 8C, and a rod-shaped switch terminal 322 that can advance from and retract into one end of each of the main body portions 321 in an axial line direction. Each of the main body portions 321 is installed in the interior of the main unit cover 2 such that the other end is fixed to a switch support plate 320. On the one end of each of the main body portions 321, the switch terminals 322 can advance and retract through a plurality of through holes 8D formed in the rear support portion 8C. Normally, the switch terminals 322 are each maintained in a state of protruding from the main body portions 321 by spring members (not shown in the drawings) that are provided in the interiors of the main body portions 321. When the switch terminals 322 are not being pressed, they are in the state of protruding from the main body portions 321 (an off state), and when the switch terminals 322 are being pressed, they are in the state of being pushed into the main body portions 321 (an on state).

As shown in FIG. 2, when the tape cassette 30 is not inserted in the cassette housing portion 8, the respective rear detection switches 301 are separated from the tape cassette 30, and thus they are all in the off state. As shown in FIG. 4 and FIG. 5, when the tape cassette 30 is inserted in the cassette housing portion 8, the respective rear detection switches 310 face the bottom surface 30B of the tape cassette 30 and they are selectively pressed by the rear indicator portion 950. The tape printer 1 detects the type of the tape (hereinafter referred to as the tape type) housed in the tape cassette 30, based on a combination of the on and off states of the respective rear detection switches 310. The detection of the tape type by the rear detection portion 300 will be separately described later.

The cassette housing portion 8 is provided with a feeding mechanism that pulls out the tape from the tape cassette 30 and feeds it, a printing mechanism that prints characters etc. on a surface of the tape, and the like. As shown in FIG. 3 to FIG. 5, a ribbon take-up shaft 95 is provided in the cassette housing portion 8 in a standing manner in order to rotatably drive a ribbon spool 42, which will be described later. On the front left side of the ribbon take-up shaft 95, a head holder 74 that has a substantially rectangular shape in a front view is provided in a standing manner. On the left side of the head holder 74, a tape drive shaft 100 is provided in a standing manner in order to rotatably drive a tape drive roller 46, which will be described later.

As shown in FIG. 4 and FIG. 5, a thermal head 10 that prints characters etc. on a film tape 59 is attached to a front surface of the head holder 74. An arm-shaped platen holder 12 is provided in front of the head holder 74 and is supported such that the platen holder 12 can swing around a shaft support portion 12A. A platen roller 15 and a movable feed roller 14 are both rotatably supported on the leading end side of the platen holder 12. The platen roller 15 faces the thermal head 10 and is able to come into contact with and separate from the thermal head 10. The movable feed roller 14 faces the tape drive roller 46 that fits with the tape drive shaft 100 by insertion, and is able to come into contact with and separate from the tape drive roller 46.

## 6

A release lever (not shown in the drawings), which moves in the left-right direction in response to the opening and closing of the cassette cover 6, is coupled to the platen holder 12. When the cassette cover 6 is opened, the release lever moves in the right direction, and the platen holder 12 moves toward the stand-by position shown in FIG. 4. In the stand-by position shown in FIG. 4, the platen holder 12 has moved in the direction separating it from the cassette housing portion 8, and the tape cassette 30 can therefore be inserted into or removed from the cassette housing portion 8. The platen holder 12 is constantly elastically urged to remain in the stand-by position by a coil spring that is not shown in the drawings.

When the cassette cover 6 is closed, the release lever moves in the left direction and the platen holder 12 moves toward the print position shown in FIG. 5. In the print position shown in FIG. 5, the platen holder 12 has moved in the direction that brings it into proximity with the cassette housing portion 8. Then, when the tape cassette 30 is inserted in the cassette housing portion 8, the platen roller 15 applies pressure to the thermal head 10 via the film tape 59 and an ink ribbon 60. The movable feed roller 14 applies pressure to the tape drive roller 46 via a double-sided adhesive tape 58 and the film tape 59. In the print position shown in FIG. 5, printing can be performed using the tape cassette 30 inserted in the cassette housing portion 8. The double-sided adhesive tape 58, the film tape 59 and the ink ribbon 60 will be described in detail later.

A feed path, through which a laminated tape 50 is fed, is provided from a tape discharge opening 49 of the tape cassette 30 to the discharge slit 9 (refer to FIG. 2) of the tape printer 1. A cutting mechanism 17 that cuts the laminated tape 50 at a predetermined position is provided on the feed path. The cutting mechanism 17 is formed by a fixed blade 18, and a movable blade 19 that faces the fixed blade 18 and that is supported such that it can move in the forward-rearward direction (in the up-down direction shown in FIG. 4). The movable blade 19 is moved in the forward-rearward direction by a cutter motor 24 (refer to FIG. 8).

A rear side surface of the platen holder 12, namely, a surface on a side facing the thermal head 10 is provided with an arm detection portion 200 slightly to the right of a middle position in the longitudinal direction of the surface. Hereinafter, the rear side surface of the platen holder 12 is referred to as a cassette-facing surface 12B. The arm detection portion 200 includes arm detection switches 210 that are a plurality of detection switches. A switch terminal 222 of each of the arm detection switches 210 protrudes substantially horizontally from the cassette-facing surface 12B toward the cassette housing portion 8.

In other words, each of the arm detection switches 210 protrudes in a direction that is substantially orthogonal to the direction in which the tape cassette 30 is inserted into and removed from the cassette housing portion 8, and faces a front surface (more specifically, an arm front surface 35 that will be described later) of the tape cassette 30 that is in the cassette housing portion 8. When the tape cassette 30 is inserted in a proper position in the cassette housing portion 8, each of the arm detection switches 210 is provided at a height position corresponding to the arm indicator portion 800 (refer to FIG. 9) that will be described later.

A detailed arrangement and structure of the arm detection switches 210 provided on the platen holder 12 will be explained with reference to FIG. 6 and FIG. 7. As shown in FIG. 6, five through holes 12C are provided, arranged in three rows in the up-down direction, in the cassette-facing surface 12B of the platen holder 12. Specifically, they are



arranged as two holes in a top row, two holes in a middle row and one hole in a bottom row. The positions of the through holes 12C in the left-right direction are different from each other. Specifically, the five through holes 12C are arranged in a zigzag pattern, from the right side (the left side in FIG. 6) of the cassette-facing surface 12B, in order from the bottom row, the right side of the top row, the right side of the middle row, the left side of the top row, and the left side of the middle row. The five arm detection switches 210 are provided corresponding to these through holes 12C.

As shown in FIG. 7, the arm detection switches 210 are provided with substantially cylindrically-shaped main body portions 221 that are installed in the interior of the platen holder 12, and with the rod-shaped switch terminals 222 that can advance from and retract into one end of each of the main body portions 221 in the axial line direction. The other end of each of the main body portions 221 is fastened to a switch support plate 220 in the interior of the platen holder 12. On the one end of each of the main body portions 221, the switch terminals 222 can advance and retract through the plurality of through holes 12C formed in the cassette-facing surface 12B of the platen holder 12. Normally, the switch terminals 222 are each maintained in a state of protruding from the main body portions 221 by spring members (not shown in the drawings) that are provided in the interiors of the main body portions 221. When the switch terminals 222 are not being pressed, they are in the state of protruding from the main body portions 221 (an off state), and when the switch terminals 222 are being pressed, they are in the state of being pushed into the main body portions 221 (an on state).

In a case where the tape cassette 30 has been inserted in the cassette housing portion 8, when the platen holder 12 moves toward the stand-by position (refer to FIG. 4), the respective arm detection switches 210 are separated from the tape cassette 30 and thus they are all in the off state. When the platen holder 12 moves toward the print position (refer to FIG. 5), the arm detection switches 210 face the front surface (more specifically, the arm front surface 35 that will be described later) of the tape cassette 30 and are selectively pressed by the arm indicator portion 800 that will be described later. The tape printer 1 detects the type of the tape in the tape cassette 30 based on a combination of the on and off states of the respective arm detection switches 210. Detection of the tape type by the arm detection portion 200 will be explained in more detail later.

As shown in FIG. 4 and FIG. 5, a latch projection 225 that is a plate-shaped projecting portion that extends in the left-right direction is provided on the cassette-facing surface 12B of the platen holder 12. The latch projection 225 protrudes substantially horizontally from the cassette-facing surface 12B toward the cassette housing portion 8, in the same manner as the switch terminals 222 of the arm detection switches 210. In other words, the latch projection 225 protrudes such that it faces the front surface (more specifically, the arm front surface 35 that will be described later) of the tape cassette 30 that is in the cassette housing portion 8. When the tape cassette 30 is inserted in the proper position in the cassette housing portion 8, the latch projection 225 is provided at a height position corresponding to a latch hole 804 (refer to FIG. 9) that will be described later.

An arrangement and structure of the latch projection 225 on the platen holder 12 will be explained with reference to FIG. 6 and FIG. 7. As shown in FIG. 6, the latch projection 225 is provided on the cassette-facing surface 12B of the platen holder 12 and is positioned above the detection switches 210 in the top row, extending to the right from a

position in the left-right direction between the arm detection switch 210 on the right side (the left side in FIG. 6) in the top row and the arm detection switch 210 in the bottom row.

As shown in FIG. 7, the latch projection 225 is integrally formed with the platen holder 12 such that it protrudes toward the rear (the left side in FIG. 7) from the cassette-facing surface 12B of the platen holder 12. A height of protrusion of the latch projection 225 when taking the cassette-facing surface 12B as a reference is substantially the same as or slightly greater than a height of protrusion of each of the switch terminals 222 when taking the cassette-facing surface 12B as a reference. A portion of a lower surface of the latch projection 225 is inclined with respect to the horizontal direction such that the thickness gradually reduces toward the leading end side (the left side in FIG. 7).

Next, an electrical configuration of the tape printer 1 will be explained with reference to FIG. 8. As shown in FIG. 8, the tape printer 1 includes a control circuit 400 formed on a control board. In the control circuit 400, a ROM 402, a CGROM 403, a RAM 404 and an input/output interface 411 are connected, via a data bus 410, to a CPU 401 that controls each instrument.

Various types of programs that are performed by the CPU 401 to control the tape printer 1 are stored in the ROM 402. A table to identify the tape type of the tape cassette 30 inserted in the cassette housing portion 8 is also stored in the ROM 402. Printing dot pattern data for printing characters is stored in the CGROM 403. A plurality of storage areas are provided in the RAM 404 for a text memory, a print buffer and the like.

The arm detection switches 210, the rear detection switches 310, the keyboard 3, a liquid crystal drive circuit (LCDC) 405, drive circuits 406, 407, 408, and the like are connected to the input/output interface 411. The drive circuit 406 is an electronic circuit for driving the thermal head 10. The drive circuit 407 is an electronic circuit for driving a tape feed motor 23. The drive circuit 408 is an electronic circuit for driving the cutter motor 24, which operates the movable blade 19. The liquid crystal drive circuit (LCDC) 405 includes a video RAM (not shown in the drawings) for outputting display data to the display 5.

Next, a structure of the tape cassette 30 according to the present embodiment will be explained with reference to FIG. 4, FIG. 5 and FIG. 9 to FIG. 12. The tape cassette 30 of the present embodiment is a general-purpose tape cassette that can be used as various types of tape cassettes, such as a heat-sensitive type, a receptor type, a laminated type, a heat-sensitive laminated type and the like, and an example is described in which it is used as a laminated type tape cassette.

As shown in FIG. 9, the tape cassette 30 includes the cassette case 31 that is overall a substantially cuboid (box shaped) housing with corners that are rounded in a plan view. The cassette case 31 is provided with a bottom case 31B, which includes the bottom surface 30B of the cassette case 31, and a top case 31A, which includes a top surface 30A of the cassette case 31 and which is fixed to an upper portion of the bottom case 31B. Hereinafter, a distance from the bottom surface 30B to the top surface 30A is referred to as a height dimension of the tape cassette 30 or the cassette case 31.

As shown in FIG. 10, the top case 31A is provided with a rectangular-shaped top wall 31E that is longer in the left-right direction in a plan view. The top wall 31E is provided with support holes 65, 66 and 67 that rotatably support spools etc. that will be described later. A lower surface of the top wall 31E is provided with a plurality of



substantially cylinder-shaped pin portions **33A** that protrude downward. An upper semi-circular portion **38A**, which is recessed in a substantially semi-circular shape in a plan view, is formed on a front edge portion of the top wall **31E**. A hook-shaped fixing portion **38D** extends downward from a left portion of the upper semi-circular portion **38A**. The fixing portion **38D** includes an extending portion **38F** that extends downward from the top wall **31E**, and a tab portion **38G** that protrudes from a leading end portion of the extending portion **38F** toward the front.

As shown in FIG. **11**, the bottom case **31B** is formed in a box shape in which an upper portion opens, and is provided with a bottom wall **31G**, a right front wall **31H**, a right side wall **31J**, a left side wall **31K**, a back wall **31M** and a lower semi-circular portion **38B**. The bottom wall **31G** is provided with a support hole **87** and support shafts **85** and **86** that rotatably support the spools etc. that will be described later. The bottom wall **31G** is provided with a plurality of cylindrically-shaped boss portions **33B** that protrude upward from a top surface. The diameter of cylindrical holes provided in the boss portions **33B** is substantially the same as the diameter of the pin portions **33A**. An upper end position of the boss portions **33B** is the same as an upper end position of the right front wall **31H**, the right side wall **31J**, the left side wall **31K** and the back wall **31M**.

A rear surface portion **68**, which is a substantially triangular-shaped flat portion in a plan view and which corresponds to the rear support portion **8C** (refer to FIG. **2**), is provided in a substantially central portion, in the left-right direction, of the rear end edge of the bottom wall **31G**. The rear surface portion **68** is located on a same plane (namely, at a same height position) as a lower surface of a corner portion **32A** (refer to FIG. **9**). The rear surface portion **68** is provided with a rear indicator portion **950** (refer to FIG. **4** and FIG. **5**) that will be described later.

The right front wall **31H** is extended from a front right corner portion of the bottom case **31B** to the left along a front end portion of the bottom wall **31G**. The lower semi-circular portion **38B**, which is recessed in a substantially semi-circular shape in a plan view, is provided continuously to the left side of the right front wall **31H**. The lower semi-circular portion **38B** is positioned slightly to the right of the center in the left-right direction of the cassette case **31**. An upper left portion of the lower semi-circular portion **38B** is provided with a fixing hole **79** that is a horizontally long rectangular through hole in a front view.

When the top case **31A** (refer to FIG. **9**) is attached to the bottom case **31B**, the pin portions **33A** are inserted from above into the cylindrical holes of the boss portions **33B**. When the top case **31A** is pushed downward, the tab portion **38G** of the top case **31A** is fitted into the fixing hole **79** of the bottom case **31B**. Thus, the top case **31A** is attached to the bottom case **31B** and the cassette case **31** is formed. An open portion **30D** (refer to FIG. **12**) that will be described later is formed in the front surface of the cassette case **31**.

As shown in FIG. **9**, the cassette case **31** has corner portions **32A** that are formed to have the same width (the same length in the up-down direction) regardless of the tape type (the tape width, the printing format and the like, for example) of the tape cassette **30**. The corner portions **32A** protrude to the outside so as to form a right angle in a plan view. However, in the plan view, the front left corner portion **32A** does not form a right angle because the tape discharge opening **49** is provided in the corner.

As shown in FIG. **4** and FIG. **5**, three types of tape rolls, i.e., the double-sided adhesive tape **58** wound around a first tape spool **40**, the transparent film tape **59** wound around a

second tape spool **41**, and the ink ribbon **60** wound around the ribbon spool **42** are housed in the cassette case **31**. The double-sided adhesive tape **58** is a double-sided tape having a surface to which a release paper is adhered, and is adhered to a print surface of the printed film tape **59**.

The first tape spool **40**, around which the double-sided adhesive tape **58** is wound with the release paper facing the outside, is rotatably arranged in a rear left portion inside the cassette case **31** via the above-described support hole **65**. The second tape spool **41**, around which the film tape **59** is wound, is rotatably arranged in a rear right portion inside the cassette case **31** via the above-described support hole **66**. The ink ribbon **60** that is wound around the ribbon spool **42** is rotatably arranged in a front right portion inside the cassette case **31**.

The rear indicator portion **950** is provided between the double-sided adhesive tape **58** that is wound around the first tape spool **40** and the film tape **59** that is wound around the second tape spool **41**. The rear indicator portion **950** is provided in a position that corresponds to the rear detection portion **300** (refer to FIG. **3**). The rear indicator portion **950** has a plurality of indicator portions. Each of the indicator portions is either a non-pressing portion **951** that is a hole, whose opening shape is circular, into which the switch terminal **322** can be inserted, or a pressing portion **952** that is a surface portion that comes into contact with the switch terminal **322**. The rear indicator portion **950** of the present embodiment includes either the non-pressing portion **951** or the pressing portion **952** in each of five positions corresponding to the five switch terminals **322**.

The arrangement pattern of the non-pressing portions **951** and the pressing portions **952** is determined in accordance with information (color information) indicating a tape color and a character color of the tape cassette **30**. Note that a data table, in which the combinations of the on and off states of the five rear detection switches **310** are associated with the color information of the tape cassette **30**, is stored in the ROM **402** (refer to FIG. **8**) of the tape printer **1**. In this data table, the off state of the rear detection switch **310** corresponds to the non-pressing portion **951**, and the on state of the rear detection switch **310** corresponds to the pressing portion **952**.

A ribbon take-up spool **44** is rotatably arranged via the above-described support hole **67** between the first tape spool **40** and the ribbon spool **42** inside the cassette case **31**. When the ribbon take-up spool **44** is rotatably driven by the ribbon take-up shaft **95** that is fitted into its interior by insertion, the ribbon take-up spool **44** pulls out the ink ribbon **60** from the ribbon spool **42** and takes up the ink ribbon **60** that has been used for printing characters etc.

As shown in FIG. **9**, a semi-circular groove **38** that is a groove portion forming a generally semi-circular shape in a plan view is provided in the front surface of the cassette case **31**, and extends across the height direction of the cassette case **31** (in other words, extends from the top surface **30A** to the bottom surface **30B**). The semi-circular groove **38** is provided with the upper semi-circular portion **38A** formed in the top case **31A** and the lower semi-circular portion **38B** formed in the bottom case **31B**. The semi-circular groove **38** is a recess provided such that, when the tape cassette **30** is inserted in the cassette housing portion **8**, there is no interference between the shaft support portion **12A** (refer to FIG. **4**) of the platen holder **12** and the cassette case **31**.

Of the front surface of the cassette case **31**, the section that extends to the left from the semi-circular groove **38** is referred to as the arm front surface **35**. A part that extends from the right portion of the tape cassette **30** in the left



direction and that is defined by the arm front surface 35, and an arm back surface 37 that is positioned separately to the arm front surface 35 in the rearward direction and extending in the height direction, is referred to as an arm portion 34.

As shown in FIG. 4 and FIG. 5, the film tape 59 pulled out from the second tape spool 41 and the ink ribbon 60 pulled out from the ribbon spool 42 are both guided into the arm portion 34. A discharge opening 34A is formed by the arm front surface 35 and the leading end of the arm back surface 37. The film tape 59 and the ink ribbon 60 that have been guided into the arm portion 34 are overlapped at the discharge opening 34A and discharged toward an exposure portion 77 that will be described later.

A space that is defined by the arm back surface 37 and by a peripheral wall surface which is provided continuously from the arm back surface 37, that is a generally rectangular shape in a plan view and that penetrates the tape cassette 30 in the up-down direction, is a head insertion portion 39. The head insertion portion 39 is connected to the outside at the front surface of the tape cassette 30 through the exposure portion 77 that is an opening provided in the front surface of the tape cassette 30. The head holder 74 that supports the thermal head 10 of the tape printer 1 is inserted into the head insertion portion 39. At the exposure portion 77, one of the surfaces of the film tape 59 discharged from the discharge opening 34A of the arm portion 34 is exposed to the front, and the other surface of the film tape 59 faces the thermal head 10 positioned to the rear. In the present embodiment, the other surface of the film tape 59 faces the thermal head 10 with the ink ribbon 60 interposed therebetween. At the exposure portion 77, printing is performed on the film tape 59 by the thermal head 10 using the ink ribbon 60.

The tape drive roller 46 is rotatably and axially supported on a downstream side of the head insertion portion 39, in a feed direction of the film tape 59 and the ink ribbon 60 from the discharge opening 34A of the arm portion 34 to the tape discharge opening 49. When the tape drive roller 46 is rotatably driven by the tape drive shaft 100 that is fitted into its interior by insertion, it pulls out the print tape 59 from the second tape spool 41 by moving in concert with the movable feed roller 14 of the platen holder 12 that faces the tape drive roller 46. At the same time, the double-sided adhesive tape 58 is pulled out from the first tape spool 40 and guided so that it adheres to the print surface of the film tape 59.

As shown in FIG. 4, FIG. 5 and FIG. 9, a pair of upper and lower regulating members 36 are provided on an upstream side of the tape drive roller 46. On a downstream side of the thermal head 10, base portions of the regulating members 36 restrict the printed film tape 59 in the up-down direction (in the tape width direction) and guide it toward the tape discharge opening 49. The film tape 59 and the double-sided adhesive tape 58 are bonded together correctly without generating any positional displacement between them.

A guide wall 47 is provided in a standing manner in the vicinity of the regulating members 36. The guide wall 47 separates the used ink ribbon 60, which has been fed via the head insertion portion 39, from the film tape 59 and guides it toward the ribbon take-up spool 44. A second separating wall 48 is provided in a standing manner between the guide wall 47 and the ribbon take-up spool 44. The second separating wall 48 inhibits mutual contact between the used ink ribbon 60 that is guided along the guide wall 47 and the double-sided adhesive tape 58 that is wound on and supported by the first tape spool 40.

As shown in FIG. 9 and FIG. 12, a first indicator member 900, which is a plate-shaped member having a horizontally long rectangular shape in a front view, is detachably pro-

vided on a front portion of the arm portion 34. The first indicator member 900 is provided with the arm indicator portion 800 that indicates the tape type of the tape cassette 30. As shown in FIG. 12, when the first indicator member 900 is removed from the front portion of the arm portion 34, the open portion 30D, through which the film tape 59 can be visually checked, is formed in the front portion of the arm portion 34. When the first indicator member 900 is attached to the open portion 30D, the arm front surface 35 is formed on the front portion of the arm portion 34.

Structures of the open portion 30D and the first indicator member 900 will be explained with reference to FIG. 12. The open portion 30D is formed continuously from the discharge opening 34A to the right. The open portion 30D has a cutout shape that corresponds to a front shape of the first indicator member 900, and is provided with a lower edge surface 34G, a right edge surface 34H and an upper edge surface 34J.

A groove portion 30E is provided from the left end to the right end of the lower edge surface 34G. The right edge surface 34H is the left end face of the lower semi-circular portion 38B. A notch portion 31L, which is notched from a front edge portion of the bottom wall 31G (refer to FIG. 11) toward the rear, is formed in the lower edge surface 34G slightly to the left of the right edge surface 34H. A convex portion 30F is provided that continuously protrudes downward from the left end to the right end of the upper edge surface 34J. A through hole 30G, whose opening shape is a vertically long rectangular shape, is provided to the right of the open portion 30D.

The first indicator member 900 is formed in a flat plate shape and has a horizontally long rectangular shape in a front view. A groove portion 901 is formed from the left end to the right end of the upper end face of the first indicator member 900. A convex portion 907 is formed that continuously protrudes downward from the left end to the right end of the lower end face of the first indicator member 900.

A hook arm 904 that protrudes to the right is provided on a right end portion of the first indicator member 900. The hook arm 904 is a hook-shaped body that extends to the right using a right rear end portion of the first indicator member 900 as a base portion, and is provided with an extending portion 905 and a hook portion 906. The extending portion 905 is a plate-shaped portion having a thickness thinner than that of the first indicator member 900. The hook portion 906 is a projecting portion which protrudes from a leading end portion of the extending portion 905 toward the front, and which has a substantially triangular shape in a plan view. When the extending portion 905 receives a force from the front to the rear, it deflects to the rear.

A method for attaching and removing the first indicator member 900 to and from the open portion 30D will be explained with reference to FIG. 9 to FIG. 12. When the first indicator member 900 is attached to the open portion 30D, an operator slidably moves the first indicator member 900 from the discharge opening 34A side to the right side, and thereby pushes the first indicator member 900 into the open portion 30D. At this time, the operator causes the groove portion 901 to slide along the convex portion 30F and also causes the convex portion 907 to slide along the groove portion 30E.

When the leading end (the right end) of the hook arm 904 reaches the right edge surface 34H and enters the rear side of the semi-circular groove 38, the hook portion 906 comes into contact with a rear surface of the semi-circular groove 38 and is pressed rearward. The extending portion 905 deflects to the rear, with the base portion serving as a base



point, because its leading end portion receives a rearward force. When the first indicator member **900** moves further to the right and the hook portion **906** reaches the through hole **30G**, the hook portion **906**, which is impelled by the extending portion **905**, enters the through hole **30G**. The position of the hook portion **906** is fixed and the first indicator member **900** is attached to the open portion **30D**.

When the first indicator member **900** is removed from the open portion **30D**, the operator pushes the hook portion **906** that has entered the through hole **30G** toward the rear and releases the fixation of the hook portion **906**. In this state, the operator slidingly moves the first indicator member **900** to the left from the inside of the open portion **30D**, and thereby pulls out the first indicator member **900** to the discharge opening **34A** side. At this time, the groove portion **901** is guided along the convex portion **30F** and the convex portion **907** is guided along the groove portion **30E**. Thus, the first indicator member **900** is removed from the open portion **30D**.

The arm indicator portion **800** that is provided on the first indicator member **900** will be explained with reference to FIG. **13**. The arm indicator portion **800** is provided in a position corresponding to the arm detection portion **200** (refer to FIG. **7**). The arm indicator portion **800** includes a plurality of indicator portions. Each of the indicator portions is either a non-pressing portion **801** that is a through hole whose opening shape is a vertically long rectangular shape and into which the switch terminal **222** can be inserted, or a pressing portion **802** that is a surface portion that comes into contact with the switch terminal **222**. The arm indicator portion **800** of the present embodiment includes either the non-pressing portion **801** or the pressing portion **802** at each of five positions corresponding to the five switch terminals **222**.

An arrangement pattern of the non-pressing portions **801** and the pressing portions **802** is determined in accordance with the tape type (in the present embodiment, printing information that indicates the tape width and the printing format) of the tape cassette **30**. Note that a data table, in which the combinations of the on and off states of the five arm detection switches **210** are associated with the printing information of the tape cassette **30**, is stored in the ROM **402** (refer to FIG. **8**) of the tape printer **1**. In this data table, the off state of the arm detection switch **210** corresponds to the non-pressing portion **801**, and the on state of the arm detection switch **210** corresponds to the pressing portion **802**.

Hereinafter, the arrangement pattern of the non-pressing portions **801** and the pressing portions **802** will be explained with reference to FIG. **13**. Note that, when the non-pressing portions **801** and the pressing portions **802** are collectively referred to or when no distinction is made between them, they are simply referred to as indicator portions **800A** to **800E**.

The indicator portion **800A** and the indicator portion **800D** are provided side by side along the left-right direction, slightly below the center in the vertical direction of the first indicator member **900**. The indicator portion **800B** and the indicator portion **800C** are provided side by side along the left-right direction, slightly above the center in the vertical direction of the first indicator member **900**. The indicator portion **800E** is provided in a right portion of a lower end portion of the first indicator member **900**. In the present embodiment, the positions of the indicator portions **800A** to **800E** in the left-right direction are different from each other. In other words, the indicator portions **800A** to **800E** are not

mutually arranged in rows in the up-down direction, and the respective indicator portions **800A** to **800E** are arranged in a zigzag pattern.

In the present embodiment, the indicator portions **800A**, **800B** and **800E** indicate the width (seven types from 3.5 mm to 36 mm, for example) of the tape that is housed in the tape cassette **30**, by a combination of each of the non-pressing portions **801** and the pressing portions **802**. A printing format (normal image printing or mirror image printing, for example) of the tape that is housed in the tape cassette **30** is indicated by whether the indicator portion **800C** is the non-pressing portion **801** or the pressing portion **802**. Other information (whether a tape color is white or a color other than white, for example) relating to the tape that is housed in the tape cassette **30** is indicated by whether the indicator portion **800D** is the non-pressing portion **801** or the pressing portion **802**.

In the first indicator member **900**, the latch hole **804**, which is a through hole having a substantially rectangular shape in a front view and which is longer in the left-right direction, is provided in the upper right of the arm indicator portion **800**. The latch hole **804** is a hole portion into which the latch projection **225** is inserted when the platen holder **12** moves to the print position (refer to FIG. **5**). Note that a section of a lower wall of the latch hole **804** is formed to be inclined with respect to the horizontal direction so that the an opening width of the latch hole **804** in the up-down direction is largest on the arm front surface **35** and the opening width is gradually reduced toward the inside.

When the tape cassette **30** having the above-described structure is assembled, first, as shown in FIG. **4**, the operator houses the double-sided adhesive tape **58**, the film tape **59** and the ink ribbon **60** respectively in predetermined positions in the bottom case **31B**. Next, the operator attaches the top case **31A** (refer to FIG. **10**) to the bottom case **31B** (refer to FIG. **11**). When the top case **31A** is attached to the bottom case **31B**, the open portion **30D** is formed in the front portion of the arm portion **34** as shown in FIG. **12**. Lastly, the operator attaches the first indicator member **900** to the open portion **30D** and thus the assembly of the tape cassette **30** is completed.

When the length in the up-down direction of the first indicator member **900** is smaller than a predetermined width, the length in the up-down direction of the indicator portion **800E**, which is provided in the lowest position among the plurality of indicator portions **800A** to **800E**, may become smaller than that of the other indicator portions **800A** to **800D**. In this case, regardless of the fact that the indicator portion **800E** is the non-pressing portion **801**, there is a possibility that the switch terminal **222** of the arm detection switch **210** that faces the indicator portion **800E** comes into contact with the bottom wall **31G** of the bottom case **31B** and the on state is established erroneously.

In the present embodiment, in a case where the indicator portion **800E** is the non-pressing portion **801**, when the first indicator member **900** is attached to the open portion **30D**, the non-pressing portion **801** is communicatively connected to the notch portion **31L** in the up-down direction (refer to FIG. **9** and FIG. **13**), the notch portion **31L** being formed in the open portion **30D** of the bottom case **31B**. Thus, even when the length in the up-down direction of the indicator portion **800E** is smaller than that of the other indicator portions **800A** to **800D**, the arm detection switch **210** that faces the indicator portion **800E** does not come into contact with the bottom wall **31G** and is appropriately inserted into the non-pressing portion **801**.



On the other hand, when the length in the up-down direction of the first indicator member **900** is larger than the predetermined width, the length in the up-down direction of the indicator portion **800E** is the same as that of the other indicator portions **800A** to **800D**. Therefore, in a case where the indicator portion **800E** is the non-pressing portion **801**, in a similar way to a case in which the other indicator portions **800A** to **800D** are the non-pressing portions **801**, it can be a hole portion that is open only in the front surface of the tape cassette **30**.

A method for identifying the tape type based on the arm indicator portion **800** and the rear indicator portion **950** will be explained below.

Detection of the tape type by the arm detection portion **200** will be explained with reference to FIG. 4, FIG. 5 and FIG. 13. When the tape cassette **30** is inserted in the proper position in the cassette housing portion **8** by a user and the cassette cover **6** is closed, the platen holder **12** moves from the stand-by position shown in FIG. 4 toward the print position shown in FIG. 5. In response to this, the arm detection portion **200** and the latch projection **225** that are provided in the cassette-facing surface **12B** of the platen holder **12** move to positions respectively facing the arm indicator portion **800** and the latch hole **804** that are provided in the arm front surface **35** of the tape cassette **30**.

Each of the switch terminals **222** (refer to FIG. 6 and FIG. 7) of the five arm detection switches **210** that protrude from the cassette-facing surface **12B** respectively faces either the non-pressing portion **801** or the pressing portion **802** that is provided in corresponding position of the arm indicator portion **800**, and the switch terminals **222** are selectively pressed. In the example of the tape cassette **30** shown in FIG. 13, the switch terminals **222** that face the indicator portions **800A** and **800C** in the arm indicator portion **800** are pressed by the surface portions of the arm front surface **35** that are the pressing portions **802**. The switch terminals **222** that face the non-pressing portions **801** in the arm indicator portion **800**, namely the indicator portions **800B**, **800D** and **800E**, are inserted into switch holes that are the non-pressing portions **801**. Thus, in the arm detection portion **200**, the two arm detection switches **210** corresponding to the indicator portions **800A** and **800C** are in the on state, and the three arm detection switches **210** corresponding to the indicator portions **800B**, **800D** and **800E** are in the off state.

As described above, the data table in which the combinations of the on and off states of the arm detection switches **210** are associated with the printing information is stored in the ROM **402** (refer to FIG. 8) of the tape printer **1**. The CPU **401** (refer to FIG. 8) refers to this data table and identifies the printing information corresponding to the combination of the on and off states of the arm detection switches **210**. Specifically, the tape width, the printing format and the other information of the tape cassette **30** are identified.

The way in which the tape type is detected by the rear detection portion **300** will be explained with reference to FIG. 4 and FIG. 5. As shown in FIG. 4 and FIG. 5, when the tape cassette **30** is inserted in the proper position in the cassette housing portion **8**, the periphery (more specifically, the corner portions **32A**) of the cassette case **31** is supported from below by the cassette support portion **8B** (refer to FIG. 2) of the cassette housing portion **8**. At the same time, the rear surface portion **68** of the bottom case **31B** is supported from below by the rear support portion **8C** (refer to FIG. 2).

The rear detection portion **300** (refer to FIG. 2) provided in the rear support portion **8C** (refer to FIG. 2) faces the rear indicator portion **950** of the tape cassette **30**. More specifically, the switch terminals **322** (refer to FIG. 3) of the rear

detection switches **310** that protrude from the rear support portion **8C** respectively face either the non-pressing portion **951** or the pressing portion **952** provided at corresponding positions in the rear indicator portion **950**, and are selectively pressed. More specifically, the rear detecting switches **310** that face the non-pressing portions **951** are inserted into the non-pressing portions **951**, and are thus in the off state. The rear detecting switches **310** that face the pressing portions **952** are pressed by the pressing portions **952**, and are thus in the on state.

As described above, the data table, in which the combinations of the on and off states of the rear detection switches **310** are associated with the color information, is stored in the ROM **402** (refer to FIG. 8) of the tape printer **1**. The CPU **401** (refer to FIG. 8) refers to this data table and identifies the color information corresponding to the combination of the on and off states of the rear detection switches **310**.

The tape cassette **30** of the present embodiment is structured such that not only the tape printer **1** can recognize the printing information by detecting the arm indicator portion **800**, but also a person can recognize the printing information by visually checking the arm indicator portion **800**. A method for recognizing the printing information by visually checking the arm indicator portion **800** will be explained with reference to FIG. 13.

As described above, whether each of the indicator portions **800A**, **800B** and **800E** is the non-pressing portion **801** or the pressing portion **802** is determined in advance in accordance with the tape width. The operator can ascertain the tape width by visually checking the arm indicator portion **800** and simply confirming whether each of the indicator portions **800A**, **800B** and **800E** is the non-pressing portion **801** or the pressing portion **802**.

Whether the indicator portion **800C** is the non-pressing portion **801** or the pressing portion **802** is determined in advance in accordance with the printing format. By simply confirming the indicator portion **800C**, the operator can ascertain whether normal image printing or mirror image printing is to be performed. Whether the indicator portion **800D** is the non-pressing portion **801** or the pressing portion **802** is determined in advance in accordance with the other information (whether the tape color is white or not, for example). The operator can ascertain whether the tape color is white or not by simply confirming the indicator portion **800D**.

In this manner, in the tape cassette **30** of the present embodiment, the arrangement pattern of the non-pressing portions **801** and the pressing portions **802** is determined based on predetermined rules depending on the tape type. Therefore, the tape type (the printing information in the present embodiment) of the tape cassette **30** can be recognized by the person visually checking the arm indicator portion **800**.

Printing operations of the tape printer **1** in which the tape cassette **30** is inserted will be simply explained with reference to FIG. 4 and FIG. 5. When the tape cassette **30** is inserted in the cassette housing portion **8**, the tape drive shaft **100** is fittingly inserted into the tape drive roller **46** and the ribbon take-up shaft **95** is fittingly inserted into the ribbon take-up spool **44** (refer to FIG. 4). When the cassette cover **6** is closed, the platen holder **12** moves to the print position, the platen roller **15** faces the thermal head **10**, and the movable feed roller **14** presses the tape drive roller **46** (refer to FIG. 5).

When printing is performed in the tape printer **1**, the tape drive roller **46** that is rotatably driven via the tape drive shaft **100** pulls out the film tape **59** from the second tape spool **41**



by moving in concert with the movable feed roller 14. The ribbon take-up spool 44 that is rotatably driven via the ribbon take-up shaft 95 pulls out the unused ink ribbon 60 from the ribbon spool 42 in synchronization with the print speed. The film tape 59 that has been pulled out from the second tape spool 41 is fed along a feed path within the arm portion 34 while passing outside of the ribbon spool 42. Then, the film tape 59 is supplied from the discharge opening 34A to the head insertion portion 39 in a state in which the ink ribbon 60 is joined to the print surface of the film tape 59, and is fed between the thermal head 10 and the platen roller 15 of the tape printer 1.

Then, characters, graphics and symbols etc. are printed onto the print surface of the film tape 59 by the thermal head 10. Following that, the used ink ribbon 60 is separated from the printed film tape 59 at the guide wall 47 and is taken up by the ribbon take-up spool 44. Meanwhile, the double-sided adhesive tape 58 is pulled out from the first tape spool 40 by the tape drive roller 46 moving in concert with the movable feed roller 14. While being guided and caught between the tape drive roller 46 and the movable feed roller 14, the double-sided adhesive tape 58 is laminated and affixed to the print surface of the printed film tape 59. The printed film tape 59 to which the double-sided adhesive tape 58 has been affixed (namely, the laminated tape 50) is fed toward the tape discharge opening 49, and then cut by the cutting mechanism 17. Thus, the printing operations of the tape printer 1 are completed.

Note that, in the present embodiment, the laminated type tape cassette 30 formed from a general purpose cassette is used in the tape printer 1 that is a general purpose machine. Therefore, the single tape printer 1 can be adapted to be used for tape cassettes of various types, such as the heat-sensitive type, the receptor type, the heat-sensitive laminated type and the like.

As explained above, in the tape cassette 30 of the first embodiment, the arm indicator portion 800 to identify the type of the tape housed in the cassette case 31 is provided on the first indicator member 900 that is independent from the top case 31A and the bottom case 31B. Therefore, the common top case 31A and the common bottom case 31B can be used regardless of the type of the tape housed in the cassette case 31. As compared to a case in which the bottom cases 31B and the top cases 31A that are different depending on each tape type are prepared, it is possible to reduce the types of the bottom case 31B and the top case 31A. Thus, component management of the bottom case 31B and the top case 31A during manufacture is simplified. It is possible to reduce dies for manufacturing the bottom case 31B and the top case 31A, and to reduce manufacturing costs of the tape cassette 30.

The arrangement pattern of the non-pressing portions 801 and the pressing portions 802 formed in the first indicator member 900 is determined in advance so that a person can recognize the tape type by visual check. The first indicator member 900 is provided on the upstream side, in the tape feed direction, of the discharge opening 34A in the arm portion 34. Therefore, the person can visually check the arm indicator portion 800 as well as the tape in the arm portion 34 from the front of the tape cassette 30. Accordingly, the operator can verify the type of the tape to be housed in the cassette case 31 against the tape type indicated by the arm indicator portion 800, and it is therefore possible to accurately manufacture the tape cassette 30.

The operator can visually check the film tape 59 housed in the tape cassette 30, at the open portion 30D to which the first indicator member 900 is attached. The operator can

attach the first indicator member 900 to the open portion 30D while confirming the film tape 59 from the open portion 30D.

Since the first indicator member 900 is slidably attached to the open portion 30D, it can be easily attached. The operator also can remove the first indicator member 900 from the open portion 30D. Therefore, even in case of a combination error of the tape type and the first indicator member 900, it is sufficient to replace only the first indicator member 900. Therefore, even if there is an assembly error of the tape or the first indicator member 900, it is possible to omit a useless process, such as disassembling the cassette case 31.

A tape cassette 230 of a second embodiment will be explained with reference to FIG. 14. In the tape cassette 230 of the second embodiment, a first indicator member 920 in the form of a film is adhered to a wall portion 235 that is formed on the upstream side, in the tape feed direction, of the discharge opening 34A in the arm portion 34. Note that the tape cassette 230 is the same as the tape cassette 30 according to the first embodiment except for some of the structural components. Therefore, the same structural components and processes are denoted with the same reference numerals and an explanation thereof is omitted or simplified.

The tape cassette 230 includes a cassette case 231 that is provided with a top case 231A and a bottom case 231B. The semi-circular groove 38 is formed in a front surface of the cassette case 231, in a similar way to the cassette case 31 of the first embodiment. The tape cassette 230 is provided with the wall portion 235 which extends from a left end portion of the semi-circular groove 38 to the discharge opening 34A and which blocks the front portion of the arm portion 34. The wall portion 235 is provided with five detection holes 236.

In the present embodiment, four of the five detection holes 236 are through holes whose opening shape is a vertically long rectangular shape, and one of them is open continuously from a right portion of a lower end portion of the wall portion 235 to the bottom wall 31G. In a state in which the tape cassette 230 is inserted in the cassette housing portion 8 of the tape printer 1, the detection holes 236 are arranged respectively at positions facing the switch terminals 222 of the arm detection switches 210. The first indicator member 920 in the form of a film is adhered to a front surface of the wall portion 235.

The first indicator member 920 will be explained with reference to FIG. 14. The first indicator member 920 is a film having a rectangular shape in a plan view, and adhesive is applied to one of its surfaces. An arm indicator portion 820 is formed in the first indicator member 920. The arm indicator portion 820 is provided with communication holes 821 and blocking portions 822 that are formed in an arrangement pattern corresponding to the type of the tape cassette 230. When the first indicator member 920 is adhered to the front surface of the wall portion 235, the communication holes 821 and the blocking portions 822 are formed in positions that respectively correspond to the plurality of detection holes 236 formed in the wall portion 235.

The plurality of communication holes 821 have an opening width that is slightly larger than that of the detection holes 236. In the present embodiment, among the plurality of communication holes 821, the communication hole 821 that is formed in a position corresponding to one of the indicator portions 800A to 800D (refer to FIG. 13) of the first embodiment is a hole whose opening shape is a vertically long rectangular shape. The communication hole 821 that is formed in a position corresponding to the indicator portion



**800E** (refer to FIG. 13) of the first embodiment is a cutout portion having a convex shape that is cut out upward from a lower edge portion.

When the first indicator member **920** is affixed to the wall portion **235**, the detection holes **236** that face the communication holes **821** are exposed via the communication holes **821**. Therefore, the switch terminals **222** of the arm detection switches **210** can be inserted. In other words, the arm detection switches **210** that face the detection holes **236** that are exposed via the communication holes **821** are in the off state because the switch terminals **222** are inserted into the detection holes **236**.

The blocking portions **822** are surface portions where the communication holes **821** are not formed. When the first indicator member **920** is affixed to the wall portion **235**, the detection holes **236** that face the blocking portions **822** are covered by the blocking portions **822**. Therefore, the switch terminals **222** of the arm detection switches **210** cannot be inserted. In other words, the arm detection switches **210** that face the detection holes **236** covered by the blocking portions **822** are in the on state because the switch terminals **222** come into contact with the blocking portions **822**.

An arrangement pattern of the communication holes **821** and the blocking portions **822** that are formed in the first indicator member **920** is determined in advance based on predetermined rules depending on the tape type, in a similar way to the non-pressing portions **801** and the pressing portions **802** in the first embodiment. Therefore, not only the tape printer **1** can recognize the tape type by detecting the first indicator member **920**, but also a person can recognize the tape type by visually checking the first indicator member **920**.

As explained above, in the tape cassette **230** of the second embodiment, since the first indicator member **920** is affixed to the wall portion **235**, it is possible to change the arm indicator portion **820** that is formed on the wall portion **235**. Therefore, the common top case **231A** and the common bottom case **231B** can be used regardless of the type of the tape housed in the cassette case **231**. Further, since the first indicator member **920** is a member in the form of a film, it can be formed by press working at a low cost. It is therefore possible to reduce manufacturing costs of the tape cassette **230**. Note that the first indicator member **920** may be a member in the form of a sheet.

A tape cassette **330** of a third embodiment will be explained with reference to FIG. 15 to FIG. 19. In the tape cassette **330** of the third embodiment, an arm indicator portion **830** and a rear indicator portion **953** are formed on a top case **331A**. Note that the tape cassette **330** is the same as the tape cassette **30** according to the first embodiment except for some of the structural components. Therefore, the same structural components are denoted with the same reference numerals and an explanation thereof is omitted or simplified.

As shown in FIG. 19, the tape cassette **330** is provided with the top case **331A** and a bottom case **331B**. The top case **331A** will be explained with reference to FIG. 15 and FIG. 16. The top case **331A** is provided with a top wall **331E** that is formed in a rectangular shape that is longer in the left-right direction in a plan view. A rear edge portion of the top wall **331E** is provided with a left arc portion **339A**, which is formed in a substantially quarter arc shape that bulges toward the rear right in a plan view, and a right arc portion **338A**, which is formed in a substantially quarter arc shape that bulges toward the rear left in the plan view, such that they are arranged side by side in the left-right direction.

A middle portion **341A** that extends linearly in the left-right direction is formed between the right arc portion **338A** and the left arc portion **339A**.

As shown in FIG. 16, a plate-shaped protruding plate portion **342A** is provided that protrudes downward from the left arc portion **339A**, the right arc portion **338A** and the middle portion **341A**. A height dimension (a dimension in the up-down direction) of the protruding plate portion **342A** is the same as the height dimension from the top surface **30A** of the tape cassette **330** to the lower surface of the corner portions **32A** (refer to FIG. 9).

A second indicator plate portion **955**, which extends in a direction orthogonal to a surface of the protruding plate portion **342A**, is formed on the lower end of the protruding plate portion **342A**, the second indicator plate portion **955** being a flat surface portion that has a substantially triangular shape in a plan view and that corresponds to the rear support portion **8C** (refer to FIG. 2). The second indicator plate portion **955** is provided with the rear indicator portion **953**. The rear indicator portion **953** is similar to the rear indicator portion **950** of the first embodiment and an explanation thereof is thus omitted.

As shown in FIG. 15, a plate-shaped first indicator plate portion **930** is provided protruding downward from a central portion of the front end of the top wall **331E** of the top case **331A**. The first indicator plate portion **930** is formed in a substantially rectangular plate shape that is horizontally long in a front view. The first indicator plate portion **930** is a portion of the front surface of the arm portion **34** that is provided on the top case **331A**.

A cutout portion **931**, which is cut out in a vertically long rectangular shape in a front view, is formed in a lower left corner portion of the first indicator plate portion **930**. A convex portion **335A** that continuously protrudes to the right is provided from an upper end portion to a lower end portion of the right end face of the first indicator plate portion **930**. A convex portion **336A** that continuously protrudes to the left is provided from a central portion in the up-down direction to a lower end portion of the left end face of the first indicator plate portion **930**. A convex portion **337A** that continuously protrudes downward is provided from a left end portion to a right end portion of the lower end face of the first indicator plate portion **930**. A height dimension (a dimension in the up-down direction) of the first indicator plate portion **930** is the same as the height dimension of the tape cassette **330**. The first indicator plate portion **930** is provided with the arm indicator portion **830**. The arm indicator portion **830** is similar to the arm indicator portion **800** of the first embodiment and an explanation thereof is thus omitted.

Note that the pin portions **33A** are provided protruding downward from a lower surface of the top wall **331E**, in a similar way to the first embodiment. A height dimension of the pin portions **33A** is smaller than the height dimension of the first indicator plate portion **930** and the height dimension of the protruding plate portion **342A**.

The bottom case **331B** will be explained with reference to FIG. 17 and FIG. 18. The bottom case **331B** is formed in a box shape in which an upper portion opens. A rear edge portion of a bottom wall **331G** has a shape in which two substantially quarter arcs are provided side by side in a plan view in a central portion, corresponding to the shape of the rear edge portion of the top wall **331E**. A central portion in the left-right direction of a back wall **331M** is provided with a recessed portion **343B** that is recessed toward the front in the up-down direction. The recessed portion **343B** is a concave portion that is recessed in a substantially triangular



shape corresponding to the above-described second indicator plate portion 955 in a plan view.

A right guide wall 348B, which is a wall portion provided continuously to the lower semi-circular portion 38B, is provided on the left side of the lower semi-circular portion 38B. A groove portion 345B that is continuous from the upper end to the lower end is formed in the left end face of the right guide wall 348B. The right guide wall 348B is a portion of the front surface of the arm portion 34 that is provided on the upstream side, in the tape feed direction, of the discharge opening 34A in the bottom case 331B.

On the left side of the right guide wall 348B, a left guide wall 344B, which is a wall portion formed in a vertically long rectangular plate shape in a front view, is provided in a standing manner on the bottom wall 331G away from the right guide wall 348B. The left guide wall 344B is a portion of the front surface of the arm portion 34 that is provided in the vicinity of the discharge opening 34A in the bottom case 331B. A groove portion 346B that is continuous from the upper end to the lower end is formed in the right end face of the left guide wall 344B.

A cutout space that opens upwardly and that is surrounded by the right guide wall 348B, the left guide wall 344B and the bottom wall 331G is an indicator plate attachment portion 350B to which the above-described first indicator plate portion 930 is attached. In a portion of the bottom wall 331G between the right guide wall 348B and the left guide wall 344B, a groove portion 347B is formed along the left-right direction of the indicator plate attachment portion 350B.

A method for assembling the tape cassette 330 having the above-described structure will be explained with reference to FIG. 19. The operator houses the double-sided adhesive tape 58, the film tape 59 and the ink ribbon 60 respectively in predetermined positions of the bottom case 331B. Next, the operator puts the top case 331A on the bottom case 331B from above. At this time, the first indicator plate portion 930 is inserted between the right guide wall 348B and the left guide wall 344B, namely, into the indicator plate attachment portion 350B. At the same time, the second indicator plate portion 955 is inserted into the recessed portion 343B.

When the operator presses the top case 331A downward onto the bottom case 331B, the first indicator plate portion 930 slidingly moves downward in the indicator plate attachment portion 350B while being guided between the right guide wall 348B and the left guide wall 344B. Specifically, the convex portion 336A slidingly moves along the groove portion 346B, and the convex portion 335A slidingly moves along the groove portion 345B. At the same time, the second indicator plate portion 955 slidingly moves downward in the recessed portion 343B while being guided by the back wall 331M.

The plurality of pin portions 33A that are provided on the top case 331A are respectively fitted into the cylindrical holes of the plurality of boss portions 33B that are provided in the bottom case 331B. When the top case 331A is moved further downward, the fixing portion 38D of the top case 331A is fitted into the fixing hole 79 of the bottom case 331B. When the first indicator plate portion 930 is fitted into the indicator plate attachment portion 350B and the second indicator plate portion 955 is fitted into the recessed portion 343B, the convex portion 337A of the top case 331A is joined to the groove portion 347B of the bottom case 331B. This completes the attachment of the top case 331A to the bottom case 331B.

When the top case 331A is attached to the bottom case 331B, the second indicator plate portion 955 is included in

a portion of the bottom wall 331G in a similar way to the above-described rear surface portion 68 (refer to FIG. 11). The second indicator plate portion 955 is on the same plane (i.e., at the same height position) as the lower surface of the corner portions 32A (refer to FIG. 9). Therefore, when the tape cassette 330 is inserted in the cassette housing portion 8 (refer to FIG. 2), the second indicator plate portion 955 is supported from below by the rear support portion 8C and the rear indicator portion 953 is detected by the rear detection portion 300, in a similar way to the first embodiment.

As explained above, according to the tape cassette 330 of the third embodiment, the arm indicator portion 830 and the rear indicator portion 953 are formed on the top case 331A. Therefore, the common bottom case 331B can be used regardless of the type of the tape housed in the tape cassette 330, and it is thus possible to reduce manufacturing costs of the tape cassette 330. Further, the operator can attach the top case 331A provided with the arm indicator portion 830 to the bottom case 331B while confirming the tape housed in the bottom case 331B. Therefore, assembly errors of the cassette case 331 are reduced.

The operator can mount the arm indicator portion 830 and the rear indicator portion 953 on the tape cassette 330 by simply attaching the top case 331A to the bottom case 331B. Therefore, the workability of the tape cassette 330 in a manufacturing process is improved. Further, when the top case 331A is attached to the bottom case 331B, the first indicator plate portion 930 on which the arm indicator portion 830 is formed is guided downward by the right guide wall 348B and the left guide wall 344B. The second indicator plate portion 955 that is provided with the rear indicator portion 953 is guided downward by the back wall 331M. Therefore, the operator can accurately insert the first indicator plate portion 930 into the indicator plate attachment portion 350B, and thus the workability of the tape cassette 330 in the manufacturing process is further improved.

Note that it is needless to mention that the present disclosure is not limited to the above-described embodiments and various modifications are possible. For example, in the first embodiment, the first indicator member 900 is attached to the open portion 30D that is formed in a state in which the top case 31A is attached to the bottom case 31B. However, as shown in FIG. 21, a bottom case 431B may be provided with an attachment portion 430D to which a first indicator member 940 is attached.

Hereinafter, a tape cassette 430 of a first modified example, in which the bottom case 431B is provided with the attachment portion 430D to which the first indicator member 940 is attached, will be explained with reference to FIG. 20 and FIG. 21. Note that the tape cassette of the first modified example is structured in a similar way to the first embodiment except that the first indicator member 940 is attached. Therefore, in the following explanation, portions different from those of the first embodiment only will be explained and the other structural components are denoted with the same reference numerals and an explanation thereof will be omitted.

As shown in FIG. 20, the tape cassette 430 of the first modified example is provided with a top case 431A and the bottom case 431B. An extending portion 431D that is formed in a horizontally long rectangular plate shape in a front view is provided on the left side of the upper semi-circular portion 38A of the top case 431A. The extending portion 431D extends downward from the front end of the top wall 31E. The lower end face of the extending portion 431D is provided with two concave portions (not shown in



the drawings) that are recessed upward and arranged side by side in the left-right direction.

The bottom case **431B** will be explained with reference to FIG. **21**. The bottom case **431B** includes, on the left side of the lower semi-circular portion **38B**, the attachment portion **430D** that is a space in which the first indicator member **940** can be removably attached. The left end face of the lower semi-circular portion **38B** is provided with a groove portion **431J** that is continuously formed from the upper end to the lower end. In a front edge portion of a top surface of the bottom wall **31G**, two concave portions **430F** and **430E** that are recessed downward are provided from the lower semi-circular portion **38B** toward the left such that they are arranged side by side with an interval between them. The concave portions **430E** and **430F** are provided along the front edge of the lower end face of the arm portion **34** in the bottom case **331B**.

A structure of the first indicator member **940** will be explained with reference to FIG. **21**. The first indicator member **940** is formed in a rectangular flat plate shape that is horizontally long in a front view. The upper end face of the first indicator member **940** is provided with cylindrically-shaped convex portions **941** and **942** that protrude upward such that they are arranged side by side in the left-right direction. The lower end face of the first indicator member **940** is provided with cylindrically-shaped convex portions **943** and **944** that protrude downward such that they are arranged side by side in the left-right direction. A convex portion **945** that continuously protrudes to the right is provided from the upper end to the lower end of the right end face of the first indicator member **940**. The first indicator member **940** is provided with the arm indicator portion **800**, which is the same as that of the first embodiment.

A method for assembling the tape cassette **430** will be explained with reference to FIG. **20** and FIG. **21**. As shown in FIG. **21**, the operator attaches the first indicator member **940** to the attachment portion **430D** of the bottom case **431B**. Specifically, the first indicator member **940** is caused to move downward from above the attachment portion **430D**. At this time, the first indicator member **940** is slidingly moved downward so that the convex portion **945** slides along the groove portion **431J**. The convex portions **943** and **944** of the first indicator member **940** are respectively fitted into the concave portions **430E** and **430F** of the bottom case **431B**. Next, as shown in FIG. **20**, the operator puts the top case **431A** on the bottom case **431B**. At this time, the pin portions **33A** of the top case **431A** are fitted into the boss portions **33B** of the bottom case **431B**. The convex portions **941** and **942** of the first indicator member **940** are fitted into the two concave portions (not shown in the drawings) provided in the lower end face of the extending portion **431D**. This completes the assembly of the tape cassette **430**.

According to the tape cassette **430** of the first modified example, the tape housed in the bottom case **431B** can be visually checked through the attachment portion **430D**. While confirming the tape housed in the bottom case **431B**, the operator can attach the first indicator member **940** that indicates the correct tape type to the bottom case **431B**, and it is thus possible to suppress assembly errors of the tape cassette **430**.

As a modified example of the third embodiment, at least one of the arm indicator portion **830** and the rear indicator portion **953** may be provided on a member that can be attached to and removed from a top case **531A**. Hereinafter, a tape cassette **530** of a second modified example, in which the arm indicator portion **830** and the rear indicator portion

**953** are respectively provided on members that can be attached to and removed from the top case **531A**, will be explained with reference to FIG. **22** and FIG. **23**. Note that the tape cassette **530** of the second modified example is structured in a similar way to the third embodiment except that the arm indicator portion **830** and the rear indicator portion **953** are respectively provided on the members that can be attached to and removed from the top case **531A**. Therefore, in the following explanation, portions different from those of the third embodiment only will be explained and the other structural components are denoted with the same reference numerals and an explanation thereof will be omitted.

The top case **531A** will be explained with reference to FIG. **22** and FIG. **23**. As shown in FIG. **22**, on the left side of the upper semi-circular portion **38A**, a plate-shaped attachment portion **530D** is extended downward from a front end portion of the top wall **31E** of the top case **531A**. When viewed from the front, the attachment portion **530D** has a shape obtained by rotating an L-shape by 90 degrees in the clockwise direction. The attachment portion **530D** is provided with: a fixing portion **531D** which is formed continuously to a left end portion of the upper semi-circular portion **38A** and which has a horizontally long rectangular shape in a front view; and a downwardly extending guide portion **532D** which is formed continuously to the left side of the attachment portion **530D** and which has a vertically long rectangular shape in the front view. The lower end face of the fixing portion **531D** is provided with two concave portions (not shown in the drawings) that are recessed upward and arranged side by side in the left-right direction. A groove portion **533D** is formed that is continuous from the upper end to the lower end of the right end face of the guide portion **532D**. A plate-shaped first indicator member **935** can be attached to and removed from the attachment portion **530D**.

The first indicator member **935** will be explained with reference to FIG. **22**. The first indicator member **935** is formed in a substantially rectangular plate shape that is horizontally long in a front view. The upper end face of the first indicator member **935** is provided with two upwardly protruding convex portions **537A** and **538A** such that they are arranged side by side in the left-right direction. A convex portion **535A** that continuously protrudes to the right is provided from the upper end to the lower end of the right end face of the first indicator member **935**. A convex portion **536A** that continuously protrudes to the left is provided from the upper end to the lower end of the left end face of the first indicator member **935**. The first indicator member **935** is provided with the arm indicator portion **830**, which is the same as that of the third embodiment.

A method for attaching the first indicator member **935** to the attachment portion **530D** will be explained with reference to FIG. **22**. The operator moves the first indicator member **935** upward from below the attachment portion **530D**. At this time, the first indicator member **935** is slidingly moved upward so that the convex portion **536A** slides along the groove portion **533D**. The convex portions **537A** and **538A** of the first indicator member **935** are respectively fitted into the two concave portions of the top case **531A**. This completes the attachment of the first indicator member **935** to the top case **531A**.

As shown in FIG. **23**, a plate-shaped extending plate portion **442A** is provided that extends downward from the left arc portion **339A**, the right arc portion **338A** and the middle portion **341A** of the top case **531A**. The extending plate portion **442A** is formed by a left plate portion **443A**



that extends downward from the left arc portion 339A, a right plate portion 444A that extends downward from the right arc portion 338A, and a middle plate portion 445A that extends downward from the middle portion 341A. A height dimension (a dimension in the up-down direction) of the extending plate portion 442A is the same as the height dimension from the top surface 30A of the tape cassette 530 to the lower surface of the corner portions 32A (refer to FIG. 9). A left end portion of the lower end face of the left plate portion 443A, a right end portion of the lower end face of the right plate portion 444A, and a right end portion of the lower end face of the middle plate portion 445A are respectively provided with concave portions (not shown in the drawings) that are recessed upward.

As shown in FIG. 23, a second indicator member 956 can be attached to and removed from the extending plate portion 442A. The second indicator member 956 is formed in a flat plate shape and has a substantially triangular shape in a plan view. A right end portion, a left end portion and a front end portion of the second indicator member 956 are respectively provided with convex portions 957, 958 and 959 that protrude upward from a top surface. The second indicator member 956 is provided with the rear indicator portion 953 in a similar way to the third embodiment. When the second indicator member 956 is attached to the extending plate portion 442A, the convex portions 957, 958 and 959 of the second indicator member 956 are respectively fitted into three concave portions that are formed in a lower end portion of the extending plate portion 442A of the top case 531A.

When the tape cassette 530 of the second modified example is assembled, the top case 531A, to which the first indicator member 935 and the second indicator member 956 have been attached, is attached to the bottom case 331B which is the same as that of the third embodiment. In a state in which the top case 531A is attached to the bottom case 331B, the second indicator member 956 is included in a portion of the bottom wall 331G (refer to FIG. 19) in a similar way to the above-described second indicator plate portion 955 (refer to FIG. 16). Therefore, when the tape cassette 530 is inserted in the cassette housing portion 8 (refer to FIG. 2), the second indicator member 956 is supported from below by the rear support portion 8C, and the rear indicator portion 953 is detected by the rear detection portion 300.

According to the tape cassette 530 of the second modified example, the first indicator member 935 and the second indicator member 956 are provided independently from the top case 531A and the bottom case 331B. Therefore, the common top case 531A and the common bottom case 331B can be respectively used regardless of the type of the tape housed in the tape cassette.

As shown in FIG. 24, as a modified example of the tape cassette 230 of the second embodiment, after a first indicator member 925 is adhered to a bottom case 631B, a top case may be attached to the bottom case 631B to form a cassette case. A tape cassette 630 of a third modified example, in which the first indicator member 925 is adhered to the bottom case 631B, will be explained with reference to FIG. 24.

The tape cassette 630 of the third modified example is provided with the bottom case 631B that has a substantially box shape. A wall portion 635 that is continuously provided from the lower semi-circular portion 38B to the left is formed in the bottom case 631B along a front end portion of the bottom wall 31G. Detection holes 266 are formed in the wall portion 635 in a similar way to the second embodiment. The first indicator member 925 in the form of a film is

adhered to a front surface of the wall portion 635. The first indicator member 925 is provided with the arm indicator portion 820 in a similar way to the second embodiment.

Also in the tape cassette 630 of the third modified example, it is possible to attach the first indicator member 925 to the bottom case 631B while visually checking a surface of the tape housed in the bottom case 631B. The operator can attach the first indicator member 925 that indicates the correct tape type while confirming the type of the tape housed in the bottom case 631B, and it is thus possible to suppress assembly errors of the tape cassette 630.

In the above-described embodiments and modified examples, the arm indicator portions 800, 820 and 830 include the plurality of indicator portions. However, it is sufficient if each indicator portion includes at least one indicator hole (the non-pressing portion 801 in the present embodiment) and indicates the tape type. Although the non-pressing portion 801 is a through hole having a vertically long rectangular shape, the non-pressing portion 801 may have another shape. For example, the non-pressing portion 801 may have any opening shape, such as a square shape, a circular shape or the like, as long as the arm detection switch 210 can be inserted.

Further, although the rear indicator portions 950 and 953 include the plurality of indicator portions, it is sufficient if each indicator portion includes at least one indicator hole (the non-pressing portion 951 in the present embodiment) and indicates the tape type. The non-pressing portion 951 need not necessarily be a circular hole, and it may have a square shape, a rectangular shape or the like as long as the rear detection switch 310 can be inserted.

Although in the first embodiment, the latch hole 804 provided in the arm front surface 35 is provided in the first indicator member 900, it may be provided in the top case 31A. In this case, the first indicator member 900 need not be provided with the latch hole 804. Further, the latch hole 804 may be provided in a boundary portion between the first indicator member 900 and the top case 31A. Further, an upper end position of the indicator portions 800B and 800C may be used as a boundary between the first indicator member 900 and the top case 31A.

In the above-described embodiments and modified examples, the non-pressing portions 801 and the latch hole 804 are independent hole portions. In place of these, the plurality of non-pressing portions 801 may be included in a single continuous hole portion, or the non-pressing portions 801 and the latch hole 804 may be included in a single continuous hole portion.

In the first embodiment, the groove portion 901 is formed on the upper end face of the first indicator member 900, and the convex portion 907 is formed on the lower end face of the first indicator member 900. In the open portion 30D, the convex portion 30F is formed corresponding to the groove portion 901 and the groove portion 30E is formed corresponding to the convex portion 907. In place of these, a convex portion may be formed on the upper end face of the first indicator member 900, and a groove portion corresponding to this convex portion may be provided in the open portion 30D. A groove portion may be formed in the lower end face of the first indicator member 900, and a convex portion corresponding to this groove portion may be provided on the open portion 30D.

In the second embodiment, the first indicator member 920 is provided with the hole portion that corresponds to the latch hole 804. In place of this, the first indicator member 920 may have a size that covers the arm indicator portion 820 only.



The apparatus and methods described above with reference to the various embodiments are merely examples. It goes without saying that they are not confined to the depicted embodiments. While various features have been described in conjunction with the examples outlined above, various alternatives, modifications, variations, and/or improvements of those features and/or examples may be possible. Accordingly, the examples, as set forth above, are intended to be illustrative. Various changes may be made without departing from the broad spirit and scope of the underlying principles.

What is claimed is:

**1.** A tape cassette comprising:

a cassette case having a first end portion and a second end portion separated from the first end portion in a first direction, and having a third end portion and a fourth end portion separated from the third end portion in a second direction;

a first spool positioned in the cassette case, the first spool positioned closer to the third end portion of the cassette case than to the fourth end portion in the second direction, the first spool positioned closer to the second end portion than to the first end portion in the first direction;

a ribbon spool positioned in the cassette case, the ribbon spool positioned closer to the fourth end portion than to the third end portion in the second direction; and

a tape drive roller rotatable about an axis extending in a third direction, the tape drive roller configured to allow a tape to be discharged from inside of the cassette case, the tape drive roller positioned closer to the first end portion of the cassette case in the first direction than to the second end portion, the tape drive roller positioned closer to the third end portion of the cassette case than the fourth end portion of the cassette in the second direction, wherein

the cassette case includes an arm positioned at the first end portion, the arm extending in the second direction, the arm having a first outer surface facing a portion of the cassette case in the first direction and a second outer surface facing away from the cassette case in the first direction, and the arm has an exit configured to allow an ink ribbon to be discharged toward the tape drive roller from inside of the cassette case, wherein

the second outer surface includes a first indicator and a second indicator in a predetermined pattern, a position of the first indicator is different from a position of the second indicator in the second direction and the third direction,

wherein the second outer surface is detachably attached to the arm.

**2.** The tape cassette according to claim 1, wherein each of the first indicator and the second indicator is one of a hole extending through the second outer surface and a predetermined area of the second outer surface.

**3.** The tape cassette according to claim 2, wherein the predetermined area is continuous with the second outer surface.

**4.** The tape cassette according to claim 1, wherein the first indicator is a hole extending through the second outer surface, and

wherein the second indicator is a predetermined area of the second outer surface.

**5.** The tape cassette according to claim 4, wherein the predetermined area is continuous with the second outer surface.

**6.** The tape cassette according to claim 1, wherein the second direction is orthogonal to the first direction, and wherein the third direction is orthogonal to the first direction and the second direction.

**7.** The tape cassette according to claim 6, further comprising:

a tape wound around the first spool.

**8.** The tape cassette according to claim 7, wherein the first indicator indicates a width of the tape.

**9.** The tape cassette according to claim 1, further comprising:

a tape wound around the first spool.

**10.** The tape cassette according to claim 9, wherein the first indicator indicates a width of the tape.

**11.** The tape cassette according to claim 4, wherein the second direction is orthogonal to the first direction, and wherein the third direction is orthogonal to the first direction and the second direction.

**12.** The tape cassette according to claim 11, further comprising:

a tape wound around the first spool.

**13.** The tape cassette according to claim 12, wherein the first indicator indicates a width of the tape.

**14.** The tape cassette according to claim 4, further comprising:

a tape wound around the first spool.

**15.** The tape cassette according to claim 14, wherein the first indicator indicates a width of the tape.

**16.** The tape cassette according to claim 5, wherein the second direction is orthogonal to the first direction, and wherein the third direction is orthogonal to the first direction and the second direction.

**17.** The tape cassette according to claim 16, further comprising:

a tape wound around the first spool.

**18.** The tape cassette according to claim 17, wherein the first indicator indicates a width of the tape.

**19.** The tape cassette according to claim 5, further comprising:

a tape wound around the first spool.

**20.** The tape cassette according to claim 19, wherein the first indicator indicates a width of the tape.