



US012138059B2

(12) **United States Patent**
Olson et al.

(10) **Patent No.:** **US 12,138,059 B2**
(45) **Date of Patent:** ***Nov. 12, 2024**

(54) **MASKED RING ELECTRODES**

(71) Applicant: **St. Jude Medical, Cardiology Division, Inc.**, St. Paul, MN (US)

(72) Inventors: **Gregory K. Olson**, Elk River, MN (US); **Travis Dahlen**, Forest Lake, MN (US); **Brian M. Monahan**, Elk River, MN (US); **Loell B. Moon**, Ham Lake, MN (US)

(73) Assignee: **St. Jude Medical, Cardiology Division, Inc.**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/089,116**

(22) Filed: **Dec. 27, 2022**

(65) **Prior Publication Data**

US 2023/0210432 A1 Jul. 6, 2023

Related U.S. Application Data

(63) Continuation of application No. 16/042,336, filed on Jul. 23, 2018, now Pat. No. 11,647,935.
(Continued)

(51) **Int. Cl.**
A61B 18/00 (2006.01)
A61B 5/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/283** (2021.01); **A61B 5/25** (2021.01); **A61B 5/287** (2021.01); **A61B 5/6858** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC **A61B 5/283**; **A61B 5/287**; **A61B 5/6858**; **A61B 18/1492**; **A61B 5/4848**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,522,212 A 6/1985 Gelinis et al.
4,690,155 A 9/1987 Hess
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2015202258 A1 5/2015
AU 2016204351 A1 1/2017
(Continued)


Primary Examiner — Adam Z Minchella

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(57) **ABSTRACT**

A partially-masked electrode includes a conductive material and an insulated coating having an outer surface. The insulated coating defines a contoured opening that exposes or reveals an area of the conductive material, wherein the contoured opening has an upper perimeter at the outer surface of the insulated coating. When the upper perimeter of the insulated surface coating is placed in contact with a tissue of interest, wherein the tissue of interest is proximate a blood pool, the insulated coating creates a seal between the blood pool and the contoured opening so that no blood in the blood pool can contact the conductive material. This seal reduces or eliminates the reception of far field effects in the blood pool by the electrode, making it easier to locate and diagnose unhealthy tissue.

19 Claims, 20 Drawing Sheets



| Related U.S. Application Data | | | | | |
|--------------------------------------|---|---------------|---------|--------------------------|--|
| (60) | Provisional application No. 62/536,369, filed on Jul. 24, 2017. | 7,257,435 B2 | 8/2007 | Plaza | |
| | | 7,306,594 B2 | 12/2007 | Collins et al. | |
| | | 7,412,274 B2 | 8/2008 | Mejia | |
| | | 7,429,261 B2 | 9/2008 | Kunis et al. | |
| | | 7,561,907 B2 | 7/2009 | Fuimaono et al. | |
| (51) | Int. Cl. | 7,608,063 B2 | 10/2009 | Le et al. | |
| | <i>A61B 5/25</i> (2021.01) | 7,625,365 B2 | 12/2009 | McGlinch et al. | |
| | <i>A61B 5/283</i> (2021.01) | 7,666,204 B2 | 2/2010 | Thornton et al. | |
| | <i>A61B 5/287</i> (2021.01) | 7,959,601 B2 | 6/2011 | McDaniel et al. | |
| | <i>A61B 18/14</i> (2006.01) | 7,985,215 B2 | 7/2011 | Guo et al. | |
| | <i>A61N 1/05</i> (2006.01) | 8,103,327 B2 | 1/2012 | Harlev et al. | |
| (52) | U.S. Cl. | 8,137,321 B2 | 3/2012 | Argentine | |
| | CPC <i>A61B 18/1492</i> (2013.01); <i>A61N 1/056</i> | 8,157,796 B2 | 4/2012 | Collins et al. | |
| | (2013.01); <i>A61B 5/4848</i> (2013.01); <i>A61B</i> | 8,221,390 B2 | 7/2012 | Pal et al. | |
| | <i>2018/00071</i> (2013.01); <i>A61B 2018/00083</i> | 8,224,416 B2 | 7/2012 | de la Rama et al. | |
| | (2013.01); <i>A61B 2018/00107</i> (2013.01); <i>A61B</i> | 8,271,099 B1 | 9/2012 | Swanson | |
| | <i>2018/00267</i> (2013.01); <i>A61B 2018/00357</i> | 8,273,016 B2 | 9/2012 | O'Sullivan | |
| | (2013.01); <i>A61B 2018/00363</i> (2013.01); <i>A61B</i> | 8,376,990 B2 | 2/2013 | Ponzi et al. | |
| | <i>2018/00839</i> (2013.01); <i>A61B 2018/1497</i> | 8,391,947 B2 | 3/2013 | Urman et al. | |
| | (2013.01) | 8,447,377 B2 | 5/2013 | Harlev et al. | |
| (58) | Field of Classification Search | 8,486,063 B2 | 7/2013 | Werneth et al. | |
| | CPC <i>A61B 2018/00071</i> ; <i>A61B 2018/00083</i> ; | 8,560,086 B2 | 10/2013 | Just et al. | |
| | <i>A61B 2018/00107</i> ; <i>A61B 2018/00267</i> ; | 8,565,894 B2 | 10/2013 | Vetter et al. | |
| | <i>A61B 2018/00357</i> ; <i>A61B 2018/00363</i> ; | 8,603,069 B2 | 12/2013 | Selkee | |
| | <i>A61B 2018/00839</i> ; <i>A61B 2018/1497</i> ; | 8,608,703 B2 | 12/2013 | Riles et al. | |
| | <i>A61N 1/056</i> | 8,649,880 B1 | 2/2014 | Parker, Jr. | |
| | See application file for complete search history. | 8,700,120 B2 | 4/2014 | Koblisch | |
| (56) | References Cited | 8,700,129 B2 | 4/2014 | Hauck et al. | |
| | U.S. PATENT DOCUMENTS | 8,706,193 B2 | 4/2014 | Govari et al. | |
| | 4,847,980 A 7/1989 Witkowski et al. | 8,744,599 B2 | 6/2014 | Tegg | |
| | 5,029,585 A 7/1991 Lieber et al. | 8,755,861 B2 | 6/2014 | Harlev et al. | |
| | 5,224,939 A 7/1993 Holman et al. | 8,777,929 B2 | 7/2014 | Schneider et al. | |
| | 5,380,301 A 1/1995 Prichard et al. | 8,792,962 B2 | 7/2014 | Esguerra et al. | |
| | 5,400,783 A 3/1995 Pomeranz et al. | 8,814,824 B2 | 8/2014 | Kauphusman et al. | |
| | 5,456,254 A 10/1995 Pietroski et al. | 8,814,825 B2 | 8/2014 | Tegg et al. | |
| | 5,626,136 A 5/1997 Webster, Jr. | 8,882,705 B2 | 11/2014 | McDaniel et al. | |
| | 5,643,255 A 7/1997 Organ | 8,894,610 B2 | 11/2014 | Macnamara et al. | |
| | 5,702,438 A 12/1997 Avitall | 8,996,091 B2 | 3/2015 | de la Rama et al. | |
| | 5,715,817 A 2/1998 Stevens-Wright et al. | 9,017,308 B2 | 4/2015 | Klisch et al. | |
| | 5,715,832 A 2/1998 Koblisch et al. | 9,033,917 B2 | 5/2015 | Magana et al. | |
| | 5,772,590 A 6/1998 Webster, Jr. | 9,044,245 B2 | 6/2015 | Condie et al. | |
| | 5,827,278 A 10/1998 Webster, Jr. | 9,050,010 B2 | 6/2015 | Bui et al. | |
| | 5,876,373 A 3/1999 Giba et al. | 9,101,733 B2 | 8/2015 | McDaniel | |
| | 5,964,757 A 10/1999 Ponzi | 9,204,929 B2 | 12/2015 | Solis | |
| | 6,029,091 A 2/2000 de la Rama et al. | 9,216,056 B2 | 12/2015 | Datta et al. | |
| | 6,071,282 A 6/2000 Fleischman | 9,247,990 B2 | 2/2016 | Kauphusman et al. | |
| | 6,074,379 A 6/2000 Prichard | 9,326,815 B2 | 5/2016 | Watson | |
| | 6,123,699 A 9/2000 Webster, Jr. | 9,339,331 B2 | 5/2016 | Tegg et al. | |
| | 6,171,277 B1 1/2001 Ponzi | 9,339,631 B2 | 5/2016 | Graham et al. | |
| | 6,183,463 B1 2/2001 Webster, Jr. | 9,433,751 B2 | 9/2016 | Ponzi et al. | |
| | 6,198,974 B1 3/2001 Webster, Jr. | 9,433,752 B2 | 9/2016 | Jimenez et al. | |
| | 6,210,407 B1 4/2001 Webster | 9,468,495 B2 | 10/2016 | Kunis et al. | |
| | 6,267,746 B1 7/2001 Bumbalough | 9,486,280 B2 | 11/2016 | Koblisch et al. | |
| | 6,273,404 B1 8/2001 Holman et al. | 9,486,282 B2 | 11/2016 | Solis | |
| | 6,415,187 B1 7/2002 Kuzma et al. | 9,539,413 B2 | 1/2017 | Ogle | |
| | 6,491,681 B1 12/2002 Kunis et al. | 9,649,158 B2 | 5/2017 | Datta et al. | |
| | 6,522,932 B1 2/2003 Kuzma et al. | 9,687,166 B2 | 6/2017 | Subramaniam et al. | |
| | 6,554,794 B1 4/2003 Mueller et al. | 9,693,733 B2 | 7/2017 | Altmann et al. | |
| | 6,652,515 B1 11/2003 Maguire et al. | 9,694,159 B2 | 7/2017 | Schneider et al. | |
| | 6,658,302 B1 12/2003 Kuzma et al. | 9,694,161 B2 | 7/2017 | Selkee | |
| | 6,692,492 B2 2/2004 Simpson et al. | 9,788,895 B2 | 10/2017 | Solis | |
| | 6,837,886 B2 1/2005 Collins et al. | 9,820,664 B2 | 11/2017 | Hoitink et al. | |
| | 6,961,602 B2 11/2005 Fuimaono et al. | 9,844,645 B2 | 12/2017 | Pai et al. | |
| | 7,004,937 B2 2/2006 Lentz et al. | 9,848,795 B2 | 12/2017 | Marecki et al. | |
| | 7,027,851 B2 4/2006 Mejia | 9,872,717 B2* | 1/2018 | Bencini A61B 18/02 | |
| | 7,089,045 B2 8/2006 Fuimaono et al. | 9,907,480 B2 | 3/2018 | Basu et al. | |
| | 7,099,712 B2 8/2006 Fuimaono et al. | 9,919,132 B2 | 3/2018 | Tegg et al. | |
| | 7,214,220 B2 5/2007 McGlinch et al. | 9,949,656 B2 | 4/2018 | Wu et al. | |
| | 7,217,256 B2 5/2007 Di Palma | 9,986,949 B2 | 6/2018 | Govari et al. | |
| | 7,228,164 B2 6/2007 Fuimaono et al. | 10,004,877 B2 | 6/2018 | Tegg | |
| | 7,255,695 B2 8/2007 Falwell et al. | 10,034,637 B2 | 7/2018 | Harlev et al. | |
| | | 10,052,457 B2 | 8/2018 | Nguyen et al. | |
| | | 10,065,019 B2 | 9/2018 | Hamuro et al. | |
| | | 10,099,036 B2 | 10/2018 | Heideman et al. | |
| | | 10,118,022 B2 | 11/2018 | Helgeson et al. | |
| | | 10,143,394 B2 | 12/2018 | Solis | |
| | | 10,285,610 B2 | 5/2019 | Wu | |
| | | 10,322,261 B2 | 6/2019 | Pai et al. | |
| | | 10,362,952 B2 | 7/2019 | Basu et al. | |

(56)

References Cited

U.S. PATENT DOCUMENTS

10,362,954 B2 7/2019 de la Rama et al.
 10,376,170 B2 8/2019 Quinn et al.
 10,384,036 B2 8/2019 Romoscanu
 10,398,500 B2 9/2019 Huszar et al.
 10,478,325 B2 11/2019 Syed
 10,506,938 B2 12/2019 Wu et al.
 10,537,259 B2 1/2020 Wu et al.
 10,542,899 B2 1/2020 Wu et al.
 10,556,091 B2 2/2020 Truhler et al.
 10,575,742 B2 3/2020 Wu et al.
 10,575,745 B2 3/2020 Solis
 10,578,737 B2 3/2020 Gliner et al.
 10,595,738 B2 3/2020 Sterrett et al.
 10,595,740 B2 3/2020 Hoitink et al.
 10,602,948 B2 3/2020 Wu et al.
 10,646,692 B2 5/2020 Tegg et al.
 10,653,423 B2 5/2020 Starnes
 10,702,177 B2 7/2020 Aujla
 10,702,677 B2 7/2020 Okamura et al.
 10,737,060 B2 8/2020 Gupta et al.
 10,835,712 B2 11/2020 Wada
 10,842,990 B2 11/2020 de la Rama et al.
 10,857,349 B2 12/2020 de la Rama et al.
 10,869,992 B2 12/2020 Pai et al.
 10,898,685 B2 1/2021 Tegg
 10,912,925 B2 2/2021 Houck
 10,953,196 B2 3/2021 Raab et al.
 10,966,623 B2 4/2021 Wu et al.
 10,966,753 B2 4/2021 Coyle et al.
 10,967,150 B2 4/2021 Helgeson et al.
 10,987,045 B2 4/2021 Basu et al.
 11,033,715 B2 6/2021 Beeckler et al.
 11,039,772 B2 6/2021 Wu et al.
 11,039,773 B2 6/2021 Sterrett et al.
 11,083,400 B2 8/2021 Hoitink et al.
 11,116,436 B2 9/2021 Wu et al.
 11,116,476 B2 9/2021 Buessler et al.
 11,141,568 B2 10/2021 Hsueh et al.
 11,160,482 B2 11/2021 Solis
 11,172,858 B2 11/2021 Olson et al.
 11,272,886 B2 3/2022 Harley et al.
 2001/0012918 A1 8/2001 Swanson
 2002/0165484 A1 11/2002 Bowe et al.
 2003/0212395 A1 11/2003 Woloszko et al.
 2004/0162554 A1 8/2004 Lee et al.
 2004/0181139 A1 9/2004 Falwell et al.
 2005/0159741 A1 7/2005 Paul et al.
 2007/0005053 A1* 1/2007 Dando A61B 18/1492
 606/41
 2007/0299490 A1* 12/2007 Yang A61N 1/056
 607/116
 2009/0171274 A1* 7/2009 Harlev A61B 5/6859
 604/95.04
 2009/0198300 A1 8/2009 Zhang et al.
 2010/0219085 A1 9/2010 Oviatt, Jr.
 2011/0118726 A1 5/2011 de la Rama et al.
 2011/0213231 A1 9/2011 Hall et al.
 2012/0130220 A1 5/2012 Maskara et al.
 2012/0143298 A1 6/2012 Just et al.
 2012/0271302 A1 10/2012 Behl et al.
 2012/0296232 A1 11/2012 Ng
 2013/0172715 A1 7/2013 Just et al.
 2013/0253504 A1 9/2013 Fang
 2013/0274582 A1 10/2013 Afonso et al.
 2014/0058197 A1 2/2014 Salahieh et al.
 2014/0100639 A1 4/2014 Lee et al.
 2014/0200639 A1 7/2014 de la Rama
 2014/0296902 A1 10/2014 Huszar et al.
 2014/0316496 A1 10/2014 Masson et al.
 2014/0350564 A1 11/2014 Huszar et al.
 2015/0080715 A1* 3/2015 Deno A61B 8/5238
 600/424
 2015/0105645 A1 4/2015 Subramaniam et al.
 2015/0119911 A1 4/2015 Mckenzie
 2015/0141785 A1 5/2015 Hayam et al.

2015/0159741 A1 6/2015 Versteyhe et al.
 2015/0351652 A1 12/2015 Marecki et al.
 2016/0143588 A1 5/2016 Hoitink et al.
 2016/0213423 A1 7/2016 Kauphusman et al.
 2016/0213916 A1 7/2016 de la Rama
 2016/0278851 A1 9/2016 Mannion et al.
 2016/0317094 A1 11/2016 Byrd et al.
 2016/0331254 A1 11/2016 Tegg et al.
 2016/0331933 A1 11/2016 Knutsen
 2016/0374753 A1 12/2016 Wu et al.
 2017/0000365 A1 1/2017 Wu et al.
 2017/0042449 A1 2/2017 Deno et al.
 2017/0100075 A1 4/2017 Eliason et al.
 2017/0112404 A1 4/2017 de la Rama et al.
 2017/0112405 A1 4/2017 Sterrett et al.
 2017/0319269 A1 11/2017 Oliverius et al.
 2017/0367756 A1 12/2017 Sliwa et al.
 2018/0042667 A1 2/2018 Pappone et al.
 2018/0050190 A1 2/2018 Masson
 2018/0070845 A1 3/2018 Hoitink et al.
 2018/0085064 A1 3/2018 Auerbach et al.
 2018/0116539 A1 5/2018 Olson et al.
 2018/0161093 A1 6/2018 Basu et al.
 2018/0229030 A1 8/2018 Dubuclet et al.
 2018/0369574 A1 12/2018 Dubuclet et al.
 2019/0009052 A1 1/2019 Oliverius et al.
 2019/0192826 A1 6/2019 Wada
 2020/0138378 A1 5/2020 de la Rama et al.
 2020/0253496 A1 8/2020 Deno et al.
 2020/0405166 A1 12/2020 Wu et al.
 2021/0145342 A1 5/2021 Wang
 2021/0187246 A1 6/2021 Houck
 2021/0204871 A1 7/2021 Goedeke et al.
 2021/0268234 A1 9/2021 Helgeson et al.
 2021/0298656 A1 9/2021 Wu et al.
 2021/0361216 A1 11/2021 Hoitink et al.
 2021/0401345 A1 12/2021 Wu et al.
 2022/0023594 A1 1/2022 Pai
 2022/0054066 A1 2/2022 Solis
 2022/0061727 A1 3/2022 Olson et al.

FOREIGN PATENT DOCUMENTS

AU 2016204353 A1 1/2017
 AU 2016204355 A1 1/2017
 CA 2934209 A1 12/2016
 CA 2934211 A1 12/2016
 CA 2934214 A1 12/2016
 CN 101927053 B 1/2015
 CN 103157168 B 4/2015
 CN 101797181 B 12/2015
 CN 105960201 A 9/2016
 CN 106264715 A 1/2017
 CN 106264716 A 1/2017
 CN 106308790 A 1/2017
 CN 106859765 A 6/2017
 CN 206880930 U 1/2018
 CN 104958824 B 12/2018
 CN 104434083 B 4/2019
 CN 104968261 B 5/2019
 CN 105592778 B 7/2019
 CN 110536646 A 12/2019
 CN 111657866 A 9/2020
 CN 106264715 B 11/2020
 CN 106264716 B 11/2020
 CN 106308790 B 6/2021
 CN 107529958 B 7/2021
 CN 109310469 B 7/2021
 CN 109641121 B 9/2021
 CN 109952123 B 9/2021
 CN 110545874 B 9/2021
 CN 110559544 B 9/2021
 CN 113425304 A 9/2021
 CN 105615994 B 10/2021
 CN 109963610 B 11/2021
 CN 108289709 B 3/2022
 EP 0889744 B1 1/2004
 EP 1254641 B1 11/2008
 EP 1690564 B1 4/2009

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP 1723981 B1 8/2010
 EP 2135634 B1 10/2011
 EP 2018203 B1 6/2012
 EP 1814450 B1 1/2013
 EP 2269532 B1 3/2013
 EP 2664295 A1 11/2013
 EP 2604306 81 1/2014
 EP 2752153 A1 7/2014
 EP 2907462 A1 8/2015
 EP 2915555 A1 9/2015
 EP 2732843 B1 1/2016
 EP 1968679 B1 9/2016
 EP 2241279 B1 9/2016
 EP 3114987 A1 1/2017
 EP 3115076 A4 10/2017
 EP 3117863 A4 10/2017
 EP 3111871 B1 3/2018
 EP 3111872 B1 4/2018
 EP 3057488 B1 5/2018
 EP 2848226 B1 7/2018
 EP 3363397 A1 8/2018
 EP 3391928 A1 10/2018
 EP 3122276 B1 11/2018
 EP 3398549 A1 11/2018
 EP 1759668 B1 12/2018
 EP 3037122 B1 12/2018
 EP 2234537 B1 1/2019
 EP 2569040 B1 2/2019
 EP 3023052 B1 3/2019
 EP 3466363 A1 4/2019
 EP 2550989 B1 6/2019
 EP 3512589 A1 7/2019
 EP 3512590 A1 7/2019
 EP 3527125 A1 8/2019
 EP 3531903 A1 9/2019
 EP 3434218 B1 2/2020
 EP 2908723 B1 3/2020
 EP 3114987 B1 8/2020
 EP 3178516 B1 9/2020
 EP 3738508 A1 11/2020
 EP 3738509 A1 11/2020
 EP 3340916 B1 12/2020
 EP 3579908 B1 12/2020
 EP 3750475 A1 12/2020
 EP 2155301 B1 4/2021
 EP 3432820 B1 4/2021
 EP 3579758 B1 5/2021
 EP 2809254 B1 6/2021
 EP 3508245 B1 7/2021
 EP 3858277 A1 8/2021
 EP 3791820 B9 4/2022
 IL 246415 B 12/2019

JP 4545384 B2 7/2010
 JP 4887810 B2 2/2012
 JP 4940332 B2 3/2012
 JP 2012055602 A 3/2012
 JP 2012200509 A 10/2012
 JP 5154031 B2 2/2013
 JP 5193190 B2 5/2013
 JP 5372314 B2 12/2013
 JP 2014014713 A 1/2014
 JP 5550150 B2 5/2014
 JP 5762697 B2 6/2015
 JP 5908270 B2 4/2016
 JP 5944331 B2 7/2016
 JP 6050522 B2 12/2016
 JP 2017012750 A 1/2017
 JP 2017012755 A 1/2017
 JP 2017038919 A 2/2017
 JP 2017051211 A 3/2017
 JP 2017104552 A 6/2017
 JP 6246742 B2 12/2017
 JP 5856712 B2 2/2018
 JP 6342524 B2 6/2018
 JP 6434495 B2 12/2018
 JP 6445509 B2 12/2018
 JP 6445742 B1 12/2018
 JP 6466114 B2 2/2019
 JP 6515084 B2 5/2019
 JP 6528010 B1 6/2019
 JP 6655655 B2 2/2020
 JP 6776021 B2 10/2020
 JP 6776025 B2 10/2020
 JP 6786275 B2 11/2020
 JP 6821812 B2 1/2021
 JP 2021007772 A 1/2021
 JP 6843502 B2 3/2021
 JP 6894004 B2 6/2021
 JP 6920312 B2 8/2021
 JP 6926306 B2 8/2021
 JP 6932484 B2 8/2021
 JP 6936872 B2 9/2021
 JP 6980386 B2 11/2021
 JP 2022020838 A 2/2022
 WO 9843530 A1 10/1998
 WO 0168178 A1 9/2001
 WO 2008091197 A1 7/2008
 WO 2015057521 A1 4/2015
 WO 2015095577 A1 6/2015
 WO 2015130824 A1 9/2015
 WO 2016001015 A1 1/2016
 WO 2017070559 A1 4/2017
 WO 2017098198 A1 6/2017
 WO 2018053148 A1 3/2018
 WO 2018053164 A1 3/2018
 WO 2018136741 A1 7/2018

* cited by examiner




FIG. 1
(PRIOR ART)




FIG.2




FIG. 3




FIG. 4




FIG. 5




FIG. 8




FIG. 9




FIG. 6




FIG. 7




FIG. 10A




FIG. 10B

Biosignals ~ 1 Hz Localization signal ~ 8 kHz




FIG. 10C




FIG. 11




FIG.12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24A




FIG. 24B

MASKED RING ELECTRODES

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a Continuation of U.S. patent application Ser. No. 16/042,336 filed Jul. 23, 2018 (Allowed); which claims the benefit of U.S. Provisional Appln No. 62/536,369 filed Jul. 24, 2017, the disclosures which are incorporated herein by reference in their entirety for all purposes.

FIELD OF THE INVENTION

The present disclosure relates to electrophysiology catheters. In particular, the instant disclosure relates to an electrophysiology catheter having one or more partially insulated or masked electrodes that reduce or eliminate far field effects on electrical signals indicative of tissue in a region of interest.

BACKGROUND OF THE INVENTION

Electrophysiology (EP) mapping catheters are used to generate electrophysiology maps of tissue in a region of interest. The EP mapping data may be used, for example, in the diagnosis and treatment of tissues within a body. For example, EP maps of heart tissue can be used to guide ablation catheters which are used to convey an electrical stimulus to a region of interest within the heart and create tissue necrosis. Ablation catheters may be used to necrose heart tissue to correct conditions such as atrial and ventricular arrhythmias (including, but not limited to, ectopic atrial tachycardia, atrial fibrillation, atrial flutter and ventricular tachycardias). In addition to guiding ablation catheters, EP maps can also be used to evaluate the effectiveness of ablation therapy, or to locate ectopic sources or a critical isthmus.

An EP mapping catheter may include one or more electrodes at a distal end that samples electrical activity in tissue. Many EP mapping catheters have a relatively large number of electrodes to enable sampling over a relatively wide area of interest and reduce procedure time. Referring to FIG. 1, one type of EP mapping catheter **10** in use today includes a collapsible and expandable basket electrode assembly **12** disposed at the distal end of the catheter **10**. The basket electrode assembly **12** assumes a compressed state as the catheter is maneuvered through an introducer sheath to a region of interest in the body and an expanded state once the catheter reaches the region of interest and emerges from the sheath. The basket electrode assembly **12** includes a plurality of splines **14** on which un-insulated or un-masked electrodes **16** are disposed. The splines **14** are coupled together at proximal and distal ends and bow outward (i.e., a bowed shape) when the basket assembly **12** is in an expanded state.

The foregoing discussion is intended only to illustrate the present field and should not be taken as a disavowal of claim scope.

BRIEF SUMMARY

The present disclosure relates to an electrophysiology catheter. In particular, the instant disclosure relates to an electrophysiology catheter having a plurality of partially-masked electrodes which, when placed in contact with the

surface of a tissue of interest, the conductive material of the partially-masked electrode is not in contact with the blood pool.

A partially-masked electrode, in accordance with at least one embodiment of the present disclosure, includes a conductive material and an insulated coating having an outer surface. The insulated coating defines a contoured opening that exposes or reveals an area of the conductive material, wherein the contoured opening has an upper perimeter at the outer surface of the insulated coating. The upper perimeter of the opening defines an imaginary boundary area above the exposed area of the conductive material beyond which no part of the exposed conductive material extends.

A catheter in accordance with at least another embodiment of the present disclosure includes an elongate, deformable shaft comprising a proximal end and a distal end. The catheter further includes a distal tip assembly coupled to said distal end of said shaft, said distal tip assembly comprising a plurality of partially-masked electrodes disposed thereon. At least one of the plurality of partially-masked electrodes comprises a conductive material and an insulated coating having an outer surface. The insulated coating defines a contoured opening that exposes an area of the conductive material, wherein the contoured opening has an upper perimeter at the outer surface of the insulated coating. The upper perimeter of the opening defines an imaginary boundary area above the exposed area of the conductive material beyond which no part of the exposed conductive material extends.

A catheter in accordance with at least another embodiment of the present disclosure includes an elongate, deformable shaft having a proximal end and a distal end. The catheter further includes a distal tip assembly coupled to said distal end of said shaft, said distal tip assembly comprising a plurality of partially-masked electrodes disposed thereon. At least one of the plurality of partially-masked electrodes comprises a conductive material and an insulated coating having an outer surface, wherein the insulated coating defines a contoured opening that exposes or reveals an area of the conductive material. The contoured opening has an upper perimeter at the outer surface of the insulated coating. When the upper perimeter of the insulated coating is placed in contact with a tissue of interest, wherein the tissue of interest is proximate a blood pool, the insulated coating creates a seal between the blood pool and the contoured opening so that no blood in the blood pool can contact the conductive material.

A catheter in accordance with at least another embodiment of the present disclosure includes an elongate, deformable shaft having a proximal end and a distal end. The catheter further includes a basket electrode assembly coupled to the distal end of the shaft. The basket electrode assembly comprises a proximal end and a distal end, and is configured to assume a compressed state and an expanded state. The basket catheter assembly includes a first spline comprising a plurality of partially-masked electrodes disposed thereon. At least one of the plurality of partially-masked electrodes comprises a conductive material and an insulated coating having an outer surface, wherein the insulated coating defines a contoured opening that exposes or reveals an area of the conductive material. The contoured opening has an upper perimeter at the outer surface of the insulated coating. The upper perimeter of the opening defines an imaginary boundary area above the exposed area of the conductive material beyond which no part of the exposed conductive material extends.

3

A catheter in accordance with at least another embodiment of the present disclosure includes an elongate, deformable shaft comprising a proximal end and a distal end and a flexible tip portion located adjacent to the distal end of the shaft. The flexible tip portion comprises a flexible framework and a plurality of partially-masked electrodes disposed on the flexible framework and forms a flexible array of partially-masked electrodes adapted to conform to tissue. At least one of the plurality of partially-masked electrodes comprises a conductive material and an insulated coating having an outer surface, wherein the insulated coating defines a contoured opening that exposes or reveals an area of the conductive material. The contoured opening has an upper perimeter at the outer surface of the insulated coating. The upper perimeter of the opening defines an imaginary boundary area above the exposed area of the conductive material beyond which no part of the exposed conductive material extends.

A partially-masked electrode in accordance with at least another embodiment of the present disclosure includes a conductive material and an insulated coating having an outer surface. The insulated coating defines a contoured opening that exposes or reveals an area of the conductive material, wherein the contoured opening has an upper perimeter at the outer surface of the insulated coating. When the upper perimeter of the insulated coating is placed in contact with a tissue of interest, wherein the tissue of interest is proximate a blood pool, the insulated coating creates a seal between the blood pool and the contoured opening so that no blood in the blood pool can contact the conductive material.

A catheter in accordance with at least another embodiment of the present disclosure includes an elongate, deformable shaft having a proximal end and a distal end. The catheter further includes a basket electrode assembly coupled to the distal end of the shaft. The basket electrode assembly comprises a proximal end and a distal end and is configured to assume a compressed state and an expanded state and includes a first spline comprising a plurality of partially-masked electrodes disposed thereon. At least one of the plurality of partially-masked electrodes comprises a conductive material and an insulated coating having an outer surface, wherein the insulated coating defines a contoured opening that exposes or reveals an area of the conductive material. The contoured opening has an upper perimeter at the outer surface of the insulated coating. When the upper perimeter of the insulated coating is placed in contact with a tissue of interest, wherein the tissue of interest is proximate a blood pool, the insulated coating creates a seal between the blood pool and the contoured opening so that no blood in the blood pool can contact the conductive material.

A catheter in accordance with at least another embodiment of the present disclosure includes an elongate, deformable shaft comprising a proximal end and a distal end and a flexible tip portion located adjacent to the distal end of the shaft. The flexible tip portion comprises a flexible framework and a plurality of partially-masked electrodes disposed on the flexible framework and forming a flexible array of partially-masked electrodes adapted to conform to tissue. At least one of the plurality of partially-masked electrodes comprises a conductive material and an insulated coating having an outer surface, wherein the insulated coating defines a contoured opening that exposes or reveals an area of the conductive material. The contoured opening has an upper perimeter at the outer surface of the insulated coating. When the upper perimeter of the insulated coating is placed in contact with a tissue of interest, wherein the tissue of interest is proximate a blood pool, the insulated coating

4

creates a seal between the blood pool and the contoured opening so that no blood in the blood pool can contact the conductive material.

A partially-masked electrode, in accordance with at least another embodiment of the present disclosure, includes an insulated coating that is selected and configured to allow the reception of a localization signal by a conductive material of the partially-masked electrode. The insulated coating is selected and configured to prevent the reception of at least a significant amount of a far field signal by the conductive material.

A catheter in accordance with at least another embodiment of the present disclosure includes an insulated coating on at least one partially-masked electrode that is selected and configured to allow the reception of a localization signal by a conductive material of the partially-masked electrode. The insulated coating on the at least one partially-masked electrodes configured to prevent the reception of at least a portion of a far field signal by the conductive material.

A partially-masked electrode in accordance with various embodiments of the present disclosure wherein the insulated coating is selected and configured to allow the reception of a localization signal by the conductive material; and wherein the insulated coating is configured to prevent the reception of at least a portion of a far field signal by the conductive material.

A catheter in accordance with various embodiments of the present disclosure, wherein the insulated coating of at least one of the partially-masked electrodes configured to receive a localization signal through the conductive material; and wherein the insulated coating of at least one of the partially-masked electrodes is configured to prevent the reception of at least a portion of a far field signal via the conductive material.

A method of using a catheter in accordance with various embodiments of the present disclosure, the method comprising tracking the location of at least one of the partially-masked electrodes within a body of a patient, wherein the insulated coating of at least one of the partially-masked electrodes is configured to receive a localization signal by the conductive material; and wherein the insulated coating of at least one of the partially-masked electrodes is configured to prevent the reception of at least a portion of a far field signal by the conductive material; and placing the upper perimeter of the insulated coating of at least one of the partially-masked electrodes in contact with a tissue of interest in the body of the patient, the tissue of interest being proximate a blood pool, such that the insulated coating creates a seal between the blood pool and the contoured opening to inhibit the receipt of the far field signal in the blood pool.

A method of using a catheter in accordance with various embodiments of the present disclosure, the method comprising: tracking the location of one of a plurality of partially-masked electrodes within a body of a patient; wherein the insulated coating of the partially-masked electrode is configured to receive a localization signal by the conductive material; and wherein the insulated coating of the partially-masked electrode is configured to prevent the reception of at least a portion of a far field signal by the conductive material; placing the upper perimeter of the insulated coating of the partially-masked electrode in contact with a tissue of interest at a first location in the body of the patient, the tissue of interest being proximate a blood pool, such that the insulated coating creates a seal between the blood pool and the contoured opening to inhibit the receipt of the far field signal in the blood pool; and receiving, via the partially-

5

masked electrode, a first local electrical signal from the first location on the tissue of interest at the contoured opening, the first local electrical signal having a first magnitude, wherein as a result of the seal between the blood pool and the contoured opening the first local electrical signal comprises little or no far field signal.

The foregoing and other aspects, features, details, utilities, and advantages of the present disclosure will be apparent from reading the following description and claims, and from reviewing the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an isometric view of a prior art electrophysiology mapping catheter.

FIG. 2 is a diagrammatic view of an electrophysiology catheter according to an embodiment of the disclosure.

FIG. 3 is an enlarged isometric view of a distal tip assembly of the electrophysiology catheter of FIG. 2 comprising a basket electrode assembly.

FIG. 4 is a cross-sectional view of a spline comprising part of the basket electrode assembly of FIG. 3, taken along line 4-4 in FIG. 3.

FIG. 5 is an enlarged side view of the region in the dashed circle labeled "FIG. 5" in FIG. 3, depicting a partially masked electrode on a section of a spline of the basket electrode assembly depicted in FIG. 3.

FIG. 6 is an enlarged isometric view of the region in dashed circle 5 in FIG. 3.

FIG. 7 is an enlarged, cross-sectional view of the partially-masked electrode depicted in FIGS. 5 and 6, taken along line 7-7 of FIG. 5.

FIG. 8 is a cross-sectional side view of a partially-masked electrode positioned against a tissue of interest.

FIG. 9 is a cross-sectional view taken along line 9-9 of FIG. 5, with the partially-masked electrode positioned against a tissue of interest.

FIG. 10A is a graphical user interface display showing measured electrocardiogram voltages of a prior art unmasked electrode and a partially-masked electrode, according to various embodiment of the disclosure.

FIG. 10B is a graph showing the measured capacitance frequency response of an acrylated urethane masking material, according to an embodiment of the disclosure.

FIG. 10C is a graph showing the measured impedance of an acrylated urethane masking material, according to an embodiment of the disclosure.

FIG. 11 is a top plan view of a distal tip assembly comprising a planar array of partially-masked electrodes, according to another embodiment of the disclosure.

FIG. 12 is a top plan view of a distal tip assembly comprising a planar array of partially-masked electrodes, according to another embodiment of the disclosure.

FIG. 13 is an isometric view of a distal tip assembly comprising a basket electrode assembly having partially-masked flex circuit electrodes, according to another embodiment of the disclosure.

FIG. 14 is an enlarged view of the region in the dashed circle labeled "FIG. 14" in FIG. 13, depicting a partially-masked electrode on a section of a spline of the basket electrode assembly depicted in FIG. 13.

FIG. 15 is an enlarged, cross-sectional view of the partially-masked flex circuit electrode depicted in FIGS. 13 and 14 taken along line 15-15 of FIG. 14.

FIG. 16 is a cross-sectional view of a partially-masked flex circuit electrode of FIGS. 13-15 positioned against a tissue of interest.

6

FIG. 17 is a plan view of a partially-masked flex circuit electrode according to another embodiment of the disclosure.

FIG. 18 is a cross-sectional view of a partially-masked flex circuit electrode of FIG. 17 taken along line 18-18 of FIG. 17.

FIG. 19 depicts a plan view of a partially-masked flex circuit electrode according to another embodiment of the disclosure.

FIG. 20 is a cross-sectional view of the partially-masked flex circuit electrode of FIG. 19 taken along line 20-20.

FIG. 21 depicts a plan view of a partially-masked flex circuit electrode according to another embodiment of the disclosure.

FIG. 22 depicts a cross-sectional view of the partially-masked flex circuit electrode of FIG. 21 taken along line 22-22.

FIG. 23 is a flowchart illustrating a method of using catheters having partially-masked electrodes according to various embodiments of the disclosure.

FIGS. 24A-24B are flowcharts illustrating another method of using catheters having partially-masked electrodes according to various embodiments of the disclosure.

DETAILED DESCRIPTION

Typical catheter-based electrodes have predominantly been cylindrically-shaped (e.g., rings, tips, or spots). These electrodes have been used to take electrical signal measurements in a tissue of interest, for example the heart. As these electrodes are in the blood pool (or conductive pool), the electrodes will pick up various electrical signals in the heart, including signals proximal to the electrodes as well as signals distal the electrodes, the latter generally called far field effects. When an electrode is in contact with healthy tissue, a more distinct and/or stronger electrical signal is measured by the electrode. The electrical signal from the tissue is often referred to as a local source. However, in use, only a portion of a typical electrode, such as electrode 16 shown in FIG. 1, is in direct contact with the tissue of interest. Most of the electrode 16 is exposed to the blood pool and therefore the resulting output signal of the electrode 16 is a combination of local and far field effects. That is, the far field effects create noise in the received signal which makes it difficult to identify, locate, and/or diagnose unhealthy tissue.

Typically, the method to locate, identify, and/or diagnose unhealthy regions of tissue, such as diseased or damaged tissue (e.g., a lesion) includes sensing one or more electrophysiological characteristics from the tissue. However, the local electrical signals from unhealthy tissue are often much weaker than the local electrical signals from healthy tissue. In some instances, the magnitude of the local electrical signals from unhealthy tissue is about equal to or less than the far field magnitude. Therefore, it becomes difficult to distinguish between the far field and local effects. That is, the signal-to-noise ratio when sensing on or near unhealthy tissue may approach 1. The poor signal fidelity and/or low magnitude at the unhealthy tissue of interest makes it difficult to determine, for example, what is a boundary edge or conduction path/gap between unhealthy tissue and healthy tissue.

Additionally, as investigations and research in industry progress down the path of smaller electrode sizes and tighter physical positioning to increase the resolution for locating and identifying unhealthy tissue, aspects of the present

disclosure are directed to the use of printed or flex circuit electrodes to increase resolution.

Some benefits of printed or flex circuit electrodes are that they can be manufactured via batch fabrication, which reduces costs, and allow for the design of small and/or close electrodes and associated electrical connections into a smaller space. In addition, the printed and/or flex circuit electrodes tend to be one-sided electrodes. That is, they are only conductive on one side, and thereby minimize exposure of the electrode to the blood pool enhancing signal fidelity. However, the focus of the industry so far has been on size and/or spacing optimization and not on tissue contact and/or far field isolation.

One disadvantage of printed or flex circuit-based electrodes and traces is the increase impedance to that of a typical ring electrode. Increased impedance is detrimental to impedance based location systems (e.g., higher signal-to-noise ratio), and may degrade the accuracy of sensed bio-signals (ECG). These issues may also result in the increased noise from the printed or flex circuit electrodes as compared to typical ring electrodes, and may negate some of the isolation benefits of the one-sided structure of the printed or flex circuit electrode.

Additionally, printed or flex circuit electrodes tend to be planar and relatively smooth. Both of these qualities result in poor contact with tissue by the printed or flex circuit electrodes which may allow some blood pool contact and far field influence into a sensed electrophysiology signal.

In accordance with various embodiments of the present disclosure, catheters including electrodes which are partially-masked with an insulating material facilitate improved EP diagnostics. The insulating material of the partially-masked electrodes creates a seal between the blood pool and the conductive material of the partially-masked electrode which reduces or eliminates the reception of the far field effects by the partially-masked electrode, making it easier to locate and diagnose unhealthy tissue.

Referring now to the drawings wherein like reference numerals are used to identify identical components in the various views, FIG. 2 illustrates one embodiment of an electrophysiology catheter **18** having a plurality of partially-masked electrodes in accordance with the present disclosure. Catheter **18** is provided for use in generating an electrophysiological map of tissue and, in particular, cardiac tissue. It should be understood, however, that catheter **18** may be used in conjunction with various tissue types. Catheter **18** may include a cable connector or interface **20**, a handle **22**, a shaft **24** having a proximal end **26** and a distal end **28**, and a distal tip assembly such as the basket electrode assembly **30** depicted in FIG. 2. Catheter **18** may also include other conventional components not illustrated herein such as deflection mechanisms, additional electrodes and corresponding conductors or leads.

Connector **20** provides mechanical and electrical connection(s) for cables extending from an electronic control unit (ECU) (not shown) or similar device that is configured to receive signals generated by basket electrode assembly **30**. Connector **20** may be conventional in the art and be disposed at the proximal end **26** of catheter **18**.

Handle **22** provides a location for the physician to hold catheter **18** and may further provides a means for steering or guiding shaft **24** within the body. For example, handle **22** may include means to change the length of a guide wire extending through catheter **18** to distal end **28** of shaft **24** to steer distal end **28** and, thus, shaft **24**. Handle **22** may also be conventional in the art and it will be understood that the construction of handle **22** may vary.

Shaft **24** is an elongate, deformable member configured for movement within the body. Shaft **24** supports electrode assembly **30**, associated conductors, and, in some embodiments, additional electronics used for signal processing or conditioning. Shaft **24** may also be configured to permit transport, delivery, and/or removal of fluids (including irrigation fluids and bodily fluids), medicines, and/or surgical tools or instruments. Shaft **24** may be made from conventional materials such as polyurethane and defines one or more lumens configured to house and/or transport electrical conductors, fluids, medicines, guide wires or surgical tools or instruments. Shaft **24** may be introduced into a blood vessel or other structure within the body through an introducer sheath. Shaft **24** may then be steered or guided through the body to a desired location such as tissue in a region of interest using guide wires or pull wires or other means known in the art including remote control guidance systems.

Referring now to FIGS. 3 and 4, basket electrode assembly **30** provides a means for conducting an electrophysiological study of tissue. Assembly **30** may be coupled to a distal end of shaft **24** and includes a proximal end **32** and a distal end **34**. Assembly **30** may include a plurality of splines **36** on which electrodes are disposed and that form an electrode "basket" that is configured to assume a compressed state and an expanded state. Assembly **30** may assume the expanded state in the absence of an extraneous force acting on the assembly **30** (i.e., assembly **30** may be biased to the expanded state by, for example, nickel titanium memory alloy components) or may be urged to the expanded state through mechanical means (e.g., wires that are pulled or pushed) or by an internal balloon that can be expanded within the basket electrode assembly **30**. Assembly **30** may assume the compressed state, for example, as catheter **18** is maneuvered through an introducer sheath within the body to the region of interest and assume the expanded state upon emerging from a distal end of the sheath. Splines **36** are configured to support electrodes in a predetermined configuration to allow contact and/or non-contact mapping of electrical activity in tissue. Referring to FIG. 4, each spline **36** may include a tubular body **38**, means, such as wire **40**, for supporting (and biasing) body **38** to assume a predetermined shape, one or more partially-masked electrodes **42** (as shown in FIG. 3), and associated conductors **44**. Although a particular embodiment for a spline, e.g., spline **36**, is illustrated herein, it should be understood that spline(s) may be constructed in a variety of ways. In one embodiment, for example, one or more splines may include a flexible circuit as described and illustrated in U.S. Patent Publication No. 2012-0143298 (now issued as U.S. Pat. No. 8,560,086), the entire disclosure of which is incorporated by reference as though fully set forth herein. Additional embodiments of splines and/or basket electrode assemblies may be found described in one or more of U.S. Patent Publication No. 2011-0213231 (now issued as U.S. Pat. No. 8,588,885) and U.S. Patent Publication No. 2013-0172715 (now issued as U.S. Pat. No. 8,825,130), the entire disclosures which are incorporated by reference as though fully set forth herein.

Body **38** provides structural support for partially-masked electrodes **42** and insulates conductors **44** from bodily fluids and other elements. Referring to FIG. 4, body **38** is tubular and may be annular in shape. It should be understood, however, that the shape of body **38** may vary. Body **38** may be made from conventional polymeric materials such as polyurethane, and nylon or thermoplastic elastomers such as the elastomer sold under the registered trademark "PEBAX" by Arkema, Inc. and reinforcements such as metallic braids.

Body **38** may define a central lumen **46** extending between proximal and distal ends **48**, **50** (as shown in FIG. **3**) of body **38** and configured to allow passage of wire **40** and conductors **44**. It should be understood, however, that body **38** may alternatively define one or more channels each configured to receive one of wire **40** or a conductor **44**. In the illustrated embodiment, wire **40** is illustrated at the center of lumen **46** with conductors **44** disposed circumferentially around wire **40**. It should be understood, however, that the relative arrangement of wire **40** and conductors **44** within lumen **46** may vary.

Wire **40** is provided to support and bias body **38** to assume a predetermined shape. Wire may be made from a shape memory alloy such as nitinol (nickel titanium). Wire extends through lumen **46** of body **38** from proximal end **48** of body **38** to distal end **50** and may extend through the bodies **38** of multiple splines **36** to couple one or more splines together. Alternatively, or in addition, splines **36** may be coupled at distal end **50** by a hinge connector **52** or in any of the ways described and illustrated in U.S. patent application Ser. No. 13/340,760 (published as United States Patent Application Publication No. US 2013/0172715), the entire disclosure of which is incorporated by reference as though fully set forth herein. The distal end **34** of the basket electrode assembly **30** may be specialized to form a small, but blunt mechanical connection point so that the distal portion of the catheter **18** may safely be pressed against tissue.

Referring again to FIG. **3**, partially-masked electrodes **42** may be configured to diagnose, sense, and measure electrical activity in tissue such as cardiac tissue. One or more partially-masked electrodes **42** may also be used to provide tissue ablation therapy. Each partially-masked electrode **42** is coupled to a corresponding conductor **44** or one or more electrodes being coupled to the same conductor with the signal being multi-plexed.

Referring again to FIGS. **3** and **4**, conductors **44** may be configured to transmit electrical signals from partially-masked electrodes **42** through shaft **24** of catheter **18** to an electronic control unit or similar device. Conductors **44** may comprise wires or cables or other means for conducting signals and may be disposed with the lumen **46** of a body **38** of a given spline **36**. Each conductor **44** may be coupled at a distal end to a corresponding partially-masked electrode **42** and extend through lumen **46** to the proximal end **32** of basket electrode assembly **30**.

Referring now to FIGS. **5-9**, each of the partially-masked electrodes **42** may be formed of a conductive band **54** attached circumferentially about body **38**. For the purposes of clarity, the internals of body **38** shown in FIG. **4** are not represented in FIGS. **7**, **8**, and **9**. The conductive bands **54** may be composed of platinum, gold, stainless steel, iridium, or alloys of these metals, or other biocompatible, electrically-conductive materials or compositions thereof. The conductive bands **54** of each partially-masked ring electrode **42** may have an electrically-insulating, polymer surface coating **56**. The surface coating **56** may be formed of a material with high dielectric properties that can be applied in a very thin layer. Exemplary surface coatings may include thin coatings of polyester, polyamides, polyimides, and blends of polyurethane and polyimides. In one embodiment, for example only and without limitation, surface coating **56** may be Parylene (e.g., Parylene C, Parylene N). In other embodiments, for example only and without limitation, surface coating **56** may be an acrylated urethane. In various embodiments, for example only and without limitation, the thickness of the surface coating **56** may range from about 0.0001 mm to about 0.05 mm. In other embodiments, for

example only and without limitation, the thickness of the surface coating **56** may range from about 0.0003 mm to about 0.0006 mm. In various embodiments, for example only and without limitation, the surface coating **56** may be thicker around the opening **58** in order to create a taller “wall” to aid in creating a seal between the conductive band **54** and the blood pool, and thinner around the rest of the conductive band **54** to aid in reception of the localization signal by the partially-masked electrode **42**.

An aperture is formed in the insulated surface coating **56** to create a contoured opening **58** that exposes or reveals a small area of the conductive band **54**. The contoured opening **58** may be formed by laser, chemical, or other material removing or etching process to remove a portion of the insulated surface coating **56** to expose the conductive band **54** underneath. The edges or corners of the contoured opening **58** may be curved, rounded, or otherwise contoured to minimize any edge effects that could arise due to the imposition of a sharp edge, corner, or point. In various embodiments, for example only and without limitation, the openings **58** are oriented on the partially-masked electrodes **42** such that when the splines **36** of basket electrode assembly **30** are expanded, the openings **58** are facing the tissue of interest, such that they can contact the tissue of interest. In other embodiments, for example only and without limitation, the openings **58** are oriented on the partially-masked electrodes **42** such that when the splines **36** of basket electrode assembly **30** are expanded, the openings **58** may be maneuvered or oriented such that they are facing the tissue of interest and can contact the tissue of interest.

Although the contoured opening **58** is shown as having an oval shape, it will be understood that opening **58** may have other shapes, with or without rounded edges or corners, without departing from the scope of the disclosure, including, for example only and without limitation, a circle, an ellipse, a diamond, a rectangle, a hexagon, a square, a pentagon, an irregular polygon, a triangle. Opening **58** may be of different sizes without departing from the scope of the disclosure. For example, only and without limitation, where opening **58** is a circle, the diameter of the opening **58** may range from about 0.010 mm to about 0.050 mm. In one embodiment, for example only and without limitation, the diameter of the opening **58** may be about 0.014 mm. In another embodiment, for example only and without limitation, the diameter of the opening **58** may be about 0.022 mm. In yet another embodiment, for example only and without limitation, the diameter of the opening **58** may be about 0.031 mm. Moreover, although a single opening **58** is shown per partially-masked electrode **42**, it will be understood that each partially-masked electrode **42** may include more than one opening **58** (e.g., 2, 3, 4, or more) without departing from the scope of the disclosure.

In some embodiments, for example only and without limitation, the surface area of the conductive band **54** exposed at the opening **58** is only about 10 percent (10%) of the total surface area of the conductive band **54**. Stated another way, about 90 percent (90%) of the conductive band **54** is insulated. Therefore, the electrically-conductive surface area of electrode **42** is only about 10 percent (10%) of the electrically-conductive surface area of a typical unmasked (un-insulated) ring electrode. In various embodiments, for example only and without limitation, the surface area of an un-insulated ring electrode may be about 2.5 mm² whereas the surface area of the opening **58** and thus the exposed area of conductive band **54** is about 0.25 mm². In various embodiments, for example only and without limitation, the exposed area of conductive band **54** may be from

11

about 0.01 mm² to about 1.0 mm². In other embodiments, for example only and without limitation, the exposed area of conductive band 54 may be from about 0.044 mm² to about 0.486 mm².

As shown in FIGS. 6 and 7, opening 58 has an upper perimeter 58p at the outer surface 56s of the surface coating 56. The upper perimeter 58p of opening 58 defines an imaginary boundary area 59 above the exposed area of the conductive band 54 beyond which no part of the exposed conductive band 54 extends. The imaginary boundary area 59 is an imaginary surface having an outer edge(s) which is/are coincident and coextensive with the upper perimeter 58p of opening 58. Depending on the shape of opening 58, the imaginary boundary area 59 may be a plane or may have a contoured surface such as, for example only and without limitation, a saddle shape, a hyperbolic paraboloid, and a parabolic cylinder. The imaginary boundary area 59 is represented in FIG. 6 by a series of lines covering opening 58 within upper perimeter 58p. The imaginary boundary area 59 is represented in FIG. 7 by a dashed line extending from one side of the opening 58 to the other side of the opening within upper perimeter 58p. Therefore partially-masked electrode 42 includes a gap or void 59v between imaginary boundary area 59 and conductive band 54.

Referring now to FIGS. 8 and 9, partially-masked electrode 42 is shown interfacing with the surface 60 of a tissue of interest. As shown in the end view of FIG. 8 and the side view of FIG. 9, the surface coating 56 is between the conductive band 54 and the surface 60 of the tissue of interest. Because no part of conductive band 54 extends beyond the imaginary boundary area 59 shown in FIGS. 6 and 7, a void 62 is created between the conductive band 54 and the surface 60 of the tissue of interest at the location of the opening 58 in the surface coating 56. It is desirable to have the void 62 be as small as possible to increase the signal received by the partially-masked electrode 42. Thus, if the surface 60 of the tissue is touching the conductive band 54 the received signal may be increased.

Even if the surface 60 of the tissue does not come into contact with the conductive band 54, the raised surface coating 56 which is between the conductive band 54 and the surface 60, the thickness of the surface coating 56 creates a cupped or cup-like profile at the opening 58 which isolates the conductive band 54 of the partially-masked electrode 42 from the conductive path through the blood pool. That is, when the upper perimeter 58p of the raised surface coating 56 is placed in contact with the surface 60 of the tissue of interest, the surface coating 56 creates a seal between the blood pool and the opening 58 so that no blood in the blood pool can contact conductive band 54. When the opening 58 is oriented toward the tissue of interest and the surface coating 56 around the perimeter of the opening 58 makes contact with the surface 60 of the tissue of interest, the conductive band 54 is completely isolated or sealed from any far field effects present in the blood pool. This will be even more effective in smoother tissue than in rougher tissue. With typical un-masked electrodes, due to the combination of the rough surface and far field interference, the signal received by a typical un-masked electrode may be inaccurate. However, with a partially-masked electrode 42, even if a complete seal may not be able to be achieved against rough ventricle surface, for example. The isolation provided by the surface coating 56 of the partially-masked electrode 42 (with potentially more sealing at a tissue peak than a tissue valley) will still provide net improvement in EP measurements, as compared to a typical un-masked electrode. Except for opening 58, partially-masked electrode 42

12

has no other open conductive ends or portions as with typical ring electrodes. This results in a more focused electrode as compared to un-masked electrodes. Thus it is desirable to minimize the volume of the void 62 while maintaining the seal from the blood pool provided by surface coating 56.

By completely isolating partially-masked electrode 42 from any far field effects present in the blood pool, the noise from the far field effects is significantly reduced or eliminated. This increases the signal to noise ratio of the electrical signal measured by the partially-masked electrode 42. Because the far field effects are no longer measured by the partially-masked electrode 42, the signal quality and magnitude of the measured weak local electrical signals from unhealthy tissue is improved as compared to a typical un-insulated ring electrode 16. This also allows for easier identification, locating, detecting and/or diagnosing unhealthy tissue. For example, as shown in FIG. 10A, pre-clinical testing has shown that the electrogram (EGM) peak-to-peak voltage (Vpp) signal from partially-masked electrode 42 (identified by arrows labeled PM) is about three to four times the magnitude of a typical un-insulated ring electrode 16 (identified by arrows labeled UM). In one embodiment, the measured peak-to-peak voltage (Vpp) signal from partially-masked electrode 42 was about 13.5 mV compared to 3.5 mV from a typical un-insulated ring electrode 16. Additionally, the slopes of the EGM signals from partially-masked electrode 42 were steeper than those measured by a typical un-insulated ring electrode 16.

In various embodiments, the surface coating 56 material and/or the surface coating 56 thickness is selected and configured to inhibit or block the receipt of the far field electrical signals when the surface coating 56 creates a seal between the blood pool and the opening 58, while still allowing the partially-masked ring electrode 42 to receive a localization signal. That is, the surface coating 56 is of a sufficient thickness and has material properties or characteristics such that the far field electrical signals cannot penetrate the surface coating 56 to the underlying conductive band 54, but still allows the localization signal to penetrate the surface coating 56 to the underlying conductive band 54. Thus, partially-masked electrode 42 can function as both an electrode for mapping and/or diagnostic purposes and for localization purposes. In essence, the surface coating 56 substantially or completely filters out the far field signals, with minimal or no filtering out of the localization signals. For example, through the selection and configuration of the material and/or thickness of the surface coating 56, the partially-masked electrode 42 may be tuned to filter out far field signals from about 1.0 Hz to about 600 Hz while being receptive to localization signals at or above approximately 8 kHz. Thus, the partially masked electrode 42 can filter out frequencies around the normal heart rate frequency (i.e., 1.0 Hz to about 1.67 Hz). The insulating properties of the insulated surface coating 56 therefore, may be frequency dependent.

FIGS. 10B and 10C illustrate frequency response and impedance of an acrylated urethane insulated surface coating having a thickness of 0.5 mm. It is believed that the measured properties of the acrylated urethane insulated surface coating will behave similarly when applied to conductive band 54 to create an embodiment of partially-masked electrode 42. For example, as shown in FIG. 10B, the capacitance is much higher at lower frequencies (e.g., from about 1.0 Hz to about 300 Hz), and decreases before substantially leveling off at higher frequencies (e.g., from about 400 Hz and above). It is expected that a partially-masked electrode 42, that is partially-masked with an acry-

lated urethane insulated surface coating having a thickness of 0.5 mm, will effectively filter out lower frequency signals (including far field biosignals), but will not filter out higher frequency signals (including localization signals). For example only and without limitation, the localization signal may be a current pulse as described in U.S. Pat. No. 7,263,397, the entire disclosure of which is incorporated by reference as though fully set forth herein. Thus it is expected that the partially-masked electrode **42** will work like a high-pass filter, and will have an equivalent circuit like a parallel RC (resistor-capacitor) circuit. The capacitance change shown in FIG. **10B** results in the impedance curves shown in FIG. **10C**. The increase in capacitance, at low frequency, will effectively act as a far-field biosignal filter by dielectric relaxational screening of the non-contact low frequency noise.

As shown in FIG. **10C**, a resultant real component impedance of a tested acrylated urethane insulated surface coating with a thickness of 0.5 mm is equal to $(z \cdot \cos(\theta))$. Thus it is expected that a partially-masked electrode **42** having a 0.5 mm thick acrylated urethane insulated surface coating **56** will result in an impedance of about 90k ohms between 100 Hz and 10 kHz. Accordingly, an insulated surface coating **56** of 5 μm will have an impedance of about 900 ohms. This impedance is within the range measured between partially-masked and un-masked electrodes. Therefore, the increased impedance of the partially-masked electrodes is still usable with impedance-based localization systems, such that the partially-masked electrodes **42** may be used for localization purposes as well as measuring biosignals from tissues of interest.

Pre-clinical testing has also shown that partially-masked electrodes, where the surface area of the opening **58** is only about 10 percent (10%) of the total surface area of the conductive band **54**, had a smaller impedance increase than printed or flex circuit electrodes. Thus the impedance localization performance impact is minimized as compared to printed or flex circuit electrodes. The impedance of the partially-masked electrodes only increases from about 200-350 ohms to a range of about 430-610 ohms, as compared to un-masked electrodes.

Although partially-masked electrodes **42** are incorporated into a basket catheter having the structure shown in FIGS. **2** and **3**, it will be understood that partially-masked electrodes **42** may be used in any type of catheter structure without departing from the scope of the disclosure. For example only and without limitation, partially-masked electrodes **42** may be incorporated into any of the basket catheter structures as described and illustrated in U.S. Patent Publication No. 2017-0100075 (now issued as U.S. Pat. No. 9,986,950), U.S. Patent Publication No. 2016-0331254, U.S. Pat. Nos. 9,339,331 and 8,224,416, the entire disclosures which are incorporated by reference as though fully set forth herein.

In addition to being incorporated into basket catheter structures, partially-masked electrodes **42** may be incorporated into another distal tip assembly comprising a planar array of partially-masked electrodes. The distal tip assembly may be, for example, a high density electrode assembly as shown in FIGS. **11** and **12**. FIG. **11** depicts a top view of a high density electrode assembly **101** according to various embodiments of the present disclosure. In some embodiments, the high density electrode assembly **101** may include a flexible tip portion **110** that forms a flexible array of partially-masked electrodes **42** having openings **58** in an insulated coating. This planar array (or 'paddle' configuration) of partially-masked electrodes **42** comprises four side-by-side, longitudinally-extending arms **103**, **104**, **105**, **106**,

which can form a flexible framework on which the partially-masked electrodes **42** are disposed. The four microelectrode-carrier arms comprise a first outboard arm **103**, a second outboard arm **106**, a first inboard arm **104**, and a second inboard arm **105**. These arms are laterally separated from each other. In some embodiments, as shown in FIG. **11**, there may be a distal member (or 'button') **109** where one or more of the arms come together. This distal member **109** may be constructed from metal or some other radiopaque material to provide fluoro visualization and semi-independent planar movement between the outer and inner arms. In other embodiments, high density electrode assembly **101** does not include distal member **109**. In various embodiments, for example only and without limitation, high density electrode assembly **101** may be used for electrophysiology (EP) mapping. In other embodiments, for example only and without limitation, high density electrode assembly **101** may be used for tissue ablation.

Each of the four arms may carry a plurality of partially-masked electrodes **42**. For example, each of the four arms can carry partially-masked electrodes **42** spaced along a length of each of the four arms. Although the high density electrode assembly **101** depicted in FIG. **11** depicts four arms, the high density electrode assembly **101** could comprise more or fewer arms. As shown in FIG. **11**, one or more of the arms may include electrode **116**, which may be an un-masked, partially-masked, or fully masked electrode. In some embodiments, for example only and without limitation, electrodes **116** may be fully masked and may be used for localization purposes. For example, as described in greater detail above, electrodes **116** may be masked with an insulated coating that isolates the conductive material of electrode **116** from far field or tissue signals (e.g., cardiac signals), but does not isolate electrode **116** from localization signals. Additionally, while the high density electrode assembly **101** depicted in FIG. **11** depicts 16 partially-masked electrodes (e.g., 4 partially-masked electrodes **42** on first outboard arm **103** and second outboard arm **106** and 4 partially-masked electrodes **42** on first inboard arm **104** and second inboard arm **105**), the catheters can include more or fewer than 16 partially-masked electrodes. In addition, the first outboard arm **103** and second outboard arm **106** can include more or fewer than 4 partially-masked electrodes and the first inboard arm **104** and second inboard arm **105** can include more or fewer than 4 partially-masked electrodes.

While the partially-masked electrodes are shown as substantially equally distributed on arms **103**, **104**, **105** and **106**, it will be understood that the electrodes may be spaced at different intervals on each arm without departing from the scope of the disclosure. That is, for example only and without limitation, in various embodiments, electrodes on first outboard **103** may be spaced closer together or further apart than electrodes on first inboard arm **104**. While the electrodes are shown as substantially evenly distributed on arms **103**, **104**, **105** and **106**, it will be understood that the electrodes may be unevenly spaced intervals on each arm without departing from the scope of the disclosure. That is, for example only and without limitation, in various embodiments, the electrodes may be located on the arms such that the electrodes are closer together near the distal end of flexible tip portion **110** and further apart near the proximal end of flexible tip portion **110**. Alternatively, for example only and without limitation, in various embodiments, the electrodes may be located on the arms such that the elec-

trodes are farther apart near the distal end of flexible tip portion **110** and closer together near the proximal end of flexible tip portion **110**.

In some embodiments, the partially-masked electrodes **42** can be used in diagnostic, therapeutic, and/or mapping procedures. For example and without limitation, the partially-masked electrodes **42** can be used for electrophysiological studies, pacing, cardiac mapping, and ablation. In some embodiments, the partially-masked electrodes **42** can be used to perform unipolar or bipolar ablation. This unipolar or bipolar ablation can create specific lines or patterns of lesions. In some embodiments, the partially-masked electrodes **42** can receive electrical signals from the heart, which can be used for electrophysiological studies. In some embodiments, the partially-masked electrodes **42** can perform location or position sensing functions related to cardiac mapping.

In some embodiments, the high density electrode assembly **101** can include a catheter shaft **107**. The catheter shaft **107** can include a proximal end and a distal end. The proximal end of catheter shaft **107** may be connected to or integrally formed with the distal end **28** of shaft **24** of catheter **18**, as shown in FIG. **2**, in place of electrode assembly **30**. That is, the distal tip assembly of the basket electrode assembly **30** may be swapped with, interchanged with, or substituted with the distal tip assembly of the high density electrode assembly **101**. The distal end can include a connector **108**, which can couple the distal end of the catheter shaft **107** to a proximal end of the planar array. The catheter shaft **107** can define a catheter shaft longitudinal axis *aa*, as depicted in FIG. **11**, along which the first outboard arm **103**, first inboard arm **104**, second inboard arm **105**, and second outboard arm **106** can generally extend parallel in relation therewith. The catheter shaft **107** can be made of a flexible material, such that it can be threaded through a tortuous vasculature of a patient. In some embodiments, the catheter shaft **107** can include one or more ring electrodes **111** disposed along a length of the catheter shaft **107**. The ring electrodes **111** can be used for diagnostic, therapeutic, and/or mapping procedures, in an example. In various embodiments, ring electrodes **111** may be partially-masked in the same manner as partially-masked electrodes **42**. In other embodiments, ring electrodes **111** may be un-masked. In yet other embodiments, the high density electrode assembly **101** may include a combination of partially-masked, un-masked, or fully masked ring electrodes.

The flexible tip portion **110** can be adapted to conform to tissue (e.g., cardiac tissue). For example, when the flexible tip portion **110** contacts tissue, the flexible tip portion can deflect, allowing the flexible framework to conform to the tissue. In some embodiments, the arms (or the understructure of the arms) comprising the paddle structure (or multi-arm, electrode-carrying, flexible framework) at the distal end of the catheter depicted in FIG. **11** is preferably constructed from a flexible or spring-like material such as Nitinol and/or a flexible substrate, as discussed herein. The construction (including, for example, the length and/or diameter of the arms) and material of the arms can be adjusted or tailored to create, for example, desired resiliency, flexibility, foldability, conformability, and stiffness characteristics. These characteristics may vary from a proximal end to a distal end of an arm, or between or among the plurality of arms comprising a single paddle structure. The foldability of materials such as Nitinol and/or flexible substrate provide the additional advantage of facilitating insertion of the paddle structure into a delivery catheter or introducer,

whether during delivery of the catheter into the body or removal of the catheter from the body at the end of a procedure.

Another embodiment of a distal tip assembly comprises a planar array of partially-masked electrodes, wherein the distal tip assembly is a high density electrode assembly **201** of the disclosure is illustrated in FIG. **12** and is described below. Some features of high density electrode assemblies **201** and **101** are common to one another and, accordingly, descriptions of such features in one embodiment should be understood to apply to the other embodiment. Furthermore, particular characteristics and aspects of one embodiment may be used in combination with, or instead of, particular characteristics and aspects of another embodiment.

FIG. **12** illustrates another embodiment of a high density electrode assembly **201** which includes a variety of partially-masked and un-masked electrodes. Other than the differences in the electrodes, high density electrode assembly **201** is substantially the same or identical to high density electrode assembly **101**. High density electrode mapping catheter **201** includes a population of partially-masked electrodes having different sized openings. For example only and without limitation, first outboard arm **103** includes four partially-masked electrodes **42a** each having an opening **58a**, first inboard arm **104** includes four partially-masked electrodes **42b** each having an opening **58b** smaller than opening **58a**, and second inboard arm **105** includes four partially-masked electrodes **42c** each having an opening **58c** smaller than openings **58a** and **58b**. In an embodiment, for example only and without limitation, opening **58a** may have a diameter about 0.031 mm, opening **58b** may have a diameter about 0.022 mm, and opening **58c** may have a diameter about 0.014 mm. Although the openings **58a**, **58b**, and **58c** are shown as having an oval shape, it will be understood that openings **58a**, **58b**, and **58c** may have other shapes, with or without rounded edges or corners, without departing from the scope of the disclosure, including, for example only and without limitation, a circle, an ellipse, a diamond, a rectangle, a hexagon, a square, a pentagon, an irregular polygon, a triangle. Openings **58a**, **58b**, and **58c** may be of different sizes without departing from the scope of the disclosure. Additionally, in various embodiments, for example only and without limitation, second outboard arm **106** of high density electrode assembly **201** includes four un-masked electrodes **16**. In other embodiments, for example only and without limitation, second outboard arm **106** may include partially-masked electrodes having openings of a different shape and/or size from openings **58a**, **58b**, and **58c**.

High density electrode assembly **201** may be used as a test bed for testing one or more parameters, such as for example only and without limitation: opening **58** shapes, opening **58** sizes, coating **56** thickness, coating material, electrode spacing, distribution, and number of electrodes (masked, un-masked, and partially masked).

While the partially-masked electrodes shown and described herein are ring electrodes, it will be understood that printed or flex circuit electrodes may be partially-masked without departing from the scope of the disclosure. Thus, the embodiment of FIGS. **13-15** incorporate partially-masked flex circuit electrodes **342** into a distal tip. Some features of partially-masked flex circuit electrodes **34** and partially-masked electrodes **42** are common to one another and, accordingly, descriptions of such features in one embodiment should be understood to apply to other embodiments. Furthermore, particular characteristics and aspects of

one embodiment may be used in combination with, or instead of, various aspects of another embodiment.

With reference to FIG. 13, a distal tip assembly comprising a basket electrode assembly 325 is shown having a plurality of partially-masked flex circuit electrodes 342 (as shown in FIG. 14) which are oriented to contact tissue of interest. Basket electrode assembly 325 is shown with the basket portion of the catheter in an expanded configuration.

Basket electrode assembly 325 is shown as it may include an outer tubing 330 housing, a deployment member 331, and a terminal end 350. The outer tubing 330 of basket electrode assembly 325 may be connected to, or integrally formed with, the distal end 28 of shaft 24 of catheter 18, as shown in FIG. 2 (in place of electrode assembly 30). Basket electrode assembly is shown having splines 336a-f; however, the basket catheter 325 is not limited to any particular number of splines 336, as will be readily understood by those having ordinary skill in the art after becoming familiar with the teachings herein. Additional features and structure of basket electrode assembly are shown and described in U.S. patent application Ser. No. 15/333,798 (published as U.S. Patent Application Pub. No. 2017/0100075) the entire disclosure of which is incorporated by reference as though fully set forth herein.

Each spline 336 is connected at the proximal end of the splines 336 to the outer tubing 330, and each spline 336 is connected at the opposite or distal end of the splines 336 to the deployment member 331. The deployment member 331 is operable to be moved in a first direction (e.g., in the direction of arrow 338a) relative to the outer tubing 330 to expand the splines 336 to a deployed position, as shown in FIG. 13. The deployment member 331 is also operable to be moved in a second direction (e.g., in the direction of arrow 338b) relative to the outer tubing 330 to collapse the splines 336 to an undeployed position.

The deployment member 331 may include a pull wire. The deployment member 331 may be a solid stainless steel or Nitinol wire. Alternatively, the deployment member 331 may be a hollow tube (or configured to house tubing). The deployment member 331 should be manufactured to be sufficiently stiff such that the deployment member 331 can be operated remotely (e.g., outside of the patient's body), and be moved in the directions illustrated by arrows 338a and 338b to expand and contract the splines 336.

In any event, the basket electrode assembly 325 may be inserted into a catheter shaft (e.g., sheath (not shown) in its undeployed position for placement in the patient's body (e.g., within a heart chamber). The basket electrode assembly 325 may then be expanded to its deployed position for a medical procedure within the patient's body. Following the procedure, the basket electrode assembly 325 may again be collapsed to its undeployed position so that the basket electrode assembly 325 may be withdrawn from the patient.

In various embodiments, for example only and without limitation, the splines 336 are formed from sheets. The sheets can be formed of a suitable flexible material such as plastic (e.g., polyimide) or metal (e.g., platinum, gold, stainless steel, iridium, or alloys of these metals). As shown in FIGS. 13, 14 and 15, a population of spaced apart partially-masked flex circuit electrodes 342 and corresponding electrode traces 344 (as shown in FIG. 14) are provided on the splines 336. With specific reference to FIG. 15 the partially-masked flex circuit electrodes 342 may be formed of a conductive material 354 which may be printed, adhered, bonded, etched or otherwise provided on the splines 336, which may serve as a substrate for the partially-masked flex circuit electrodes 342.

The traces 344 may then be connected to electrical wiring and extend through a catheter (e.g., catheter 18 shown in FIG. 2). The electrical wiring may convey electrical signals between the partially-masked flex circuit electrodes 342 and one or more control system (not shown). For example, the electrical signals may be used to control output of ablation electrodes, or for processing input from mapping electrodes for viewing or storage by the user (e.g., on an electrical monitoring device).

The conductive material 354 may be composed of platinum, gold, stainless steel, iridium, or alloys including one or more of these metals, or other biocompatible, electrically-conductive material. As shown in FIG. 15, an electrically-insulating, polymer surface coating 356 may be applied to each spline 336 and the conductive material 354. The surface coating 356 may be formed of a material with high dielectric properties that can be applied in a very thin layer. Exemplary surface coatings may include thin coatings of polyester, polyamides, polyimides, and blends of polyurethane and polyimides. In one embodiment, for example only and without limitation, surface coating 356 may be Parylene. In various embodiments, for example only and without limitation, the thickness of the surface coating 356 may range from about 0.0001 mm to about 0.05 mm. In other embodiments, for example only and without limitation, the thickness of the surface coating 356 may range from about 0.0003 mm to about 0.0006 mm.

An aperture is formed in the surface coating 356 to create a contoured opening 358 that exposes or reveals a small area of the conductive band 354. The contoured opening 358 may be formed by laser, chemical, or other material removing or etching process to remove a portion of the surface coating 356 to expose the conductive band 354 underneath. The edges or corners of the contoured opening 358 may be curved, rounded, or otherwise contoured to minimize any edge effects that could arise due to the imposition of a sharp edge, corner, or point. In various embodiments, for example only and without limitation, the openings 358 are oriented on the partially-masked electrodes 342 such that when the splines 336 of basket electrode assembly 325 are expanded, the openings 358 are facing the tissue of interest, such that they can contact the tissue of interest. In other embodiments, for example only and without limitation, the openings 358 are oriented on the partially-masked electrodes 342 such that when the splines 336 of basket electrode assembly 325 are expanded, the openings 358 may be maneuvered or oriented such that they are facing the tissue of interest and can contact the tissue of interest.

Although the contoured opening 358 is shown as having an oval shape, it will be understood that opening 358 may have other shapes, with or without rounded edges or corners, without departing from the scope of the disclosure, including, for example only and without limitation, a circle, an ellipse, a diamond, a rectangle, a hexagon, a square, a pentagon, an irregular polygon, a triangle. Opening 358 may be of different sizes without departing from the scope of the disclosure. For example only and without limitation, where opening 358 is a circle, the diameter of the opening 358 may range from about 0.010 mm to about 0.050 mm. In one embodiment, for example only and without limitation, the diameter of the opening 358 may be about 0.014 mm. In another embodiment, for example only and without limitation, the diameter of the opening 358 may be about 0.022 mm. In yet another embodiment, for example only and without limitation, the diameter of the opening 358 may be about 0.031 mm. Moreover, although a single opening 358 is shown per partially-masked flex circuit electrode 342, it

will be understood that each partially-masked flex circuit electrode **342** may include more than one opening **358** (e.g., 2, 3, 4, or more) without departing from the scope of the disclosure.

As shown in FIG. **15**, opening **358** has an upper perimeter **358p** at the outer surface **356s** of the surface coating **356**. The upper perimeter **358p** of opening **358** defines an imaginary boundary area **359** above the exposed area of the conductive material beyond which no part of the exposed conductive material **354** extends. The imaginary boundary area **359** is a planar surface having an outer edge(s) which is/are coincident and coextensive with the upper perimeter **358p** of opening **358**. Therefore partially-masked flex circuit electrode **342** includes a gap or void **359v** between imaginary boundary area **359** and conductive band **354**.

Referring now to FIG. **16**, partially-masked flex circuit electrode **342** is shown interfacing with the surface **60** of a tissue of interest. The surface coating **356** is between the conductive material **354** and the surface **60** of the tissue of interest and because no part of conductive material **354** extends beyond the imaginary boundary area **359** shown in FIG. **15**, a void **62** is created between the conductive material **354** and the surface **60** of the tissue of interest at the location of the opening **358** in the surface coating **356**. It is desirable to have the void **62** be as small as possible to increase the signal received by the partially-masked flex circuit electrode **342**. Thus, if the surface **60** of the tissue is touching the conductive material **354** the received signal may be increased. In some embodiments, for example only and without limitation, an electrical signal may be emitted by the partially-masked flex circuit electrode **342** to attract the surface **60** of the tissue toward the conductive material **354**.

The raised surface coating **356**, which is between the conductive material **354** and the surface **60**, creates a cupped or cup-like profile at the opening **358** which isolates the conductive material **354** of the partially-masked flex circuit electrode **342** from the conductive path through the blood pool. That is, when the upper perimeter **358p** of the raised surface coating **356** is in contact with the tissue of interest, the surface coating **356** creates a seal between the blood pool and the opening **358** so that no blood in the blood pool can contact conductive material **354**. When the opening **358** is oriented toward the tissue of interest and the surface coating **356** around the perimeter of the opening **358** makes contact with the surface **60** of the tissue of interest, the conductive band **354** is completely isolated or sealed from any far field effects present in the blood pool. This will be even more effective in rougher tissue (e.g., ventricle) than in smoother tissue (e.g., atria). Thus, except for opening **358**, partially-masked flex circuit electrode **342** has no other open conductive ends or portions as with typical ring electrodes. This results in a more focused electrode as compared to unmasked electrodes. Aspects of the present disclosure are desirable to minimize the volume of the void **62** while maintaining the seal from the blood pool provided by surface coating **356**.

By completely isolating partially-masked flex circuit electrode **342** from any far field effects present in the blood pool, the noise from the far field effects is significantly reduced or eliminated. This increases the signal to noise ratio of the electrical signal measured by the partially-masked flex circuit electrode **342**. Because the far field effects are no longer measured by the partially-masked electrode **342**, the signal quality and magnitude of the measured (weak) local electrical signals from unhealthy tissue is improved as compared

to a typical un-insulated ring electrode **16**. This also allows for easier identification, locating, detecting and/or diagnosing unhealthy tissue.

Another embodiment of a partially-masked flex circuit electrode **442** of the disclosure is illustrated in FIGS. **17** and **18** and is described below. Some features of partially-masked flex circuit electrode **442** and **342** are common to one another and, accordingly, descriptions of such features in one embodiment should be understood to apply to other embodiments. Furthermore, particular characteristics and aspects of one embodiment may be used in combination with, or instead of, particular characteristics and aspects of another embodiment.

With further reference to FIGS. **17** and **18**, a spline **336'** is shown with a conductive material **354** which may be printed, adhered, bonded, etched, or otherwise provided on the spline **336'**. Additionally, an electrically-insulating, polymer surface coating **456** may be applied to each spline **336'**. However, unlike partially-masked flex circuit electrode **342** shown in FIGS. **14-16**, the surface coating **456** is not applied on top of conductive material **354**, or is fully removed from conductive material, such that opening **458** in the surface coating **456** has the same area as conductive material **354**. Thus, as shown in FIG. **18**, surface coating **456** abuts, but does not overlap, conductive material **354**.

Another embodiment of a partially-masked flex circuit electrode **542** of the disclosure is illustrated in FIGS. **19** and **20** and is described below. Some features of partially-masked flex circuit electrode **542** and **342** are common to one another and, accordingly, descriptions of such features in one embodiment should be understood to apply to other embodiments. Furthermore, particular characteristics and aspects of one embodiment may be used in combination with, or instead of, particular characteristics and aspects of another embodiment.

With further reference to FIGS. **19** and **20**, a spline **336''** is shown with a conductive material **354** which may be printed, adhered, bonded, etched or otherwise provided on the spline **336''**. The conductive material **354** has an outer perimeter or outer edge defined by dashed line **355** in FIG. **19**. In this embodiment, as in several of the other embodiments described herein, the outer perimeter **355** is an ellipsoid, but may define other shapes, including irregular shapes. Additionally, an electrically-insulating, polymer surface coating **556** may be applied to each spline **336''** locally around conductive material **354**. That is, unlike partially-masked flex circuit electrodes **342** and **442** shown in FIGS. **14-16** and **17-18**, the surface coating **556** is only applied proximate to the outer perimeter **355** of conductive material **354**. Thus, surface coating **556** surrounds the outer edges or sides of conductive material **354** and projects above conductive material **354** but does not otherwise cover all of spline **336''**. Surface coating **556** therefore only rings around conductive material **354**. An opening **558** smaller than the area of conductive material **354** is provided in surface coating **556**.

Another embodiment of a partially-masked flex circuit electrode **642** of the disclosure is illustrated in FIGS. **21** and **22** and is described below. Some features of partially-masked flex circuit electrode **642**, **542**, **442**, and **342** are common to one another and, accordingly, descriptions of such features in one embodiment should be understood to apply to other embodiments. Furthermore, particular characteristics and aspects of one embodiment may be used in combination with, or instead of, particular characteristics and aspects of another embodiment.

With further reference to FIGS. 21 and 22, a spline 336''' is shown with a conductive material 354 which may be printed, adhered, bonded, etched, or otherwise provided on the spline 336'''. Additionally, an electrically-insulating, polymer surface coating 656 may be applied to each spline 336''' locally around conductive material. That is, unlike partially-masked flex circuit electrodes 342 and 442 shown in FIGS. 14-16 and 17-18, the surface coating 656 is only applied proximate conductive material 354. Thus, surface coating 656 surrounds the sides of conductive material 354 and projects above conductive material 354 but does not otherwise cover all of spline 336. Surface coating 656 therefore only rings around conductive material 354. Moreover, like opening 458 (see FIGS. 17 and 18) of partially-masked flex circuit electrode 442, the surface coating 656 is not applied on top of conductive material 354, or is fully removed from conductive material, such that opening 658 in the surface coating 656 has the same area as conductive material 354. Thus, as shown in FIG. 22, surface coating 656 abuts, but does not overlap, conductive material 354.

While the partially-masked electrodes described herein are described as being oriented and/or maneuvered such that they contact the tissue of interest, it will be understood that in various embodiments for example, additional un-masked and/or partially-masked electrodes may be provided which are oriented such that they do not contact the tissue of interest. These non-contact electrodes may be electrically connected with conductors or leads separately from the conductors or leads to the partially-masked electrodes which contact the tissue of interest. Thus, these electrically separate non-contact electrodes may be used to sense the blood pool and/or far field effects separately from the tissue local field. This arrangement is described in greater detail in PCT Application No. PCT/US2016/058244 (published as WO 2017/070559), the entire disclosure of which is incorporated by reference as though fully set forth herein.

Although the partially-masked electrodes described herein are shown as being used in basket electrode assemblies and high density electrode assemblies, it will be understood that the partially-masked electrodes can be used in any type and shape of distal tip assembly for a catheter, including for example only and without limitation, a catheter having a single distal tip assembly which may be steerable.

Additionally, in the various embodiments described herein, the insulated surface coating material, the insulated surface coating thickness, and/or the insulated surface coating location may be selected and configured to allow repeated opening and closing of the splines of the basket electrode assemblies and repeated flexure of the arms of the high density electrode assemblies described herein without cracking, flaking, breaking and/or other failure of the insulated surface coating. This aids durability, longevity and/or reliability of the distal tip assembly having the partially-masked electrodes. Such aspects also reduce the potential for the insulated surface coating to be released from the distal tip assembly and remaining in a patient. Moreover, the surface coating material, the surface coating thickness, and/or the insulated surface coating location may be selected and configured such that the insulated surface coating does not impede or inhibit the opening and closing of the splines of the basket electrode assemblies or the flexure of the arms of the high density electrode assembly described herein. For example, the localized insulated surface coating is only proximate the conductive material as shown in FIGS. 19-22. Because the insulated surface coating is only proximate the conductive material, the impact of the insulated surface coating on the opening and closing of the splines is reduced

or eliminated. Additionally, due to a potential increased stiffness of the spline proximate the conductive material, the localized insulated surface coating is less likely to flex during the opening and closing of the splines. The localized insulated surface coating is thus potentially subject to lower stresses and strains as compared to an insulated surface coating along the entire spline (see e.g., FIGS. 14-18).

While clinical benefits of the partially-masked electrodes have been described herein, the use of the insulated surface coatings to partially mask electrodes may also provide manufacturing advantages. For example only and without limitation, because a surface coating is applied to an electrode and an opening is made to expose a portion of the conductive material of the electrode, the manufacturing tolerances of the conductive material may be reduced. That is, the size of the conductive material does not need to be held to such a tight tolerance because the effective size of the conductive area of the electrode will be determined by the size of the opening in the surface coating. This may allow the use of a common size of conductive material for different applications, wherein the size of the opening is varied for the particular application. This may also reduce manufacturing costs and time.

Among other things, the disclosed catheters, with their plurality of partially-masked electrodes, are useful to (1) define regional propagation maps of particularly sized areas (e.g., one centimeter square areas) within the atrial walls of the heart; (2) identify complex fractionated atrial electrograms for ablation; (3) identify localized, focal potentials between the microelectrodes for higher electrogram resolution; and/or (4) more precisely target areas for ablation. These mapping catheters and ablation catheters are constructed to conform to, and remain in contact with, cardiac tissue despite potentially erratic cardiac motion. Such enhanced stability of the catheter on a heart wall during cardiac motion provides more accurate mapping and ablation due to sustained tissue electrode contact. Additionally, the catheters described herein may be useful for epicardial and/or endocardial use. For example, the planar array embodiments depicted herein may be used in an epicardial procedure where the planar array of partially-masked electrodes is positioned between the myocardial surface and the pericardium. Alternatively the planar array embodiments may be used in an endocardial procedure to quickly sweep and/or analyze the inner surfaces of the myocardium and quickly create high-density maps of the heart tissue's electrical properties.

Now with reference to FIG. 23, a method of using catheters having the partially-masked electrodes described herein is shown and described. At step 2300, the method includes tracking the location of at least one of the partially-masked electrodes 42 within a body of a patient. The insulated coating 56 of at least one of the partially-masked electrodes 42 is selected and configured to allow the reception of a localization signal by the conductive material 54, as described herein. The insulated coating 56 of at least one of the partially-masked electrodes 42 is selected and configured to prevent the reception of at least a significant amount of a far field signal by the conductive material 54. The method further includes, at step 2302, placing the upper perimeter 58p of the insulated coating 56 of at least one of the partially-masked electrodes 42 in contact with a tissue of interest in the body of the patient, the tissue of interest being proximate a blood pool, such that the insulated coating 56 creates a seal between the blood pool and the contoured opening 58 to inhibit the receipt of the far field signal in the blood pool.

Now with reference to FIGS. 24A and 24B, another method of using catheters having the partially-masked electrodes described herein is shown and described. At step 2400, the method includes tracking the location of one of the partially-masked electrodes 42 within a body of a patient. The insulated coating 56 of the partially-masked electrode 42 is selected and configured to allow the reception of a localization signal by the conductive material 54, as described in greater detail elsewhere herein. The insulated coating 56 of the partially-masked electrode 42 is selected and configured to prevent the reception of at least a significant amount of a far field signal by the conductive material 54. At step 2402, the method further includes placing the upper perimeter 58p of the insulated coating 56 of the partially-masked electrode 42 in contact with a tissue of interest at a first location in the body of the patient, the tissue of interest being proximate a blood pool, such that the insulated coating 56 creates a seal between the blood pool and the contoured opening 58 to inhibit the receipt of the far field signal in the blood pool. At step 2404, the method further includes receiving, by the partially-masked electrode 42, a first local electrical signal from the first location on the tissue of interest at the contoured opening 58. The first local electrical signal having a first magnitude, wherein as a result of the seal between the blood pool and the contoured opening the first local electrical signal comprises little or no far field signal.

As shown in FIG. 24B, the method may continue, at step 2406, with moving the partially-masked electrode 42 from the first location to a second location in the body of the patient. At step 2408, the method may further include placing the upper perimeter 58p of the insulated coating 56 of the partially-masked electrode 42 in contact with the tissue of interest at the second location in the body of the patient. The tissue of interest being proximate a blood pool, such that the insulated coating 56 creates a seal between the blood pool and the contoured opening 58, and thereby inhibits the receipt of the far field signal in the blood pool. Then at step 2410, the method may further include, receiving, by the partially-masked electrode 42, a second local electrical signal from the second location on the tissue of interest at the contoured opening 58. The second local electrical signal having a second magnitude, wherein as a result of the seal between the blood pool and the contoured opening the second local electrical signal comprises little or no far field signal. In various embodiments, the second local electrical signal may have a second magnitude different from the first magnitude of the first local electrical signal. Then at step 2412, the method may further include diagnosing the health of the tissue of interest based on the difference between the first magnitude and the second magnitude. That is, the state (e.g., voltage magnitude) of the tissue can be determined and an assessment of the health of the tissue may be able to be made based on the measured state.

In some embodiments consistent with the present disclosure, one or more partially-masked electrodes may be oriented inward (away from the tissue) relative to the catheter. Accordingly, these inward oriented partially-masked electrodes are solely exposed to a blood pool and receives signals from the blood pool indicative of "far field" influences. Controller circuitry may utilize the signal from such inward oriented partially-masked electrodes to filter out such "far field" influences from the signals received from outward facing partially-masked electrodes in contact with the tissue.

Although several embodiments of an apparatus, system, and method in accordance with present teachings have been described above with a certain degree of particularity, those

skilled in the art could make numerous alterations to the disclosed embodiments without departing from the scope of this disclosure. All directional references (e.g., upper, lower, upward, downward, left, right, leftward, rightward, top, bottom, above, below, vertical, horizontal, clockwise and counterclockwise) are only used for identification purposes to aid the reader's understanding of the disclosed embodiments, and do not create limitations, particularly as to the position, orientation, or use of the disclosed embodiments. Joinder references (e.g., attached, coupled, connected, and the like) are to be construed broadly and may include intermediate members between a connection of elements and relative movement between elements. As such, joinder references do not necessarily infer that two elements are directly connected and in fixed relation to each other. It is intended that all matter contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative only and not as limiting. Changes in detail or structure may be made without departing from the present teachings as defined in the appended claims.

Various embodiments are described herein to various apparatuses, systems, and/or methods. Numerous specific details are set forth to provide a thorough understanding of the overall structure, function, manufacture, and use of the embodiments as described in the specification and illustrated in the accompanying drawings. It will be understood by those skilled in the art, however, that the embodiments may be practiced without such specific details. In other instances, well-known operations, components, and elements have not been described in detail so as not to obscure the embodiments described in the specification. Those of ordinary skill in the art will understand that the embodiments described and illustrated herein are non-limiting examples, and thus it can be appreciated that the specific structural and functional details disclosed herein may be representative and do not necessarily limit the scope of the embodiments, the scope of which is defined solely by the appended claims.

Reference throughout the specification to "various embodiments," "some embodiments," "one embodiment," or "an embodiment", or the like, means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, appearances of the phrases "in various embodiments," "in some embodiments," "in one embodiment," or "in an embodiment", or the like, in places throughout the specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Thus, the particular features, structures, or characteristics illustrated or described in connection with one embodiment may be combined, in whole or in part, with the features, structures, or characteristics of one or more other embodiments without limitation given that such combination is not illogical or non-functional.

It will be appreciated that the terms "proximal" and "distal" may be used throughout the specification with reference to a clinician manipulating one end of an instrument used to treat a patient. The term "proximal" refers to the portion of the instrument closest to the clinician and the term "distal" refers to the portion located furthest from the clinician. It will be further appreciated that for conciseness and clarity, spatial terms such as "vertical," "horizontal," "up," and "down" may be used herein with respect to the illustrated embodiments. However, surgical instruments may be used in many orientations and positions, and these terms are not intended to be limiting and absolute.

Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

What is claimed is:

1. A partially-masked electrode for a catheter, comprising: a conductive material; and an insulated coating having an outer surface, wherein the insulated coating is applied locally as a ring having an outer perimeter and an inner perimeter, the inner perimeter and the outer perimeter are aligned such that center points of each of the inner perimeter and the outer perimeter are disposed on a plane parallel to a longitudinal axis of the catheter, the outer perimeter and the inner perimeter of the ring being disposed around an outer perimeter of the conductive material such that the inner perimeter of the ring of insulated coating projects above and over an outer edge of the conductive material to create an overhang of the insulated coating over the conductive material and defines an opening that exposes an area of the conductive material.
2. The partially-masked electrode of claim 1, wherein the insulated coating is applied proximate to the outer perimeter of the conductive material.
3. The partially-masked electrode of claim 1, wherein the insulated coating surrounds the outer edge of the outer perimeter of the conductive material.
4. The partially-masked electrode of claim 1, wherein the opening defined by the insulated coating is smaller than the outer perimeter of the conductive material.
5. The partially-masked electrode of claim 1, wherein the outer perimeter is an ellipsoid.
6. A partially-masked electrode for a catheter, comprising: a conductive material; and an insulated coating having an outer surface, wherein the insulated coating abuts and surrounds an outer edge of the conductive material forming a ring having an outer perimeter and an inner perimeter, wherein the inner perimeter and the outer perimeter are aligned such that center points of each of the inner perimeter and the outer perimeter are disposed on a plane parallel to a longitudinal axis of the catheter, wherein the inner perimeter of the ring at least partially overhangs the outer edge of the conductive material and, wherein the insulated coating defines an opening that exposes an area of the conductive material.
7. The partially-masked electrode of claim 6, wherein the conductive material has an outer perimeter.
8. The partially-masked electrode of claim 7, wherein an area of the opening of the insulated coating is smaller than an area of the conductive material defined by the outer perimeter.
9. The partially-masked electrode of claim 6, wherein the partially-masked electrode comprises a ring electrode and the exposed area of the conductive material is a surface that extends radially about a longitudinal axis of the ring electrode.

10. The partially-masked electrode of claim 6, wherein the insulated coating has a thickness ranging from 0.0003 mm to about 0.0006 mm, and wherein an offset between a perimeter of the opening of the insulated coating and the exposed area of the conductive material is the thickness of the insulated coating.

11. The partially-masked electrode of claim 10, wherein the perimeter of the opening of the insulated coating is configured and arranged to be placed in contact with a tissue of interest, the tissue of interest being proximate a blood pool, the insulated coating configured to create a seal between the blood pool and the opening so that no blood in the blood pool can contact the conductive material.

12. A catheter, comprising: an elongate, deformable shaft comprising a proximal end and a distal end; and a distal tip assembly coupled to the distal end of the shaft, the distal tip assembly comprising a plurality of partially-masked electrodes disposed thereon, wherein at least one of the plurality of partially-masked electrodes comprises a conductive material and an insulated coating having an outer surface, wherein the insulated coating abuts and surrounds an outer edge of the conductive material forming a ring having an outer perimeter and an inner perimeter, wherein the inner perimeter and the outer perimeter are aligned such that center points of each of the inner perimeter and the outer perimeter are disposed on a plane parallel to a longitudinal axis of the catheter, wherein the inner perimeter of the ring at least partially overhangs the outer edge of the conductive material and, wherein the insulated coating defines an opening that exposes an area of the conductive material.

13. The catheter of claim 12, wherein at least one of the plurality of partially-masked electrodes comprises a ring electrode.

14. The catheter of claim 12, wherein the distal tip assembly is a basket electrode assembly, the basket electrode assembly coupled to the distal end of the shaft, the basket electrode assembly further includes a proximal end and a distal end, and a first spline with the plurality of partially-masked electrodes disposed thereon, the basket electrode assembly is configured to assume a compressed state and an expanded state.

15. The catheter of claim 12, wherein the distal tip assembly comprises a high density electrode assembly.

16. The catheter of claim 12, wherein a perimeter of the opening of the insulated coating is placed in contact with a tissue of interest, the tissue of interest being proximate a blood pool, the insulated coating configured and arranged to create a seal between the blood pool and the opening so that no blood in the blood pool contacts the conductive material.

17. The catheter of claim 12, wherein at least one of the plurality of partially-masked electrodes comprises a flex printed electrode.

18. The catheter of claim 12, wherein the distal tip assembly is a flexible tip portion including a flexible framework, the plurality of partially-masked electrodes are disposed on the flexible framework and form a flexible array of partially-masked electrodes configured to conform to tissue.

19. The catheter of claim 12, wherein the insulated coating is configured to isolate the conductive material and to mitigate a reception of at least a portion of a far field signal by the conductive material.