



US012141215B2

(12) **United States Patent**
Leveau et al.

(10) **Patent No.:** **US 12,141,215 B2**
(45) **Date of Patent:** ***Nov. 12, 2024**

(54) **GRAPH-BASED PREDICTION FOR CONTACT SUGGESTION IN A LOCATION SHARING SYSTEM**

(71) Applicant: **Snap Inc.**, Santa Monica, CA (US)

(72) Inventors: **Pierre Leveau**, Paris (FR); **Antoine Sinton**, Courteuil (FR)

(73) Assignee: **Snap Inc.**, Santa Monica, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/450,110**

(22) Filed: **Aug. 15, 2023**

(65) **Prior Publication Data**

US 2023/0385347 A1 Nov. 30, 2023

Related U.S. Application Data

(63) Continuation of application No. 16/353,604, filed on Mar. 14, 2019, now Pat. No. 11,868,414.

(51) **Int. Cl.**

G06F 16/9535 (2019.01)

G06F 3/0484 (2022.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06F 16/9535** (2019.01); **G06N 20/00** (2019.01); **G06F 3/0484** (2013.01); **G06N 3/08** (2013.01)

(58) **Field of Classification Search**

CPC ... G06F 16/9535; G06F 3/0484; G06N 20/00; G06N 3/08

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

666,223 A 1/1901 Shedlock
4,581,634 A 4/1986 Williams

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2887596 A1 7/2015
CN 109863532 A 6/2019

(Continued)

OTHER PUBLICATIONS

Xiang, Rongjing, Jennifer Neville, and Monica Rogati. "Modeling relationship strength in online social networks." Proceedings of the 19th international conference on World wide web. 2010. (Year: 2010).*

(Continued)

Primary Examiner — Mohsen Almani


(74) *Attorney, Agent, or Firm* — Schwegman Lundberg & Woessner, P.A.

(57)

ABSTRACT

Methods, systems, and devices for generating contact suggestions for a user of a social network. A first score is computed for each one of the plurality of users, the first score being computed using an edge-weighted ranking algorithm based on the user graph. A second score is computed, using a machine learning model, for each user of the plurality of users, the second score of each user being, at least partially, based on the first score of said user, with the second score of each user being representative of a probability of a first user sending a connection request to said user. A ranked contact suggestion list of one or more users of the plurality of users is generated, the one or more users being ranked based on their respective second score.

20 Claims, 11 Drawing Sheets



(51)	Int. Cl.					
	G06F 16/9536	(2019.01)		7,124,164 B1	10/2006	Chemtob
	G06N 3/08	(2023.01)		7,149,893 B1	12/2006	Leonard et al.
	G06N 5/022	(2023.01)		7,173,651 B1	2/2007	Knowles
	G06N 20/00	(2019.01)		7,188,143 B2	3/2007	Szeto
(56)	References Cited			7,203,380 B2	4/2007	Chiu et al.
	U.S. PATENT DOCUMENTS			7,206,568 B2	4/2007	Sudit
	4,975,690 A	12/1990	Torres	7,227,937 B1	6/2007	Yoakum et al.
	5,072,412 A	12/1991	Henderson, Jr. et al.	7,237,002 B1	6/2007	Estrada et al.
	5,493,692 A	2/1996	Theimer et al.	7,240,089 B2	7/2007	Boudreau
	5,713,073 A	1/1998	Warsta	7,269,426 B2	9/2007	Kokkonen et al.
	5,754,939 A	5/1998	Herz et al.	7,280,658 B2	10/2007	Amini et al.
	5,855,008 A	12/1998	Goldhaber et al.	7,315,823 B2	1/2008	Brondrup
	5,880,731 A	3/1999	Liles et al.	7,342,587 B2	3/2008	Danzig et al.
	5,883,639 A	3/1999	Walton et al.	7,349,768 B2	3/2008	Bruce et al.
	5,999,932 A	12/1999	Paul	7,356,564 B2	4/2008	Hartselle et al.
	6,012,098 A	1/2000	Bayeh et al.	7,394,345 B1	7/2008	Ehlinger et al.
	6,014,090 A	1/2000	Rosen et al.	7,411,493 B2	8/2008	Smith
	6,023,270 A	2/2000	Brush, II et al.	7,423,580 B2	9/2008	Markhovsky et al.
	6,029,141 A	2/2000	Bezos et al.	7,454,442 B2	11/2008	Cobleigh et al.
	6,038,295 A	3/2000	Mattes	7,468,729 B1	12/2008	Levinson
	6,049,711 A	4/2000	Yehezkel et al.	7,508,419 B2	3/2009	Toyama et al.
	6,154,764 A	11/2000	Nitta et al.	7,519,670 B2	4/2009	Hagale et al.
	6,167,435 A	12/2000	Druckenmiller et al.	7,535,890 B2	5/2009	Rojas
	6,204,840 B1	3/2001	Petelycky et al.	7,546,554 B2	6/2009	Chiu et al.
	6,205,432 B1	3/2001	Gabbard et al.	7,607,096 B2	10/2009	Oreizy et al.
	6,216,141 B1	4/2001	Straub et al.	7,636,755 B2	12/2009	Blattner et al.
	6,223,165 B1	4/2001	Lauffer	7,639,251 B2	12/2009	Gu et al.
	6,285,381 B1	9/2001	Sawano et al.	7,639,943 B1	12/2009	Kalajan
	6,285,987 B1	9/2001	Roth et al.	7,650,231 B2	1/2010	Gadler
	6,310,694 B1	10/2001	Okimoto et al.	7,668,537 B2	2/2010	DeVries
	6,317,789 B1	11/2001	Rakavy et al.	7,770,137 B2	8/2010	Forbes et al.
	6,334,149 B1	12/2001	Davis, Jr. et al.	7,775,885 B2	8/2010	Van Luchene et al.
	6,349,203 B1	2/2002	Asaoka et al.	7,778,973 B2	8/2010	Choi
	6,353,170 B1	3/2002	Eyzaguirre et al.	7,779,444 B2	8/2010	Glad
	6,446,004 B1	9/2002	Cao et al.	7,787,886 B2	8/2010	Markhovsky et al.
	6,449,657 B2	9/2002	Stanbach et al.	7,796,946 B2	9/2010	Eisenbach
	6,456,852 B2	9/2002	Bar et al.	7,801,954 B2	9/2010	Cadiz et al.
	6,484,196 B1	11/2002	Maurille	7,856,360 B2	12/2010	Kramer et al.
	6,487,601 B1	11/2002	Hubacher et al.	7,859,551 B2	12/2010	Bulman et al.
	6,523,008 B1	2/2003	Avrunin	7,885,931 B2	2/2011	Seo et al.
	6,542,749 B2	4/2003	Tanaka et al.	7,925,703 B2	4/2011	Dinan et al.
	6,549,768 B1	4/2003	Fraccaroli	8,001,204 B2	8/2011	Burtner et al.
	6,618,593 B1	9/2003	Drutman et al.	8,032,586 B2	10/2011	Challenger et al.
	6,622,174 B1	9/2003	Ukita et al.	8,082,255 B1	12/2011	Carlson, Jr. et al.
	6,631,463 B1	10/2003	Floyd et al.	8,088,044 B2	1/2012	Tchao et al.
	6,636,247 B1	10/2003	Hamzy et al.	8,090,351 B2	1/2012	Klein
	6,636,855 B2	10/2003	Holloway et al.	8,095,878 B2	1/2012	Bates et al.
	6,643,684 B1	11/2003	Malkin et al.	8,098,904 B2	1/2012	Ioffe et al.
	6,658,095 B1	12/2003	Yoakum et al.	8,099,109 B2	1/2012	Altman et al.
	6,665,531 B1	12/2003	Soderbacka et al.	8,108,774 B2	1/2012	Finn et al.
	6,668,173 B2	12/2003	Greene	8,112,716 B2	2/2012	Kobayashi
	6,684,238 B1	1/2004	Dutta	8,117,281 B2	2/2012	Robinson et al.
	6,684,257 B1	1/2004	Camut et al.	8,130,219 B2	3/2012	Fleury et al.
	6,698,020 B1	2/2004	Zigmond et al.	8,131,597 B2	3/2012	Hudetz
	6,700,506 B1	3/2004	Winkler	8,135,166 B2	3/2012	Rhoads
	6,720,860 B1	4/2004	Narayanaswami	8,136,028 B1	3/2012	Loeb et al.
	6,724,403 B1	4/2004	Santoro et al.	8,146,001 B1	3/2012	Reese
	6,757,713 B1	6/2004	Ogilvie et al.	8,146,005 B2	3/2012	Jones et al.
	6,772,195 B1	8/2004	Hatlelid et al.	8,151,191 B2	4/2012	Nicol
	6,832,222 B1	12/2004	Zimowski	8,161,115 B2	4/2012	Yamamoto
	6,834,195 B2	12/2004	Brandenberg et al.	8,161,417 B1	4/2012	Lee
	6,836,792 B1	12/2004	Chen	8,195,203 B1	6/2012	Tseng
	6,842,779 B1	1/2005	Nishizawa	8,199,747 B2	6/2012	Rojas et al.
	6,898,626 B2	5/2005	Ohashi	8,208,943 B2	6/2012	Petersen
	6,959,324 B1	10/2005	Kubik et al.	8,214,443 B2	7/2012	Hamburg
	6,970,088 B2	11/2005	Kovach	8,234,350 B1	7/2012	Gu et al.
	6,970,907 B1	11/2005	Ullmann et al.	8,276,092 B1	9/2012	Narayanan et al.
	6,980,909 B2	12/2005	Root et al.	8,279,319 B2	10/2012	Date
	6,981,040 B1	12/2005	Konig et al.	8,280,406 B2	10/2012	Ziskind et al.
	7,020,494 B2	3/2006	Spiestersbach et al.	8,285,199 B2	10/2012	Hsu et al.
	7,027,124 B2	4/2006	Foote et al.	8,287,380 B2	10/2012	Nguyen et al.
	7,072,963 B2	7/2006	Anderson et al.	8,301,159 B2	10/2012	Hamynen et al.
	7,085,571 B2	8/2006	Kalhan et al.	8,306,922 B1	11/2012	Kunal et al.
	7,110,744 B2	9/2006	Freeny, Jr.	8,312,086 B2	11/2012	Velusamy et al.
				8,312,097 B1	11/2012	Siegel et al.
				8,326,315 B2	12/2012	Phillips et al.
				8,326,327 B2	12/2012	Hymel et al.
				8,332,475 B2	12/2012	Rosen et al.
				8,352,546 B1	1/2013	Dollard

(56)

References Cited

U.S. PATENT DOCUMENTS

8,379,130 B2	2/2013	Forutanpour et al.	9,100,806 B2	8/2015	Rosen et al.
8,384,719 B2	2/2013	Reville et al.	9,100,807 B2	8/2015	Rosen et al.
8,385,950 B1	2/2013	Wagner et al.	9,105,014 B2	8/2015	Collet et al.
RE44,054 E	3/2013	Kim	9,113,301 B1	8/2015	Spiegel et al.
8,396,708 B2	3/2013	Park et al.	9,119,027 B2	8/2015	Sharon et al.
8,402,097 B2	3/2013	Szeto	9,123,074 B2	9/2015	Jacobs et al.
8,405,773 B2	3/2013	Hayashi et al.	9,143,382 B2	9/2015	Bhogal et al.
8,418,067 B2	4/2013	Cheng et al.	9,143,681 B1	9/2015	Ebsen et al.
8,423,409 B2	4/2013	Rao	9,152,477 B1	10/2015	Campbell et al.
8,425,322 B2	4/2013	Gillo et al.	9,191,776 B2	11/2015	Root et al.
8,458,601 B2	6/2013	Castelli et al.	9,204,252 B2	12/2015	Root
8,462,198 B2	6/2013	Lin et al.	9,225,897 B1	12/2015	Sehn et al.
8,471,914 B2	6/2013	Sakiyama et al.	9,241,184 B2	1/2016	Weerasinghe
8,472,935 B1	6/2013	Fujisaki	9,256,860 B2	2/2016	Herger et al.
8,484,158 B2	7/2013	Deluca et al.	9,258,459 B2	2/2016	Hartley
8,495,503 B2	7/2013	Brown et al.	9,298,257 B2	3/2016	Hwang et al.
8,495,505 B2	7/2013	Smith et al.	9,314,692 B2	4/2016	Konoplev et al.
8,504,926 B2	8/2013	Wolf	9,330,483 B2	5/2016	Du et al.
8,510,383 B2	8/2013	Hurley et al.	9,344,606 B2	5/2016	Hartley et al.
8,527,345 B2	9/2013	Rothschild et al.	9,357,174 B2	5/2016	Li et al.
8,554,627 B2	10/2013	Svendsen et al.	9,361,510 B2	6/2016	Yao et al.
8,559,980 B2	10/2013	Pujol	9,378,576 B2	6/2016	Bouaziz et al.
8,560,612 B2	10/2013	Kilmer et al.	9,385,983 B1	7/2016	Sehn
8,564,621 B2	10/2013	Branson et al.	9,396,354 B1	7/2016	Murphy et al.
8,564,710 B2	10/2013	Nonaka et al.	9,402,057 B2	7/2016	Kaytaz et al.
8,581,911 B2	11/2013	Becker et al.	9,407,712 B1	8/2016	Sehn
8,594,680 B2	11/2013	Ledlie et al.	9,407,816 B1	8/2016	Sehn
8,597,121 B2	12/2013	Andres del Valle	9,412,192 B2	8/2016	Mandel et al.
8,601,051 B2	12/2013	Wang	9,430,783 B1	8/2016	Sehn
8,601,379 B2	12/2013	Marks et al.	9,439,041 B2	9/2016	Parvizi et al.
8,613,089 B1	12/2013	Holloway et al.	9,443,227 B2	9/2016	Evans et al.
8,632,408 B2	1/2014	Gillo et al.	9,450,907 B2	9/2016	Pridmore et al.
8,648,865 B2	2/2014	Dawson et al.	9,459,778 B2	10/2016	Hogeg et al.
8,659,548 B2	2/2014	Hildreth	9,460,541 B2	10/2016	Li et al.
8,660,358 B1	2/2014	Bergboer et al.	9,489,661 B2	11/2016	Evans et al.
8,660,369 B2	2/2014	Llano et al.	9,489,760 B2	11/2016	Li et al.
8,660,793 B2	2/2014	Ngo et al.	9,491,134 B2	11/2016	Rosen et al.
8,682,350 B2	3/2014	Altman et al.	9,503,845 B2	11/2016	Vincent
8,683,354 B2	3/2014	Khandelwal et al.	9,508,197 B2	11/2016	Quinn et al.
8,692,830 B2	4/2014	Nelson et al.	9,532,171 B2	12/2016	Allen et al.
8,718,333 B2	5/2014	Wolf et al.	9,537,811 B2	1/2017	Allen et al.
8,724,622 B2	5/2014	Rojas	9,544,257 B2	1/2017	Ogundokun et al.
8,732,168 B2	5/2014	Johnson	9,576,400 B2	2/2017	Van Os et al.
8,744,523 B2	6/2014	Fan et al.	9,589,357 B2	3/2017	Li et al.
8,745,132 B2	6/2014	Obradovich	9,592,449 B2	3/2017	Barbalet et al.
8,761,800 B2	6/2014	Kuwahara	9,628,950 B1	4/2017	Noeth et al.
8,768,876 B2	7/2014	Shim et al.	9,648,376 B2	5/2017	Chang et al.
8,775,972 B2	7/2014	Spiegel	9,697,635 B2	7/2017	Quinn et al.
8,788,680 B1	7/2014	Naik	9,706,040 B2	7/2017	Kadirvel et al.
8,790,187 B2	7/2014	Walker et al.	9,710,821 B2	7/2017	Heath
8,797,415 B2	8/2014	Arnold	9,744,466 B2	8/2017	Fujioka
8,798,646 B1	8/2014	Wang et al.	9,746,990 B2	8/2017	Anderson et al.
8,810,513 B2	8/2014	Ptucha et al.	9,749,270 B2	8/2017	Collet et al.
8,812,171 B2	8/2014	Filev et al.	9,792,714 B2	10/2017	Li et al.
8,832,201 B2	9/2014	Wall	9,839,844 B2	12/2017	Dunstan et al.
8,832,552 B2	9/2014	Arrasvuori et al.	9,854,219 B2	12/2017	Sehn
8,839,327 B2	9/2014	Amento et al.	9,883,838 B2	2/2018	Kaleal, III et al.
8,856,349 B2	10/2014	Jain et al.	9,898,849 B2	2/2018	Du et al.
8,874,677 B2	10/2014	Rosen et al.	9,911,073 B1	3/2018	Spiegel et al.
8,886,227 B2	11/2014	Schmidt et al.	9,936,165 B2	4/2018	Li et al.
8,890,926 B2	11/2014	Tandon et al.	9,959,037 B2	5/2018	Chaudhri et al.
8,892,999 B2	11/2014	Nims et al.	9,980,100 B1	5/2018	Charlton et al.
8,909,679 B2	12/2014	Root et al.	9,990,373 B2	6/2018	Fortkort
8,909,725 B1	12/2014	Sehn	10,039,988 B2	8/2018	Lobb et al.
8,924,250 B2	12/2014	Bates et al.	10,097,492 B2	10/2018	Tsuda et al.
8,963,926 B2	2/2015	Brown et al.	10,116,598 B2	10/2018	Tucker et al.
8,972,357 B2	3/2015	Shim et al.	10,155,168 B2	12/2018	Blackstock et al.
8,989,786 B2	3/2015	Feghali	10,242,477 B1	3/2019	Charlton et al.
8,995,433 B2	3/2015	Rojas	10,242,503 B2	3/2019	McPhee et al.
9,015,285 B1	4/2015	Ebsen et al.	10,262,250 B1	4/2019	Spiegel et al.
9,020,745 B2	4/2015	Johnston et al.	10,362,219 B2	7/2019	Wilson et al.
9,040,574 B2	5/2015	Wang et al.	10,475,225 B2	11/2019	Park et al.
9,055,416 B2	6/2015	Rosen et al.	10,504,266 B2	12/2019	Blattner et al.
9,086,776 B2	7/2015	Ye et al.	10,573,048 B2	2/2020	Ni et al.
9,094,137 B1	7/2015	Sehn et al.	10,657,701 B2	5/2020	Osman et al.
			10,674,311 B1	6/2020	Bouba et al.
			10,893,385 B1	1/2021	Berardino et al.
			10,936,066 B1	3/2021	Jaureguiberry et al.
			10,939,246 B1	3/2021	Dancie et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

10,945,098 B2	3/2021	Dancie et al.	2007/0136228 A1	6/2007	Petersen
11,032,670 B1	6/2021	Baylin et al.	2007/0168863 A1	7/2007	Blattner et al.
11,039,270 B2	6/2021	Bouba et al.	2007/0176921 A1	8/2007	Iwasaki et al.
11,166,123 B1	11/2021	Guillaume	2007/0192128 A1	8/2007	Celestini
11,275,439 B2	3/2022	Jaureguiberry et al.	2007/0198340 A1	8/2007	Lucovsky et al.
11,294,936 B1	4/2022	Jaureguiberry	2007/0198495 A1	8/2007	Buron et al.
11,307,747 B2	4/2022	Dancie et al.	2007/0208751 A1	9/2007	Cowan et al.
11,868,414 B1	1/2024	Leveau et al.	2007/0210936 A1	9/2007	Nicholson
2002/0047868 A1	4/2002	Miyazawa	2007/0214180 A1	9/2007	Crawford
2002/0067362 A1	6/2002	Agostino Nocera et al.	2007/0214216 A1	9/2007	Carrer et al.
2002/0078456 A1	6/2002	Hudson et al.	2007/0233556 A1	10/2007	Koningstein
2002/0087631 A1	7/2002	Sharma	2007/0233801 A1	10/2007	Eren et al.
2002/0097257 A1	7/2002	Miller et al.	2007/0233859 A1	10/2007	Zhao et al.
2002/0122659 A1	9/2002	Mcgrath et al.	2007/0243887 A1	10/2007	Bandhole et al.
2002/0128047 A1	9/2002	Gates	2007/0244750 A1	10/2007	Grannan et al.
2002/0144154 A1	10/2002	Tomkow	2007/0255456 A1	11/2007	Funayama
2002/0169644 A1	11/2002	Greene	2007/0281690 A1	12/2007	Altman et al.
2003/0001846 A1	1/2003	Davis et al.	2008/0022329 A1	1/2008	Glad
2003/0016247 A1	1/2003	Lai et al.	2008/0025701 A1	1/2008	Ikeda
2003/0017823 A1	1/2003	Mager et al.	2008/0032703 A1	2/2008	Krumm et al.
2003/0020623 A1	1/2003	Cao et al.	2008/0033930 A1	2/2008	Warren
2003/0023874 A1	1/2003	Prokupets et al.	2008/0043041 A2	2/2008	Hedenstroem et al.
2003/0037124 A1	2/2003	Yamaura et al.	2008/0049704 A1	2/2008	Witteman et al.
2003/0052925 A1	3/2003	Daimon et al.	2008/0062141 A1	3/2008	Chandhri
2003/0101230 A1	5/2003	Benschoter et al.	2008/0076505 A1	3/2008	Ngyen et al.
2003/0110503 A1	6/2003	Perkes	2008/0092233 A1	4/2008	Tian et al.
2003/0126215 A1	7/2003	Udell	2008/0094387 A1	4/2008	Chen
2003/0148773 A1	8/2003	Spriestersbach et al.	2008/0097980 A1	4/2008	Sullivan
2003/0164856 A1	9/2003	Prager et al.	2008/0104503 A1	5/2008	Beall et al.
2003/0229607 A1	12/2003	Zellweger et al.	2008/0109844 A1	5/2008	Baldeschweiler et al.
2004/0027371 A1	2/2004	Jaeger	2008/0120409 A1	5/2008	Sun et al.
2004/0064429 A1	4/2004	Hirstius et al.	2008/0147730 A1	6/2008	Lee et al.
2004/0078367 A1	4/2004	Anderson et al.	2008/0148150 A1	6/2008	Mall
2004/0111467 A1	6/2004	Willis	2008/0158222 A1	7/2008	Li et al.
2004/0158739 A1	8/2004	Wakai et al.	2008/0158230 A1	7/2008	Sharma et al.
2004/0189465 A1	9/2004	Capobianco et al.	2008/0168033 A1	7/2008	Ott et al.
2004/0203959 A1	10/2004	Coombes	2008/0168489 A1	7/2008	Schraga
2004/0215625 A1	10/2004	Svendsen et al.	2008/0189177 A1	8/2008	Anderton et al.
2004/0243531 A1	12/2004	Dean	2008/0207176 A1	8/2008	Brackbill et al.
2004/0243688 A1	12/2004	Wugofski	2008/0208692 A1	8/2008	Garaventi et al.
2005/0021444 A1	1/2005	Bauer et al.	2008/0214210 A1	9/2008	Rasanen et al.
2005/0022211 A1	1/2005	Veselov et al.	2008/0222545 A1	9/2008	Lemay
2005/0048989 A1	3/2005	Jung	2008/0255976 A1	10/2008	Altberg et al.
2005/0078804 A1	4/2005	Yomoda	2008/0256446 A1	10/2008	Yamamoto
2005/0097176 A1	5/2005	Schatz et al.	2008/0256577 A1	10/2008	Funaki et al.
2005/0102381 A1	5/2005	Jiang et al.	2008/0266421 A1	10/2008	Takahata et al.
2005/0104976 A1	5/2005	Currans	2008/0270938 A1	10/2008	Carlson
2005/0114783 A1	5/2005	Szeto	2008/0288338 A1	11/2008	Wiseman et al.
2005/0119936 A1	6/2005	Buchanan et al.	2008/0306826 A1	12/2008	Kramer et al.
2005/0122405 A1	6/2005	Voss et al.	2008/0313329 A1	12/2008	Wang et al.
2005/0162419 A1	7/2005	Kim et al.	2008/0313346 A1	12/2008	Kujawa et al.
2005/0193340 A1	9/2005	Amburgey et al.	2008/0318616 A1	12/2008	Chipalkatti et al.
2005/0193345 A1	9/2005	Klassen et al.	2009/0006191 A1	1/2009	Arankalle et al.
2005/0198128 A1	9/2005	Anderson	2009/0006565 A1	1/2009	Velusamy et al.
2005/0206610 A1	9/2005	Cordelli	2009/0015703 A1	1/2009	Kim et al.
2005/0223066 A1	10/2005	Buchheit et al.	2009/0016617 A1	1/2009	Bregman-amitai et al.
2005/0288954 A1	12/2005	McCarthy et al.	2009/0024956 A1	1/2009	Kobayashi
2006/0026067 A1	2/2006	Nicholas et al.	2009/0030774 A1	1/2009	Rothschild et al.
2006/0107297 A1	5/2006	Toyama et al.	2009/0030999 A1	1/2009	Gatzke et al.
2006/0114338 A1	6/2006	Rothschild	2009/0040324 A1	2/2009	Nonaka
2006/0119882 A1	6/2006	Harris et al.	2009/0042588 A1	2/2009	Lottin et al.
2006/0242239 A1	10/2006	Morishima et al.	2009/0055484 A1	2/2009	Vuong et al.
2006/0252438 A1	11/2006	Ansamaa et al.	2009/0058822 A1	3/2009	Chaudhri
2006/0265417 A1	11/2006	Amato et al.	2009/0070688 A1	3/2009	Gyorfi et al.
2006/0270419 A1	11/2006	Crowley et al.	2009/0079846 A1	3/2009	Chou
2006/0287878 A1	12/2006	Wadhwa et al.	2009/0089678 A1	4/2009	Sacco et al.
2006/0294465 A1	12/2006	Ronen et al.	2009/0089710 A1	4/2009	Wood et al.
2007/0004426 A1	1/2007	Pfleging et al.	2009/0093261 A1	4/2009	Ziskind
2007/0038715 A1	2/2007	Collins et al.	2009/0099925 A1	4/2009	Mehta et al.
2007/0040931 A1	2/2007	Nishizawa	2009/0106672 A1	4/2009	Burstrom
2007/0073517 A1	3/2007	Panje	2009/0132341 A1	5/2009	Klinger
2007/0073823 A1	3/2007	Cohen et al.	2009/0132453 A1	5/2009	Hangartner et al.
2007/0075898 A1	4/2007	Markhovsky et al.	2009/0132665 A1	5/2009	Thomsen et al.
2007/0082707 A1	4/2007	Flynt et al.	2009/0148045 A1	6/2009	Lee et al.
2007/0113181 A1	5/2007	Blattner et al.	2009/0153492 A1	6/2009	Popp
			2009/0157450 A1	6/2009	Athsani et al.
			2009/0157752 A1	6/2009	Gonzalez
			2009/0158170 A1	6/2009	Narayanan et al.
			2009/0160970 A1	6/2009	Fredlund et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0163182	A1	6/2009	Gatti et al.	2011/0083101	A1	4/2011	Sharon et al.
2009/0177299	A1	7/2009	Van De Sluis	2011/0093780	A1	4/2011	Dunn
2009/0177976	A1	7/2009	Bokor et al.	2011/0102630	A1	5/2011	Rukes
2009/0192900	A1	7/2009	Collision	2011/0115798	A1	5/2011	Nayar et al.
2009/0199242	A1	8/2009	Johnson et al.	2011/0119133	A1	5/2011	Igelman et al.
2009/0202114	A1	8/2009	Morin et al.	2011/0137881	A1	6/2011	Cheng et al.
2009/0215469	A1	8/2009	Fisher et al.	2011/0145564	A1	6/2011	Moshir et al.
2009/0232354	A1	9/2009	Camp, Jr. et al.	2011/0148864	A1	6/2011	Lee et al.
2009/0234815	A1	9/2009	Boerries et al.	2011/0159890	A1	6/2011	Fortescue et al.
2009/0239552	A1	9/2009	Churchill et al.	2011/0164163	A1	7/2011	Bilbrey et al.
2009/0249222	A1	10/2009	Schmidt et al.	2011/0197194	A1	8/2011	D'Angelo et al.
2009/0249244	A1	10/2009	Robinson et al.	2011/0202598	A1	8/2011	Evans et al.
2009/0265604	A1	10/2009	Howard et al.	2011/0202968	A1	8/2011	Nurmi
2009/0265647	A1	10/2009	Martin et al.	2011/0211534	A1	9/2011	Schmidt et al.
2009/0288022	A1	11/2009	Almstrand et al.	2011/0213845	A1	9/2011	Logan et al.
2009/0291672	A1	11/2009	Treves et al.	2011/0215966	A1	9/2011	Kim et al.
2009/0292608	A1	11/2009	Polachek	2011/0225048	A1	9/2011	Nair
2009/0300525	A1	12/2009	Jolliff et al.	2011/0238763	A1	9/2011	Shin et al.
2009/0303984	A1	12/2009	Clark et al.	2011/0239136	A1	9/2011	Goldman et al.
2009/0319288	A1*	12/2009	Slaney G06Q 10/10 705/1.1	2011/0255736	A1	10/2011	Thompson et al.
2009/0319607	A1	12/2009	Belz et al.	2011/0273575	A1	11/2011	Lee
2009/0327073	A1	12/2009	Li	2011/0282799	A1	11/2011	Huston
2010/0011422	A1	1/2010	Mason et al.	2011/0283188	A1	11/2011	Farrenkopf
2010/0023885	A1	1/2010	Reville et al.	2011/0314419	A1	12/2011	Dunn et al.
2010/0062794	A1	3/2010	Han	2011/0320373	A1	12/2011	Lee et al.
2010/0082427	A1	4/2010	Burgener et al.	2012/0028659	A1	2/2012	Whitney et al.
2010/0082693	A1	4/2010	Hugg et al.	2012/0033718	A1	2/2012	Kauffman et al.
2010/0100568	A1	4/2010	Papin et al.	2012/0036015	A1	2/2012	Sheikh
2010/0113065	A1	5/2010	Narayan et al.	2012/0036443	A1	2/2012	Ohmori et al.
2010/0115426	A1	5/2010	Liu et al.	2012/0054797	A1	3/2012	Skog et al.
2010/0130233	A1	5/2010	Parker	2012/0059722	A1	3/2012	Rao
2010/0131880	A1	5/2010	Lee et al.	2012/0062805	A1	3/2012	Candelore
2010/0131895	A1	5/2010	Wohlert	2012/0084731	A1	4/2012	Filman et al.
2010/0153144	A1	6/2010	Miller et al.	2012/0084835	A1	4/2012	Thomas et al.
2010/0159944	A1	6/2010	Pascal et al.	2012/0099800	A1	4/2012	Llano et al.
2010/0161658	A1	6/2010	Hamynen et al.	2012/0108293	A1	5/2012	Law et al.
2010/0161831	A1	6/2010	Haas et al.	2012/0110096	A1	5/2012	Smarr et al.
2010/0162149	A1	6/2010	Sheleheda et al.	2012/0113106	A1	5/2012	Choi et al.
2010/0183280	A1	7/2010	Beauregard et al.	2012/0113143	A1	5/2012	Adhikari et al.
2010/0185552	A1	7/2010	Deluca et al.	2012/0113272	A1	5/2012	Hata
2010/0185665	A1	7/2010	Horn et al.	2012/0123830	A1	5/2012	Svendsen et al.
2010/0191631	A1	7/2010	Weidmann	2012/0123871	A1	5/2012	Svendsen et al.
2010/0197318	A1	8/2010	Petersen et al.	2012/0123875	A1	5/2012	Svendsen et al.
2010/0197319	A1	8/2010	Petersen et al.	2012/0124126	A1	5/2012	Alcazar et al.
2010/0198683	A1	8/2010	Aarabi	2012/0124176	A1	5/2012	Curtis et al.
2010/0198694	A1	8/2010	Muthukrishnan	2012/0124458	A1	5/2012	Cruzada
2010/0198826	A1	8/2010	Petersen et al.	2012/0130717	A1	5/2012	Xu et al.
2010/0198828	A1	8/2010	Petersen et al.	2012/0131507	A1	5/2012	Sparandara et al.
2010/0198862	A1	8/2010	Jennings et al.	2012/0131512	A1	5/2012	Takeuchi et al.
2010/0198870	A1	8/2010	Petersen et al.	2012/0143760	A1	6/2012	Abulafia et al.
2010/0198917	A1	8/2010	Petersen et al.	2012/0150978	A1	6/2012	Monaco
2010/0201482	A1	8/2010	Robertson et al.	2012/0158622	A1	6/2012	Mital et al.
2010/0201536	A1	8/2010	Robertson et al.	2012/0165100	A1	6/2012	Lalancette et al.
2010/0203968	A1	8/2010	Gill et al.	2012/0166971	A1	6/2012	Sachson et al.
2010/0214436	A1	8/2010	Kim et al.	2012/0169855	A1	7/2012	Oh
2010/0223128	A1	9/2010	Dukellis et al.	2012/0172062	A1	7/2012	Altman et al.
2010/0223343	A1	9/2010	Bosan et al.	2012/0173991	A1	7/2012	Roberts et al.
2010/0227682	A1	9/2010	Reville et al.	2012/0176401	A1	7/2012	Hayward et al.
2010/0250109	A1	9/2010	Johnston et al.	2012/0184248	A1	7/2012	Speede
2010/0257196	A1	10/2010	Waters et al.	2012/0197724	A1	8/2012	Kendall
2010/0259386	A1	10/2010	Holley et al.	2012/0200743	A1	8/2012	Blanchflower et al.
2010/0273509	A1	10/2010	Sweeney et al.	2012/0209924	A1	8/2012	Evans et al.
2010/0281045	A1	11/2010	Dean	2012/0210244	A1	8/2012	De Francisco Lopez et al.
2010/0306669	A1	12/2010	Della Pasqua	2012/0212632	A1	8/2012	Mate et al.
2010/0311395	A1	12/2010	Zheng et al.	2012/0220264	A1	8/2012	Kawabata
2011/0004071	A1	1/2011	Faiola et al.	2012/0226748	A1	9/2012	Bosworth et al.
2011/0010205	A1	1/2011	Richards	2012/0233000	A1	9/2012	Fisher et al.
2011/0029512	A1	2/2011	Folgnier et al.	2012/0236162	A1	9/2012	Imamura
2011/0040783	A1	2/2011	Uemichi et al.	2012/0239761	A1	9/2012	Linner et al.
2011/0040804	A1	2/2011	Peirce et al.	2012/0250951	A1	10/2012	Chen
2011/0050909	A1	3/2011	Ellenby et al.	2012/0252418	A1	10/2012	Kandekar et al.
2011/0050915	A1	3/2011	Wang et al.	2012/0254325	A1	10/2012	Majeti et al.
2011/0064388	A1	3/2011	Brown et al.	2012/0278387	A1	11/2012	Garcia et al.
2011/0066743	A1	3/2011	Hurley et al.	2012/0278692	A1	11/2012	Shi
				2012/0290637	A1	11/2012	Perantatos et al.
				2012/0299954	A1	11/2012	Wada et al.
				2012/0304052	A1	11/2012	Tanaka et al.
				2012/0304080	A1	11/2012	Wormald et al.
				2012/0307096	A1	12/2012	Ford et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0307112 A1	12/2012	Kunishige et al.	2014/0096029 A1	4/2014	Schultz
2012/0319904 A1	12/2012	Lee et al.	2014/0114565 A1	4/2014	Aziz et al.
2012/0323933 A1	12/2012	He et al.	2014/0122658 A1	5/2014	Haeger et al.
2012/0324018 A1	12/2012	Metcalf et al.	2014/0122787 A1	5/2014	Shalvi et al.
2013/0006759 A1	1/2013	Srivastava et al.	2014/0125678 A1	5/2014	Wang et al.
2013/0024757 A1	1/2013	Doll et al.	2014/0129343 A1	5/2014	Finster et al.
2013/0036364 A1	2/2013	Johnson	2014/0129953 A1	5/2014	Spiegel
2013/0045753 A1	2/2013	Obermeyer et al.	2014/0143143 A1	5/2014	Fasoli et al.
2013/0050260 A1	2/2013	Reitan	2014/0149519 A1	5/2014	Redfern et al.
2013/0055083 A1	2/2013	Fino	2014/0155102 A1	6/2014	Cooper et al.
2013/0057587 A1	3/2013	Leonard et al.	2014/0173424 A1	6/2014	Hogeg et al.
2013/0059607 A1	3/2013	Herz et al.	2014/0173457 A1	6/2014	Wang et al.
2013/0060690 A1	3/2013	Oskolkov et al.	2014/0189592 A1	7/2014	Benchenaa et al.
2013/0063369 A1	3/2013	Malhotra et al.	2014/0207679 A1	7/2014	Cho
2013/0067027 A1	3/2013	Song et al.	2014/0214471 A1	7/2014	Schreiner, III
2013/0071093 A1	3/2013	Hanks et al.	2014/0222564 A1	8/2014	Kranendonk et al.
2013/0080254 A1	3/2013	Thramann	2014/0258405 A1	9/2014	Perkin
2013/0085790 A1	4/2013	Palmer et al.	2014/0265359 A1	9/2014	Cheng et al.
2013/0086072 A1	4/2013	Peng et al.	2014/0266703 A1	9/2014	Dalley, Jr. et al.
2013/0090171 A1	4/2013	Holton et al.	2014/0279061 A1	9/2014	Elimeliah et al.
2013/0095857 A1	4/2013	Garcia et al.	2014/0279436 A1	9/2014	Dorsey et al.
2013/0103760 A1	4/2013	Golding et al.	2014/0279540 A1	9/2014	Jackson
2013/0104053 A1	4/2013	Thornton et al.	2014/0280537 A1	9/2014	Pridmore et al.
2013/0110885 A1	5/2013	Brundrett, III	2014/0282096 A1	9/2014	Rubinstein et al.
2013/0111514 A1	5/2013	Slavin et al.	2014/0287779 A1	9/2014	O'keefe et al.
2013/0128059 A1	5/2013	Kristensson	2014/0289833 A1	9/2014	Briceno
2013/0129252 A1	5/2013	Lauper	2014/0306986 A1	10/2014	Gottesman et al.
2013/0132477 A1	5/2013	Bosworth et al.	2014/0317302 A1	10/2014	Naik
2013/0145286 A1	6/2013	Feng et al.	2014/0324627 A1	10/2014	Haver et al.
2013/0159110 A1	6/2013	Rajaram et al.	2014/0324629 A1	10/2014	Jacobs
2013/0159919 A1	6/2013	Leydon	2014/0325383 A1	10/2014	Brown et al.
2013/0169822 A1	7/2013	Zhu et al.	2015/0020086 A1	1/2015	Chen et al.
2013/0173729 A1	7/2013	Starenky et al.	2015/0046278 A1	2/2015	Pei et al.
2013/0182133 A1	7/2013	Tanabe	2015/0071619 A1	3/2015	Brough
2013/0185131 A1	7/2013	Sinha et al.	2015/0081725 A1	3/2015	Ogawa et al.
2013/0191198 A1	7/2013	Carlson et al.	2015/0087263 A1	3/2015	Branscomb et al.
2013/0194301 A1	8/2013	Robbins et al.	2015/0088622 A1	3/2015	Ganschow et al.
2013/0198176 A1	8/2013	Kim	2015/0095020 A1	4/2015	Leydon
2013/0201187 A1	8/2013	Tong et al.	2015/0096042 A1	4/2015	Mizrachi
2013/0218965 A1	8/2013	Abrol et al.	2015/0116529 A1	4/2015	Wu et al.
2013/0218968 A1	8/2013	Mcevilley et al.	2015/0169827 A1	6/2015	Laborde
2013/0222323 A1	8/2013	Mckenzie	2015/0172534 A1	6/2015	Miyakawa et al.
2013/0227476 A1	8/2013	Frey	2015/0178260 A1	6/2015	Brunson
2013/0232194 A1	9/2013	Knapp et al.	2015/0206349 A1	7/2015	Rosenthal et al.
2013/0249948 A1	9/2013	Reitan	2015/0222814 A1	8/2015	Li et al.
2013/0257877 A1	10/2013	Davis	2015/0261917 A1	9/2015	Smith
2013/0263031 A1	10/2013	Oshiro et al.	2015/0301579 A1 *	10/2015	Vaccari G06F 16/29 713/340
2013/0265450 A1	10/2013	Barnes, Jr.	2015/0312184 A1	10/2015	Langholz et al.
2013/0267253 A1	10/2013	Case et al.	2015/0350136 A1	12/2015	Flynn, III et al.
2013/0275505 A1	10/2013	Gauglitz et al.	2015/0365795 A1	12/2015	Allen et al.
2013/0290443 A1	10/2013	Collins et al.	2015/0370798 A1 *	12/2015	Ju H04L 12/185 707/748
2013/0304646 A1	11/2013	De Geer	2015/0378502 A1	12/2015	Hu et al.
2013/0311255 A1	11/2013	Cummins et al.	2016/0006927 A1	1/2016	Sehn
2013/0325964 A1	12/2013	Berberat	2016/0014063 A1	1/2016	Hogeg et al.
2013/0344896 A1	12/2013	Kirmse et al.	2016/0085773 A1	3/2016	Chang et al.
2013/0346869 A1	12/2013	Asver et al.	2016/0085863 A1	3/2016	Allen et al.
2013/0346877 A1	12/2013	Borovoy et al.	2016/0099901 A1	4/2016	Allen et al.
2014/0006129 A1	1/2014	Heath	2016/0134840 A1	5/2016	Mcculloch
2014/0011538 A1	1/2014	Mulcahy et al.	2016/0180887 A1	6/2016	Sehn
2014/0012918 A1	1/2014	Chin et al.	2016/0182422 A1	6/2016	Sehn et al.
2014/0019264 A1	1/2014	Wachman et al.	2016/0182875 A1	6/2016	Sehn
2014/0032682 A1	1/2014	Prado et al.	2016/0234149 A1	8/2016	Tsuda et al.
2014/0043204 A1	2/2014	Basnayake et al.	2016/0239248 A1	8/2016	Sehn
2014/0043329 A1	2/2014	Wang et al.	2016/0277419 A1	9/2016	Allen et al.
2014/0045530 A1	2/2014	Gordon et al.	2016/0321708 A1	11/2016	Sehn
2014/0047016 A1	2/2014	Rao	2016/0358214 A1	12/2016	Shalunov et al.
2014/0047045 A1	2/2014	Baldwin et al.	2017/0006094 A1	1/2017	Abou Mahmoud et al.
2014/0047335 A1	2/2014	Lewis et al.	2017/0011037 A1 *	1/2017	Qian G06Q 50/01
2014/0049652 A1	2/2014	Moon et al.	2017/0061308 A1	3/2017	Chen et al.
2014/0052485 A1	2/2014	Shidfar	2017/0080346 A1	3/2017	Abbas
2014/0052633 A1	2/2014	Gandhi	2017/0087473 A1	3/2017	Siegel et al.
2014/0055554 A1	2/2014	Du et al.	2017/0113140 A1	4/2017	Blackstock et al.
2014/0057660 A1	2/2014	Wager	2017/0118145 A1	4/2017	Aittoniemi et al.
2014/0082651 A1	3/2014	Sharifi	2017/0199855 A1	7/2017	Fishbeck
2014/0092130 A1	4/2014	Anderson et al.	2017/0235848 A1	8/2017	Van Deusen et al.
			2017/0287006 A1	10/2017	Azmoodeh et al.
			2017/0310934 A1	10/2017	Du et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0312634	A1	11/2017	Ledoux et al.
2018/0047200	A1	2/2018	O'hara et al.
2018/0113587	A1	4/2018	Allen et al.
2018/0115503	A1	4/2018	Baldwin et al.
2018/0150464	A1 *	5/2018	Ma H04L 67/55
2018/0315076	A1	11/2018	Andreou
2018/0315133	A1	11/2018	Brody et al.
2018/0315134	A1	11/2018	Amitay et al.
2019/0001223	A1	1/2019	Blackstock et al.
2019/0057616	A1	2/2019	Cohen et al.
2019/0188749	A1	6/2019	Peng et al.
2019/0188920	A1	6/2019	Mcphee et al.
2020/0314586	A1	10/2020	Bouba et al.
2020/0382912	A1	12/2020	Dancie et al.
2020/0401225	A1	12/2020	Jaureguiberry et al.
2021/0011612	A1	1/2021	Dancie et al.
2021/0152979	A1	5/2021	Berardino et al.
2021/0266704	A1	8/2021	Dancie et al.
2021/0377693	A1	12/2021	Bouba et al.
2021/0409904	A1	12/2021	Baylin et al.
2022/0174455	A1	6/2022	Guillaume
2022/0269345	A1	8/2022	Jaureguiberry et al.

FOREIGN PATENT DOCUMENTS

CN	110168478	A	8/2019
EP	2051480	A1	4/2009
EP	2151797	A1	2/2010
EP	2184092	A2	5/2010
GB	2399928	A	9/2004
JP	2001230801	A	8/2001
JP	5497931	B2	3/2014
KR	19990073076	A	10/1999
KR	20010078417	A	8/2001
KR	101445263	B1	9/2014
WO	WO-1996024213	A1	8/1996
WO	WO-1999063453	A1	12/1999
WO	WO-2000058882	A1	10/2000
WO	WO-2001029642	A1	4/2001
WO	WO-2001050703	A3	7/2001
WO	WO-2003094072	A1	11/2003
WO	WO-2004095308	A1	11/2004
WO	WO-2006107182	A1	10/2006
WO	WO-2006118755	A2	11/2006
WO	WO-2007092668	A2	8/2007
WO	WO-2007134402	A1	11/2007
WO	WO-2009043020	A2	4/2009
WO	WO-2011040821	A1	4/2011
WO	WO-2011119407	A1	9/2011
WO	WO-2012139276	A1	10/2012
WO	WO-2013008238	A1	1/2013
WO	WO-2013027893	A1	2/2013
WO	WO-2013045753	A1	4/2013
WO	WO-2013152454	A1	10/2013
WO	WO-2013166588	A1	11/2013
WO	WO-2014006129	A1	1/2014
WO	WO-2014031899	A1	2/2014
WO	WO-2014068573	A1	5/2014
WO	WO-2014115136	A1	7/2014
WO	WO-2014194262	A2	12/2014
WO	WO-2014194439	A1	12/2014
WO	WO-2015192026	A1	12/2015
WO	WO-2016044424	A1	3/2016
WO	WO-2016054562	A1	4/2016
WO	WO-2016065131	A1	4/2016
WO	WO-2016090605	A1	6/2016
WO	WO-2016100318	A2	6/2016
WO	WO-2016100318	A3	6/2016
WO	WO-2016100342	A1	6/2016
WO	WO-2016149594	A1	9/2016
WO	WO-2016179166	A1	11/2016
WO	WO-2018081013	A1	5/2018
WO	WO-2018102562	A1	6/2018
WO	WO-2018129531	A1	7/2018
WO	WO-2019089613	A1	5/2019

OTHER PUBLICATIONS

Zheng, Yu. "Location-based social networks: Users." Computing with spatial trajectories. New York, NY: Springer New York, 2011. 243-276. (Year: 2011).*

Pham, Manh Cuong, et al. "Enhancing academic event participation with context-aware and social recommendations." 2012 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining. IEEE, 2012. (Year: 2012).*

Ackerman, Eduardo Jacobo Miranda. "Dynamic Group Generation based on Interests."; Oct. 12, 2009 (Year: 2009).*

"A Whole New Story", Snap, Inc., [Online] Retrieved from the Internet: <URL: <https://www.snap.com/en-US/news/>>, (2017), 13 pgs.

"Adding photos to your listing", eBay, [Online] Retrieved from the Internet: <URL: <http://pages.ebay.com/help/sell/pictures.html>>, (accessed May 24, 2017), 4 pgs.

"U.S. Appl. No. 16/353,604, Examiner Interview Summary mailed Mar. 28, 2023", 2 pgs.

"U.S. Appl. No. 16/353,604, Final Office Action mailed Feb. 8, 2022", 19 pgs.

"U.S. Appl. No. 16/353,604, Final Office Action mailed Dec. 27, 2022", 21 pgs.

"U.S. Appl. No. 16/353,604, Non Final Office Action mailed May 27, 2022", 21 pgs.

"U.S. Appl. No. 16/353,604, Non Final Office Action mailed Jul. 28, 2021", 19 pgs.

"U.S. Appl. No. 16/353,604, Notice of Allowance mailed Apr. 17, 2023", 8 pgs.

"U.S. Appl. No. 16/353,604, Response filed Mar. 27, 2023 to Final Office Action mailed Dec. 27, 2022", 12 pgs.

"U.S. Appl. No. 16/353,604, Response filed May 9, 2022 to Final Office Action mailed Feb. 8, 2022", 11 pgs.

"U.S. Appl. No. 16/353,604, Response filed Sep. 27, 2022 to Non Final Office Action mailed May 27, 2022", 10 pgs.

"BlogStomp", StompSoftware, [Online] Retrieved from the Internet: <URL: <http://stompsoftware.com/blogstomp>>, (accessed May 24, 2017), 12 pgs.

"Cup Magic Starbucks Holiday Red Cups come to life with AR app", Blast Radius, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20160711202454/http://www.blastradius.com/work/cup-magic>>, (2016), 7 pgs.

"Daily App: InstaPlace (iOS/Android): Give Pictures a Sense of Place", TechPP, [Online] Retrieved from the Internet: <URL: <http://techpp.com/2013/02/15/instaplace-app-review>>, (2013), 13 pgs.

"InstaPlace Photo App Tell the Whole Story", [Online] Retrieved from the Internet: <URL: youtu.be/uF_gFkg1hBM>, (Nov. 8, 2013), 113 pgs., 1:02 min.

"International Application Serial No. PCT/US2015/037251, International Search Report mailed Sep. 29, 2015", 2 pgs.

"Introducing Snapchat Stories", [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20131026084921/https://www.youtube.com/watch?v=88Cu3yN-LIM>>, (Oct. 3, 2013), 92 pgs.; 00:47 min.

"Macy's Believe-o-Magic", [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190422101854/https://www.youtube.com/watch?v=xvzRXy3J0Z0&feature=youtu.be>>, (Nov. 7, 2011), 102 pgs.; 00:51 min.

"Macy's Introduces Augmented Reality Experience in Stores across Country as Part of Its 2011 Believe Campaign", Business Wire, [Online] Retrieved from the Internet: <URL: <https://www.businesswire.com/news/home/20111102006759/en/Macys-Introduces-Augmented-Reality-Experience-Stores-Country>>, (Nov. 2, 2011), 6 pgs.

"Starbucks Cup Magic", [Online] Retrieved from the Internet: <URL: <https://www.youtube.com/watch?v=RWwQXi9RG0w>>, (Nov. 8, 2011), 87 pgs.; 00:47 min.

"Starbucks Cup Magic for Valentine's Day", [Online] Retrieved from the Internet: <URL: <https://www.youtube.com/watch?v=8nvqOzjq10w>>, (Feb. 6, 2012), 88 pgs.; 00:45 min.

"Starbucks Holiday Red Cups Come to Life, Signaling the Return of the Merriest Season", Business Wire, [Online] Retrieved from the Internet: <URL: <http://www.businesswire.com/news/home/>>

(56)

References Cited

OTHER PUBLICATIONS

20111115005744/en/2479513/Starbucks-Holiday-Red-Cups-Life-Signaling-Return>, (Nov. 15, 2011), 5 pgs.

Carthy, Roi, "Dear all Photo Apps: Mobli Just Won Filters", TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2011/09/08/mobli-filters>>, (Sep. 8, 2011), 10 pgs.

Chen, Mei-Hua, et al., "Augmentable Paraphrase Extraction Framework", Proceedings of the Sixth International Joint Conference on Natural Language Processing, (2013), 6 pgs.

Halstead, Susanne H, et al., "Finding top ui/ux design talent on adobe behance", Procedia Computer Science 51, (2015), 9 pgs.

Janthong, Isaranu, "Instaplace ready on Android Google Play store", Android App Review Thailand, [Online] Retrieved from the Internet: <URL: <http://www.android-free-app-review.com/2013/01/instaplace-android-google-play-store.html>>, (Jan. 23, 2013), 9 pgs.

Kostakos, Vassilis, et al., "Who's your best friend? Targeted privacy attacks in location-sharing social networks", Proceedings of the 13th international conference on Ubiquitous computing, (2011).

MacLeod, Duncan, "Macys Believe-o-Magic App", [Online] Retrieved from the Internet: <URL: <http://theinspirationroom.com/daily/2011/macys-believe-o-magic-app>>, (Nov. 14, 2011), 10 pgs.

MacLeod, Duncan, "Starbucks Cup Magic Lets Merry", [Online] Retrieved from the Internet: <URL: <http://theinspirationroom.com/daily/2011/starbucks-cup-magic>>, (Nov. 12, 2011), 8 pgs.

Notopoulos, Katie, "A Guide to the New Snapchat Filters and Big Fonts", [Online] Retrieved from the Internet: <URL: https://www.buzzfeed.com/katienotopoulos/a-guide-to-the-new-snapchat-filters-and-big-fonts?utm_term=.bkQ9qVZWe#.nv58YXpkV>, (Dec. 22, 2013), 13 pgs.

Panzarino, Matthew, "Snapchat Adds Filters, A Replay Function and for Whatever Reason, Time, Temperature and Speed Overlays", TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2013/12/20/snapchat-adds-filters-new-font-and-for-some-reason-time-temperature-and-speed-overlays/>>, (Dec. 20, 2013), 12 pgs.

Shang, Yanmin, et al., "A new interest-sensitive and network-sensitive method for user recommendation", IEEE Eighth International Conference on Networking, Architecture and Storage, (2013).

Tripathi, Rohit, "Watermark Images in PHP and Save File on Server", [Online] Retrieved from the Internet: <URL: <http://code.rohitink.com/2012/12/28/watermark-images-in-php-and-save-file-on-server>>, (Dec. 28, 2012), 4 pgs.

Xiang, Rongjing, et al., "Modeling relationship strength in online social networks", Proceedings of the 19th international conference on World wide web, (Apr. 26-30, 2010).

Xing, Wenpu, et al., "Weighted pagerank algorithm", Proceedings Second Annual Conference on Communication Networks and Services Research, IEEE, (2004).

Zheng, Yu, "Location-based social networks: Users", Computing with spatial trajectories. Springer, New York, NY, (2011), 243-276.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

1

GRAPH-BASED PREDICTION FOR CONTACT SUGGESTION IN A LOCATION SHARING SYSTEM

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. patent application Ser. No. 16/353,604, filed Mar. 14, 2019, which is incorporated by reference herein in its entirety.

BACKGROUND

The popularity of electronic messaging, particularly instant messaging, continues to grow. Users increasingly share media content items such as electronic images and videos with each other, reflecting a global demand to communicate more visually. Similarly, users increasingly seek to customize the media content items they share with others, providing challenges to social networking systems seeking to generate custom media content for their members. Embodiments of the present disclosure address these and other issues.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.

FIG. 1 is a diagrammatic representation of a networked environment in which the present disclosure may be deployed, in accordance with some example embodiments.

FIG. 2 is a diagrammatic representation of a data structure as maintained in a database, in accordance with some example embodiments.

FIG. 3 is a diagrammatic representation of a processing environment, in accordance with some example embodiments.

FIG. 4 is block diagram showing a software architecture within which the present disclosure may be implemented, in accordance with some example embodiments.

FIG. 5 is a diagrammatic representation of a machine, in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed, in accordance with some example embodiments.

FIG. 6 illustrates a method in accordance with one embodiment.

FIG. 7 illustrates a method in accordance with one embodiment.

FIG. 8 illustrates a method in accordance with one embodiment.

FIG. 9 illustrates a method in accordance with one embodiment.

FIG. 10 illustrates a model in accordance with one embodiment.

FIG. 11 illustrates a user interface in accordance with one embodiment.

DETAILED DESCRIPTION

Various embodiments of the present disclosure provide systems, methods, techniques, instruction sequences, and computing machine program products for generating contact suggestions for a user of a social network.

2

Conventional methods for generating contact suggestions for a user of a social network are limited in their ability to generate relevant contact suggestions. Motivated by these challenges, some embodiments of the present disclosure provide improvements over conventional methods for generating contact suggestions by building a user graph and generating contact suggestions based on the user graph. In some embodiments, the contact suggestions are then ranked using a machine learning model trained to predict a probability of a user sending a connection request to another user based on being presented with the other user as a contact suggestion.

For example, in some embodiments, user data of a plurality of users are accessed. A user graph of the plurality of users is generated. In the user graph, two users that have a relationship (e.g., “friends” in the social network graph) are connected via a weighted edge. The weight of the weighted edge between the two users is based, at least partially, on an amount of time the two users that have a relationship (e.g., “friends” in the social network graph) have spent together. A first score is computed for each one of the plurality of users, the first score being computed using an edge-weighted, edge-based ranking algorithm based on the user graph. A second score is computed, using a machine learning model, for each user of the plurality of users, the second score of each user being, at least partially, based on the first score of said user, the second score of each user being representative of a probability of a first user sending a connection request to said user. A ranked contact suggestion list of one or more users of the plurality of users is generated, with the one or more users being ranked based on their respective second score. The ranked list is displayed on a client device of a first user.

The present disclosure provides various improvements over conventional user interfaces. In particular, in some embodiments, the amount of time users spend with the users they are connected to (e.g., “friends” in a social network graph) is tracked, and the contact suggestion list displayed on the graphical user interface (GUI) is updated based on the amount of time the users have been spending together, automatically moving the contact suggestions with which the first user is most likely to interact to a higher position on the GUI based on the determined amount of time the users have been spending together.

The description that follows includes systems, methods, techniques, instruction sequences, and computing machine program products that embody illustrative embodiments of the disclosure. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide an understanding of various embodiments of the inventive subject matter. It will be evident, however, to those skilled in the art, that embodiments of the inventive subject matter may be practiced without these specific details. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

FIG. 1 is a block diagram showing an example location sharing system 100 for exchanging location data over a network. The location sharing system 100 includes multiple instances of a client device 102, each of which hosts a number of applications including a location sharing client application 104. Each location sharing client application 104 is communicatively coupled to other instances of the location sharing client application 104 and a location sharing server system 108 via a network 106 (e.g., the Internet).

A location sharing client application 104 is able to communicate and exchange data with another location sharing

client application **104** and with the location sharing server system **108** via the network **106**. The data exchanged between location sharing client application **104**, and between a location sharing client application **104** and the location sharing server system **108**, includes functions (e.g., commands to invoke functions) and payload data (e.g., location data, text, audio, video or other multimedia data).

The location sharing server system **108** provides server-side functionality via the network **106** to a particular location sharing client application **104**. While certain functions of the location sharing system **100** are described herein as being performed by either a location sharing client application **104** or by the location sharing server system **108**, the location of certain functionality either within the location sharing client application **104** or the location sharing server system **108** is a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the location sharing server system **108** but to later migrate this technology and functionality to the location sharing client application **104** where a client device **102** has a sufficient processing capacity.

The location sharing server system **108** supports various services and operations that are provided to the location sharing client application **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the location sharing client application **104**. This data may include geolocation information, message content, client device information, media annotation and overlays, message content persistence conditions, social network information, and live event information, as examples. Data exchanges within the location sharing system **100** are invoked and controlled through functions available via user interfaces (UIs) of the location sharing client application **104**.

Turning now specifically to the location sharing server system **108**, an Application Program Interface (API) server **110** is coupled to, and provides a programmatic interface to, an application server **112**. The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the application server **112**.

The API server **110** receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application server **112**. Specifically, the API server **110** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the location sharing client application **104** in order to invoke functionality of the application server **112**. The API server **110** exposes various functions supported by the application server **112**, including account registration; login functionality; the sending of messages, via the application server **112**, from a particular location sharing client application **104** to another location sharing client application **104**; the sending of media files (e.g., images or video) from a location sharing client application **104** to the location sharing server application **114** and for possible access by another location sharing client application **104**; the setting of a collection of media data (e.g., story); the retrieval of a list of friends of a user of a client device **102**; the retrieval of such collections; the retrieval of messages and content; the addition and deletion of friends to a social graph; the location of friends within a social graph; and opening an application event (e.g., relating to the location sharing client application **104**).

The application server **112** hosts a number of applications and subsystems, including a location sharing server application **114**, a messaging server application **116**, and a social network system **122**.

Examples of functions and services supported by the location sharing server application **114** include generating a map GUI. In some embodiments, the map GUI may include representations of at least approximate respective positions of a user and a user's friends in a social network graph accessed by the social media application using avatars for each respective user.

The location sharing server application **114** may receive user authorization to use, or refrain from using, the user's location information. In some embodiments, the location sharing server application **114** may likewise opt to share or not share the user's location with others via the map GUI. In some cases, the user's avatar may be displayed to the user on the display screen of the user's computing device regardless of whether the user is sharing his or her location with other users.

In some embodiments, a user can select groups of other users (audiences) to which his/her location will be displayed and may specify different display attributes for the different respective groups or for different respective individuals. In one example, audience options include: "Best Friends," "Friends," and "Custom" (which is an individual-level whitelist of people). In this example, if "Friends" is selected, all new people added to the user's friends list will automatically be able to see their location. If they are already sharing with the user, their avatars will appear on the user's map.

In some embodiments, when viewing the map GUI, the user is able to see the location of all his/her friends that have shared their location with the user on the map, with each friend represented by their respective avatar. In some embodiments, if a friend does not have an avatar, the friend may be represented using a profile picture or a default icon displayed at the corresponding location for the friend.

In some embodiments, the user can select between friends on the map via a menu, such as a carousel. In some embodiments, selecting a particular friend automatically centers the map view on the avatar of that friend. Embodiments of the present disclosure may also allow the user to take a variety of actions with the user's friends from within the map GUI. For example, the system may allow the user to chat with the user's friends without leaving the map. In one particular example, the user may select a chat icon from a menu presented in conjunction with the map GUI to initiate a chat session.

The client device **102** host a messaging client application **124**. The messaging server application **116** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the location sharing client application **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available, by the location sharing server application **114**, to the location sharing client application **104**. Other processor and memory intensive processing of data may also be performed server-side by the location sharing server application **114**, in view of the hardware requirements for such processing.

5

The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data processed by the location sharing server application **114**.

The social network system **122** supports various social networking functions and services, and makes these functions and services available to the location sharing server application **114**. To this end, the social network system **122** maintains and accesses an entity graph **30a** user graph **204** (as shown in FIG. 2) within the database **120**. Examples of functions and services supported by the social network system **122** include the identification of other users of the location sharing system **100** with which a particular user has relationships or is “following” and also the identification of other entities and interests of a particular user.

FIG. 2 is a schematic diagram illustrating data structures **200** which may be stored in the database **120** of the location sharing server system **108**, according to certain example embodiments. While the content of the database **120** is shown to comprise a number of tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object-oriented database).

The database **120** includes message data stored within a message table **210**. A user table **202** stores user data, including a user graph **204**. The user graph **204** furthermore stores information regarding relationships and associations between users. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example. Such relationships may include that a user is sharing his/her location with another user via the location sharing system (e.g., location sharing system **100**). Such relationships may include an amount of time (e.g., tracked by the location sharing system **100**) a user has spent with another user. Such relationships may include that a user is a preferred contact (e.g., “friend” in the social network graph) of another user in a social network (e.g., social network system **122**). Such relationships may include that a user is in an address book of another user in a messaging application (e.g., messaging client application **124**). Such relationships may include that a user is in a contact book stored in a client device (e.g., client device **102**) of another user. The user table **202** may also store the amount of time a user has spent with each of the users with whom the given user has a relationship.

A location table **206** stores historical and current location data of users (e.g., geolocation information determined by a positioning system (e.g., GPS) unit of client devices (e.g., client device **102**)).

A training data table **208** stores training data comprising historical contact suggestions provided to users, and connection requests sent. In some embodiments, the training data further comprises resulting connections created based on users accepting a connection request. The connection request may be a request to connect via the location sharing system **100**, and/or the messaging application **446**, and/or the social network system **122**.

Turning now to FIG. 3, there is shown a diagrammatic representation of a processing environment **300**, which includes at least a processor **302** (e.g., a GPU, CPU or combination thereof).

The processor **302** is shown to be coupled to a power source **304**, and to include (either permanently configured or temporarily instantiated) modules, namely a location component **306**, a link analysis component **308**, a time component **310**, a graph component **318**, a machine learning component **314**, a training component **316**, and a UI component **312**. The location component **306** determines a

6

location of a user based on location data of the user collected by one or more client device (e.g., client device **102**) associated with the user. The time component **310** accesses location data from the location component **306**, and tracks, for a given user, the amount of time the given user has spent with the users with whom the given user has a relationship. In some embodiments, two users are considered to spend time together when their respective location is within a preset distance of each other. The graph component **318** accesses user data from the user table **202** and builds a user graph **204** based on the user data. The link analysis component **308** performs a link analysis algorithm on the graph to generate a ranked list of contact suggestions. The training component **316** accesses the training data and trains the machine learning component **314** on the task of predicting the probability of a user sending a connection request to another user. The machine learning component **314** accesses the ranked list of contact suggestions outputted by the link analysis component and outputs a reranked contact suggestion lists, ranked based on the probability of the user sending a connection request to each user of the reranked contact suggestion list. The UI component **312** operationally generates user interfaces comprising the reranked list of contact suggestion and causes the user interfaces to be displayed on client devices.

FIG. 4 is a block diagram **400** illustrating a software architecture **404**, which can be installed on any one or more of the devices described herein. The software architecture **404** is supported by hardware such as a machine **402** that includes processors **420**, memory **426**, and I/O components **438**. In this example, the software architecture **404** can be conceptualized as a stack of layers, where each layer provides a particular functionality. The software architecture **404** includes layers such as an operating system **412**, libraries **410**, frameworks **408**, and applications **406**. Operationally, the applications **406** invoke API calls **450** through the software stack and receive messages **452** in response to the API calls **450**.

The operating system **412** manages hardware resources and provides common services. The operating system **412** includes, for example, a kernel **414**, services **416**, and drivers **422**. The kernel **414** acts as an abstraction layer between the hardware and the other software layers. For example, the kernel **414** provides memory management, processor management (e.g., scheduling), component management, networking, and security settings, among other functionality. The services **416** can provide other common services for the other software layers. The drivers **422** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **422** can include display drivers, camera drivers, BLUETOOTH® or BLUETOOTH® Low Energy drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

The libraries **410** provide a low-level common infrastructure used by the applications **406**. The libraries **410** can include system libraries **418** (e.g., C standard library) that provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **410** can include API libraries **424** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint

Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic content on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries **410** can also include a wide variety of other libraries **428** to provide many other APIs to the applications **406**.

The frameworks **408** provide a high-level common infrastructure that is used by the applications **406**. For example, the frameworks **408** provide various graphical user interface (GUI) functions, high-level resource management, and high-level location services. The frameworks **408** can provide a broad spectrum of other APIs that can be used by the applications **406**, some of which may be specific to a particular operating system or platform.

In an example embodiment, the applications **406** may include a home application **436**, a contacts application **430**, a browser application **432**, a book reader application **434**, a location application **442**, a media application **444**, a messaging application **446**, a game application **448**, and a broad assortment of other applications such as third-party applications **440**. The applications **406** are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications **406**, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, the third-party applications **440** (e.g., applications developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the third-party applications **440** can invoke the API calls **450** provided by the operating system **412** to facilitate functionality described herein.

FIG. **5** is a diagrammatic representation of a machine **500** within which instructions **508** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **500** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **508** may cause the machine **500** to execute any one or more of the methods described herein. The instructions **508** transform the general, non-programmed machine **500** into a particular machine **500** programmed to carry out the described and illustrated functions in the manner described. The machine **500** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **500** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **500** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a PDA, an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **508**, sequentially or otherwise, that specify actions to be taken by the machine **500**. Further, while only a single machine **500** is illustrated, the term “machine” shall

also be taken to include a collection of machines that individually or jointly execute the instructions **508** to perform any one or more of the methodologies discussed herein.

The machine **500** may include processors **502**, memory **504**, and I/O components **542**, which may be configured to communicate with each other via a bus **544**. In an example embodiment, the processors **502** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an ASIC, a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **506** and a processor **510** that execute the instructions **508**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **5** shows multiple processors **502**, the machine **500** may include a single processor with a single core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

The memory **504** includes a main memory **512**, a static memory **514**, and a storage unit **516**, both accessible to the processors **502** via the bus **544**. The main memory **504**, the static memory **514**, and storage unit **516** store the instructions **508** embodying any one or more of the methodologies or functions described herein. The instructions **508** may also reside, completely or partially, within the main memory **512**, within the static memory **514**, within machine-readable medium **518** within the storage unit **516**, within at least one of the processors **502** (e.g., within the processor’s cache memory), or any suitable combination thereof, during execution thereof by the machine **500**.

The I/O components **542** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **542** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones may include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **542** may include many other components that are not shown in FIG. **5**. In various example embodiments, the I/O components **542** may include output components **528** and input components **530**. The output components **528** may include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **530** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or another pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

In further example embodiments, the I/O components **542** may include biometric components **532**, motion components **534**, environmental components **536**, or position components **538**, among a wide array of other components. For example, the biometric components **532** include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like. The motion components **534** include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environmental components **536** include, for example, illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **538** include location sensor components (e.g., a GPS receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

Communication may be implemented using a wide variety of technologies. The I/O components **542** further include communication components **540** operable to couple the machine **500** to a network **520** or devices **522** via a coupling **524** and a coupling **526**, respectively. For example, the communication components **540** may include a network interface component or another suitable device to interface with the network **520**. In further examples, the communication components **540** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), WiFi® components, and other communication components to provide communication via other modalities. The devices **522** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

Moreover, the communication components **540** may detect identifiers or include components operable to detect identifiers. For example, the communication components **540** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **540**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

The various memories (e.g., memory **504**, main memory **512**, static memory **514**, and/or memory of the processors **502**) and/or storage unit **516** may store one or more sets of instructions and data structures (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. These instructions (e.g., the instructions **508**), when executed by processors **502**, cause various operations to implement the disclosed embodiments.

The instructions **508** may be transmitted or received over the network **520**, using a transmission medium, via a network interface device (e.g., a network interface component included in the communication components **540**) and using any one of a number of well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **508** may be transmitted or received using a transmission medium via the coupling **526** (e.g., a peer-to-peer coupling) to the devices **522**.

FIG. **6** is a flowchart illustrating a method **600** for generating a contact suggestion list for a first user and displaying the contact suggestion list to the first user. The method **600** may be embodied in computer-readable instructions for execution by one or more processors (e.g., processor **302**) such that the steps of the method **600** may be performed in part or in whole by functional components (e.g., location component **308**, link analysis component **308**, a time component **312**, a graph component **320**, a machine learning component **316**, training component **318**, and UI component **314**) of a processing environment **300** of a system (e.g., application server **112**); accordingly, the method **600** is described below by way of example with reference thereto. However, it shall be appreciated that the method **600** may be deployed on various other hardware configurations and is not intended to be limited to the functional components of the processing environment **300**.

In block **602**, method **600** accesses, from a database (e.g., database **120**) coupled to a server computer (e.g., application server **112**), user data of a plurality of users.

The system may need to receive authorization from the user to utilize user data prior to performing the remaining steps of method **600**. Such authorization may be obtained via acceptance of a terms of service for utilizing an online social network or other service provided by the system, by acceptance on a case-by-case basis by the user (e.g., via popups displayed on the user's computing device), or using any other suitable method for obtaining authorization by the user(s).

The plurality of users is selected among all the users registered in a user table (e.g., user table **202**) based on their relationship with the first user. The plurality of users may be users of a location tracking system, a social media application, and/or a messaging system. In some embodiments, the plurality of users are the users having at least either a one-degree incoming relationship to the first user or a two-degree outgoing relationship from the first user.

A degree of a relationship between user *u* and user *v* is a number of links between user *u* and user *v*. If user *u* is in a direct relationship with user *v*, user *u* and user *v* are in a one-degree relationship. If user *u* is in a direct relationship with user *w*, and user *w* is in a direct relationship with user *v*, the user *u* and user *v* are in a two-degree relationship.

A user *u* has an incoming relationship from user *v* when there is a relationship from user *v* to user *u*, such as, for example, user *v* is sharing his/her location with user *u* via the location sharing system (e.g., location sharing system **100**), user *u* is a preferred contact (e.g., "friend" in the social network graph) of user *v* in a social network (e.g., social network system **122**), user *u* is in an address book of user *v*

11

in a messaging application (e.g., messaging application **446**), or user *u* is in an address book stored in a client device (e.g., client device **102**) of user *v*.

A user *u* has an outgoing relationship to user *v* when there is a relationship from user *u* to user *v*, such as, for example, user *u* is sharing his/her location with user *v* via the location sharing system (e.g., location sharing system **100**), user *u* is a preferred contact (e.g., “friend” in the social network graph) of user *v* in a social network (e.g., social network system **122**), user *u* is in an address book of user *v* in a messaging application (e.g., messaging application **446**), or user *v* is in an address book stored in a client device (e.g., client device **102**) of user *u*.

In block **604**, method **600** generates, using one or more processors of the server computer, a user graph (e.g., user graph **1002** of FIG. **10**) of the plurality of users. The graph component **318** accesses the user table **202** and builds the weighted graph based on the information retrieved from the user table **202**. The graph includes an edge between every pair of users for which a relationship is recorded in the user table **202**. The graph may be a directed graph.

The graph may be a weighted graph. The weight of the weighted edge between a user *u* and a user *v* may be based on one or more of the following criteria:

- for every pair of users (*u*, *v*), the weight of the weighted edge from user *u* to user *v* is incremented if user *v* is included in a group of users with which user *u* is sharing his/her position (e.g., via the location sharing system **100**);

- for every pair of users (*u*, *v*), the weight of the weighted edge from user *u* to user *v* is incremented if user *v* is included in a group of user *u*, such as “Best Friends,” “Friends,” and “Custom” (which is an individual-level whitelist of people) in a social network (e.g., in the social network system **122**);

- for every pair of users (*u*, *v*), the weight of the weighted edge from user *u* to user *v* is incremented if user *v* is a preferred contact (e.g., “friend” in the social network graph) of user *u* in a social network (e.g., social network system **122**);

- for every pair of users (*u*, *v*), the weight of the weighted edge from user *u* to user *v* is incremented if user *v* is in an address book of user *u* in a messaging application (e.g., messaging application **446**);

- for every pair of users (*u*, *v*), the weight of the weighted edge from user *u* to user *v* is incremented if user *v* is in an address book stored in a client device of user *u*;

- for every pair of users (*u*, *v*), the weight of the weighted edge from user *u* to user *v* is based on whether user *u* sent a connection request to user *v*. Such connection request may be an invitation to share his/her position via the location sharing system **100**;

- for every pair of users (*u*, *v*) that have a relationship (e.g., “friends” in the social network graph), a weight of a weighted edge between user *u* and user *v* is based, at least partially, on an amount of time user *u* and user *v* have spent together.

In block **606**, method **600** (e.g., the link analysis component **308**) computes, by the one or more processors, a first score for each one of the plurality of users, based on the graph. The first score is computed using a link-based ranking algorithm (e.g., edge-weighted PageRank) based on the user graph (e.g., user graph **1002** of FIG. **10**) of the plurality of users. In embodiments, if the graph is a weighted graph, the first score is computed using an edge-weighted edge-based ranking algorithm (e.g., edge-weighted PageRank) based on the weighted user graph.

12

The algorithm may be initialized to a same value for all users. At each iteration, a contribution to the value $PR(u)$ of a user *u* conferred by an edge from user *v* to user *u* is equal to the value $PR(v)$ of user *v* divided by the number of edges $L(v)$ from user *v* weighted by the weight of the edge $W(u, v)$ from user *v* to user *u*.

In embodiments, the value for any user can be expressed as:

$$PR(u) = \sum_{v \in B_u} W(u, v) \frac{PR(v)}{L(v)}$$

The value $PR(u)$ for a user *u* is dependent on the values $PR(v)$ for each user *v* contained in the set B_u (the set containing all users linked to user *u*), divided by the number $L(v)$ of links from the user *v*, and weighted by the weight $W(u, v)$ of the link from user *v* to user *u* in case of a directed graph.

In embodiments, the link analysis component **308** generates a ranked list of the users (e.g., ranked list **1004** of FIG. **10**), with the users being ranked based on their respective first score.

In block **608**, method **600** (e.g., the machine learning component **314**) computes a second score for each user of the plurality of users. The second score of a user may be computed as a probability of the first user sending a connection request to the user upon being presented with a suggestion to add the user as a contact. The second score of a user may also be computed as a probability of the user accepting a connection request sent by the first user. As explained in more details in relation to FIG. **7**, the second score of a user may be computed using a machine learning model (e.g., machine learning model **1006** of FIG. **10**).

The second score may depend on the age of the first user. For example, the score may be higher for a younger first user and lower for an older first user. Indeed, it has been observed that younger users are more likely to send a connection request to users with whom they have a weaker connection, while older users are more likely to only send a connection request to users with whom they have a stronger connection. The score may also depend on an age difference between the first user and the user. The score may also depend on a distance between the location of the first user and the location of the user at computation time. The score may also depend on the country of residency of the first user.

In block **610**, method **600** (e.g., the machine learning component **316**) generates a contact suggestion list (e.g., reranked list **1008** of FIG. **10**) of one or more of the plurality of users, the contact suggestion list being ranked based on the second score of the plurality of users. In embodiments, the users having a higher second score are ranked higher in the contact suggestion list.

In block **612**, method **600** (e.g., the UI component **314**) causes display, on a client device of the first user, of the contact suggestion list (e.g., user interface **1100** of FIG. **11**).

As shown in FIG. **7**, the method **600** may further comprise a block **702** and a block **704**, according to some embodiments. Consistent with some embodiments, block **702** may be performed before block **602**, and block **704** may be performed as part of (e.g., as sub-blocks or as a subroutine) of block **608**, where the system computes a second score for each of the users of the plurality of users.

In block **702**, the method **600** (e.g., the training component **318**) trains a machine learning model (e.g., machine learning model **1006**) on a training set comprising historical user data. The machine learning model may include an

artificial neural network or a random forest classifier. The machine learning model may include an artificial neural network, a random forest classifier, or gradient boosted trees. Gradient-boosted trees are based on an ensemble of tree-based classifiers that are iteratively optimized to minimize the prediction error.” In some embodiments, the historical user data comprises historical contact suggestions and resulting connection requests (e.g., contact suggestion presented to a user *u* to add a user *v* as a contact and a resulting connection request sent from user *u* to user *v*). The connection request may be a request to connect via the location sharing system **100**, and/or the messaging application **446**, and/or the social network system **122**. The machine learning model is trained on a learning task defined as predicting a probability of a user sending a connection request to another user.

In some embodiments, the historical data further comprises connections created as a result of contact suggestions presented to users (e.g., connection created from user *u* to user *v*, as a result of user *v* accepting the connection request sent by user *u*). The connection may be a connection via the location sharing system **100**, and/or the messaging application **446**, and/or the social network system **122**. The machine learning model is trained on a learning task defined as predicting a probability of a user accepting a connection request received from another user.

In block **704**, method **600** (e.g., the machine learning component **316**) computes the second score using the trained machine learning model (e.g., machine learning model **1006**). In some embodiments, the trained machine learning model computes the second score of each user as a probability of the first user sending a connection request to said user. In some embodiments, the trained machine learning model computes the second score of each user as a probability of said user accepting a connection request from the first user. In block **608**, method **600** (e.g., the machine learning component **314**) computes the second score of each user, based, at least partially, on the second score of said user.

As shown in FIG. **8**, the method **600** may further comprise a block **802**, according to some embodiments. Consistent with some embodiments, block **802** may be performed as part of (e.g., as sub-blocks or as a subroutine) of block **610**, where the system generates a contact suggestion list including one or more of the plurality of users.

In block **802**, the method **600** filters out the users having a second score below a threshold. The threshold is selected as a compromise between the number of contact suggestion and the relevance of the contact suggestions.

In block **610**, the contact suggestion list displayed on the display screen of the client device of the first user only includes users that have a second score that exceeds the threshold.

As shown in FIG. **9**, the method **600** may further comprise a block **902**, a block **904**, a block **906**, a block **908**, a block **910**, a block **912**, a block **914**, block **916** and a block **918** according to some embodiments. Consistent with some embodiments, block **902**, block **904**, block **906**, block **908**, block **910**, block **912**, block **914**, and block **916** may be performed as part of (e.g., as sub-blocks or as a subroutine) of block **612**, where the system causes display of the ranked contact suggestion list on the client device of the first user.

In block **902**, the method **600** receives new location data of one or more users of the plurality of users. In some embodiments, the location sharing server application **114** receives, from one or more client devices (e.g., client device **102**) associated with one or more of the plurality of users,

via a wireless communication, over a network (e.g., network **106**), an electronic communication containing current location data of the user. The current location data of the user may include location data gathered by one or more of the client devices of the user over a recent period of time. The system may receive location data on a periodic basis or on an irregular basis and may request data from the client device or receive such data from the client device without such a request. In some embodiments, the client device contains software that monitors the location from the client device and transmits updates to the system in response to detecting new location. For example, the client device may update the system with a new location only after the location changes by at least a predetermined distance to allow a user to move about a building or other location without triggering updates.

In block **904**, method **600** (e.g., the time component **312**) detects, based on the new location data, that at least two users connected via an edge of the user graph (e.g., users that are “friends” in the social network graph) have been spending time together. In embodiments, users are considered to spend time together when they are located within a maximum distance of each other for a minimum amount of time. For example, the time component **312** detects, based on location data received from user *u* and user *v*, that user *u* and user *v* have been spending time together since the last time the amount of time user *u* and user *v* had spent together was last computed.

In block **906**, method **600** (e.g., the time component **312**) computes, based on detecting that user *u* and user *v* have been spending time together since the last time the amount of time user *u* and user *v* have spent together was computed, an updated amount of time user *u* and user *v* have spent together and updates the user table **202** with the updated amount of time.

In block **908**, method **600** (e.g., the graph component **320**) computes, based on the updated amount of time user *u* and user *v* have spent together, an updated weight for the weighted edge between the user *u* and user *v*.

In block **910**, method **600** (e.g., the graph component **320**) generates, based on the updated weight, an updated user graph of the plurality of users.

In block **912**, method **600** (e.g., the link analysis component **308**) computes, based on the updated user graph, an updated first score for each one of the plurality of users.

In block **914**, method **600** (e.g., the machine learning component **316**) computes, based on the updated first score of each of the plurality of users, an updated second score for each user of the plurality of users.

In block **916**, method **600** (e.g., the contact suggestion component **316**) generates an updated ranked contact suggestion list based on the updated second score of each user of the plurality of users.

In block **918**, method **600** (e.g., the UI component **314**) automatically causes display, on the client device of the first user, of the updated ranked contact suggestion list. In embodiments, the UI component **314** reorders the icons displayed on the user interface based on the updated second score of each of the one or more users.

FIG. **10** illustrates a model **1000** implemented in some embodiments of method **600**. The model **1000** includes a user graph **1002** of the plurality of users (e.g., implemented by the graph component **320**) and a machine learning model **1006** (e.g., implemented by the machine learning component **316**). The user graph **1002** is built based on user data related to a first user (user *u-1*). A link analysis algorithm is performed on the user graph **1002** (e.g., by the link analysis

15

component 308) and outputs a ranked list 1004 of one or more users of the plurality of users. The ranked list 1004 is processed through the machine learning model 1006. The machine learning model 1006 outputs a reranked list 1008 comprising the one or more users of the ranked list 1004 ranked according to their second score, with the users having a higher second score being ranked higher in the reranked list 1008.

As shown in FIG. 11, user interface 1100 is an example of a user interface that may be displayed on a display screen of a client device of a first user. The user interface 1100 comprises a ranked contact suggestion list comprising a plurality of contact suggestions 1102, with each contact suggestion 1102 being associated with a user included in the ranked contact suggestion list. Each contact suggestion 1102 is displayed alongside an interactive user interface element 1104, with the interactive user interface element 1104 triggering the emission of a connection request from the first user to the user associated with the contact suggestion 1102.

Upon detecting a user interaction with one of the interactive user interface elements 1104, a connection request is sent to the user associated with the contact suggestion 1102. If the user associated with the contact suggestion 1102 accepts the connection request, a relationship between the first user and the user is created. The relationship is registered in the user table 202. In embodiments, the user graph 204 is updated based on the updated user table 202, and the ranked contact suggestion list displayed on the user interface 1100 is updated based on the updated user graph 204, automatically moving the contact suggestions with whom the first user is most likely to interact with to a higher position on the user interface 1100 based on the newly created relationship.

In embodiments, the amount of time users that have a relationship (e.g., “friends” in the social network graph) spend together is tracked, and the ranked contact suggestion list displayed on the graphical user interface 1100 is updated based on the amount of time the users that have a relationship (e.g., are friends in the social network) have been spending together, automatically moving the contact suggestions with whom the first user is most likely to interact with to a higher position on the user interface 1100 based on the determined amount of time the users have been spending together.

Throughout this specification, plural instances may implement components, operations, or structures described as a single instance. Although individual operations of one or more methods are illustrated and described as separate operations, one or more of the individual operations may be performed concurrently, and nothing requires that the operations be performed in the order illustrated. Structures and functionality presented as separate components in example configurations may be implemented as a combined structure or component. Similarly, structures and functionality presented as a single component may be implemented as separate components. These and other variations, modifications, additions, and improvements fall within the scope of the subject matter herein.

Although an overview of the inventive subject matter has been described with reference to specific example embodiments, various modifications and changes may be made to these embodiments without departing from the broader scope of embodiments of the present disclosure.

The embodiments illustrated herein are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed. Other embodiments may be used and derived therefrom, such that structural and logical substitu-

16

tions and changes may be made without departing from the scope of this disclosure. The Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

As used herein, the term “or” may be construed in either an inclusive or exclusive sense. Moreover, plural instances may be provided for resources, operations, or structures described herein as a single instance. Additionally, boundaries between various resources, operations, modules, engines, and data stores are somewhat arbitrary, and particular operations are illustrated in a context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within a scope of various embodiments of the present disclosure. In general, structures and functionality presented as separate resources in the example configurations may be implemented as a combined structure or resource. Similarly, structures and functionality presented as a single resource may be implemented as separate resources. These and other variations, modifications, additions, and improvements fall within a scope of embodiments of the present disclosure as represented by the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

“Signal Medium” refers to any intangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine and includes digital or analog communications signals or other intangible media to facilitate communication of software or data. The term “signal medium” shall be taken to include any form of a modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. The terms “transmission medium” and “signal medium” mean the same thing and may be used interchangeably in this disclosure.

“Communication Network” refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other types of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long-range protocols, or other data transfer technology.

“Processor” refers to any circuit or virtual circuit (a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., “commands”, “op codes”, “machine code”, etc.) and which produces corresponding output signals that are applied to operate a machine. A processor may, for example, be a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC) or any combination thereof. A processor may further be a multi-core processor having two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously.

“Machine-Storage Medium” refers to a single or multiple storage devices and/or media (e.g., a centralized or distributed database, and/or associated caches and servers) that store executable instructions, routines and/or data. The term shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media and/or device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms “machine-storage medium,” “device-storage medium,” “computer-storage medium” mean the same thing and may be used interchangeably in this disclosure. The terms “machine-storage media,” “computer-storage media,” and “device-storage media” specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium.”

“Component” refers to a device, physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an

application specific integrated circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software), may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a

method may be performed by one or more processors 1004 or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

“Carrier Signal” refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such instructions. Instructions may be transmitted or received over a network using a transmission medium via a network interface device.

“Computer-Readable Medium” refers to both machine-storage media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals. The terms “machine-readable medium,” “computer-readable medium” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure.

“Client Device” refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smartphones, tablets, ultrabooks, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

“Ephemeral Message” refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

What is claimed is:

1. A system comprising:

one or more processors; and

a memory storing instructions that, when executed by the one or more processors, configure the system to perform operations comprising:

accessing, from a database coupled to a server computer, user data of a plurality of users;

generating, using one or more processors of the server computer, a directed graph of the plurality of users, wherein a weight of a weighted edge between two users of the plurality of users is based, at least partially, on an amount of time the two users have spent together;

computing, by the one or more processors, a first score for each user of the plurality of users, the first score of each user being computed using an edge-weighted edge-based ranking algorithm based on the directed graph,

wherein for each user u of the plurality of users, the first score is dependent on edge-weighted values for each user v included in a set containing all users linked to the user u , divided by a number of links from the second user v ;

computing, by the one or more processors, using a machine learning model, a second score for each user of the plurality of users, the second score of each user being, at least partially, based on the first score of the user, the second score for each user being computed based on a first probability of a first user of the plurality of users sending a connection request to the user, and on a second probability of the user accepting the connection request received from the first user;

generating, by the one or more processors, a ranked contact suggestion list of one or more users of the plurality of users, the one or more users being ranked based on their respective second score, and the one or more users for presenting as contact suggestions to the first user; and

causing display, on a client device of the first user, of the ranked contact suggestion list.

2. The system of claim 1, the operations further comprising:

training the machine learning model on a training set comprising a plurality of training examples, the training examples comprising historical contact suggestions and whether the historical contact suggestions resulted in connection requests, and on a learning task defined as predicting a probability of an exemplary user sending a connection request to another exemplary user, wherein computing the second score for each user of the plurality of users comprises computing, using the trained machine learning model, the first probability of the first user sending the connection request to the user.

3. The system of claim 2, wherein the training examples further comprise whether the historical contact suggestions resulted in connections,

wherein the learning task is further defined as predicting a probability the exemplary user accepting an invitation request received from the other exemplary user, and wherein computing the second score for each user of the plurality of users further comprises computing, using the trained machine learning model, the second probability of the user accepting the connection request received from the first user.

4. The system of claim 1, wherein the one or more users of the plurality of users are the users having a second score that exceeds a threshold.

5. The system of claim 1, wherein causing display of the ranked contact suggestion list comprises causing display of a user interface comprising a plurality of icons, each icon being associated with one user of the one or more users of the ranked contact suggestion list, a location of each icon on the user interface being based on the second score of the user associated with the icon.

6. The system of claim 5, the operations further comprising:

generating, in response to detecting a user interaction with one icon of the plurality of icons, a connection request from the first user to the user associated with the one icon.

7. The system of claim 1, the operations further comprising:

accessing an address book stored in a client device of each user of the plurality of users,

21

wherein the weight of the weighted edge from the first user to a second user of the plurality of users is based on whether the second user is included in the address book of the first user.

8. The system of claim 1,

wherein the weight of the weighted edge from the first user to a second user of the plurality of users is based on whether the first user sent a connection request to the second user.

9. The system of claim 1, the operations further comprising:

tracking a location of at least one user of the plurality of users; and

dynamically updating the ranked contact suggestion list as new location data of the at least one user is received.

10. The system of claim 9, wherein dynamically updating the ranked contact suggestion list comprises:

detecting that the first user and a second user of the plurality of users have been spending more time together since the amount of time the first and second users have spent together was computed;

computing an updated amount of time the first and second users have spent together;

computing, based on the updated amount of time the first and second users have spent together, an updated weight for the weighted edge between the first and second users;

generating, based on the updated weight, an updated directed graph of the plurality of users; and

computing, based on the updated directed graph, an updated first score for at least one user of the plurality of users;

computing, based on the updated first score of the at least one user, a second score for the at least one user; and

generating, based on the updated second score of the at least one user, an updated ranked list.

11. A method comprising:

accessing, from a database coupled to a server computer, user data of a plurality of users;

generating, using one or more processors of the server computer, a directed graph of the plurality of users,

wherein a weight of a weighted edge between two users of the plurality of users is based, at least partially, on an amount of time the two users have spent together;

computing, by the one or more processors, a first score for each user of the plurality of users, the first score of each user being computed using an edge-weighted edge-based ranking algorithm based on the directed graph,

wherein for each user u of the plurality of users, the first score is dependent on edge-weighted values for each user v included in a set containing all users linked to the user u , divided by a number of links from the second user v ;

computing, by the one or more processors, using a machine learning model, a second score for each user of the plurality of users, the second score of each user being, at least partially, based on the first score of the user, the second score for each user being computed based on a first probability of a first user of the plurality of users sending a connection request to the user, and on a second probability of the user accepting the connection request received from the first user;

generating, by the one or more processors, a ranked contact suggestion list of one or more users of the plurality of users, the one or more users being ranked

22

based on their respective second score, and the one or more users for presenting as contact suggestions to the first user; and

causing display, on a client device of the first user, of the ranked contact suggestion list.

12. The method of claim 11, further comprising:

training the machine learning model on a training set comprising a plurality of training examples, the training examples comprising historical contact suggestions and whether the historical contact suggestions resulted in connection requests, and on a learning task defined as predicting a probability of an exemplary user sending a connection request to another exemplary user,

wherein computing the second score for each user of the plurality of users comprises computing, using the trained machine learning model, the first probability of the first user sending the connection request to the user.

13. The method of claim 12, wherein the training examples further comprise whether the historical contact suggestions resulted in connections,

wherein the learning task is further defined as predicting a probability the exemplary user accepting an invitation request received from the other exemplary user, and

wherein computing the second score for each user of the plurality of users further comprises computing, using the trained machine learning model, the second probability of the user accepting the connection request received from the first user.

14. The method of claim 11, wherein the one or more users of the plurality of users are the users having a second score that exceeds a threshold.

15. The method of claim 11, wherein causing display of the ranked contact suggestion list comprises causing display of a user interface comprising a plurality of icons, each icon being associated with one user of the one or more users of the ranked contact suggestion list, a location of each icon on the user interface being based on the second score of the user associated with the icon.

16. The method of claim 15, further comprising:

generating, in response to detecting a user interaction with one icon of the plurality of icons, a connection request from the first user to the user associated with the one icon.

17. The method of claim 11, further comprising:

accessing an address book stored in a client device of each user of the plurality of users,

wherein the weight of the weighted edge from the first user to a second user of the plurality of users is based on whether the second user is included in the address book of the first user.

18. The method of claim 11,

wherein the weight of the weighted edge from the first user to a second user of the plurality of users is based on whether the first user sent a connection request to the second user.

19. The method of claim 11, further comprising:

tracking a location of at least one user of the plurality of users; and

dynamically updating the ranked contact suggestion list as new location data of the at least one user is received.

20. A non-transitory computer-readable storage medium, the computer-readable storage medium including instructions that when executed by a computer, cause the computer to perform operations comprising:

accessing, from a database coupled to a server computer, user data of a plurality of users;

generating, using one or more processors of the server
 computer, a directed graph of the plurality of users,
 wherein a weight of a weighted edge between two users
 of the plurality of users is based, at least partially, on an
 amount of time the two users have spent together; 5
 computing, by the one or more processors, a first score for
 each user of the plurality of users, the first score of each
 user being computed using an edge-weighted edge-
 based ranking algorithm based on the directed graph,
 wherein for each user u of the plurality of users, the first 10
 score is dependent on edge-weighted values for each
 user v included in a set containing all users linked to the
 user u , divided by a number of links from the second
 user v ;
 computing, by the one or more processors, using a 15
 machine learning model, a second score for each user
 of the plurality of users, the second score of each user
 being, at least partially, based on the first score of the
 user, the second score for each user being computed
 based on a first probability of a first user of the plurality 20
 of users sending a connection request to the user, and
 on a second probability of the user accepting the
 connection request received from the first user;
 generating, by the one or more processors, a ranked
 contact suggestion list of one or more users of the 25
 plurality of users, the one or more users being ranked
 based on their respective second score, and the one
 more users for presenting as contact suggestions to the
 first user; and
 causing display, on a client device of the first user, of the 30
 ranked contact suggestion list.

* * * * *