



US012149303B2

(12) **United States Patent**
Chritz

(10) **Patent No.:** **US 12,149,303 B2**
(45) **Date of Patent:** **Nov. 19, 2024**

(54) **SYSTEM FOR OPTIMIZING ROUTING OF COMMUNICATION BETWEEN DEVICES AND RESOURCE REALLOCATION IN A NETWORK**

(71) Applicant: **MICRON TECHNOLOGY, INC.**,
Boise, ID (US)

(72) Inventor: **Jeremy Chritz**, Seattle, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 129 days.

(21) Appl. No.: **17/687,915**

(22) Filed: **Mar. 7, 2022**

(65) **Prior Publication Data**
US 2022/0190881 A1 Jun. 16, 2022

Related U.S. Application Data

(60) Division of application No. 16/671,111, filed on Oct. 31, 2019, now Pat. No. 11,316,561, which is a
(Continued)

(51) **Int. Cl.**
H04B 7/04 (2017.01)
H04B 7/0413 (2017.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04B 7/04** (2013.01); **H04B 7/0413** (2013.01); **H04W 28/0231** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC ... H04B 7/04; H04B 7/0413; H04W 28/0231;
H04W 28/18; H04W 72/04; H04W 16/28;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,905,873 A 5/1999 Hartmann et al.
6,047,002 A 4/2000 Hartmann et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1487700 A 4/2004
CN 101253735 A 8/2008
(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 16/709,033 titled "System for Optimizing Routing of Communication Between Devices and Resource Reallocation in a Network", filed Dec. 10, 2019.

(Continued)


Primary Examiner — Peter P Chau

(74) *Attorney, Agent, or Firm* — Dorsey & Whitney LLP

(57) **ABSTRACT**

Methods, systems, and devices for signal processing and wireless communication are described. For example, a device may include a plurality of antennas operable to transmit and receive communication packets via a plurality of communication protocols and an integrated circuit chip coupled to the plurality of antennas. The integrated circuit chip may comprise a first and a second plurality of processing elements. The first plurality of processing elements may be operable to receive communication packets via a first one of a plurality of communication protocols and process an optimal route. The second plurality of processing elements may be communicatively coupled to the first plurality of processing elements and operable to determine the optimal route to transmit the communication packets from a source device to a destination device based, at least in part, on transmission characteristics associated with at least one of the source or destination devices.

18 Claims, 10 Drawing Sheets



Related U.S. Application Data

division of application No. 15/726,281, filed on Oct. 5, 2017, now Pat. No. 10,511,353, which is a continuation-in-part of application No. 15/647,676, filed on Jul. 12, 2017, now Pat. No. 10,516,606.

(51) **Int. Cl.**

H04W 28/02 (2009.01)
H04W 28/18 (2009.01)
H04W 72/04 (2023.01)
H04L 47/24 (2022.01)
H04W 16/28 (2009.01)

(52) **U.S. Cl.**

CPC *H04W 28/18* (2013.01); *H04W 72/04* (2013.01); *H04L 47/24* (2013.01); *H04W 16/28* (2013.01)

(58) **Field of Classification Search**

CPC H04W 88/06; H04W 76/16; H04L 47/24; H04L 45/52; H04L 45/08; H04L 45/24
 See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,950,394	B1	9/2005	Chou et al.
7,328,270	B1	2/2008	Reents et al.
7,573,885	B1	8/2009	Dykeman et al.
8,472,372	B1	6/2013	Dulai et al.
8,811,422	B2	8/2014	Georgiou et al.
10,511,353	B2	12/2019	Chritz
10,516,606	B2	12/2019	Chritz et al.
11,165,468	B2	11/2021	Chritz
11,190,441	B2	11/2021	Chritz et al.
11,316,561	B2	4/2022	Chritz
11,784,923	B2	10/2023	Chritz et al.
2002/0035633	A1	3/2002	Bose et al.
2003/0067894	A1	4/2003	Schmidt
2004/0071164	A1	4/2004	Baum
2004/0218548	A1	11/2004	Kennedy et al.
2004/0252643	A1	12/2004	Joshi
2005/0088980	A1*	4/2005	Olkkonen H04W 48/16 370/255
2006/0098608	A1	5/2006	Joshi
2006/0277307	A1	12/2006	Bernardin et al.
2007/0195768	A1	8/2007	Kanazawa et al.
2009/0268668	A1	10/2009	Tinnakornsrisuphap et al.
2010/0027418	A1	2/2010	Rodrig
2010/0100934	A1	4/2010	Mejdrich et al.
2010/0150161	A1	6/2010	Saksena et al.
2011/0138259	A1	6/2011	Tan et al.
2012/0082171	A1	4/2012	Georgiou et al.
2012/0087377	A1	4/2012	Lai
2014/0122560	A1	5/2014	Ramey et al.
2014/0189152	A1	7/2014	Morris
2014/0213256	A1	7/2014	Meylan et al.
2014/0289303	A1	9/2014	Tarricone et al.

2016/0021627	A1	1/2016	Etkin et al.
2016/0066788	A1	3/2016	Tran et al.
2016/0119775	A1	4/2016	Karaoguz
2016/0150459	A1	5/2016	Patil et al.
2017/0116154	A1	4/2017	Palmer et al.
2017/0201927	A1	7/2017	Kobayashi
2018/0007042	A1	1/2018	Weizman
2019/0020382	A1	1/2019	Chritz
2019/0020383	A1	1/2019	Chritz
2019/0020581	A1	1/2019	Chritz et al.
2020/0067571	A1	2/2020	Chritz
2020/0112506	A1	4/2020	Chritz et al.
2022/0060410	A1	2/2022	Chritz et al.

FOREIGN PATENT DOCUMENTS

CN	101360124	A	2/2009
CN	102137466	A	7/2011
CN	102571591	A	7/2012
CN	103457849	A	12/2013
CN	104918305	A	9/2015
CN	106464593	A	2/2017
EP	3047609	A1	7/2016
WO	2016197004	A2	12/2016
WO	2019014383	A1	1/2019

OTHER PUBLICATIONS

PCT Application No. PCT/US2018/041695, titled "System for Optimizing Routing of Communication Between Devices and Resource Reallocation in a Network" filed on Jul. 11, 2018.

U.S. Appl. No. 16/107,796 titled "System for Optimizing Routing of Communication Between Devices and Resource Reallocation in a Network", filed Aug. 21, 2018.

U.S. Appl. No. 16/671,111 titled "System for Optimizing Routing of Communication Between Devices and Resource Reallocation in a Network" filed Oct. 31, 2019, pp. all.

U.S. Appl. No. 15/647,676, entitled "System for Optimizing Routing of Communication Between Devices and Resource Reallocation in a Network", filed Jul. 12, 2017, pp. all.

U.S. Appl. No. 15/726,281, entitled "System for Optimizing Routing of Communication Between Devices and Resource Reallocation in a Network", filed Oct. 5, 2017, pp. all.

Chakeres, Ian D. et al. "Transparent Influence of Path Selection in Heterogeneous Ad Hoc Networks", IEEE 15th International Symposium on Personal, Indoor and Mobile Radio Communications, Sep. 2004, 5 pages.

U.S. Appl. No. 17/517,544 titled "System for Optimizing Routing of Communication Between Devices and Resource Reallocation in a Network", filed Nov. 2, 2021.

Hu, Feifei et al. "TCP-BM: A TCP Protocol Improvement Strategy for Heterogeneous Networks", Electronic Technology Application: Communication and Network, vol. 36, Issue 4, Jun. 2020, 4 pgs [English translation of title and abstract only].

U.S. Appl. No. 18/460,392, titled "System for Optimizing Routing of Communication Between Devices and Resource Reallocation in a Network", filed Sep. 1, 2023, pp. all pages of application as filed.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

1

SYSTEM FOR OPTIMIZING ROUTING OF COMMUNICATION BETWEEN DEVICES AND RESOURCE REALLOCATION IN A NETWORK

CROSS REFERENCE TO RELATED APPLICATION(S)

This application is a divisional of U.S. patent application Ser. No. 16/671,111 filed Oct. 31, 2019 and issued as U.S. Pat. No. 11,316,561 on Apr. 26, 2022, which is a divisional of U.S. patent application Ser. No. 15/726,281 filed Oct. 5, 2017 and issued as U.S. Pat. No. 10,511,353 on Dec. 17, 2019, which application is a Continuation-in-Part of pending U.S. patent application Ser. No. 15/647,676 filed Jul. 12, 2017 and issued as U.S. Pat. No. 10,516,606 on Dec. 24, 2019. The aforementioned applications, and issued patents, are incorporated herein by reference, in their entirety, for any purpose.

TECHNICAL FIELD

Examples described herein generally relate to optimizing routing of communication between devices and reallocation of processing resources in a network based on resource availability, and in particular based on prediction of resource availability.

BACKGROUND OF THE DISCLOSURE

The use of mobile communication devices, such as mobile phones (e.g., smart phones), tablets, and laptops while on-the-go has become a ubiquitous routine in society. As the adaptation of on-the-go communication practice becomes more widespread, limitations on the communication systems are becoming apparent. For example, during peak communication hours where there is increased communication traffic, a cellular network might experience sluggishness due to an overly leveraged communication system or communication across a WiFi hotspot zone may experience significant delays.

As such, it is desirable to have a system and method that optimizes routing of communication packets or signals between mobile devices in a manner that avoids communication sluggishness across a network.

BRIEF DESCRIPTION OF THE DRAWINGS

Reference will now be made to the attached drawings, when read in combination with the following specification, wherein like reference numerals refer to like parts throughout the several views, and in which:

FIG. 1 is a block diagram of an integrated circuit chip, according to one illustrated example.

FIG. 2 is a flowchart illustrating a method for processing signals with a single integrated circuit chip, according to one illustrated example.

FIG. 3 is a flowchart illustrating a method for processing signals with a single integrated circuit chip, according to one illustrated example.

FIG. 4 is block diagram of plurality of processing elements and communication interfaces, according to one illustrated example.

FIG. 5 is a block diagram of a plurality of processing elements, according to one illustrated example.

FIG. 6 is a block diagram of a processing element, according to one illustrated example.

2

FIG. 7 is a block diagram of an integrated circuit chip configured to optimize routing of communication packets, according to one illustrated example.

FIG. 8 is a graphical representation of a communication system having a plurality of devices communicatively coupled via a network, according to one illustrated example.

FIG. 9 is a schematic illustration of a wireless communications system arranged in accordance with aspects of the present disclosure.

FIG. 10 is a schematic illustration of a wireless communications system arranged in accordance with aspects of the present disclosure.

DETAILED DESCRIPTION

Examples disclosed herein may recognize that a single chip solution for processing communications signals provides reduced power consumption and a smaller physical footprint, which may make a single chip solution preferable in mobile and/or wireless systems, such as smartphones. Moreover, such single chip solutions may provide increased versatility by allowing for the dynamic allocation of processing elements to process communications signals. Such single chip solutions may also integrate traditional wireless communications bands (e.g., industrial, scientific, and medical radio band) with sub 1-GHz bands that many emerging Internet of Things (IoT) systems may utilize. Stated differently, the single chip solutions described herein are not limited to certain frequency bands like traditional systems (e.g., a smartphone being limited to 4G long-term evolution (LTE), WiFi, and/or Bluetooth®). Instead, examples of single-chip solutions described herein may integrate those communication technologies with transceivers for IoT systems, such as Z-Wave operating at 900 MHz; radio frequency identification (RFID) systems operating at any of 13.56 MHz, 433 MHz, or 902-928 MHz ranges; and/or even microwave frequencies at 3.1-10 GHz.

In various examples, a processing element with a reconfigurable fabric can be used to process different protocols, according to the demand of a wireless system or an IoT system. For example, hardware and power complexity may be reduced when utilizing the reconfigurable fabric space for baseband and digital front and processing for any type of analog processing system (e.g., different antennas for corresponding frequency bands). In contrast to conventional wireless transceivers and IoT reader systems, the processing capability of each of those receiver systems may be integrated into the reconfigurable fabric space that can be dynamically shifted for processing of signals from any analog processing system. In this shared reconfigurable fabric space application, processing for each receiver system may be allocated to a respective cluster(s) of processing elements. In such an example, the aggregate processing results of each receiver system can be processed in the shared, coherent memory space, before deciding whether to transmit an aggregated processing result via a specific transmitter. For example, using a shared reconfigurable fabric, a processing result derived from measurements of an IoT system and information from an LTE system can be transmitted via an RFID system, in some examples, utilizing the same processing element.

FIG. 1 is a block diagram of an integrated circuit chip **102**, in accordance with an example of the present disclosure. The integrated circuit chip **102** is a single chip capable of processing communications signals. Examples of single chip systems include those where circuitry for performing the described tasks are fabricated on and/or into a common

substrate generally using semiconductor fabrication techniques. The integrated circuit chip **102** includes a plurality of processing elements **104**, a network on chip (NOC) **106**, a dispatch unit **108**, a radio interface **110**, and a cellular interface **112**. The integrated circuit chip **102** may be coupled to a plurality of antennas **114**. The plurality of antennas **114** may include a first set of antennas **116** and a second set of antennas **118**.

The processing elements **104** may be implemented using one or more processors, for example, having any number of cores. In some examples, the processing elements **104** may include circuitry, including custom circuitry, and/or firmware for performing functions described herein. For example, circuitry can include multiplication unit/accumulation units for performing the described functions, as described herein. Processing elements **104** can be any type including but not limited to a microprocessor or a digital signal processor (DSP), or any combination thereof. For example, processing elements **104** can include levels of caching, such as a level one cache and a level two cache, a core, and registers. An example processor core can include an arithmetic logic unit (ALU), a bit manipulation unit, a multiplication unit, an accumulation unit, an adder unit, a look-up table unit, a memory look-up unit, or any combination thereof.

The NOC **106** may be implemented as an on-chip communications sub-system configured to facilitate communication between the processing elements **104** and the dispatch unit **108**. The NOC **106** may include, for example, one or more links, such as copper wires, connecting the processing elements **104** and the dispatch unit **108** and configured to carry information from the processing elements **104** to the dispatch unit **108** and vice versa.

The dispatch unit **108** may include instructions sets (e.g., one or more program instructions or operations) to be performed by the processing elements **104**. The dispatch unit may include, for example, computer software, hardware, firmware, or a combination thereof configured to provide instruction sets from a storage device to the processing elements **104**. For example, the instruction sets may include instructions to perform certain logic or arithmetic operations on data, transmit data from one processing element **104** to another processing element **104**, or perform other operations. In some examples, a first processing element instruction set may be loaded onto a first processing element **104** and include instructions for a processing element to receive a signal of a first type (e.g., a signal associated with a received radio signal), to process the received signal of a first type to generate a set of data, and to transmit the set of data to a second processing element **104**. A second processing element instruction set may be loaded onto a second processing element **104** and be configured to receive the set of data, process the set of data to generate a second signal of a second type and to transmit the second signal with a plurality of antennas. The dispatch unit **108** may retrieve instructions for the processing elements **104** from one or more memories, such as a volatile (e.g., dynamic random access memory (DRAM)) or non-volatile memory (e.g., Flash memory). The processing element instruction sets may be stored in one or more data structures, such as a database.

The radio interface **110** may be coupled to the plurality of antennas **114** and to one or more of the processing elements **104**. The radio interface **110** may be configured to receive radio signals detected by the plurality of antennas **114** and convert the received signals into a signal that can be manipulated by the one or more processing elements **104** and route the resulting signal to the one or more processing elements.

In some examples, radio interface **110** may include an analog to digital converter. In other examples, the radio interface **110** may include additional or different components, circuits, etc. Although described as a “radio interface,” in some examples, the interface may generally be adapted to convert a received signal of any type to a signal that can be manipulated by the processing elements **104**. For example, the radio interface **110** may be configured to receive Wi-Fi signals, optical signals, auditory signals, or any other type of signals. In some examples, the radio interface **110** is configured to receive RFID signals detected by the plurality of antennas **114** and to provide the received signals to the one or more processing elements **104**.

The cellular interface **112** may be coupled to the plurality of antennas **114** and to one or more of the processing elements **104**. The cellular interface **112** may be configured to transmit/receive cellular signals with the plurality of antennas **114** and convert the signals between a signal that can be manipulated by the one or more processing elements **104** and a signal that can be transmitted using the plurality of antennas **114**. In some examples, cellular interface **112** may include a digital to analog converter. In other examples, the cellular interface **112** may include additional or different components, circuits, etc. Although described as a “cellular interface,” in some examples, the interface may generally be adapted to any type of signal. A cellular signal may generally refer to any protocol of cellular signal, such as 3G, 4G, 4G LTE, 5G, etc. The cellular interface **112** may be configured to transmit Wi-Fi signals, optical signals, auditory signals, or any other type of signals. In some examples, the cellular interface **112** is configured to transmit a different type of signal than the radio interface **110**.

The plurality of antennas **114** is configured to receive and transmit wireless signals. The plurality of antennas **114** may generally be any type of antennas, such as a wire antenna (e.g., a dipole antenna, a loop antenna, a monopole antenna, a helix antenna, etc.), an aperture antenna (e.g., a waveguide, a horn antenna, etc.), a reflector antenna e.g., a parabolic reflector, a corner reflector, etc.), a lens antenna (e.g., a convex-plane, a concave-plane, a convex-convex, or a concave-concave), a microstrip antenna (e.g., a circular shaped, rectangular shaped, metallic patch, etc.), an array antenna (e.g., a Yagi-Uda antenna, a micro strip patch array, an aperture array, a slotted wave guide array, etc.), or combinations thereof.

In the example of FIG. 1, the plurality of antennas **114** includes a first subset of antennas **116** configured to receive radio signals and to communicate the received signals to the radio interface **110**. The plurality of antennas **114** further includes a second subset of antennas **118** configured to communicate over a cellular network. The second subset of antennas **118** may receive signals from the cellular interface **112** and transmit the received signals to one or more cellular nodes (not shown), such as a cellular tower. In various examples, the plurality of antennas **114** may be configurable. For example, antennas in the plurality of antennas **114** may be adjustable to receive and/or transmit signals of different types. In such examples, the first subset of antennas **116** and the second subset of antennas **118** may be the same antennas. For example, the first subset of antennas **116** may be configured to receive radio signals, such as an RFID signal and to communicate the received radio signal to the processing elements **104** via the radio interface **110**. The first subset of antennas **116** may be reconfigured to communicate using a cellular network as the second subset of antennas **118**. For example, the plurality of antennas **118** may include or be coupled to an integrated inner mechanism, such as RF

5

switches, varactors, mechanical actuators, or tunable materials, that enable the intentional redistribution of currents over the surface of the antenna to produce modifications of its properties. The processing elements **104** may process the received radio signals according to the instruction sets fetched by the dispatch unit **108** and communicate a resulting cellular signal to the second subset of antennas **118** via the cellular interface **112**. The second subset of antennas **118** may then communicate the received signals via a cellular network.

FIG. 2 is a flowchart illustrating a method of processing signals with a single integrated circuit chip, in accordance with an example of the present disclosure.

In operation **202**, a first signal of a first type is received with a plurality of antennas. The signal may be received, for example, with the plurality of antennas **114**, and specifically with the first subset of antennas **116**. In various examples, the first signal of the first type may be a radio signal associated with an RFID device. The first subset of antennas **114** may employ beam forming to detect one or more first signals of the first type. Beamforming is a signal processing technique that enables directional signal transmission or reception. Beamforming typically uses a phased antenna array in such a way that signals at particular angles experience constructive interference while signals at other angles experience destructive interference.

In operation **204**, the first signal of the first type is provided to a first set of processing elements. For example, the first subset of antennas **116** may provide the received first signal of the first type to one or more of the processing elements **104** via the radio interface **110**. The particular processing element(s) **104** to which the first signal of the first type is provided may be determined, for example, by the instructions sets provided by the dispatch unit **108**.

In operation **206**, the first signal of the first type is processed to generate a set of data. For example, the one or more processing elements **104** may process the received first signal to generate a particular set of data. The set of data may generally be any type of data. For example, the set of data may include location information for one or more devices that transmitted the first signal of the first type. In one example, an RFID device emits a radio signal. The radio signal is detected by the first subset of antennas **116**. The one or more processing elements **104** may process the received signals based on known beamforming or interferometry properties of the first subset of antennas **116** to derive location information about the one or more RFID devices.

In operation **208**, the set of data may be transmitted to a second set of processing elements. For example, the first set of processing elements **104** may transmit the set of data to a second set of processing elements **104**. The particular processing elements **104** included in the second set may be identified by the processing element instruction set(s) being executed by the first set of processing elements **104**. For example, the processing element instruction set may include address information for the second set of processing elements **104**. Once the first set of processing elements **104** generates the set of data, the processing element instruction set may instruct the first set of processing elements **104** to transmit, the set of data to a switch. The switch may then transmit the set of data to the second set of processing elements **104**.

In operation **210**, the set of data may be processed to generate a second signal of a second type. For example, the set of data may be formatted for transmission according to a communications protocol P corresponding to the second type of signal. The communications protocol P may, for

6

example, be a cellular communications protocol P_{cell} , such as 3G, 4G, or 5G. In other examples, the communications protocol P may be protocol P_{WiFi} , Bluetooth® protocol P_{IoT} , or any other type of communication protocol P.

In operation **212**, the second signal of the second type is transmitted with the plurality of antennas. For example, the second set of processing elements **104** may transmit the second signal of the second type to the plurality of antennas **114** and specifically to the second subset of antennas **114** via the cellular interface **112**. The second subset of antennas **118** may transmit the second signal of the second type to a cellular tower for example, or in the case of Wi-Fi, to a Wi-Fi node, such as a router.

FIG. 3 is a flow chart illustrating a method of processing signals with a single integrated circuit chip, in accordance with an example of the present disclosure.

In operation **302**, a first instruction set is loaded to a first set of processing elements. For example, an instruction set of the processing elements loaded by the dispatch unit **108** may be transferred to a first set of processing elements **104** via the NOC **106**. The first set of processing elements **104** may process data according to the received first instruction set.

In operation **304**, a second instruction set is loaded to a second set of processing elements. For example, an instruction set of the processing elements **104** loaded by the dispatch unit **108** may be transferred to a second set of the processing elements **104**, different from the first set of processing elements **104** in operation **302**, via the NOC **106**. The second set of processing elements **104** may process data according to the received second instruction set. The second instruction set may generally include any types of instructions. In one example, the second instruction set includes instructions to convert received signals from a first format (e.g., signal type or communications protocol) to a second format. For example, the second instruction set may include instructions to convert a signal from an RFID format to a format that can be communicated via cellular or WiFi network.

In operation **306**, a signal of a first type is received from a plurality of antennas. For example, the plurality of antennas **114** may detect one or more signals of a first type, such as a radio frequency signal (e.g., and RFID signal). In one example, the signal of the first type may be received by the first set of antennas **116**.

In operation **308**, the signal of the first type is routed to the first set of processing elements. For example, the plurality of antennas **114** may transfer the received signal of the first type to the radio interface **110**. The radio interface **110** may transfer the signal of the first type to the first set of processing elements. As discussed above, the radio interface **110** may include various circuits, such as analog to digital converters, etc.

In operation **310**, the signal of the first type is processed based on the first instruction set. For example, the first set of processing elements **104**, into which the first instruction sets were loaded in operation **302**, may process the received signal of the first type in accordance with the first instruction set. For example, the first instruction set may include processing instructions to determine a location of one or more sources of the signals of the first type. However, those skilled in the art will appreciate that any series of instructions may be executed by the first set of processing elements **104**.

In operation **312**, the processed signal is routed to a second set of processing elements. For example, the first instruction set loaded into the first set of processing elements

104 may include instructions to transfer the processed signal of the first type to the second set of processing elements **104** into which the second instruction set was loaded in operation **304**. Specifically, the first set of processing elements **104** may transfer the processed signal to one or more switches along with an instruction to transmit the signal to the particular processing elements **104** executing the second instruction set. The one or more switches may then transfer the processed signal to the second set of processing elements **104**.

In operation **314**, the signal is processed based on the second instruction set. For example, the second set of processing elements **104**, into which the second instruction set was loaded in operation **304**, may process signals received in operation **312** to generate signals of a second type. As a specific example, the second set of processing elements may convert received signals into a format that can be transmitted via a cellular network or a WiFi network. Such processing may include, for example, converting the received signals into data packets of information for transmission.

In operation **316**, the signal is routed to the plurality of antennas. For example, the second set of processing elements **104** may transmit the processed signal to the cellular interface **112**. As discussed above, the cellular interface **112** may include various circuits, such as an analog to digital converter. The cellular interface **112** may provide the signal of the second type to the plurality of antennas **114**. In a specific example, the cellular interface **112** may provide the signal of the second type to the second set of antennas **118**. In various examples, the second set of antennas **118** may be the same antennas as the first set of antennas **116** on which the signal of the first type was received in operation **306**.

In operation **318**, the signal of the second type is transmitted via the plurality of antennas.

FIG. **4** is a block diagram of plurality of clusters **406** of processing elements **104**, a radio interface **110**, a cellular interface **112**, and an IoT interface **400**, in accordance with an example of the present disclosure. The clusters **406** of processing elements **104**, the radio interface **110**, and the cellular interface **112** may be implemented as described above with respect to FIG. **1**. Similarly to the radio and cellular interfaces **110**, **112** described above, the IoT interface **400** may be coupled to the plurality of antennas **114** and to the one or more of the processing elements **104**. The interface **400** may be configured to transmit and/or receive communication packets or signals at a sub 1-GHz band (i.e., IoT band) via the plurality of antennas **114**. The received communication packets at the IoT frequency band may be converted by the IoT interface into a signal or communication packets that may be manipulated by the one or more processing elements **104** and route the resulting signal to the one or more processing elements **104**.

As shown in FIG. **4**, some of the clusters **406** may be grouped into one or more sets. For example, a first number of clusters **406** may be grouped into a first set **402** and a second number of clusters **406** may be grouped into a second set **404**. Each of the clusters **406** in the first set **402** may be coupled to the radio interface **110**, and the radio interface may route received signals to the clusters **406** in the first set **402**. Each of the processing elements **104** in the clusters **406** may have a first instruction set loaded thereon and may process signals received from the radio interface **110** according to the first instruction set. The clusters **406** of the first set **402** may transmit processed signals to the clusters **406** of the second set **404** via one or more switches. Each of the processing elements **104** of the clusters **406** of the second set

404 may have a second instruction set loaded thereon and process the received signals according to the second instruction set to generate signals of a second type. The clusters **406** of the second set **404** may be coupled to the cellular interface **112** and may transfer the signals of the second type to the cellular interface **112** to be transmitted via a plurality of antennas (not shown).

Although each of the first set **402** and the second set **404** are shown as including nine clusters **406**, greater or fewer clusters **406** may be dynamically added or subtracted from the first set **402** and/or the second set **404** based on system demands or signaling volumes. For example, if the number of radio signals received by the antennas and transmitted to the radio interface **110** increases, additional clusters **406** may be added to the first set **402** to handle the increased processing load.

Furthermore, additional sets of clusters **406** may be included within the reconfigurable fabric. For example, a third and fourth number of clusters **406** may be grouped into a third set of clusters **410** and fourth set of clusters **415**. The third set of clusters **410** may correspond with a packet module **710**, while the fourth set of clusters **415** may correspond with a routing module **715**. Both the packet module **710** and the routing module **715** will be described in detail herein.

FIG. **5** is a block diagram of a plurality of clusters **406** coupled through a switch **502**, in accordance with an example of the present disclosure. In the example of FIG. **5**, each cluster **406** includes four processing elements **104**. Each processing element **104** of a given cluster **406** may communicate directly with another processing element **104** within that same cluster **406**. For example, each of the processing elements PE0-3 can directly communicate with one another. Similarly, processing elements PE4-7 can communicate directly, as can processing elements PE8-11 and PE12-15. Processing elements **104** of different clusters **406** may communicate with one another via a switch **502** based on instructions in whatever instruction set is loaded for a given processing element **104**. For example, the processing element PE14 may transmit a signal to the switch **502** with an instruction that the signal should be routed to the processing element PE1. The switch may route the signal directly to the processing element PE1 or the switch may route the signal to another processing element in the same cluster as PE1 (i.e., processing elements PE0, PE2, or PE3), which then route the received signal to processing element PE1. By linking clusters of processing elements together in this manner, greater or fewer clusters **406** may be added simply by changing the instruction sets that are loaded for a set of processing elements.

FIG. **6** is a block diagram of a processing element **104**, in accordance with an example of the present disclosure. The processing element **104** generally includes a processor **602** coupled to an instruction memory **604**, a data memory **606**, a direct memory access controller **608**, and a switch **610**.

The processor **602** may include, for example, a number of processing cores. In some examples, the processor **602** may include circuitry, including custom circuitry, and/or firmware for performing functions described herein. For example, circuitry can include multiplication units/accumulation units for performing operations described herein. The processor **602** may be, for example, a microprocessor or a digital signal processor (DSP), or any combination thereof. An example processor core can include an arithmetic logic unit (ALU), a bit manipulation unit, a multiplication unit, an accumulation unit, an adder unit, a look-up table unit, a memory look-up unit, or any combination thereof. The

instruction memory **604** is a memory device configured to store a processing element instruction set. The instruction memory **604** may generally be any type of memory. For example, the instruction memory **604** may be a volatile memory, such as dynamic random access memory, or non-volatile memory, such as flash memory. The data memory **606** is a memory device configured to store received data, such as the data included in the signals received and/or transmitted from the plurality of antennas **114**. The data memory **606** may generally be any type of memory. For example, the data memory **606** may be a volatile memory, such as dynamic random access memory, or non-volatile memory, such as flash memory. The direct memory access controller **608** includes control circuitry for the processor **602** to access the instruction memory **604** and the data memory **606**. The switch **610** routes data from one processing element **104** to another processing element **104**. For example, the switch **610** may route data from one processing element **104** to another processing element **104** within a single cluster **406**. The switch may generally be any type of switching fabric.

In operation, a processing element instruction set may be loaded into and stored in the instruction memory **604**. Data in the form of the received signals are stored in the data memory **606**. The processor **602** processes the data in the data memory **606** in accordance with the processing element instruction set stored in the instruction memory **604**. For example, the processor **602** may perform arithmetic operations, convert the data from one format to another, or perform any other type of operations. The direct memory access controller **608** may control access of the processor **602** to the instruction memory **604** and/or the data memory **606**. The processor **602** may transfer processed data to one or more other processing elements **104** via the switch **610**.

FIG. 7 shows a block diagram of the communication device **700** having an integrated circuit chip **702** and a plurality of antennas **705** embedded therein, while FIG. 8 shows a graphical representation of a communication system **800** having a plurality of communication devices **805** communicatively coupled via a network **810**, according to one illustrated example. Reference will now be made to both FIGS. 7 and 8.

The integrated circuit chip **702** is configured to optimize routing of communication packets or signals from a source device **805A** to a destination device **805B** via one or more of the plurality of communication devices **805** through the network **810**, as illustrated in FIG. 8. The network **810** may be configured to provide a plurality of communication paths **815A**, **815B**, **815C** (collectively referenced **815**) to route the communication packets or signals via a plurality of communication protocols P_{cell} , P_{WiFi} , P_{IoT} (collectively referenced P). The plurality of communication paths **815** include data transmission paths between one or more of the plurality of devices **805** via one or more of the plurality of communication protocols P . The network **810** may, for example, take the form of one or more cellular, WiFi, and IoT (e.g., Bluetooth, ZIGBEE) networks operable to transmit signals or communication packets via one or more of the plurality of communication protocols. The network **810** may be a Local Area Network (LAN) or Wide Area Network (WAN).

The plurality of communication devices **805** may, for example, include mobile phones, tablets, smart phones, personal computers, and laptops, to name a few. The plurality of antennas **705** are operable to transmit and receive the communication signals via a plurality of communication protocols, such as cellular, 4G LTE, 5G, WiFi, BLUETOOTH, and ZIGBEE to name a few. The plurality of

antennas **705** may be communicatively coupled to a plurality of interfaces **707**. The plurality of interfaces **707** may include an analog to digital converter to convert the received communication signal via the plurality of antennas **705** into the communication packets that can be processed within the integrated circuit chip **702**. Furthermore, the plurality of interfaces **707** may also include a digital to analog converter to convert the processed plurality of communication packets into an analog signal for transmission via the plurality of antennas **705**.

In one example, the plurality of antennas **705** comprise various sets of antennas **705a**, **705b**, **705c** where each of the sets receive communication signals via different ones of the plurality of communication protocols P . The plurality of antennas **705** are operable to transmit and receive the communication packets or signals via the plurality of communication protocols P .

In one example, first, second and third sets of antennas **705a**, **705b**, **705c**, are respectively coupled to first, second, and third interfaces **707a**, **707b**, **707c**. Each of the first, second, and third interfaces may convert the signals received via defined ones of the plurality of protocols. For example the first interface may be a cellular interface, the second interface may be a radio interface, and a third interface may be an IoT interface. In other words, the first interface **707a** may be configured to convert signals received via a cellular protocol, the second interface **707b** may convert signals received via the radio protocol, and the third interface **707c** may convert signals received via one of the IoT protocols. It will be appreciated by those of ordinary skill in the art that the communication device **700** may employ a single set of antennas **705** coupled to a single interface **707**, where signals received via any one of the plurality of protocols may be converted by the interface **707** for processing by the integrated circuit chip **702**.

Similarly to the FIG. 1 description, the integrated circuit chip **702** may be a single chip capable of processing the plurality of communication packets or signals. Examples of single chip systems include those where circuitry for performing the described tasks are fabricated on and/or into a common substrate generally using semiconductor fabrication techniques. The integrated circuit chip **702** comprises a packet module **710**, a routing module **715** communicatively coupled to a machine learning module **720**, and an application layer **725**.

The packet module **710** comprises a first plurality of processing elements **104** (or a third set of clusters **410**) operable to receive the communication packets via a first one of the plurality of communication protocols P and process an optimal route to transmit the communication packets from the source device **805A** to the destination device **805B** via the network **810**. As will be described in more detail herein, the optimal route may be one or more of the communication paths **815** through the one or more devices **805** that results in an optimized transmission of the communication packets or signals. The packet module **710** may detect transmission of the communication packets from the source device **805A** intended for the destination device **805B**, and process a re-route of the transmitted communication packets or signal to the destination device **805** via the optimal route of the plurality of communication paths **815**. In particular, the optimal route includes the one or more of the communication paths **815** via one or more of the plurality of communication protocols P . For example, the optimal route between the source device **805A** and the destination device **805B** may be through the communication

paths **815A** and **815C** via a cellular protocol P_{cell} and then through communication paths **815C** and **815B** via a WiFi protocol P_{WiFi} .

The routing module **715** comprises a second plurality of processing elements **104** (or a fourth set of clusters **415**) 5 communicatively coupled to the first plurality of processing elements **104** of the packet module **710**. The routing module **715** is operable to determine the optimal route to re-route the transmitted communication packets or signal from the source device **805A** to the destination device **805B** based on 10 transmission characteristics associated with the plurality of devices **805**. The transmission characteristics include at least one of availability of processing resources and telemetry information associated with respective ones of the plurality of devices **805**.

The availability of processing resources associated with respective ones of the plurality of devices **805** may refer to a percentage of processing elements **104** available for respective ones of the plurality of communication protocols P . The processing resources include respective ones of the plurality of processing elements **104** associated with respective ones of the plurality of communication protocols P . As discussed above, the integrated circuit chip **702** includes the sets of clusters **406** having processing elements **104** therein. 20 Each of the processing elements **104** in the clusters **406** may have instructions loaded thereon and process received signals or communication packets according to those instructions. For example, in each of the plurality of devices **805**, a portion of the plurality of processing elements **104** may be instructed to process signals via a first one of the plurality of communication protocols P_{cell} , while another portion of the plurality of processing elements **104** may be instructed to process signals via a second one of the plurality of communication protocols P_{WiFi} . In other words, a defined percentage of the plurality of processing elements **104** on respective ones of the plurality of devices **805** may be allocated for a particular communication protocol P . As such, as devices communicate in real-time via various ones of the communication protocols P , availability of the processing resources may decrease. The availability of processing resources is an indication of whether transmission of signals or communication packets via particular communication protocols P and communication devices **805** may be delayed or interrupted.

The telemetry information may include at least one of velocity, direction of movement, or geographic location of respective ones of the plurality of devices **805**. For example, as will be described in more detail herein, the destination device **805B** may be moving outside a WiFi zone while the source device **805A** attempts to transmit the signal or communication packets. The routing module **715** of at least one of the plurality of devices **805** may re-route the transmitted signal via the cellular protocols P_{cell} and across the communication paths **815A** and **815B** to prevent disconnect while leveraging communication via the WiFi protocol. It will be appreciated by those of ordinary skill in the art that this is merely one example, and any other combination of communication paths **815**, devices **805**, and communication protocols P are within the scope of examples of the disclosure. The routing module **715** may receive telemetry information and resource availability information from each of the plurality of devices **805**. The receipt of such information at the routing module **715** may occur in real-time or close to real-time. This information may be shared with the machine learning module **720** to allow of communication trends to more accurately predict a likelihood of resource availability for each of the plurality of devices **805**, as well as determine

efficient re-allocation of processing resources to better handle future communication requests.

The routing module **715** is communicatively coupled to a machine learning module **720**. The machine learning module **720** may be located within the routing module **715**, embedded within the integrated circuit chip **702**, or located remote from the integrated circuit chip **702**. For example, the machine learning module **720** may be located in the cloud to offload processing power from the integrated circuit chip **702**. It will be appreciated by those of ordinary skill in the art, the machine learning module **720** may be located anywhere. Additionally, the machine learning module may be communicatively coupled to the routing module **715** embedded within each one of the plurality of communication devices **805**. Alternatively, the machine learning module **720** may be communicatively coupled with only one of the plurality of devices **805** that is in hierarchical control of remaining ones of the plurality of devices **805** in the system **800**.

The machine learning module **720** is operable to calculate the optimal route to re-route the transmitted communication packets or signal based on historic transmission characteristics associated with the plurality of communication devices **805**. The historic transmission characteristics of the plurality of communication devices **805** allows the machine learning module **720** to extrapolate a likelihood that one or more of the plurality of communication devices **805** will have particular transmission characteristic in a future time. Based on the likelihood determination, the routing module **715** calculates the optimal route and instructs the packet module **710** accordingly. The optimal route may be based on at least one of the anticipated amount of available processing resources and telemetry information for respective devices **805** in the near future. The optimal route to re-route the transmitted communication packets or signal includes one or more of the communication paths **815** between one or more of the plurality of devices **805** via one or more of the plurality of communication protocols P .

Consequently, the routing module **715** leverages both the real-time (or near real-time) and anticipated resource determination when instructing the packet module **710** to route the communication packets or signal.

The following are a few example examples implementing the route optimization and resource allocation as described above. These are not meant to be an exhaustive listing of examples but a mere sampling to highlight the above-described optimization scheme.

In one example, the system **800** is configured to determine a single one of the plurality of devices **805** that will have hierarchical control over remaining ones of the devices **805**. For example, the device **805C** may be in hierarchical control (“control device”) over the source device **805A** and the destination device **805B**. The control device **805C** may obtain hierarchical control in an ad hoc manner or as part of a hierarchical network. The ad hoc determination of the control device **805C** may be in response to a contention algorithm where the control device **805C** establishes control over the devices **805A** and **805B**. Alternatively, the system **800** may employ the hierarchical network configuration where the control device **805C** is dedicated as the hierarchical control over the other devices **805A**, **805B** in the system **800**.

In a first example, the source device **805A** transmits communication packets or signals to the destination device **805B** via a first communication protocol P_{cell} (e.g., cellular) at a same time each day. The destination device **805B** may consistently travels through a same WiFi zone at that time.

Additionally, a user of the destination device **805B** may typically be downloading data on the device **805B** via the first communication protocol P_{cell} at the same time each day while traversing between WiFi and non-WiFi zones. The machine learning module **720** may learn the transmission characteristics associated with the devices **805A** and **805B**, namely that the source device **805A** transmits the signal via the first communication protocol P_{cell} and that the destination device **805B** travels through a WiFi zone at the same time each day while the destination device **805B** downloads data via the first communication protocol (e.g., 4G LTE). Consequently, the routing module **715** may instruct the packet module **710** to specifically re-route the communication packets from the source device **805A** to the destination device **805B** to create efficient or optimized communications. In particular, the source device **805A** may transmit the communication packets via the first communication protocol P_{cell} to the control device **805C**, and then the control device **805C** may transmit the communication packets to the destination device **805B** via a second communication protocol P_{WiFi} (e.g., WiFi communication). As such, the optimal route processed by the routing module and implemented by the packet module allows for leveraging one or more of the devices **805** to efficiently use available processing resources.

In a second example, the control device **805C** may be leveraged to reallocate processing resources for each of the plurality of devices **805** based on the transmission characteristics as determined in real-time (or close to real-time) and as predicted in the future. For example, through the machine learning module **720**, the control device **805C** may learn that a majority of the plurality of devices **805** leverage the processing resources for downloading streaming media content at a particular time of a day. Consequently, those ones of the plurality of devices **805** may have a majority of the plurality of processing elements **104** re-allocated to WiFi or IoT protocols during the particular time of the day. This would allow for an efficient use of the existing amount of processing resources on the integrated circuit chip **702**.

Alternatively and/or additionally, rather than relying on a single one of the plurality of devices **805** to serve as the control device **805C**, each one of the plurality of devices **805** may be configured to leverage its own reallocation of processing resources based on monitoring its own usage.

As a third example, the source device **805A** may have its processing resources allocated to the first communication protocol P_{cell} (e.g., cellular) and the second communication protocol P_{WiFi} (e.g., WiFi). On the other hand, the destination device **805B** may have processing resources allocated to the second communication protocol P_{WiFi} and the third communication protocol P_{IoT} (e.g., Zigbee, RFID, Bluetooth). The routing module **715** of the control device **805C** or of any other of the plurality of devices **805** may determine the distance between the source and destination devices **805A**, **805B** is great and/or the WiFi network connection therebetween is clogged. In response to such determination, the routing module **715** may instruct the packet module **710** to re-route the communication packets through the communication paths **815A** and **815C** via the first communication protocol P_{cell} to the control device **805C**. Then the control device **805C** may transmit the received communication packets along the communication paths **815C** and **815B** via the third communication protocol P_{IoT} to the destination device **805B**. In other words, the routing module **715** may determine a common communication protocol P between respective ones of the plurality of devices **805** to transmit the communication packets or signals. The common communi-

cation protocol P selected may be one that has sufficient processing resources available therewith.

In another example, the machine learning module **720** may be operable to prioritize routing the signals or communication packets between the plurality of devices **805**. In particular, the machine learning module **720** may determine priority based on historical bandwidth consumption associated with a specific type of data transmission. For example, streaming media transmission may have a higher priority than a cellular transmission, while the cellular transmission may have a higher priority than asynchronous text-messaging communication. It will be appreciated by those of ordinary skill in the art that priority ranking of various types of communication may be set according to any desired ranking. Additionally, the particular ranking of communication types may, for example, vary based on various factors such as, for example, time, day, location, weather patterns, etc.

Alternatively and/or additionally, the routing module **715** may determine prioritization of routes based, at least in part, on a defined user hierarchy associated with each of the plurality of devices **805**. For example, if the source device **805A** or the destination device **805B** is owned by a President of a company, the President's device **805A**, **805B** may have a higher priority over devices **805** used by employees of the company. In other words, the communication packets or signals routed to or from the President's device **805** may be allocated a faster route (or priority route) than the route allocated to communication packets or signals transmitted to/from the employees' devices **805**.

Furthermore, the routing module **715** may single out a specific communication as highest priority level for routing, regardless of the defined user hierarchy associated with respective ones of the plurality of devices **805** or bandwidth considerations. For example, the routing module **715** may allocate emergency communications (e.g., 9-1-1 calls or 9-1-1 text messaging) as highest priority communication. It will be appreciated by those of ordinary skill in the art, the routing module **715** may single out and allocate any other communication as highest priority such as, for example, calls originating from a child's school or a child's caretaker.

Prioritizing routes refers to allocating transmission of the signals or communication packets through various communication paths **815** and protocols to achieve a speedy communication between the source and destination devices **805A**, **805B** via the network **810**. The prioritized routes may entail real-time communication without substantial communication delay. A high priority communication may be allocated a fast communication route between the source and destination devices **805A**, **805B**, while a low priority communication may be allocated a slower communication route between the source and destination devices **805A**, **805B**. As mentioned above, the control device **805C** may receive the communication packets transmitted from the source device **805A** intended for the destination device **805B**. For example, if the plurality of devices **805** comprise more than one pair of source-destination devices **805A**, **805B**, the control device **805C** may prioritize which ones of the source-destination device **805A**, **805B** pairs will have priority over the other. In other words, the control device **805C** may allocate a faster communication path for a first one of the source-destination device **805A**, **805B** pairs and a slower communication path for a second one of the source-destination device **805A**, **805B** pairs. In particular, this allocation of priority may be determined in response to the control device **805C** detecting at least one of the type of communication packets received at the packet module **710**, the

bandwidth consumption associated with the communication packets or signal as determined by the machine learning module **720**, the origin of transmitted communication packets or signal, or the defined user hierarchy associated with the destination and/or source devices **805A**, **805B**.

Based on the control device's **805C** detection, the routing module **715** will determine the one or more communication paths **815** through the one or more devices **805** that results in a transmission speed in-line with the determined priority level of the communication.

Having described some examples of the disclosure, additional examples will become apparent to those skilled in the art to which it pertains. Specifically, although reference was made throughout the specification and drawings to three communication devices (i.e., source, destination, and control devices), it will be appreciated that the system and methods described herein are applicable to examples having any number of communication devices. The example of three communication devices was described merely to readily convey and describe various aspects of re-routing communication packets to optimize the communication between devices, and was not intended to limit the system in any way. For example, the routing module may instruct re-routing of the communication packets or signals from the source device to the destination devices through the control device and any other communication device within the network. Alternatively, the re-routed communication packets may be routed through any of the plurality of devices and not through the control device.

The control device may be any one of the plurality of devices **805**, or embedded within a base station. Additionally, each of the plurality of communication devices **805** may have a routing module coupled to a machine learning module where the routing module communicates with other routing modules of the plurality of devices. As such, each of the plurality of devices **805** may serve as its own control device to coordinate and process optimized routing of communication packets or signals therebetween without requiring a central control device.

The term "communication packets" and "signal" have been used interchangeably herein and both refer to data that is communicated between communication devices. The "communication packets" may refer to a digitized format of data while "signals" may refer to an analog form of data. Examples described herein are applicable to all forms of data.

The terms "communication devices" and "devices" have been used interchangeably herein. The plurality of devices **805** may, for example, be mobile communication devices.

FIG. **9** illustrates an example of a wireless communications system **900** in accordance with aspects of the present disclosure. The wireless communications system **900** includes a base station **910**, a mobile device **915**, a drone **917**, a small cell **930**, and vehicles **940**, **945**. The base station **910** and small cell **930** may be connected to a network that provides access to the Internet and traditional communication links. The system **900** may facilitate a wide-range of wireless communications connections in a 5G system that may include various frequency bands, including but not limited to: a sub-6 GHz band (e.g., 700 MHz communication frequency), mid-range communication bands (e.g., 2.4 GHz), and mmWave bands (e.g., 24 GHz). Additionally or alternatively, the wireless communications connections may support various modulation schemes, including but not limited to: filter bank multi-carrier (FBMC), the generalized frequency division multiplexing (GFDM), universal filtered multi-carrier (UFMC) transmission, bi-orthogonal fre-

quency division multiplexing (BFDM), sparse code multiple access (SCMA), non-orthogonal multiple access (NOMA), multi-user shared access (MUSA), and faster-than-Nyquist (FTN) signaling with time-frequency packing. Such frequency bands and modulation techniques may be a part of a standards framework, such as Long Term Evolution (LTE) or other technical specification published by an organization like 3GPP or IEEE, which may include various specifications for subcarrier frequency ranges, a number of subcarriers, uplink/downlink transmission speeds, TDD/FDD, and/or other aspects of wireless communication protocols.

The system **900** may depict aspects of a radio access network (RAN), and system **900** may be in communication with or include a core network (not shown). The core network may include one or more serving gateways, mobility management entities, home subscriber servers, and packet data gateways. The core network may facilitate user and control plane links to mobile devices via the RAN, and it may be an interface to an external network (e.g., the Internet). Base stations **910**, communication devices **920**, and small cells **930** may be coupled with the core network or with one another, or both, via wired or wireless backhaul links (e.g., S1 interface, X2 interface, etc.).

The system **900** may provide communication links connected to devices or "things," such as sensor devices, e.g., solar cells **937**, to provide an Internet of Things ("IoT") framework. Connected things within the IoT may operate within frequency bands licensed to and controlled by cellular network service providers, or such devices or things may. Such frequency bands and operation may be referred to as narrowband IoT (NB-IoT) because the frequency bands allocated for IoT operation may be small or narrow relative to the overall system bandwidth. Frequency bands allocated for NB-IoT may have bandwidths of 1, 5, 10, or 20 MHz, for example.

Additionally or alternatively, the IoT may include devices or things operating at different frequencies than traditional cellular technology to facilitate use of the wireless spectrum. For example, an IoT framework may allow multiple devices in system **900** to operate at a sub-6 GHz band or other industrial, scientific, and medical (ISM) radio bands where devices may operate on a shared spectrum for unlicensed uses. The sub-6 GHz band may also be characterized as and may also be characterized as an NB-IoT band. For example, in operating at low frequency ranges, devices providing sensor data for "things," such as solar cells **937**, may utilize less energy, resulting in power-efficiency and may utilize less complex signaling frameworks, such that devices may transmit asynchronously on that sub-6 GHz band. The sub-6 GHz band may support a wide variety of uses case, including the communication of sensor data from various sensors devices. Examples of sensor devices include sensors for detecting energy, heat, light, vibration, biological signals (e.g., pulse, EEG, EKG, heart rate, respiratory rate, blood pressure), distance, speed, acceleration, or combinations thereof. Sensor devices may be deployed on buildings, individuals, and/or in other locations in the environment. The sensor devices may communicate with one another and with computing systems which may aggregate and/or analyze the data provided from one or multiple sensor devices in the environment.

In such a 5G framework, devices may perform functionalities performed by base stations in other mobile networks (e.g., UMTS or LTE), such as forming a connection or managing mobility operations between nodes (e.g., handoff or reselection). For example, mobile device **915** may receive sensor data from the user utilizing the mobile device **915**,

such as blood pressure data, and may transmit that sensor data on a narrowband IoT frequency band to base station **910**. In such an example, some parameters for the determination by the mobile device **915** may include availability of licensed spectrum, availability of unlicensed spectrum, and/or time-sensitive nature of sensor data. Continuing in the example, mobile device **915** may transmit the blood pressure data because a narrowband band is available and can transmit the sensor data quickly, identifying a time-sensitive component to the blood pressure (e.g., if the blood pressure measurement is dangerously high or low, such as systolic blood pressure is three standard deviations from norm).

Additionally or alternatively, mobile device **915** may form device-to-device (D2D) connections with other mobile devices or other elements of the system **900**. For example, the mobile device **915** may form RFID, WiFi, MultiFire, Bluetooth, or Zigbee connections with other devices, including communication device **920** or vehicle **945**. In some examples, D2D connections may be made using licensed spectrum bands, and such connections may be managed by a cellular network or service provider. Accordingly, while the above example was described in the context of narrowband IoT, it can be appreciated that other device-to-device connections may be utilized by mobile device **915** to provide information (e.g., sensor data) collected on different frequency bands than a frequency band determined by mobile device **915** for transmission of that information.

Moreover, some communication devices may facilitate ad-hoc networks, for example, a network being formed with communication devices **920** attached to stationary objects (e.g., lampposts in FIG. 9) and the vehicles **940**, **945**, without a traditional connection to a base station **910** and/or a core network necessarily being formed. Other stationary objects may be used to support communication devices **920**, such as, but not limited to, trees, plants, posts, buildings, blimps, dirigibles, balloons, street signs, mailboxes, or combinations thereof. In such a system **900**, communication devices **920** and small cell **930** (e.g., a small cell, femtocell, WLAN access point, cellular hotspot, etc.) may be mounted upon or adhered to another structure, such as lampposts and buildings to facilitate the formation of ad-hoc networks and other IoT-based networks. Such networks may operate at different frequency bands than existing technologies, such as mobile device **915** communicating with base station **910** on a cellular communication band.

The communication devices **920** may form wireless networks, operating in either a hierarchal or ad-hoc network fashion, depending, in part, on the connection to another element of the system **900**. For example, the communication devices **920** may utilize a 700 MHz communication frequency to form a connection with the mobile device **915** in an unlicensed spectrum, while utilizing a licensed spectrum communication frequency to form another connection with the vehicle **945**. Communication devices **920** may communicate with vehicle **945** on a licensed spectrum to provide direct access for time-sensitive data, for example, data for an autonomous driving capability of the vehicle **945** on a 5.9 GHz band of Dedicated Short Range Communications (DSRC).

Vehicles **940** and **945** may form an ad-hoc network at a different frequency band than the connection between the communication device **920** and the vehicle **945**. For example, for a high bandwidth connection to provide time-sensitive data between vehicles **940**, **945**, a 24 GHz mmWave band may be utilized for transmissions of data between vehicles **940**, **945**. For example, vehicles **940**, **945** may share real-time directional and navigation data with

each other over the connection while the vehicles **940**, **945** pass each other across a narrow intersection line. Each vehicle **940**, **945** may be tracking the intersection line and providing image data to an image processing algorithm to facilitate autonomous navigation of each vehicle while each travels along the intersection line. In some examples, this real-time data may also be substantially simultaneously shared over an exclusive, licensed spectrum connection between the communication device **920** and the vehicle **945**, for example, for processing of image data received at both vehicle **945** and vehicle **940**, as transmitted by the vehicle **940** to vehicle **945** over the 24 GHz mmWave band. While shown as automobiles in FIG. 9, other vehicles may be used including, but not limited to, aircraft, spacecraft, balloons, blimps, dirigibles, trains, submarines, boats, ferries, cruise ships, helicopters, motorcycles, bicycles, drones, or combinations thereof.

While described in the context of a 24 GHz mmWave band, it can be appreciated that connections may be formed in the system **900** in other mmWave bands or other frequency bands, such as 28 GHz, 37 GHz, 38 GHz, 39 GHz, which may be licensed or unlicensed bands. In some cases, vehicles **940**, **945** may share the frequency band that they are communicating on with other vehicles in a different network. For example, a fleet of vehicles may pass vehicle **940** and, temporarily, share the 24 GHz mmWave band to form connections among that fleet, in addition to the 24 GHz mmWave connection between vehicles **940**, **945**. As another example, communication device **920** may substantially simultaneously maintain a 700 MHz connection with the mobile device **915** operated by a user e.g., a pedestrian walking along the street) to provide information regarding a location of the user to the vehicle **945** over the 5.9 GHz band. In providing such information, communication device **920** may leverage antenna diversity schemes as part of a massive MIMO framework to facilitate time-sensitive, separate connections with both the mobile device **915** and the vehicle **945**. A massive MIMO framework may involve a transmitting and/or receiving devices with a large number of antennas (e.g., 12, 20, 64, 128, etc.), which may facilitate precise beamforming or spatial diversity unattainable with devices operating with fewer antennas according to legacy protocols (e.g., WiFi or LTE).

The base station **910** and small cell **930** may wirelessly communicate with devices in the system **900** or other communication-capable devices in the system **900** having at the least a sensor wireless network, such as solar cells **937** that may operate on an active/sleep cycle, and/or one or more other sensor devices. The base station **910** may provide wireless communications coverage for devices that enter its coverage area, such as the mobile device **915** and the drone **917**. The small cell **930** may provide wireless communications coverage for devices that enter its coverage area, such as near the building that the small cell **930** is mounted upon, such as vehicle **945** and drone **917**.

Generally, a small cell **930** may be referred to as a small cell and provide coverage for a local geographic region, for example, coverage of 200 meters or less in some examples. This may contrasted with at macrocell, which may provide coverage over a wide or large area on the order of several square miles or kilometers. In some examples, a small cell **930** may be deployed (e.g., mounted on a building) within some coverage areas of a base station **910** (e.g., a macrocell) where wireless communications traffic may be dense according to a traffic analysis of that coverage area. For example, a small cell **930** may be deployed on the building in FIG. 9 in the coverage area of the base station **910** if the base station

910 generally receives and/or transmits a higher amount of wireless communication transmissions than other coverage areas of that base station **910**. A base station **910** may be deployed in a geographic area to provide wireless coverage for portions of that geographic area. As wireless communications traffic becomes more dense, additional base stations **910** may be deployed in certain areas, which may alter the coverage area of an existing base station **910**, or other support stations may be deployed, such as a small cell **930**. Small cell **930** may be a femtocell, which may provide coverage for an area smaller than a small cell (e.g., 100 meters or less in some examples (e.g., one story of a building)).

While base station **910** and small cell **930** may provide communication coverage for a portion of the geographical area surrounding their respective areas, both may change aspects of their coverage to facilitate faster wireless connections for certain devices. For example, the small cell **930** may primarily provide coverage for devices surrounding or in the building upon which the small cell **930** is mounted. However, the small cell **930** may also detect that a device has entered its coverage area and adjust its coverage area to facilitate a faster connection to that device.

For example, a small cell **930** may support a massive MIMO connection with the drone **917**, which may also be referred to as an unmanned aerial vehicle (UAV), and, when the vehicle **915** enters its coverage area, the small cell **930** adjusts some antennas to point directionally in a direction of the vehicle **945**, rather than the drone **917**, to facilitate a massive MIMO connection with the vehicle, in addition to the drone **917**. In adjusting some of the antennas, the small cell **930** may not support as fast as a connection to the drone **917**, as it had before the adjustment. However, the drone **917** may also request a connection with another device (e.g., base station **910**) in its coverage area that may facilitate a similar connection as described with reference to the small cell **930**, or a different (e.g., faster, more reliable) connection with the base station **910**. Accordingly, the system **930** may enhance existing communication links in providing additional connections to devices that may utilize or demand such links. For example, the small cell **930** may include a massive MIMO system that directionally augments a link to vehicle **945**, with antennas of the small cell directed to the vehicle **945** for a specific time period, rather than facilitating other connections (e.g., the small cell **930** connections to the base station **910**, drone **917**, or solar cells **937**). In some examples, drone **917** may serve as a movable or aerial base station.

The wireless communications system **900** may include devices such as base station **910**, communication device **920**, and small cell **930** that may support several connections to devices in the system **900**. Such devices may operate in a hierarchal mode or an ad-hoc mode with other devices in the network of system **900**. While described in the context of a base station **910**, communication device **920**, and small cell **930**, it can be appreciated that other devices that can support several connections with devices in the network may be included in system **900**, including but not limited to: macrocells, femtocells, routers, satellites, and RFID detectors.

In various examples, the elements of wireless communication system **900**, such as base station **910**, a mobile device **915**, a drone **917**, communication device **920**, a small cell **930**, and vehicles **940**, **945**, may be implemented utilizing an integrated circuit chip as described herein. For example, the communication device **920** may be implemented with an integrated circuit chip **102** or integrated circuit chip **702**. In

the latter case, the communication device **920** may be implemented as the communication device **700**. In various examples, the elements of communication system **900** may implement any of the systems described in FIGS. **1** and **4-8** or methods described in FIGS. **2-3**.

FIG. **10** illustrates an example of a wireless communications system **1000** in accordance with aspects of the present disclosure. The wireless communications system **1000** includes a mobile device **1015**, a drone **1017**, a communication device **1020**, and a small cell **1030**. A building **1010** also includes devices of the wireless communication system **1000** that may be configured to communicate with other elements in the building **1010** or the small cell **1030**. The building **1010** includes networked workstations **1040**, **1045**, virtual reality device **1050**, IoT devices **1055**, **1060**, and networked entertainment device **1065**. In the depicted system **1000**, IoT devices **1055**, **1060** may be a washer and dryer, respectively, for residential use, being controlled by the virtual reality device **1050**. Accordingly, while the user of the virtual reality device **1050** may be in different room of the building **1010**, the user may control an operation of the IoT device **1055**, such as configuring a washing machine setting. Virtual reality device **1050** may also control the networked entertainment device **1065**. For example, virtual reality device **1050** may broadcast a virtual game being played by a user of the virtual reality device **1050** onto a display of the networked entertainment device **1065**.

The small cell **1030** or any of the devices of building **1010** may be connected to a network that provides access to the Internet and traditional communication links. Like the system **900**, the system **1000** may facilitate a wide-range of wireless communications connections in a 5G system that may include various frequency bands, including but not limited to: a sub-6 GHz band (e.g., 700 MHz communication frequency), mid-range communication bands (e.g., 2.4 GHz), and mmWave bands (e.g., 24 GHz). Additionally or alternatively, the wireless communications connections may support various modulation schemes as described above with reference to system **900**. System **1000** may operate and be configured to communicate analogously to system **900**. Accordingly, similarly numbered elements of system **1000** and system **900** may be configured in an analogous way, such as communication device **920** to communication device, small cell **930** to small cell **1030**, etc. . . .

Like the system **900**, where elements of system **900** are configured to form independent hierarchal or ad-hoc networks, communication device **920** may form a hierarchal network with small cell **1030** and mobile device **1015**, while an additional ad-hoc network may be formed among the small cell **1030** network that includes drone **1017** and some of the devices of the building **1010**, such as networked workstations **1040**, **1045** and IoT devices **1055**, **1060**.

Devices in communication system **1000** may also form (D2D) connections with other mobile devices or other elements of the system **1000**. For example, the virtual reality device **1050** may form a narrowband IoT connections with other devices, including IoT device **1055** and networked entertainment device **1065**. As described above, in some examples, D2D connections may be made using licensed spectrum bands, and such connections may be managed by a cellular network or service provider. Accordingly, while the above example was described in the context of a narrowband IoT, it can be appreciated that other device-to-device connections may be utilized by virtual reality device **1050**.

In various examples, the elements of wireless communication system **1000**, such as the mobile device **1015**, the

drone **1017**, the communication device **1020**, and the small cell **1030**, the networked workstations **1040**, **1045**, the virtual reality device **1050**, the IoT devices **1055**, **1060**, and the networked entertainment device **1065**, may be implemented utilizing an integrated circuit chip as described herein. For example, the communication device **1020** may be implemented with an integrated circuit chip **102** or integrated circuit chip **702**. In an example, the IoT devices **1055**, **1060** may implement an integrated circuit having several processing elements like processing element **104** that is coupled to an IoT interface **400** in that integrated circuit for transmitting and/or receiving communication packets or signals at an IoT band via the plurality of antennas **114**.

In an example, the small cell **1030** may determine prioritized routes among the device of the building **1010**. Higher prioritized routes may include a cellular connection for the drone **1017** and WiFi connections for the networked workstations **1040**, **1045**, while lower prioritized routes may include an IoT connection to the IoT device **1060**. Consequently, a routing module **715** of the small cell **1030** may instruct the packet module **710** to specifically re-route the communication packets from the networked workstation **1040** to the drone **1017** to create efficient or optimized communications. In the example, the networked workstation **1040** may transmit the communication packets via a first communication protocol (e.g., P_{WiFi}) to the small cell **1030**, and then the small cell **1030** may transmit the communication packets to the drone **1017** via a second communication protocol (e.g., P_{cell}). Additionally or alternatively, in a cluster of processing elements **104** that are communicating a processed signal to a cellular interface **112** for the small cell **1030** to communicate with the drone **1017**, greater or fewer clusters **406** may be dynamically added or subtracted from a first set of clusters **402** and/or a second set of clusters **404** based on system demands or signaling volumes. For example, if a number of cellular signals received by the antennas and transmitted to the a cellular interface **112** increases based on additional communication signals from the drone **1017**, additional clusters **406** may be added to the first set of clusters **404** to handle the increased processing load.

While described above in the context of some specific examples of the elements of communication system **1000**, the elements of communication system **1000** may implement any of the systems described in FIGS. **1** and **4-8** or methods described in FIGS. **2-3**.

Certain details are set forth above to provide a sufficient understanding of described examples. However, it will be clear to one skilled in the art that examples may be practiced without various of these particular details. The description herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The terms “exemplary” and “example” as may be used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be

referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

Techniques described herein may be used for various wireless communications systems, which may include multiple access cellular communication systems, and which may employ code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal frequency division multiple access (OFDMA), or single carrier frequency division multiple access (SC-FDMA), or any a combination of such techniques. Some of these techniques have been adopted in or relate to standardized wireless communication protocols by organizations such as Third Generation Partnership Project (3GPP), Third Generation Partnership Project 2 (3GPP2) and IEEE. These wireless standards include Ultra Mobile Broadband (UMB), Universal Mobile Telecommunications System (UMTS), Long Term Evolution (LTE), LTE-Advanced (LTE-A), LTE-A Pro, New Radio (NR), IEEE 802.11 (WiFi), and IEEE 802.16 (WiMAX), among others.

The terms “5G” or “5G communications system” may refer to systems that operate according to standardized protocols developed or discussed after, for example, LTE Releases 13 or 14 or WiMAX 80216e-2005 by their respective sponsoring organizations. The features described herein may be employed in systems configured according to other generations of wireless communication systems, including those configured according to the standards described above.

The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, non-transitory computer-readable media can comprise RAM, ROM, electrically erasable programmable read only memory (EEPROM), or optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor.

Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Combinations of the above are also included within the scope of computer-readable media.

Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

Also, as used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

From the foregoing it will be appreciated that, although specific examples have been described herein for purposes of illustration, various modifications may be made while remaining within the scope of the claimed technology. The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein, but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

What is claimed is:

1. An apparatus comprising:

a plurality of antennas operable to transmit or receive communication packets via a plurality of communication protocols; and

an integrated circuit chip coupled to the plurality of antennas, the integrated circuit chip comprising:

a first plurality of processing elements configured to process a first plurality of communication packets based on a first instruction set associated with a first communication protocol of the plurality of communication protocols;

a second plurality of processing elements configured to determine a route for the first plurality of communication packets;

a third plurality of processing elements configured to determine routing among a plurality of devices to transmit the first plurality of communication packets; and

a fourth plurality of processing elements configured to generate a second plurality of communication packets based on a second instruction set associated with

a second communication protocol of the plurality of communication protocols.

2. The apparatus of claim 1, wherein a processing element of the first plurality of processing elements comprises at least one of an arithmetic logic unit (ALU), a bit manipulation unit, a multiplication unit, an accumulation unit, an adder unit, a look-up table unit, or a memory look-up unit, or any combination thereof.

3. The apparatus of claim 1, further comprising:

a switch configured to communicatively couple the first, second, third, and fourth pluralities of processing elements.

4. The apparatus of claim 3, wherein the switch is configured to transfer a processed plurality of communication packets to the fourth plurality of processing elements for generation of the second plurality of communication packets.

5. The apparatus of claim 1, wherein the plurality of communication protocols comprise at least one of a cellular communication protocol, WiFi, Zigbee, Bluetooth, or a radio frequency.

6. The apparatus of claim 1, further comprising:

a first memory in electronic communication with the first plurality of processing elements and configured to store the first instruction set; and

a second memory configured to store the second instruction set.

7. The apparatus of claim 1, wherein the first plurality of processing elements is configured to process a third plurality of communication packets associated with the second communication protocol based on a processing element of the first plurality of processing elements being allocated to a processing cluster associated with the second communication protocol, the processing cluster including the second plurality of processing elements.

8. The apparatus of claim 1, further comprising:

a plurality of interfaces respectively coupled to the plurality of antennas based on an associated communication protocol.

9. A method comprising:

receiving a first communication packet associated with a first communication protocol;

processing the first communication packet based on a first instruction set associated with the first communication protocol;

determining a route for the first communication packet to be transmitted among a plurality of devices;

processing the first communication packet to generate a second communication packet based on a second instruction set associated with a second communication protocol;

transmitting the second communication packet associated with the second communication protocol;

detecting transmission of the first communication packet from a first device of the plurality of devices to a second device of the plurality of devices; and

determining a re-route of the first communication packet based on transmission characteristics associated with the plurality of devices, wherein determining the re-route of the first communication packet further comprises:

extrapolating a likelihood that one or more of the plurality of devices will have a particular transmission characteristic in a future time based on a respective historic transmission characteristic associated with the plurality of devices.

25

10. The method of claim 9, further comprising:
determining a first device of the plurality of devices has hierarchical control over remaining ones of the plurality of devices in an ad hoc manner.
11. The method of claim 9, further comprising:
loading the first instruction set on a first portion of a plurality of processing elements; and
loading the second instruction set on a second portion of the plurality of processing elements.
12. A method comprising:
receiving a first communication packet associated with a first communication protocol;
processing the first communication packet based on a first instruction set associated with the first communication protocol;
determining a route for the first communication packet to be transmitted among a plurality of devices;
processing the first communication packet to generate a second communication packet based on a second instruction set associated with a second communication protocol;
transmitting the second communication packet associated with the second communication protocol;
detecting transmission of the first communication packet from a first device of the plurality of devices to a second device of the plurality of devices; and
determining a re-route of the first communication packet based on transmission characteristics associated with the plurality of devices, wherein the transmission characteristics include at least one of availability of processing resources and telemetry information associated with respective ones of the plurality of devices.
13. The method of claim 12, wherein the availability of processing resources associated with the respective ones of the plurality of devices is based on a percentage of processing elements available for respective ones of the first communication protocol and the second communication protocol.
14. The method of claim 12, wherein the telemetry information comprises at least one of velocity, direction of movement, or geographic location of respective ones of the plurality of devices.
15. A system comprising:
a first device comprising a first antenna operable to receive or transmit first signals or communication packets via a first plurality of communication protocols;

26

- a second device comprising a second antenna operable to receive or transmit second signals or communication packets via a second plurality of communication protocols;
- a third device comprising an integrated circuit chip; and
a network coupled to the first, second, and third devices, wherein the network is configured to provide a plurality of communication paths to route the first communication packets via a plurality of communication protocols,
- wherein the integrated circuit chip of the third device comprises:
a first plurality of processing elements operable to receive the first communication packets via a first communication protocol from the first device and process a route to transmit the first communication packets from the first device to the second device via one or more of the plurality of communication paths based on a first instruction set associated with the first communication protocol; and
a second plurality of processing elements communicatively coupled to the first plurality of processing elements, the second plurality of processing elements operable to determine a re-route of the first communication packets from the first device to the second device based on transmission characteristics associated with the second device.
16. The system of claim 15, wherein the first device further comprises an analog to digital converter configured to convert the first signals into the first communication packets responsive to the first antenna receiving the first signals.
17. The system of claim 15, wherein the second device further comprises a digital to analog converter configured to convert the second communication packets into the second communication signals for transmission via the second antenna responsive to the second antenna receiving the second communication packets.
18. The system of claim 15, wherein the first plurality of processing elements is further configured to detect transmission of the first communication packets from the first device intended for the second device.

* * * * *