



US012260783B2

(12) **United States Patent**
Vaccaro et al.

(10) **Patent No.:** **US 12,260,783 B2**
(45) **Date of Patent:** **Mar. 25, 2025**

(54) **HANGER FOR MOUNTING CABLES**

(56) **References Cited**

(71) Applicant: **Outdoor Wireless Networks LLC**,
Claremont, NC (US)

(72) Inventors: **Ronald A. Vaccaro**, Taylorsville, NC
(US); **Aviral Joshi**, Chicago, IL (US);
Taig S. Rajpal, Chicago, IL (US)

(73) Assignee: **Outdoor Wireless Networks LLC**,
Richardson, TX (US)

U.S. PATENT DOCUMENTS

4,958,792 A 9/1990 Rinderer
5,967,468 A 10/1999 Veghte et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1260605 A 7/2000
FR 2417870 A1 9/1979
(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

Extended European Search Report corresponding to European Appli-
cation No. 16773786.5 dated Oct. 5, 2018.
(Continued)

Primary Examiner — Steven M Marsh
(74) *Attorney, Agent, or Firm* — Myers Bigel, P.A.

(65) **Prior Publication Data**
US 2024/0153413 A1 May 9, 2024

Related U.S. Application Data

(60) Continuation of application No. 18/150,447, filed on
Jan. 5, 2023, now Pat. No. 11,830,386, which is a
(Continued)

(51) **Int. Cl.**
F16M 13/00 (2006.01)
E01F 9/608 (2016.01)
(Continued)


(52) **U.S. Cl.**
CPC **G09F 15/0018** (2013.01); **E01F 9/608**
(2016.02); **E01F 9/65** (2016.02);
(Continued)

(58) **Field of Classification Search**
None
See application file for complete search history.

(57) **ABSTRACT**

A cable hanger includes: a base panel having opposed ends;
a pair of arms, each of the arms attached to a respective end
of the base panel and having a free end; a pair of locking
projections, each of the locking projections attached to a
respective free end of the arms; and a pair of gripping
members, each gripping member attached to a respective
arm, each gripping member having opposed ends, wherein
one of the ends of each gripping member is fixed to the arms
and the other of the ends of each gripping member is fixed
to the arm or to the base panel. The arms and locking
projections are configured to spread apart to enable insertion
of a cable between the arms, wherein the gripping projec-
tions engage and grip the cable, and wherein the locking
projections are configured to be inserted into the aperture of
the supporting structure.

8 Claims, 10 Drawing Sheets



Related U.S. Application Data

continuation of application No. 17/569,784, filed on Jan. 6, 2022, now Pat. No. 11,551,589, which is a continuation of application No. 17/195,809, filed on Mar. 9, 2021, now Pat. No. 11,238,762, which is a division of application No. 16/360,485, filed on Mar. 21, 2019, now Pat. No. 11,004,367, which is a continuation of application No. 16/114,760, filed on Aug. 28, 2018, now Pat. No. 10,243,339, which is a division of application No. 15/834,766, filed on Dec. 7, 2017, now Pat. No. 10,158,218, which is a division of application No. 15/081,177, filed on Mar. 25, 2016, now Pat. No. 9,866,004.

(60) Provisional application No. 62/248,460, filed on Oct. 30, 2015, provisional application No. 62/206,558, filed on Aug. 18, 2015, provisional application No. 62/139,057, filed on Mar. 27, 2015.

(51) Int. Cl.

E01F 9/65 (2016.01)
F16B 1/00 (2006.01)
G09F 15/00 (2006.01)
H02G 3/32 (2006.01)
F16B 2/24 (2006.01)
F16B 5/06 (2006.01)
G09F 23/00 (2006.01)

(52) U.S. Cl.

CPC F16B 1/00 (2013.01); G09F 15/0037 (2013.01); G09F 15/0062 (2013.01); G09F 15/0075 (2013.01); H02G 3/32 (2013.01); F16B 2/243 (2013.01); F16B 5/0685 (2013.01); G09F 23/00 (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

6,161,804 A 12/2000 Paske et al.
6,257,530 B1 7/2001 Tsai
6,354,543 B1 3/2002 Paske
7,097,142 B1 8/2006 Schmidt

7,146,688 B2 12/2006 Yi
7,293,745 B2 11/2007 Catapano
8,011,621 B2 9/2011 Korczak
8,079,561 B2 12/2011 Jafari
8,191,836 B2 6/2012 Korczak
8,439,316 B2 5/2013 Feige
9,306,380 B2 4/2016 Vaccaro
9,879,803 B2 * 1/2018 Leng H02G 3/32
9,903,510 B2 2/2018 Joshi et al.
10,637,226 B2 4/2020 Bell et al.
10,823,312 B2 * 11/2020 Vaccaro F16L 3/133
10,927,980 B2 2/2021 Varale
2002/0005463 A1 1/2002 Paske et al.
2005/0109890 A1 5/2005 Korczak et al.
2009/0230256 A1 9/2009 Widlacki et al.
2009/0294602 A1 12/2009 Korczak
2010/0000763 A1 1/2010 Stansberry, Jr.
2010/0264277 A1 10/2010 Gardner
2011/0226913 A1 9/2011 Feige
2016/0281881 A1 9/2016 Vaccaro et al.
2018/0045336 A1 2/2018 Vaccaro
2018/0163899 A1 6/2018 Rajpal et al.
2018/0172183 A1 6/2018 Joshi et al.



FOREIGN PATENT DOCUMENTS



GB 1031573 A 6/1966
GB 2014644 A 8/1979
GB 2191241 A 12/1987
WO 03041541 A2 5/2003



OTHER PUBLICATIONS



Extended European Search Report corresponding to European Application No. 22192711.4 dated Mar. 27, 2023.
Extended European Search Report corresponding to European Patent Application No. 20185679.6 mailed Sep. 30, 2020, 8 pages.
International Search Report and Written Opinion for corresponding PCT Application No. PCT/US2016/023939, date of mailing Aug. 24, 2016, 11 pages.
Office Action corresponding to Chinese Application No. 201910515191.8 dated Jun. 15, 2020.
Office Action corresponding to Chinese Application No. 201910515191.8 issued Jan. 13, 2021.

* cited by examiner












FIG. 9







FIG. 10






FIG. 14








FIG. 15








FIG. 20




FIG. 21

HANGER FOR MOUNTING CABLES**RELATED APPLICATIONS**

The present application is a continuation of and claims priority to U.S. patent application Ser. No. 18/150,447, filed Jan. 5, 2023, which is a continuation of and claims priority to U.S. patent application Ser. No. 17/569,784, filed Jan. 6, 2022, now U.S. Pat. No. 11,551,589, which is a continuation of and claims priority to U.S. patent application Ser. No. 17/195,809, filed Mar. 9, 2021, now U.S. Pat. No. 11,238,762, which is a divisional of and claims priority to U.S. patent application Ser. No. 16/360,485, filed Mar. 21, 2019, now U.S. Pat. No. 11,004,367, which is a continuation of and claims priority to U.S. patent application Ser. No. 16/114,760, filed Aug. 28, 2018, now U.S. Pat. No. 10,243,339, which is a divisional of and claims priority to U.S. patent application Ser. No. 15/834,766, filed Dec. 7, 2017, now U.S. Pat. No. 10,158,218, which is a divisional of U.S. patent application Ser. No. 15/081,177, filed Mar. 25, 2016, now U.S. Pat. No. 9,866,004 and claims priority from the benefit of U.S. Provisional Patent Application Nos. 62/139,057, filed Mar. 27, 2015; 62/206,558, filed Aug. 18, 2015; and 62/248,460, filed Oct. 30, 2015, the disclosures of which are hereby incorporated herein by reference in their entirety.

FIELD OF THE INVENTION

This invention relates generally to devices for supporting cables and, in particular, to hangers for securing cables to support structures.

BACKGROUND OF THE INVENTION

Cable hangers are commonly used to secure cables to structural members of antenna towers and or along tunnel walls. Generally, each cable is attached to a structural member by cable hangers mounted at periodically-spaced attachment points.

Antenna towers and or tunnels may be crowded due to the large numbers of cables required for signal-carrying. Over time, as systems are added, upgraded and/or expanded, installation of additional cables may be required. To conserve space, it may be desirable for each set of cable hangers to secure more than a single cable. Certain cable hangers have been constructed to secure multiple cables; other cable hangers have a stackable construction that permits multiple cable hangers to be interlocked extending outwardly from each mounting point/structural member. Stacked and multiple-cable-type cable hangers significantly increase the number of cables mountable to a single attachment point.

One popular stackable cable hanger is discussed in U.S. Pat. No. 8,191,836 to Korczak, the disclosure of which is hereby incorporated herein in its entirety. Hangers disclosed therein have generally a U- or C-shaped profile with rounded arms. A locking projection extends from the free end of each arm, and the "root" of the hanger that spans the fixed ends of the arms has a large aperture. The hanger can hold a cable between the arms; gripping of the cable is enhanced by short fingers that extend inwardly from the arms to engage the cable. Hangers can be "stacked" onto each other by inserting the locking projections of one hanger into the large aperture of the next hanger.

One variety of cable hanger of this type is the SNAP-STAK® hanger, available from CommScope, Inc. (Joliet, Illinois). The SNAP-STAK® hanger is offered in multiple sizes that correspond to the outer diameters of different

cables. This arrangement has been suitable for use with coaxial power cables, which tend to be manufactured in only a few different outer diameters; however, the arrangement has been less desirable for fiber optic cables, which tend to be manufactured in a much greater variety of diameters. Moreover, fiber optic cables tend to be much heavier than coaxial cables (sometimes as much as three times heavier per unit foot), which induces greater load and stress on the hangers.

SUMMARY

As a first aspect, embodiments of the invention are directed to a cable hanger for securing a cable to a supporting structure having an aperture. The cable hanger comprises: a base panel having opposed ends; a pair of arms, each of the arms attached to a respective end of the base panel and having a free end; a pair of locking projections, each of the locking projections attached to a respective free end of the arms; and a pair of gripping members, each gripping member attached to a respective arm, each gripping member having opposed ends, wherein one of the ends of each gripping member is fixed to the arms and the other of the ends of each gripping member is fixed to the arm or to the base panel. The arms and locking projections are configured to spread apart to enable insertion of a cable between the arms, wherein the gripping projections engage and grip the cable, and wherein the locking projections are configured to be inserted into the aperture of the supporting structure.

As a second aspect, a cable hanger for securing a cable to a supporting structure having an aperture comprises: a base panel having opposed ends; a pair of arms, each of the arms attached to a respective end of the base panel and having a free end; a pair of locking projections, each of the locking projections attached to a respective free end of the arms; and a pair of gripping members, each gripping member attached to a respective arm, each gripping member having opposed ends, wherein one of the ends is fixed to a respective arm or to the base panel, and wherein the other of the ends engages a feature mounted to the arm. The arms and locking projections are configured to spread apart to enable insertion of a cable between the arms, wherein the gripping projections engage and grip the cable, and wherein the locking projections are configured to be inserted into the aperture of the supporting structure.

As a third aspect, a cable hanger for securing a cable to a supporting structure having an aperture comprises: a base panel having opposed ends; a pair of arms, each of the arms attached to a respective end of the base panel and having a free end; a pair of locking projections, each of the locking projections attached to a respective free end of the arms; and a pair of gripping members, each gripping member attached to a respective arm, each gripping member having opposed ends, wherein a first end of each of the gripping members is fixed to a respective arm or to the base panel, and wherein a second end of each of the gripping members includes a locking feature that is configured to interlock with a second end of the other gripping member. The arms and locking projections are configured to spread apart to enable insertion of a cable between the arms, wherein the gripping projections engage and grip the cable, and wherein the locking projections are configured to be inserted into the aperture of the supporting structure.

As a fourth aspect, a cable hanger for securing a cable to a supporting structure having an aperture comprises: a base panel having opposed ends; a pair of arms, each of the arms

3

attached to a respective end of the base panel and having a free end; a pair of locking projections, each of the locking projections attached to a respective free end of the arms; a pair of flex members, each flex member attached to a respective arm, each flex member having opposed ends, wherein one of the ends of each flex member is fixed to the arms and the other of the ends of each flex member is fixed to the arm or to the base panel; and a cantilevered gripping member extending from each flex member. The arms and locking projections are configured to spread apart to enable insertion of a cable between the arms, wherein the cantilevered gripping members engage and grip the cable, and wherein the locking projections are configured to be inserted into the aperture of the supporting structure.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a perspective view of a prior art cable hanger. FIG. 2 is a top view of the prior art cable hanger of FIG. 1.

FIG. 3 is a side view of a cable hanger according to embodiments of the invention.

FIG. 4 is a top view of the cable hanger of FIG. 3.

FIG. 5 is a side view of a cable hanger according to alternative embodiments of the invention.

FIG. 6 is a top view of the cable hanger of FIG. 5.

FIG. 7 is a top view of a cable hanger according to additional embodiments of the invention.

FIG. 8 is a side view of the cable hanger of FIG. 7.

FIG. 9 is a partial top view of a cable hanger according to further embodiments of the invention with a smaller diameter cable in place.

FIG. 10 is a partial top view of the cable hanger of FIG. 9 with a larger diameter cable in place.

FIG. 11 is a partial top view of a cable hanger according to still further embodiments of the invention prior to securing of a cable.

FIG. 12 is a side view of the cable hanger of FIG. 11.

FIG. 13 is a top view of the cable hanger of FIG. 11 after securing of a cable.

FIG. 14 is a partial top view of the cable hanger of FIG. 3.

FIG. 15 is a partial top view of a cable hanger according to additional embodiments of the invention.

FIG. 16 is a perspective view of a cable hanger according to further embodiments of the invention.

FIG. 17 is a top view of the cable hanger of FIG. 16.

FIG. 18 is a perspective view of a cable hanger according to further embodiments of the invention.

FIG. 19 is a top view of the cable hanger of FIG. 18.

FIG. 20 is a perspective view of a portion of a cable hanger according to still further embodiments of the invention.

FIG. 21 is a top view of a portion of the cable hanger of FIG. 20.

DETAILED DESCRIPTION

The present invention is described with reference to the accompanying drawings, in which certain embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments that are pictured and described herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. It will also be appreciated that the embodiments dis-

4

closed herein can be combined in any way and/or combination to provide many additional embodiments.

Unless otherwise defined, all technical and scientific terms that are used in this disclosure have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. The terminology used in the below description is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used in this disclosure, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that when an element (e.g., a device, circuit, etc.) is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, there are no intervening elements present.

Referring now to the figures, a prior art cable hanger, designated broadly at 10, is shown in FIGS. 1 and 2. The hanger 10 includes curved arms 5 that extend from a flat base 6. Locking projections 7 extend from the free ends of the arms 5. As can be seen in FIGS. 1 and 2, the locking projections 7 are inserted into a reinforced hole 8 in a tower structure 4 to mount the hanger 10 thereon. The base 6 of the hanger 10 includes a reinforced hole 9 that can receive the projections of another hanger 10 to mount a second cable.

As can be best seen in FIG. 2, the arms 5 include arcuate sections 14 that together generally define a circle within which a cable can be grasped. Two cantilevered tabs 12 extend radially inwardly and toward the base 6 at one end of the arcuate sections 14, and two cantilevered tabs 16 extend radially inwardly and toward the base 6 from the opposite ends of the arcuate sections 14. The cantilevered tabs 12, 16 are deployed to deflect radially outwardly when the hanger 10 receives a cable for mounting; this deflection generates a radially inward force from each tab 12, 16 that grips the jacket of the cable.

As discussed above, fiber optic cables tend to be much denser than coaxial cables, and therefore generate a much greater load than coaxial cables of similar diameter. Also, fiber optic cables are currently offered in a larger variety of outer diameters. Accordingly, the hanger 10 may not be suitable for the mounting of some fiber optic cables.

A hanger that may address some of the issues above is illustrated in FIGS. 3 and 4 and designated broadly at 110. The hanger 110 has a base 106, curved arms 105 and locking projections 107 that are similar to those of the hanger 10 discussed above. However, rather than having only cantilevered tabs extending from the arms, the hanger 110 has cantilevered locating projections 112, 116 and straight gripping members 118. These are described in greater detail below.

The locating projections 112 are positioned near the ends of the arcuate sections 114 near the base 106. As can be seen in FIG. 4, each locating projection 112 extends away from its respective arm 105 at an angle that is generally tangent to the outer diameter of a cable captured within the arms 105. Similarly, the locating projections 116 are positioned near the ends of the arcuate sections 114 near the locking projections 107, and extend generally tangent to the outer diameter of a cable captured by the arms 105. Each of the gripping members 118 is fixed at both ends of a respective arcuate section 114 and extends as a straight beam to define a chord of the arcuate section 114.

When the hanger 110 is used to mount a cable, the arms 105 are spread to enable the cable to slip between the

5

locking projections **107** and into the space **S** between the arms **105**. The locating projections **112**, **116** can help to locate the cable within the space **S**. The outer surface of the jacket of the cable presses into and deflects the gripping members **118**; this deflection provides a gripping force on the jacket that can hold the cable in place.

The gripping force of the gripping members **118** can be considerably higher than that provided by the cantilevered tabs **12**, **16** of the prior hanger **10**. The force applied by a deflected cantilevered beam can be calculated as

$$N=(3DEI)/L^3 \quad (1)$$

wherein

N=the force normal to the beam;

D=the amount of deflection experienced by the beam;

E=elastic modulus of the material of the beam;

I=moment of inertia through the cross-section of the beam; and

L=length of the beam.

In contrast, the force applied by a deflected beam fixed at both ends is:

$$N=(192DEI)/L^3 \quad (2)$$

wherein N, D, E, I and L are as defined above in equation (1). Thus, for a beam of equal length and cross-section (such that L and I are the same in both equations), and formed of the same material (such that E is the same in both equations), the force generated by an equal deflection is 64 times greater (i.e., 192/3) by a beam fixed at both ends than by a cantilevered beam.

Accordingly, assuming that the deflection of the gripping members **118** is essentially the same as that of the tabs **12**, **16**, the gripping members **118** exert 64 times as much gripping force onto the cable jacket as the tabs **12**, **16**. This markedly increased gripping force can assist in the mounting of heavier cables, such as fiber optic cables.

This concept can be applied in different ways. For example, FIG. **14** is a partial top view of an arm **105** and gripping member **118** of the cable hanger **110**. As can be seen in FIG. **14**, the length of the gripping member **118** is less than that of the length of the arcuate section **A** of the arm **105** extending between the ends of the gripping member **118**. As such, if the arm **105** and gripping member **118** were stamped from a single sheet of metal (such as sheet steel), their different lengths should be accounted for. One technique for doing so is illustrated in FIG. **15**, wherein the gripping member **118'** is offset from the arm **105'** by two bridge segments **119**. The bridge segments **119** may be sized such that each bridge segment **119** has a length that is approximately half of the difference in length between the gripping member **118'** and the arcuate section **A**. Employing bridge members **119** of this size would render the combined bridge members **119** and gripping member **118'** approximately the same length as the arcuate section **A**, which would facilitate stamping the cable hanger **110** from a single sheet of metal. The mismatch in lengths between the gripping member **118** and the arcuate section **A** may also be addressed by including curvature (e.g., concave or convex) in the gripping member **118**.

Referring now to FIGS. **5** and **6**, another embodiment of a cable hanger, designated broadly at **210**, is shown therein. The hanger **210** has a base **206**, curved arms **205** and locking projections **207** that are similar to those of the hangers **10**, **110** discussed above. However, rather than having only cantilevered tabs extending from the arms, the hanger **210**

6

has serpentine locating projections **212**, **216** and serpentine gripping members **218**. These are described in greater detail below.

The locating projections **212** are positioned near the ends of the arcuate sections **214** near the base **206**. As can be seen in FIG. **5**, each locating projection **212** has a central portion **212a** that extends away from its respective arm **205** at an angle that is generally tangent to the outer diameter of a cable captured within the arms **205**. Similarly, the locating projections **216** are positioned near the ends of the arcuate sections **214** near the locking projections **207** and have coils **216a**, **216b** that extend generally tangent to the outer diameter of a cable captured by the arms **205**.

Each of the gripping members **218** is fixed at both ends of a respective arcuate section **214**. Each gripping member **218** includes three vertical runs **218a**, **218b**, **218c** connected by two horizontal runs **218d**, **218e**. The vertical run **218a** is attached to the arm **205** at its upper end via a bridge **218f**, and the vertical run **218c** is attached to the arm **205** at its lower end via a bridge **218g**. The vertical runs **218a**, **218b**, **218c**, the horizontal runs **218d**, **218e**, and the bridges **218f**, **218g** define generally a vertical plane that forms a chord within the arcuate section **214** of the arm **205**.

In the same manner described above for the hangers **10**, **110**, the hanger **210** is deployed by separating the arms **205** to permit insertion of a cable. The outer surface of the jacket of the cable presses into and deflects the gripping members **218**, which generates a gripping force on the jacket that can hold the cable in place.

Although the gripping members **218** are beams with fixed ends in the manner of gripping members **218** above, the gripping force generated by the gripping members **218** will be somewhat less than that of a straight beam of similar horizontal span due to the ability of the gripping members **218** to twist along the vertical runs **218a**, **218b**, **218c**. As such, a serpentine arrangement such as that shown herein can reduce the gripping force of a cable should a lower force be needed (for example, to enable the arms **205** to close sufficiently to insert the locking projections **207** into a mounting hole), and can be employed to "tune" the magnitude of the gripping force. Similarly, the serpentine arrangement of the locating projections **212**, **216** can reduce the force imparted by these structures to the cable.

Another embodiment of a cable hanger, designated broadly at **310**, is illustrated in FIGS. **7** and **8**. The hanger **310** has a base **306**, arms **305** and locking projections **307** that are similar to those of the hangers **10**, **110**, **210** discussed above; however, as can be seen in FIGS. **7** and **8**, the arms **305** are relatively straight and lack arcuate sections. Also, the hanger **310** lacks locating projections, and includes arcuate gripping members **318** that are fixed at one end near the base **306**. Each gripping member **318** is supported at its opposite end by a respective a brace **320** or other feature that extends inwardly from the end of the arm **305** near the locking projections **307**. The gripping members **318** include bent tips **318a** that engage the ends of the braces **320**.

As can be seen in FIG. **7**, the cable hanger **310** receives a cable between the arcuate surfaces of the gripping members **318**. As the gripping members **318** deflect to receive the cable, the tips **318a** engage the braces **320**. The presence of the braces **320** supporting the tips **318a** of the gripping members **318** provide support that can be approximated as a "pinned" joint (i.e., a hinge joint, wherein the member rotates about the joint but does not translate in any direction relative to the joint). The equation for calculating the force generated for a beam that is fixed at one end and pinned at the opposite end is approximately:

$$N=(6DEI)/L^3 \quad (3)$$

wherein N, D, E, I and L are as defined above in Equations (1) and (2). (The denominator of Equation 3 is not exactly L^3 , but is calculated with a lengthy equation that simplifies to approximately L^3 , so for simplicity L^3 is used herein). Thus, for a given length of beam and deflection, the normal force is approximately twice the magnitude exerted by a cantilevered beam.

Applying equation (3) to the gripping members **318** of the cable hanger **310**, the gripping members **318** should provide approximately twice the gripping force to a cable that cantilevered gripping members of similar length would provide.

Referring now to FIGS. **9** and **10**, another embodiment of a cable hanger, designated broadly at **410**, is shown therein. As can be seen in the partial view of FIGS. **9** and **10**, the hanger **410** has a base **406** and arms **405** (only one of which is shown in FIGS. **9** and **10**); the cable hanger **410** has locking projections on the arms **405** that are not shown in the figures. The cable hanger **410** includes gripping members **418** with arcuate sections **418a** and angled tips **418b** that are mounted as cantilevered beams in an undeflected state. When, as shown in FIG. **9**, a relatively small diameter cable **450** is mounted within the gripping members **418**, the deflection of the gripping members **418** is sufficiently small that the tips **418b** of the gripping members do not contact the arms **405**. As a result, the gripping force imparted to the cable **450** by the gripping members **418** can be calculated using Equation (1) above for a cantilevered beam. In contrast, if a relatively larger cable **460** is mounted within the gripping members **418**, the deflection of the gripping members **418** is sufficient that the tips **418b** of the gripping members **418** engage the arms **405** (see FIG. **10**). In this instance, the gripping force imparted to the cable **460** by the gripping members **418** can be approximately calculated using Equation (3) above for a fixed-pinned beam, which of course produces a larger gripping force than a cantilevered beam. (It is noted that there may be some sliding of the tip **418b** relative to the arm **405** as deflection increases, such that it is not a true "pinned" joint, but Equation (3) should still suffice for approximating the gripping force). Thus, the gripping members **418** of the cable hanger **410** can produce a higher gripping force for larger diameter cables, which presumably are heavier than smaller diameter cables.

Referring now to FIGS. **11-13**, a further embodiment of a cable hanger, designated broadly at **510**, is shown therein. The cable hanger **510** includes a base **506**, arms **505** and locking projections **507** as discussed above. However, the cable hanger **510** includes two differently configured gripping members **518**, **519**. The gripping member **518** includes an arcuate section **518a** and a radially-inwardly extending locking tab **518b** with a hook **518c**. The gripping member **519** has a similar arcuate section **519a**, but has a locking panel **519b** with horizontal slots **519c** (shown in the inset of FIG. **11**).

To mount a cable with the cable hanger **510**, the locking projections **507** are spread to enable insertion of the cable **550** between the gripping members **518**, **519**. The free ends of the gripping members **518**, **519** are then brought together, with the locking tab **518c** of the gripping member **518** being inserted into an appropriate slot **519c** of the gripping member **519** to grip the cable **550**. The locking projections **507** are then inserted into a mounting hole of either a mounting structure or another cable hanger in the manner described

above. The multiplicity of slots **519c** can provide the cable hanger **510** with the flexibility to mount a variety of cable sizes.

Those of skill in this art will appreciate that locking features other than the locking tab **518** and the slotted locking panel **519b** may be employed with cable hanger according to embodiments of the invention.

Referring now to FIGS. **16** and **17**, another embodiment of a cable hanger, designated broadly at **610**, is shown therein. The cable hanger **610** is somewhat similar to the cable hanger **110**, inasmuch as it has a base **606**, curved arms **605** and locking projections **607** that resemble those of the hanger **110** discussed above. The cable hanger **610** also has flex members **618** that define chords across the arcuate sections **614** of the arms **605**. However, as can be seen in FIG. **17**, cantilevered gripping members **612**, **616** extend from the flex members **618** and into the cable-gripping space S within the arms **605**. It can also be seen in FIG. **16** that the flex members **618** are tripartite, with two vertically offset horizontal runs **618a**, **618c** merging with the arcuate sections **614** of the arms **605** and a vertical run **618b** extending between the horizontal runs **618a**, **618c**. The gripping members **612**, **616** extend from opposite sides of the vertical run **618b** and are vertically offset from each other.

In use, the cable hanger **610** is employed in the same manner as the cable hanger **110**; a cable is inserted into the space S between the arms **605**, which are then closed around the cable as the locking projections **607** are inserted into a mounting hole. The cantilevered gripping members **612**, **616** can help to grip and to center the cable within the space S. The presence of the flex members **618**, which are fixed end beams like the gripping members **118** of the cable hanger **110**, can provide additional gripping force in the manner described above in connection with the cable hanger **110**.

Referring now to FIGS. **18** and **19**, another embodiment of a cable hanger, designated broadly at **710**, is shown therein. The cable hanger **710** is somewhat similar to the cable hanger **610** in that it includes a base **706**, arms **705** and locking projections **707**, as well as having tripartite flex members **718** with vertically offset cantilevered gripping members **712**, **716**. However, the arms **705** of the cable hanger **710** are not smoothly arcuate, but instead include straight sections **705a**, **705b** and a curved section **705c**. Also, the flex members **718** are angled, with the horizontal run **718a** emerging from the straight section **705a** of the arm **705**, and the horizontal run **718c** being angled relative to the vertical run **718b** to meet the straight section **705b**. The straight sections **705a**, **705b** include raised ribs **705d**, **705e** to provide additional stiffness to the arms **705**.

The cable hanger **710** is employed in the same manner as the cable hanger **610**, with a cable being inserted into the space S between the arms **705** and being gripped by the gripping members **712**, **716**. Notably, the shapes of the straight sections **705a**, **705b** of the arms **705** and the horizontal runs **718a**, **718c** of the flex members **718** are selected so that a similar length of material is used for each (i.e., the combined lengths of the straight sections **705a**, **705b** are approximately the same as the combined lengths of the horizontal runs **718a**, **718c**) to facilitate stamping of the material and to maintain strength of the stamped material.

Referring now to FIGS. **20** and **21**, another embodiment of a cable hanger, designated broadly at **810**, is illustrated therein. The cable hanger **810** is similar to the cable hanger **610** of FIGS. **16** and **17** described above. The cable hanger **810** has a base **806**, curved arms **805** and locking projections **807** that resemble those of the hanger **610** discussed above. The cable hanger **810** also has tripartite flex members **818**

(only one of which is shown in FIGS. 20 and 21) that define chords across the arcuate sections 814 of the arms 805, with cantilevered gripping members 812, 816 extending from the flex members 818 and into the cable-gripping space S within the arms 805. However, in this embodiment each of the gripping members 812, 816 includes two longitudinal gripping flanges 822 at its free end. The gripping flanges 822 are located on each side of an open-ended slot 820 and extend with flat edges 824 into the space S between the arms 805.

In use, the cable hanger 810 is employed in the same manner as the cable hanger 610; a cable is inserted into the space S between the arms 805, which are then closed around the cable as the locking projections 807 are inserted into a mounting hole. The gripping flanges 822 improve the grip of the cable hanger 810 on the cable.

During installation, the flat edges 824 of the gripping flanges 822 can slide over the cable jacket relatively easily, as the sliding action occurs along the length of the flat edges 824. This configuration can facilitate installation compared to prior hangers that have included individual barbs rather than flanges, as the barbs tend to “hang up” on the cable jacket as the hanger is slid into place. Once in position, the gripping flanges 822 can provide superior gripping force to hangers that employ a coined edge as a gripping feature. Moreover, the presence of the gripping flanges 822 increases the moment of inertia of the gripping members 812, 816, which stiffens the gripping members 812, 816 and thereby increases the gripping force.

Those of skill in this art will appreciate that other configurations of gripping flanges may be employed. For example, in some embodiments only one of the gripping members 812, 816 may include a gripping flange, or only one gripping flange may be included on each gripping member. The length and height of the gripping flanges may vary. Other variations may also be suitable.

Those skilled in this art will appreciate that the cable hangers discussed above are typically formed of a metallic material, such as steel, and may be formed as a unitary member (often from a flat blank stamped from sheet steel and bent into a desired shape).

Also, it will be apparent to those of skill in this art that the cable hangers 110, 210, 310, 410, 510, 610, 710, 810 can be arranged in a “stacked” relationship by inserting the locking projections of one cable hanger into the mounting hole in the base of a second cable hanger in the manner described above with respect to cable hanger 10. The second cable hanger may be identical to or different from the first cable hanger as needed for hanging the cable in question.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments

without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

What is claimed is:

1. A method of gripping a cable with a cable hanger, comprising:

(a) providing a cable hanger comprising:

a base panel having opposed ends;

a pair of arms, each of the arms attached to a respective end of the base panel and having a free end, each of the arms including a cantilevered feature;

a pair of locking projections, each of the locking projections attached to a respective free end of the arms, wherein the locking projections are configured to be inserted into an aperture of a supporting structure; and a pair of gripping members, each gripping member having opposed ends, wherein one of the ends is fixed to a respective arm or to the base panel, and wherein the other of the ends is a free end positioned to engage a respective cantilevered feature;

(b) inserting a cable between the gripping members, the gripping members deflecting to receive and grasp the cable;

(c) forcing the locking projections toward each other;

(d) inserting the locking projections into a mounting hole of a mounting structure, wherein the mounting hole has a nominal diameter of $\frac{3}{4}$ inch;

wherein, when a cable of sufficient diameter is gripped by the gripping members, each of the gripping members deflects to engage the respective cantilevered feature.

2. The method defined in claim 1, wherein each of the cantilevered features is a brace extending from the arm.

3. The method defined in claim 1, wherein the fixed end of each gripping member is fixed to a respective arm.

4. The method defined in claim 1, wherein each of the gripping members engages the respective cantilevered feature within a periphery of the cable hanger.

5. The method defined in claim 1, wherein the cable hanger is formed as a unitary member.

6. The method defined in claim 1, wherein the base panel has a mounting hole.

7. The method defined in claim 6, wherein the mounting hole has a nominal diameter of $\frac{3}{4}$ inch.

8. The method defined in claim 1, wherein each of the arms includes a first segment that extends generally perpendicularly from the base panel and a second segment that extends generally perpendicularly from an end of the first segment to merge with a respective one of the locking projections.

* * * * *