

US012396064B2

(12) **United States Patent**  
**Zhilin et al.**

(10) **Patent No.:** **US 12,396,064 B2**  
(45) **Date of Patent:** **Aug. 19, 2025**

(54) **UNIVERSAL MULTI-MODE UNDERWATER SOFTWARE DEFINED MODEM**

(71) Applicant: **Technology Innovation Institute—Sole Proprietorship LLC, Masdar (AE)**

(72) Inventors: **Igor V. Zhilin, Abu Dhabi (AE); Osama M. Bushnaq, Abu Dhabi (AE); Giulia De Masi, Abu Dhabi (AE); Enrico Natalizio, Dubai (AE); Ian F. Akyildiz, Atlanta, GA (US); Najwa Aaraj, Abu Dhabi (AE)**

(73) Assignee: **Technology Innovation Institute—Sole Proprietorship LLC, Masdar (AE)**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 336 days.

(21) Appl. No.: **17/931,816**

(22) Filed: **Sep. 13, 2022**

(65) **Prior Publication Data**  
US 2024/0090080 A1 Mar. 14, 2024

(51) **Int. Cl.**  
**H04W 88/06** (2009.01)  
**H04M 11/06** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **H04W 88/06** (2013.01); **H04M 11/06** (2013.01)

(58) **Field of Classification Search**  
CPC ..... H04M 11/06; H04M 11/066; H04W 88/06  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,853,742	B1	12/2017	Radosevic et al.
2006/0052124	A1	3/2006	Pottenger et al.
2008/0242239	A1*	10/2008	Wilson ..... H04B 1/52 455/83
2016/0262113	A1	9/2016	Diamond et al.
2018/0145771	A1*	5/2018	Melodia ..... H04B 11/00

FOREIGN PATENT DOCUMENTS

EP	1978645	A2	10/2008
WO	2018075984	A1	4/2018

OTHER PUBLICATIONS

I. Zhilin, O. Bushnaq, G. D. Masi, E. Natalizio and I. F. Akyildiz, “A Universal Multimode (Acoustic, Magnetic Induction, Optical, RF) Software Defined radio Architecture for Underwater Communication,” WUWNet’21, Nov. 23-26, 2021, Shenzhen, Gu (Year: 2021).\*


(Continued)

*Primary Examiner* — Nader Bolourchi  
(74) *Attorney, Agent, or Firm* — DLA PIPER LLP (US)

(57) **ABSTRACT**

A software-defined modem includes a multi-mode head and a baseband unit. The multi-mode head includes a plurality of mode frontends including, but not limited to acoustic, magnetic induction, radio frequency and optical. Each mode frontend of the plurality of mode frontends is configured to transmit and/or receive communications according to a preset communication mode. The baseband unit is configured to control operation of the multi-mode head. The multi-mode head is configured to simultaneously use one or more communication modes.

**20 Claims, 10 Drawing Sheets**



(56)

**References Cited**

## OTHER PUBLICATIONS

I. V. Zhilin, O. M. Bushnaq, G. D. Masi, E. Natalizio and I. F. Akyildiz, "A Universal Multimode (Acoustic, Magnetic Induction, Optical, RF) Software Defined Modem Architecture for Underwater Communication," in IEEE Transactions on Wireless Communications, vol. 22, No. 12, pp. 9105-9116, Dec. 2023 (Year: 2023).\*

Demirors E., et al., "Design of A Software-defined Underwater Acoustic Modem with Real-time Physical Layer Adaptation Capabilities," In: Proceedings of the 9th International Conference on Underwater Networks Systems, Association for Computing Machinery, Nov. 12, 2014, 8 pages.

International Search Report and Written Opinion for Application No. PCT/IB2023/059092, mailed on Nov. 16, 2023, 11 pages.

Li Y., et al., "The Design and Experiment of a Software Defined Acoustic Modern for Underwater Sensor Network," Institute of Acoustics, Chinese Academy of Sciences, May 24-27, 2010, 4 pages.

Zhilin, et al., "A Universal Multimode (Acoustic, Magnetic Induction, Optical, RF) Software Defined Radio Architecture for Underwater Communication," The 15th International Conference on Underwater Networks & Systems, Nov. 2021, 4 pages.

Stojanovic, "On the relationship between capacity and distance in an underwater acoustic communication channel," Proceedings of the 1st ACM International Workshop on Underwater Networks, 2006, 10 pages.

Volkov, et al., "An Arctic-type shallow-water acoustic waveguide as an information transmission channel for underwater communications," Acoustical Physics 64.6, 2018, pp. 692-697.

Volkov, et al., "Underwater Acoustic Communications Using Vertical Receiver Arrays in Ice-Covered Shallow-Water Areas," Oceanology 61.4, 2021, pp. 569-580.

Tu, et al., "Cooperative MIMO-OFDM communications: Receiver design for Doppler-distorted underwater acoustic channels," 2010 Conference Record of the Forty Fourth Asilomar Conference on Signals, Systems and Computers, 2010, 5 pages.

Sklivanitis, et al., "Distributed mimo underwater systems: Receiver design and software-defined testbed implementation," 2016 IEEE Global Communications Conference (GLOBECOM), 2016, 7 pages.

Morel, et al., "Optical properties of the "clearest" natural waters," The American Society of Limnology and oceanography 52.1, 2007, pp. 217-229.

Sonardyne, "Bluecomm 200 UV—optical communications system," 2021.

Hydromea, "LUMA—high-speed, long range wireless optical modem," 2021.

Wang, et al., "100 m/500 Mbps underwater optical wireless communication using an NRZ-OOK modulated 520 nm laser diode," Optical Society of America 27.9, Apr. 2019, 11 pages.

Chen, et al., "26 m/5.5 Gbps air-water optical wireless communication based on an OFDM-modulated 520-nm laser diode," Optical Society of America 25.13, Jun. 2017, 6 pages.

Domingo, "Magnetic induction for underwater wireless communication networks," IEEE transactions on antennas and propagation 60.6, 2012, pp. 2929-2939.

Akyildiz, et al., "SoftWater: Software-defined networking for next-generation underwater communication systems," Ad Hoc Networks 46, 2016, 11 pages.

Campagnaro, et al., "Wireless remote control for underwater vehicles," Journal of Marine Science and Engineering 8.10, Aug. 2020, 32 pages.

Campagnaro, et al., "Multimodal underwater networks: Recent advances and a look ahead," Association for Computing Machinery, Proceedings of the International Conference on Underwater Networks & Systems, Nov. 2017, 8 pages.

Vasilescu, et al., "Data collection, storage, and retrieval with an underwater sensor network," Association for Computing Machinery, Proceedings of the 3rd international conference on Embedded networked sensor systems, 2005, pp. 154-165.

Signori, et al., "Data gathering from a multimodal dense underwater acoustic sensor network deployed in shallow fresh water scenarios," Journal of Sensor and Actuator Networks 8.4, Sep. 2019, 28 pages.

Basagni, et al., "Finding Marlin: Exploiting multi-modal communications for reliable and low-latency underwater networking," IEEE INFOCOM 2017—IEEE Conference on Computer Communications, 2017, 9 pages.

Diamant, et al., "Fair and throughput-optimal routing in multimodal underwater networks," IEEE Transactions on Wireless Communications 17.3, Nov. 2016, 30 pages.

Hu, et al., "Murao: A multi-level routing protocol for acoustic-optical hybrid underwater wireless sensor networks," 2012 9th Annual IEEE Communications Society Conference on Sensor, Mesh and Ad Hoc Communications and Networks (SECON), 2012, pp. 218-226.

Li, et al., "Underwater cooperative MIMO communications using hybrid acoustic and magnetic induction technique," Computer Networks 173, Oct. 2019, 24 pages.

Akyildiz, et al., "Realizing underwater communication through magnetic induction," IEEE Communications Magazine 53.11, Nov. 2015, pp. 42-48.

Campagnaro, et al., "Implementation of a multi-modal acoustic-optical underwater network protocol stack," Oceans 2016—Shanghai, IEEE, 2016, 6 pages.

Johnson, "The underwater optical channel," Dept. Eng., Univ. Warwick, Coventry, UK, Tech. Rep, Feb. 2012, 18 pages.

Kaushal, et al., "Underwater optical wireless communication," IEEE access 4, 2016, pp. 1518-1547.

Office Action and Search Report for United Arab Emirates Patent Application No. P6002300/2023, dated May 14, 2025, 10 pages.

\* cited by examiner



100




FIG. 1




FIG. 2




FIG. 3






FIG. 5




FIG. 6A






FIG. 6B

700




FIG. 7




800

FIG. 8



## 1

UNIVERSAL MULTI-MODE UNDERWATER  
SOFTWARE DEFINED MODEM

## FIELD OF DISCLOSURE

The present disclosure generally relates to a universal multi-mode underwater software defined modem and a method for operating the same.

## BACKGROUND

Underwater acoustic communication is the most popular physical layer technology due to its reliable and long range communication, which can exceed several kilometers. However, acoustic communication has high propagation delays due to the low speed of sound in water. Furthermore, long-range acoustic propagation is efficient over a limited spectral bandwidth, thus limiting the channel capacity even when advanced technologies, such as multiple input multiple output (MIMO) are used. Wide bandwidth acoustics may be capable of achieving data rates of 1 Mbps for distances up to 100 m. This makes acoustic communication the preferred mechanism in underwater applications compared to other forms of communication, such as magnetic induction and optical communication in terms of capacity. However, propagation delay in acoustic communication may still be limited by the speed of sound.

Alternatively, optical communication has high propagation speed

$$\left( \text{e.g., } 225 \frac{\text{m}}{\mu\text{s}} \right)$$

and ultimately wide bandwidth (e.g., hundreds of THz). However, optical waves may suffer from high absorption and scattering depending on the water characteristics, which may limit achievable transmission range to  $\approx 500$  m in the most transparent ocean waters and to  $\approx 10$  m and below in turbulent water. Practical implementations of optical communication systems have achieved up to 10 Mbps at 150 m using wide-beam LED modems. Higher data rates, such as 500 Mbps at 100 m and 5.5 Gbps at 26 m may be achieved using collimated laser beam in a lab environment.

Radio frequency (RF) communication is another transmission mode that can maintain a short-range signal propagation and can provide high data rates. Since electromagnetic waves in water may be absorbed at distance of order of the wavelength, electromagnetic waves may not be used at close contact, or at very low frequencies, which may lead to giant antenna sizes and very low data rates. Finally, magnetic induction may provide reliable short-range communications depending on water conductivity with high propagation speeds at  $\approx 33$  m/ $\mu\text{s}$ . As those skilled in the art understand, one transmission mode can be preferred over the others, depending on the transmission requirements, water types/characteristics, and/or transmission range.

Conventional approaches to the above limitations involve multi-mode underwater communication systems with multiple frontends to meet the different communication quality of service requirements. Such conventional approaches simply use dual separate modems with acoustic communication to maintain low-bandwidth control signaling, and optical or

## 2

magnetic induction communication for high-speed data off-load, when the nodes are close to each other.

## SUMMARY

5

In some embodiments, a software-defined modem is disclosed herein. The software-defined modem includes a multi-mode head and a baseband unit. The multi-mode head includes a plurality of mode frontends. Each mode frontend of the plurality of mode frontends is configured to transmit and receive communications according to a preset communication mode. The baseband unit is configured to control operation of the multi-mode head. The multi-mode head is configured to simultaneously use two or more communication modes.

In some embodiments, a software-defined modem is disclosed herein. The software-defined modem includes a multi-mode head and a baseband unit. The multi-mode head includes a first mode frontend and a second mode frontend. The first mode frontend is configured to transmit and receive communications according to a first communication mode. The second mode frontend is configured to transmit and receive communications according to a second communication mode. The baseband unit is configured to control operation of the multi-mode head. The multi-mode head is configured to simultaneously use the first communication mode and the second communication mode. The baseband unit is configured to select one of the first communication mode or the second communication mode for communicating with a node by probing the first communication mode and the second communication mode and establishing a first communication link with the node via the first communication mode and a second communication link with the node via the second communication mode, receiving a first set of transmissions via the first communication mode and a second set of transmissions via the second communication mode, determining that the first communication mode results in a lower hardware resource load on the software-defined modem, and, responsive to the determining, sending data to the node using the first communication mode.

In some embodiments, a method of operating a software-defined modem configured to simultaneously use two or more communication modes is disclosed herein. The method includes probing a first communication mode of the software-defined modem and a second communication mode of the software-defined modem. The method further includes establishing a first communication link with a target node via the first communication mode and a second communication link with the target node via the second communication mode. The method further includes receiving a first set of transmissions via the first communication mode and a second set of transmissions via the second communication mode. The method further includes determining that the first communication mode results in a lower hardware resource load on the software-defined modem. The method further includes, responsive to the determining, sending data to the target node using the first communication mode.

## BRIEF DESCRIPTION OF THE DRAWINGS

60

So that the manner in which the above recited features of the present disclosure can be understood in detail, a more particular description of the disclosure, briefly summarized above, may be had by reference to embodiments, some of which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrated only typical embodiments of this disclosure and are therefore not

65



## 3

to be considered limiting of its scope, for the disclosure may admit to other equally effective embodiments.

FIG. 1 is a block diagram illustrating an architecture of a universal multi-mode software defined modem, according to example embodiments.

FIG. 2 is a block diagram illustrating an exemplary architecture of a radio frequency mode frontend, according to example embodiments.

FIG. 3 is a block diagram illustrating an exemplary architecture of an acoustics mode frontend, according to example embodiments.

FIG. 4 is a block diagram illustrating an exemplary architecture of an optical mode frontend, according to example embodiments.

FIG. 5 is a block diagram illustrating an exemplary architecture of a magnetic induction mode frontend, according to example embodiments.

FIG. 6A is a block diagram illustrating an exemplary architecture of a wired mode frontend, according to example embodiments.

FIG. 6B is a block diagram illustrating an exemplary architecture of a wired mode frontend, according to example embodiments.

FIG. 7 is a block diagram illustrating an exemplary computing environment, according to example embodiments.

FIG. 8 is a flow diagram illustrating a method of operating a universal multi-mode software defined modem, according to example embodiments.

FIG. 9A is a block diagram illustrating a computing device, according to example embodiments.

FIG. 9B is a block diagram illustrating a computing device, according to example embodiments.

To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures. It is contemplated that elements disclosed in one embodiment may be beneficially utilized on other embodiments without specific recitation.

## DETAILED DESCRIPTION

Conventional approaches to multi-mode underwater communication systems may employ multiple frontends to meet the different levels of quality of service required for the communication. Such conventional approaches simply use separate modems with acoustic communication to maintain low-bandwidth control signaling, and optical or magnetic induction communication for high-speed data offload, when the nodes are close to each other. While these conventional approaches may operate over several modes simultaneously by utilizing several independent transceivers, such approaches typically suffer from several limitations. First, the transceiver separation may add internal routing delays. Second, the processing may be limited to standard packet reception and transmission. For example, amplify-and-forward techniques cannot be implemented without low-level interconnection between the modes that will allow to pass non-processed signal from one mode to another. Third, inter-mode co-operative operation is often difficult, since it requires precise synchronization.

One or more techniques disclosed herein provide a universal software-defined modem architecture that integrates multi-mode device operation. Realization of the universal software-defined modem architecture can significantly improve system performance by allowing simplified communication between different communication modes,

## 4

improve synchronization accuracy, and reduce modem cost and size. The universal software-defined modem architecture disclosed herein may enable joint operation of multiple modes at the same time. For example, the universal software-defined modem architecture may include a physical layer that may combine functions of the separate modes, as well as synchronization and signal processing. In this manner, the universal software-defined modem architecture may be able to support any physical frontend or several frontends simultaneously.

In some embodiments, such universal software-defined modem may be utilized in one or more underwater communications environments. For example, the universal software-defined modem described herein may be used in underwater applications to wirelessly transmit data to surface nodes and sub-surface nodes. For example, using the universal software-defined modem, a surface user may communicate with a sub-surface user (e.g., a user in an underwater vehicle).

FIG. 1 is a block diagram illustrating an architecture of a universal multi-mode software defined modem ("UniSDM device") 100, according to example embodiments. As shown, UniSDM device 100 may include a baseband unit 102 and a multi-mode head 104. In some embodiments, UniSDM device 100 may include more than one multi-mode head 104. However, for ease of discussion and illustration, only one multi-mode head 104 is shown. In some embodiments, baseband unit 102 and multi-mode head 104 may operate as a single unit. In some embodiments, baseband unit 102 and multi-mode head 104 may be distributed and connected, similar to cloud radio access networks of modern terrestrial mobile networks. In some embodiments, the connection interface may provide functionality similar to the Common Public Radio Interface (CPRI™), but may account for network modality, i.e., provide access to various physical modes with different properties.

Baseband unit 102 may be configured to control UniSDM device 100. For example, as shown, baseband unit 102 may include a controller 106 and a digital signal processor 108. Controller 106 may be configured to interface with a user. For example, as discussed above in conjunction with FIG. 1, a user or user device may communicate with UniSDM device 100. Controller 106 may act as the interface between the user or user device (e.g., client device 702 in FIG. 7) and UniSDM device 100. In some embodiments, controller 106 may be configured to control one or more subsystems of UniSDM device 100. For example, controller 106 can load different modules (e.g., PHY layer functions (e.g., modulation and coding schemes), higher-layer communication protocols (e.g., medium access control, routing, transport layer), network management and control solutions) to digital signal processor 108 or digital signal processor 114, activate or deactivate these modules to decrease the power consumption. The controller 106 can decide which modules to load based on scenarios.

Digital signal processor 108 may be configured to implement one or more processes or algorithms of UniSDM device 100. For example, digital signal processor 108 may be configured to implement one or more protocols from high medium access control (high-MAC) to high physical layer (high-PHY). For example, DSP 108 may implement some existing standardized protocols for acoustic communication, e.g. JANUS by NATO Europe, or terrestrial standards, e.g. 4G (LTE; Long-Term Evolution) and 5G, as well as other standards such as Wi-Fi, Bluetooth, ZigBee, etc. In operation, data may flow from controller 106 through digital signal processor 108 and to multi-mode head 104. Similarly,



## 5

data may flow in the opposite direction, i.e., from multi-mode head **104** to digital signal processor **108** and to controller **106**.

Multi-mode head **104** may be configured to provide baseband unit **102** with access to various wired or wireless communication modes of UniSDM device **100**. As shown, baseband unit **102** may include a signals unit **110** and two or more mode frontends **112**.

Signals unit **110** may be configured to communicate with controller **106**. For example, signals unit **110** may be configured to forward control signals from controller **106** to mode frontends **112**. Signals unit **110** may include a digital signal processor **114**, conversion module **115**, a communications module **116**, and a synchronization and timing module **118**. Each of digital signal processor **114**, conversion module **115**, communications module **116**, and synchronization and timing module **118** may be comprised of one or more software modules and/or one or more hardware modules. The one or more software modules are collections of code or instructions stored on a media (e.g., memory) that represent a series of machine instructions (e.g., program code) that implements one or more algorithmic steps. Such machine instructions may be the actual computer code the processor interprets to implement the instructions or, alternatively, may be a higher level of coding of the instructions that are interpreted to obtain the actual computer code. The one or more software modules may also include one or more hardware components. One or more aspects of an example algorithm may be performed by the hardware components (e.g., circuitry) itself, rather than as a result of the instructions.

Digital signal processor **114** may be configured to perform one or more digital signal operations. For example, digital signal processor **114** may be configured to filter the digital signal provided by baseband unit **102**, may execute algorithms for Peak-to-Average Power Ratio reduction and gain control as well as may perform frequency conversion.

Conversion module **115** may be configured to perform an analog-to-digital and/or a digital-to-analog conversion. In some embodiments, conversion module **115** may include a digital-to-analog converter (e.g., DAC **150**) configured to convert an electrical signal to an analog signal before the signal is transmitted through a selected mode frontend **112**. In some embodiments, conversion module **115** may include an analog-to-digital converter (e.g., ADC **152**) configured to convert a received analog signal to a digital signal before the digital signal is processed by signals unit **110** and baseband unit **102**.

Communications module **116** may be configured to generate and communicate control signals. For example, along with control signals generated by baseband unit **102**, communications module **116** may also be configured to generate and communicate control signals at signals unit **110**. In some embodiments, communications module **116** may generate control signals that may include information on the selected mode frontend **112**.

Synchronization and timing module **118** may be configured to manage modulation and coding schemes that may use more than one mode frontend **112**, including MIMO and multi-mode cooperative MIMO. In some embodiments, synchronization and timing module **118** may be representative of high-precision clocking circuitry configured to provide reference signals for mode frontends **112** when needed. In some embodiments, synchronization and timing module **118** may exchange synchronization signals with baseband unit **102**. In some embodiments, synchronization and timing module **118** may exchange synchronization signals with

## 6

external devices, such as external Global Navigation Satellite Systems (GNSS) receivers.

Mode frontends **112** may be configured to transmit and receive communications according to a preset communication mode. For example, as shown, mode frontends **112** may include a first mode frontend **120a** and a second mode frontend **120b**. Generally, mode frontends **112** may include *n* mode frontends (e.g., mode frontend **120n**). Mode frontend **120a** may be configured to transmit and receive communications according to a first communication mode. Exemplary first communication modes may include, but are not limited to, radio frequency communication, magnetic induction communication, acoustic communication, optical communication, and wired communication. Mode frontend **120b** may be configured to transmit and receive communications according to a second communication mode. Exemplary second communication modes may include, but are not limited to, radio frequency communication, magnetic induction communication, acoustic communication, optical communication, and wired communication. As those skilled in the art understand, although only two mode frontends **120a**, **120b** are illustrated, multi-mode head **104** may include more than two mode frontends. By providing multiple mode frontends **112**, UniSDM device **100** may support multi-mode operation, i.e., more than one type of communication mode, with their specifications.

In some embodiments, multiple mode frontends **112** may allow UniSDM device **100** to support MIMO operations. Such MIMO operations can be implemented in a variety of ways. In some embodiments, mode frontends **112** may include multiple receiver and/or transmitter channels. For example, a given mode frontend **112** can provide four receiver/transmitter channels. In some embodiments, UniSDM device **100** may include several identical frontends **112**. For example, UniSDM device **100** may include four identical 1-channel optical mode frontends. The structure of UniSDM device **100** may allow for cooperation and synchronization between multiple modes, thus it is possible to use several mode frontends together to provide MIMO operations. In some embodiments, the two foregoing approaches may be used together. For example, a UniSDM device **100** may include two mode frontends, each having four channels, thus providing 8-channel operation.

Mode frontends **112** may be configured to provide three main functions: frequency up/down conversion, power level control, and signal conversions.

In some embodiments, for high frequencies (e.g., RF and beyond), the baseband signal generated by signals unit **110** must be converted to actual radio frequency. The electrical-optical conversion may be viewed as a variant of frequency conversion. For example, a transmission at a 400 nm wavelength is essentially a transmission at 750 THz carrier frequency.

In some embodiments, the electrical interface between signals unit **110** and mode frontends **112** may use standardized signal levels for the interconnection. In some embodiments, signals' power may be adjusted before being converted to another medium for transmission. Conversely, the received signals' powers may be adjusted to standardized levels before being processed at signals unit **110** and baseband unit **102**. In order to match the signal power levels, the interface between signals unit **110** and mode frontends **112** may carry information on the required transmission signal power and average received signal power.

Mode frontends **112** may be configured to convert between baseband electric signals and signals in actual physical modes (e.g., RF, magnetic induction, optical sig-



nals, wired signals, etc.). Details of signal conversion may be found below in conjunction with FIGS. 2-5.

In some embodiments, UniSDM device **100** may support multiple operation modes with one or more communication technologies per mode. For example, RF mode could implement 5G technology for broadband data connectivity or long range (LoRa®) technology for low-rate data transmission. In another example, an acoustic mode can implement various communication protocols, e.g., JANUS or proprietary protocols. Depending on the required communication quality of service, and the measured channel state information for all supported modes and bands within modes, one or more nodes may be selected to conduct transmission. Due to the software-defined-modem nature of UniSDM device **100**, the configuration can be remotely updated. Such functionality allows for UniSDM device **100** to support future technologies, including MIMO.

Since each technology operation may require various resources (e.g., memory for storage, Digital Signal Processing (DSP) resource for implementation, power for power activation), controller **106** may implement one or more mode selection algorithms (discussed below) that may take the resources' availability into account.

In some embodiments, UniSDM device **100** may be configurable in various states. Exemplary states may include, but are not limited to, active communication, standby (e.g., active reception mode), sleep (e.g., requiring external request to power-up), and hibernated (e.g., not loaded to DSP and needing additional time, and possibly rebooting, for enabling).

In some embodiments, UniSDM device **100** may be configured to establish a communication with another node. To establish a connection, UniSDM device **100** may be configured to decide which mode or modes it is going to use. To make that determination, controller **106** may initiate a channel probing process in which controller **106** may probe the available modes and establish a link with the other node. Once one or more links between UniSDM device **100** and the node is established, controller **106** may collect the links' channel station information to select one of the modes to perform the data transmission based on a given criteria.

In some embodiments, to probe the modes, UniSDM device **100** may send probing packets at maximum available power. When another node receives such packet, it may reply to it. During this two-way communication, each node may measure the received power and response delay, and thus obtain information about the propagation delay and the path loss. In some embodiments, the modes' probing may be done sequentially, starting from the mode that may provide the lowest delay. Such an approach may reduce the required transmission time and may minimize interference. For example, if two nodes can establish an optical mode link, they can use the optical mode link for all types of communication, both control and data. If, for example, the optical link is not available, the nodes should probe a magnetic induction mode. If, for example, neither optical nor magnetic probing succeeded, the nodes should switch to acoustic, which may provide the longest range but at the lowest speed.

In some embodiments, controller **106** may select the mode that may result in the lowest hardware load according to one or more metrics. In some embodiments, controller **106** may select the mode based on signal-to-noise ratio (SNR) threshold with higher-speed mode priority. In some embodiments, controller **106** may select the mode based on energy efficiency per distance (e.g., J/bit/m). Such selection may reduce the overall energy used by UniSDM device **100**.

In some embodiments, controller **106** may select the mode based on transmit time for latency minimization and throughput maximization considering non uniform density. In some embodiments, controller **106** may select the mode based on the energy efficiency of the current node (e.g., J/bit). In some embodiments, controller **106** may select the mode based on other performance metrics such as transmit time, energy used, or the amount of the medium occupied by the transmission. In some embodiments, controller **106** may select the mode based on transmit time multiplied by the number of neighbors capable of hearing the communication for per-volume throughput maximization considering non-uniform node density.

Such mode switching for a given task stands in contrast to traditional engineering approaches that utilize separate modes for separate tasks, i.e., acoustic modem for remote control at any distance and optical model for data offload at short ranges. The present functionality provides an improvement over such systems by anticipating the medium (e.g., the water) becoming much more crowded with underwater sensors, autonomous underwater vehicles, remotely operated vehicles, and other underwater Internet-of-Things devices becoming more widespread, and accounting for that change. For example, by allowing for the automatic switching between modes (e.g., from a long-range mode to a short-range mode), UniSDM device **100** can mitigate any interference problems.

FIG. 2 is a block diagram illustrating an exemplary architecture of a radio frequency mode frontend **200**, according to example embodiments. In some embodiments, radio frequency mode frontend **200** may be representative of a mode frontend that may be used in UniSDM device **100**. For example, radio frequency mode frontend **200** may be representative of mode frontend **112** discussed above in conjunction with FIG. 1.

As shown, radio frequency mode frontend **200** may include a transmitter **202**, a receiver **204**, a transmitter/receiver switch **206**, and an antenna **208**. Although not shown, in some embodiments, frequency mode frontend **200** may further include one or more local oscillators, mixers, filters, and amplifiers. In some embodiments, transmitter **202** may be a power amplification transmitter (e.g., Tx PA). For example, transmitter **202** may receive signal **201** from signals unit **110**, amplify signal **201**, and provide signal **201** to switch **206** for transmission via antenna **208**. In some embodiments, receiver **204** may be a low noise amplifier receiver (e.g., Rx LNA). For example, receiver **204** may receive an incoming signal **203**, via antenna **208**, amplify incoming signal **203**, and provide amplified incoming signal **203** to signals unit **110** for processing.

Switch **206** may be configured to toggle between a transmitter mode and a receiver mode. Accordingly, in some embodiments, switch **206** may toggle to transmitter mode to transmit an amplified signal provided by transmitter **202** via antenna **208**; in some embodiments, switch **206** may toggle to receiver mode to receive an incoming signal via antenna **208** and subsequently provide the incoming signal to receiver **204**.

As shown, in some embodiments, radio frequency mode frontend **200** may receive synchronization connections **210** from synchronization and timing module **118** of signals unit **110**. In some embodiments, synchronization connections **210** may be used to synchronize the local oscillators of radio frequency mode frontend **200**. For example, such synchronization may be used during MIMO operation, such as when multiple radio-frequency mode frontends **200** are employed. In some embodiments, synchronization connections **210**



may be used to amplify the outgoing signal (e.g., shown via node **212**). In some embodiments, synchronization connections **210** may be used to amplify the incoming signal (e.g., shown via node **214**).

FIG. **3** is a block diagram illustrating an exemplary architecture of an acoustics mode frontend **300**, according to example embodiments. In some embodiments, acoustics mode frontend **300** may be representative of a mode frontend that may be used in UniSDM device **100**. For example, acoustics mode frontend **300** may be representative of the mode frontend **112** discussed above in conjunction with FIG. **1**.

As shown, acoustics mode frontend **300** may include a transmitter **302**, a receiver **304**, a transmitter/receiver switch ("switch") **306**, a transmit transducer **308**, and a receive transducer **310** (e.g., hydrophone). In some embodiments, transmitter **302** may be a power amplification transmitter (e.g., Tx PA). For example, transmitter **302** may receive a signal **301** from signals unit **110**, amplify signal **301**, and provide signal **301** to switch **306** for transmission via transmit transducer **308**. In some embodiments, receiver **304** may be a low noise amplifier receiver (e.g., Rx LNA). For example, receiver **304** may receive an incoming signal **303**, via receive transducer **310**, amplify incoming signal **303**, and provide amplified incoming signal **303** to signals unit **110** for processing.

Acoustics mode frontend **300** may be configured to operate in a wide array of varying frequencies. Generally, acoustics transmission frequencies are low compared to radio frequencies, thus additional frequency conversion may not be needed. In some embodiments, depending on the frequencies and dynamic range requirements, receive transducer **310** and transmit transducer **308** may be combined or separated.

FIG. **4** is a block diagram illustrating an exemplary architecture of an optical mode frontend **400**, according to example embodiments. In some embodiments, optical mode frontend **400** may be representative of a mode frontend that may be used in UniSDM device **100**. For example, optical mode frontend **400** may be representative of a mode frontend **112** discussed above in conjunction with FIG. **1**.

As shown, optical mode frontend **400** may include a transmitter **402**, a receiver **404**, a light source **406**, and an optical receiver **408**. Transmitter **402** may receive signal **401** from signals unit **110** and may provide signal **401** to light source **406** for transmission. In some embodiments, receiver **404** may receive an incoming signal **403**, via optical receiver **408**, and may provide incoming signal **403** to signals unit **110** for processing.

In some embodiments, light source **406** may be representative of a light emitting device, such as LEDs or LASERS. In some embodiments, optical receiver **408** may be implemented by p-i-n photodiodes, avalanche photodiodes, photomultiplier tubes, or other photo-detector types. Controller **106** may be interested in the properties of the received transmission. Example properties may include, but are not limited to, transmission power, modulation bandwidth, carrier frequency (e.g., wavelength), directivity, and noise per performance (e.g., amplitude noise, and phase noise for coherent modulators. Because optical properties of water vary with the water type, UniSDM device **100** may implement various wavelengths. For example, UniSDM device **100** may implement around violet-blue (e.g., 410 nm) for clear water, or around 520 nm for shallow sea and coastal lines waters. In some embodiments, these modes may be used in wavelength-division multiplexing approach, increasing the available bandwidth. For example, multi-mode head

**104** may implement several modes with different wavelengths, e.g., 400 nm, 450 nm and 520 nm. It may use all modes simultaneously and may triple the throughput accordingly. Note that a single mode (e.g., 400 nm) between any two nodes A and B and another mode (e.g., 450 nm) between A and C may be used simultaneously by multi-mode head **104**. Note also that different modes may be used for bi-directional communication, e.g. one mode from A to B and another one from B to A.

FIG. **5** is a block diagram illustrating an exemplary architecture of a magnetic induction mode frontend **500**, according to example embodiments. In some embodiments, magnetic induction mode frontend **500** may be representative of a mode frontend that may be used in UniSDM device **100**. For example, magnetic induction mode frontend **500** may be representative of a mode frontend **112** discussed above in conjunction with FIG. **1**.

As shown, magnetic induction mode frontend **500** may include a transmitter **502**, a receiver **504**, a transmitter/receiver switch ("switch") **506**, and an antenna **508**. In some embodiments, transmitter **502** may be a power amplification transmitter (e.g., Tx PA). For example, transmitter **502** may receive a signal **501** from signals unit **110**, amplify signal **501**, and provide signal **501** to switch **506** for transmission via antenna **508**. In some embodiments, receiver **504** may be a low noise amplifier receiver (e.g., Rx LNA). For example, receiver **504** may receive an incoming signal **503**, via antenna **508**, amplify incoming signal **503**, and provide amplified incoming signal **503** to signals unit **110** for processing.

Switch **506** may be configured to toggle between a transmitter mode and a receiver mode. Accordingly, in some embodiments, switch **506** may toggle to transmitter mode to transmit an amplified signal provided by transmitter **502** via antenna **508**; in some embodiments, switch **506** may toggle to receiver mode to receive an incoming signal via antenna **508** and subsequently provide the incoming signal to receiver **504**. Antenna **508** may be representative of a magnetic antenna. For example, antenna **508** may be representative of one or more three-axis antennas for omnidirectional transmission and reception.

FIG. **6A** is a block diagram illustrating an exemplary architecture of a wired mode frontend **600**, according to example embodiments. In some embodiments, wired mode frontend **600** may be representative of a mode frontend that may be used in UniSDM device **100**. For example, wired mode frontend **600** may be representative of a mode frontend **112** discussed above in conjunction with FIG. **1**.

As shown, wired mode frontend **600** may be representative of a copper cable wired mode front end. Wired mode frontend **600** may include a transmitter **602** and a receiver **604**. In some embodiments, transmitter **602** may be a power amplification transmitter (e.g., Tx PA). For example, transmitter **602** may receive a signal **601** from signals unit **110**, amplify signal **601**, and may transmit the signal. In some embodiments, receiver **604** may be a low noise amplifier receiver (e.g., Rx LNA). For example, receiver **604** may receive an incoming signal **603**, may amplify incoming signal **603**, and provide amplified incoming signal **603** to signals unit **110** for processing.

FIG. **6B** is a block diagram illustrating an exemplary architecture of a wired mode frontend **650**, according to example embodiments. In some embodiments, wired mode frontend **650** may be representative of a mode frontend that may be used in UniSDM device **100**. For example, wired mode frontend **650** may be representative of a mode frontend **112** discussed above in conjunction with FIG. **1**.



## 11

As shown, wired mode frontend **650** may be representative of a fibre optic wired mode front end. Wired mode frontend **650** may include a transmitter **652**, a receiver **654**, a laser **656**, and a photodiode **658**. In some embodiments, transmitter **652** may be a power amplification transmitter (e.g., Tx PA). For example, transmitter **652** may receive a signal **651** from signals unit **110**, amplify signal **651**, and may transmit signal **651**, via laser **656**. In some embodiments, receiver **654** may be a low noise amplifier receiver (e.g., Rx LNA). For example, receiver **654** may receive an incoming signal **653**, via photodiode **658**, may amplify incoming signal **653**, and provide amplified incoming signal **653** to signals unit **110** for processing.

FIG. 7 is a block diagram illustrating an exemplary computing environment **700**, according to example embodiments. Computing environment **700** may include at least one or more user devices **702** and one or more UniSDMs (e.g., UniSDM device **704a**, UniSDM device **704n**) communicating via network **705**.

Network **705** may be of any suitable type, including individual connections via the Internet, such as cellular or Wi-Fi networks. In some embodiments, network **705** may connect terminals, services, and mobile devices using direct connections, such as radio frequency identification (RFID), near-field communication (NFC), Bluetooth™, low-energy Bluetooth™ (BLE), Wi-Fi™ ZigBee™, ambient backscatter communication (ABC) protocols, USB, WAN, or LAN. Because the information transmitted may be personal or confidential, security concerns may dictate one or more of these types of connection be encrypted or otherwise secured. In some embodiments, however, the information being transmitted may be less personal, and therefore, the network connections may be selected for convenience over security.

Network **705** may include any type of computer networking arrangement used to exchange data. For example, network **705** may be the Internet, a private data network, virtual private network using a public network and/or other suitable connection(s) that enables components in computing environment **700** to send and receive information between the components of computing environment **700**.

User device **702** may be operated by a user. User device **702** may be representative of a mobile device, a tablet, a desktop computer, or any computing system having the capabilities described herein. In some embodiments, user device **702** may be configured to remotely update software of UniSDM **704a** or UniSDM **604n**. Such remote updating allows UniSDM **704a** and UniSDM **704n** to support future or new technologies, such as MIMO. In some embodiments, user device **702** may be configured to send and/or receive one or more digital signals to UniSDM **704a** and/or UniSDM **704n** via network **705**.

As shown, user device **702** may communicate with UniSDM **704a** and UniSDM **704n**. Although two UniSDMs are illustrated in FIG. 7, those skilled in the art understand that client device **702** may communicate with a plurality of UniSDM devices. UniSDM **704a** and UniSDM **704n** may be representative of UniSDM device **100** discussed above in conjunction with FIG. 1. In operation, UniSDM **704a** may receive a signal from client device **702**. UniSDM device **704a** may process and send the signal to one or more nodes **706a-706m**. Exemplary nodes **706a-706m** may include, but are not limited to, underwater sensors, autonomous underwater vehicles, remotely operated vehicles, and other underwater Internet-of-Things devices. Similarly, UniSDM device **704n** may process and send the signal to one or more nodes **706n-706z**. Exemplary nodes **706n-706z** may include, but are not limited to, underwater sensors, autonomous

## 12

underwater vehicles, remotely operated vehicles, and other underwater Internet-of-Things devices.

FIG. 8 is a flow diagram illustrating method **800** of operating a universal multi-mode software defined modem (e.g., UniSDM device **100**), according to example embodiments. Method **800** may begin at step **802**.

At step **802**, controller **106** on UniSDM device **100** may initiate a channel probing process in which controller **106** may probe the available modes and establish a link with the other node. Controller **106** may establish one or more links between UniSDM device **100** and the other node. In some embodiments, to probe the modes, UniSDM device **100** may send probing packets at maximum available power to the other node. When the other node receives such packet, it may reply to it. During this two-way communication, each node may measure the received power and response delay, and thus obtain information about the propagation delay and the path loss. In some embodiments, the modes probing may be done sequentially, starting from the mode that may provide the lowest delay. Such an approach may reduce the required transmission time and may minimize interference. For example, if two nodes can establish an optical mode link, they can use the optical mode link for all types of communication, both control and data. If, for example, the optical link is not available, the nodes should probe a magnetic induction mode. If, for example, neither optical nor magnetic probing succeeded, the nodes should switch to acoustic, which may provide the highest range but at the lowest speed.

At step **804**, UniSDM device **100** may receive transmissions from the node over the established links. For example, controller **106** may collect the links' channel station information to select one of the modes to perform the data transmission based on a given criteria.

At step **806**, UniSDM device **100** may select the mode that may result in the lowest hardware load according to one or more metrics. In some embodiments, controller **106** may select the mode based on SNR threshold with higher-speed mode priority. In some embodiments, controller **106** may select the mode based on energy efficiency per distance (e.g., J/bit/m). Such selection may reduce the overall energy used by UniSDM device **100**. In some embodiments, controller **106** may select the mode based on transmit time for latency minimization and throughput maximization considering non uniform density. In some embodiments, controller **106** may select the mode based on the energy efficiency of the current node (e.g., J/bit). In some embodiments, controller **106** may select the mode based on other performance metrics such as transmit time, energy used, or the amount of the medium occupied by the transmission. In some embodiments, controller **106** may select the mode based on transmit time multiplied by the number of neighbors capable of hearing the communication for per-volume throughput maximization considering non-uniform node density.

At step **808**, UniSDM device **100** may send data to the node using the identified mode. For example, based on the determined mode in step **806**, UniSDM device **100** may configure a signal to be transmitted to the other node using the identified mode.

FIG. 9A illustrates a system bus architecture of computing system **900**, according to example embodiments. System **900** may be representative of at least a portion of baseband unit **102** and/or multi-mode head **104**. One or more components of system **900** may be in electrical communication with each other using a bus **905**. System **900** may include a processing unit (CPU or processor) **910** and a system bus **905** that couples various system components including the



system memory **915**, such as read only memory (ROM) **920** and random access memory (RAM) **925**, to processor **910**. System **900** may include a cache of high-speed memory connected directly with, in close proximity to, or integrated as part of processor **910**. System **900** may copy data from memory **915** and/or storage device **930** to cache **912** for quick access by processor **910**. In this way, cache **912** may provide a performance boost that avoids processor **910** delays while waiting for data. These and other modules may control or be configured to control processor **910** to perform various actions. Another system memory **915** may be available for use as well. Memory **915** may include multiple different types of memory with different performance characteristics. Processor **910** may include any general purpose processor and a hardware module or software module, such as service **1 932**, service **2 934**, and service **3 936** stored in storage device **930**, configured to control processor **910** as well as a special-purpose processor where software instructions are incorporated into the actual processor design. Processor **910** may essentially be a completely self-contained computing system, containing multiple cores or processors, a bus, memory controller, cache, etc. A multi-core processor may be symmetric or asymmetric.

To enable user interaction with the computing system **900**, an input device **945** may represent any number of input mechanisms, such as a microphone for speech, a touch-sensitive screen for gesture or graphical input, keyboard, mouse, motion input, speech and so forth. An output device **935** may also be one or more of a number of output mechanisms known to those of skill in the art. In some instances, multi-mode systems may enable a user to provide multiple types of input to communicate with computing system **900**. Communications interface **940** may generally govern and manage the user input and system output. There is no restriction on operating on any particular hardware arrangement and therefore the basic features here may easily be substituted for improved hardware or firmware arrangements as they are developed.

Storage device **930** may be a non-volatile memory and may be a hard disk or other types of computer readable media which may store data that are accessible by a computer, such as magnetic cassettes, flash memory cards, solid state memory devices, digital versatile disks, cartridges, random access memories (RAMs) **925**, read only memory (ROM) **920**, and hybrids thereof.

Storage device **930** may include services **932**, **934**, and **936** for controlling the processor **910**. Other hardware or software modules are contemplated. Storage device **930** may be connected to system bus **905**. In one aspect, a hardware module that performs a particular function may include the software component stored in a computer-readable medium in connection with the necessary hardware components, such as processor **910**, bus **905**, output device **935** (e.g., display), and so forth, to carry out the function.

FIG. **9B** illustrates a computer system **950** having a chipset architecture that may represent at least a portion of baseband unit **102** and/or multi-mode head **104**. Computer system **950** may be an example of computer hardware, software, and firmware that may be used to implement the disclosed technology. System **950** may include processor **955**, representative of any number of physically and/or logically distinct resources capable of executing software, firmware, and hardware configured to perform identified computations. Processor **955** may communicate with a chipset **960** that may control input to and output from processor **955**. In this example, chipset **960** outputs information to output **965**, such as a display, and may read and write

information to storage device **970**, which may include magnetic media, and solid state media, for example. Chipset **960** may also read data from and write data to storage device **975** (e.g., RAM). A bridge **980** for interfacing with a variety of user interface components **985** may be provided for interfacing with chipset **960**. Such user interface components **985** may include a keyboard, a microphone, touch detection and processing circuitry, a pointing device, such as a mouse, and so on. In general, inputs to system **950** may come from any of a variety of sources, machine generated and/or human generated.

Chipset **960** may also interface with one or more communication interfaces **990** that may have different physical interfaces. Such communication interfaces may include interfaces for wired and wireless local area networks, for broadband wireless networks, as well as personal area networks. Some applications of the methods for generating, displaying, and using the GUI disclosed herein may include receiving ordered datasets over the physical interface or be generated by the machine itself by processor **955** analyzing data stored in storage device **970** or storage device **975**. Further, the machine may receive inputs from a user through user interface components **985** and execute appropriate functions, such as browsing functions by interpreting these inputs using processor **955**.

It may be appreciated that example systems **900** and **950** may have more than one processor **910** or be part of a group or cluster of computing devices networked together to provide greater processing capability.

While the foregoing is directed to embodiments described herein, other and further embodiments may be devised without departing from the basic scope thereof. For example, aspects of the present disclosure may be implemented in hardware or software or a combination of hardware and software. One embodiment described herein may be implemented as a program product for use with a computer system. The program(s) of the program product define functions of the embodiments (including the methods described herein) and can be contained on a variety of computer-readable storage media. Illustrative computer-readable storage media include, but are not limited to: (i) non-writable storage media (e.g., read-only memory (ROM) devices within a computer, such as CD-ROM disks readably by a CD-ROM drive, flash memory, ROM chips, or any type of solid-state non-volatile memory) on which information is permanently stored; and (ii) writable storage media (e.g., floppy disks within a diskette drive or hard-disk drive or any type of solid state random-access memory) on which alterable information is stored. Such computer-readable storage media, when carrying computer-readable instructions that direct the functions of the disclosed embodiments, are embodiments of the present disclosure.

It will be appreciated to those skilled in the art that the preceding examples are exemplary and not limiting. It is intended that all permutations, enhancements, equivalents, and improvements thereto are apparent to those skilled in the art upon a reading of the specification and a study of the drawings are included within the true spirit and scope of the present disclosure. It is therefore intended that the following appended claims include all such modifications, permutations, and equivalents as fall within the true spirit and scope of these teachings.

The invention claimed is:

1. A software-defined modem, comprising:
  - a multi-mode head, the multi-mode head comprising a plurality of mode frontends, each mode frontend of the plurality of mode frontends to transmit and receive



## 15

communications according to a preset communication mode, wherein the plurality of mode frontends are controlled by the software-defined modem; and

a baseband unit configured to control operation of the multi-mode head, wherein the multi-mode head is configured to simultaneously use at least two or more communication modes selected from a radio frequency communication mode, an acoustics communication mode, an optical communications mode, and a magnetic induction communication mode.

2. The software-defined modem of claim 1, wherein the multi-mode head further comprises:

a signals unit configured to forward control signals from the baseband unit to the plurality of mode frontends.

3. The software-defined modem of claim 2, wherein the signals unit comprises:

a digital signal processor configured to perform one or more digital signal operations to incoming or outgoing digital signals.

4. The software-defined modem of claim 2, wherein the signals unit comprises:

a conversion module configured to convert an electrical signal to an analog signal and an analog signal to an electrical signal.

5. The software-defined modem of claim 2, wherein the signals unit comprises:

a communication module configured to generate and communicate a control signal to a selected mode frontend of the plurality of mode frontends.

6. The software-defined modem of claim 1, wherein the plurality of mode frontends comprises:

a radio frequency mode frontend configured to communicate in the radio frequency communication mode, the radio frequency mode frontend comprising:

an antenna;

a transmitter/receiver switch in communication with the antenna;

a transmitter in communication with the transmitter/receiver switch, the transmitter configured to provide an outgoing signal to the antenna via the transmitter/receiver switch; and

a receiver in communication with the transmitter/receiver switch, the receiver configured to provide an incoming signal, received through the antenna, to the baseband unit.

7. The software-defined modem of claim 6, wherein the radio frequency mode frontend further comprises:

a plurality of oscillators.

8. The software-defined modem of claim 7, wherein the baseband unit comprises:

a synchronization and timing module configured to generate and provide reference signals to the plurality of mode frontends.

9. The software-defined modem of claim 8, wherein the synchronization and timing module is configured to generate synchronization connections to synchronize the plurality of oscillators of the radio frequency mode frontend.

10. The software-defined modem of claim 1, wherein the plurality of mode frontends comprises:

an acoustic mode frontend configured to communicate in an acoustic communication mode, the acoustic mode frontend comprising:

a transmit transducer configured to transmit an outgoing acoustic signal; and

## 16

a transmitter in communication with the transmit transducer, the transmitter configured to provide the outgoing acoustic signal to the transmit transducer; and/or

a receive transducer configured to receive an incoming acoustic signal; and

a receiver in communication with the receive transducer, the receiver configured to receive the incoming acoustic signal, received through the receive transducer, to the baseband unit.

11. The software-defined modem of claim 1, wherein the plurality of mode frontends comprises:

an acoustic mode frontend configured to communicate in an acoustic communication mode, the acoustic mode frontend comprising:

a transmit/receive transducer configured to transmit and/or receive an acoustic signal;

a transmitter/receiver switch in communication with the transmit/receive transducer;

a transmitter in communication with the transmitter/receiver switch, the transmitter configured to provide an outgoing acoustic signal to the transmit/receive transducer via the transmitter/receiver switch; and

a receiver in communication with the transmitter/receiver switch, the receiver configured to receive an incoming acoustic signal, received through the transmit/receive transducer, to the baseband unit.

12. The software-defined modem of claim 1, wherein the plurality of mode frontends comprises:

an optical mode frontend configured to communicate in an optical communication mode, the optical mode frontend comprising:

a light source configured to transmit an outgoing optical signal; and

an optical receiver configured to receive an incoming optical signal.

13. The software-defined modem of claim 1, wherein the plurality of mode frontends comprises:

a magnetic induction mode frontend configured to communicate in the magnetic induction communication mode, the magnetic induction mode frontend comprising:

a magnetic antenna;

a transmitter/receiver switch in communication with the magnetic antenna;

a transmitter in communication with the transmitter/receiver switch, the transmitter configured to provide an outgoing magnetic induction signal to the magnetic antenna via the transmitter/receiver switch; and

a receiver in communication with the transmitter/receiver switch, the receiver configured to provide an incoming magnetic induction signal, received through the magnetic antenna, to the baseband unit.

14. The software-defined modem of claim 1, wherein the baseband unit further comprises:

a digital signal processor configured to implement one or more protocols of the software-defined modem.

15. A software-defined modem, comprising:

a multi-mode head, the multi-mode head comprising:

a first mode frontend configured to transmit and receive communications according to a first communication mode, and

a second mode frontend configured to transmit and receive communications according to a second communication mode;

wherein the first mode frontend and the second mode frontend are controlled by the software-defined



17

modem to transmit and receive communications according to the first communication mode and the second communication mode; and

a baseband unit configured to control operation of the multi-mode head, wherein the multi-mode head is configured to simultaneously use the first communication mode and the second communication mode, the baseband unit configured to select one of the first communication mode or the second communication mode for communicating with a node by:

probing the first communication mode and the second communication mode and establishing a first communication link with the node via the first communication mode and a second communication link with the node via the second communication mode, receiving a first set of transmissions via the first communication mode and a second set of transmissions via the second communication mode, determining that the first communication mode results in a lower hardware resource load on the software-defined modem than the second communication mode, and responsive to the determining, sending data to the node using the first communication mode.

**16.** The software-defined modem of claim **15**, wherein determining that the first communication mode results in the lower hardware resource load on the software-defined modem comprises:

determining that the first communication mode has a signal-to-noise ratio threshold with a higher-speed mode priority than the second communication mode.

**17.** The software-defined modem of claim **15**, wherein determining that the first communication mode results in the lower hardware resource load on the software-defined modem comprises:

determining that the first communication mode is more energy efficient, per distance, than the second communication mode.

18

**18.** The software-defined modem of claim **15**, wherein determining that the first communication mode results in the lower hardware resource load on the software-defined modem comprises:

determining that the first communication mode has a faster transmit time than the second communication mode.

**19.** The software-defined modem of claim **15**, wherein determining that the first communication mode results in the lower hardware resource load on the software-defined modem is based on a function of transmit time and a number of receiver devices capable of receiving a transmission.

**20.** A method of operating a software-defined modem configured to simultaneously use two or more communication modes, the method comprising:

probing a first communication mode of the software-defined modem and a second communication mode of the software-defined modem;

establishing a first communication link with a target node via a first mode frontend configured to transmit and receive communications according to the first communication mode and a second communication link with the target node via a second mode frontend configured to transmit and receive communications according to the second communication mode;

wherein the first mode frontend and the second mode frontend are controlled by the software-defined modem to transmit and receive communications according to the first communication mode and the second communication mode;

receiving a first set of transmissions via the first communication mode and a second set of transmissions via the second communication mode;

determining that the first communication mode results in a lower hardware resource load on the software-defined modem than the second communication mode; and responsive to the determining, sending data to the target node using the first communication mode.

\* \* \* \* \*