

US012436438B2

(12) **United States Patent**
Brown et al.

(10) **Patent No.:** **US 12,436,438 B2**
(45) **Date of Patent:** **Oct. 7, 2025**

(54) **MULTIPURPOSE CONTROLLER FOR MULTISTATE WINDOWS**

(71) Applicant: **View, Inc.**, Milpitas, CA (US)

(72) Inventors: **Stephen C. Brown**, San Mateo, CA (US); **Dhairya Shrivastava**, Los Altos, CA (US)

(73) Assignee: **View Operating Corporation**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/946,196**

(22) Filed: **Jun. 9, 2020**

(65) **Prior Publication Data**
US 2020/0301236 A1 Sep. 24, 2020

Related U.S. Application Data

(63) Continuation of application No. 15/891,866, filed on Feb. 8, 2018, now Pat. No. 10,908,470, which is a (Continued)

(51) **Int. Cl.**
G02F 1/163 (2006.01)
E06B 7/28 (2006.01)
E06B 9/24 (2006.01)
G02F 1/133 (2006.01)
H04L 12/28 (2006.01)

(52) **U.S. Cl.**
CPC **G02F 1/163** (2013.01); **E06B 7/28** (2013.01); **E06B 9/24** (2013.01); **G02F 1/13318** (2013.01); **H04L 12/2803** (2013.01); **E06B 2009/2464** (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

253,392 A 2/1882 Jones et al.
2,121,753 A 6/1938 Cornell, Jr.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1380991 A 11/2002
CN 1822951 A 8/2006
(Continued)

OTHER PUBLICATIONS

Preliminary Amendment filed Oct. 18, 2016 in U.S. Appl. No. 15/228,992.

(Continued)


Primary Examiner — Carlos R Ortiz Rodriguez

(74) *Attorney, Agent, or Firm* — Cha & Reiter, LLC.

(57) **ABSTRACT**

“Smart” controllers for windows having controllable optical transitions are described. Controllers with multiple features can sense and adapt to local environmental conditions. Controllers described herein can be integrated with a building management system (BMS) to greatly enhance the BMS’s effectiveness at managing local environments in a building. The controllers may have one, two, three or more functions such as powering a smart window, determining the percent transmittance, size, and/or temperature of a smart window, providing wireless communication between the controller and a separate communication node, etc.

10 Claims, 5 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/932,474, filed on Nov. 4, 2015, now Pat. No. 9,927,674, which is a continuation of application No. 13/049,756, filed on Mar. 16, 2011, now Pat. No. 9,454,055.

(56)

References Cited

U.S. PATENT DOCUMENTS

3,379,859 A	4/1968	Marriott		8,669,503 B2	3/2014	Johnson et al.
3,876,862 A	4/1975	Newman et al.		8,711,465 B2	4/2014	Bhatnagar et al.
3,947,837 A *	3/1976	Bitterice B32B 17/10376	8,800,221 B1	8/2014	Header
			109/42	8,810,889 B2	8/2014	Brown et al.
4,306,140 A	12/1981	Stromquist		9,019,588 B2	4/2015	Brown et al.
4,691,486 A	9/1987	Niekrasz et al.		9,436,054 B2	9/2016	Brown et al.
4,935,723 A *	6/1990	Vallance G08B 13/04	9,442,339 B2	9/2016	Parker et al.
			310/322	9,482,922 B2	11/2016	Brown et al.
4,937,423 A	6/1990	Yoshihara et al.		9,671,665 B2	6/2017	Brown et al.
4,941,302 A	7/1990	Barry		9,690,162 B2	6/2017	Brown et al.
4,958,917 A	9/1990	Hashimoto et al.		9,728,920 B2	8/2017	Brown et al.
5,017,755 A	5/1991	Yahagi et al.		9,769,459 B2	9/2017	Thompson et al.
5,097,358 A	3/1992	Ito et al.		10,139,696 B2	11/2018	Brown et al.
5,124,833 A	6/1992	Barton et al.		10,139,697 B2	11/2018	Wilbur et al.
5,170,108 A	12/1992	Peterson et al.		10,175,549 B2	1/2019	Brown et al.
5,313,761 A	5/1994	Leopold		10,180,606 B2	1/2019	Mullins et al.
5,379,146 A	1/1995	Defendini		10,288,971 B2	5/2019	Phillips et al.
5,384,653 A	1/1995	Benson et al.		10,322,680 B2	6/2019	Terashima et al.
5,457,564 A	10/1995	Leventis et al.		10,591,799 B2	3/2020	Brown et al.
5,657,149 A	8/1997	Buffat et al.		10,678,103 B2	6/2020	Mullins et al.
5,657,150 A	8/1997	Kallman et al.		11,067,869 B2	7/2021	Brown et al.
5,724,175 A	3/1998	Hichwa et al.		11,092,868 B2	8/2021	Phillips et al.
5,822,107 A	10/1998	Lefrou et al.		11,181,797 B2	11/2021	Brown et al.
5,877,936 A	3/1999	Nishitani et al.		11,255,120 B2	2/2022	Shrivastava et al.
5,948,195 A	9/1999	Thomas		11,262,626 B2	3/2022	Mullins et al.
6,001,487 A	12/1999	Ladang et al.		11,352,834 B2	6/2022	Brown et al.
6,039,390 A	3/2000	Agrawal et al.		11,408,223 B2	8/2022	Brown
6,045,896 A	4/2000	Boire et al.		11,719,039 B2	8/2023	Brown et al.
6,055,088 A	4/2000	Fix et al.		11,719,992 B2	8/2023	Brown et al.
6,068,720 A	5/2000	McHugh		11,733,579 B2	8/2023	Phillips et al.
6,176,715 B1	1/2001	Buescher		12,085,818 B2	9/2024	Mullins et al.
6,204,953 B1	3/2001	Zieba et al.		2002/0075552 A1	6/2002	Poll et al.
6,261,641 B1	7/2001	Zieba et al.		2003/0111447 A1	6/2003	Corkum et al.
6,275,157 B1 *	8/2001	Mays G07C 5/085	2003/0191546 A1	10/2003	Bechtel et al.
			340/572.5	2003/0210450 A1	11/2003	Yu et al.
6,337,758 B1	1/2002	Beteille et al.		2003/0227663 A1	12/2003	Agrawal et al.
6,369,935 B1	4/2002	Cardinal et al.		2004/0047050 A1	3/2004	Bauer et al.
6,407,847 B1	6/2002	Poll et al.		2004/0208600 A1	10/2004	Guenter et al.
6,420,071 B1	7/2002	Lee et al.		2005/0002081 A1	1/2005	Beteille et al.
6,529,308 B2	3/2003	Beteille et al.		2005/0166495 A1	8/2005	Cho et al.
6,535,126 B2 *	3/2003	Lin B60R 25/33	2006/0077511 A1	4/2006	Poll et al.
			340/545.4	2006/0187608 A1	8/2006	Stark
6,559,411 B2	5/2003	Borgeson et al.		2006/0283084 A1	12/2006	Johnson
6,567,708 B1	5/2003	Bechtel et al.		2007/0020442 A1	1/2007	Giron et al.
6,795,226 B2 *	9/2004	Agrawal B32B 17/10174	2007/0067048 A1 *	3/2007	Bechtel
			359/254		 E06B 9/24
6,897,936 B1	5/2005	Li et al.				359/275
6,919,530 B2	7/2005	Borgeson et al.		2007/0103761 A1	5/2007	Giron et al.
6,950,221 B1	9/2005	Terada et al.		2007/0133078 A1	6/2007	Fanton et al.
7,002,720 B2	2/2006	Beteille et al.		2007/0236180 A1	10/2007	Rodgers
7,033,655 B2	4/2006	Beteille et al.		2007/0248756 A1	10/2007	Krisko et al.
7,230,748 B2	6/2007	Giron et al.		2008/0238706 A1	10/2008	Kenwright
7,259,730 B2	8/2007	O'Keeffe		2008/0239452 A1	10/2008	Xu et al.
7,362,491 B2	4/2008	Busick et al.		2008/0310007 A1	12/2008	Agrawal et al.
7,531,101 B2	5/2009	Beteille		2009/0016715 A1	1/2009	Furey
7,586,664 B2	9/2009	O'Shaughnessy et al.		2009/0058295 A1	3/2009	Auday et al.
7,710,671 B1	5/2010	Kwak et al.		2009/0067031 A1	3/2009	Piroux et al.
7,869,114 B2	1/2011	Valentin et al.		2009/0097098 A1	4/2009	Piroux
7,894,119 B2	2/2011	Valentin et al.		2009/0110918 A1	4/2009	Jacquioid et al.
7,929,194 B2	4/2011	Legois et al.		2009/0114928 A1	5/2009	Messere et al.
7,941,982 B2	5/2011	Merica		2009/0130409 A1	5/2009	Reutler et al.
8,035,882 B2	10/2011	Fanton et al.		2009/0148642 A1	6/2009	Mausser et al.
8,125,336 B2 *	2/2012	Ieda G08B 13/1481	2009/0153208 A1	6/2009	Lynch
			340/550	2009/0157358 A1	6/2009	Kim
8,213,074 B1	7/2012	Shrivastava et al.		2009/0174300 A1	7/2009	Jousse et al.
8,254,013 B2	8/2012	Mehtani et al.		2009/0181203 A1	7/2009	Valentin et al.
8,643,933 B2	2/2014	Brown et al.		2009/0231662 A1	9/2009	Sorensen et al.
				2009/0251758 A1	10/2009	Valentin et al.
				2009/0255576 A1	10/2009	Tischler
				2009/0262411 A1	10/2009	Karmhag et al.
				2009/0297806 A1	12/2009	Dawson-Elli et al.
				2009/0323160 A1	12/2009	Egerton et al.
				2009/0323162 A1	12/2009	Fanton et al.
				2010/0067090 A1	3/2010	Egerton et al.
				2010/0146883 A1	6/2010	Benkel
				2010/0208326 A1	8/2010	Kwak et al.
				2010/0243427 A1	9/2010	Kozlowski et al.
				2010/0245973 A1	9/2010	Wang et al.
				2010/0315693 A1	12/2010	Lam et al.
				2011/0043885 A1	2/2011	Lamine et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0048614 A1 3/2011 Veerasamy et al.
 2011/0051221 A1 3/2011 Veerasamy
 2011/0059275 A1 3/2011 Stark
 2011/0094585 A1 4/2011 Debije et al.
 2011/0148218 A1 6/2011 Rozbicki et al.
 2011/0211247 A1 9/2011 Kozlowski et al.
 2011/0216389 A1 9/2011 Piroux et al.
 2011/0248014 A1 10/2011 Chubb
 2011/0249314 A1 10/2011 Wang et al.
 2011/0260961 A1 10/2011 Burdis
 2011/0266137 A1 11/2011 Wang et al.
 2011/0266138 A1 11/2011 Wang et al.
 2011/0267672 A1 11/2011 Sbar et al.
 2011/0267674 A1 11/2011 Wang et al.
 2011/0267675 A1 11/2011 Wang et al.
 2011/0279882 A1 11/2011 Chan et al.
 2011/0292488 A1 12/2011 McCarthy et al.
 2011/0299149 A1 12/2011 Park et al.
 2012/0026573 A1 2/2012 Collins et al.
 2012/0033287 A1 2/2012 Friedman et al.
 2012/0062975 A1 3/2012 Mehtani et al.
 2012/0133315 A1 5/2012 Berman et al.
 2012/0147449 A1 6/2012 Bhatnagar et al.
 2012/0194895 A1 8/2012 Podbelski et al.
 2012/0200908 A1 8/2012 Bergh et al.
 2012/0239209 A1 9/2012 Brown et al.
 2012/0268803 A1 10/2012 Greer et al.
 2012/0300280 A1 11/2012 Murphy et al.
 2012/0327499 A1 12/2012 Parker et al.
 2013/0057937 A1 3/2013 Berman et al.
 2013/0085614 A1 4/2013 Wenzel et al.
 2013/0143419 A1 6/2013 Wei et al.
 2013/0157493 A1 6/2013 Brown
 2013/0241299 A1 9/2013 Snyder et al.
 2013/0271812 A1 10/2013 Brown et al.
 2013/0271813 A1 10/2013 Brown
 2013/0271814 A1 10/2013 Brown
 2013/0271815 A1 10/2013 Brown et al.
 2013/0278988 A1 10/2013 Jack et al.
 2013/0319756 A1 12/2013 Snyder et al.
 2014/0000191 A1 1/2014 Snyder et al.
 2014/0007530 A1 1/2014 Liao
 2014/0041933 A1 2/2014 Snyder et al.
 2014/0160550 A1 6/2014 Brown et al.
 2014/0170863 A1 6/2014 Brown
 2014/0192393 A1 7/2014 Bhatnagar et al.
 2014/0247475 A1 9/2014 Parker et al.
 2014/0317514 A1 10/2014 Bokotey
 2014/0349497 A1 11/2014 Brown et al.
 2014/0355097 A1 12/2014 Brown et al.
 2015/0002919 A1 1/2015 Jack et al.
 2015/0070745 A1 3/2015 Pradhan et al.
 2015/0092260 A1 4/2015 Parker et al.
 2015/0103389 A1 4/2015 Klawuhn et al.
 2015/0118869 A1 4/2015 Brown et al.
 2015/0219975 A1 8/2015 Phillips et al.
 2016/0027391 A1 1/2016 Gibson et al.
 2016/0091769 A1 3/2016 Rozbicki et al.
 2016/0134932 A1 5/2016 Karp et al.
 2016/0344148 A1 11/2016 Mullins et al.
 2016/0357083 A1 12/2016 Brown et al.
 2017/0006679 A1 1/2017 Chin et al.
 2017/0045795 A1 2/2017 Brown et al.
 2017/0082903 A1 3/2017 Vigano et al.
 2017/0097553 A1 4/2017 Jack et al.
 2017/0104318 A1 4/2017 Uno
 2017/0117674 A1 4/2017 Brown et al.
 2017/0219908 A1 8/2017 Brown et al.
 2017/0250163 A1 8/2017 Wilbur et al.
 2018/0130455 A1 5/2018 Plummer et al.
 2018/0144696 A1 5/2018 Zhang et al.
 2018/0198232 A1 7/2018 Troufflard et al.
 2018/0301858 A9 10/2018 Mullins et al.
 2018/0314100 A1 11/2018 Mullins et al.
 2019/0056631 A1 2/2019 Brown et al.

2019/0121214 A1 4/2019 Wilbur et al.
 2019/0196292 A1 6/2019 Brown et al.
 2019/0243207 A1 8/2019 Brown et al.
 2019/0265571 A1 8/2019 Phillips et al.
 2020/0080364 A1 3/2020 Shrivastava et al.
 2020/0260556 A1 8/2020 Rozbicki et al.
 2020/0310214 A1 10/2020 Brown
 2020/0393719 A1 12/2020 Mullins et al.
 2021/0149266 A1 5/2021 Brown et al.
 2021/0333679 A1 10/2021 Phillips et al.
 2022/0136319 A1 5/2022 Shrivastava et al.
 2022/0187671 A1 6/2022 Brown et al.
 2022/0214575 A1 7/2022 Mullins et al.
 2022/0316270 A1 10/2022 Brown
 2022/0325574 A1 10/2022 Brown et al.
 2023/0288771 A1 9/2023 Frank et al.
 2024/0045299 A1 2/2024 Brown et al.
 2024/0085754 A1 3/2024 Martinson et al.
 2024/0210782 A1 6/2024 Brown et al.

FOREIGN PATENT DOCUMENTS

CN 101365850 2/2009
 CN 102253559 A 11/2011
 CN 202108407 U 1/2012
 CN 202157436 U 3/2012
 CN 102797310 A 11/2012
 CN 103649826 A 3/2014
 CN 106125442 A 11/2016
 CN 106837094 A 6/2017
 CN 110515425 A 11/2019
 DE 2113876 A1 10/1972
 DE 3531443 A1 9/1985
 DE 10322561 A1 12/2004
 DE 102006042538 3/2008
 EP 1267029 A1 12/2002
 EP 0676058 B1 4/2003
 EP 1529922 A2 10/2004
 EP 2136409 12/2009
 EP 2348357 7/2011
 FR 2938289 A1 5/2010
 GB 1437198 5/1976
 JP 2000-257352 A 9/2000
 JP 2001-193364 7/2001
 JP 2004-504630 A 12/2004
 JP 2006095040 A 4/2006
 JP 2007-516147 A 6/2007
 JP 2009-544997 A 12/2009
 KR 100909893 B1 7/2009
 KR 101457323 B1 11/2014
 KR 101495310 B1 2/2015
 KR 20150089161 A 8/2015
 KR 20180024214 A 3/2018
 KR 101930724 B1 12/2018
 TW 185608 6/1992
 TW 526383 B 4/2003
 WO WO98/42163 A1 9/1998
 WO WO2002/008826 A1 1/2002
 WO WO02/101188 A1 12/2002
 WO WO2005/076061 8/2005
 WO WO2006/133298 A2 12/2006
 WO WO2006/133298 A3 12/2007
 WO WO2008/043951 4/2008
 WO WO2009/097001 A1 8/2009
 WO WO2009/145876 12/2009
 WO WO2009/148861 12/2009
 WO WO-2009158510 A2 12/2009
 WO WO2010/077409 A2 7/2010
 WO WO2011/010067 1/2011
 WO WO2011/028253 3/2011
 WO WO2011/028254 3/2011
 WO WO2011/050291 4/2011
 WO WO2011/109688 9/2011
 WO WO2012/145155 10/2012
 WO WO2013/090264 6/2013
 WO WO2013/109881 7/2013
 WO WO2013/177575 11/2013
 WO WO2014/032023 2/2014
 WO WO2014/169253 10/2014

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO2015/120063	8/2015
WO	WO2015/134789	9/2015
WO	WO2016/004109 A1	1/2016
WO	WO2017/192881	11/2017
WO	WO2018/098089	5/2018
WO	WO-2018191499 A1	10/2018
WO	WO2019/040809 A1	2/2019
WO	WO-2019141749 A1	7/2019
WO	WO2020/007638 A1	1/2020
WO	WO-2020084083 A1	4/2020
WO	WO-2022072454 A1	4/2022

OTHER PUBLICATIONS

Preliminary Amendment filed Jun. 22, 2017 for U.S. Appl. No. 15/493,003.

Preliminary Amendment filed Sep. 26, 2017 for U.S. Appl. No. 15/597,041.

Preliminary Amendment filed Jun. 26, 2018 for U.S. Appl. No. 16/016,450.

US Preliminary Amendment dated Jan. 23, 2020 in U.S. Appl. No. 16/469,848.

US Office Action dated Nov. 3, 2014 in U.S. Appl. No. 13/456,056.

US Office Action dated Oct. 6, 2014 in U.S. Appl. No. 13/968,258.

US Final Office Action dated Jun. 5, 2015 in U.S. Appl. No. 13/968,258.

US Office Action dated Jan. 21, 2016 in U.S. Appl. No. 13/968,258.

US Notice of Allowance dated Jun. 20, 2016 in U.S. Appl. No. 13/968,258.

US Office Action dated Aug. 8, 2019 in U.S. Appl. No. 16/386,096.

US Office Action dated Jul. 11, 2013 in U.S. Appl. No. 13/312,057.

US Notice of Allowance dated Dec. 13, 2013 in U.S. Appl. No. 13/312,057.

US Office Action dated Jan. 30, 2015 in U.S. Appl. No. 14/152,873.

US Notice of Allowance dated May 19, 2015 in U.S. Appl. No. 14/152,873.

US Office Action dated Mar. 31, 2015 in U.S. Appl. No. 14/196,895.

US Notice of Allowance dated Sep. 18, 2013 in U.S. Appl. No. 13/326,168.

US Notice of Allowance dated Jun. 13, 2014 in U.S. Appl. No. 14/103,660, and allowed claims.

US Notice of Allowance dated Oct. 9, 2014 in U.S. Appl. No. 14/325,290.

US Notice of Allowance dated Feb. 25, 2015 in U.S. Appl. No. 14/325,290.

Office Action dated Feb. 4, 2015 for U.S. Appl. No. 14/591,851.

Final Office Action dated Sep. 11, 2015 for U.S. Appl. No. 14/591,851.

Notice of Allowance dated May 9, 2016 for U.S. Appl. No. 14/591,851.

Notice of Allowance (corrected) dated Jun. 30, 2016 for U.S. Appl. No. 14/591,851.

Notice of Allowance (2nd corrected) dated Aug. 9, 2016 for U.S. Appl. No. 14/591,851.

US Notice of Allowance dated Feb. 15, 2017 for U.S. Appl. No. 15/217,873.

US Notice of Allowance dated Mar. 28, 2018 for U.S. Appl. No. 15/597,041.

US Notice of Allowance dated Jul. 19, 2018 for U.S. Appl. No. 15/597,041.

US Notice of Allowance dated Mar. 14, 2019 for U.S. Appl. No. 16/163,445.

US Notice of Allowance dated Jul. 31, 2019 for U.S. Appl. No. 16/163,445.

US Notice of Allowance dated Dec. 12, 2019 for U.S. Appl. No. 16/163,445.

US Office Action dated Jun. 27, 2016 for U.S. Appl. No. 14/363,769.

US Notice of Allowance dated Nov. 18, 2016 for U.S. Appl. No. 14/363,769.

US Notice of Allowability (Corrected) dated May 10, 2017 for U.S. Appl. No. 14/363,769.

US Notice of Allowance dated Mar. 17, 2017 for U.S. Appl. No. 15/394,637.

US Notice of Allowance dated Oct. 5, 2017 for U.S. Appl. No. 15/493,003.

US Notice of Allowance dated Jan. 31, 2018 for U.S. Appl. No. 15/493,003.

US Notice of Allowance dated Jul. 23, 2018 for U.S. Appl. No. 15/493,003.

US Notice of Allowance dated Oct. 11, 2017 for U.S. Appl. No. 15/228,992.

US Notice of Allowance dated Jan. 25, 2018 for U.S. Appl. No. 15/228,992.

US Notice of Allowance dated May 23, 2018 for U.S. Appl. No. 15/228,992.

US Notice of Allowance dated Oct. 3, 2018 for U.S. Appl. No. 15/228,992.

US Notice of Allowance dated Nov. 14, 2019 for U.S. Appl. No. 16/016,450.

US Notice of Allowance dated Feb. 21, 2020 for U.S. Appl. No. 16/016,450.

US Notice of Allowance dated Dec. 5, 2017 for U.S. Appl. No. 15/243,816.

US Notice of Allowance dated Apr. 11, 2018 for U.S. Appl. No. 15/243,816.

US Notice of Allowance dated Aug. 23, 2018 for U.S. Appl. No. 15/243,816.

US Office Action dated Jul. 15, 2016 for U.S. Appl. No. 14/401,081.

US Final Office Action dated Jan. 10, 2017 for U.S. Appl. No. 14/401,081.

US Office Action dated May 4, 2017 for U.S. Appl. No. 14/401,081.

US Final Office Action Sep. 25, 2017 for U.S. Appl. No. 14/401,081.

US Office Action dated Mar. 8, 2018 for U.S. Appl. No. 14/401,081.

US Final Office Action dated Jul. 5, 2018 for U.S. Appl. No. 14/401,081.

US Office Action dated Dec. 15, 2017 in U.S. Appl. No. 14/423,085.

US Final Office Action dated Aug. 8, 2018 in U.S. Appl. No. 14/423,085.

US Notice of Allowance dated Nov. 29, 2018 in U.S. Appl. No. 14/423,085.

US Notice of Allowance (corrected) dated Apr. 19, 2019 in U.S. Appl. No. 14/423,085.

US Office Action dated Nov. 29, 2019 in U.S. Appl. No. 16/407,080.

US Office Action dated Apr. 16, 2020 in U.S. Appl. No. 16/407,080.

US Final Office Action dated Mar. 6, 2020 in U.S. Appl. No. 16/386,096.

International Search Report and Written Opinion dated Aug. 12, 2013 for PCT/US2013/037644.

International Preliminary Report on Patentability dated Nov. 6, 2014 for PCT/US2013/037644.

International Search Report and Written Opinion dated Jul. 23, 2012, from PCT/US2011/063534.

International Preliminary Report on Patentability dated Jun. 20, 2013, from PCT/US2011/063534.

International Search Report and Written Opinion dated Apr. 1, 2013 from PCT/US2012/068950.

International Preliminary Report on Patentability dated Jun. 26, 2014 from PCT/US2012/068950.

International Search Report and Written Opinion dated May 18, 2015 for PCT/US2015/014479.

International Preliminary Report on Patentability dated Aug. 9, 2016 for PCT/US2015/014479.

International Search Report and Written Opinion for PCT/2013/042765 dated Aug. 23, 2013.

International Preliminary Report on Patentability for PCT/2013/042765 dated Dec. 4, 2014.

International Search Report and Written Opinion dated Nov. 22, 2013 for PCT/US2013/056506.

International Preliminary Report on Patentability dated Mar. 5, 2015 for PCT/US2013/056506.

International Search Report and Written Opinion dated Aug. 19, 2014 for PCT/US2014/033870.

(56)

References Cited

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Apr. 13, 2018 for PCT/US2017/066486.

International Preliminary Report on Patentability dated Jun. 27, 2019 for PCT/US2017/066486.

Canadian Office Action dated May 1, 2019 in CA Application No. 2,882,878.

EP Office Action dated Nov. 4, 2013 for EP Application No. 11846667.1.

European Search Report dated Mar. 3, 2014 for EP Application No. 11846667.1.

European Search Report dated Apr. 2, 2015 for EP Application No. 12858168.3.

European Office Action dated Jul. 1, 2016 for EP Application No. 12858168.3.

European Office Action dated Mar. 13, 2017 for EP Application No. 12858168.3.

European Opposition dated Jun. 25, 2019 to EP Patent No. 2,791,451 (EP Application No. 12858168.3) by GEZE GmbH.

European Opposition Communication dated Jan. 31, 2020 enclosing Letter from Opponent to EP Patent No. 2,791,451 (EP Application No. 12858168.3) by GEZE GmbH.

Partial European Search Report dated Mar. 21, 2016 for EP Application No. 13830992.7.

Extended European Search Report dated Jul. 15, 2016 for EP Application No. 13830992.7.

Extended European Search Report dated Dec. 14, 2018 for EP Application No. 18194665.8.

European Office Action dated Dec. 8, 2017 in EP Application No. 13830992.7.

European Office Action dated Jul. 18, 2018 in EP Application No. 13830992.7.

European Office Action dated Mar. 19, 2019 in EP Application No. 13830992.7.

European Office Action dated Jul. 25, 2019 in EP Application No. 13830992.7.

CN Office Action dated Jun. 3, 2015 in CN Application No. 201280069715.1.

CN Office Action dated Mar. 11, 2016 in CN Application No. 201280069715.1.

CN Office Action dated Mar. 29, 2018 in CN Application No. 201610921855.7.

CN Office Action dated Dec. 18, 2018 in CN Application No. 201610921855.7.

CN Office Action dated Aug. 15, 2019 in CN Application No. 201610921855.7.

CN Office Action dated Mar. 27, 2020 in CN Application No. 201610921855.7.

TW Office Action dated Oct. 28, 2016 in TW Application No. 101147237.

TW Office Action dated Aug. 23, 2018 in TW Application No. 106129194.

TW Office Action dated Jun. 25, 2019 in TW Application No. 106129194.

TW Decision of Rejection dated Jan. 30, 2020 in TW Application No. 106129194.

CN Office Action dated May 26, 2020 in CN Application No. 201780082949.2.

Ernst, Randi, "Gas Filling of IG Units" by FDR Design, Inc. (undated), 37 pages.

Armstrong, Dave, "Smart, energetic glass could take over" in Earth Times, [<http://www.earthtimes.org/energy/smart-energetic-glass-take-over/2866/>] Apr. 12, 2015.

"Smart glass' changes colour and produces electricity", ZeeNewsIndia.com [http://zeenews.india.com/news/sci-tech/smart-glass-changes-colour-and-produces-electricity_1577561.html] Apr. 12, 2015.

Boylestad, R., et al., "Electronic devices and circuit theory (7th Edition)," 1999, pp. 76-82.

McManis, C., "H-Bridges: theory and practice," Chuck's Robotics Notebook, 2004, 3 pp.

McWane, J., "Introduction to Electronics Technology (2nd Edition)," 1981, p. 12 & pp. 228-233.

Westinghouse User's Manual, "LD-325 Series," 2010, 67 pp.

"Velux" Skylights brochure, known as of Jan. 31, 2014, 4 pp.

Halio Smart-Tinting Glass System, Product Data Sheet, Kinestral Technologies, 2017, 4 pp.

Halio Black Insulated Glass Unit, Product Data Sheet, Kinestral Technologies, 2020, 5 pp.

U.S. Appl. No. 16/777,758, filed Jan. 30, 2020, Brown et al.

U.S. Appl. No. 16/883,975, filed May 26, 2020, Mullins et al.

Preliminary Amendment dated Jul. 10, 2020 for U.S. Appl. No. 16/777,758.

CN Office Action dated Jan. 13, 2021 in CN Application No. 201780082949.2.

CN Office Action dated Jul. 21, 2021 in CN Application No. 201780082949.2.

CN Office Action dated Nov. 4, 2020 in CN Application No. 201610921855.7.

European Office Action dated Apr. 30, 2021 for EP Application No. 18194665.8.

European Opposition Communication dated Jun. 2, 2021 from Opponent to EP Patent No. 2,791,451 (EP Application No. 12858168.3) by GEZE GmbH.

Extended European Search Report dated May 14, 2021 for EP Application No. 21152835.1.

Extended European Search Report dated Nov. 2, 2020 in EP Application No. 17880595.8.

Notice of Allowance dated Oct. 13, 2021 in U.S. Appl. No. 16/883,975.

Notice of Allowance dated Oct. 29, 2021 in U.S. Appl. No. 16/469,848.

TW Office Action dated Oct. 26, 2021, in application No. TW20170144418.

TW Search Report received with TW Decision to Grant dated Apr. 27, 2021 in TW Application No. 106129194.

US Corrected Notice of Allowability dated Oct. 22, 2021, in U.S. Appl. No. 16/197,178.

US Final Office Action dated Jan. 6, 2021 in U.S. Appl. No. 16/386,096.

US Final Office Action dated Mar. 31, 2021 in U.S. Appl. No. 16/407,080.

US Final Office Action dated Nov. 25, 2020 in U.S. Appl. No. 16/407,080.

US Notice of Allowance dated Apr. 21, 2021 in U.S. Appl. No. 16/386,096.

US Notice of Allowance dated Jul. 14, 2021 for U.S. Appl. No. 16/197,178.

U.S. Notice of Allowance dated Oct. 18, 2021, in U.S. Appl. No. 16/469,848.

US Notice of allowance dated Sep. 17, 2021, in U.S. Appl. No. 16/168,720.

US Office Action dated Dec. 23, 2020 for U.S. Appl. No. 16/197,178.

US Office Action dated Jan. 7, 2021 in U.S. Appl. No. 16/469,848.

US Office Action dated Mar. 17, 2021 for U.S. Appl. No. 16/168,720.

US Office Action dated Sep. 10, 2020 in U.S. Appl. No. 16/386,096.

US Office Action dated Sep. 21, 2021, in U.S. Appl. No. 16/777,758.

U.S. Appl. No. 17/365,900, inventors Phillips et al., filed on Jul. 1, 2021.

U.S. Appl. No. 63/154,352, Inventors Martinson et al., filed on Feb. 26, 2021.

U.S. Appl. No. 63/170,245, Inventors Martinson et al., filed on Apr. 2, 2021.

U.S. Appl. No. 63/212,483, inventors Martinson et al., filed on Jun. 18, 2021.

EP Office Action dated May 20, 2022, in Application No. EP20170880595.8.

U.S. Non-Final office Action dated Sep. 1, 2022 in U.S. Appl. No. 17/247,662.

U.S. Appl. No. 17/816,548, inventors Brown et al., filed on Aug. 1, 2022.

U.S. Corrected Notice of Allowance dated Apr. 26, 2022 in U.S. Appl. No. 16/777,758.

(56)

References Cited

OTHER PUBLICATIONS

U.S. Corrected Notice of Allowance dated Jan. 31, 2022 in U.S. Appl. No. 16/883,975.
 U.S. Corrected Notice of Allowance dated May 10, 2022 in U.S. Appl. No. 16/168,720.
 U.S. Notice of Allowance dated Jan. 27, 2022 in U.S. Appl. No. 16/168,720.
 U.S. Notice of Allowance dated Mar. 22, 2022 in U.S. Appl. No. 16/777,758.
 U.S. Appl. No. 17/450,950, filed Oct. 14, 2021.
 U.S. Appl. No. 17/660,781, filed Apr. 26, 2022.
 U.S. Appl. No. 17/808,228, inventor Brown., filed on Jun. 22, 2022.
 U.S. Non-Final office Action dated Nov. 25, 2022 in U.S. Appl. No. 17/450,950.
 U.S. Non-Final Office Action dated Nov. 25, 2022 in U.S. Appl. No. 17/578,320.
 U.S. Non-Final Office Action dated Nov. 25, 2022 in U.S. Appl. No. 17/660,781.
 EP Office Action dated Jan. 10, 2023 for EP Application No. 18194665.8.
 European Office Action dated Jan. 30, 2023 in Application No. EP21152835.1.
 International Preliminary Report on Patentability dated Apr. 13, 2023 in PCT Application No. No. PCT/US2021/052587.
 International Search Report and Written Opinion dated Mar. 8, 2022 in PCT Application No. PCT/US2021/052587.
 TW Office Action dated Feb. 23, 2023 in Application No. TW111118193 with English translation.
 U.S. Corrected Notice of Allowance dated Feb. 15, 2023 in U.S. Appl. No. 17/808,228.
 U.S. Notice of Allowance dated Apr. 10, 2023 in U.S. Appl. No. 17/450,950.
 U.S. Notice of Allowance dated Apr. 10, 2023 in U.S. Appl. No. 17/660,781.
 U.S. Notice of Allowance dated Feb. 6, 2023 in U.S. Appl. No. 17/808,228.
 U.S. Notice of Allowance dated Mar. 17, 2023 in U.S. Appl. No. 17/450,950.
 U.S. Notice of Allowance dated Mar. 17, 2023 in U.S. Appl. No. 17/660,781.
 U.S. Appl. No. 18/028,292, inventors Martinson et al., filed on Mar. 24, 2023.
 International Preliminary Report on Patentability dated Mar. 9, 2023 in PCT Application No. PCT/US2021/047809.
 International Search Report and Written Opinion dated Jan. 10, 2022, in Application No. PCT/US2021/047809.

TW Office Action dated Feb. 14, 2022, in Application No. TW110127821 with English Translation.
 TW Office Action dated Sep. 15, 2023, in Application No. TW112120485 with English translation.
 U.S. Corrected Notice of Allowance dated Jul. 17, 2023, in U.S. Appl. No. 17/365,900.
 U.S. Corrected Notice of Allowance dated Jun. 30, 2023, in U.S. Appl. No. 17/660,781.
 U.S. Final office Action dated Jul. 5, 2023 in U.S. Appl. No. 17/578,320.
 U.S. Final Office Action dated Nov. 20, 2023 in U.S. Appl. No. 17/808,228.
 U.S. Non-Final Office Action dated Jul. 5, 2023, in U.S. Appl. No. 17/808,228.
 U.S. Non-Final Office Action dated Oct. 5, 2023, in U.S. Appl. No. 17/576,862.
 U.S. Notice of Allowance dated Jul. 3, 2023 in U.S. Appl. No. 17/450,950.
 U.S. Notice of Allowance dated Jun. 7, 2023 in U.S. Appl. No. 17/365,900.
 U.S. Notice of Allowance dated Nov. 20, 2023 in U.S. Appl. No. 17/578,320.
 U.S. Appl. No. 18/338,842, inventors Brown S.C et al., filed on Jun. 21, 2023.
 International Search Report and Written Opinion dated Feb. 22, 2024 in PCT Application No. PCT/US2023/036098.
 International Search Report and Written Opinion dated Jan. 3, 2024 in PCT Application No. PCT/US2023/031768.
 U.S. Corrected Notice of Allowance dated Aug. 5, 2024 in U.S. Appl. No. 17/578,320.
 U.S. Corrected Notice of Allowance dated Jun. 25, 2024 in U.S. Appl. No. 17/578,320.
 U.S. Non-Final Office Action dated Mar. 28, 2024 in U.S. Appl. No. 17/808,228.
 U.S. Notice of Allowance dated Mar. 20, 2024 in U.S. Appl. No. 17/578,320.
 U.S. Appl. No. 18/744,446, inventors Mullins D, et al., filed on Jun. 14, 2024.
 EP Office Action dated Oct. 29, 2024 in EP Application No. 18194665.8.
 U.S. Non-Final Office Action dated Sep. 20, 2024 in U.S. Appl. No. 18/599,060.
 U.S. Corrected Notice of Allowance dated Feb. 6, 2025 in U.S. Appl. No. 17/808,228.
 U.S. Notice of Allowance dated Jan. 30, 2025 in U.S. Appl. No. 17/808,228.
 U.S. Appl. No. 19/026,565, inventor Brown S.C, filed on Jan. 17, 2025.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

1

**MULTIPURPOSE CONTROLLER FOR
MULTISTATE WINDOWS****CROSS REFERENCE TO RELATED
APPLICATIONS**

An Application Data Sheet is filed concurrently with this specification as part of the present application. Each application that the present application claims benefit of or priority to as identified in the concurrently filed Application Data Sheet is incorporated by reference herein in their entireties and for all purposes.

FIELD

The invention relates generally to electrochromic devices, more particularly to controllers for electrochromic windows.

BACKGROUND

Electrochromism is a phenomenon in which a material exhibits a reversible electrochemically-mediated change in an optical property when placed in a different electronic state, typically by being subjected to a voltage change. The optical property is typically one or more of color, transmittance, absorbance, and reflectance. One well known electrochromic material is tungsten oxide (WO_3). Tungsten oxide is a cathodic electrochromic material in which a coloration transition, transparent to blue, occurs by electrochemical reduction.

Electrochromic materials may be incorporated into, for example, windows for home, commercial and other uses. The color, transmittance, absorbance, and/or reflectance of such windows may be changed by inducing a change in the electrochromic material, that is, electrochromic windows are windows that can be darkened or lightened electronically. A small voltage applied to an electrochromic device (EC) of the window will cause them to darken; reversing the voltage causes them to lighten. This capability allows control of the amount of light that passes through the windows, and presents an opportunity for electrochromic windows to be used as energy-saving devices.

While electrochromism was discovered in the 1960's, EC devices, and particularly EC windows, still unfortunately suffer various problems and have not begun to realize their full commercial potential despite many recent advancements in EC technology, apparatus and related methods of making and/or using EC devices.

SUMMARY OF INVENTION

"Smart" controllers for EC windows are described. Controllers with multiple features can sense and adapt to local environmental conditions. Controllers described herein can be integrated with a building management system (BMS) to greatly enhance the BMS's effectiveness at managing local environments in a building. Controllers described herein may have functionality for providing one, two, three or more of the following features: (a) powering an EC device of an EC window; (b) determining percent transmittance of an EC window; (c) determining size of an EC window; (d) determining temperature of an EC device of an EC window; (e) determining damage to an EC device of an EC window; (f) determining wire length between the EC window controller and an EC window; (g) wireless communication between the EC window controller and a separate communication node; (h) storing and transmitting data relating to an EC window

2

via an RFID tag that is actively or passively powered; (i) storing charge resulting from a transition of an EC device of the EC window and/or direct such charge to a power grid; (j) repairing short related defects of an EC device of an EC window; and (k) heating one or both electrodes of an EC device of an EC window.

In one disclosed aspect, a window controller for controlling one or more windows capable of undergoing reversible optical transitions is configured or designed to provide at least two functions. In certain embodiments may be any two of the following: (a) powering a reversible optical transition of at least one of the one or more windows; (b) determining transmittance of at least one of the one or more windows; (c) determining a size of at least one of the one or more windows; (d) determining temperature of at least one of the one or more windows; (e) determining damage to at least one of the one or more windows; (f) determining wire length between the window controller and at least one of the one or more windows; (g) wireless communication between the window controller and a separate communication node; (h) storing and transmitting data relating to at least one of the one or more windows via an RFID tag that is actively or passively powered; (i) storing charge resulting from a transition of at least one of the one or more windows and/or direct such charge to a power grid; (j) repairing short related defects of at least one of the one or more windows; and (k) heating one or both electrodes of an electrochromic device of at least one of the one or more windows. In various embodiments, the controller is configured or designed to provide at least functions (b), (c), (d) and (e). In other embodiments, the controller is configured or designed to provide at least functions (a), (b), (c), (d) and (e). In still other embodiments, the controller is configured or designed to provide at least functions (a), (b), (d), (g), and (h).

Some disclosed aspects concern a controller as described but provided as part of a larger combination of system of elements such as a building management system containing window controller as described. In another example, an apparatus includes (i) a Building Management System (BMS); (ii) the window controller as described above; and (iii) a multistate electrochromic window. In yet another example, an apparatus includes (i) the window controller as described above, and (ii) an electrochromic window. In various embodiments, the electrochromic window is entirely solid state and inorganic.

Other disclosed aspects pertain to methods of managing a building's systems. Such methods may make use of data collected by a window controller from one or more windows capable of undergoing reversible optical transitions in the building. This data is used as input for adjusting at least one other system of the building, such as HVAC, lighting, security, power, fire suppression and elevator control. In some related methods, the controller provides power to the one or more windows to drive the reversible optical transitions. In a specific embodiment, the method includes the following operations: (a) powering the reversible optical transition of at least one of the one or more windows; (b) determining transmittance of at least one of the one or more windows; (c) determining temperature of at least one of the one or more windows; (d) wireless communication between the window controller and a separate communication node; and (e) storing and transmitting data relating to at least one of the one or more windows via an RFID tag that is actively or passively powered.

In a specific example, the method further involves collecting one or more of the following types of data about the one or more windows: transmittance, size, temperature. In a

different example, the method additionally involves storing data, in the controller, about the one or more windows.

Still other disclosed aspects pertain to window controllers for controlling one or more windows capable of undergoing reversible optical transitions, where the window controllers are configured or designed to provide the following functions: (a) powering a reversible optical transition of at least one of the one or more windows; (b) determining transmittance of at least one of the one or more windows; (c) determining temperature of at least one of the one or more windows; (d) communication between the window controller and a separate communication node; and (e) storing and transmitting data relating to at least one of the one or more windows.

In such controllers, the function of determining temperature of at least one of the one or more windows may be implemented by direct measurement from one or more sensors on the at least one window. Alternatively, the function of determining temperature of at least one of the one or more windows may be implemented by algorithmically inferring temperature from current and/or voltage information from the at least one window.

In such controllers, the function of powering the reversible optical transition may be implemented with pulse width amplifier rendered as an h-bridge or a buck converter. Additionally or alternatively, the function of determining transmittance of at least one of the one or more windows is implemented by direct measurement from one or more sensors on the at least one window. In certain embodiments, the function of storing and transmitting data relating to at least one of the one or more windows may involve reading data from a controller embedded in the at least one window.

These and other features and advantages will be described in further detail below, with reference to the associated drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The following detailed description can be more fully understood when considered in conjunction with the drawings in which:

FIG. 1 depicts a an EC window controller interfaced with a building management system.

FIG. 2 is a schematic representation of a charge storage mechanism of controllers described herein.

FIG. 3 is a schematic of an onboard window controller.

FIG. 4 depicts a different onboard window controller and associated user interface.

FIG. 5 is a cross section schematic of an all solid state and inorganic EC device on a substrate.

DETAILED DESCRIPTION

Conventional EC window controllers have a number of pitfalls. For example, they typically need to be calibrated at the factory for a specific insulated glass unit (IGU) size and wire length—any mismatch at the time of installation can cause problems. Also, conventional window controllers must be hard wired to a building management system and commands to the controller are usually entered by hand at the controller or via a BMS. Sensors on such window controllers typically have separate sensors for providing data feedback for control of the window and for supplying a BMS with data. Conventional EC window controllers also are limited in the type of data they collect from the EC window environment and how they collect such data. Controllers described herein do not suffer from such issues. Multipur-

pose EC window controllers described herein include features that provide easier installation, improved user interfaces, wireless communication and control, higher and consistent performance under varying conditions and capability to enhance environmental conditions, for example, when integrated into a building management system.

EC Devices

Controllers described herein are used to control EC devices, particularly in EC windows. Virtually any EC device will work with multipurpose controllers described herein. Additionally, non-electrochromic optically switchable devices such liquid crystal devices and suspended particle devices. For context, EC device technology is described below in relation to all solid state and inorganic EC devices, particularly low-defectivity all solid state and inorganic EC devices. See the discussion associated with FIG. 5. Because of their low defectivity and robust nature, these devices are particularly well suited for multipurpose controllers described herein. One embodiment is any controller described herein where the controller includes one or more EC devices selected from those described herein.

EC Windows

Electrochromic windows may use one or more EC devices and for those that use more than one EC device, more than one type of EC device can used in a window unit (IGU plus frame and/or accompanying structural support). An EC window will typically have wires or leads that extend from the bus bars of the EC device(s) through a seal in the IGU. These leads may also pass through a window frame. A window controller is wired to the leads, for example, near the EC window or not. EC windows are described in the patent applications incorporated by reference herein. Although not limited to such use, multipurpose controllers described herein find particular use with multistate EC windows, that is, windows that can transition not only between disparate states of coloring and bleaching, but also can transition to one or more intermediate colored states. Particular examples of multistate windows, having two or more EC panes, are described in U.S. patent application Ser. No. 12/851,514, filed on Aug. 5, 2010, and entitled "Multipane Electrochromic Windows," which is incorporated by reference herein for all purposes. One advantage to such multipane EC windows is that the likelihood of defects in each of the EC panes aligning perfectly, and thus being observable to the end user, is quite small. This advantage is accentuated when low-defectivity panes are used. Controllers described herein are well suited for controlling and coordinating the function of one or more EC devices, for example, in a single window.

When used in combination with EC windows that have superior performance characteristics, for example short transition times, low-defectivity, long life, uniform transitions and the like, for example, all solid state and inorganic EC windows, the window controllers described herein significantly augment environmental control in a building. This is particularly true when window controllers are integrated with a BMS. Interrelationships between window performance, microclimate sensing, and environmental control are described in more detail below.

Building Management Systems

Although not limited to this context, multipurpose controllers described herein are well suited for integration with a BMS. A BMS is a computer based control system installed in a building that monitors and controls the building's mechanical and electrical equipment such as ventilation, lighting, power systems, elevators, fire systems, and security systems including automatic door locks, alarms, turnstiles

and the like. A BMS consists of hardware and associated software for maintaining conditions in the building according to preferences set by the occupants and or building manager. The software can be based on, for example, internet protocols and/or open standards.

A BMS is most common in a large building, and typically functions at least to control the environment within the building. For example, a BMS may control temperature, carbon dioxide levels and humidity within a building. Typically there are many mechanical devices that are controlled by a BMS such as heaters, air conditioners, blowers, vents, and the like. To control the building environment, a BMS may turn on and off these various devices under defined conditions. A core function of a typical modern BMS is to maintain a comfortable environment for the building's occupants while minimizing heating and cooling losses. Thus a modern BMS is used not only to monitor and control, but also to optimize the synergy between various systems, for example to conserve energy and lower building operation costs. One embodiment is a multipurpose controller as described herein, integrated with a BMS, where the multipurpose controller is configured to control one or more EC windows. In one embodiment, the one or more EC windows include at least one all solid state and inorganic EC device. In one embodiment, the one or more EC windows include only all solid state and inorganic windows. In one embodiment, the EC windows are multistate EC windows as described in U.S. patent application Ser. No. 12/851,514, filed on Aug. 5, 2010, and entitled "Multipane Electrochromic Windows."

FIG. 1 is a schematic of a BMS, **100**, that manages a number of systems of a building, **101**, including security systems, heating/ventilation/air conditioning (HVAC), lighting of the building, power systems, elevators, fire systems and the like. Security systems may include magnetic card access, turnstiles, solenoid driven door locks, surveillance cameras, burglar alarms, metal detectors and the like. Fire systems may include fire alarms, fire suppression systems including water plumbing control. Lighting systems may include interior lighting, exterior lighting, emergency warning lights, emergency exit signs, and emergency floor egress lighting. Power systems may include main power, backup power generators, and uninterrupted power source (UPS) grids.

Also, BMS **100** manages a window controller, **102**. In this example, window controller **102** is depicted as a distributed network of window controllers including a master controller, **103**, intermediate controllers, **105**, and end or leaf controllers, **110**. For example, master controller **103** may be in proximity to the BMS, and each floor of building **101** may have one or more intermediate controllers **105**, while each window of the building has its own end controller **110**. In this example, each of controllers **110** controls a specific EC window of building **101**.

Each of controllers **110** can be in a separate location from the EC window that it controls, or be integrated into the EC window. For simplicity, only ten EC windows of building **101** are depicted as controlled by window controller **102**. In a typical setting there may be a very large number of EC windows in a building controlled by window controller **102**. Window controller **102** need not be a distributed network of window controllers, for example, a single end controller which controls the functions of a single EC window also falls within the scope of the invention. Advantages and features of incorporating multipurpose EC window controllers as described herein with BMS's are described below in more detail and in relation to FIG. 1 where appropriate.

One aspect of the invention is a BMS including a multipurpose EC window controller as described herein. By incorporating feedback from a multipurpose EC window controller, a BMS can provide, for example, enhanced: 1) environmental control, 2) energy savings, 3) security, 4) flexibility in control options, 5) improved reliability and usable life of other systems due to less reliance thereon and therefore less maintenance thereof, 6) information availability and diagnostics, 7) effective use of staff, and various combinations of these, because the EC windows can be automatically controlled. Such multipurpose controllers are described in more detail below, for example, in the context of being integrated into a BMS, however, the invention is not limited in this way. Multipurpose controllers of the invention may be stand alone controllers, for example, configured to control the functions of a single window or a plurality of EC windows, without integration into a BMS.

Multipurpose Controllers for EC Windows

Window controllers described herein have a microprocessor that controls one or more functions of one or more EC devices of an EC window. In one example, the controller regulates the potential applied to the EC device of the window and may optionally control other functions (alone or combined with other microprocessors) such as recharging a battery used to function the window, wirelessly communicating with a remote control, such as a hand held ("clicker") and/or a BMS.

Because electrochromic windows offer enhanced control of not only the amount of light that enters the interior of a building, but also can serve, for example, to keep heat in, or out, of a building by providing a superior thermal barrier, the benefits of EC windows are enhanced by multipurpose controllers described herein. This is especially true when the controllers are integrated with a BMS, for example, in a building having many EC windows. The benefits are multiplied even more when the multipurpose controllers are not only integrated into a BMS, but also are used to control the functions of multistate EC windows.

In one embodiment, the EC window controller is a multipurpose controller, that is, it can control and/or monitor a number of functions and/or characteristics of one or more EC windows. One way to enhance the capabilities of a BMS which includes an EC window controller into its systems is to have a window controller with such enhanced capabilities providing feedback to the BMS, particularly where the feedback includes a number of parameters and on a more granular, window-by-window basis. These capabilities and/or functions allow synergistic control of, for example, a building's energy requirements and thus can save money above and beyond installing EC windows in a building, with or without conventional automatic control of the windows. The more efficient and versatile the EC windows employed in such a system, the greater energy savings and environmental control. Multistate EC windows are an exemplary choice for BMS's configured with multipurpose controllers.

Embodiments described herein include multipurpose controllers that can control one or more EC devices of an EC window and also one or more functions of each EC device of the associated window. One aspect of the invention is an EC window controller that includes one, two, three or more of the following functions: (a) powering an EC device of the EC window; (b) determining percent transmittance of an EC window; (c) determining size of the EC window; (d) determining temperature of an EC device of the EC window; (e) determining damage to an EC device of the EC window; (f) determining wire length between the EC window controller and the EC window; (g) wireless communication between

the EC window controller and a separate communication node; (h) storing and transmitting data relating to an EC window via an RFID tag that is actively or passively powered; (i) storing charge resulting from a transition of an EC device of the EC window and/or direct such charge to a power grid; (j) repairing short related defects of an EC device of the EC window; and (k) heating one or both electrodes of an EC device of the EC window. Each of these capabilities and functions is described in more detail below.

Powering an EC Device

In some embodiments, the multipurpose controller can power one or more EC devices in an EC window. Typically, this function of the controller is augmented with one or more other functions described in more detail below. Controllers described herein are not limited to those that have the function of powering an EC device to which it is associated for the purposes of control. That is, the power source for the EC window may be separate from the controller, where the controller has its own power source and directs application of power from the window power source to the window. However, it is convenient to include a power source to the controller and configure the controller to power the window directly, because it obviates the need for separate wiring for powering the EC window.

One embodiment is a window controller with one, two, three or more capabilities described herein, where at least one of the capabilities is to control the optical state of an EC window. In various embodiments, there are certain conditions in which current and voltage may to be individually limited, and there is an optimum sequence by which the window is controlled with current limits and/or voltage limits to ensure reasonably quick and non-damaging optical transitions (such as coloring and bleaching an electrochromic window). Examples of such sequences are disclosed in U.S. patent application Ser. No. 13/049,623, naming Pradhan, Mehtani, and Jack as inventors, titled "Controlling Transitions In Optically Switchable Devices" and filed on Mar. 16, 2011, which is incorporated herein by reference in its entirety. As part of the window control process, the controller may receive measurements of current and/or voltage on a window. Once such measurements are made the "control" function may impose appropriate current and/or voltage limits to allow the window to reliability change state.

An example of powering an electrochromic window involves use of a controller having a pulse width modulated amplifier (see FIG. 3) rendered as an "h-bridge" which allows the load to float, be grounded, or be set to any voltage or polarity between the input voltage to the controller and ground. In other embodiments, an EC controller is implemented using a "buck converter" and a separate polarity switch allowing the load to set to any voltage or polarity between the input voltage to the controller and ground. Control may also include current limits during all or part of the transition from one state to another.

Percent Transmittance (% T)

Electrochromic windows have at least one EC device deposited on a glass or other transparent substrate and may have other coatings and panes that are part of an IGU in a window unit. The percent transmittance (% T) of an EC window, typically the integrated transmittance across the visible spectrum for an IGU of an EC window, is an important parameter because it is a measure of how much light is entering a room where the window is installed. When using windows with multistate capability, that is having intermediate states as well as end states of colored and bleached, it may be important to have feedback on the % T

in order to maintain a particular state of transition and/or move to a new color transition according to the desire of the end user. Controllers described herein can measure % T by use of sensors and/or by using current/voltage (I/V) parameters to calculate % T.

Determining the % T can be inferred algorithmically or measured directly using a sensor (e.g. a photometric sensor such as a silicon photodiode) wired to a controller's analog input (AI-Transmittance). See FIGS. 3 and 4, discussed below. Another acceptable sensor is a pyranometer which measures solar irradiance across a larger spectrum of solar radiation.

In one embodiment, the controller includes a sensor on the outside of the building (or window side which will face outside when installed), which serves one or more EC windows and measures the solar spectrum that is entering the window or windows, and one more internal sensors which measure solar irradiance transmitted through the window of each window's IGU. These two energy values are compared in logic in the controller to provide a measure of % T of the window. When one sensor on the outside of the building (or window) is used to serve more than one window, the controller will typically sample solar irradiance on the exterior for use in calculating (effective) % T of each window unit. Sensors are calibrated to their respective IGU's, for example, when installed or replaced in the field.

In one embodiment, the controller employs an outside and an inside sensor for % T for each window. This embodiment is particularly well suited for obtaining more granular feedback on % T for adjusting individual windows' transmissivities accordingly, or for example when the window controller is integrated into a BMS, for adjusting a number of parameters of a building such as HVAC and the like. For example, referring again to FIG. 1, window controller 102 controls five EC windows on side A of building 101, and five windows on side B of building 101. These windows are depicted as being on the top floor of building 101. In this example, intermediate controller 105a controls three windows of one room of building 101, and intermediate controller 105b controls seven windows in another room, two on side A of building 101 and five on side B of building 101. In this example, there is a shadow of a cloud on side B of building 101 because a cloud is obscuring part of the sun's rays. Assuming all the EC windows are of the same size and type, each of the two windows controlled by intermediate controller 105b on side A of building 101 will have the same approximate % T, while each of the five windows controlled by intermediate controller 105b on side B of building 101 will have different % T values because each has a different percent area covered by the shadow from the cloud.

This granularity in data feedback is highly valuable in controlling the environment, for example light, heat, etc., in the room having these seven windows. Intermediate controller 105b uses the % T feedback to maintain the desired environment in the room having these seven windows. Master controller 103 uses the data from intermediate controller 105a and 105b to control the environment of both rooms. For example if the room having the EC windows controlled by intermediate controller 105b is a conference room with many people, the drop in % T due to the cloud's shadow will make the room easier to cool, or for example, lessen the power requirements for darkening the window during a slide presentation in the conference room.

Multipurpose controllers described herein include logic for using this type of feedback for adjusting parameters of the building, via a BMS, for maximizing energy savings. In this example, the energy saved in the conference room due

to the shadow's cooling and darkening effects can be used for transitioning windows in the room controlled by intermediate window controller **105a**, or, for example, the energy can be stored for later use in the windows in the conference room (see "Charge Storage" below).

In one embodiment, % T is inferred from the I/V characteristics of an EC device of the IGU. An IGU or a window can be characterized by the relationship between an electrical pulse sent through the device and how the device behaves before and after the pulse. For example, a direct current (DC) pulse is sent through an EC device of an IGU, and the DC voltage measured across the electrodes (TCO's) of the device as a result provides an I/V characteristic of the device. Environmental factors such as temperature or material characteristics of the device can produce non-linear I/V relationships (and cause hysteresis). Thus EC devices are tested at varying temperatures in order to create data for programming into the logic of controllers of the invention for reference when determining various characteristics of the IGU installed with the controller. In one embodiment, % T is measured in this way. For example, upon power up, the controller sends a pre-determined signal to the IGU of a window and based on the IGU's response to the signal, the % T is calculated by knowing the hysteresis curve of the EC device of the IGU. % T may also be inferred as a function of "ionic current," which can be calculated by measuring the applied current and subtracting the leakage current.

In one embodiment, the open circuit voltage (V_{oc}) of the EC device is measured, then an electrical pulse is applied, followed by measuring the V_{oc} again. The change in the V_{oc} as a result of the electrical pulse allows calculation of % T based on, for example, prior characterization of the device. In one example, the temperature of the device is measured along with V_{oc} and the % T calculated based on the EC device's behavior to such pulses in previous characterization tests.

Size and Temperature of the IGU

The "temperature of an electrochromic device can be inferred algorithmically or measured directly using a sensor (e.g. a thermocouple, thermister, or RTD (resistive thermal device)). In various embodiments, such device is wired or otherwise communicatively coupled to a controller analog input (AI-EC Temperature). See FIGS. 3 and 4.

Using I/V measurements as described above, along with characterization data of the IGU, the size and temperature of the IGU can be determined by controllers described herein. For example, for each of a 20" by 20" window, a 40" by 40" window and a 60" by 60" window, data is collected based on I/V measurements at a number of temperatures. This data is programmed into a window controller which has distinct capabilities and functions with respect to these three window sizes. In the field, during installation, an installer connects the window controller so programmed with an EC window. The controller sends an electrical pulse through the IGU of the window and from the current response, and correlating with the programmed data, the controller can determine the size and temperature of the window. This information is used, for example, to program the controller's logic according to the appropriate window size so that, for example, the appropriate power is used to transition the window during operation.

Damage to the EC Device

In one embodiment, window controllers described herein use I/V characteristics such as those described above to determine damage to an EC device in an IGU of an EC. For example, given the characterized leakage current of the EC device programmed into the controller's logic, when the

controller pings the IGU for I/V feedback, this data can be compared to the data for that IGU from the factory and/or when installed. If the leakage current is greater than it was at installation, then damage to the IGU is likely. The larger the change in I/V characteristics, the more likely damage has occurred to the EC device of the IGU. For example, if the window is damaged by an object hitting the window, controllers described herein would detect the damage (for example a large electrical short) as described and, for example, alert the appropriate repair or security personnel via a BMS. In another example, over time, a number of defects arise in the EC device of an IGU which results in a change in I/V characteristics of the window. This data is fed back to an end user and/or a BMS to inform the appropriate personnel that the IGU needs to be replaced or repaired (see "In Field Short-Related Defect Repair" below).

Wire Length: Ranging

Controllers described herein may have the logic and associated hardware to determine the length of wire between a window and the controller. For example, the controller may apply an electrical signal to the wiring that leads to the one or more IGU's that they control and then measure the change in frequency in the line transmission of the signal. This change in frequency is used to determine the length of the wiring or "range" between the controller and the IGU. Knowing the length of the wiring can be important because the amount of power provided by the source is dependent on how much wiring the power must traverse, as there is a power drop off associated with resistance in the wire. The power source may need to adjust the amount of power it sends to power windows separated from it by differing lengths of wire.

Ranging is typically done between an end controller and an associated IGU in a window. Ranging can be done either actively or passively. In active ranging, the EC device of the IGU is active and can reply to a signal from the controller. In passive ranging, the EC device is switched out of the circuit while ranging is performed.

In certain implementations, a relay is provided at the IGU end of the wire, typically embedded in the IGU secondary seal. The controller sends a message down IGU power lines (using, e.g., MAXIM's OneWire interface, see www.maxim-ic.com/products/1-wire/flash/overview/index.cfm (incorporated by reference)), and the IGU then switches itself out of the circuit for a finite time period to allow the controller to conduct a ranging test. At some predefined time interval the IGU would then switch itself back into the circuit and allow normal control of the IGU to resume.

In some embodiments, the controller is located in or very near the window frame, and thus ranging is not necessary as all end controllers have the same length of wiring between them and their respective IGU's.

Wireless or Wired Communication

In some embodiments, window controllers described herein include components for wired or wireless communication between the window controller and separate communication node. Wireless or wired communications may be accomplished with a communication interface that interfaces directly with the window controller. Such interface could be native to the microprocessor or provided via additional circuitry enabling these functions.

A separate communication node for wireless communications can be, for example, another wireless window controller, an end, intermediate or master window controller, a remote control device, or a BMS. Wireless communication is used in the window controller for at least one of the following operations: programming and/or operating the EC

11

window, collecting data from the EC window from the various sensors and protocols described herein, and using the EC window as a relay point for wireless communication. Data collected from EC windows also may include count data such as number of times an EC device has been activated, efficiency of the EC device over time, and the like. Each of these wireless communication features is described in more detail below.

In one embodiment, wireless communication is used to operate the associated EC windows, for example, via an infrared (IR), and/or radio frequency (Rf) signal. In certain embodiments, the controller will include a wireless protocol chip, such as Bluetooth, EnOcean, WiFi, Zigbee, and the like. Window controllers may also have wireless communication via a network. Input to the window controller can be manually input by a user, either directly or via wireless communication, or the input can be from a BMS of a building of which the EC window is a component.

In one embodiment, when the window controller is part of a distributed network of controllers, wireless communication is used to transfer data to and from each of a plurality of EC windows via the distributed network of controllers, each having wireless communication components. For example, referring again to FIG. 1, master window controller 103, communicates wirelessly with each of intermediate controllers 105, which in turn communicate wirelessly with end controllers 110, each associated with an EC window. Master controller 103 may also communicate wirelessly with the BMS. In one embodiment, at least one level of communication in the window controller is performed wirelessly.

In some embodiments, more than one mode of wireless communication is used in the window controller distributed network. For example, a master window controller may communicate wirelessly to intermediate controllers via WiFi or Zigbee, while the intermediate controllers communicate with end controllers via Bluetooth, Zigbee, EnOcean or other protocol. In another example, window controllers have redundant wireless communication systems for flexibility in end user choices for wireless communication.

Wireless communication between, for example, master and/or intermediate window controllers and end window controllers offers the advantage of obviating the installation of hard communication lines. This is also true for wireless communication between window controllers and BMS. In one aspect, wireless communication in these roles is useful for data transfer to and from EC windows for operating the window and providing data to, for example, a BMS for optimizing the environment and energy savings in a building. Window location data as well as feedback from sensors are synergized for such optimization. For example, granular level (window-by-window) microclimate information is fed to a BMS in order to optimize the building's various environments.

A BMS may also collect data on how many times an EC device is powered and the like for higher level feedback to vendors, for example, on quality control and reliability of the windows installed in the building. However, there are other advantages for such wireless communications. For example, since EC window control and data transfer does not require a large amount of bandwidth, having a distributed network of wirelessly linked windows and controllers offers a very useful opportunity to use the network for other purposes. In one embodiment, the wireless window controller network is used for relaying other, non-EC window related information within a building. Zigbee, for example, uses the window controller to build a mesh network, with

12

other window controllers or other devices like dimmable ballasts, alarm systems, etc. that also employ Zigbee. As such network traffic passing through the window controller may not be related to window control at all, the window controller is simply improving the mesh reliability.

Radio Frequency Identification

Radio-frequency identification (RFID) involves interrogators (or readers), and tags (or labels). RFID tags use communication via electromagnetic waves (typically radio frequency) to exchange data between a terminal and an object, for example, for the purpose of identification and tracking of the object. Some RFID tags can be read from several meters away and beyond the line of sight of the reader.

Most RFID tags contain at least two parts. One is an integrated circuit for storing and processing information, modulating and demodulating a radio-frequency (Rf) signal, and other specialized functions. The other is an antenna for receiving and transmitting the signal.

There are three types of conventional RFID tags: passive RFID tags, which have no power source and require an external electromagnetic field to initiate a signal transmission, active RFID tags, which contain a battery and can transmit signals once a reader has been successfully identified, and battery assisted passive (BAP) RFID tags, which require an external source to wake up but have significant higher forward link capability providing greater range. RFID has many applications; for example, it may be used in enterprise supply chain management to improve the efficiency of EC device inventory tracking and management.

One embodiment is a window controller as described herein including an RFID tag. In one embodiment, the window controller is an end controller associated with a particular IGU. In one embodiment, the RFID tag may be installed on the IGU prior to installation of the window controller, that is, after the IGU and window controller are wired together, the RFID tag is considered part of the window controller. The RFID tag may be active, passive or BAP, depending on the controller's capability to power the RFID. An RFID tag in a window controller as described herein may contain at least one of the following types of data: warranty information, installation information, vendor information, batch/inventory information, EC device/IGU characteristics, customer information, manufactured date, window size, and specific parameters to be used for a particular window.

Such RFID tags obviate the need for stickers on IGU's or windows with such information and some RFID's have rudimentary processing capability such as keeping track of how many times an associated EC device has been activated. An unsophisticated BMS can use such information for environmental control, for example, based on known performance of EC devices as a function of usage. In another example, an installer can use a portable reader to decide which end controller to install in a particular window and/or the controller itself may read the RFID tag and program itself prior to, or upon wiring, to the IGU.

In related embodiments, a controller could also read data from the IGU that has an embedded (e.g. part of a wiring harness, or encapsulated by the secondary seal, etc.) but physically separate RFID tag, EEPROM or FLASH memory chip that would allow various details of the window to be stored with one of these storage devices. Examples of information that may be stored on the tag or memory device embedded in the IGU include warranty information, installation information, vendor information, batch/inventory

information, EC device/IGU characteristics, an EC device cycle count, customer information, manufactured date, and window size.

Charge Storage

The amount of ions held in the counter electrode layer during the bleached state (and correspondingly in the EC layer during the colored state) and available to drive the EC transition depends on the composition of the layers as well as the thickness of the layers and the fabrication method. Both the EC layer and the counter electrode layer are capable of supplying charge (in the form of lithium ions and electrons) in the neighborhood of several tens of millicoulombs per square centimeter of layer surface area. The charge capacity of an EC film is the amount of charge that can be loaded and unloaded reversibly per unit area and unit thickness of the film by applying an external voltage or potential. In some embodiments, window controllers have the capability of storing charge that is produced when an associated EC device undergoes a transition that produces a charge. In other embodiments, the charge produced by the EC window transitions is diverted to a power grid. The charge is then reused, for example, for further transitions of EC windows or, for example where a BMS is integrated with the window controller, for other needs in a building where appropriate. Although the charge produced by an EC window's reverse transition is not large, the charge can be stored in, for example, a battery or sent to a grid where collectively they can be reused, for example, for further window operations including transitions.

FIG. 2 depicts a circuit, **200**, where an IGU, **205**, including an EC device, is powered via a source, **210**. In accord with embodiments described herein, source **210** could be part of the window controller, or not. In this example, when power is supplied to the EC device of IGU **205**, the EC device transitions to a colored state as depicted in the top portion of FIG. 2. Circuit **200** also includes a charge storage device, **215**. Device **215** may be a capacitor or battery, for example. As depicted at the bottom of FIG. 2, when the EC device transitions from colored to bleached, upon discontinuing application of power from source **210**, the circuit is reconfigured, for example using double pole switches, to send the resultant charge that the EC device creates into charge storage device **215**. This stored charge may be used to power further transitions of the EC device in IGU **205**, or to power other aspects of the window controller such as electrical pulses for I/V measurements, ranging pulses and the like. In one embodiment, charge from an EC device's transition is sent to a power grid for combination with other charge from other window's transitions for use in the EC window system or for other purposes. By reusing charge created from the transition of EC windows, the energy efficiency of the windows is enhanced because this charge is not simply wasted by discharging it to ground.

In Field Short-Related Defect Repair ("AC Zap")

As discussed above, EC devices can develop short circuit defects between oppositely charged conductive layers, for example, when a conductive particle makes contact with each of two conductive and electrically charged layers. When a short circuit occurs, electrons rather than ions migrate between the EC layer and the counter electrode, typically resulting in bright spots or halos at the location of, and surrounding, the electrical short when the EC device is otherwise in the colored state. Over time, some EC windows can develop many such electrical shorts and thus degrade in performance due to a significant increase in the leakage current and the appearance of many such bright spots. In certain embodiments, multipurpose window controllers

have the capability to repair short related defects in associated EC devices. This has the great advantage of repairing the IGU rather than replacing it, and repairing the IGU without removing it from the window unit.

In one embodiment, the window controller repairs short related defects in the EC device by sending a high voltage alternating current (AC) through the EC device for a period of time. While not wishing to be bound to theory, it is believed that this repairs the short related defects because during application of the AC current, the frequency of the AC current does not allow ions to move across the EC stack materials, but current does flow, especially through the short related defects. The device does not transition during the application of AC current and therefore is protected from damage, while the high AC current "overloads" the shorts and burns them out, effectively sealing the short related defect areas from further current leakage. This method of in situ repair of short related defects is described in U.S. patent application Ser. No. 12/336,455, naming McMeeking et al. as inventors, and filed on May 2, 2008, which is incorporated herein by reference in its entirety.

Window (Resistive) Heating

The electrode layers of EC devices can be used for resistive heating, for example, by passing a current through one of the electrodes and thus using it as a resistive heating element. In one embodiment, the window controller includes the function of heating one or both electrodes of an EC device of the EC window for resistive heating. Resistive heating is useful for controlling the temperature of IGU for thermal barrier, to defrost the IGU and to control the temperature of the EC device to aid transitions. In one embodiment, window controllers described herein can alternate between transitioning the device and heating the device to aid in transitions. One embodiment is an apparatus including a multipurpose EC window controller as described herein and an EC window where at least one transparent conductive oxide layer of an electrochromic device of the EC window is configured to be heated independently of operation of the EC device.

Examples of Smart Controllers

The above described features of a smart controller may be used alone or in combination with one another. A few specific embodiments will now be described. In one embodiment, the following functions are combined in a single smart controller: (i) powering one or more smart windows, (ii) determining a percent transmittance of the one or more smart windows (at any particular instance in time), (iii) determining the temperature of the one or more smart windows (at any particular instance in time), (iv) providing a communications interface for communicating with the one or more smart windows, and (v) reading data from physically separate memory devices or tags embedded in IGUs associated with the one or more smart windows.

In the embodiment just outlined, the powering a smart window may be accomplished using pulse width modulated amplifier rendered as, for example, an "h-bridge" allowing the window load to float, be grounded, or be set to any voltage or polarity between the input voltage to the controller and ground. The powering function could also be realized using a "buck converter" and a separate polarity switch allowing the load to set to any voltage or polarity between the input voltage to the controller and ground. Control may also include current limits during all or part of the transition from one state to another.

Determining the "percent transmittance" can be could be inferred algorithmically or measured directly using a sensor (e.g. a silicon photo diode) communicating by a wired or

15

wireless interface to an analog input (AI-Transmittance) of the controller. See FIGS. 3 and 4, for example. Determining the “temperature of an electrochromic device” can be inferred algorithmically or measured directly using a sensor (e.g. a thermocouple, thermister, or RTD) communicating by wireless or wired interface to an analog input (AI-EC Temperature) of the controller. See FIGS. 3 and 4, for example. Wireless and/or wired communications may be accomplished using a communication interface that interfaces directly with the smart controller. This may be native to the controller’s microprocessor or additional circuitry enabling these functions. Finally, the exemplary smart controller may read data from an embedded memory devices or tags in the smart windows. Such devices or tags may be part of a wiring harness, encapsulated by the secondary seal, etc. but physically separate from the smart controller. Examples of such devices or tags include RFID tag, EEPROM or FLASH memory chips that would allow all storage of various information about the windows including temperature, number of cycles, manufacturing date, etc.

In another embodiment, the following functions are combined in a single smart controller: (i) powering one or more smart windows, (ii) determining a percent transmittance of the one or more smart windows (at any particular instance in time), (iii) determining the size of one or more windows, (iv) measuring the temperature of the one or more smart windows (at any particular instance in time), (v) determining if damage to the window has occurred (evolved defects), (vi) providing a communications interface for communicating with the one or more smart windows, and (vii) reading data from physically separate memory devices or tags embedded in IGUs associated with the one or more smart windows.

In the embodiment just outlined, the powering a smart window may be accomplished using pulse width modulated amplifier (either h-bridge or buck) as outlined in the previous embodiment but now combined with sensors to simultaneously measure current and voltage delivered to the EC window. Transmittance may be determined algorithmically using a single photo sensor, knowledge of the real-time voltage and current values as the window transitions state and measuring the actual EC window temperature with a sensor in direct contact with the EC coating. Furthermore, direct knowledge of the voltage and current profiles together with measurement of the EC window temperature allows algorithmic determination of the window dimensions. The voltage and current sensing capability allows the controller to compare the current readings against historic values stored in the controller, or conveyed and retrieved via communication with the BMS, to determine if damage to the EC coating has occurred.

In yet another embodiment, a controller is designed or configured to perform the following functions: (i) powering a reversible optical transition of one or more windows; (ii) determining the transmittance of the one or more windows; (iii) determining the temperature of the one or more windows; and (iv) storing and transmitting data relating to the one or more windows via an RFID tag or via memory. A separate implementation provides a controller designed or configured to perform the following functions: (i) powering a reversible optical transition of one or more windows; (ii) determining the size(s) of the one or more windows; (iii) determining the temperature of the one or more windows; (iv) communicating between the controller and a separate communication node; and (v) storing and transmitting data relating to the one or more windows via an RFID tag or via memory. Yet another controller is designed or configured to perform the following combination of functions: (i) power-

16

ing a reversible optical transition of one or more windows; (ii) determining the transmittance of the one or more windows; (iii) determining the size(s) of the one or more windows; (iv) determining the temperature of the one or more windows; (v) determining damage to the one or more windows; (vi) determining a wire length between the window controller and the one or more windows; (vii) communicating between the window controller and a separate communication node; (viii) storing and transmitting data relating to the one or more windows via an RFID tag or via memory; and (ix) repairing short related defects of the one or more windows. In these examples, as well as others given herein, when a controller interfaces with more than one window, the recited functions can apply to any one of the controlled windows, or any combination of these windows, or all of the windows.

Another controller is designed or configured to perform the following functions: (i) powering a reversible optical transition of one or more windows; (ii) determining temperature of the one or more windows; and (iii) heating a device on the one or more windows. The heated device may be the electrochromic devices themselves or a separate device formed on the windows. This embodiment is particularly appropriate for cold weather climates when it is desirable to include relatively large windows. It permits the windows to operate in a relatively untinted state when the flux of solar radiation is sufficient. The additional heating permitted by function (iii) permits use of larger window panes in areas where insulated walls are typically expected in place of large windows.

Examples of Controller Architectures

FIG. 3 is a schematic depiction of a window controller configuration, 300, including an interface for integrating smart windows into, for example, a residential system or a building management system. Such controller may serve as a smart controller of the type herein described or it may serve to provide “local” information from a smart window indirectly controlled by a smart controller. The disclosed embodiment may be implemented in a controller embedded in an IGU, for example. Such controllers are sometimes referred to as “onboard” controllers and are described in more detail in U.S. patent application Ser. No. 13/049,750, titled “Onboard Controller for Multistate Windows” and filed on Mar. 16, 2011, which is incorporated herein by reference in its entirety.

In the depiction of FIG. 3, a voltage regulator accepts power from a standard 24 v AC/DC source. The voltage regulator is used to power a microprocessor (μ p) as well as a pulse width modulated (PWM) amplifier which can generate current at high and low output levels, for example, to power an associated smart window. A communications interface allows, for example, wireless communication with the controller’s microprocessor. In one embodiment, the communication interface is based on established interface standards, for example, in one embodiment the controller’s communication interface uses a serial communication bus which may be the CAN 2.0 physical layer standard introduced by Bosch and widely used today in automotive and industrial applications. “CAN” is a linear bus topology allowing for 64 nodes (window controllers) per network, with data rates of 10 kbps to 1 Mbps, and distances of up to 2500 m. Other hard wired embodiments include MODBUS, LonWorks™, power over Ethernet, BACnet MS/TP, etc. The bus could also employ wireless technology (e.g. Zigbee, Bluetooth, etc.).

In the depicted embodiment, the controller includes a discrete input/output (DIO) function, where a number of

inputs, digital and/or analog, are received, for example, tint levels, temperature of EC device(s), % transmittance, device temperature (for example from a thermistor), light intensity (for example from a LUX sensor) and the like. Output includes tint levels for the EC device(s). The configuration depicted in FIG. 3 is particularly useful for automated systems, for example, where an advanced BMS is used in conjunction with EC windows having EC controllers as described herein. For example, the bus can be used for communication between a BMS gateway and the EC window controller communication interface. The BMS gateway also communicates with a BMS server.

Some of the functions of the discrete I/O will now be described.

DI-TINT Level bit 0 and DI-TINT Level bit 1: These two inputs together make a binary input (2 bits or $2^2=4$ combinations; 00, 01, 10 and 11) to allow an external device (switch or relay contacts) to select one of the four discrete tint states for each EC window pane of an IGU. In other words, this embodiment assumes that the EC device on a window pane has four separate tint states that can be set. For IGUs containing two window panes, each with its own four-state TINT Level, there may be as many as eight combinations of binary input. See U.S. patent application Ser. No. 12/851,514, filed on Aug. 5, 2010 and previously incorporated by reference. In some embodiments, these inputs allow users to override the BMS controls (e.g. untint a window for more light even though the BMS wants it tinted to reduce heat gain).

AI-EC Temperature: This analog input allows a sensor (thermocouple, thermister, RTD) to be connected directly to the controller for the purpose of determining the temperature of the EC coating. Thus temperature can be determined directly without measuring current and/or voltage at the window. This allows the controller to set the voltage and current parameters of the controller output, as appropriate for the temperature.

AI-Transmittance: This analog input allows the controller to measure percent transmittance of the EC coating directly. This is useful for the purpose of matching multiple windows that might be adjacent to each other to ensure consistent visual appearance, or it can be used to determine the actual state of the window when the control algorithm needs to make a correction or state change. Using this analog input, the transmittance can be measured directly without inferring transmittance using voltage and current feedback.

AI-Temp/Light Intensity: This analog input is connected to an interior room or exterior (to the building) light level or temperature sensor. This input may be used to control the desired state of the EC coating several ways including the following: using exterior light levels, tint the window (e.g. bright outside, tint the window or vice versa); using and exterior temperature sensor, tint the window (e.g. cold outside day in Minneapolis, untint the window to induce heat gain into the room or vice versa, warm day in Phoenix, tint the widow to lower heat gain and reduce air conditioning load).

AI-% Tint: This analog input may be used to interface to legacy BMS or other devices using 0-10 volt signaling to tell the window controller what tint level it should take. The controller may choose to attempt to continuously tint the window (shades of tint proportionate to the 0-10 volt signal, zero volts being fully untinted, 10 volts being fully tinted) or to quantize the signal (0-0.99 volt means untint the window, 1-2.99 volts means tint the window 5%, 3-4.99 volts equals 40% tint, and above 5 volts is fully tinted). When a signal is

present on this interface it can still be overridden by a command on the serial communication bus instructing a different value.

DO-TINT LEVEL bit 0 and bit 1: This digital input is similar to DI-TINT Level bit 0 and DI-TINT Level bit 1. Above, these are digital outputs indicating which of the four states of tint a window is in, or being commanded to. For example if a window were fully tinted and a user walks into a room and wants them clear, the user could depress one of the switches mentioned and cause the controller to begin untinting the window. Since this transition is not instantaneous these digital outputs will be alternately turned on and off signaling a change in process and then held at a fixed state when the window reaches its commanded value.

FIG. 4 depicts a controller configuration 402 having a user interface. For example where automation is not required, the EC window controller, for example as depicted in FIG. 3, can be populated without the PWM components and function as I/O controller for an end user where, for example, a keypad, 404, or other user controlled interface is available to the end user to control the EC window functions. The EC window controller and optionally I/O controllers can be daisy chained together to create networks of EC windows, for automated and non-automated EC window applications.

In certain embodiments, the controller 402 does not directly control a window but may indirectly control one or more windows. The controller may direct or coordinate the operation of one or more other controllers such as controllers 103 and/or 105 in FIG. 1.

30 Solid-State and Inorganic EC Devices

A description of EC devices is provided for context, because window controllers described herein include functions that use features of EC devices, for example, in order to measure parameters such as temperature, window size, percent transmission and the like, as well as using EC devices in a non-conventional sense, for example, using an electrode of an EC device for resistive heating. Thus structure and function of EC devices is described in the context of solid-state and inorganic EC devices, although controllers described herein can control any EC device. Further, as noted above, such controllers may be used with windows having non-electrochromic optically switchable devices such as liquid crystal devices and suspended particle devices.

FIG. 5 depicts a schematic cross-section of an EC device, 500. Electrochromic device 500 includes a substrate, 502, a conductive layer (CL), 504, an EC layer (EC), 506, an ion conducting layer (IC), 508, a counter electrode layer (CE), 510, and a conductive layer (CL), 514. Layers 504, 506, 508, 510, and 514 are collectively referred to as an EC stack, 520. A voltage source, 516, operable to apply an electric potential across EC stack 520, effects the transition of the EC device from, for example, a bleached state to a colored state (depicted). The order of layers can be reversed with respect to the substrate. The EC device 500 may include one or more additional layers (not shown) such as one or more passive layers. Passive layers used to improve certain optical properties may be included in EC device 500. Passive layers for providing moisture or scratch resistance may also be included in the EC device 500. For example, the conductive layers may be treated with anti-reflective or protective oxide or nitride layers. Other passive layers may serve to hermetically seal the EC device 500.

Such all solid-state and inorganic EC devices, methods of fabricating them, and defectivity criterion are described in more detail in U.S. patent application Ser. No. 12/645,111, entitled, "Fabrication of Low-Defectivity Electrochromic

Devices,” filed on Dec. 22, 2009 and naming Mark Kozlowski et al. as inventors, and in U.S. patent application Ser. No. 12/645,159, entitled, “Electrochromic Devices,” filed on Dec. 22, 2009 and naming Zhongchun Wang et al. as inventors, both of which are incorporated by reference herein for all purposes. In accordance with certain embodiments, EC devices where the counter electrode and EC electrodes are formed immediately adjacent one another, sometimes in direct contact, without separately depositing an ionically conducting layer, are used with controllers described herein. Such devices, and methods of fabricating them, are described in U.S. patent application Ser. Nos. 12/772,055 and 12/772,075, each filed on Apr. 30, 2010, and in U.S. patent application Ser. Nos. 12/814,277 and 12/814,279, each filed on Jun. 11, 2010—each of the four applications is entitled “Electrochromic Devices,” each names Zhongchun Wang et al. as inventors, and each is incorporated by reference herein in their entireties. These devices do not have an IC layer per se, but function as if they do.

It should be understood that the reference to a transition between a bleached state and colored state is non-limiting and suggests only one example, among many, of an EC transition that may be implemented. The term “bleached” refers to an optically neutral state, for example, uncolored, transparent or translucent. Still further, unless specified otherwise herein, the “color” of an EC transition is not limited to any particular wavelength or range of wavelengths. In the bleached state, a potential is applied to the EC stack **520** such that available ions in the stack that can cause the EC material **506** to be in the colored state reside primarily in the counter electrode **510**. When the potential on the EC stack is reversed, the ions are transported across the ion conducting layer **508** to the EC material **506** and cause the material to enter the colored state.

In this example, the materials making up EC stack **520** are both inorganic and solid state. Because organic materials tend to degrade over time, inorganic materials offer the advantage of a reliable EC stack that can function for extended periods of time. Materials in the solid state also offer the advantage of not having containment and leakage issues, as materials in the liquid state often do. One embodiment is an apparatus including a controller as described herein and an EC device that is all solid state and inorganic.

Referring again to FIG. 5, voltage source **516** is typically a low voltage electrical source and may be configured in multipurpose controllers to operate in conjunction with other components such as sensors, RFID tags, and the like. In certain embodiments, multipurpose controllers described herein include the capability to supply power to an EC device, for example, as voltage source **516**.

A typical substrate **502** is glass. Suitable glasses include either clear or tinted soda lime glass, including soda lime float glass. Typically, there is a sodium diffusion barrier layer (not shown) between substrate **502** and conductive layer **504** to prevent the diffusion of sodium ions from the glass into conductive layer **504**.

On top of substrate **502** is conductive layer **504**. Conductive layers **504** and **514** may be made from a number of different materials, including conductive oxides, thin metallic coatings, conductive metal nitrides, and composite conductors. Typically, conductive layers **504** and **514** are transparent at least in the range of wavelengths where electrochromism is exhibited by the EC layer. Transparent conductive oxides include metal oxides and metal oxides doped with one or more metals. Since oxides are often used for these layers, they are sometimes referred to as “transparent conductive oxide” (TCO) layers.

The function of the TCO layers is to spread an electric potential provided by voltage source **516** over surfaces of the EC stack **520** to interior regions of the stack, with very little ohmic potential drop. The electric potential is transferred to the conductive layers through electrical connections to the conductive layers. Typically, bus bars, one in contact with conductive layer **504** and one in contact with conductive layer **514**, provide the electric connection between the voltage source **516** and the conductive layers **504** and **514**. Generally, various thicknesses of the layers of the conductive material may be employed so long as they provide the necessary electrical properties (for example, conductivity) and optical properties (for example, transmittance). Typically, the conductive layers **504** and **514** are as thin as possible to increase transparency and to reduce cost. Preferably, the thickness of the each conductive layer **504** and **514** is also substantially uniform.

The sheet resistance (R_s) of the conductive layers is also important because of the relatively large area spanned by the layers, for example, when the device is part of an electrochromic window. The sheet resistance of conductive layers **504** and **514** may be between about 5 Ohms per square to about 30 Ohms per square. In general, it is desirable that the sheet resistance of each of the two conductive layers be about the same. The conductive layers can be exploited for resistive heating of the device, by virtue of their sheet resistance, rather than for functioning the EC device of which they are a part. In one embodiment, multipurpose controllers described include the function of resistive heating using one or more conductive layers of an EC device. Such resistive heating as described in more detail below.

Overlaying conductive layer **504** is EC layer **506**. The EC layer may contain any one or more of a number of different EC materials, including metal oxides. An EC layer **506** including a metal oxide is capable of receiving ions transferred from counter electrode layer **510**. The thickness of the EC layer **506** depends on the EC material selected for the EC layer. The EC layer **506** may be about 50 nm to 2,000 nm thick.

An ion conducting layer **508** overlays EC layer **506**. Any suitable material may be used for the ion conducting layer **508** provided it allows for the passage of ions between the counter electrode layer **510** to the EC layer **506** while substantially preventing the passage of electrons.

On top of ion conducting layer **508** is counter electrode layer **510**. The counter electrode layer may include one or more of a number of different materials that are capable of serving as reservoirs of ions when the EC device is in the bleached state. During an EC transition initiated by, for example, application of an appropriate electric potential, the counter electrode layer transfers some or all of the ions it holds to the EC layer, via the IC layer, changing the EC layer to the colored state. Concurrently, in the case of nickel tungsten oxide (NiWO), the counter electrode layer colors with the loss of ions. Because counter electrode layer **510** contains the ions used to produce the EC phenomenon in the EC material when the EC material is in the bleached state, the counter electrode preferably has high transmittance and a neutral color when it holds significant quantities of these ions. When charge is removed from a counter electrode **510** made of NiWO (that is, ions are transported from the counter electrode **510** to the EC layer **506**), the counter electrode layer will turn from a transparent state to a brown colored state. Thus when potential is applied to an electrochromic device, an optical transition occurs. Likewise, when an EC device transitions in the other direction, it behaves as a battery, and produces an electrical charge by virtue of the

21

ions traversing the IC layer in the opposite direction, current flows from the EC device. Multipurpose controllers described herein exploit this phenomenon by capturing and/or diverting this charge to a power grid for reuse.

Although the foregoing invention has been described in some detail to facilitate understanding, the described embodiments are to be considered illustrative and not limiting. It will be apparent to one of ordinary skill in the art that certain changes and modifications can be practiced within the scope of the appended claims.

We claim:

1. A window controller for controlling a window, the window controller comprising one or more microprocessors configured to:

determine a wire length between the controller and the window;

actively and reversibly power a reversible optical transition between at least a bleached end state and a colored end state of the window, wherein powering is based, at least in part, on the determined length of the wire, wherein the window comprises a first conductive layer, a second conductive layer, and an electrochromic layer between the first and second conductive layers, wherein powering the reversible optical transition comprises applying a DC voltage to the first and second conductive layers to provide an electrical potential across the electrochromic layer establishing a load, wherein the load is floated; and

communicate with a communication node.

2. The window controller of claim 1 wherein determining the wire length is performed actively.

22

3. The window controller of claim 1 wherein determining the wire length is performed passively.

4. The window controller of claim 1 wherein the one or more microprocessors are further configured to measure a transmittance of the window and wherein powering is further based, at least in part, on the measured transmittance.

5. The window controller of claim 1 wherein the one or more microprocessors are further configured to measure a size of the window and wherein powering is further based on the measured size.

6. The window controller of claim 1 wherein the one or more microprocessors are further configured to:

determine damage to the window based on current information; and

in response to determining damage, repair the window by sending a high voltage current through the window.

7. The window controller of claim 1 wherein the one or more microprocessors are further configured to determine a temperature of the window based on current information.

8. The window controller of claim 1 wherein the one or more microprocessors are further configured to store charge resulting from a transition of the window and to direct such charge to a power grid.

9. The window controller of claim 1 wherein the one or more microprocessors are further configured to heat the window by passing current through one or more electrodes at the window.

10. The window controller of claim 1 wherein the one or more microprocessors are further configured to store and transmit data relating to the window via a radio-frequency identification tag or via memory.

* * * * *