US012747742B1

(12) **United States Patent**
Scott et al.

(10) **Patent No.: US 12,747,742 B1**
(45) **Date of Patent: Sep. 29, 2026**

(54) **SYSTEM FOR CONTROLLING TEMPERATURE AND PRESSURE INSIDE A PROPELLANT TANK**

(71) Applicant: **United Launch Alliance, L.L.C.**, Centennial, CO (US)

(72) Inventors: **Joel Cy Scott**, Lone Tree, CO (US); **Jeffrey J. Rogers**, Littleton, CO (US)

(73) Assignee: **United Launch Alliance, L.L.C.**, Centennial, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 14 days.

(21) Appl. No.: **18/907,198**

(22) Filed: **Oct. 4, 2024**

Related U.S. Application Data

(60) Division of application No. 17/850,839, filed on Jun. 27, 2022, now Pat. No. 12,110,911, which is a continuation-in-part of application No. 17/584,738, filed on Jan. 26, 2022, now Pat. No. 11,982,406.

(60) Provisional application No. 63/147,092, filed on Feb. 8, 2021, provisional application No. 63/147,097, filed on Feb. 8, 2021.

(51) **Int. Cl.**
F04F 5/10 (2006.01)
F04F 5/02 (2006.01)
F04F 5/48 (2006.01)

(52) **U.S. Cl.**
CPC ***F04F 5/10*** (2013.01); ***F04F 5/02*** (2013.01); ***F04F 5/48*** (2013.01)

(58) **Field of Classification Search**
CPC F04F 5/02–5/36; F04F 5/48–5/52; F02K 9/44; F02K 9/48; F02K 9/50; F02K 9/58; B64G 1/402; B64G 1/4021; F17C 13/00
USPC 417/76, 188
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,159,957 A * 11/1915 Kneass F04F 5/469 417/189
1,988,635 A * 1/1935 Sutton D06F 71/34 417/188
2,399,670 A * 5/1946 Freygang B63C 9/18 417/188
5,624,239 A * 4/1997 Osika F04F 5/20 15/409
6,151,900 A 11/2000 Lak et al.
6,315,000 B1 11/2001 Goodyear
7,255,136 B2 8/2007 Templet et al.
(Continued)

FOREIGN PATENT DOCUMENTS

GB 2450565 12/2008

OTHER PUBLICATIONS

"Basic principles of vacuum technology, brief overview," Festo, Jul. 2013, 54 pages [retrieved online Feb. 18, 2022 from: www.festo.com/net/SupportPortal/Files/286804/Basic_Vacuum_Technology_Principles.pdf].
(Continued)

Primary Examiner — Bryan M Lettman
(74) *Attorney, Agent, or Firm* — Sheridan Ross P.C.

(57) **ABSTRACT**

Apparatus, systems and methods for pumping fluids, including for the purpose of controlling temperature and pressure in a propellant tank include a type of novel ejector, consisting of a typical ejector and an isolation valve integrated on the inlet of secondary fluid to an ejector, or suction chamber. The inlet valve is actuated by the application of the primary motive fluid pressure to a motive nozzle. The ejector is configured to operate when submerged in the secondary fluid.

11 Claims, 17 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

7,536,864	B2	5/2009	Wolfe et al.	
8,083,495	B2	12/2011	Whaling et al.	
8,142,169	B2	3/2012	Whaling et al.	
9,140,470	B2	9/2015	Verma et al.	
9,175,688	B2	11/2015	Neel	
11,982,406	B1	5/2024	Rogers et al.	
12,110,911	B1	10/2024	Scott et al.	
2004/0144102	A1	7/2004	Lozano et al.	
2015/0152885	A1	6/2015	Dennis	
2019/0309996	A1	10/2019	Chancery et al.	
2020/0173608	A1*	6/2020	Heisch	F17C 5/02

OTHER PUBLICATIONS

Official Action for U.S. Appl. No. 17/584,738, dated Oct. 10, 2023 8 pages Restriction Requirement.
Notice of Allowance for U.S. Appl. No. 17/584,738, dated Dec. 20, 2023 8 pages.
Official Action for U.S. Appl. No. 17/850,839, dated Aug. 3, 2023 8 pages Restriction Requirement.
Official Action for U.S. Appl. No. 17/850,839, dated Oct. 25, 2023 13 pages.
Notice of Allowance for U.S. Appl. No. 17/850,839, dated Jun. 28, 2024 9 pages.

* cited by examiner


10
60
34
30
74
12
32
50
36
40
38
48
44
22
16
30'
34'
74'
14
32'
50'
36'
42
38'
24
44'
20
18

FIG.1



FIG.2A



FIG.2B



FIG.2C



FIG.2D



FIG.2E



FIG.3



FIG.4


100
112
150
160
130
140
148
122
144
160'
114
130'
116
150'
142
124
148'
120
144'
118

FIG.5


10
112
150
130
160
180
140
148
122
114
150'
160'
130'
116
180'
148'
142
124
118

FIG.6



FIG.7



FIG.8



FIG.9



FIG.10



FIG.11



FIG.12


300
340
346a
334
332
352
360
362
364
354
340a
330
346b
333
364
302
340a
348
346
350
344

FIG.13

SYSTEM FOR CONTROLLING TEMPERATURE AND PRESSURE INSIDE A PROPELLANT TANK

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional application of and claims the benefit of priority from U.S. patent application Ser. No. 17/850,839 filed Jun. 27, 2022 and entitled "Ejector with Integrated Isolation Valve," U.S. patent application Ser. No. 17/584,738 filed Jan. 26, 2022 and entitled "Method and Apparatus for Controlling Temperature and Pressure Inside a Propellant Tank," now issued U.S. Pat. No. 11,982,406, and which claims the benefit of priority from U.S. Provisional Patent Application No. 63/147,092 filed Feb. 8, 2021 entitled "Ullage Conditioning System Without Pressurization," and U.S. Provisional Patent Application No. 63/147,097 filed Feb. 8, 2021 entitled "Ullage Conditioning System With Pressurization," the entire disclosures of which are hereby expressly incorporated by reference in their entireties.

FIELD OF THE INVENTION

The present disclosure relates to the field of mechanical engineering and, more particularly, to fluid devices and, more particularly, to ejectors. The present disclosure improves upon the prior art of ejectors to add functionality.

BACKGROUND OF THE INVENTION

Ejectors placed in a process often require an isolation valve upstream of the secondary fluid inlet in order for the process fluid to not leak or pass through the ejector when the ejector is not operating. This isolation valve is normally a separate piece of hardware that has its own actuator and actuation operation.

One common example of this configuration is a line priming operation whereby an ejector is used to suction fluid into an unprimed line before the fluid process can start. Once the line is primed, the ejector will isolate from the process with an isolation valve so that process fluids do not continue to leak out of the system through the non-operating ejector. This system and method is often employed in pump priming. In this example, the pump must be primed with fluid in order to start the pump, but once the pump is running it will generate a syphon and keep itself primed though out operation.

Another example that may require an isolation valve upstream of the ejector's secondary fluid inlet is a vacuum application. Ejectors are used to lower the pressure of a fluid volume to create pressures that are lower than atmospheric pressure. Pressures lower than local atmospheric pressure will be termed vacuum henceforth. In this case, the ejector may be run continuously to maintain the vacuum while a process is being used, e.g. in-space rocket engine testing or thermal vacuum testing, or the ejector may be isolated from the fluid volume once the vacuum is achieved. In the latter case, an operating ejector may negatively affect the process that is carried out under vacuum conditions and as such it must be non-operational and isolated to preserve the vacuum.

In any operation that requires the isolation valve to be closed when the ejector is not in operation, the isolation valve and the ejector may be combined into a single integrated unit.

In another application, the ejector may be used as a pump to move process fluid from the main process to a secondary process. In such an application, the ejector operates in the same manner as in previous examples, and the secondary fluid inlet valve is again used to isolate the ejector from the main process when not in use.

Ejectors may be used to safely fill a propellant tank without venting. On earth, where there is a constant gravitational field, liquid propellant transfer during a tank fill is straight forward since the liquid loads from the bottom up and allows a vent valve at the top of the tank to vent the displaced gas volume, and the boiled off gases in the case of super cold propellants. Super cold propellants are those that change from a liquid phase to a gas phase at temperatures below zero degrees Centigrade or 32 degrees Fahrenheit. Cryogens are an example of a super cold propellant. In most rocket stage tanks, whether in a microgravity environment such as on-orbit, in space, or on the earth's surface generally, propellant in a tank could be in two phases, namely, a liquid phase and a gaseous phase. For purposes of this disclosure, the solid phase is not considered. A super cold liquid propellant transferred into the tank will flash boil as the liquid enters the warmer tank and will result in increased tank pressure that must be controlled. Moreover, in a microgravity environment, the liquid portion of the propellant could be anywhere within the tank which means that venting to control the pressure would likely vent valuable quantities of the precious liquid propellant rather than venting the boil off gas or gaseous phase propellant making the transfer process in space inefficient. Aspects of the present disclosure provide a system and method of controlling the ullage temperature and pressure during microgravity propellant transfer allowing for propellant fill without venting of the tank.

A different issue associated with the use of super cold propellants in space travel is ullage pressure collapse (UPC). In one example, UPC can occur in a microgravity environment when the super cold liquid propellant unsettles and moves about the propellant tank. This phenomenon may occur, for example, when an upper stage is separated from a booster followed by an upper stage or second stage engine start where the upper or second stage accelerates. Conversely, UPC could also be caused by a deceleration. Unsettled super cold liquid propellant may crest and rain through or mix with the ullage causing the ullage to cool significantly. In turn, pressure within the propellant tank drops significantly and, in some cases, uncontrollably. The result can lead to a structural failure of the propellant tank and intermediate bulkhead, or engine malfunction. Higher ullage volumes could exacerbate the issue. Aspects of the present disclosure provide a system and method of controlling the ullage temperature and pressure to eliminate UPC.

Ejectors used for ullage conditioning benefit from being submerged in the liquid of the process or propellant tank, however, this causes the ejector to be flooded when it is not operating. A flooded ejector used for ullage conditioning adversely effects its performance in this task by creating an inconsistent startup transient. The slug of liquid that is ejected from the ejector during this startup can cause an undesired ullage collapse.

These same systems and methods may also be used on the launch pad, on earth, during tank fill operations to condition ullage and prevent catastrophic over pressurization events.

A microgravity environment is a spatial environment in which acceleration is minimal or nearly zero. Such environments are imposed on objects while within earth's gravita-

tional influence when the object is in free fall, or outside of earth's gravitational influence when the object has little to no acceleration.

SUMMARY OF THE INVENTION

Ejectors (also known as jet pumps) are simple devices for controlling the entrainment into and the discharge from a ducted coaxial jet. The suction fluid, or secondary fluid or process fluid, is pumped by means of the momentum of the driving motive fluid jet. A high pressure motive fluid is required to generate the high velocity motive jet. Embodiments according to the present disclosure make additional use of this high pressure motive fluid source by pneumatically actuating and opening a valve at the inlet of the suction chamber simultaneously as it generates the high velocity jet. The valve presented in the preferred embodiment is a poppet valve that is actuated by a normally-closed, pneumatic, spring-return, actuator. Actuator opening pressure must be able to overcome both the spring-return, in addition to the forces imposed on the poppet by the secondary fluid. Any other form of valve maybe utilized, however the pneumatic actuator and its orientation may need to change, for example: a ball valve or a butterfly valve. These quarter-turn valves would require an actuator with a mechanical linkage to convert linear motion to rotational motion that are required. Embodiments of the present disclosure, then, effectively allow the user to actuate both an ejector and an inlet valve with one single control valve that initiates the flow of the motive fluid.

Ejectors according to embodiments of the present disclosure are comprised of at least the following parts: a secondary fluid inlet valve and actuator, a suction chamber, a motive fluid inlet, a motive fluid nozzle, and a mixing tube.

In at least some embodiments, the secondary fluid inlet valve is a normally closed, pneumatically actuated, spring return poppet valve. The actuator receives fluid power from the motive fluid inlet, which is also required by the ejector. The valve poppet isolates the suction chamber from the secondary fluid. Once actuated, the poppet translates to place the suction chamber in fluid communication with the secondary fluid. Once motive fluid pressure is decreased, a spring acting on the actuator piston translates the piston back to its normal position, which consequently translates the valve poppet closed isolating the ejector from the secondary fluid.

The suction chamber is a fluid volume where static pressure is locally reduced to draw in and entrain the secondary fluid. The suction chamber is in fluid communication with the motive fluid nozzle and mixing tube. Once motive fluid is emitted from the motive fluid nozzle at a high velocity it lowers static pressure in the suction chamber which induces flow of the secondary fluid into the suction chamber, through the open valve, and into contact with the high velocity motive fluid.

The motive fluid inlet is a fluid volume that accepts the motive fluid and distributes it to both the motive fluid nozzle and the secondary fluid inlet valve actuator.

The motive fluid nozzle is a nozzle that accelerates the motive fluid to a sufficiently high velocity at its exit to reduce local pressure. The nozzle may be an orifice, a nozzle, or a converging/diverging nozzle.

The mixing tube is in fluid communication with the motive fluid, secondary fluid, and the downstream process. In the mixing tube the sufficiently high velocity motive fluid is in contact with the secondary fluid. At the motive fluid nozzle exit plane, the two fluid streams are coflowing jets that are in contact with one another. The two fluid streams exchange momentum via fluid mixing, which lowers the velocity of the motive fluid, but increases the velocity of the secondary fluid. This momentum exchange effectively mixes these two fluid streams in the mixing tube and ejects the mixture out the end of the mixing tube.

Aspects of the present disclosure provide the ability to refuel cryogenic propulsion stages on-orbit which, in turn facilitates space transportation beyond low earth orbit. The ability to efficiently transfer cryogens between earth-to-orbit tanker vehicles, orbiting propellant depots, and space transportation vehicles is an alternate for earth departure missions rather than developing larger rockets.

Aspects of the present disclosure provide the ability to eliminate UPC by conditioning the temperature and pressure of the ullage and to extract thermal potential energy from the ullage and prevent ullage pressure collapse. The present invention can be utilized to condition the ullage gas on the ground and in flight.

In one embodiment, one or more aerodynamic pumps are associated with a propellant tank. In a preferred embodiment, the aerodynamic pump is a jet pump. A pressurized motive fluid source supplies a condensable motive fluid to an inlet of the aerodynamic pump. The pressure of the motive fluid source must be greater than the pressure in the propellant tank to allow flow. A larger pressure difference is preferred. Liquid propellant within the propellant tank is also in fluid communication with an inlet of the aerodynamic pump. In operation, the condensable motive fluid is accelerated through a nozzle to create a high velocity fluid stream or jet that reduces local static pressure and thereby creates a vacuum. The low static pressure syphons or suctions liquid cryogen out of the liquid space within the propellant tank. The syphoned liquid propellant is entrained or mixed into the flow of the high velocity motive fluid within a mixing tube or chamber. The two fluids mix to form a highly atomized spray of both the liquid cryogen propellant and the motive fluid through momentum transfer between the coflowing fluids. The mixed solution is then exhausted into the ullage space of the propellant tank where evaporation of the atomized spray lowers the ullage gas temperature. The condensable motive fluid is cooled by the mixing with the liquid cryogenic propellant. Because the resulting mixture has a lower temperature than the ullage, the temperature of a localized volume of the ullage is reduced and the total pressure of the ullage is reduced or at least not increased. Continued operation the aerodynamic pump expands the localized volume of reduced temperature ullage and continues to reduce the pressure within the propellant tank. The motive fluid can be pulsed repeatedly until the ullage gas is at the desired conditions or throttled proportionally until the desired operating conditions of the system are attained. Thus, pressure within the propellant tank may be controlled without venting of the propellant tank and without loss of propellant.

According to aspects of this embodiment, the motive fluid may be the same as the propellant, for example liquid hydrogen or some other cryogenic propellant, or it may be some different fluid that does not adversely affect the tanked propellants, for example a fluid that may go into solution with the propellants. The motive fluid source may be external or internal to the propellant tank. The one or more aerodynamic pumps may be located at a perimeter of the propellant tank or at any other location within the propellant tank. The aerodynamic pump or, at a minimum, the mixing chamber of the aerodynamic pump, may be configured to move, oscillate or rotate relative to the interior of the

propellant tank to eject the mixture of atomized motive fluid and liquid propellant over a larger localized volume.

The system of this embodiment is operated only by the introduction of the higher pressure motive fluid. No moving parts are required other than a valve to control the motive fluid supply. This system is ideally suited for use in the reduced or microgravity environment of space.

In another embodiment, an atomizer replaces the jet pump. Operation of the system remains similar. A pressurized primary fluid is accelerated, atomized, and ejected into the ullage of the propellant tank. Because the atomized spray has a temperature lower than the ullage, a localized volume of the ullage is cooled and pressure within the propellant tank is reduced. Continued operation the atomizer expands the localized volume of reduced temperature ullage and continues to reduce the pressure within the propellant tank. The fluid entering the atomizer can be pulsed repeatedly until the ullage gas is at the desired conditions or throttled proportionally until the desired operating conditions of the system are attained. Thus, pressure within the propellant tank may be controlled without venting of the propellant tank and without loss of propellant.

According to aspects of this embodiment, the atomized fluid may be the same as the propellant, for example liquid hydrogen or some other cryogenic propellant, or it may be some different fluid that does not adversely affect the tanked propellants, for example a fluid that may go into solution with the propellants. The fluid source may be external or internal to the propellant tank. One or more atomizers may be located at a perimeter of the propellant tank or at any other location within the propellant tank. The atomizer may be configured to move, oscillate or rotate relative to the interior of the propellant tank to spray the atomized fluid over a larger localized volume.

In another embodiment, a mechanical pump may be combined with an atomizer and the added condensable fluid may be unpressurized. One example of an acceptable mechanical pump is a centrifugal pump. Other types of mechanical pumps acceptable for this purpose include pumps of the positive displacement variety. Compared to an aerodynamic pump that has no moving parts, a mechanical pump includes moving parts which introduce possible points for failure not present with an aerodynamic pump. The mechanical pump would pressurize and drive the added primary fluid through an atomizer thereby atomizing the fluid. A localized volume or zone of ullage proximate the point of ejection from the atomizer will undergo a temperature decrease thereby reducing the pressure in the propellant tank. Continued operation the pump expands the localized volume or zone of reduced temperature ullage and continues to reduce the pressure within the propellant tank. The fluid can be pulsed repeatedly until the ullage gas is at the desired conditions or throttled proportionally until the desired operating conditions of the system are attained. Thus, pressure within the propellant tank may be controlled without venting of the propellant tank and without loss of propellant.

According to aspects of this embodiment, the primary fluid may be the same as the propellant, for example liquid hydrogen or some other cryogenic propellant, or it may be some different fluid that does not adversely affect the tanked propellants, for example a fluid that may go into solution with the propellants. The fluid source may be external or internal to the propellant tank. One or more mechanical pumps may be utilized. The pumps may be located external or internal to the propellant tank. The fluid may be introduced at a perimeter of the propellant tank or at any other location within the propellant tank. The pump or, at a minimum, the atomizer, may be configured to move, oscillate, or rotate relative to the interior of the propellant tank to eject the atomized fluid over a larger localized volume.

In a further embodiment, which is a variation of the first embodiment discussed above, an aerodynamic jet pump is combined with an unpressurized source of a condensable motive fluid and a mechanical pump pressurizes the motive fluid prior to the motive fluid entering the jet pump. This embodiment otherwise operates the same as the first embodiment.

In yet a further embodiment, an incondensable or non-condensable motive fluid is used to affect a different result. The pump may be an aerodynamic pump, for example, a jet pump. In the embodiments of FIGS. **1-4** and **7-13**, the motive fluid is accelerated through a nozzle to create a high velocity fluid jet that reduces local static pressure and thereby creates a vacuum. The low static pressure suctions liquid cryogen propellant into a mixing tube where the cryogenic liquid propellant is entrained into the flow of the high velocity motive fluid to form a highly atomized spray of both the liquid cryogen and the motive fluid through momentum transfer between the coflowing fluids. The mixed solution is then exhausted into the ullage space of the propellant tank where evaporation of the atomized spray lowers the ullage gas temperature. Additionally, the non-condensable constituent increases the total pressure of the ullage. By reducing or minimizing the thermal potential energy, e.g., the difference in temperature between the ullage gas and the temperature of the liquid cryogenic propellant, the degree by which the ullage pressure can collapse is reduced and minimized, or perhaps eliminated.

Conditioning a propellant tank to avoid ullage collapse may be initiated while the tank is in a gravity environment, i.e., on earth. Conditioning may continue through launch and stage separation. Conditioning may also be initiated at or prior to other acceleration or deceleration events in a microgravity environment.

According to aspects of this embodiment, the incondensable motive fluid may not be the same as the propellant and should be some gaseous phase fluid that has a vaporization temperature below that of the propellant in which it is being mixed. For example, in a liquid hydrogen propellant tank, gaseous helium may be used. The incondensable motive fluid source may be external or internal to the propellant tank. The one or more pumps may be located external or internal to the propellant tank. The mixture of incondensable motive fluid and liquid propellant may be introduced at a perimeter of the propellant tank or at any other location within the propellant tank. The pump or, at a minimum, the mixing chamber of the pump, may be configured to move, oscillate or rotate relative to the interior of the propellant tank to eject the mixture of atomized motive fluid and liquid propellant over a larger localized volume.

According to yet another embodiment, one or more aerodynamic or jet pumps may be partially submerged in the liquid propellant. In order to avoid or limit prolonged exposure of the internal components of the jet pump to the liquid propellant, a valve closes the fluid inlet between the jet pump and the liquid propellant. As one example, a pressure actuated poppet valve may be used to restrict or limit the introduction of liquid propellant inside the body of the jet pump when not in use. The poppet valve is linked to a piston that is displaced by the introduction of the pressurized motive fluid into the jet pump. Movement of the piston, in turn, opens the poppet valve, which allows liquid propellant to be drawn or syphoned through the inlet or open valve into the mixing tube or chamber of the jet pump where it is

entrained or mixed into the flow of the sufficiently high velocity motive fluid within the mixing tube or chamber. The mixture is then exhausted out of the jet pump and into an area of the propellant tank containing ullage as described above in connection with other embodiments. The poppet valve is biased to a closed position and closes by ceasing the introduction of the pressurized motive fluid.

This embodiment allows the ejector or jet pump to be submerged in a fluid without the suction chamber being flooded while not in operation. One advantage is the elimination of a suction tube communicating liquid to the ejector or, alternatively, the ability to utilize a reduced length suction tube, which can enhance the efficiency of the jet pump. Another advantage of this submerged suction chamber is additional liquid head pressure that is gained by secondary fluid. Added head pressure to the liquid increases the entrainment ratio of the jet pump, where the entrainment ratio is defined as the ratio of the secondary fluid, in this case the liquid, to the motive fluid, which can enhance the efficiency of the jet pump. Reducing or eliminating fluid in the jet pump when not operating also reduces exposure of the components of the jet pump to the liquid. In some scenarios, the liquid may be corrosive and reducing contact between the fluid and the jet pump components prolongs the life of the jet pump. The valve also eliminates or reduces the opportunity for the liquid to enter the supply line for the motive fluid circuit, e.g., back flow through the motive nozzle into the motive fluid supply line. A flooded jet pump may also adversely affect the start up of the jet pump, e.g., liquid hydrogen in the mixing tube would be pushed out as a slug, which could lead to an inconsistent operation, water hammering or other damage to the pump.

The phrases "at least one", "one or more", and "and/or", as used herein, are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions "at least one of A, B and C", "at least one of A, B, or C", "one or more of A, B, and C", "one or more of A, B, or C" and "A, B, and/or C" means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together.

Unless otherwise indicated, all numbers expressing quantities, dimensions, conditions, and so forth used in the specification and claims are to be understood as being modified in all instances by the term "about".

The term "a" or "an" entity, as used herein, refers to one or more of that entity. As such, the terms "a" (or "an"), "one or more" and "at least one" can be used interchangeably herein.

The use of "including," "comprising," or "having" and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. Accordingly, the terms "including," "comprising," or "having" and variations thereof can be used interchangeably herein.

It shall be understood that the term "means" as used herein shall be given its broadest possible interpretation in accordance with 35 U.S.C. Section 112 (f). Accordingly, a claim incorporating the term "means" shall cover all structures, materials, or acts set forth herein, and all of the equivalents thereof. Further, the structures, materials, or acts and the equivalents thereof shall include all those described in the summary of the invention, brief description of the drawings, detailed description, abstract, and claims themselves.

These and other advantages will be apparent from the disclosure of the invention(s) contained herein. The above-described embodiments, objectives, and configurations are neither complete nor exhaustive. The Summary of the Invention is neither intended nor should it be construed as being representative of the full extent and scope of the present invention. Moreover, references made herein to "the present invention" or aspects thereof should be understood to mean certain embodiments of the present invention and should not necessarily be construed as limiting all embodiments to a particular description. The present invention is set forth in various levels of detail in the Summary of the Invention as well as in the attached drawings and the Detailed Description and no limitation as to the scope of the present invention is intended by either the inclusion or non-inclusion of elements, components, etc. in this Summary of the Invention. Additional aspects of the present invention will become more readily apparent from the Detailed Description, particularly when taken together with the drawings.

The above-described benefits, embodiments, and/or characterizations are not necessarily complete or exhaustive, and in particular, as to the patentable subject matter disclosed herein. Other benefits, embodiments, and/or characterizations of the present disclosure are possible utilizing, alone or in combination, as set forth above and/or described in the accompanying figures and/or in the description herein below. However, the Detailed Description, the drawing figures, and the exemplary claims set forth herein, taken in conjunction with this Summary of the Invention, define the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Those of skill in the art will recognize that the following description is merely illustrative of the principles of the invention, which may be applied in various ways to provide many different alternative embodiments. This description is made for illustrating the general principles of the teachings of this invention and is not meant to limit the inventive concepts disclosed herein.

FIG. **1** is a schematic diagram of one embodiment of an upper or second stage of a launch vehicle including a system for controlling ullage temperature and pressure.

FIG. **2**A is a cross-sectional view of one embodiment of a non-operating jet pump assembly inside a propellant tank.

FIG. **2**B is a cross-sectional view of the embodiment of FIG. **2**A, with the jet pump assembly operating and showing propellant entering a syphon.

FIG. **2**C is a cross-sectional view of the embodiment of FIG. **2**A, with the jet pump assembly operating and showing motive fluid and propellant mixing in a mixing tube and exiting the mixing tube into a propellant tank.

FIG. **2**D is a cross-sectional view of the embodiment of FIG. **2**A, with the jet pump assembly operating and showing a volume of ullage at a temperature lower than the temperature of the ullage generally.

FIG. **2**E is a cross-sectional view of the embodiment of FIG. **2**A showing the effect of continuing operation of the jet pump assembly.

FIG. **3** is a schematic diagram of a propellant tank containing an alternative embodiment of a jet pump assembly.

FIG. **4** is a schematic diagram of a propellant tank containing multiple jet pump assemblies.

FIG. **5** is a schematic diagram of an alternative embodiment of an upper or second stage of a launch vehicle including a system for controlling ullage temperature and pressure.

FIG. **6** is a schematic diagram of a further alternative embodiment of an upper or second stage of a launch vehicle including a system for controlling ullage temperature and pressure.

FIG. **7** is a schematic diagram of another alternative embodiment of an upper or second stage of a launch vehicle including a system for controlling ullage temperature and pressure.

FIG. **8** is a schematic diagram of a further alternative embodiment of jet pump partially submerged in a liquid and including an inlet valve to control liquid flow to the jet pump.

FIG. **9** is the embodiment of FIG. **8**, showing an inlet valve in an open position and the introduction of a motive fluid.

FIG. **10** is the schematic view of FIG. **9**, further showing liquid being drawn in to the jet pump and a mixture of liquid and motive fluid exhausted from the jet pump.

FIG. **11** is a schematic diagram of an alternative embodiment of the jet pump of FIG. **8** (add syphon tube extension).

FIG. **12** is a schematic diagram of a further alternative embodiment of a jet pump.

FIG. **13** is a schematic of the embodiment of FIG. **12**, with the valve open.

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together with the general description of the invention given above and the detailed description of the drawings given below, serve to explain the principles of the invention.

The drawings are not necessarily to scale and various dimensions may be altered. In certain instances, details that are not necessary for an understanding of the invention or that render other details difficult to perceive may have been omitted. It should be understood, of course, that the invention is not necessarily limited to the particular embodiments illustrated herein.

DETAILED DESCRIPTION

Although the following text sets forth a detailed description of numerous different embodiments, it should be understood that the legal scope of the description is defined by the words of the claims set forth at the end of this disclosure. The detailed description is to be construed as exemplary only and does not describe every possible embodiment since describing every possible embodiment would be impractical, if not impossible. Numerous alternative embodiments could be implemented, using either current technology or technology developed after the filing date of this patent, which would still fall within the scope of the claims.

FIG. **1** illustrates a first embodiment of a propellant system for a launch vehicle **10**. Two propellant tanks **12** and **14** are shown in coaxial alignment. Each tank contains a liquid cryogenic propellant, for example, oxygen **40** in tank **12** or hydrogen **42** in tank **14**. A propellant supply line **16** connects the upper tank **12** to the engine **18**. A second propellant supply line **20** connects the lower tank **14** to the engine **18**. The two propellants are mixed and combusted by the engine **18**. A valve **22** may be provided in association with the upper tank **12** to supply propellant to or vent propellant from the upper tank **12**. Similarly, a second valve **24** may be provided in association with the lower thank **14** to supply propellant from the tank **14**.

Using the upper tank **12** for discussion purposes, FIG. **1** shows an aerodynamic jet pump assembly **30** comprising a motive nozzle **32** disposed in the proximal end of a mixing tube **34**, a syphon **36** in fluid communication with the mixing tube **34** and having a distal end **38** disposed in liquid cryogenic propellant **40**. A source **44** of pressurized motive fluid **46** is in fluid communication with the motive nozzle **32** by a supply line **48**. A valve **50** controls the supply of motive fluid **46** to the motive nozzle **32**. The motive fluid **46** is maintained under pressure within the source **44**. When the valve **50** is opened, motive fluid **46** will flow to the motive nozzle **32** and when the valve **50** is closed, no motive fluid will be supplied to the motive nozzle **32**. The motive fluid **46** may be the same as the propellant, for example, liquid oxygen in the case of tank **12** or some other cryogenic propellant. Alternatively, the motive fluid may be different from the propellant, for example, helium or some other element or composition that would not adversely affect the propellant.

Tank **14** uses a second jet pump assembly **30'** that is the same as jet pump assembly **30** associated with tank **12**. The same reference numerals, further including a prime (') symbol, are used to designate duplicate components associated with tank **40**. Thus, the jet pump assembly **30'** includes a motive nozzle **32'**, a mixing tube **34'**, and a syphon **36'** with a distal end **38'**. Here, because propellant tank **14** contains liquid hydrogen, the source **44'** associated with tank **14** may contain liquid hydrogen as the motive fluid **46'**. A valve **50'** controls the flow of pressurized motive fluid **46'** in supply line **48'** to the tank **14**.

Turning to FIGS. **2**A-**2**E, operation of the jet pump assembly **30** will be described. Jet pump **30'** operates in the same way. FIG. **2**A illustrates the jet pump assembly **30** in a static or non-operating state. The jet pump assembly **30** includes a jet pump body **31** housing a motive nozzle **32** and defining a suction chamber **33**. A mixing chamber or mixing tube **34** and a syphon **36** extend from the ejector body **31**. As seen, the distal end **38** of the syphon **36** is positioned within the liquid propellant **40**. The motive nozzle **32** and mixing tube **34** are not positioned in the liquid propellant but are positioned in ullage or gaseous propellant **60**. It will be appreciated by those of skill in the art that a propellant tank will rarely, if ever, be filled completely with liquid cryogenic propellant. Rather, some portion of the propellant in the tank will be in a gaseous state—also known as ullage. Also, the position of the interface between the liquid and gaseous propellant will change over time and will not always be demarcated by a planer surface as illustrated in the drawings of this disclosure which are provided for illustrative purposes and not intended to depict every possible scenario of liquid and gaseous propellant cohabitating in a single propellant tank. The label Tliq represents the temperature of the liquid cryogenic propellant **40**. The label TU represents the temperature of the ullage **60**. The temperature of the liquid cryogenic liquid propellant will always be less than that of the ullage **60** (Tliq<TU).

In FIG. **2**B, valve **50** is open and pressurized motive fluid **46** is flowing from the source **44** to the motive nozzle **32**. The condensable motive fluid **46** is accelerated through the nozzle **32** to create a high velocity fluid stream or jet that reduces local static pressure and thereby creates a vacuum. The nozzle **32** may be configured as a subsonic, sonic or supersonic nozzle. Consistent with Bernoulli's principle, an area or zone of low static pressure **64** is created proximate the exit **66** of the motive nozzle **32**. An effect of the low-pressure area **64** is that the liquid propellant **40** is drawn through the syphon **36** to a suction chamber **33** and then into the mixing chamber or mixing tube **34** as seen in FIG. **2**C.

FIG. **2**C illustrates mixing of the liquid propellant **40** with the motive fluid **46**. More particularly, as motive fluid **46**

continues to be supplied to the motive nozzle **32**, the propellant **40** will be fully drawn into the mixing tube **34** where it will mix with or be entrained into the high velocity motive fluid **46** exiting the motive nozzle **32**. The two fluids mix to form a highly atomized spray or mixture **70** of both the liquid cryogen propellant **40** and the motive fluid **46** through momentum transfer between the coflowing fluids.

FIG. **2**D illustrates the creation of an area **72** of reduced temperature within the ullage **60** proximate the exit **74** of the mixing tube. More particularly, the condensable motive fluid **46** is cooled by the mixing with the liquid cryogenic propellant **40**. As a result, the temperature T of the area **72** is less than the temperature TU of the ullage **60** and greater that the temperature Tliq of the propellant **40** (Tliq<T<=TU). Because evaporation is occurring, if the process continues the temperature of the area **72** and the temperature of the ullage (TU) could reach an equilibrium and approach or reach the temperature of the liquid propellant (TU). Vaporization of the liquid droplets in the mixture efficiently cools the ullage. Because the resulting mixture of the motive fluid **46** and the liquid propellant **40** has a lower temperature than the ullage **60**, the temperature of a localized volume **72** of the ullage is reduced and the total pressure of the ullage **60** is reduced or at least not increased. The arrow VP illustrates that the volume of the liquid propellant **40** diminishes as the result of syphoning liquid propellant **40** to mix with the motive fluid **32**. The arrow V**72** illustrates that the volume of the localized area **72** increases based upon the duration of the operation of the jet pump assembly **30**. Indeed, as the jet pump assembly continues to operate, the volume of area **72** will increase as generally illustrated in FIG. **2**E expanding the volume V**72** of reduced temperature ullage and further reducing the pressure within the propellant tank.

The present invention is superior to a detachable ground-only conditioning system for several reasons, including: 1) it has the unique capability to condition the ullage in flight to reduce the effects of aero heating and ambient helium pressurization, 2) it is more cost effective, 3) it is less complicated, 4) there are no additional moving parts, and 5) the ambient helium and the ullage gas are cooled.

By using forced convective vaporization as explained above, a propellant tank may be filled with cryogenic liquid propellant without a need to vent the tank during the fill operation. The operation introduces a motive fluid in the form of a condensable, pressurized and atomized cryogenic liquid propellant into the tank ullage to decrease the ullage gas temperature in a controlled manner. In the specific example of FIG. **1**, the vehicle **10** includes two propellant tanks **12** and **14**, each with a different cryogenic propellant. Cryogenic liquid oxygen may be in one tank and cryogenic liquid hydrogen in the other. In this context, where the motive fluid is condensable, cryogenic liquid oxygen may be the motive fluid for the oxygen tank **12** and cryogenic liquid hydrogen may be the motive fluid for the hydrogen tank. In this scenario, cryogenic liquid oxygen should not be added to the tank containing cryogenic liquid hydrogen. In other scenarios, it may be acceptable to utilize a single common condensable motive fluid for each propellant tank **12** and **14**. The motive fluid need not be continuously supplied to the motive nozzle but may be pulsed repeatedly, intermittently stopped and started or the nozzle **50** and **50'** may be throttled proportionally to regulate the cooling in the tank and control pressure. In FIGS. **1** and **2**A-**2**E, the jet pump assembly **30** is shown at a position adjacent a perimeter wall of the tank. As illustrated in FIGS. **3** and **4**, the jet pump assembly **30** may be positioned in the center of the tank or at another location based upon other factors. The assembly may also be configured to rotate or oscillate to disperse the atomized mixture over a larger volume. In alternative embodiments, multiple jet pump assemblies may be included in a single tank. In addition, the source **44** of the motive fluid **46** is show outside of the tank **12**. In a non-limiting alternative embodiment, the source **30** may be positioned inside the tank **12**. Further still, FIG. **1** shows a separate source **44** and **44'** for each tank **12** and **14**, respectively. A single source tank may supply motive fluid to both tanks **12** and **14** in appropriate circumstances and under appropriate conditions as would be understood by those of skill in the art upon review of the present disclosure.

FIG. **5** illustrates another embodiment of a system for controlling propellant tank temperature and pressure for use in filling propellant tanks with cryogenic liquid propellant without the need to vent the tank. An upper or second stage **100** of a launch vehicle is shown. The vehicle contains a first propellant tank **112** for holding a first cryogenic liquid propellant **140** and a second propellant tank **114** for holding a second cryogenic liquid propellant **142**. A propellant supply line **116** connects the upper tank **112** to the engine **118**. A second propellant supply line **120** connects the lower tank **114** to the engine **118**. The two propellants are mixed and combusted by the engine **118**. A valve **122** may be provided in association with the upper tank **112** to supply propellant to or vent propellant from the upper tank **112**. Similarly, a second valve **124** may be provided in association with the lower thank **14** to supply propellant or vent propellant from the tank **114**.

The upper tank **112** further includes an atomizer **130** connected to a source **144** of a pressurized, motive fluid **146** that is supplied to the atomizer **130** by a supply line **148**. A valve **150** controls the flow of motive fluid **146** to the atomizer **130**. The lower or second tank **114** includes the same components. An atomizer **130'** is connected to a source **144'** of a pressurized, motive fluid **146'** that is supplied to the atomizer **130'** by a supply line **148'**. Nozzle **150'** controls the flow of the motive fluid **146'** to the atomizer **130'**.

The embodiment of FIG. **6** illustrates a further alternative. Here, the motive fluid is the cryogenic liquid propellant in each of the tanks **112** and **114**. A pump **180** is provided in association with the first tank **112** and a pump **180'** is provided in association with the second tank **114** to withdraw the propellant from the tank and forward it to the atomizers **130** and **130'**. In one non-limiting example, the pumps **180** and **180'** are centrifugal pumps. Alternative pumps could be of the positive displacement variety.

The embodiments illustrated in FIGS. **5** and **6** may also be used to control ullage temperature and pressure within a propellant tank containing cryogenic liquid propellant. In operation, a condensable motive fluid under pressure is supplied to the atomizer **130** and **130'** which atomizes the motive fluid and disperses it into the ullage of a propellant tank containing a liquid cryogenic propellant. Similar to the embodiments that utilize a jet pump assembly, the atomized spray has a temperature less than that of the ullage. In one non-limiting example regarding the embodiment of FIG. **5**, the motive fluid **146** and **146'** is the same liquid propellant as contained in the propellant tank. In other non-limiting examples involving the embodiment of FIG. **5**, the motive fluid may be cryogenic liquid helium or nitrogen. The atomized spray creates a volume or localized area having a temperature less than that of the ullage generally, which reduces pressure within the tank. Continuing to supply the motive fluid to the atomizer further reduces the temperature of the ullage and further controls pressure within the tank.

In the embodiments of FIGS. **5** and **6**, the motive fluid **146** and **146'** need not be continuously supplied to the atomizer **130** and **130'** but may be pulsed repeatedly, intermittently stopped and started or the nozzle **150** and **150'** may be throttled proportionally to regulate the cooling in the tank and control pressure. In FIGS. **5** and **6**, the atomizers **130** and **130'** are shown at a position adjacent a perimeter wall of the tank. Similar to the jet pump assembly embodiments illustrated in FIGS. **4** and **5**, the atomizers **130** and **130'** may be positioned in the center of the tank or at another location based upon relevant factors. The atomizer may also be configured to rotate or oscillate to disperse the atomized mixture over a larger volume. In alternative embodiments, multiple atomizers may be included in a single tank. In addition, the source **144** and **144'** of the motive fluid **146** and **146'** are shown outside of the tank **12**. In a non-limiting alternative embodiment, the source **144** and **144'** may be positioned inside the tank **112** and **114**. Further still, FIG. **5** shows a separate source **144** and **144'** for each tank **112** and **114**, respectively. A single source tank may supply motive fluid to both tanks **112** and **114** under appropriate circumstances and under appropriate conditions as would be understood by those of skill in the art upon review of the present disclosure.

The embodiment illustrated in FIG. **7** is an alternative to the embodiments of FIGS. **1** and **3-5**. Here, a single motive fluid source **44"** provides pressurized, incondensable motive fluid to the jet pump assemblies **30** and **30'**. Because there are two different cryogenic propellants involved, the motive fluid should not be one of the propellants but rather a fluid that is incondensable in both propellants like helium. As with all of the embodiments disclosed herein, the propellant tanks may be conditioned separately or simultaneously.

There may be circumstances in which it is desirable to submerge or partially submerge the body of a jet pump within a liquid, i.e., within a liquid propellant in a tank or container containing liquid and gaseous propellant. One example is illustrated in FIG. **8** where the body **236** of an ejector or jet pump **230** is partially submerged in liquid propellant **240** within a propellant tank **212**. As also seen, a supply line **248** supplies motive fluid, under pressure, to a nozzle **232** positioned inside the body **236** of the ejector or jet pump **230**. In such a scenario, it also may be desirable to control or limit when the liquid **240** is allowed into the interior of the jet pump **230**. Allowing the liquid to remain continuously inside the jet pump could cause or accelerate damage to the jet pump. For example, the liquid **240** may comprise a strong acid or a strong base that can harm special coatings on the internal components of the pump **230**. Prolonged exposure to liquid hydrogen can lead to hydrogen embrittlement in the internal metal components. In addition, an on-going presence of the liquid **240** inside the jet pump could cause the liquid to infiltrate the motive fluid supply line **248** and motive fluid source, which could lead to contaminating the motive fluid affecting the properties of the motive fluid causing blockages and icing of the motive supply line and the motive fluid source container may not be rated for the cold temperatures of the liquid **240** also causing damage to this hardware. Chemical reactions between the motive fluid and liquid may also cause unintended pressure increases. Additionally, the presence of a liquid slug in the mixing tube **34**, above the motive nozzle **232**, prior to jet pump operation could expel an unmixed liquid slug into the ullage that would lead to a start-up transient of the jet pump that may excessively cool the ullage or otherwise lead to inconsistent behavior.

Accordingly, in this embodiment, the jet pump **230** is provided with an inlet valve **250** to control the ingress of liquid **240** into the interior of the jet pump. As illustrated in FIG. **8** the inlet valve **250** includes an isolation valve **252** that has a closed state (FIG. **8**) and an open state (seen in FIG. **9**). The isolation valve **252** included a valve body **254** connected to a piston **256** by a valve stem **258**. Motive fluid **246** is introduced into the jet pump **230** via supply line **248**. Turning to FIG. **9**, the pressure of the motive fluid **246** forces a portion of the motive fluid **246***a* to travel through the nozzle **232** to create a high velocity fluid stream or jet that reduces local static pressure and thereby creates a vacuum as discussed herein in connection with other embodiments. A second portion of the pressurized motive fluid **246***b* displaces piston **256** downwardly or outwardly in the context of FIG. **9**. The piston **256** is biased to the closed position illustrated in FIG. **8** by spring **260**. Therefore, the force of the motive fluid **246***b* must be sufficient to overcome the force of the spring **260**. When in the closed position illustrated in FIG. **8**, the valve body **254** is positioned in a seat **262** formed at the liquid inlet **264** of the pump **230**. A gasket or similar seal **266** may be provided on the valve body **254** or around the inlet **264** to facilitate creating a liquid seal when the valve body **254** is closed. Upon the motive fluid **246***b* displacing the piston **254**, the rod or stem **256** displaces the valve body **254** to open the inlet **264**. Simultaneously, as a result of the low-pressure zone generated by the motive fluid **246***a* passing through the nozzle **232**, liquid propellant **240***a* is syphoned or drawn into the suction chamber **233** and then to the mixing chamber **234** as illustrated in FIG. **10**. As long as the motive fluid **246** is delivered at or above a threshold pressure needed to displace the piston **256**, the valve body **254** will remain open. Ceasing the supply of the motive fluid **246** will cause the valve body **254** to close as illustrated in FIG. **8**. It should be appreciated that the liquid inlet **264** of the isolation valve **252** may be in direct communication with a liquid **240**, as illustrated in FIGS. **8-10** where the ejector body **236** is submerged in the liquid **240** or, alternatively, as illustrated in FIG. **11**, a suction or syphon tube **268** may extend from the valve **252** to allow the jet pump **230** to draw liquid from a farther distance.

FIGS. **12** and **13** show an embodiment according to the present disclosure in service on process piping. Here, the jet pump is used to suction fluid from main process piping. Non-limiting examples include suctioning fluid into an unprimed line before a primary fluid process commences, generating a vacuum in association with a primary process, e.g., in-space rocket engine testing or thermal vacuum testing, moving fluid from a primary process to a secondary process, or in any operation that requires the isolation valve to be closed when the ejector is not in operation. Turning to the FIGS. **12** and **13**, a primary fluid line or pipe **300** and a secondary line or pipe **302** are shown. A jet pump **330** is positioned in the secondary line **302** which is in fluid communication with the primary line **300**. When valve **350** is opened, motive fluid **346** under pressure from motive fluid source **344** is released into motive fluid supply line **348**. The motive fluid **346** splits with a first portion **346***a* entering the jet pump **330** and a second portion **346***b* engaging a piston **356** that is part of isolation valve **352**. The force of the motive fluid portion **346***b* overcomes the counter force of spring **360** and the piston is moved downwardly as illustrated in FIG. **13**. Downward movement of piston **356** cause valve stem **358** to open the valve body **354**. The valve body **354** rests in or on a valve seat **362** when closed. A gasket or seal **366** may be provided on the valve body **354** or around the seat **362**. As a result of a low pressure area created by

motive fluid **346***a* exiting nozzle **332**, primary fluid **340***a* is drawn through the opening **364** of the isolation valve **352** and into a suction chamber **333** and then into the mixing chamber **334** of the jet pump **330** where it mixes with motive fluid **346***a*. The motive fluid pressure opens the secondary fluid inlet valve **354** and subsequently draws in the process fluid **340***a* from the process or primary pipe **300**, pumps this fluid out of the process pipe **300** to secondary process(es), or simply reduces the pressure in the main process piping **300** to prime the line, create vacuum, or to evacuate the line to bring the process into or out of service. Once the ejector **330** has completed its operation, the motive fluid pressure supply is isolated and the secondary fluid inlet valve **354** is closed, effectively isolating the jet pump **330** and its downstream process from the main process.

At least some of the embodiments illustrated and discussed herein may be used for purposes other than filling a propellant tank with a liquid cryogenic propellant without needing to vent the tank. In particular, embodiments illustrated and described may be used to reduce or eliminate the occurrence of ullage collapse. In the embodiments illustrated in FIGS. **1-4** and **7-13**, an incondensable or non-condensable fluid may be used in place of the condensable motive fluid. The incondensable motive fluid is accelerated through a nozzle to create a high velocity fluid jet that reduces local static pressure and thereby creates a vacuum. The low static pressure suctions liquid cryogen out of the liquid space within the propellant tank where it is entrained into the flow of the high velocity motive fluid, preferably within a mixing chamber or tube, to form a highly atomized spray of both the liquid cryogen and the motive fluid through momentum transfer between the coflowing fluids. The mixed solution is then exhausted into the ullage space of the propellant tank where evaporation of the atomized spray lowers the ullage gas temperature. In the embodiment of FIG. **6**, the motive fluid is accelerated through an atomizer creating a highly atomized spray that has a temperature lower than that of the ullage generally. Because a non-condensable motive fluid is used, total pressure of the ullage is increased. By reducing or minimizing the thermal potential energy, e.g., the difference in temperature between the ullage gas and the temperature of the liquid cryogenic propellant, the degree by which the ullage pressure can collapse is reduced and the risk or ullage collapse is also reduced or perhaps eliminated.

While various embodiments of the present invention have been described in detail, it is apparent that modifications and alterations of those embodiments will occur to those skilled in the art. However, it is to be expressly understood that such modifications and alterations are within the scope and spirit of the present invention, as set forth in the following claims. Further, the invention(s) described herein is capable of other embodiments and of being practiced or of being carried out in various ways. It is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

The foregoing discussion of the disclosure has been presented for purposes of illustration and description. The foregoing is not intended to limit the disclosure to the form or forms disclosed herein. In the foregoing Detailed Description for example, various features of the disclosure are grouped together in one or more embodiments, configurations, or aspects for the purpose of streamlining the disclosure. The features of the embodiments, configurations, or aspects of the disclosure may be combined in alternate embodiments, configurations, or aspects other than those discussed above. This method of disclosure is not to be interpreted as reflecting an intention that the claimed disclosure requires more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed embodiment, configuration, or aspect. Thus, the following claims are hereby incorporated into this Detailed Description, with each claim standing on its own as a separate preferred embodiment of the disclosure.

The features of the various embodiments described herein are not intended to be mutually exclusive when the nature of those features does not require mutual exclusivity. Instead, features and aspects of one embodiment may be combined with features or aspects of another embodiment. Additionally, the description of a particular element with respect to one embodiment may apply to the use of that particular element in another embodiment, regardless of whether the description is repeated in connection with the use of the particular element in the other embodiment.

Examples provided herein are intended to be illustrative and non-limiting. Thus, any example or set of examples provided to illustrate one or more aspects of the present disclosure should not be considered to comprise the entire set of possible embodiments of the aspect in question. Examples may be identified by use of the terms or phrases "for example," "such as," "by way of example," "e.g.," and other language commonly understood to indicate that what follows is an example.

What is claimed is:

1. A system for controlling a temperature and pressure in a propellant tank, comprising:

a. a first tank;

b. a cryogenic fluid in the first tank, the cryogenic fluid comprising a liquid portion and a gas portion;

c. a forced convective vaporization (FVC) device positioned inside the first tank, the FVC device having:

i. a suction chamber having a first inlet and a first outlet spaced from the first inlet, the first outlet submerged in at least a portion of the liquid portion of the cryogenic fluid;

ii. a motive nozzle having a second inlet and a second outlet spaced downstream from the second inlet, the second outlet located within the suction chamber, the motive nozzle second inlet configured to receive pressurized motive fluid;

iii. a mixing tube having a first end and a second end, the first end in fluid communication with the first outlet of the suction chamber and the second end positioned in the gas portion of the cryogenic fluid; and

iv. a valve associated with the first inlet of the suction chamber, the valve having an open position and a closed position wherein the valve moves from the closed position to the open position by the introduction of pressurized motive fluid to the motive nozzle and moves to the closed position by stopping the supply of motive fluid to the motive nozzle.

2. The system of claim **1**, wherein the valve comprises a piston movable between a first position and a second position, a stem interconnecting the piston with a valve body, and the valve body movable between a first position where the valve body closes a first valve inlet and a second position where the valve body is spaced from the first valve inlet.

3. The system of claim **2**, further comprising a biasing member that biases the piston to the first position and biases the valve body to the closed position.

4. The system of claim 2, wherein the first valve inlet is in fluid communication with the first inlet of the suction chamber.

5. The system of claim 2, further comprising a syphon tube having a first end and a second end spaced from the first end, wherein the first end is in fluid communication with the first valve inlet and the second end is configured to be in fluid communication with at least a portion of the liquid portion of the cryogenic fluid.

6. The system of claim 5, wherein the second end of the mixing tube is in fluid communication with at least a portion of the gas portion of the cryogenic fluid.

7. The system of claim 5, wherein the second end of the syphon tube is submerged in at least a portion of the liquid portion of the cryogenic fluid.

8. The system of claim 2, comprising:

a. a second tank;

b. a cryogenic fluid in the second tank, the cryogenic fluid comprising a liquid portion and a gas portion;

c. a forced convective vaporization (FVC) device positioned inside the second tank, the FVC device having:

i. a suction chamber having a first inlet and a first outlet spaced from the first inlet;

ii. a motive nozzle having a second inlet and a second outlet spaced downstream from the second inlet, the second outlet located within the suction chamber, the motive nozzle second inlet configured to receive pressurized motive fluid;

iii. a mixing tube having a first end and a second end, the first end in fluid communication with the first outlet of the suction chamber and the second end in fluid communication with the interior of the second tank; and

iv. a valve associated with the first inlet of the suction chamber, the valve having an open position and a closed position wherein the valve moves from the closed position to the open position by the introduction of pressurized motive fluid to the motive nozzle and moves to the closed position by stopping the supply of motive fluid to the motive nozzle.

9. The system of claim 1, further comprising a pressurized source of motive fluid in fluid communication with the second inlet of the motive nozzle.

10. The system of claim 9, wherein the pressurized source of motive fluid is located outside the first tank.

11. The system of claim 9, wherein the pressurized source of motive fluid is located inside the first tank.

* * * * *