

D. T. DAY.
 PROCESS FOR EXTRACTING OILS AND HYDROCARBON MATERIAL FROM SHALE
 AND SIMILAR BITUMINOUS ROCKS.

1,342,741.

APPLICATION FILED JAN. 17, 1918.

Patented June 8, 1920.

Fig. 1.





Fig. 2.



Inventor

David T. Day,

By *Wm. B. Prentiss*

Attorney

UNITED STATES PATENT OFFICE.

DAVID T. DAY, OF WASHINGTON, DISTRICT OF COLUMBIA.

PROCESS FOR EXTRACTING OILS AND HYDROCARBON MATERIAL FROM SHALE AND SIMILAR BITUMINOUS ROCKS.

1,342,741.

Specification of Letters Patent.

Patented June 8, 1920.

Application filed January 17, 1918. Serial No. 212,317.

To all whom it may concern:

Be it known that I, DAVID T. DAY, a citizen of the United States, residing at Washington, in the District of Columbia, have invented new and useful Improvements in Processes for Extracting Oils and Hydrocarbon Material from Shale and Similar Bituminous Rocks, of which the following is a specification.

This invention relates to a process for extracting oils and similar material from shale and bituminous material which is in its natural condition in the ground. The process has to do with the distillation of the volatile contents of the shale, bituminous sandstone, or bituminous lime stone.

Heretofore, it has been customary to mine the shale and treat it in retorts by various processes. In some cases it has been suggested to introduce hot solvent or steam into holes bored in the ground to drive out or extract the oil material.

The present invention provides for the extraction of the oil material by the introduction of hot gases of combustion, or other hot gases substantially devoid of oxygen, into holes drilled in the shale to effect the vaporization of the volatile matter in the shale and carry the same to the surface of the ground where suitable condensing apparatus or separators collect the oil material. The process is essentially one for heat treating oil shale while in its native state to vaporize all of the oil from the shale while in the ground, and the condensation of such oil after being recovered above the ground.

The invention provides for the generation of the hot gases in suitable apparatus located above the surface of the ground, and provides for the application of the hot gases to the shale under pressure greater than atmospheric pressure and at high temperatures. By the use of hot gases of combustion, the process may be operated at the highest efficiency. The gases carry and absorb a very large amount of the oil and there is less condensation than if steam is used.

In conducting the process, apparatus may be used designed according to the form represented diagrammatically in the accompanying drawing, in which—

Figure 1 represents a section of a driven well in the shale-like material together with the apparatus for conducting the process;

Fig. 2 represents an enlarged sectional view of the combustion chamber used for generating the hot gases of combustion.

Referring in detail to the drawing, 1 represents a combustion chamber of suitable metal which preferably is tested for pressure of at least six hundred pounds and is lined on the inside with fire brick 2. An outer covering may be provided by ordinary red brick 3 according to the condition and mounting desired for the combustion chamber. 4 represents a mechanical spray for injecting oil or oil and steam which may be admitted from the pipes 5 and 6 respectively. An additional pipe 7 is provided for admitting air to the combustion chamber at a point relatively near the spray 4 so that the combustion may be facilitated. A discharge passage leading from the combustion chamber is indicated at 8. A predetermined pressure may be brought about by a pump 9 which is connected to the combustion chamber at the injector end. The outlet passage or pipe 8 is provided with a control valve 10 adapted to regulate the flow or volume of the gases being delivered to the bottom of an opening in the ground. Referring to Fig. 1, an opening or driven well is shown extending downwardly into the ground and the lower end thereof is presumed to be located in a bed of shale or other unmined material containing the desired hydrocarbon oils which are to be extracted. The outlet pipe 8 is continued by the downwardly extending pipe 11 which extends to a point immediately adjacent the lower end of the boring. The pipe 11 is supported at a point above the ground by cap 12 covering the upper end of the shaft casing 12^a which also projects for a suitable distance down into the ground and is designed to prevent the soil from falling into and closing the lower end of the driven well. At the top and if desired also at the bottom there may be an annular plug of concrete or some other solid material as indicated at 13 and designed to prevent the escape of gases from the boring. Hot gases are discharged through the pipe 8 and sent downwardly through the pipe 11 to the lower end of the boring. At this point the hot gases act on the oiliferous matter contained in the shale or bituminous sand stone or similar material surrounding the lower end

of the pipe 11. The material is heated and the oily matters and any water present will be driven out as vapor or as gas through the casing 12^a. If there be lateral cracks or
 5 porous strata in the shale or surrounding earthy material it may be that separate borings located at a distance from the pipe 11 could be provided to conduct to the surface the vapors or gases which have been
 10 generated and which are so provided under pressure in the porous strata or fissures. The treatment at the bottom of the boring brings about a vaporization which is conducted under pressure greater than atmospheric pressure and at very considerable
 15 temperature. The vaporized material and the gases of combustion pass upwardly through the casing 12^a and are directed into a trap 14 in which the heavier materials
 20 condense and may be drawn off through an outlet pipe 14^a. The lighter materials pass outwardly through a pipe 15 and are conducted into a condenser having coils 16 located within the condenser box 17. Liquid
 25 condensed in the coils together with the remaining gases pass through the pipe 18 into a final trap 19 where the liquid is confined and the gases may be led off through the pipe 20 to any suitable gas tank, not
 30 shown.

From the foregoing it will be seen that this invention provides a relatively inexpensive method of generating heat on the surface of the ground and applying this heat
 35 in an incombustible form to the deposit of oil bearing material located within the earth to vaporize the desired material and transport a maximum amount of the volatile products to the surface without mining the
 40 material. It is known that processes have been provided for providing combustion at the bottom of oil wells to throw out the oil material, paraffin and similar material and it is also known that various devices have been
 45 provided for operation at the bottom of the wells in order to generate heat at that point. This invention is an improvement over all such previous inventions in that the heat is generated above the ground and the hot
 50 gases are used for the production of valuable vapors, ammonia, and other material without mining the material and without the unsatisfactory results to be found when solvents are used introducing foreign material
 55 as is necessary when liquid solvents or steam is used. This process is particularly useful for the extraction of hydrocarbon materials when the residue does not constitute a valuable waste product such as is the case when
 60 certain shales are used which do not contain any appreciable amount of other useful material.

What I claim is:—

1. The process of extracting hydrocarbon
 65 material from earthy material while in its

natural state, in the ground, which comprises the production of hot gases of combustion substantially devoid of oxygen, the introduction of said hot gases of combustion into an opening extending into the earth
 70 and into contact with said earthy material containing the desired hydrocarbon material, heating and vaporizing the hydrocarbon material by contact with said hot gases of combustion, the conduction of the combined
 75 vaporized products and hot gases of combustion in their aeriform state from said opening in the earth, and the separation of the combined materials so extracted.

2. The process of extracting hydrocarbon
 80 material from earthy material while in its natural state, in the ground, which comprises the production of hot gases of combustion, the introduction of said hot gases of combustion into an opening extending into the
 85 earth and into contact with said hydrocarbon material, vaporizing the hydrocarbon material by contact with said hot gases of combustion under a pressure greater than atmospheric pressure, the conduction of the
 90 combined vaporized products and hot gases of combustion while in their aeriform state from the earth, and the separation of the combined materials so extracted.

3. The process of extracting hydrocarbon
 95 material from earthy material while in its natural state, in the ground, which comprises the production of hot gases of combustion, the release of a current of said hot gases of combustion within the earth and
 100 into contact with the hydrocarbon material to be extracted, vaporizing at least a portion of said hydrocarbon material by contact with said hot gases of combustion, the removal of the hot gases of combustion and
 105 the extracted hydrocarbon material taken up thereby while in the aeriform state, and the recovery of the extracted material.

4. The process of extracting hydrocarbon
 110 material from earthy material while in its natural state, in the ground, which comprises the production of hot gases of combustion, the introduction of a current of said hot gases of combustion into an opening
 115 extending into the earth and into contact with said hydrocarbon material, vaporizing at least a portion of said hydrocarbon material by contact with said current of said hot gases of combustion under a pressure greater than atmospheric pressure, the
 120 removal of said hot gases and the hydrocarbon material taken up thereby while in the aeriform state, and the separation of said material so removed.

5. The process of extracting hydrocarbon
 125 material from shale and similar material while in its natural state in the ground, which comprises producing hot gases of combustion substantially devoid of oxygen at a point removed from the shale, releasing
 130

said hot gases under pressure greater than atmospheric pressure into contact with the shale containing the desired hydrocarbon material, thereby vaporizing the hydrocarbon material from said shale by said hot
5 gases of combustion, removing the resultant hot gases with the extracted hydrocarbon

material taken up thereby while in the aeriform state, and recovering the extracted material.

In testimony whereof I have hereunto set
my hand.

10

DAVID T. DAY.