Nov. 18, 1924.

T- -----

H. K. STURDY, JR

DISPLAY DEVICE

Filed Sept. 8, 1923

1,515,909



TQ. L 20 Herbert K. Sturdy Jr. Part Jack Carlos Attorneys F.G. 6 By



Application filed September 8, 1923. Serial No. 661,675.

a specification.

10 of the type adapted to display small articles of the front plate to support the article to ject of this invention is to provide a holder and the following is a detailed description of this character which comprises a plural- of one construction of display device by ity of openings therein, and holder cards which these results may be obtained. ¹⁵ adapted to fit into and have their edges ar- With reference to the drawing, 10 desigupward above the plane of the front plate

To all whom it may concern: vide a front plate having a series of open-55 Be it known that I, HERBERT K. STURDY, ings therein and a member formed by fold-Jr., a citizen of the United States, residing ing a strip of cardboard or other material at Attleboro Falls, in the county of Bristol upon itself with one or both of its ends ar-⁵ and State of Massachusetts, have invented ranged to be tucked under the edges of the certain new and useful Improvements in opening in such a way that the holder card 60 Display Devices, of which the following is can not be accidentally disconnected therefrom, the folded portion of the holder being This invention relates to display devices adapted to stand at an angle above the plane such as jewelry and the like; and the ob- be displayed in this upstanding portion; 65

ranged to engage those of the openings, said nates the front plate of a display device and 70 cards having intermediate portions standing 11 the back plate thereof which is spaced from the front plate by means of intermediand adapted to have the articles to be dis- ate spacers 12 arranged along the edges of 20 played mounted on the upstanding portions. these plates. The front plate is provided With these and other objects in view, the with a plurality of openings 13, the side 75 invention consists of certain novel features walls of these openings being oppositely of construction, as will be more fully de- notched or recessed as at 14 intermediate its My improved article holder member 15 is preferably formed of cardboard and in so Figure 1 is a front view of my improved rectangular shape, as illustrated in Figure display device showing a plurality of open-4, the same being adapted to be folded upon ings in the front plate thereof, of the de- itself along the line 16 and this folded portion is provided with openings 17 into which Figure 2 is a sectional side elevation on the cuff buttons 20, or other article, to be 85 line 2-2 of Figure 1, showing spaced-apart displayed, are inserted. The width of the front and back plates and the holder cards rear end portion 19 of this holder is submounted therein supporting the articles of stantially that of the width of the opening through the notches 14 and is adapted to be Figure 3 is a fragmental section on line passed inwardly through these notches and 90 3-3 of Figure 1, showing the front and then extend back beneath the portions 18 back plates with a spacer interposed between between the front and back plates to securely retain the holder in its opening. To Figure 4 shows one of the holder cards further lock the holder in its inverted posiin extended position, one of the ends of the tion, I have notched its front edges as at 95 21 and inserted these notched edges into the Figure 5 shows one of the holder cards opening whereby the inherent spring in the stock of the holder causes its edge 22 to engage the edge 23 in the opening thereby securely locking the whole in its opening 100 effectually preventing the holder when so positioned, from dropping out of the card even when inverted. My improved display device is extremely simple and practical in construction and ef- 105 fective in its operation and by its use deboth heads of a button may be seen while vices such as cuff buttons and the like, may be mounted so that both the head members

scribed, and particularly pointed out in the upper and lower marginal edges. appended claims.

In the accompanying drawings:-

30 sired shape.

35 jewelry.

them.

card being notched.

40

folded intermediate its ends to support the article to be displayed above the plane of its supporting plate.

Figure 6 shows a cuff button which is one of the many articles of jewelry which may be displayed in my improved display device. 50

It is found in the displaying of such articles as cuff buttons where it is desired that mounted in its holder, of advantage to pro-

1,515,909

may be seen while supported in display powall thereof to support said folded portion sition. in upstanding position.

The foregoing description is directed solely towards the construction illustrated. 5 but I desire it to be understood that I reserve the privilege of resorting to all the mechanical changes to which the device is susceptible, the invention being defined and limited only by the terms of the appended 10 claims. I claim:

2

35 3. A display device for jewelry or the like, comprising a plate having an opening therein generally rectangular in shape with opposite recessed side walls, in combination with a holder card having an upstanding 40 intermediate portion folded upon itself to provide portions in substantially parallel planes having one end adapted to extend through said side wall recesses and beneath 1. A display device for jewelry or the like, the adjacent edges of the plate and the other 45 comprising a plate having an opening there- end portion to engage an end wall of the HERBERT K. STURDY. JR.

in generally rectangular in shape with its opening and support said folded portion in 15 opposite side walls recessed, in combina- upstanding position, whereby the articles to tion with a holder card folded to provide be displayed are exposed on both faces. an upstanding intermediate portion and hav- 4. A display device for jewelry or the 50 ing one end portion extending through said like, comprising a plate having an opening recesses beneath the stock of said plate adja- therein generally rectangular in shape with 20 cent the recesses and its opposite end engag- opposite recessed side walls, in combination ing an end wall of said opening to support with a holder card having an upstanding said folded portion in upstanding position. intermediate portion folded upon itself and 55 2. A display device for jewelry or the having one end portion shaped to extend like, comprising a plate having an opening through said side wall recesses and beneath 25 therein generally rectangular in shape with the stock at the rear of the recesses and the its opposite side walls recessed, in combina- other end portion to engage an end wall of tion with a holder card folded to provide the opening forward of the recesses to sup- 60 an upstanding intermediate portion and port said folded portion in upstanding pohaving one end portion extending through sition whereby the articles to be displayed said recesses beneath the stock of said plate are exposed on both faces. 30° and under an end wall of said opening, and In testimony whereof I affix my signaits opposite end being notched to extend into ture. said opening and engage the opposite end

.

.

.

. .

.