Ċ

Nov. 18, 1924.

E. F. MEYER

Filed Jan. 4, 1924

+

10

1,516,024

Fig. 1.

HAT HANGER

Fig. 2.



Patented Nov. 18, 1924.

1,516,024

EUGENE F. MEYER, OF LOUISVILLE, KENTUCKY.

HANGER. HAT

UNITED STATES PATENT OFFICE.

Application filed January 4, 1924. Serial No. 684,375.

To all whom it may concern: wire forming the shank 12. The extremi-Be it known that EUGENE F. MEYER, a ties of the wires are then bent at right 55 citizen of the United States, residing at angles to this plane as at 14 and after ex-Louisville, in the county of Jefferson and tending out a certain distance are rebent 5 State of Kentucky, has invented certain new to form loop ends 15. The rebent portions and useful Improvements in Hat Hangers, extend through said plane and are again of which the following is a specification. rebent to form end loops 16 and terminal 60 This invention relates to hat hangers and portions 17, the latter being in line with those parts of the wire between the bends has special reference to a display hanger 14 and 15. In this manner there is formed 10 for hats and caps. an upper hook, a shank, and a pair of lower One object of the invention is to provide an improved and simple form for a device hooks having flat parallel loop ends. 65 In the form shown in Figure 3 there is of this description. A second important object of the inven- illustrated a hanger suitable for a single 15 tion is to provide a hanger of this de- hat and in this form one end of the wire is scription made from a single length of bent to form a supporting hook 17. The wire, bent in a novel and improved man- wire is then bent as at 18 at right angles 70 to the plane of the supporting hook and is ner. A third object of the invention is to pro- next bent at 19 to extend downward and

20 vide a novel and improved double hanger made from a single length of wire and bends 18 and 19 forming an offset 21. At adapted to support a pair of hats or caps.

With the above and other objects in view as will be hereinafter apparent, the in-25 vention consists in general of certain novel details of construction and combinations of parts hereinafter fully described, illustrated in the accompanying drawings and specifically claimed.

30 several views, and:

Figure 1 is a perspective view of the hanger in one position.

Figure 2 is a similar view showing another position of the double hanger.

Figure 3 is a view showing modified form for a single hanger.

40 shown in Figure 1 a suitable length of wire made in the form and construction of the is taken and this is doubled at its center invention without departing from the maportion at at 10. The two halves of the terial spirit thereof. It is not, therefore, de-95 wire are bent back so as to lie along side sired to confine the invention to the exact of each other for a suitable distance. Ad- form herein shown and described, but it is desired to include all such as properly come 45 jacent bend 10 the doubled wire is bent transwithin the scope claimed. versely of the plane passing through the axis of the halves so as to form a hook 11. Having thus described the invention, 100 The remaining portion of the doubled wire what is claimed as new, is: forms a shank 12 which depends from the A hat hanger formed from a single length of wire bent double at its middle to hook. The ends of the wire are first bent 50form a pair of parallel lengths, the wire adaway from each other and upward to form jacent the bend being bent into a supporting 105 the U-shaped bends 13. These bends lie in the plane passing through the axes of the hook and the remaider of the parallel por-

form the shank 20, the part between the the bottom of the shank the wire is bent 75 upwards in a U-shaped bend 22, the outer length 23 being parallel to the shank 20 and lying in the plane of the hook 17. At the upper end of this outer length there is provided a flat loop 24 similar to the loop 80 previously described and also lying in the plane of the hook 17.

In the accompanying drawings like char- It will be obvious that while the device acters of reference indicate like parts in the here shown has been made from wire, it may be cast in this form, made from 85 separate parts, either all wood or all metal or part of one and part of the other, and in fact may be made in a variety of ways.

> There has thus been provided a simple and efficient device of the kind described 90 and for the purpose specified.

In the construction of the invention as It is obvious that minor changes may be

35

.

· · ·

· .

1,516,024

tions forming a shank, the hook being at bent portions being each bent to form a right angles to a plane passing through the flat loop at right angles to said plane and axes of the shank portions, the ends of said having its longer axis horizontal. wires being first bent away from each other ⁵ and upwardly in said plane to form hat ture. hooks and the extremities of the upwardly

In testimony whereof I affix my signa- 10 EUGENE F. MEYER.

· ·

.

.

. · · .

· · · · · • • •

. · · · . · · · · · · · .

· . . . · .

. . . •

. · . ·

· · · . · · · • -.

· · · · · · · . • .

- . . . • . · · . . .

· . · • . . · · · · .

. · · · · . . ·

. . · . . • . . . • .

.* . '

· · · .

. . . .

. . .

.

· . . .

· . · .

· · · · .

> .

. .

> . . · · ·

. · .

· .