



March 20, 1928.

1,663,406

H. W. HOLMES ET AL

SLUICE GATE

Filed April 23, 1926



Harry W. Holmes
Erwin B. Philips
INVENTORS

BY *Edwin J. Carver*
ATTORNEY

UNITED STATES PATENT OFFICE.

HARRY W. HOLMES AND ERWIN B. PHILIPS, OF KENTON, OHIO, ASSIGNORS TO PHILIPS AND DAVIES, A PARTNERSHIP COMPOSED OF ERWIN B. PHILIPS AND FRANCIS DAVIES, OF KENTON, OHIO.

SLUICE GATE.

Application filed April 23, 1926. Serial No. 104,201.

Our invention relates broadly to sluice gates and pertains, more particularly, to sluice gates of the type wherein the sluice-way frame and the contacting rim of the sluice gate are so inclined as to prevent frictional resistance between these parts during opening and closing of the gate.

A sluice gate of the general type to which the present invention relates is shown in the United States patent to Broome, No. 1,306,370, and, by reference to Figure 4 thereof, it will be noticed that there is an offset or depression in the tunnel floor at the sluice-way frame or, in other words, that the floor of the tunnel on the downstream side of the sluice-way frame is at a higher level than the floor of the tunnel on the upstream side of the sluice-way frame. The gate shown in the Broome patent is vertically reciprocable to effect opening and closing of the sluice-way and is provided with set-screws whereby the extent of descent of the gate may be adjusted so the rim of the gate will form a water-tight seal with the sluice-way frame and permit of elevation of the gate without first overcoming friction between the sealing rim of the gate with the sluice-way frame. In other words, the sluice gate may be so adjusted by proper manipulation of the set-screws that, when the elevating force is applied, the sealing rim of the gate will leave its seat on the sluice-way frame immediately and without friction between it and the sluice-way frame. Also, in the Broome patent, the seal between the bottom of the gate sealing rim and the sluice-way frame is obtained by overlapping these parts and, consequently, manipulation of the set-screws for the purposes above-described automatically varies the extent of overlapping and so results in a water-tight seal at the bottom of the gate without special adjustment. This overlap between the bottom of the gate-sealing rim and the bottom portion of the sluice-way frame necessitates the above-referred to offset in the tunnel floor.

This offset in some situations is undesirable in that it induces eddy currents which detrimentally affect the water-flow efficiency of the sluice-way and are likely to damage the entrance to the tunnel. A further objectionable feature of this construction is

that the offset forms a lodging place for gravel, sand and other débris which may accumulate and prevent or interfere with complete closing of the gate.

The principal object of our present invention is the elimination of the above-described offset in the floor of the tunnel, and this will prevent accumulation of débris which might interfere with proper closing of the gate and avoid eddy currents which might damage the entrance to the tunnel or impair the water-flow efficiency of the sluice-way.

By doing away with the offset in the tunnel floor, the overlapping seal between the bottom of the gate-sealing rim and the bottom portion of the sluice-way frame is, also, eliminated and, accordingly, a further object of our invention is the provision of an independently adjustable means for obtaining a water-tight seal at the bottom of the gate. Unlike the overlapping bottom seal of the Broome construction, which automatically effects a water-tight seal when the gate is adjusted for eliminating friction, our present invention employs a separately adjustable member which must be independently positioned after the gate has been adjusted for eliminating friction between the side and top portions of the gate seal rim and the corresponding portions of the sluice-way frame.

Other objects of our present invention will be explained in the following description and all features are illustrated in the accompanying drawings wherein similar reference numerals designate corresponding parts in the several figures and wherein—

Figure 1 is a fragmentary sectional view of the bottom portion of a sluice gate and sluice-way frame taken on line 1—1 of Figure 2; and

Figure 2 is a fragmentary vertical sectional view of the bottom portion of a sluice gate and sluice-way frame taken on line 2—2 of Figure 1.

In the drawings, our invention is shown in association with a sluice-way 1 that is provided adjacent its entrance with a frame 2 having inclined seal strips 3 that are designed to form a seat for the similar strips 4 carried by the sluice gate 5. The lowermost portion of the sluice-way frame 2 is

embedded in the masonry 6 and is provided with a seat bar 7 and a striking plate 8. Both the seat bar 7 and the striking plate 8 are flush with the bottom 9 of the tunnel and the upstream portion of the tunnel bottom is in substantially the same plane as the downstream portion of the tunnel bottom, but the portion shown to the right of the sluice-way frame in Figure 2 could be at a lower level than the upstream portion, or the portion shown to the left of the frame in Figure 2, without affecting this invention since the principal object, as above-stated, is the elimination of the depression in the tunnel floor on the upstream side of the sluice-way frame. It will be noted, by reference to Figure 2, that this form of construction does away with all obstruction to free water flow over the bottom of the tunnel and thereby avoids the formation of eddy currents and the accumulation of debris near the gate seat and the striking plate.

The sluice gate 5, on its opposite sides, is provided with endless chain anti-friction rollers 10 which operate between vertical guides 11 when the gate is elevated or allowed to descend. Inclined seal strips 4, forming the side members of the seal rim, are secured to the downstream side of the gate and contact with the similar seal strips 3 of the sluice-way frame 2 when the gate is closed. The respective top seal strips of the gate and the sluice-way frame are of usual construction. The gate shown may be of the self-closing variety, that is capable of closing against the sluice-way frame without the application of compression forces to its top, and the respective seal strips of the sluice-way frame and gate are inclined from the vertical to make possible a tight seal therebetween without allowing the gate seal strips to slide over the sluice-way frame seal strips. This feature avoids frictional resistance between the gate seal strips and the sluice way frame seal strips when the gate is being vertically elevated, because the gate seal strips leave their seat immediately upon application of the lifting force and do not slide over or upon the sluice way frame seal strips to an extent which would make the elevation of the gate difficult or impossible without the application of excessively large lifting forces.

For the purpose of adjusting the extent of descent of the gate to ensure a water-tight seal without encountering friction when elevating the gate, the set-screws 12 are provided. These set-screws abut against the striking plate 8 and are carried by the beam 13. By suitably adjusting these set-screws, the lowermost position of the gate may be determined, a water-tight seal between the seal strips of the gate and the corresponding seal strips of the sluice-way frame effected and the seal strips of the gate

positioned in non-frictional relation to the seal strips of the sluice-way frame.

Since the overlapping and, consequently, self-adjusting gate and frame bottom seal referred to in connection with the Broome patent has been done away with by eliminating the offset in the tunnel floor, it becomes necessary to provide a separately adjustable means for obtaining a water-tight seal between the bottoms of the gate and sluice-way frame for all positions in which it may be necessary to set the gate to obtain a water-tight and nonfrictional relation between the side and top seal strips of the gate and the corresponding seal strips of the sluice-way frame. The means provided for this purpose comprises a seal bar 14 which is provided with a plurality of slotted holes 15. This seal bar 14 has its opposite ends fitted into cutaway portions 16 of the side seal strips 4 and may be adjusted up or down with relation to such side seal strips and the seat bar 7. Bolts 17 which extend through holes in the flanges 18 of beam 13 and through the slotted holes 15 are provided for securing the seal bar 14 in any adjusted position.

To further explain the important features of our invention, the adjustment of the gate with relation to the side seal strips of the sluice-way frame and the seat bar 7 will be briefly described. The bolts 15 are loosened sufficiently to permit the seal bar 14 to slide freely, then the gate or, rather, the lowermost position of the gate, is adjusted up or down by means of the set-screws 12 until the side and top seal strips of the gate are positioned in water-tight and non-frictional relation to the corresponding seal strips of the sluice-way frame, whereupon the set-screws 12 may be secured to maintain this position by means of the lock nuts 19. When this has been accomplished, the seal bar 14 may be lowered or placed in water-tight relation to the seat bar 7, and fastened by means of the bolts 17 which have a water-tight relation to the flanges 18 of the beam 13. The adjusting screws 12 may be omitted without impairing the value of this invention though the seal bar 8 is not intended to be a stop for the gate when lowered onto the frame seal bar 7.

From the preceding description, it will be obvious that our invention effectively eliminates both offsets and the necessity for offsets in the tunnel floor, and makes for more positive and certain operation of the gate, avoids the formation of eddy currents and increases the water flow efficiency of the sluice-way.

While our invention has been described with particular reference to the type of sluice gate shown in the Broome patent, yet it is understood that it may be employed in other types of sluice gates and for other pur-

poses without foregoing any of its advantageous features as set forth in the appended claims.

Having thus described our invention, what we claim is:

1. In a sluice gate, adjustable sealing means mounted upon the bottom of said gate, and other means on the gate for limiting the lowermost position of said gate.
2. In a sluice gate, adjustable sealing means mounted upon the bottom of said gate, and other adjustable means on the gate for limiting the lowermost position of said gate.
3. The combination of a sluice way and a sluice way frame having a striking plate and a seal bar so mounted therein as to be flush with the floor of said sluice way, the floor of the sluice way at the sluice way frame being substantially flat, and free of any offsets.
4. The combination of a sluice way and a sluice way frame having a striking plate and seal bar so mounted therein as to be flush with the floor of said sluice way, of a coacting sluice gate having a means for limiting the lowermost position of said gate relative to said frame adapted to rest upon said striking plate, and adjustable sealing means mounted upon the bottom of said gate adapted to contact with said seal bar, the floor of the sluice way being free of any offsets.
5. The combination of a sluice way and a sluice way frame having a striking plate and seal bar so mounted therein as to be flush with the floor of the said sluice way, of a coacting sluice gate having a means for limiting the lowermost position of said gate relative to said frame adapted to rest upon said striking plate, and adjustable sealing means mounted upon the bottom of said gate adapted to contact with said seal bar, the floor of the sluice way on the up stream side of said sluice way frame being substantially flat, and free of any offsets.
6. The combination with a sluice way frame having an inclined seat and a sluice gate having a similarly inclined seat, said gate having means for limiting the lowermost position of said gate with relation to said frame and adjustable means mounted upon the bottom of said gate for forming a water tight seal between the bottom of said frame and said gate.
7. The combination of a sluice way and a sluice way frame having an inclined seat of a sluice gate having a similarly inclined seat vertically movable with respect to said frame, said gate having means for limiting the lowermost position of said gate with relation to said frame and adjustable means mounted upon the bottom of said gate for forming a water tight seal between the bottom of said frame and said gate.
8. In a sluice gate, adjustable sealing means mounted upon the bottom of said gate, and means independent of said sealing means for limiting the lowermost position of said gate.

In testimony whereof we hereby affix our signatures.

HARRY W. HOLMES.
ERWIN B. PHILIPS.