
W. H. ROSE

GARMENT SUPPORT

Filed Dec. 17, 1927



## UNITED STATES PATENT OFFICE.

WILLIAM H. ROSE, OF JERSEY CITY, NEW JERSEY.

GARMENT SUPPORT.

Application filed December 17, 1927. Serial No. 240,724.

My invention relates to garment supports and refers particularly to supports adapted for attachment to radiators.

It is frequently desirable to wash and dry 5 small articles of wearing apparel without being submitted to the expense and delay incident to regular laundering.

The washing of articles of this character 10 ficulty is usually experienced in finding a prises a supporting rod 10, the lower portion 65 convenient and effective means for drying the thus washed garments.

ing a wet garment upon a heated radiator bent into a suspending hook 13. 15 has numerous objections among which may In operation the radiator hook 13 is placed 70 be mentioned the possibility of soiling the goods because of the dusty and dirty condition of the radiator, the intense heat at the points of contact between the garment 20 and the heated metal and the liability of rust spots.

jectionable features incident to the usually my invention.

My device comprises an elongated mem- free from contact with, the radiator. ber having opposed radiator supports which In the modification shown in Figure 5, the zontal radiator conduit thus holding the but out of contact with, the radiator.

expensive and is readily carried in the ordi- any particular form of radiator. nary suit case and that it subjects all por- It will thus be seen that my device pretions of the garment to practically equal contact with dust and dirt.

In the accompanying drawing illustrating modified forms of the device of my invention, similar parts are designated by similar numerals.

Figure 1 illustrates a radiator with one form of the device of my invention employed therewith.

Figure 2 is an enlarged vertical cross-section of the radiator shown in Figure 1, with my device employed therewith.

Figure 3 is a perspective view of my de-55 vice shown in Figure 2.

Figure 4 is a side view of a modified form of my device.

Figure 5 is a front view of the device of Figure 4.

Figure 6 is a side view of a modified 60 form of my device partly in vertical crosssection and broken away.

The particular form of the device of my is readily accomplished but considerable dif- invention shown in Figures 1, 2 and 3 comof which is bent into two flaring supports 11, 11 and terminating in a radiator hook The frequently employed method of plac- 12. The upper portion of the rod 10 is

between two of the vertical radiator conduits 14, 14 and hooked beneath and in abutment with one of the radiator connecting conduits 15, the two flaring, or wing, supports resting upon the upper faces of the two vertical con- 75 duits 14, 14, the device being thus positioned All of the above mentioned, and other, ob- in an inclined position as shown in Figure 2.

The device is thus retained in such an inemployed methods of drying by means of clined position that a garment, or other ma-25 radiator heat are overcome by the device of terial, carried by the suspending hook 13 80 will be positioned in close proximity to, but

will abut upon the upper portion of a flaring supports of the previous figures are 30 radiator, when a radiator hook member is replaced by a truncated triangular radiator 85 partially around and abutting upon a hori-support 16 fixedly attached to the rod 10.

In the modification shown in Figure 6, device in inclined position so that a garment the rod 10 carries a movable truncated conisuspended from the upper portion of the de- cal shaped radiator support 16, maintained in vice will be positioned in close proximity to, any desired position upon the rod 10 by the 90 set screw 17, thus allowing of the movement It will thus be seen that my device is in- of the radiator support to fit the device to

sents a simple, economical and convenient 95 heat without the danger of injury through means whereby moist garments and other uneven heating, production of rust spots or materials may be effectively dried through the medium of a heated radiator.

I do not limit myself to the particular size, shape, number, arrangement or material 100 of parts as shown and described as these are given simply as a means for clearly describing the device of my invention.

What I claim is:—

1. In a garment support capable of attach- 105 ment to a radiator, in combination, an elongated member having a radiator hook at one end capable of placement around the under face of a horizontal radiator conduit, an extended support carried by the elongated 110

member capable of abutment upon the adjacent upper perpendicular portion of a radiator and so positioned that when the radiator hook is in abutment with the horizontal radiator conduit the device will be maintained in inclined position and a suspending hook carried by the opposite por-

tion of the elongated member.

2. In a garment support capable of attachment to a radiator, in combination, a rod one end of which is bent to form a radiator hook capable of abutment around the under face of a horizontal radiator conduit and the other end of which is bent to form a reverse suspending hook and a triangular shaped radiator support carried by the rod, the plane of the triangular shaped member being in angular position with respect to the plane of the hooks.

.

. . .

3. In a garment support capable of attachment to a radiator, in combination, a rod one end of which is bent to form a radiator hook capable of abutment around the under face of a horizontal radiator conduit and the other end of which is bent to form a reverse suspending hook, a triangular shaped radiator support carried by and movable along the rod, the plane of the triangular member being in angular position with respect to the plane of the hooks, and means whereby the triangular member may be immovably attached to the rod at any predetermined position.

Signed at New York city, in the county of New York and State of New York, this 35

15th day of December, 1927.

WILLIAM H. ROSE.