





April 8, 1930.

H. A. TAYLOR

1,753,671

BASKET AND COVER THEREFOR

Filed Jan. 30, 1928



Witness
H. Vernon Olson

INVENTOR
Hamblen A. Taylor
BY
Warren D. House
His ATTORNEY

UNITED STATES PATENT OFFICE

HAMBLEN A. TAYLOR, OF SAN BENITO, TEXAS, ASSIGNOR TO J. O. PRENTISS AND L. S. WITTE

BASKET AND COVER THEREFOR

Application filed January 30, 1928. Serial No. 250,388.

My invention relates to improvements in baskets and covers therefor.

One of the objects of my invention is to provide a novel fastener for a basket cover which will effect the functions of the usual slat extension on the top of the cover and which securely hold the cover from upward and lateral movement on the basket.

A further object of my invention is to provide a novel fastener of the kind described and novel bail handles on a basket adapted to be releasably engaged by the fastener so that the cover is held from upward and lateral movement.

Still another object of my invention is to provide a novel cover fastener for a basket, which is simple, cheap, durable, not liable to get out of order, which is easily operated in fastening and unfastening, which affords strength to the cover and at the same time enables it to be light, and which is efficient in operation.

The novel features of my invention are hereinafter fully described and claimed.

In the accompanying drawing, which illustrates the preferred embodiment of my invention,

Fig. 1 is a side elevation of a basket and cover therefor provided with my improved fastener, shown fastened to the handle of the basket.

Fig. 2 is a top view of my improved cover, the fastener being shown with its end portions unbent and extended through the bail handles.

Fig. 3 is an enlarged sectional view through a portion of the basket and cover, the fastener being shown bent over the bail handle. Fig. 4 is an enlarged section on the central vertical transverse plane of Fig. 2.

Similar reference characters designate similar parts in the different views.

1 designates a usual form of basket having at opposite sides two bail handles 2, each of which in its transverse portion may be provided with a depressed portion forming a kink 3.

The basket cover may comprise the usual ring 4 having mounted thereon a top comprising the usual slats 5.

Extending across the slats 5 is my improved fastener which may comprise a pliable wire formed into a loop designated by 6, the end portions of the fastener being made to encircle and tightly embrace diametrically opposite portions of the ring 4, and respectively projecting outside the outer sides thereof, and adapted to be respectively extended through the bail handles 2, Figs. 2 and 4, and to be bent over the transverse portions of the handles 2, in which bent condition, as shown in Figs. 1 and 3, the end portions of the fastener 6 respectively embrace the kinks 3, and bear against both inner sides of each of said handles 2, thereby holding the cover from upward and lateral movement from its operative position.

The fastener 6 effects the functions of the usual diametrical slat having extensions arranged to be extended through the handles to hold the cover from lateral movement, so that such extension slat may be eliminated, while having its function effected by the fastener 6, which at the same time holds the cover and the slats 5 thereof from upward movement, as described. The fastener 6 thus effects three functions, that of reinforcing and holding the slats 5 from upward movement, and those of holding the cover as a body from upward and lateral movement.

In applying the cover to the basket, the end portions of the fastener 6, while in their horizontal position, are extended through the handles 2, as shown in Figs. 2 and 4, after which they are bent over the transverse portions inwardly and downwardly, as shown in Figs. 1 and 3, thereby securely holding the cover in its proper operative position.

To remove the cover, it is but necessary to unbend the bent over portions of the fastener 6, one end portion being bent downwardly and outwardly, after which the cover may be lifted from the basket. With the provision of the novel fastener herein described, which is fastened to and extends clear across the top of the cover, and is extended through the bail handles and is bent thereover, the slats of the top are held from bulging, accessory fastening means are eliminated, as is the usual diametrical slat that has project-

ing ends that pass through the bail handles, and which is difficult to insert through and to remove from the handles, and which has its projecting ends subjective to being struck with liability of damage to the cover.

5 The provision of the single loop fastener affords double protection to the slats of the top of the cover, and a firm engagement with the arms of the bail handles, for holding the cover from upward, lateral and turning move-
10 ment of the cover on the basket.

I do not limit my invention to the structure shown and described, as many modifications, within the scope of the appended claims, may be made, without departing from the spirit
15 of my invention.

What I claim is:—

1. A basket cover having a top disposed, when in operative position on a basket, wholly
20 between the bail handles thereof, and a pliable fastener extending clear across, fastened to and projecting outside opposite edges of the top and adapted to have its end portions extended respectively through said handles
25 and to be bent thereover to hold the cover from upward movement, and arranged to engage both inner sides of each of said handles to hold the cover from lateral movement.

2. A basket cover having a ring and a top mounted thereon, and a pliable fastener fastened to and extending clear across said top
30 and projecting outside opposite outer sides of said ring and encircling said ring at opposite diametrical portions thereof, and adapted to have its end portions extended re-
35 spectively through opposite bail handles of a basket and to be bent thereover to hold the cover from upward movement and arranged to engage said handles to hold the cover from
40 lateral movement.

In testimony whereof I have signed my name to this specification.

HAMBLEN A. TAYLOR.