

Dec. 9, 1930.

F. E. TERMAN

1,784,119

OSCILLOGRAPH

Filed Nov. 19, 1929





FIG. 2



INVENTOR.
 Frederick E. Terman,
 BY
 Wm. J. Herdman
 ATTORNEY.

UNITED STATES PATENT OFFICE

FREDERICK E. TERMAN, OF STANFORD UNIVERSITY, CALIFORNIA, ASSIGNOR TO WIRED RADIO, INC., OF NEW YORK, N. Y., A CORPORATION OF DELAWARE

OSCILLOGRAPH

Application filed November 19, 1929. Serial No. 408,390.

My invention relates broadly to an oscillograph apparatus and more particularly to a circuit arrangement for an oscillograph in which the oscillograph record may be taken independently of the characteristics of the circuits of the oscillograph.

One of the objects of my invention is to provide a circuit arrangement for an oscillograph in which voltage oscillograms may be made by employing a transformation circuit for impressing a smaller potential upon a low impedance circuit and developing current variations that can be registered by the oscillograph.

Another object of my invention is to provide a circuit arrangement for an oscillograph in which an electron tube is employed in inverted order, with the input circuit included between the plate and cathode and the output circuit included between the grid and cathode and connected to the oscillograph vibrator, whereby the voltage to be photographed may be applied directly to the input circuit and a reducing action obtained for transforming the impressed voltage into a smaller potential acting in the output circuit for developing current variations that can be registered by the oscillograph.

Still another object of my invention is to provide a circuit arrangement for an oscillograph wherein oscillograms may be taken of relatively high voltage by the direct connection of an electron tube circuit to the potential to be photographed and the transformation thereof into a lower potential developing current variations which can be registered upon the oscillograph.

A further object of my invention is to provide an oscillograph circuit which consumes substantially negligible power and which may be connected permanently in a power line for observing at all times the condition of the power distribution system by the making of a continuous oscillograph record of the power transmitted disturbances and other surges in the line for enabling efficient operation of a power distribution system to be maintained.

Other and further objects of my invention reside in the circuit arrangement for an os-

cillograph, as set forth more particularly in the specification hereinafter following and by reference to the accompanying drawings in which:

Figure 1 diagrammatically illustrates circuit arrangements of the oscillograph of my invention; and Fig. 2 shows a characteristic curve illustrating the principle of operation of the inverted electron tube circuit employed in the oscillograph of my invention.

The oscillograph of my invention employs an inverted electron tube circuit which is set forth more fully in my co-pending application, Serial No. 405,363, filed November 7, 1929, entitled Electron tube circuit, wherein the input circuit of the electron tube is included between the plate and cathode electrodes with a negative potential biasing the plate electrode. The output circuit is included between the grid and cathode electrodes and constitutes a low impedance path. The input circuit across the plate and cathode electrodes may be connected directly to the high potential circuit in which the voltage characteristics are to be measured. The voltage which is impressed upon the input circuit is transformed into a smaller potential acting in the low impedance grid circuit for developing current variations that can be registered by the oscillograph. The oscillograph functions substantially independently of the circuit characteristics of the inverted electron tube system as the inverted electron tube system consumes substantially no current.

By reason of the low current consuming properties of the oscillograph system of my invention, it is practical to permanently connect the oscillograph to a power circuit in a power distribution system for observing a continuous record of the power transmitted and of the surges and disturbances which occur in the line. The character of service rendered to customers may thereby be readily checked.

Referring to the drawings in more detail, reference character 1 designates the electron tube employing the circuit arrangement of my invention. The electron tube 1 includes cathode 2, grid 3 and plate 4. The input

circuit of the electron tube connects between cathode 2 and plate 4. A negative biasing potential is applied to the plate 4 from battery 5 through resistance 6. The input circuit connects through condenser 7 to the power circuit 8 on which the oscillograph measurements are to be taken. I have designated generally the elements of the power distribution system at 9 to which the oscillograph circuit of my invention may be permanently connected by reason of its low power consuming characteristics. The cathode 2 is heated from a suitable source 10 through impedance 11. The output circuit extends between cathode 2 and grid 3 completing a low impedance path through resistance 12, resistance 14 and source of potential 15. The positive terminal of the source of potential 15 is directed toward the grid electrode 3. The voltage of the plate biasing battery 5 is such as to cause the electron tube 1 to operate on a straight line portion of its characteristic curve, indicated in the diagram of Fig. 2.

The resistance 12 is introduced in the output circuit for the purpose of straightening or correcting the characteristic of the tube and has a value which is at least twice the dynamic grid resistance. The vibrator element 16 of the oscillograph which is suspended at 18 and 19 for movement within an electromagnetic field designated at 17 is connected in a circuit across the terminals of resistance 14. The oscillograph circuit includes battery 20 and potentiometer 21, with a variable tap 22 thereon. The mirror of the vibrator is exposed to a source of light 23, which is reflected and photographically recorded on moving film 24. The parts of the oscillograph have been shown in elementary form and are merely for the purpose of illustrating the principles of my invention and are not to be regarded as setting forth structural features of my invention. The resistance 14 and the potentiometer 21 balance the normal steady grid current out of the vibrator 16. Values of 100 to 1000 ohms are suitable for resistance 14, while potentiometer 21 should have considerably less resistance than resistance 14. I have found that a resistance proportion of 1 to 10 between the value of resistance 14 and the resistance of potentiometer 21 is satisfactory.

The distortion introduced by the tube can be determined from the static curves, and the oscillograms corrected accordingly. This distortion can be minimized by making use of the straight line portions of the characteristic, and also by inserting a resistance in series with the grid battery, shown at 12 in Fig. 1. This resistance has the effect of straightening out the characteristic, which becomes practically a straight line if 12 is two or three times the dynamic grid resistance. When the resistance is used a higher

grid battery potential must be employed to make up for the additional voltage drop.

The vibrator of an ordinary oscillograph requires from 50 to 100 milliamperes of current to give a good deflection. This amount of current generally requires two 7.5-watt tubes in parallel, or a single 50-watt tube, if distortion is to be avoided in the transformation.

By reason of its practically infinite resistance, the plate circuit of the inverted vacuum tube can be safely introduced into any high-voltage low-amperage circuit. By the use of a tube with the proper step-down ratio, and with suitable insulation resistance, the high voltage to be photographed is stepped down without additional apparatus. The oscillograph is in a low potential circuit, and can accordingly be handled easily and safely. In cases where it is desired to photograph a wave consisting of an alternating current potential superimposed on a D. C. potential, as in the case of the plate to filament voltage of an oscillating vacuum tube, the plate biasing battery can frequently be dispensed with.

I have found the oscillograph of my invention highly practical in its construction and successful in its operation. While I have described my invention in one of its preferred embodiments, I desire that it be understood that modifications may be made and that no limitations upon my invention are intended other than those which are imposed by the scope of the appended claims.

What I claim as new and desire to secure by Letters Patent of the United States is as follows:

1. An electrical indicating system comprising, a source of variable current, an electron discharge device including plate, grid and cathode, an input circuit included between said plate and cathode and connected to said source of variable current, means interposed in said input circuit and adapted to render the alternating component only of said variable current effective on said plate, an output circuit included between said grid and cathode, and an electrical indicating device in said output circuit.

2. An oscillograph system comprising, a source of variable current, an electron discharge device including a plate, grid and cathode, an input circuit included between said plate and cathode and connected to said source of variable current, means interposed in said input circuit and adapted to render the alternating component only of said variable current effective on said plate, an output circuit included between said grid and cathode, and an oscillograph vibrator connected in said output circuit.

3. An electrical indicating system comprising, a source of fluctuating voltage, an electron discharge device including plate, grid and cathode, an input circuit included be-

tween said plate and cathode and capacitively coupled to said source of fluctuating voltage, an output circuit included between said grid and said cathode, and an electrical indicating device connected in said output circuit.

4. An oscillograph system comprising, a source of fluctuating voltage, an electron discharge device including plate, grid and cathode, an input circuit included between said plate and cathode and capacitively coupled to said source of voltage, an output circuit included between said grid and filament, and an oscillograph vibrator connected in said output circuit, said vibrator being adapted to indicate the instantaneous value of said voltage.

5. An oscillograph system comprising, a source of fluctuating voltage, an electron discharge device including plate, grid and cathode, an input circuit included between said plate and cathode, a capacitance interposed in said input circuit between said plate and said source of voltage, an output circuit included between said grid and cathode, and an oscillograph vibrator connected in said output circuit, said vibrator being adapted to follow the fluctuations of said voltage.

In testimony whereof I affix my signature.

FREDERICK E. TERMAN.

30

35

40

45

50

55

60

65