
FLORAL RACK

Filed Nov. 24, 1930



UNITED STATES PATENT OFFICE

CLARENCE J. WHITE, OF PEORIA, ILLINOIS

FLORAL RACK

Application filed November 24, 1930. Serial No. 497,732.

This invention has reference to improve spectively serving to brace the frame, such ments in floral racks particularly of the type lateral rods also serving to support certain for use by undertakers and funeral directors portions to be described. for displaying floral pieces at funeral serv- A top supplemental rack portion is pro-5 ices.

thereby.

an upper portion or section of such rack can yoke of the main frame 1 in such manner as 65 supported in other positions including a hor-connection may be otherwise created. izontal one.

25 display.

In addition, the invention includes certain features of construction believed to be novel, and which will be pointed out in the following specification and shown in the appended ³⁰ drawing forming part hereof, and wherein:

Figure 1 shows the rack of my invention in perspective.

Figure 2 is a side elevation of the same. Figure 3 is a plan of a shelf shown in Fig-35 ures 1 and 2, the same being illustrated in a collapsed flat position as for storage or ship-

ment. ger arrangement of Figures 1 and 2.

Figure 5 is an end elevation of the same on a larger scale.

Figure 6 shows in perspective parts of a latch arrangement, and

Figure 7 is an end elevation of the same. The main portion of the rack comprises in this instance a rectangular frame 1 bent into the form of a U, the leg extremities of which are recurved to create supporting feet 1', by preference merely, there being longitudinal- tion 4, 5, 6, the other ends of the rods being

vided which in this instance, also, is rectangu- 55 The invention has for an object, the pro- lar in form and comprises a frame 4 braced vision of a rack that while simple in construc- by rods 5 which may be parallel to the rods 2 tion and inconspicuous in appearance as is of the main rack portion 1, 2, 3, and braced required in such devices, part thereof can be also by lateral rods 6, all of the rods of both 10 adjusted to different positions with respect rack portions being preferably electrically 60 to the other part thereof for the best disposal welded in position at their ends. At least and arrangement of a floral piece carried two of the rods 5 extend beyond the limits of one end of the frame 4 and eyes 5' formed Another object is to provide a rack wherein thereon take around the upper portion or be supported in a position lying in the same to hingedly connect the two rack portions, it plane with the main portion, or that can be being understood, however, that the hinged

A prop or support is provided for the main Again, an object lies in the provision of a rack portion 1 which may comprise a pair of 70 shelf portion capable of attachment to the rods 7 connected by cross rods 8, for example, rack at any desired position or location for the upper end of each rod 7 having an eye to use in the disposal of a floral piece to the best engage a suitable part of the main rack by advantage in connection with the whole floral taking around a rod 3', for example, thus hingedly joining the thus constructed sup- 75 port to said main rack portion. Any suitable link may connect the support 7, 8 to the said main rack portion. This may be a member 10 taking around one of the rods 3 of the said portion and provided with a hook 11 to 80 engage a part of said support such as a bail 12 or some other portion.

It is the desire to fix the upper or top rack portion 4, 5, 6 at any desired angle with respect to the main portion 1, 2, 3, or in the 85 same plane therewith, and to provide for locating it in a horizontal plane, all to the end Figure 4 shows in perspective a certain fin- that a floral piece mounted on said portion 4, 5, 6 may be disposed in the most advantageous position for display and for its decorative effect, depending upon the form or nature of such floral piece. That any such position may be had there is provided a separate support for such portion 4, 5, 6 which in this instance consists of a pair of rods 13 95 connected by brace-rods 14, the upper ends of the former each having an eye 15 to engage loosely around one of the rods 6 of said por-⁵⁰ ly and laterally extending rods 2 and 3 re- suitably supported by any one of the rods 8 100

of the support 7, 8, for example, which rods ant advantages in that various adjustments in some of the claims I shall refer to as abut- are possible in providing for mounting and

5 that will not be released by accident there is shown in Figures 6 and 7 a U-shaped mem-this nature with flat pieces by impaling them ber 15' to the ends of which the rods 13 are upon the fingers 16'. Now by providing the affixed, as by welding, said member 15' be-shelf 17', 18 herein described the effect of ing adapted, due to its form, to engage and the too extensive blanketing of the rack can 10 lie astride any one of the rods 8. Slidable be relieved by the placing of other types of 75 of which when engaged at one side of the rod thereby greatly heightening the decorative 15 tions of the portion 4, 5, 6 it is obvious that erly. Somewhat the same is true in the use 80

rack portion.

are supported in position upon the usual finlaterally of said portion. Herein, the shelf the support 7, 8. comprises a frame 17' and bracing rods 18, While I use the said support 7, 8 as the the extremities of the frame having eyes 19 taking around a rod 20 affixed to a U-shaped frame 21 terminating in hooks 22 which may be hung upon any one of the rods 3 of said main rack portion found most suitable for a given display. The frame 21 lies against the rods 2, 3 and a support consisting of rods 23 braced by rods 24, for example, is hingedly connected at 25 to the frame 21 while the rods 24 at their other ends have eyes 26 slidably engaging certain of the rods 18 of the form of the attachment including said

itself, all of the parts shown can be made to frame and part of the prop adapted by an 120 lie flat upon each other due to the ability to collapse them. The fingers 16' mentioned have eyes 162

taking around the rods 3 or 6, as the case may be, and are connected by a rod 163 which as shown in Figure 5 limits the swinging movement of the fingers by engaging the rods 2 or 5 as the case may be.

It is now seen that I provide a rack for the purpose named that has several import-

ments for the sake of brevity and clarity. displaying such types of floral pieces that In order to have a form of attaching means heretofore have been difficult of disposition.

upon the rods 13 is a keeper 16 the parts 17 floral pieces thereagainst upon said shelf 8 effectually prevents separation of the parts effect besides best disposing of such types named. While I have shown but two posi- that are somewhat difficult to display propthe support 13, 14 for the latter may be of the top supplemental rack portion 4, 5, 6. supported from any one of the rods 8 accord- That is to say, when said portion is disposed ing to the position it is desired that the said at the top of the rack 1, $\overline{2}$, 3 at an angle to portion is to have with respect to the main the plane thereof, often a stiff appearance of a display can be softened while when said 85 In displaying floral pieces on racks of this portion is disposed horizontally it is extremetype quite often it has been found that cer- ly convenient for treating a display in the tain forms of these pieces can be best shown best possible manner besides admitting of in a horizontal or substantially horizontal supporting certain forms of pieces that could position when massed with flat pieces which not otherwise be accommodated, at least to 90 the best advantage. And it is here that the gers 16' common to some racks. That such positive latch arrangement 15, 16 is of conpieces can be accommodated in the best man-siderable value in that there is no chance for ner, therefore, I provide a shelf that can be a display once set up on the supplemental hung upon some part of the main rack por- rack portion to be accidently disarranged as 95 tion 1, 2, 3 at any desired height or location would result were the support 13, 14 to leave

portion upon which to rest the support 13, 14, it is to be understood that the latter sup- 100 port may be otherwise held i. e., on any other part of the rack structure. While said support 13, 14 might rest upon the floor its connection with some part of the rack structure is desirable since the complete rack may be 105

easily moved about as a rigid unit.

I claim: 1. In a floral rack, the combination with a main portion presenting a substantially flat the shelf 17', 18. It is to be understood that front face upon which to dispose floral pieces, 110 and a prop at its rear side for supporting it shelf may be changed to suit the idea of the in an upright position, said prop including manufacturer and that I do not, therefore, members disposed at different heights thereconfine myself to the exact structure shown. on, of a supplemental substantially flat frame ⁵⁰ I preferably make the shelf structure, how-hingedly attached to the said main portion, 315 ever, so that it can be collapsed and made to the plane of which is adapted to lie in the lie flat as in Figure 3 for easy storage and same plane with the said main portion, or at shipment. And in this connection it is to be an angle to said portion rearwardly, and a noted that due to the construction of the rack support engaging both the said supplemental adjustment with respect to the said members of the latter to maintain the said supplemental frame in either of the named positions.

> 2. In a floral rack, the combination with a 125 main portion presenting a substantially flat front face upon which to dispose floral pieces, and a prop at its rear side for supporting it in an upright position, said prop having a series of members arranged at different 130

1,907,917

heights thereon, of a supplemental substan- carried by said supplemental rack portion, tially flat frame hingedly attached to the the same having a U-shaped member fixed said main portion, the plane of said supple- with respect to it adapted to engage over the mental frame adapted to lie either in the said rod of said main rack portion, and a keep-5 same plane with said main portion or at an er slidable on said rod of said supplemental 70 frame between its ends, and at its other end ing movement adapted to engage over the members and being of a length to maintain and said keeper enclosing the last said rod. 75 the said supplemental frame in its said. In testimony whereof I affix my signature. raised position or in a lowered position.

3. In a floral rack, the combination with a main portion comprising a frame and cross 15 members therefor forming a flat structure presenting a free front face upon which to dispose floral pieces, and a prop connected to the said portion including a series of members each of a different height thereon, said 20 prop supporting the main portion in substantially an upright position, of a supplemental frame hinged at one edge to and terminating the top of said main portion adapted to lie both in the same plane with said 25 portion and to project rearwardly from the same in substantially a horizontal position in the erected position of the rack, and a support extending between the prop and said suplemental frame, hingedly attached to the 30 latter and adapted to be lodged upon one of the members of the prop for supporting the said supplemental frame in a given position. 4. In a floral rack, the combination with a

rack structure comprising a main frame in-35 cluding crossed members forming a flat structure presenting a free front face upon which to dispose floral pieces, and a prop hinged to the rear side of the frame for supporting the latter in substantially an upright posi-40 tion, said prop including a series of members at different heights thereon, of a supplemental frame hinged to and terminating the top of the said main frame adapted to lie in the same plane therewith, and also at an 45 angle thereto rearwardly, and a support hinged to said supplemental frame and adapted for selective engagement with the said members of the prop whereby to support said supplemental frame in a given position with respect to the main frame including the position first described.

5. In a latch for holding in connected relation two separable parts of a floral rack, the combination of a member to be supported, 55 a U-shaped member mounted thereon, a supporting member including a part to be received into the said U-shaped member, and a movable latch carried by the first named member adapted to close the opening of the 60 U-shaped member for retaining the supporting member within the latter.

6. In a floral rack, the combination with a supplemental rack portion and a part upon which it is to be supported, said part consist-65 ing of a rod of a main rack portion, of a rod

angle thereto rearwardly, and a support en- rack portion, the same having an extension gaging at one end the said supplemental substantially paralleling its direction of slidadapted to engage any one of said series of rod of the main rack portion, said member

CLARENCE J. WHITE.