US 20030195079A1

(19) **United States**

(12) **Patent Application Publication**

Raghavan et al.

(10) **Pub. No.: US 2003/0195079 A1**

(43) **Pub. Date: Oct. 16, 2003**

(54) **FAMILY OF TRANSMISSION MECHANISMS WITH THREE PLANETARY GEAR SETS AND A STATIONARY MEMBER**

(76) Inventors: **Madhusudan Raghavan**, West Boomfield, MI (US); **Norman Kenneth Bucknor**, Troy, MI (US); **Patrick Benedict Usoro**, Troy, MI (US)

Correspondence Address:
JEFFREY A. SEDLAR
General Motors Corporation
Legal Staff, Mail Code 482-C23-B21
P.O. Box 300
Detroit, MI 48265-3000 (US)

(21) Appl. No.: **10/123,667**

(22) Filed: **Apr. 16, 2002**

Publication Classification

(51) **Int. Cl.**[7] **F16H 3/62**

(52) **U.S. Cl.** **475/276**; 475/278

(57) **ABSTRACT**

The family of transmissions has a plurality of members that can be utilized in powertrains to provide at least seven forward speed ratios and one reverse speed ratio. The transmission family members include three planetary gear sets having six torque-transmitting mechanisms and one fixed interconnection. Also, one planetary gear member is continuously connected with the transmission housing. The powertrain includes an engine and torque converter that is continuously connected to one of the planetary gear members and an output member that is continuously connected with another one of the planetary gear members. The six torque-transmitting mechanisms provide interconnections between various gear members and with the transmission housing, and are operated in combinations of three to establish at least seven forward speed ratios and one reverse speed ratio.





Fig. 1a

	RATIOS	50	52	54	56	58	59
REVERSE	-3.74	X	X				X
NEUTRAL	0		X				X
1	4.23		X	X			X
2	2.66		X	X		X	
3	1.87	X	X	X			
4	1.26		X	X	X		
5	1	X		X	X		
6	0.81	X	X		X		
7	0.67		X		X	X	

(X = ENGAGED CLUTCH)

Fig. 1b

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.00$, $\frac{R_2}{S_2} = 2.98$, $\frac{R_3}{S_3} = 2.42$

RATIO SPREAD	6.35
RATIO STEPS	
REV/1	-0.88
1/2	1.59
2/3	1.42
3/4	1.49
4/5	1.26
5/6	1.23
6/7	1.22



Fig. 2a

Fig. 2b

	RATIOS	150	152	154	156	158	159
REVERSE	-4.22	X		X			X
NEUTRAL	0			X			X
1	5.33			X	X		X
2	3.5			X		X	X
3	2.17			X	X	X	
4	1.5	X		X		X	
5	1		X	X		X	
6	0.77		X	X	X		
7	0.68	X	X	X			
8	0.53		X		X	X	

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.50$, $\frac{R_2}{S_2} = 2.25$, $\frac{R_3}{S_3} = 1.55$

RATIO SPREAD	10.06
RATIO STEPS	
REV/1	-0.79
1/2	1.52
2/3	1.61
3/4	1.44
4/5	1.5
5/6	1.3
6/7	1.12
7/8	1.28



Fig. 3a

Fig. 3b

	RATIOS	250	252	254	256	258	259
REVERSE	-2.25	X	X		X		
NEUTRAL	0	X			X		
1	5.61	X			X		X
2	3.35	X		X			X
3	2.38	X		X	X		
4	1.67	X		X		X	
5	1	X	X	X			
6	0.71		X	X		X	
7	0.63		X	X	X		

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.33$, $\frac{R_2}{S_2} = 2.50$, $\frac{R_3}{S_3} = 2.25$

RATIO SPREAD	8.86
RATIO STEPS	
REV/1	-0.4
1/2	1.68
2/3	1.4
3/4	1.42
4/5	1.67
5/6	1.4
6/7	1.13



Fig. 4a

Fig. 4b

	RATIOS	350	352	354	356	358	359
REVERSE	-2.9	X	X			X	
NEUTRAL	0	X				X	
1	5.22	X		X		X	
2	3.48			X		X	X
3	2.17		X	X		X	
4	1.67		X	X			X
5	1		X	X	X		
6	0.67		X		X		X
7	0.6		X		X	X	

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.00$, $\frac{R_2}{S_2} = 1.50$, $\frac{R_3}{S_3} = 1.80$

RATIO SPREAD	8.72
RATIO STEPS	
REV/1	-0.56
1/2	1.5
2/3	1.6
3/4	1.30
4/5	1.67
5/6	1.5
6/7	1.11



Fig. 5a

Fig. 5b

	RATIOS	450	452	454	456	458	459
REVERSE	-3.75	X	X				X
NEUTRAL	0	X					X
1	3.54	X		X			X
2	2.01	X		X		X	
3	1.43	X	X	X			
4	1	X		X	X		
5	0.83		X	X	X		
6	0.72	X	X		X		X
7	0.6		X		X	X	

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.51$, $\frac{R_2}{S_2} = 2.33$, $\frac{R_3}{S_3} = 2.26$

RATIO SPREAD	5.89
RATIO STEPS	
REV/1	-1.06
1/2	1.76
2/3	1.41
3/4	1.43
4/5	1.2
5/6	1.16
6/7	1.19



Fig. 6a

Fig. 6b

	RATIOS	550	552	554	556	558	559
REVERSE	-2.61			X		X	X
NEUTRAL	0		X				X
1	3.25		X		X		X
2	1.9		X	X			X
3	1.3	X		X			X
4	1	X		X	X		
5	0.74	X		X		X	
6	0.49	X			X	X	
7	0.4		X		X	X	

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.24$, $\frac{R_2}{S_2} = 1.49$, $\frac{R_3}{S_3} = 1.50$

RATIO SPREAD	8.13
RATIO STEPS	
REV/1	-0.8
1/2	1.71
2/3	1.46
3/4	1.30
4/5	1.35
5/6	1.51
6/7	1.23



Fig. 7a

	RATIOS	650	652	654	656	658	659
REVERSE	-1.56	X			X		X
NEUTRAL	0		X		X		
1	3.25		X		X	X	
2	1.69	X	X		X		
3	1	X		X	X		
4	0.62	X	X	X			
5	0.49		X	X		X	
6	0.4		X	X			X
7	0.29	X		X			X

(X = ENGAGED CLUTCH)

Fig. 7b

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.25$, $\frac{R_2}{S_2} = 1.49$, $\frac{R_3}{S_3} = 2.26$

RATIO SPREAD	11.23
RATIO STEPS	
REV/1	-0.48
1/2	1.92
2/3	1.69
3/4	1.61
4/5	1.26
5/6	1.23
6/7	1.38



Fig. 8a

Fig. 8b

	RATIOS	750	752	754	756	758	759
REVERSE	-2	X			X		X
NEUTRAL	0	X			X		
1	2.5	X			X	X	
2	1.5		X		X	X	
3	1			X	X	X	
4	0.67		X	X		X	
5	0.52	X		X		X	
6	0.4			X		X	X
7	0.31	X		X			X

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.50$, $\frac{R_2}{S_2} = 2.01$, $\frac{R_3}{S_3} = 1.50$

RATIO SPREAD	8.14
RATIO STEPS	
REV/1	-0.8
1/2	1.67
2/3	1.5
3/4	1.50
4/5	1.27
5/6	1.32
6/7	1.3



Fig. 9a

Fig. 9b

	RATIOS	850	852	854	856	858	859
REVERSE	-2.04		X		X	X	
NEUTRAL	0		X		X		
1	3.6	X	X		X		
2	2.26	X	X				X
3	1.5	X	X			X	
4	1	X	X	X			
5	0.6	X		X		X	
6	0.47	X		X			X
7	0.41	X		X	X		

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.50$, $\frac{R_2}{S_2} = 1.50$, $\frac{R_3}{S_3} = 2.91$

RATIO SPREAD	8.78
RATIO STEPS	
REV/1	-0.56
1/2	1.59
2/3	1.5
3/4	1.50
4/5	1.67
5/6	1.26
6/7	1.15



Fig. 10a

Fig. 10b

	RATIOS	950	952	954	956	958	959
REVERSE	-1.4	X			X		X
NEUTRAL	0	X			X		
1	3.5	X			X	X	
2	1.89		X		X	X	
3	1.34	X	X		X		
4	1	X	X			X	
5	0.72	X		X		X	
6	0.64			X		X	X
7	0.52	X		X			X

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.82$, $\frac{R_2}{S_2} = 2.50$, $\frac{R_3}{S_3} = 2.50$

RATIO SPREAD	6.8
RATIO STEPS	
REV 1/1	-0.4
1/2	1.86
2/3	1.41
3/4	1.34
4/5	1.39
5/6	1.11
6/7	1.25



Fig. 11a

	RATIOS	1050	1052	1054	1056	1058	1059
REVERSE	-2.09		X		X	X	
NEUTRAL	0		X		X		
1	5.22	X	X		X		
2	2.69	X	X				X
3	1.67	X	X			X	
4	1	X	X	X			
5	0.6	X		X		X	
6	0.49	X		X			X
7	0.43	X		X	X		

(X = ENGAGED CLUTCH)

Fig. 11b

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.50$, $\frac{R_2}{S_2} = 1.79$, $\frac{R_3}{S_3} = 2.50$

RATIO SPREAD	12.19
RATIO STEPS	
REV/1	-0.4
1/2	1.94
2/3	1.6
3/4	1.67
4/5	1.67
5/6	1.22
6/7	1.45



Fig. 12a

	RATIOS	1150	1152	1154	1156	1158	1159
REVERSE	-1.05	X		X		X	
NEUTRAL	1	X		X			
1	2.5	X		X	X		
2	1.73		X	X	X		
3	1	X	X	X			
4	0.7	X	X		X		
5	0.58	X	X				X
6	0.41	X	X			X	
7	0.3		X			X	X

(X = ENGAGED CLUTCH)

Fig. 12b

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.34$, $\frac{R_2}{S_2} = 2.25$, $\frac{R_3}{S_3} = 1.50$

RATIO SPREAD	8.38
RATIO STEPS	
REV 1/1	-0.42
1/2	1.45
2/3	1.73
3/4	1.43
4/5	1.2
5/6	1.4
6/7	1.39



Fig. 13a

Fig. 13b

	RATIOS	1250	1252	1254	1256	1258	1259
REVERSE	-2.25				X	X	X
NEUTRAL	0		X			X	
1	2.44		X	X		X	
2	1.41		X		X	X	
3	1	X	X			X	
4	0.66	X	X		X		
5	0.48	X	X	X			
6	0.36	X	X				X
7	0.3	X			X		X
8	0.28	X		X			X

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.50$, $\frac{R_2}{S_2} = 1.79$, $\frac{R_3}{S_3} = 2.42$

RATIO SPREAD	8.06
RATIO STEPS	
REV/1	-1.02
1/2	1.73
2/3	1.41
3/4	1.52
4/5	1.35
5/6	1.36
6/7	1.18
7/8	1.07



Fig. 14a

	RATIOS	1350	1352	1354	1356	1358	1359
REVERSE	-1.12		X			X	X
NEUTRAL	0	X					X
1	2.8	X			X		X
2	1.58	X				X	X
3	1	X	X			X	
4	0.76	X		X			X
5	0.56	X		X	X		
6	0.37			X	X		X
7	0.31			X		X	X

(X = ENGAGED CLUTCH)

Fig. 14b

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.80$, $\frac{R_2}{S_2} = 2.25$, $\frac{R_3}{S_3} = 1.92$

RATIO SPREAD	9.09
RATIO STEPS	
REV/1	-0.4
1/2	1.77
2/3	1.58
3/4	1.31
4/5	1.35
5/6	1.54
6/7	1.19



Fig. 15a

	RATIOS	1450	1452	1454	1456	1458	1459
REVERSE	-1.84		X		X		X
NEUTRAL	0		X		X		
1	2.58		X		X	X	
2	1.56	X			X	X	
3	1			X	X	X	
4	0.65	X		X		X	
5	0.52		X	X		X	
6	0.4			X		X	X
7	0.3		X	X			X

(X = ENGAGED CLUTCH)

Fig. 15b

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.50$, $\frac{R_2}{S_2} = 1.84$, $\frac{R_3}{S_3} = 2.80$

RATIO SPREAD	8.58
RATIO STEPS	
REV/1	-0.71
1/2	1.66
2/3	1.56
3/4	1.54
4/5	1.25
5/6	1.3
6/7	1.33



Fig. 16a

Fig. 16b

	RATIOS	1550	1552	1554	1556	1558	1559
REVERSE	-1.87	X		X			X
NEUTRAL	0			X			X
1	2.91			X	X		X
2	1.67		X		X		X
3	1	X	X		X		
4	0.62		X		X	X	
5	0.5			X	X	X	
6	0.4		X	X		X	
7	0.3	X		X		X	

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.51$, $\frac{R_2}{S_2} = 1.86$, $\frac{R_3}{S_3} = 1.50$

RATIO SPREAD	9.62
RATIO STEPS	
REV/1	-0.64
1/2	1.75
2/3	1.67
3/4	1.60
4/5	1.24
5/6	1.26
6/7	1.32



Fig. 17a

Fig. 17b

	RATIOS	1650	1652	1654	1656	1658	1659
REVERSE	-2.96		X			X	X
NEUTRAL	0					X	X
1	6.95			X		X	X
2	4.44				X	X	X
3	2.74			X	X	X	
4	1.64		X		X	X	
5	1.3	X			X	X	
6	1.16	X	X		X		
7	1	X	X			X	
8	0.71	X		X	X		

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.50$, $\frac{R_2}{S_2} = 2.97$, $\frac{R_3}{S_3} = 2.42$

RATIO SPREAD	6.95
RATIO STEPS	
REV/1	-0.43
1/2	1.56
2/3	1.62
3/4	1.68
4/5	1.26
5/6	1.12
6/7	1.16



Fig. 18a

Fig. 18b

	RATIOS	1550	1552	1554	1556	1558	1559
REVERSE 2	-4.43			X	X		X
REVERSE 1	-2.51		X		X		X
NEUTRAL	0		X				X
1	6.27		X			X	X
2	4.34			X		X	X
3	2.5		X	X		X	
4	1.77			X	X	X	
5	1.21	X		X		X	
6	1	X			X	X	
7	0.85	X		X	X		
8	0.71	X	X	X			

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 2.50$, $\frac{R_2}{S_2} = 2.51$, $\frac{R_3}{S_3} = 2.25$

RATIO SPREAD	8.83
RATIO STEPS	
REV/1	-0.4
1/2	1.44
2/3	1.74
3/4	1.42
4/5	1.46
5/6	1.21
6/7	1.17
7/8	1.2



Fig. 19a

Fig. 19b

	RATIOS	1850	1852	1854	1856	1858	1859
REVERSE	-1.82				X	X	X
NEUTRAL	0		X		X		
1	3.76		X	X			X
2	2.61		X		X		X
3	1.79		X	X	X		
4	1.21	X	X		X		
5	1	X	X	X			
6	0.71	X		X	X		
7	0.6	X		X			X
8	0.56	X			X		X
9	0.41		X	X		X	

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.50$, $\frac{R_2}{S_2} = 2.51$, $\frac{R_3}{S_3} = 2.26$

RATIO SPREAD	9.17
RATIO STEPS	
REV/1	-0.48
1/2	1.44
2/3	1.46
3/4	1.47
4/5	1.21
5/6	1.4
6/7	1.19
7/8	1.07
8/9	1.37

Fig. 20a



Fig. 20b

	RATIOS	1950	1952	1954	1956	1958	1959
REVERSE 2	-3.89			X		X	X
REVERSE 1	-2.5				X	X	X
NEUTRAL	0		X				X
1	6.25		X	X			X
2	4.02		X		X		X
3	2.5		X	X	X		
4	1.56		X		X	X	
5	1.29	X	X		X		
6	1.16	X	X			X	
7	1	X	X	X			
8	0.71	X		X	X		
9	0.64	X		X			X
10	0.61	X			X		X

(X = ENGAGED CLUTCH)

$\frac{\text{RING GEAR}}{\text{SUN GEAR}}$ TOOTH RATIO: $\frac{R_1}{S_1} = 1.50$, $\frac{R_2}{S_2} = 2.50$, $\frac{R_3}{S_3} = 2.26$

RATIO SPREAD	10.25
RATIO STEPS	
REV/1	-0.4
1/2	1.56
2/3	1.61
3/4	1.61
4/5	1.21
5/6	1.11
6/7	1.16
7/8	1.41
8/9	1.11
9/10	1.05

FAMILY OF TRANSMISSION MECHANISMS WITH THREE PLANETARY GEAR SETS AND A STATIONARY MEMBER

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to a family of power transmissions having three planetary gear sets that are controlled by six torque-transmitting devices to provide at least seven forward speed ratios and one reverse speed ratio.

[0003] 2. Background Art

[0004] Passenger vehicles include a powertrain that is comprised of an engine, multi-speed transmission, and a differential or final drive. The multi-speed transmission increases the overall operating range of the vehicle by permitting the engine to operate through its torque range a number of times. The number of forward speed ratios that are available in the transmission determines the number of times the engine torque range is repeated. Early automatic transmissions had two speed ranges. This severely limited the overall speed range of the vehicle and therefore required a relatively large engine that could produce a wide speed and torque range. This resulted in the engine operating at a specific fuel consumption point during cruising, other than the most efficient point. Therefore, manually-shifted (countershaft transmissions) were the most popular.

[0005] With the advent of three- and four-speed automatic transmissions, the automatic shifting (planetary gear) transmission increased in popularity with the motoring public. These transmissions improved the operating performance and fuel economy of the vehicle. The increased number of speed ratios reduces the step size between ratios and therefore improves the shift quality of the transmission by making the ratio interchanges substantially imperceptible to the operator under normal vehicle acceleration.

[0006] It has been suggested that the number of forward speed ratios be increased to six or more. Six-speed transmissions are disclosed in U.S. Pat. No. 4,070,927 issued to Polak on Jan. 31, 1978; U.S. Pat. No. 6,071,208 issued to Koivunen on Jun. 6, 2000; U.S. Pat. No. 5,106,352 issued to Lepelletier on Apr. 21, 1992; and U.S. Pat. No. 5,599,251 issued to Beim and McCarrick on Feb. 4, 1997.

[0007] Six-speed transmissions offer several advantages over four- and five-speed transmissions, including improved vehicle acceleration and improved fuel economy. While many trucks employ power transmissions, such as Polak, having six or more forward gear ratios, passenger cars are still manufactured with three- and four-speed automatic transmissions and relatively few five or six-speed devices due to the size and complexity of these transmissions. The Polak transmission provides six forward speed ratios with three planetary gear sets, two clutches, and three brakes. The Koivunen and Beim patents utilize six torque-transmitting devices including four brakes and two clutches to establish six forward speed ratios and a reverse ratio. The Lepelletier patent employs three planetary gear sets, three clutches and two brakes to provide six forward speeds. One of the planetary gear sets is positioned and operated to establish two fixed input speeds for the remaining two planetary gear sets.

[0008] Seven-speed transmissions are disclosed in U.S. Pat. Nos. 4,709,594 to Maeda; 6,053,839 to Baldwin et. al.; and 6,083,135 to Baldwin et. al. Seven- and eight-speed transmissions provide further improvements in acceleration and fuel economy over six-speed transmissions. However, like the six-speed transmissions discussed above, the development of seven- and eight-speed transmissions has been precluded because of complexity, size and cost.

SUMMARY OF THE INVENTION

[0009] It is an object of the present invention to provide an improved family of transmissions having three planetary gear sets controlled to provide at least seven forward speed ratios and one reverse speed ratio.

[0010] In one aspect of the present invention, the family of transmissions has three planetary gear sets, each of which includes a first, second and third member, which members may comprise a sun gear, a ring gear, or a planet carrier assembly member.

[0011] In referring to the first, second and third gear sets in this description and in the claims, these sets may be counted "first" to "third" in any order in the drawings (i.e., left to right, right to left, etc.).

[0012] In another aspect of the present invention, each of the planetary gear sets may be of the single pinion-type or of the double pinion-type.

[0013] In yet another aspect of the present invention, the first member of the first planetary gear set is continuously interconnected to the first member of the second planetary gear set through a first interconnecting member.

[0014] In yet another aspect of the present invention, the second member of the first planetary gear set is continuously connected to a transmission housing.

[0015] In yet a further aspect of the invention, each family member incorporates an output shaft which is continuously connected with a member of the planetary gear sets and an input shaft which is continuously connected with another member of the planetary gear sets.

[0016] In still a further aspect of the invention, a first torque-transmitting mechanism, such as a clutch, selectively interconnects a member of the first planetary gear set with a member of the second or third planetary gear set.

[0017] In another aspect of the invention, a second torque-transmitting mechanism, such as a clutch, selectively interconnects a member of the second planetary gear set with a member of the first or third planetary gear set.

[0018] In a still further aspect of the invention, a third torque-transmitting mechanism, such as a clutch, selectively interconnects a member of the third planetary gear set with a member of the first or second planetary gear set.

[0019] In a still further aspect of the invention, a fourth torque-transmitting mechanism, such as a clutch, selectively interconnects a member of the first or second planetary gear set with another member of the first, second or third planetary gear set.

[0020] In a still further aspect of the invention, a fifth torque-transmitting mechanism, such as a clutch, selectively interconnects a member of the second or third planetary gear

set with another member of the first, second or third planetary gear set. Alternatively, the fifth torque-transmitting mechanism, such as a brake, selectively interconnects a member of the first, second or third planetary gear set with the transmission housing.

[0021] In still another aspect of the invention, a sixth torque-transmitting mechanism, such as a clutch, selectively interconnects a member of the first or third planetary gear set with another member of the first, second or third planetary gear set. Alternatively, the sixth torque transmitting mechanism, such as a brake, selectively connects a member of the first, second or third planetary gear set with the transmission housing.

[0022] In still another aspect of the invention, the six torque-transmitting mechanisms are selectively engageable in combinations of three to yield at least seven forward speed ratios and one reverse speed ratio.

[0023] The above object and other objects, features, and advantages of the present invention are readily apparent from the following detailed description of the best modes for carrying out the invention when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] **FIG. 1***a* is a schematic representation of a powertrain including a planetary transmission incorporating a family member of the present invention;

[0025] **FIG. 1***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 1***a;*

[0026] **FIG. 2***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0027] **FIG. 2***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 2***a;*

[0028] **FIG. 3***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0029] **FIG. 3***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 3***a;*

[0030] **FIG. 4***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0031] **FIG. 4***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 4***a;*

[0032] **FIG. 5***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0033] **FIG. 5***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 5***a;*

[0034] **FIG. 6***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0035] **FIG. 6***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 6***a;*

[0036] **FIG. 7***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0037] **FIG. 7***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 7***a;*

[0038] **FIG. 8***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0039] **FIG. 8***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 8***a;*

[0040] **FIG. 9***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0041] **FIG. 9***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 9***a;*

[0042] **FIG. 10***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0043] **FIG. 10***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 10***a;*

[0044] **FIG. 11***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0045] **FIG. 11***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 11***a;*

[0046] **FIG. 12***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0047] **FIG. 12***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 12***a;*

[0048] **FIG. 13***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0049] **FIG. 13***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 13***a;*

[0050] **FIG. 14***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0051] **FIG. 14***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 14***a;*

[0052] **FIG. 15***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0053] **FIG. 15***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 15***a;*

[0054] **FIG. 16***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0055] **FIG. 16***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 16***a;*

[0056] **FIG. 17***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0057] **FIG. 17***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 17***a;*

[0058] **FIG. 18***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0059] **FIG. 18***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 18***a;*

[0060] **FIG. 19***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention;

[0061] **FIG. 19***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 19***a;*

[0062] **FIG. 20***a* is a schematic representation of a powertrain having a planetary transmission incorporating another family member of the present invention; and

[0063] **FIG. 20***b* is a truth table and chart depicting some of the operating characteristics of the powertrain shown in **FIG. 20***a*.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0064] Referring to the drawings, wherein like characters represent the same or corresponding parts throughout the several views, there is shown in **FIG. 1***a* a powertrain **10** having a conventional engine and torque converter **12**, a planetary transmission **14**, and a conventional final drive mechanism **16**.

[0065] The planetary transmission **14** includes an input shaft **17** continuously connected with the engine and torque converter **12**, a planetary gear arrangement **18**, and an output shaft **19** continuously connected with the final drive mechanism **16**. The planetary gear arrangement **18** includes three planetary gear sets **20**, **30** and **40**.

[0066] The planetary gear set **20** includes a sun gear member **22**, a ring gear member **24**, and a planet carrier assembly **26**. The planet carrier assembly **26** includes a plurality of pinion gears **27** rotatably mounted on a carrier member **29** and disposed in meshing relationship with both the sun gear member **22** and the ring gear member **24**.

[0067] The planetary gear set **30** includes a sun gear member **32**, a ring gear member **34**, and a planet carrier assembly member **36**. The planet carrier assembly member **36** includes a plurality of pinion gears **37** rotatably mounted on a carrier member **39** and disposed in meshing relationship with both the sun gear member **32** and the ring gear member **34**.

[0068] The planetary gear set **40** includes a sun gear member **42**, a ring gear member **44**, and a planet carrier assembly member **46**. The planet carrier assembly member **46** includes a plurality of pinion gears **47** rotatably mounted on a carrier member **49** and disposed in meshing relationship with both the sun gear member **42** and the ring gear member **44**.

[0069] The planetary gear arrangement also includes six torque-transmitting mechanisms **50**, **52**, **54**, **56**, **58** and **59**. The torque-transmitting mechanisms **50**, **52**, **54** and **56** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanisms **58** and **59** are stationary-type torque-transmitting mechanisms, commonly termed brakes or reaction clutches.

[0070] The input shaft **17** is continuously connected with the sun gear member **32**, and the output shaft **19** is continuously connected with the ring gear member **24**. The sun gear member **42** is continuously connected with the transmission housing **6**o. The ring gear member **34** is continuously connected with the planet carrier assembly member **46** through the interconnecting member **70**.

[0071] The sun gear member **22** is selectively connectable with the planet carrier assembly member **36** through the clutch **50**. The sun gear member **22** is selectively connectable with the ring gear member **44** through the clutch **52**. The planet carrier assembly member **26** is selectively connectable with the planet carrier assembly member **36** through the clutch **54**. The planet carrier assembly member **26** is selectively connectable with the sun gear member **32** through the clutch **56**. The sun gear member **22** is selectively connectable with the transmission housing through the brake **58**. The planet carrier assembly member **26** is selectively connectable with the transmission housing **60** through the brake **59**.

[0072] As shown in **FIG. 1***b*, and in particular the truth table disclosed therein, the torque-transmitting mechanisms are selectively engaged in combinations of three to provide seven forward speed ratios and a reverse speed ratio. It should also be noted in the truth table that the torque-transmitting mechanisms **52** and **59** remain engaged through a neutral condition, thereby simplifying the forward/reverse interchange.

[0073] The reverse speed ratio is established with the engagement of the clutches **50**, **52** and brake **59**. The clutch **50** connects the sun gear member **22** to the planet carrier assembly member **36**. The clutch **52** connects the sun gear member **22** to the ring gear member **44**. The brake **59** connects the planet carrier assembly member **26** to the transmission housing **60**. The sun gear member **22** rotates at the same speed as the planet carrier assembly member **36** and the ring gear member **44**. The planet carrier assembly member **26** does not rotate. The ring gear member **24** rotates at the same speed as the output shaft **19**. The ring gear member **24**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the sun gear member **22** and the ring gear/sun gear tooth ratio of the planetary gear set **20**. The ring gear member **34** rotates at the same speed

as the planet carrier assembly member **46**. The sun gear member **32** rotates at the same speed as the input shaft **17**. The planet carrier assembly member **36** rotates at a speed determined from the speed of the ring gear member **34**, the speed of the sun gear member **32**, and the ring gear/sun gear tooth ratio of the planetary gear set **30**. The sun gear member **42** does not rotate. The planet carrier assembly member **46** rotates at a speed determined from the speed of the ring gear member **44** and the ring gear/sun gear tooth ratio of the planetary gear set **40**. The numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **20**, **30** and **40**.

[**0074**] The first forward speed ratio is established with the engagement of the clutches **52**, **54** and the brake **59**. The clutch **52** connects the sun gear member **22** to the ring gear member **44**. The clutch **54** connects the planet carrier assembly member **26** to the planet carrier assembly member **36**. The brake **59** connects the planet carrier assembly member **26** to the transmission housing **60**. The planet carrier assembly members **26** and **36** do not rotate. The sun gear member **22** rotates at the same speed as the ring gear member **44**. The ring gear member **24** rotates at the same speed as the output shaft **19**. The ring gear member **24**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the sun gear member **22** and the ring gear/sun gear tooth ratio of the planetary gear set **20**. The ring gear member **34** rotates at the same speed as the planet carrier assembly member **46**. The sun gear member **32** rotates at the same speed as the input shaft **17**. The ring gear member **34** rotates at a speed determined from the speed of the sun gear member **32** and the ring gear/sun gear tooth ratio of the planetary gear set **30**. The sun gear member **42** does not rotate. The ring gear member **44** rotates at a speed determined from the speed of the planet carrier assembly member **46** and the ring gear/sun gear tooth ratio of the planetary gear set **40**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **20**, **30** and **40**.

[**0075**] The second forward speed ratio is established with the engagement of the clutches **52**, **54** and the brake **58**. The clutch **52** connects the sun gear member **22** to the ring gear member **44**. The clutch **54** connects the planet carrier assembly member **26** to the planet carrier assembly member **36**. The brake **58** connects the sun gear member **22** to the transmission housing **60**. The sun gear member **22** and ring gear member **44** do not rotate. The planet carrier assembly member **26** rotates at the same speed as the planet carrier assembly member **36**. The ring gear member **24** rotates at the same speed as the output shaft **19**. The ring gear member **24**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the planet carrier assembly member **26** and the ring gear/sun gear tooth ratio of the planetary gear set **20**. The ring gear member **34** and planetary gear set **40** do not rotate. The sun gear member **32** rotates at the same speed as the input shaft **17**. The planet carrier assembly member **36** rotates at a speed determined from the speed of the sun gear member **32** and the ring gear/sun gear tooth ratio of the planetary gear set **30**. The numerical value of the second forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **20** and **30**.

[**0076**] The third forward speed ratio is established with the engagement of the clutches **50**, **52**, **54**. The clutch **50** connects the sun gear member **22** to the planet carrier assembly member **36**. The clutch **52** connects the sun gear member **22** to the ring gear member **44**. The clutch **54** connects the planet carrier assembly member **26** to the planet carrier assembly member **36**. The ring gear member **24** rotates at the same speed as the output shaft **19**. The planet carrier assembly member **26** rotates at the same speed as the sun gear member **22**, the planet carrier assembly member **36**, and the ring gear member **44**. The sun gear member **32** rotates at the same speed as the input shaft **17**. The ring gear member **34** rotates at the same speed as the planet carrier assembly member **46**. The planet carrier assembly member **36** rotates at a speed determined from the speed of the ring gear member **34**, the speed of the sun gear member **32**, and the ring gear/sun gear tooth ratio of the planetary gear set **30**. The sun gear member **42** does not rotate. The planet carrier assembly member **46** rotates at a speed determined from the speed of the ring gear member **44** and the ring gear/sun gear tooth ratio of the planetary gear set **40**. The numerical value of the third forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **30** and **40**.

[**0077**] The fourth forward speed ratio is established with the engagement of the clutches **52**, **54**, **56**. The clutch **52** connects the sun gear member **22** to the ring gear member **44**. The clutch **54** connects the planet carrier assembly member **26** to the planet carrier assembly member **36**. The clutch **56** connects the planet carrier assembly member **26** to the sun gear member **32**. The ring gear member **24** rotates at the same speed as the output shaft **19**. The planet carrier assembly member **26** rotates at the same speed as the planet carrier assembly member **36**, the sun gear member **32**, and the input shaft **17**. The sun gear member **22** rotates at the same speed as the ring gear member **44**. The ring gear member **24**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the planet carrier assembly member **26**, the speed of the sun gear member **22**, and the ring gear/sun gear tooth ratio of the planetary gear set **20**. The ring gear member **34** rotates at the same speed as the planet carrier assembly member **46**. The sun gear member **42** does not rotate. The planet carrier assembly member **46** rotates at a speed determined from the speed of the ring gear member **44** and the ring gear/sun gear tooth ratio of the planetary gear set **40**. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **20** and **40**.

[**0078**] The fifth forward speed ratio is established with the engagement of the clutches **50**, **54**, **56**. In this configuration, the input shaft **17** is directly connected to the output shaft **19**. The numerical value of the fifth forward speed ratio is 1.

[**0079**] The sixth forward speed ratio is established with the engagement of the clutches **50**, **52**, **56**. The clutch **50** connects the sun gear member **22** to the planet carrier assembly member **36**. The clutch **52** connects the sun gear member **22** to the ring gear member **44**. The clutch **56** connects the planet carrier assembly member **26** to the sun gear member **32**. The sun gear member **22** rotates at the same speed as the planet carrier assembly member **36** and the ring gear member **44**. The planet carrier assembly member **26** rotates at the same speed as the sun gear member **32** and the input shaft **17**. The ring gear member **24** rotates at the same speed as the output shaft **19**. The ring gear

member **24**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the planet carrier assembly member **26**, the speed of the sun gear member **22**, and the ring gear/sun gear tooth ratio of the planetary gear set **20**. The ring gear member **34** rotates at the same speed as the planet carrier assembly member **46**. The planet carrier assembly member **36** rotates at a speed determined from the speed of the ring gear member **34**, the speed of the sun gear member **32**, and the ring gear/sun gear tooth ratio of the planetary gear set **3**o. The sun gear member **42** does not rotate. The planet carrier assembly member **46** rotates at a speed determined from the speed of the ring gear member **44** and the ring gear/sun gear tooth ratio of the planetary gear set **40**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **20**, **30** and **40**.

[**0080**] The seventh forward speed ratio is established with the engagement of the clutches **52**, **56**, and the brake **58**. The clutch **52** connects the sun gear member **22** to the ring gear member **44**. The clutch **56** connects the planet carrier assembly member **26** to the sun gear member **32**. The brake **58** connects the sun gear member **22** to the transmission housing **60**. The ring gear member **24** rotates at the same speed as the output shaft **19**. The planet carrier assembly member **26** and sun gear member **22** rotate at the same speed as the input shaft **17**. The sun gear member **22** and ring gear member **44** do not rotate. The ring gear member **24**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the planet carrier assembly member **26** and the ring gear/sun gear tooth ratio of the planetary gear set **20**. The ring gear member **34** rotates at the same speed as the planet carrier assembly member **46**. The sun gear member **42** does not rotate. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **20**.

[**0081**] As set forth above, the engagement schedule for the torque-transmitting mechanisms is shown in the truth table of FIG. ib. This truth table also provides an example of speed ratios that are available utilizing the ring gear/sun gear tooth ratios given by way of example in **FIG. 1***b*. The R1/S1 value is the tooth ratio of the planetary gear set **20**; the R2/S2 value is the tooth ratio of the planetary gear set **30**; and the R3/S3 value is the tooth ratio of the planetary gear set **40**. Also, the chart of **FIG. 1***b* describes the ratio steps that are attained utilizing the sample of tooth ratios given. For example, the step ratio between the first and second forward speed ratios is 1.59, while the step ratio between the reverse and first forward ratio is −0.88. It can also be readily determined from the truth table of **FIG. 1***b* that all of the single step forward ratio interchanges are of the single transition variety, as are the double step forward ratio interchanges.

[**0082**] **FIG. 2***a* shows a powertrain **110** having a conventional engine and torque converter **12**, a planetary transmission **114**, and a conventional final drive mechanism **16**.

[**0083**] The planetary transmission **114** includes an input shaft **17** continuously connected with the engine and torque converter **12**, a planetary gear arrangement **118**, and an output shaft **19** continuously connected with the final drive mechanism **16**. The planetary gear arrangement **118** includes three planetary gear sets **120**, **130** and **140**.

[**0084**] The planetary gear set **120** includes a sun gear member **122**, a ring gear member **124**, and a planet carrier assembly **126**. The planet carrier assembly **126** includes a plurality of pinion gears **127** rotatably mounted on a carrier member **129** and disposed in meshing relationship with both the sun gear member **122** and the ring gear member **124**.

[**0085**] The planetary gear set **130** includes a sun gear member **132**, a ring gear member **134**, and a planet carrier assembly member **136**. The planet carrier assembly member **136** includes a plurality of pinion gears **137** rotatably mounted on a carrier member **139** and disposed in meshing relationship with both the sun gear member **132** and the ring gear member **134**

[**0086**] The planetary gear set **140** includes a sun gear member **142**, a ring gear member **144**, and a planet carrier assembly member **146**. The planet carrier assembly member **146** includes a plurality of pinion gears **147** rotatably mounted on a carrier member **149** and disposed in meshing relationship with both the sun gear member **142** and the ring gear member **144**.

[**0087**] The planetary gear arrangement **118** also includes six torque-transmitting mechanisms **150**, **152**, **154**, **156**, **158** and **159**. The torque-transmitting mechanisms **150**,**152**,**154**, **156** and **158** are of the rotating-type torque-transmitting mechanisms, commonly termed "clutches." The torque-transmitting mechanism **159** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0088**] The input shaft **17** is continuously connected with the sun gear member **122**, and the output shaft **19** is continuously connected with the planet carrier assembly member **126**. The sun gear member **142** is continuously connected with the transmission housing **160**. The ring gear member **134** is continuously connected with the planet carrier assembly member **146** through the interconnecting member **170**.

[**0089**] The sun gear member **122** is selectively connectable with the sun gear member **132** through the clutch **150**. The sun gear member **122** is selectively connectable with the planet carrier assembly member **136** through the clutch **152**. The ring gear member **124** is selectively connectable with the ring gear member **144** through the clutch **154**. The planet carrier assembly member **126** is selectively connectable with the sun gear member **132** through the clutch **156**. The planet carrier assembly member **136** is selectively connectable with the ring gear member **144** through the clutch **158**. The planet carrier assembly member **136** is selectively connectable with the transmission housing **160** through the brake **159**.

[**0090**] The truth table of **FIG. 2***b* describes the engagement sequence utilized to provide eight forward speed ratios and a reverse speed ratio in the planetary gear arrangement **118** shown in **FIG. 2***a*.

[**0091**] The reverse speed ratio is established with the engagement of the clutches **150**, **154** and the brake **159**. The clutch **150** connects the sun gear member **122** to the sun gear member **132**. The clutch **154** connects the ring gear member **124** to the ring gear member **144**. The brake **159** connects the planet carrier assembly member **136** to the transmission housing **160**. The sun gear members **122**, **132** rotate at the same speed as the input shaft **17**. The ring gear members **124**, **144** rotate at the same speed. The planet carrier assembly member **126** rotates at the same speed as the output shaft **19**. The planet carrier assembly member **126**,

and therefore the output shaft **19**, rotates at a speed determined from the speed of the ring gear member **124**, the speed of the sun gear member **122**, and the ring gear/sun gear tooth ratio of the planetary gear set **120**. The planet carrier assembly member **136** does not rotate. The ring gear member **134** rotates at the same speed as the planet carrier assembly member **146**. The ring gear member **134** rotates at a speed determined from the speed of the sun gear member **132** and the ring gear/sun gear tooth ratio of the planetary gear set **130**. The sun gear member **142** does not rotate. The planet carrier assembly member **146** rotates at a speed determined from the speed of the ring gear member **144**, and the ring gear/sun gear tooth ratio of the planetary gear set **140**. The numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the * planetary gear sets **120**, **130** and **140**.

[**0092**] The first forward speed ratio is established with the engagement of the clutches **154**, **156** and the brake **159**. The clutch **154** connects the ring gear member **124** to the ring gear member **144**. The clutch **156** connects the planet carrier assembly member **126** to the sun gear member **132**. The brake **159** connects the planet carrier assembly member **136** to the transmission housing **160**. The sun gear member **122** rotates at the same speed as the input shaft **17**. The ring gear member **124** rotates at the same speed as the ring gear member **144**. The planet carrier assembly member **126** rotates at the same speed as the sun gear member **132** and the output shaft **19**. The planet carrier assembly member **126**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the ring gear member **124**, the speed of the sun gear member **132**, and the ring gear/sun gear tooth ratio of the planetary gear set **120**. The planet carrier assembly member **136** does not rotate. The ring gear member **134** rotates at the same speed as the planet carrier assembly member **146**. The ring gear member **134** rotates at a speed determined from the speed of the sun gear member **132** and the ring gear/sun gear tooth ratio of the planetary gear set **130**. The sun gear member **142** does not rotate. The planet carrier assembly member **146** rotates at a speed determined from the speed of the ring gear member **144** and the ring gear/sun gear tooth ratio of the planetary gear set **140**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **120**, **130** and **140**.

[**0093**] The second forward speed ratio is established with the engagement of the clutches **154**, **158** and the brake **159**. The clutch **154** connects the ring gear member **124** to the ring gear member **144**. The clutch **158** connects the planet carrier assembly member **136** to the ring gear member **144**. The brake **159** connects the planet carrier assembly member **136** to the transmission housing **160**. The ring gear member **124** and the planetary gear sets **130**, **140** do not rotate. The sun gear member **122** rotates at the same speed as the input shaft **17**. The planet carrier assembly member **126** rotates at the same speed as the output shaft **19**. The planet carrier assembly member **126**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the sun gear member **122** and the ring gear/sun gear tooth ratio of the planetary gear set **120**. The numerical value of the second forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **120**.

[**0094**] The third forward speed ratio is established with the engagement of the clutches **154**, **156**, **158**. The clutch **154** connects the ring gear member **124** to the ring gear member **144**. The clutch **156** connects the planet carrier assembly member **126** to the sun gear member **132**. The clutch **158** connects the planet carrier assembly member **136** to the ring gear member **144**. The sun gear member **122** rotates at the same speed as the sun gear member **132** and the input shaft **17**. The planet carrier assembly member **126** rotates at the same speed as the output shaft **19**. The ring gear member **124** rotates at the same speed as the ring gear member **144** and the planet carrier assembly member **136**. The planet carrier assembly member **126**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the ring gear member **124**, the speed of the sun gear member **122**, and the ring gear/sun gear tooth ratio of the planetary gear set **120**. The ring gear member **134** rotates at the same speed as the planet carrier assembly member **146**. The planet carrier assembly member **136** rotates at a speed determined from the speed of the ring gear member **134**, the speed of the sun gear member **132**, and the ring gear/sun gear tooth ratio of the planetary gear set **130**. The sun gear member **142** does not rotate. The planet carrier assembly member **146** rotates at a speed determined from the speed of the ring gear member **144** and the ring gear/sun gear tooth ratio of the planetary gear set **140**. The numerical value of the third forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **120**, **130** and **140**.

[**0095**] The fourth forward speed ratio is established with the engagement of the clutches **150**, **154**, **158**. The clutch **150** connects the sun gear member **122** to the sun gear member **132**. The clutch **154** connects the ring gear member **124** to the ring gear member **144**. The clutch **158** connects the planet carrier assembly member **136** to the ring gear member **144**. The sun gear member **122** rotates at the same speed as the sun gear member **132** and the input shaft **17**. The planet carrier assembly member **126** rotates at the same speed as the output shaft **19**. The ring gear member **124** rotates at the same speed as the ring gear member **144** and the planet carrier assembly member **136**. The planet carrier assembly member **126**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the ring gear member **124**, the speed of the sun gear member **122**, and the ring gear/sun gear tooth ratio of the planetary gear set **120**. The ring gear member **134** rotates at the same speed as the planet carrier assembly member **146**. The planet carrier assembly member **136** rotates at a speed determined from the speed of the speed of the ring gear member **134**, the speed of the sun gear member **132**, and the ring gear/sun gear tooth ratio of the planetary gear set **130**. The sun gear member **142** does not rotate. The planet carrier assembly member **146** rotates at a speed determined from the speed of the ring gear member **144** and the ring gear/sun gear tooth ratio of the planetary gear set **140**. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **120**, **130** and **140**.

[**0096**] The fifth forward speed ratio is established with the engagement of the clutches **152**, **154**, **158**. In this configuration, the input shaft **17** is directly connected to the output shaft **19**. The numerical value of the fifth forward speed ratio is 1.

[**0097**] The sixth forward speed ratio is established with the engagement of the clutches **152**, **154**, **156**. The clutch

152 connects the sun gear member **122** to the planet carrier assembly member **136**. The clutch **154** connects the ring gear member **124** to the ring gear member **144**. The clutch **156** connects the planet carrier assembly member **126** to the sun gear member **132**. The sun gear member **122** rotates at the same speed as the planet carrier assembly member **136** and the input shaft **17**. The planet carrier assembly member **126** rotates at the same speed as the sun gear member **132** and the output shaft **19**. The ring gear member **124** rotates at the same speed as the ring gear member **144**. The planet carrier assembly member **126**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the ring gear member **124**, the speed of the sun gear member **122**, and the ring gear/sun gear tooth ratio of the planetary gear set **120**. The ring gear member **134** rotates at the same speed as the planet carrier assembly member **146**. The planet carrier assembly member **136** rotates at a speed determined from the speed of the ring gear member **134**, the speed of the sun gear member **132**, and the ring gear/sun gear tooth ratio of the planetary gear set **130**. The sun gear member **142** does not rotate. The planet carrier assembly member **146** rotates at a speed determined from the speed of the ring gear member **144** and the ring gear/sun gear tooth ratio of the planetary gear set **140**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **120**, **130** and **140**.

[**0098**] The seventh forward speed ratio is established with the engagement of the clutches **150**, **152**, **154**. The clutch **150** connects the sun gear member **122** to the sun gear member **132**. The clutch **152** connects the sun gear member **122** to the planet carrier assembly member **136**. The clutch **154** connects the ring gear member **124** to the ring gear member **144**. The sun gear members **122**, **132** and the planet carrier assembly member **136** rotate at the same speed as the input shaft **17**. The ring gear member **124** rotates at the same speed as the ring gear member **144**. The planet carrier assembly member **126** rotates at the same speed as the output shaft **19**. The planet carrier assembly member **126**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the ring gear member **124**, the speed of the sun gear member **132**, and the ring gear/sun gear tooth ratio of the planetary gear set **120**. The ring gear member **134** rotates at the same speed as the planet carrier assembly member **146**. The planet carrier assembly member **146** rotates at a speed determined from the speed of the ring gear member **144** and the ring gear/sun gear tooth ratio of the planetary gear set **140**. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **120** and **140**.

[**0099**] The eighth forward speed ratio is established with the engagement of the clutches **152**, **156**, **158**. The clutch **152** connects the sun gear member **122** to the planet carrier assembly member **136**. The clutch **156** connects the planet carrier assembly member **126** to the sun gear member **132**. The clutch **158** connects the planet carrier assembly member **136** to the ring gear member **144**. The planet carrier assembly member **126** rotates at the same speed as the sun gear member **132** and the output shaft **19**. The sun gear member **122** rotates at the same speed as the planet carrier assembly member **136**, the ring gear member **144**, and the input shaft **17**. The ring gear member **134** rotates at the same speed as the planet carrier assembly member **146**. The planet carrier assembly member **136** rotates at a speed determined from the speed of the ring gear member **134**, the speed of the sun gear member **132**, and the ring gear/sun gear tooth ratio of the planetary gear set **130**. The sun gear member **142** does not rotate. The planet carrier assembly member **146** rotates at a speed determined from the speed of the ring gear member **144** and the ring gear/sun gear tooth ratio of the planetary gear set **140**. The numerical value of the eighth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **130** and **140**.

[**0100**] As set forth above, the truth table of **FIG. 2***b* describes the engagement sequence of the torque-transmitting mechanisms utilized to provide a reverse drive ratio and eight forward speed ratios. It can be readily determined from the truth table that all of the single step forward interchanges are of the single transition type, as are the double step forward interchanges. The truth table also provides an example of the ratios that can be attained with the family members shown in **FIG. 2***a* utilizing the sample tooth ratios given in **FIG. 2***b*. The R1/S1 value is the tooth ratio of the planetary gear set **120**; the R2/S2 value is the tooth ratio of the planetary gear set **130**; and the R3/S3 value is the tooth ratio of the planetary gear set **140**. Also shown in **FIG. 2***b* are the ratio steps between single step ratios in the forward direction as well as the reverse to first ratio step ratio. For example, the first to second step ratio is 1.52.

[**0101**] Turning to **FIG. 3***a*, a powertrain **210** includes the engine and torque converter **12**, a planetary transmission **214**, and a final drive mechanism **16**. The planetary transmission **214** includes an input shaft **17** continuously connected with the engine and torque converter **12**, a planetary gear arrangement **218**, and an output shaft **19** continuously connected with the final drive mechanism **16**. The planetary gear arrangement **218** includes three planetary gear sets **220**, **230** and **240**.

[**0102**] The planetary gear set **220** includes a sun gear member **222**, a ring gear member **224**, and a planet carrier assembly **226**. The planet carrier assembly **226** includes a plurality of pinion gears **227** rotatably mounted on a carrier member **229** and disposed in meshing relationship with both the sun gear member **222** and the ring gear member **224**.

[**0103**] The planetary gear set **230** includes a sun gear member **232**, a ring gear member **234**, and a planet carrier assembly member **236**. The planet carrier assembly member **236** includes a plurality of pinion gears **237** rotatably mounted on a carrier member **239** and disposed in meshing relationship with both the sun gear member **232** and the ring gear member **234**.

[**0104**] The planetary gear set **240** includes a sun gear member **242**, a ring gear member **244**, and a planet carrier assembly member **246**. The planet carrier assembly member **246** includes a plurality of pinion gears **247** rotatably mounted on a carrier member **249** and disposed in meshing relationship with both the sun gear member **242** and the ring gear member **244**.

[**0105**] The planetary gear arrangement **218** also includes six torque-transmitting mechanisms **250**, **252**, **254**, **256**, **258** and **259**. The torque-transmitting mechanisms **250**, **252**, **254** and **256** are of the rotating type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanisms **258** and **259** are stationary type torque-transmitting mechanisms, commonly termed brakes or reaction clutches.

[0106] The input shaft **17** is continuously connected with the sun gear member **222**, and the output shaft **19** is continuously connected with the ring gear member **234**. The planet carrier assembly member **246** is continuously connected with the transmission housing **260**. The sun gear member **232** is continuously connected with the ring gear member **244** through the interconnecting member **270**.

[0107] The planet carrier assembly member **226** is selectively connectable with the ring gear member **234** through the clutch **250**. The planet carrier assembly member **226** is selectively connectable with the planet carrier assembly member **236** through the clutch **252**. The ring gear member **224** is selectively connectable with the planet carrier assembly member **236** through the clutch **254**. The sun gear member **222** is selectively connectable with the sun gear member **242** through the clutch **256**. The ring gear member **244** is selectively connectable with the transmission housing **260** through the brake **258**. The planet carrier assembly member **236** is selectively connectable with the transmission housing **260** through the brake **259**.

[0108] As shown in the truth table in **FIG. 3***b*, the torque-transmitting mechanisms are engaged in combinations of three to establish seven forward speed ratios and one reverse ratio.

[0109] The reverse speed ratio is established with the engagement of the clutches **250, 252, 256**. The clutch **250** connects the planet carrier assembly member **226** to the ring gear member **234**. The clutch **252** connects the planet carrier assembly member **226** to the planet carrier assembly member **236**. The clutch **256** connects the sun gear member **222** to the sun gear member **242**. The sun gear members **222, 242** rotate at the same speed as the input shaft **17**. The planet carrier assembly members **226, 236** and the ring gear member **234** rotate at the same speed as the output shaft **19**. The sun gear member **232** rotates at the same speed as the ring gear member **244**. The planet carrier assembly member **246** does not rotate. The ring gear member **244** rotates at a speed determined from the speed of the sun gear member **242** and the ring gear/sun gear tooth ratio of the planetary gear set **240**. The numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **240**.

[0110] The first forward speed ratio is established with the engagement of the clutches **250, 256** and the brake **259**. The clutch **250** connects the planet carrier assembly member **226** to the ring gear member **234**. The clutch **256** connects the sun gear member **222** to the sun gear member **242**. The brake **259** connects the planet carrier assembly member **236** to the transmission housing **260**. The sun gear members **222, 242** rotate at the same speed as the input shaft **17**. The planet carrier assembly member **226** and ring gear member **234** rotate at the same speed as the output shaft **19**. The planet carrier assembly member **236** does not rotate. The sun gear member **232** rotates at the same speed as the ring gear member **244**. The ring gear member **234**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the sun gear member **232** and the ring gear/sun gear tooth ratio of the planetary gear set **230**. The planet carrier assembly member **246** does not rotate. The ring gear member **244** rotates at a speed determined from the speed of the sun gear member **242** and the ring gear/sun gear tooth ratio of the planetary gear set **240**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **230** and **240**.

[0111] The second forward speed ratio is established with the engagement of the clutches **250, 254** and the brake **259**. The clutch **250** connects the planet carrier assembly member **226** to the ring gear member **234**. The clutch **254** connects the ring gear member **224** to the planet carrier assembly member **236**. The brake **259** connects the planet carrier assembly member **236** to the transmission housing **260**. The sun gear member **222** rotates at the same speed as the input shaft **17**. The planet carrier assembly member **226** and ring gear member **234** rotate at the same speed as the output shaft **19**. The ring gear member **224** and planet carrier assembly member **236** do not rotate. The planet carrier assembly member **226** rotates at a speed determined from the speed of the sun gear member **222** and the ring gear/sun gear tooth ratio of the planetary gear set **220**. The sun gear member **232** rotates at the same speed as ring gear member **244**. The planet carrier assembly member **246** does not rotate. The numerical value of the second forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **220**.

[0112] The third forward speed ratio is established with the engagement of the clutches **250, 254, 256**. The clutch **250** connects the planet carrier assembly member **226** to the ring gear member **234**. The clutch **254** connects the ring gear member **224** to the planet carrier assembly member **236**. The clutch **256** connects the sun gear member **222** to the sun gear member **242**. The sun gear members **222, 242** rotate at the same speed as the input shaft **17**. The planet carrier assembly member **226** and ring gear member **234** rotate at the same speed output shaft **19**. The ring gear member **224** rotates at the same speed as the planet carrier assembly member **236**. The planet carrier assembly member **226** rotates at a speed determined from the speed of the ring gear member **224**, the speed of the sun gear member **222**, and the ring gear/sun gear tooth ratio of the planetary gear set **220**. The sun gear member **232** rotates at the same speed as the ring gear member **244**. The ring gear member **234** rotates at a speed determined from the speed of the planet carrier assembly member **236**, the speed of the sun gear member **232**, and the ring gear/sun gear tooth ratio of the planetary gear set **230**. The planet carrier assembly member **246** does not rotate. The ring gear member **244** rotates at a speed determined from the speed of the sun gear member **242** and the ring gear/sun gear tooth ratio of the planetary gear set **240**. The numerical value of the third forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **220, 230** and **240**.

[0113] The fourth forward speed ratio is established with the engagement of the clutches **250, 254** and the brake **258**. The clutch **250** connects the planet carrier assembly member **226** to the ring gear member **234**. The clutch **254** connects the ring gear member **224** to the planet carrier assembly member **236**. The brake **258** connects the ring gear member **244** to the transmission housing **260**. The sun gear member **222** rotates at the same speed as the input shaft **17**. The planet carrier assembly member **226** and ring gear member **234** rotate at the same speed as the output shaft **19**. The ring gear member **224** and the planet carrier assembly member **236** rotate at the same speed. The planet carrier assembly member **226** rotates at a speed determined from the speed of the ring gear member **224**, the speed of the sun gear member

222, and the ring gear/sun gear tooth ratio of the planetary gear set **220**. The sun gear member **232** and planetary gear set **240** do not rotate. The planet carrier assembly member **236** rotates at a speed determined from the speed of the ring gear member **234** and the ring gear/sun gear tooth ratio of the planetary gear set **230**. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **220** and **230**.

[**0114**] The fifth forward speed ratio is established with the engagement of the clutches **250**, **252**, **254**. In this configuration, the input shaft **17** is directly connected to the output shaft **19**. The numerical value of the fifth forward speed ratio is 1.

[**0115**] The sixth forward speed ratio is established with the engagement of the clutches **252**, **254** and the brake **258**. The clutch **252** connects the planet carrier assembly member **226** to the planet carrier assembly member **236**. The clutch **254** connects the ring gear member **224** to the planet carrier assembly member **236**. The brake **258** connects the ring gear member **244** to the transmission housing **260**. The sun gear member **222** rotates at the same speed as the input shaft **17**. The planet carrier assembly members **226**, **236** rotate at the same speed as the ring gear member **224**. The ring gear member **234** rotates at the same speed as the output shaft **19**. The sun gear member **232** and the planetary gear set **240** do not rotate. The ring gear member **234**, and therefore the output shaft **19**, rotates at a speed determined from the speed of the planet carrier assembly member **236** and the ring gear/sun gear tooth ratio of the planetary gear set **230**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **230**.

[**0116**] The seventh forward speed ratio is established with the engagement of the clutches **252**, **254**, **256**. The clutch **252** connects the planet carrier assembly member **226** to the planet carrier assembly member **236**. The clutch **254** connects the ring gear member **224** to the planet carrier assembly member **236**. The clutch **256** connects the sun gear member **222** to the sun gear member **242**. The sun gear members **222**, **242** rotate at the same speed as the input shaft **17**. The planet carrier assembly members **226**, **236** rotate at the same speed as the ring gear member **224**. The ring gear member **234** rotates at the same speed as the output shaft **19**. The sun gear member **232** rotates at the same speed as the ring gear member **244**. The ring gear member **234** rotates at a speed determined from the speed of the planet carrier assembly member **236**, the speed of the sun gear member **232**, and the ring gear/sun gear tooth ratio of the planetary gear set **230**. The planet carrier assembly member **246** does not rotate. The ring gear member **244** rotates at a speed determined from the speed of the sun gear member **242** and the ring gear/sun gear tooth ratio of the planetary gear set **240**. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **230** and **240**.

[**0117**] As previously set forth, the truth table of **FIG. 3***b* describes the combinations of engagements utilized for the seven forward speed ratios and reverse ratio. The truth table also provides an example of speed ratios that are available with the family member described above. These examples of speed ratios are determined utilizing the tooth ratios given in **FIG. 3***b*. The R1/S1 value is the tooth ratio of the planetary gear set **220**; t he R2/S2 value is the tooth ratio of the planetary gear set **230**; and the R3/S3 value is the tooth ratio of the planetary gear set **240**. Also depicted in **FIG. 3***b* is a chart representing the ratio steps between adjacent forward speed ratios and the reverse speed ratio. For example, the first to second ratio interchange has a step of 1.68. It can also be readily determined from the truth table of **FIG. 3***b* that all of the single step forward ratio interchanges are of the single transition variety, as are all of the double step forward interchanges.

[**0118**] A powertrain **310**, shown in **FIG. 4***a*, includes the engine and torque converter **12**, a planetary transmission **314**, and the final drive mechanism **16**. The planetary transmission **314** includes an input shaft **17** continuously connected with the engine and torque converter **12**, a planetary gear arrangement **318**, and output shaft **19** continuously connected with the final drive mechanism **16**. The planetary gear arrangement **318** includes three planetary gear sets **320**, **330** and **340**.

[**0119**] The planetary gear set **320** includes a sun gear member **322**, a ring gear member **324**, and a planet carrier assembly member **326**. The planet carrier assembly member **326** includes a plurality of pinion gears **327** rotatably mounted on a carrier member **329** and disposed in meshing relationship with both the sun gear member **322** and the ring gear member **324**

[**0120**] The planetary gear set **330** includes a sun gear member **332**, a ring gear member **334**, and a planet carrier assembly member **336**. The planet carrier assembly member **336** includes a plurality of pinion gears **337** rotatably mounted on a carrier member **339** and disposed in meshing relationship with both the sun gear member **332** and the ring gear member **334**.

[**0121**] The planetary gear set **340** includes a sun gear member **342**, a ring gear member **344**, and a planet carrier assembly member **346**. The planet carrier assembly member **346** includes a plurality of pinion gears **347** rotatably mounted on a carrier member **349** and disposed in meshing relationship with both the sun gear member **342** and the ring gear member **344**.

[**0122**] The planetary gear arrangement **318** also includes six torque-transmitting mechanisms **350**, **352**, **354**, **356**, **358** and **359**. The torque-transmitting mechanisms **350**, **352**, **354**, **356** and **358** are of the rotating type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **359** is a stationary type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0123**] The input shaft **17** is continuously connected with the sun gear member **332**, and the output shaft **19** is continuously connected with the ring gear member **324**. The planet carrier assembly member **346** is continuously connected with the transmission housing **360**. The planet carrier assembly member **336** is continuously connected with the ring gear member **344** through the interconnecting member **370**.

[**0124**] The sun gear member **322** is selectively connectable with the ring gear member **324** through the clutch **350**. The sun gear member **322** is selectively connectable with the ring gear member **334** through the clutch **352**. The planet carrier assembly member **326** is selectively connectable with the planet carrier assembly member **336** through the clutch

354. The planet carrier assembly member **326** is selectively connectable with the sun gear member **332** through the clutch **356**. The ring gear member **334** is selectively connectable with the sun gear member **342** through the clutch **358**. The sun gear member **322** is selectively connectable with the transmission housing **360** through the brake **359**.

[**0125**] The truth tables given in **FIGS. 4***b*, **5***b*, **6***b*, **7***b*, **8***b*, **9***b*, **10***b*, **11***b*, **12***b*, **13***b*, **14***b*, **15***b*, **16***b*, **17***b*, **18***b*, **19***b* and **20***b* show the engagement sequences for the torque-transmitting mechanisms to provide at least seven forward speed ratios and at least one reverse ratio. As shown and described above for the configuration in **FIGS. 1***a*, **2***a* and **3***a*, those skilled in the art will understand from the respective truth tables how the speed ratios are established through the planetary gear sets identified in the written description.

[**0126**] The truth table shown in **FIG. 4***b* describes the engagement combination and the engagement sequence necessary to provide the reverse drive ratio and seven forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 4***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 4***b*. The R1/S1 value is the tooth ratio for the planetary gear set **320**; the R2/S2 value is the tooth ratio for the planetary gear set **330**; and the R3/S3 value is the tooth ratio for the planetary gear set **340**. Also given in **FIG. 4***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio. For example, the first to second forward speed ratio step is 1.5. It can be readily determined from the truth table of **FIG. 4***b* that each of the forward single step ratio interchanges is a single transition shift, as are the double step interchanges. The chart also shows that the torque-transmitting mechanisms **350** and **358** can be engaged through the neutral condition to simplify the forward/reverse interchange.

[**0127**] Those skilled in the art will recognize that the numerical values of the reverse and first forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **330** and **340**. The numerical values of the second, third and seventh forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **320**, **330** and **340**. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **320** and **330**. The numerical value of the fifth forward speed ratio is 1. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **320**.

[**0128**] A powertrain **410**, shown in **FIG. 5***a*, includes the engine and torque converter **12**, a planetary transmission **414** and the final drive mechanism **16**. The planetary transmission **414** includes a planetary gear arrangement **418**, input shaft **17** and output shaft **19**. The planetary gear arrangement **418** includes three simple planetary gear sets **420**, **430** and **440**.

[**0129**] The planetary gear set **420** includes a sun gear member **422**, a ring gear member **424**, and a planet carrier assembly **426**. The planet carrier assembly **426** includes a plurality of pinion gears **427** rotatably mounted on a carrier member **429** and disposed in meshing relationship with both the sun gear member **422** and the ring gear member **424**.

[**0130**] The planetary gear set **430** includes a sun gear member **432**, a ring gear member **434**, and a planet carrier assembly member **436**. The planet carrier assembly member **436** includes a plurality of pinion gears **437** rotatably mounted on a carrier member **439** and disposed in meshing relationship with both the sun gear member **432** and the ring gear member **434**.

[**0131**] The planetary gear set **440** includes a sun gear member **442**, a ring gear member **444**, and a planet carrier assembly member **446**. The planet carrier assembly member **446** includes a plurality of pinion gears **447** rotatably mounted on a carrier member **449** and disposed in meshing relationship with both the sun gear member **442** and the ring gear member **444**.

[**0132**] The planetary gear arrangement **418** also includes six torque-transmitting mechanisms **450**, **452**, **454**, **456**, **458** and **459**. The torque-transmitting mechanisms **450**, **452**, **454** and **456** are rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanisms **458** and **459** are stationary-type torque-transmitting mechanisms, commonly termed brakes or reaction clutches.

[**0133**] The input shaft **17** is continuously connected with the sun gear member **432**, and the output shaft **19** is continuously connected with the ring gear member **424**. The sun gear member **442** is continuously connected with the transmission housing **460**. The planet carrier assembly member **436** is continuously connected with the ring gear member **444** through the interconnecting member **470**.

[**0134**] The sun gear member **422** is selectively connectable with the ring gear member **434** through the clutch **450**. The sun gear member **422** is selectively connectable with the planet carrier assembly member **446** through the clutch **452**. The planet carrier assembly member **426** is selectively connectable with the planet carrier assembly member **436** through the clutch **454**. The planet carrier assembly member **426** is selectively connectable with the sun gear member **432** through the clutch **456**. The sun gear member **422** is selectively connectable with the transmission housing **460** through the brake **458**. The planet carrier assembly member **426** is selectively connectable with the transmission housing **460** through the brake **459**.

[**0135**] The truth table shown in **FIG. 5***b* describes the engagement combination and sequence of the torque-transmitting mechanisms **450**, **452**, **454**, **456**, **458** and **459** that are employed to provide the reverse drive ratio and the seven forward speed ratios. It should be noted that the torque-transmitting mechanisms **450** and **459** are engaged through the neutral condition to simplify the forward/reverse interchange.

[**0136**] Also given in the truth table of **FIG. 5***b* is a set of numerical values that are attainable with the present invention utilizing the ring gear/sun gear tooth ratios shown. The R1/S1 value is the tooth ratio of the planetary gear set **420**; the R2/S2 value is the tooth ratio of the planetary gear set **430**; and the R3/S3 value is the tooth ratio of the planetary gear set **440**. As can also be determined from the truth table of **FIG. 5***b*, the single step forward interchanges are single transition shifts, as are the double step interchanges in the forward direction.

[**0137**] **FIG. 5***b* also provides a chart of the ratio steps between adjacent forward ratios and between the reverse and first forward ratio. For example, the ratio step between the first and second forward ratios is 1.76.

[0138] Those skilled in the art will recognize that the numerical values of the reverse, third and sixth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **420**, **430** and **440**. The numerical values of the first and second forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **420** and **430**. The numerical value of the fourth forward speed ratio is 1. The numerical value of the fifth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **420** and **440**. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **420**.

[0139] A powertrain **510**, shown in **FIG. 6***a*, includes an engine and torque converter **12**, a planetary gear transmission **514** and the final drive mechanism **16**. The planetary transmission **514** includes the input shaft **17**, a planetary gear arrangement **518** and the output shaft **19**. The planetary gear arrangement **518** includes three planetary gear sets **520**, **530** and **540**.

[0140] The planetary gear set **520** includes a sun gear member **522**, a ring gear member **524**, and a planet carrier assembly **526**. The planet carrier assembly **526** includes a plurality of pinion gears **527** rotatably mounted on a carrier member **529** and disposed in meshing relationship with both the sun gear member **522** and the ring gear member **524**.

[0141] The planetary gear set **530** includes a sun gear member **532**, a ring gear member **534**, and a planet carrier assembly member **536**. The planet carrier assembly member **536** includes a plurality of pinion gears **537** rotatably mounted on a carrier member **539** and disposed in meshing relationship with both the sun gear member **532** and the ring gear member **534**.

[0142] The planetary gear set **540** includes a sun gear member **542**, a ring gear member **544**, and a planet carrier assembly member **546**. The planet carrier assembly member **546** includes a plurality of pinion gears **547** rotatably mounted on a carrier member **549** and disposed in meshing relationship with both the sun gear member **542** and the ring gear member **544**.

[0143] The planetary gear arrangement **518** also includes six torque-transmitting mechanisms **550**, **552**, **554**, **556**, **558** and **559**. The torque-transmitting mechanisms **550**, **552**, **554**, **556** and **558** are rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **559** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[0144] The input shaft **17** is continuously connected with the planet carrier assembly member **536**, and the output shaft **19** is continuously connected with the planet carrier assembly member **526**. The ring gear member **544** is continuously connected with the transmission housing **56**o. The ring gear member **534** is continuously connected with the sun gear member **542** through the interconnecting member **570**.

[0145] The ring gear member **524** is selectively connectable with the ring gear member **534** through the clutch **550**. The planet carrier assembly member **526** is selectively connectable with the ring gear member **534** through the clutch **552**. The sun gear member **522** is selectively connectable with the sun gear member **532** through the clutch **554**. The sun gear member **522** is selectively connectable with the planet carrier assembly member **536** through the clutch **556**. The planet carrier assembly member **536** is selectively connectable with the planet carrier assembly member **546** through the clutch **558**. The ring gear member **524** is selectively connectable with the transmission housing **560** through the brake **559**.

[0146] The truth table shown in **FIG. 6***b* describes the engagement sequence and combination of the torque-transmitting mechanisms to provide the reverse speed ratio and seven forward speed ratios. It should be noted that the torque-transmitting mechanisms **552** and **559** can remain engaged through the neutral condition, thereby simplifying the forward/reverse interchange. It can also be determined from the truth table of **FIG. 6***b* that all of the single step forward ratio interchanges are of the single transition variety, as are all of the double step forward interchanges. The chart of **FIG. 6***b* describes the ratio steps between adjacent forward speed ratios and the ratio step between the reverse and first forward speed ratio.

[0147] Those skilled in the art, upon reviewing the truth table and the schematic representation of **FIG. 6***a*, can determine that the numerical values of the reverse and fifth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **520**, **530** and **540**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **520**. The numerical values of the second and third forward speed ratios are determined utilizing the ring gear/sun gear tooth **30** ratios of the planetary gear sets **520** and **530**. The numerical value of the fourth forward speed ratio is 1. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **520** and **540**. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **540**.

[0148] The sample speed ratios given in the truth table are determined utilizing the tooth ratio values also given in **FIG. 6***b*. The R1/S1 value is the tooth ratio of the planetary gear set **520**; the R2/S2 value is the tooth ratio of the planetary gear set **530**; and the R3/S3 value is the tooth ratio of the planetary gear set **540**.

[0149] A powertrain **610**, shown in **FIG. 7***a*, has the engine and torque converter **12**, a planetary transmission **614** and the final drive mechanism **16**. The planetary transmission **614** includes the input shaft **17**, a planetary gear arrangement **618** and the output shaft **19**. The planetary gear arrangement **618** includes three planetary gear sets **620**, **630** and **640**.

[0150] The planetary gear set **620** includes a sun gear member **622**, a ring gear member **624**, and a planet carrier assembly **626**. The planet carrier assembly **626** includes a plurality of pinion gears **627** rotatably mounted on a carrier member **629** and disposed in meshing relationship with both the sun gear member **622** and the ring gear member **624**.

[0151] The planetary gear set **630** includes a sun gear member **632**, a ring gear member **634**, and a planet carrier assembly member **636**. The planet carrier assembly member **636** includes a plurality of pinion gears **637** rotatably mounted on a carrier member **639** and disposed in meshing relationship with both the sun gear member **632** and the ring gear member **634**.

[0152] The planetary gear set **640** includes a sun gear member **642**, a ring gear member **644**, and a planet carrier assembly member **646**. The planet carrier assembly member **646** includes a plurality of pinion gears **647** rotatably mounted on a carrier member **649** and disposed in meshing relationship with both the sun gear member **642** and the ring gear member **644**.

[0153] The planetary gear arrangement **618** also includes six torque-transmitting mechanisms **650**, **652**, **654**, **656**, **658** and **659**. The torque-transmitting mechanisms **650**, **652**, **654** and **656** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanisms **658** and **659** are stationary-type torque-transmitting mechanisms, commonly termed brakes or reaction clutches.

[0154] The input shaft **17** is continuously connected with the sun gear member **622**, and the output shaft **19** is continuously connected with the sun gear member **632**. The sun gear member **642** is continuously connected with the transmission housing **660**. The ring gear member **634** is continuously connected with the ring gear member **644** through the interconnecting member **670**.

[0155] The ring gear member **624** is selectively connectable with the planet carrier assembly member **646** through the clutch **650**. The planet carrier assembly member **626** is selectively connectable with the ring gear member **634** through the clutch **652**. The sun gear member **622** is selectively connectable with the planet carrier assembly member **636** through the clutch **654**. The planet carrier assembly member **636** is selectively connectable with the ring gear member **644** through the clutch **656**. The ring gear member **624** is selectively connectable with the transmission housing **660** through the brake **658**. The planet carrier assembly member **626** is selectively connectable with the transmission housing **660** through the brake **659**.

[0156] The truth table shown in **FIG. 7***b* describes the combination of torque-transmitting mechanism engagements that will provide the reverse drive ratio and seven forward speed ratios, as well as the sequence of these engagements and interchanges. The torque-transmitting mechanisms **652** and **656** can be engaged through the neutral condition, thereby simplifying the forward/reverse interchange. It can be noted from the truth table that each of the single step forward interchanges are single transition ratio changes, as are the double step forward interchanges.

[0157] The ratio values given are by way of example and are established utilizing the ring gear/sun gear tooth ratios given in **FIG. 7***b*. For example, the R1/S1 value is the tooth ratio of the planetary gear set **620**; the R2/S2 value is the tooth ratio of the planetary gear set **630**; and the R3/S3 value is the tooth ratio of the planetary gear set **640**. The ratio steps between adjacent forward ratios and the reverse to first ratio are also given in **FIG. 7***b*.

[0158] Those skilled in the art will, upon reviewing the truth table of **FIG. 7***b*, recognize that the numerical values of the reverse and second forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **620** and **640**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **620**. The numerical value of the third forward speed ratio is 1. The numerical values of the fourth and seventh forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **620**, **630** and **640**. The numerical value of the fifth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **620** and **630**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **630**.

[0159] A powertrain **710**, shown in **FIG. 8***a*, has the conventional engine and torque converter **12**, a planetary transmission **714**, and the conventional final drive mechanism **16**. The engine and torque converter **12** are drivingly connected with the planetary transmission **714** through the input shaft **17**. The planetary transmission **714** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **714** includes a planetary gear arrangement **718** that has a first planetary gear set **720**, a second planetary gear set **730**, and a third planetary gear set **740**.

[0160] The planetary gear set **720** includes a sun gear member **722**, a ring gear member **724**, and a planet carrier assembly **726**. The planet carrier assembly **726** includes a plurality of pinion gears **727** rotatably mounted on a carrier member **729** and disposed in meshing relationship with both the sun gear member **722** and the ring gear member **724**.

[0161] The planetary gear set **730** includes a sun gear member **732**, a ring gear member **734**, and a planet carrier assembly member **736**. The planet carrier assembly member **736** includes a plurality of pinion gears **737** rotatably mounted on a carrier member **739** and disposed in meshing relationship with both the sun gear member **732** and the ring gear member **734**.

[0162] The planetary gear set **740** includes a sun gear member **742**, a ring gear member **744**, and a planet carrier assembly member **746**. The planet carrier assembly member **746** includes a plurality of pinion gears **747** rotatably mounted on a carrier member **749** and disposed in meshing relationship with both the sun gear member **742** and the ring gear member **744**.

[0163] The planetary gear arrangement **718** also includes six torque-transmitting mechanisms **750**, **752**, **754**, **756**, **758** and **759**. The torque-transmitting mechanisms **750**, **752**, **754**, **756** and **758** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **759** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[0164] The input shaft **17** is continuously connected with the planet carrier assembly member **726**, and the output shaft **19** is continuously connected with the sun gear member **722**. The sun gear member **742** is continuously connected with the transmission housing **760**. The sun gear member **732** is continuously connected with the ring gear member **744** through the interconnecting member **770**.

[0165] The planet carrier assembly member **726** is selectively connectable with the sun gear member **732** through the clutch **750**. The planet carrier assembly member **726** is selectively connectable with the planet carrier assembly member **736** through the clutch **752** The ring gear member **724** is selectively connectable with the ring gear member **734** through the clutch **754**. The sun gear member **722** is selectively connectable with the ring gear member **734**

through the clutch **756**. The planet carrier assembly member **736** is selectively connectable with the planet carrier assembly member **746** through the clutch **758**. The planet carrier assembly member **736** is selectively connectable with the transmission housing **760** through the brake **759**.

[**0166**] The truth table of **FIG. 8***b* defines the torque-transmitting mechanism engagement sequence utilized for each of the forward speed ratios and the reverse speed ratio. Also given in the truth table is a set of numerical values that are attainable with the present invention utilizing the ring gear/sun gear tooth ratios given in **FIG. 8***b*. The R1/S1 value is the tooth ratio of the planetary gear set **720**; the R2/S2 value is the tooth ratio of the planetary gear set **730**; and the R3/S3 value is the tooth ratio of the planetary gear set **740**. As can also be determined from the truth table of **FIG. 8***b*, the single step forward interchanges are single transition shifts, as are the double step interchanges in the forward direction.

[**0167**] **FIG. 8***b* also provides a chart of the ratio steps between adjacent forward ratios and between the reverse and first forward ratio. For example, the ratio step between the first and second forward ratios is 1.67. Those skilled in the art will recognize that the numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **730**. The numerical values of the first and second forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **730** and **740**. The numerical value of the third forward speed ratio is 1. The numerical values of the fourth and fifth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **720**, **730** and **740**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **720**. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **720** and **730**.

[**0168**] A powertrain **810**, shown in **FIG. 9***a*, has the conventional engine and torque converter **12**, a planetary transmission **814**, and the final drive mechanism **16**. The engine and torque converter **12** are drivingly connected with the planetary transmission **814** through the input shaft **17**. The planetary transmission **814** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **814** includes a planetary gear arrangement **818** that has a first planetary gear set **820**, a second planetary gear set **830**, and a third planetary gear set **840**.

[**0169**] The planetary gear set **820** includes a sun gear member **822**, a ring gear member **824**, and a planet carrier assembly **826**. The planet carrier assembly **826** includes a plurality of pinion gears **827** rotatably mounted on a carrier member **829** and disposed in meshing relationship with both the sun gear member **822** and the ring gear member **824**.

[**0170**] The planetary gear set **830** includes a sun gear member **832**, a ring gear member **834**, and a planet carrier assembly member **836**. The planet carrier assembly member **836** includes a plurality of pinion gears **837** rotatably mounted on a carrier member **839** and disposed in meshing relationship with both the sun gear member **832** and the ring gear member **834**.

[**0171**] The planetary gear set **840** includes a sun gear member **842**, a ring gear member **844**, and a planet carrier assembly member **846**. The planet carrier assembly member **846** includes a plurality of pinion gears **847** rotatably mounted on a carrier member **849** and disposed in meshing relationship with both the sun gear member **842** and the ring gear member **844**.

[**0172**] The planetary gear arrangement **818** also includes six torque-transmitting mechanisms **850**, **852**, **854**, **856**, **858** and **859**. The torque-transmitting mechanisms **850**, **852**, **854** and **856** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanisms **858** and **859** are stationary-type torque-transmitting mechanisms, commonly termed brakes or reaction clutches.

[**0173**] The input shaft **17** is continuously connected with the sun gear member **832**, and the output shaft **19** is continuously connected with the ring gear member **824**. The ring gear member **844** is continuously connected with the transmission housing **860**. The planet carrier assembly member **836** is continuously connected with the planet carrier assembly member **846** through the interconnecting member **870**.

[**0174**] The sun gear member **822** is selectively connectable with the ring gear member **834** through the clutch **850**. The planet carrier assembly member **826** is selectively connectable with the planet carrier assembly member **836** through the clutch **852**. The planet carrier assembly member **826** is selectively connectable with the sun gear member **832** through the clutch **854**. The ring gear member **834** is selectively connectable with the sun gear member **842** through the clutch **856**. The sun gear member **822** is selectively connectable with the transmission housing **860** through the brake **858**. The planet carrier assembly member **846** is selectively connectable with the transmission housing **860** through the brake **859**.

[**0175**] The truth table shown in **FIG. 9***b* defines the torque-transmitting mechanism engagement sequence that provides the reverse ratio and seven forward speed ratios shown in the truth table and available with the planetary gear arrangement **818**. The truth table indicates that the torque-transmitting mechanisms **852** and **856** can remain engaged through the neutral condition, thereby simplifying the forward/reverse interchange. A sample of numerical values for the individual ratios is also given in the truth table of **FIG. 9***b*. These numerical values have been calculated using the ring gear/sun gear tooth ratios also given by way of example in **FIG. 9***b*. The R1/S1 value is the tooth ratio of the planetary gear set **820**; the R2/S2 value is the tooth ratio of the planetary gear set **830**; and the R3/S3 value is the tooth ratio of the planetary gear set **840**. It can be readily recognized from the truth table that all of the single and double step forward interchanges are single transition ratio interchanges. **FIG. 9***b* also describes the ratio steps between adjacent forward ratios and between the reverse and first forward ratio. For example, the ratio step between the first and second forward ratios is 1.59.

[**0176**] Those skilled in the art of planetary transmissions will recognize that the numerical values of the reverse, first and seventh forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **820**, **830** and **840**. The numerical values of the second, third and sixth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **820**

and **830**. The numerical value of the fourth forward speed ratio is 1. The numerical value of the fifth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **820**.

[**0177**] The powertrain **910**, shown in **FIG. 10***a*, includes the conventional engine and torque converter **12**, a planetary transmission **914**, and the conventional final drive mechanism **16**. The engine and torque converter **12** are drivingly connected with the planetary transmission **914** through the input shaft **17**. The planetary transmission **914** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **914** includes a planetary gear arrangement **918** that has a first planetary gear set **920**, a second planetary gear set **930**, and a third planetary gear set **940**.

[**0178**] The planetary gear set **920** includes a sun gear member **922**, a ring gear member **924**, and a planet carrier assembly **926**. The planet carrier assembly **926** includes a plurality of pinion gears **927** that are rotatably mounted on a carrier member **929** and disposed in meshing relationship with the sun gear member **922** and the ring gear member **924**, respectively.

[**0179**] The planetary gear set **930** includes a sun gear member **932**, a ring gear member **934**, and a planet carrier assembly member **936**. The planet carrier assembly member **936** includes a plurality of pinion gears **937** rotatably mounted on a carrier member **939** and disposed in meshing relationship with both the sun gear member **932** and the ring gear member **934**.

[**0180**] The planetary gear set **940** includes a sun gear member **942**, a ring gear member **944**, and a planet carrier assembly member **946**. The planet carrier assembly member **946** includes a plurality of pinion gears **947** rotatably mounted on a carrier member **949** and disposed in meshing relationship with both the sun gear member **942** and the ring gear member **944**.

[**0181**] The planetary gear arrangement **918** also includes six torque-transmitting mechanisms **950**, **952**, **954**, **956**, **958** and **959**. The torque-transmitting mechanisms **950**, **952**, **954**, **956** and **958** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **959** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0182**] The input shaft **17** is continuously connected with the planet carrier assembly member **926**, and the output shaft **19** is continuously connected with the ring gear member **924**. The ring gear member **944** is continuously connected with the transmission housing **960**. The sun gear member **932** is continuously connected with the sun gear member **942** through the interconnecting member **970**.

[**0183**] The planet carrier assembly member **926** is selectively connectable with the ring gear member **934** through the clutch **950**. The sun gear member **922** is selectively connectable with the planet carrier assembly member **936** through the clutch **952**. The sun gear member **922** is selectively connectable with the planet carrier assembly member **946** through the clutch **954**. The ring gear member **924** is selectively connectable with the planet carrier assembly member **946** through the clutch **956**. The sun gear member **932** is selectively connectable with the planet carrier assembly member **936** through the clutch **958**. The planet carrier assembly member **936** is selectively connectable with the transmission housing **960** through the brake **959**.

[**0184**] The truth table of **FIG. 10***b* describes the torque-transmitting mechanism engagement sequence utilized to provide the reverse speed ratio and seven forward speed ratios. The truth table also provides a set of examples for the ratios for each of the reverse and forward speed ratios. These numerical values have been determined utilizing the ring gear/sun gear tooth ratios given in **FIG. 10***b*. The R1/S1 value is the tooth ratio of the planetary gear set **920**; the R2/S2 value is the tooth ratio of the planetary gear set **930**; and the R3/S3 value is the tooth ratio of the planetary gear set **940**. It can also be determined from the truth table of **FIG. 10***b* that each of the forward single step ratio interchanges are of the single transition variety, as are the double step interchanges.

[**0185**] Those skilled in the art, upon reviewing the engagement combinations, will recognize that the numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **930** and **940**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **940**. The numerical values of the second, fifth and sixth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **920** and **940**. The numerical values of the third and seventh forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **920**, **930** and **940**. The numerical value of the fourth forward speed ratio is 1.

[**0186**] A powertrain **1010**, shown in **FIG. 11***a*, includes the conventional engine and torque converter **12**, a planetary transmission **1014**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1014** through the input shaft **17**. The planetary transmission **1014** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **1014** includes a planetary gear arrangement **1018** that has a first planetary gear set **1020**, a second planetary gear set **1030**, and a third planetary gear set **1040**.

[**0187**] The planetary gear set **1020** includes a sun gear member **1022**, a ring gear member **1024**, and a planet carrier assembly **1026**. The planet carrier assembly **1026** includes a plurality of pinion gears **1027** rotatably mounted on a carrier member **1029** and disposed in meshing relationship with both the sun gear member **1022** and the ring gear member **1024**.

[**0188**] The planetary gear set **1030** includes a sun gear member **1032**, a ring gear member **1034**, and a planet carrier assembly member **1036**. The planet carrier assembly member **1036** includes a plurality of pinion gears **1037** rotatably mounted on a carrier member **1039** and disposed in meshing relationship with both the sun gear member **1032** and the ring gear member **1034**.

[**0189**] The planetary gear set **1040** includes a sun gear member **1042**, a ring gear member **1044**, and a planet carrier assembly member **1046**. The planet carrier assembly member **1046** includes a plurality of pinion gears **1047** rotatably mounted on a carrier member **1049** and disposed in meshing relationship with both the sun gear member **1042** and the ring gear member **1044**.

[0190] The planetary gear arrangement **1008** also includes six torque-transmitting mechanisms **1050**, **1052**, **1054**, **1056**, **1058** and **1059**.

[0191] The torque-transmitting mechanisms **1050**, **1052**, **1054** and **1056** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanisms **1058** and **1059** are stationary-type torque-transmitting mechanisms, commonly termed brakes or reaction clutches.

[0192] The input shaft **17** is continuously connected with the sun gear member **1032**, and the output shaft **19** is continuously connected with the ring gear member **1024**. The ring gear member **1044** is continuously connected with the transmission housing **1060**. The ring gear member **1034** is continuously connected with the sun gear member **1042** through the interconnecting member **1070**.

[0193] The sun gear member **1022** is selectively connectable with the ring gear member **1034** through the clutch **1050**. The planet carrier assembly member **1026** is selectively connectable with the planet carrier assembly member **1036** through the clutch **1052**. The planet carrier assembly member **1026** is selectively connectable with the sun gear member **1032** through the clutch **1054**. The planet carrier assembly member **1036** is selectively connectable with the planet carrier assembly member **1046** through the clutch **1056**. The sun gear member **1022** is selectively connectable with the transmission housing **1060** through the brake **1058**. The planet carrier assembly member **1036** is selectively connectable with the transmission housing **1060** through the brake **1059**.

[0194] The truth table shown in **FIG. 11***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and the seven forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of FIG. **11***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 11***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1020**; the R2/S2 value is the tooth ratio for the planetary gear set **1030**; and the R3/S3 value is the tooth ratio for the planetary gear set **1040**. Also given in **FIG. 11***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[0195] Those skilled in the art will recognize that the numerical values of the reverse, first and seventh forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1020**, **1030** and **1040**. The numerical values of the second, third and sixth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1020** and **1030**. The numerical value of the fourth forward speed ratio is 1. The numerical value of the fifth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1020**.

[0196] A powertrain **1110**, shown in **FIG. 12***a*, has a conventional engine and torque converter **12**, a planetary transmission **1114**, and the conventional final drive mechanism **16**. The planetary transmission **1114** includes a planetary gear arrangement **1118** which is connected with the engine and torque converter **12** through the input shaft **17** and with the final drive mechanism **16** through the output shaft **19**. The planetary gear arrangement **1118** includes three planetary gear sets **1120**, **1130** and **1140**.

[0197] The planetary gear set **1120** includes a sun gear member **1122**, a ring gear member **1124**, and a planet carrier assembly **1126**. The planet carrier assembly **1126** includes a plurality of pinion gears **1127** rotatably mounted on a carrier member **1129** and disposed in meshing relationship with both the sun gear member **1122** and the ring gear member **1124**.

[0198] The planetary gear set **1130** includes a sun gear member **1132**, a ring gear member **1134**, and a planet carrier assembly member **1136**. The planet carrier assembly member **1136** includes a plurality of intermeshing pinion gears **1137** that are rotatably mounted on a carrier member **1139** and disposed in meshing relationship with both the sun gear member **1132** and the ring gear member **1134**.

[0199] The planetary gear set **1140** includes a sun gear member **1142**, a ring gear member **1144**, and a planet carrier assembly member **1146**. The planet carrier assembly member **1146** includes a plurality of pinion gears **1147** rotatably mounted on a carrier member **1149** and disposed in meshing relationship with both the sun gear member **1142** and the ring gear member **1144**.

[0200] The planetary gear arrangement **1118** also includes six torque-transmitting mechanisms **1150**, **1152**, **1154**, **1156**, **1158** and **1159**. The torque-transmitting mechanisms **1150**, **1152**, **1154**, **1156** and **1158** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1159** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[0201] The input shaft **17** is continuously connected with the planet carrier assembly member **1126**, and the output shaft **19** is continuously connected with the sun gear member **1122**. The ring gear member **1144** is continuously connected with the transmission housing **1160**. The ring gear member **1134** is continuously connected with the sun gear member **1142** through the interconnecting member **1170**.

[0202] The planet carrier assembly member **1126** is selectively connectable with the ring gear member **1134** through the clutch **1150**. The ring gear member **1124** is selectively connectable with the planet carrier assembly member **1136** through the clutch **1152**. The sun gear member **1122** is selectively connectable with the sun gear member **1132** through the clutch **1154**. The sun gear member **1132** is selectively connectable with the planet carrier assembly member **1146** through the clutch **1156**. The planet carrier assembly member **1136** is selectively connectable with the planet carrier assembly member **1146** through the clutch **1158**. The sun gear member **1132** is selectively connectable with the transmission housing **1160** through the brake **1159**.

[0203] The truth table shown in **FIG. 12***b* describes the engagement sequence and engagement combinations utilized with the present family member to provide a reverse drive ratio and seven forward speed ratios. The truth table of **FIG. 12***b* also provides a set of example numbers that can be established in the planetary gear arrangement **1118** utilizing the ring gear/sun gear tooth ratios. The R1/S1 value is the ring gear/sun gear tooth ratio of the planetary gear set **1120**; the R2/S2 value is the ring gear/sun gear tooth ratio of

the planetary gear set **1130**; and the R3/S3 value is the ring gear/sun gear tooth ratio of the planetary gear set **1140**.

[**0204**] The chart of **FIG. 12***b* describes the ratio steps between adjacent forward speed ratios for a seven-speed transmission. These step ratios are established utilizing the example speed ratios given in the truth table. As also shown in the truth table, the torque-transmitting mechanisms **1150** and **1154** can remain engaged through the neutral condition, thereby simplifying the forward/reverse interchange.

[**0205**] Those skilled in the art will recognize that the numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1130** and **1140**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1140**. The numerical values of the second, fourth and seventh forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1120**, **1130** and **1140**. The numerical value of the third forward speed ratio is 1. The numerical value of the fifth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1120** and **1130**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1120** and **1140**.

[**0206**] A powertrain **1210**, shown in **FIG. 13***a*, includes the conventional engine and torque converter **12**, a planetary transmission **1214**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1214** through the input shaft **17**. The planetary transmission **1214** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **1214** includes a planetary gear arrangement **1218** that has a first planetary gear set **1220**, a second planetary gear set **1230**, and a third planetary gear set **1240**.

[**0207**] The planetary gear set **1220** includes a sun gear member **1222**, a ring gear member **1224**, and a planet carrier assembly **1226**. The planet carrier assembly **1226** includes a plurality of pinion gears **1227** rotatably mounted on a carrier member **1229** and disposed in meshing relationship with both the sun gear member **1222** and the ring gear member **1224**.

[**0208**] The planetary gear set **1230** includes a sun gear member **1232**, a ring gear member **1234**, and a planet carrier assembly member **1236**. The planet carrier assembly member **1236** includes a plurality of pinion gears **1237** rotatably mounted on a carrier member **1239** and disposed in meshing relationship with both the sun gear member **1232** and the ring gear member **1234**.

[**0209**] The planetary gear set **1240** includes a sun gear member **1242**, a ring gear member **1244**, and a planet carrier assembly member **1246**. The planet carrier assembly member **1246** includes a plurality of pinion gears **1247** rotatably mounted on a carrier member **1249** and disposed in meshing relationship with both the sun gear member **1242** and the ring gear member **1244**.

[**0210**] The planetary gear arrangement **1218** also includes six torque transmitting mechanisms **1250**, **1252**, **1254**, **1256**, **1258** and **1259**. The torque-transmitting mechanisms **1250**, **1252**,**1254**, **1256** and **1258** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1259** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0211**] The input shaft **17** is continuously connected with the sun gear member **1222**, and the output shaft **19** is continuously connected with the sun gear member **1232**. The sun gear member **1242** is continuously connected with the transmission housing **1260**. The ring gear member **1234** is continuously connected with the planet carrier assembly member **1246** through the interconnecting member **1270**.

[**0212**] The sun gear member **1222** is selectively connectable with the planet carrier assembly member **1236** through the clutch **1250**. The planet carrier assembly member **1226** is selectively connectable with the ring gear member **1244** through the clutch **1252**. The ring gear member **1224** is selectively connectable with the planet carrier assembly member **1246** through the clutch **1254**. The ring gear member **1224** is selectively connectable with the ring gear member **1244** through the clutch **1256**. The planet carrier assembly member **1246** is selectively connectable with the sun gear member **1232** through the clutch **1258**. The planet carrier assembly member **1226** is selectively connectable with the transmission housing **1260** through the brake **1259**.

[**0213**] The truth table shown in **FIG. 13***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and eight forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 13***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 13***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1220**; the R2/S2 value is the tooth ratio for the planetary gear set **1230**; and the R3/S3 value is the tooth ratio for the planetary gear set **1240**. Also given in **FIG. 13***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[**0214**] Those skilled in the art will recognize that the numerical values of the reverse and first forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1220** and **1240**. The numerical value of the second forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1240**. The numerical value of the third forward speed ratio is 1. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1230** and **1240**. The numerical values of the fifth and seventh forward speed ratios are determined utilizing the ring gear/sun gear tooth ratio of the planetary gear sets **1220**, **1230** and **1240**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1230**. The numerical value of the eighth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1220** and **1230**.

[**0215**] A powertrain **1310**, shown in **FIG. 14***a*, includes the conventional engine and torque converter **12**, a planetary transmission **1314**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1314** through the input shaft **17**. The planetary transmission **1314** is drivingly connected with the final drive mechanism **16** through the

output shaft **19**. The planetary transmission **1314** includes a planetary gear arrangement **1318** that has a first planetary gear set **1320**, a second planetary gear set **1330**, and a third planetary gear set **1340**.

[**0216**] The planetary gear set **1320** includes a sun gear member **1322**, a ring gear member **1324**, and a planet carrier assembly **1326**. The planet carrier assembly **1326** includes a plurality of pinion gears **1327** rotatably mounted on a carrier member **1329** and disposed in meshing relationship with both the sun gear member **1322** and the ring gear member **1324**.

[**0217**] The planetary gear set **1330** includes a sun gear member **1332**, a ring gear member **1334**, and a planet carrier assembly member **1336**. The planet carrier assembly member **1336** includes a plurality of pinion gears **1337** rotatably mounted on a carrier member **1339** and disposed in meshing relationship with both the sun gear member **1332** and the ring gear member **1334**.

[**0218**] The planetary gear set **1340** includes a sun gear member **1342**, a ring gear member **1344**, and a planet carrier assembly member **1346**. The planet carrier assembly member **1346** includes a plurality of pinion gears **1347** rotatably mounted on a carrier member **1349** and disposed in meshing relationship with both the sun gear member **1342** and the ring gear member **1344**.

[**0219**] The planetary gear arrangement **1318** also includes six torque transmitting mechanisms **1350**, **1352**, **1354**, **1356**, **1358** and **1359**. The torque-transmitting mechanisms **1350**, **1352**, **1354**, **1356** and **1358** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1359** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0220**] The input shaft **17** is continuously connected with the planet carrier assembly member **1336**, and the output shaft **19** is continuously connected with the sun gear member **1332**. The sun gear member **1342** is continuously connected with the transmission housing **1360**. The ring gear member **1334** is continuously connected with the planet carrier assembly member **1346** through the interconnecting member **1370**.

[**0221**] The planet carrier assembly member **1326** is selectively connectable with the sun gear member **1332** through the clutch **1350**. The planet carrier assembly member **1326** is selectively connectable with the planet carrier assembly member **1336** through the clutch **1352**. The planet carrier assembly member **1326** is selectively connectable with the ring gear member **1344** through the clutch **1354**. The sun gear member **1322** is selectively connectable with the planet carrier assembly member **1336** through the clutch **1356**. The sun gear member **1322** is selectively connectable with the ring gear member **1344** through the clutch **1358**. The ring gear member **1324** is selectively connectable with the transmission housing **1360** through the brake **1359**.

[**0222**] The truth table shown in **FIG. 14***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and the seven forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 14***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 14***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1320**; the R2/S2 value is the tooth ratio for the planetary gear set **1330**; and the R3/S3 value is the tooth ratio for the planetary gear set **1340**. Also given in **FIG. 14***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[**0223**] Those skilled in the art will recognize that the numerical values of the reverse, second and sixth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1320**, **1330** and **1340**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1320**. The numerical value of the third forward speed ratio is 1. The numerical values of the fourth and fifth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1330** and **1340**. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1330**.

[**0224**] A powertrain **1410**, shown in **FIG. 15***a*, includes the conventional engine and torque converter **12**, a planetary transmission **1414**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1414** through the input shaft **17**. The planetary transmission **1414** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **1414** includes a planetary gear arrangement **1418** that has a first planetary gear set **1420**, a second planetary gear set **1430**, and a third planetary gear set **1440**.

[**0225**] The planetary gear set **1420** includes a sun gear member **1422**, a ring gear member **1424**, and a planet carrier assembly **1426**. The planet carrier assembly **1426** includes a plurality of pinion gears **1427** rotatably mounted on a carrier member **1429** and disposed in meshing relationship with both the sun gear member **1422** and the ring gear member **1424**.

[**0226**] The planetary gear set **1430** includes a sun gear member **1432**, a ring gear member **1434**, and a planet carrier assembly member **1436**. The planet carrier assembly member **1436** includes a plurality of pinion gears **1437** rotatably mounted on a carrier member **1439** and disposed in meshing relationship with both the sun gear member **1432** and the ring gear member **1434**.

[**0227**] The planetary gear set **1440** includes a sun gear member **1442**, a ring gear member **1444**, and a planet carrier assembly member **1446**. The planet carrier assembly member **1446** includes a plurality of pinion gears **1447** and **1448** rotatably mounted on a carrier member **1449** and disposed in meshing relationship with both the sun gear member **1442** and the ring gear member **1444**.

[**0228**] The planetary gear arrangement **1418** also includes six torque transmitting mechanisms **1450**, **1452**, **1454**, **1456**, **1458** and **1459**. The torque-transmitting mechanisms **1450**, **1452**, **1454**, **1456** and **1458** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1459** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0229**] The input shaft **17** is continuously connected with the planet carrier assembly member **1426**, and the output

shaft **19** is continuously connected with the sun gear member **1422**. The sun gear member **1442** is continuously connected with the transmission housing **1460**. The planet carrier assembly member **1436** is continuously connected with the planet carrier assembly member **1446** through the interconnecting member **1470**.

[**0230**] The planet carrier assembly member **1426** is selectively connectable with the planet carrier assembly member **1436** through the clutch **1450**. The planet carrier assembly member **1426** is selectively connectable with the sun gear member **1432** through the clutch **1452**. The ring gear member **1424** is selectively connectable with the ring gear member **1434** through the clutch **1454**. The sun gear member **1422** is selectively connectable with the ring gear member **1434** through the clutch **1456**. The ring gear member **1434** is selectively connectable with the ring gear member **1444** through the clutch **1458**. The planet carrier assembly member **1446** is selectively connectable with the transmission housing **1460** through the brake **1459**.

[**0231**] The truth table shown in **FIG. 11***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and the seven forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 15***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 15***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1420**; the R2/S2 value is the tooth ratio for the planetary gear set **1430**; and the R3/S3 value is the tooth ratio for the planetary gear set **1440**. Also given in **FIG. 15***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[**0232**] Those skilled in the art will recognize that the numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1430**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1430** and **1440**. The numerical value of the second forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1440**. The numerical value of the third forward speed ratio is 1. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1420** and **1440**. The numerical value of the fifth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1420**, **1430** and **1440**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1420**. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1420** and **1430**.

[**0233**] A powertrain **1510**, shown in **FIG. 16***a*, includes the conventional engine and torque converter **12**, a planetary transmission **1514**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1514** through the input shaft **17**. The planetary transmission **1514** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **1514** includes a planetary gear arrangement **1518** that has a first planetary gear set **1520**, a second planetary gear set **1530**, and a third planetary gear set **1540**.

[**0234**] The planetary gear set **1520** includes a sun gear member **1522**, a ring gear member **1524**, and a planet carrier assembly **1526**. The planet carrier assembly **1526** includes a plurality of pinion gears **1527** rotatably mounted on a carrier member **1529** and disposed in meshing relationship with both the sun gear member **1522** and the ring gear member **1524**.

[**0235**] The planetary gear set **1530** includes a sun gear member **1532**, a ring gear member **1534**, and a planet carrier assembly member **1536**. The planet carrier assembly member **1536** includes a plurality of pinion gears **1537** rotatably mounted on a carrier member **1539** and disposed in meshing relationship with both the sun gear member **1532** and the ring gear member **1534**.

[**0236**] The planetary gear set **1540** includes a sun gear member **1542**, a ring gear member **1544**, and a planet carrier assembly member **1546**. The planet carrier assembly member **1546** includes a plurality of pinion gears **1547** rotatably mounted on a carrier member **1549** and disposed in meshing relationship with both the sun gear member **1542** and the ring gear member **1544**.

[**0237**] The planetary gear arrangement **1518** also includes six torque transmitting mechanisms **1550**, **1552**, **1554**, **1556**, **1558** and **1559**. The torque-transmitting mechanisms **1550**, **1552**, **1554**, **1556** and **1558** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1559** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0238**] The input shaft **17** is continuously connected with the ring gear member **1524**, and the output shaft **19** is continuously connected with the ring gear member **1534**. The ring gear member **1544** is continuously connected with the transmission housing **1560**. The planet carrier assembly member **1536** is continuously connected with the sun gear member **1542** through the interconnecting member **1570**.

[**0239**] The sun gear member **1522** is selectively connectable with the planet carrier assembly member **1526** through the clutch **1550**. The sun gear member **1522** is selectively connectable with the planet carrier assembly member **1536** through the clutch **1552**. The sun gear member **1522** is selectively connectable with the sun gear member **1532** through the clutch **1554**. The planet carrier assembly member **1526** is selectively connectable with the ring gear member **1534** through the clutch **1556**. The ring gear member **1524** is selectively connectable with the planet carrier assembly member **1546** through the clutch **1558**. The planet carrier assembly member **1536** is selectively connectable with the transmission housing **1560** through the brake **1559**.

[**0240**] The truth table shown in **FIG. 16***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and the seven forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 16***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 16***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1520**; the R2/S2 value is the tooth ratio for the planetary gear set **1530**; and the R3/S3 value is the tooth ratio for the planetary gear set **1540**. Also given in **FIG. 16***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[0241] Those skilled in the art will recognize that the numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1530**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1520** and **1530**. The numerical value of the second forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1520**. The numerical value of the third forward speed ratio is 1. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1520** and **1540**. The numerical value of the fifth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1520**, **1530** and **1540**. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1540**. The numerical value of the seventh forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1530** and **1540**.

[0242] A powertrain **1610**, shown in **FIG. 17***a*, includes the conventional engine and torque converter **12**, a planetary transmission **1614**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1614** through the input shaft **17**. The planetary transmission **1614** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **1614** includes a planetary gear arrangement **1618** that has a first planetary gear set **1620**, a second planetary gear set **1630**, and a third planetary gear set **1640**.

[0243] The planetary gear set **1620** includes a sun gear member **1622**, a ring gear member **1624**, and a planet carrier assembly **1626**. The planet carrier assembly **1626** includes a plurality of pinion gears **1627** rotatably mounted on a carrier member **1629** and disposed in meshing relationship with both the sun gear member **1622** and the ring gear member **1624**.

[0244] The planetary gear set **1630** includes a sun gear member **1632**, a ring gear member **1634**, and a planet carrier assembly member **1636**. The planet carrier assembly member **1636** includes a plurality of pinion gears **1637** rotatably mounted on a carrier member **1639** and disposed in meshing relationship with both the sun gear member **1632** and the ring gear member **1634**.

[0245] The planetary gear set **1640** includes a sun gear member **1642**, a ring gear member **1644**, and a planet carrier assembly member **1646**. The planet carrier assembly member **1646** includes a plurality of pinion gears **1647** rotatably mounted on a carrier member **1649** and disposed in meshing relationship with both the sun gear member **1642** and the ring gear member **1644**.

[0246] The planetary gear arrangement **1618** also includes six torque transmitting mechanisms **1650**, **1652**, **1654**, **1656**, **1658** and **1659**. The torque-transmitting mechanisms **1650**, **1652**, **1654**, **1656** and **1658** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1659** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[0247] The input shaft **17** is continuously connected with the sun gear member **1622**, and the output shaft **19** is continuously connected with the ring gear member **1634**. The sun gear member **1642** is continuously connected with the transmission housing **1660**. The planet carrier assembly member **1636** is continuously connected with the planet carrier assembly member **1646** through the interconnecting member **1670**.

[0248] The sun gear member **1622** is selectively connectable with the planet carrier assembly member **1646** through the clutch **1650**. The planet carrier assembly member **1626** is selectively connectable with the sun gear member **1632** through the clutch **1652**. The planet carrier assembly member **1626** is selectively connectable with the ring gear member **1634** through the clutch **1654**. The planet carrier assembly member **1626** is selectively connectable with the ring gear member **1644** through the clutch **1656**. The ring gear member **1624** is selectively connectable with the sun gear member **1632** through the clutch **1658**. The planet carrier assembly member **1646** is selectively connectable with the transmission housing **166**o through the brake **1659**.

[0249] The truth table shown in **FIG. 17***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and the seven forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 17***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 17***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1620**; the R2/S2 value is the tooth ratio for the planetary gear set **1630**; and the R3/S3 value is the tooth ratio for the planetary gear set **1640**. Also given in **FIG. 17***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[0250] Those skilled in the art will recognize that the numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1630**. The numerical values of the first and second forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1620** and **1630**. The numerical values of the third and fifth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1620**, **1630** and **1640**. The numerical values of the fourth and sixth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1630** and **1640**. The numerical value of the seventh forward speed ratio is 1. The numerical value of the eighth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1640**.

[0251] A powertrain **1710**, shown in **FIG. 18***a*, includes the conventional engine and torque converter **12**, a planetary transmission **1714**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1714** through the input shaft **17**. The planetary transmission **1714** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **1714** includes a planetary gear arrangement **1718** that has a first planetary gear set **1720**, a second planetary gear set **1730**, and a third planetary gear set **1740**.

[0252] The planetary gear set **1720** includes a sun gear member **1722**, a ring gear member **1724**, and a planet carrier assembly **1726**. The planet carrier assembly **1726** includes a

plurality of pinion gears **1727** rotatably mounted on a carrier member **1729** and disposed in meshing relationship with both the sun gear member **1722** and the ring gear member **1724**.

[**0253**] The planetary gear set **1730** includes a sun gear member **1732**, a ring gear member **1734**, and a planet carrier assembly member **1736**. The planet carrier assembly member **1736** includes a plurality of pinion gears **1737** rotatably mounted on a carrier member **1739** and disposed in meshing relationship with both the sun gear member **1732** and the ring gear member **1734**.

[**0254**] The planetary gear set **1740** includes a sun gear member **1742**, a ring gear member **1744**, and a planet carrier assembly member **1746**. The planet carrier assembly member **1746** includes a plurality of pinion gears **1747** rotatably mounted on a carrier member **1749** and disposed in meshing relationship with both the sun gear member **1742** and the ring gear member **1744**.

[**0255**] The planetary gear arrangement **1718** also includes six torque transmitting mechanisms **1750**, **1752**, **1754**, **1756**, **1758** and **1759**. The torque-transmitting mechanisms **1750**, **1752**, **1754**, **1756** and **1758** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1759** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0256**] The input shaft **17** is continuously connected with the sun gear member **1722**, and the output shaft **19** is continuously connected with the ring gear member **1734**. The sun gear member **1742** is continuously connected with the transmission housing **1760**. The sun gear member **1732** is continuously connected with the ring gear member **1744** through the interconnecting member **1770**.

[**0257**] The sun gear member **1722** is selectively connectable with the planet carrier assembly member **1736** through the clutch **1750**. The ring gear member **1724** is selectively connectable with the ring gear member **1744** through the clutch **1752**. The ring gear member **1724** is selectively connectable with the planet carrier assembly member **1746** through the clutch **1754**. The planet carrier assembly member **1726** is selectively connectable with the sun gear member **1732** through the clutch **1756**. The planet carrier assembly member **1726** is selectively connectable with the planet carrier assembly member **1736** through the clutch **1758**. The planet carrier assembly member **1736** is selectively connectable with the transmission housing **1760** through the brake **1759**.

[**0258**] The truth table shown in **FIG. 18***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and the eight forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 18***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 18***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1720**; the R2/S2 value is the tooth ratio for the planetary gear set **1730**; and the R3/S3 value is the tooth ratio for the planetary gear set **1740**. Also given in **FIG. 18***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[**0259**] Those skilled in the art will recognize that the numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1730**. The numerical value of the first forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1720** and **1730**. The numerical values of the second, third, seventh and eighth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1720**, **1730** and **1740**. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1720** and **1740**. The numerical value of the fifth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1730** and **1740**. The numerical value of the sixth forward speed ratio is 1.

[**0260**] A powertrain **1810**, shown in **FIG. 19***a*, includes the conventional engine and torque converter **12**, a planetary transmission **1814**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1814** through the input shaft **17**. The planetary transmission **1814** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **1814** includes a planetary gear arrangement **1818** that has a first planetary gear set **1820**, a second planetary gear set **1830**, and a third planetary gear set **1840**.

[**0261**] The planetary gear set **1820** includes a sun gear member **1822**, a ring gear member **1824**, and a planet carrier assembly **1826**. The planet carrier assembly **1826** includes a plurality of pinion gears **1827** rotatably mounted on a carrier member **1829** and disposed in meshing relationship with both the sun gear member **1822** and the ring gear member **1824**.

[**0262**] The planetary gear set **1830** includes a sun gear member **1832**, a ring gear member **1834**, and a planet carrier assembly member **1836**. The planet carrier assembly member **1836** includes a plurality of pinion gears **1837** rotatably mounted on a carrier member **1839** and disposed in meshing relationship with both the sun gear member **1832** and the ring gear member **1834**.

[**0263**] The planetary gear set **1840** includes a sun gear member **1842**, a ring gear member **1844**, and a planet carrier assembly member **1846**. The planet carrier assembly member **1846** includes a plurality of pinion gears **1847** rotatably mounted on a carrier member **1849** and disposed in meshing relationship with both the sun gear member **1842** and the ring gear member **1844**.

[**0264**] The planetary gear arrangement **1818** also includes six torque transmitting mechanisms **1850**, **1852**, **1854**, **1856**, **1858** and **1859**. The torque-transmitting mechanisms **1850**, **1852**, **1854**, **1856** and **1858** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1859** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[**0265**] The input shaft **17** is continuously connected with the sun gear member **1822**, and the output shaft **19** is continuously connected with the ring gear member **1834**. The sun gear member **1842** is continuously connected with the transmission housing **1860**. The sun gear member **1832** is continuously connected with the ring gear member **1844** through the interconnecting member **1870**.

[0266] The sun gear member **1822** is selectively connectable with the planet carrier assembly member **1836** through the clutch **1850**. The planet carrier assembly member **1826** is selectively connectable with the planet carrier assembly member **1836** through the clutch **1852**. The ring gear member **1824** is selectively connectable with the sun gear member **1832** through the clutch **1854**. The ring gear member **1824** is selectively connectable with the planet carrier assembly member **1846** through the clutch **1856**. The planet carrier assembly member **1836** is selectively connectable with the planet carrier assembly member **1846** through the clutch **1858**. The planet carrier assembly member **1826** is selectively connectable with the transmission housing **1860** through the brake **1859**.

[0267] The truth table shown in **FIG. 19***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and the nine forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 19***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 19***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1820**; the R2/S2 value is the tooth ratio for the planetary gear set **1830**; and the R3/S3 value is the tooth ratio for the planetary gear set **1840**. Also given in **FIG. 19***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[0268] Those skilled in the art will recognize that the numerical values of the reverse, second, eighth and ninth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1820**, **1830** and **1840**. The numerical values of the first, third and seventh forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1820** and **1830**. The numerical value of the fourth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1830** and **1840**. The numerical value of the fifth forward speed ratio is 1. The numerical value of the sixth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1830**.

[0269] A powertrain **1910**, shown in **FIG. 20***a,* includes the conventional engine and torque converter **12**, a planetary transmission **1914**, and the conventional final drive mechanism **16**. The engine and torque converter are drivingly connected with the planetary transmission **1914** through the input shaft **17**. The planetary transmission **1914** is drivingly connected with the final drive mechanism **16** through the output shaft **19**. The planetary transmission **1914** includes a planetary gear arrangement **1918** that has a first planetary gear set **1920**, a second planetary gear set **1930**, and a third planetary gear set **1940**.

[0270] The planetary gear set **1920** includes a sun gear member **1922**, a ring gear member **1924**, and a planet carrier assembly **1926**. The planet carrier assembly **1926** includes a plurality of pinion gears **1927** rotatably mounted on a carrier member **1929** and disposed in meshing relationship with both the sun gear member **1922** and the ring gear member **1924**.

[0271] The planetary gear set **1930** includes a sun gear member **1932**, a ring gear member **1934**, and a planet carrier assembly member **1936**. The planet carrier assembly member **1936** includes a plurality of pinion gears **1937** rotatably mounted on a carrier member **1939** and disposed in meshing relationship with both the sun gear member **1932** and the ring gear member **1934**.

[0272] The planetary gear set **1940** includes a sun gear member **1942**, a ring gear member **1944**, and a planet carrier assembly member **1946**. The planet carrier assembly member **1946** includes a plurality of pinion gears **1947** rotatably mounted on a carrier member **1949** and disposed in meshing relationship with both the sun gear member **1942** and the ring gear member **1944**.

[0273] The planetary gear arrangement **1919** also includes six torque transmitting mechanisms **1950**, **1952**, **1954**, **1956**, **1958** and **1959**. The torque-transmitting mechanisms **1950**, **1952**, **1954**, **1956** and **1958** are of the rotating-type torque-transmitting mechanisms, commonly termed clutches. The torque-transmitting mechanism **1959** is a stationary-type torque-transmitting mechanism, commonly termed brake or reaction clutch.

[0274] The input shaft **17** is continuously connected with the sun gear member **1922**, and the output shaft **19** is continuously connected with the ring gear member **1934**. The sun gear member **1942** is continuously connected with the transmission housing **1960**. The sun gear member **1932** is continuously connected with the ring gear member **1944** through the interconnecting member **1970**.

[0275] The sun gear member **1922** is selectively connectable with the planet carrier assembly member **1936** through the clutch **1950**. The planet carrier assembly member **1926** is selectively connectable with the planet carrier assembly member **1936** through the clutch **1952**. The ring gear member **1924** is selectively connectable with the sun gear member **1932** through the clutch **1954**. The ring gear member **1924** is selectively connectable with the planet carrier assembly member **1946** through the clutch **1956**. The ring gear member **1934** is selectively connectable with the planet carrier assembly member **1946** through the clutch **1958**. The planet carrier assembly member **1926** is selectively connectable with the transmission housing **1960** through the brake **1959**.

[0276] The truth table shown in **FIG. 20***b* describes the engagement combinations and the engagement sequence necessary to provide the reverse drive ratio and the ten forward speed ratios. A sample of the numerical values for the ratios is also provided in the truth table of **FIG. 20***b*. These values are determined utilizing the ring gear/sun gear tooth ratios also given in **FIG. 20***b*. The R1/S1 value is the tooth ratio for the planetary gear set **1920**; the R2/S2 value is the tooth ratio for the planetary gear set **1930**; and the R3/S3 value is the tooth ratio for the planetary gear set **1940**. Also given in **FIG. 20***b* is a chart describing the step ratios between the adjacent forward speed ratios and the reverse to first forward speed ratio.

[0277] Those skilled in the art will recognize that the numerical value of the reverse speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1920**. The numerical values of the first, second and ninth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1920** and **1930**. The numerical values of the second, fourth and tenth forward speed ratios are determined utilizing the ring gear/

sun gear tooth ratios of the planetary gear sets **1920**, **1930** and **1940**. The numerical values of the fifth and sixth forward speed ratios are determined utilizing the ring gear/sun gear tooth ratios of the planetary gear sets **1930** and **1940**. The numerical value of the seventh forward speed ratio is 1. The numerical value of the eighth forward speed ratio is determined utilizing the ring gear/sun gear tooth ratio of the planetary gear set **1930**.

[**0278**] While the best modes for carrying out the invention have been described in detail, those familiar with the art to which this invention relates will recognize various alternative designs and embodiments for practicing the invention within the scope of the appended claims.

What is claimed is:

1. A family of transmissions wherein each family member comprises:

an input shaft;

an output shaft;

first, second and third planetary gear sets each having first, second and third members;

said input shaft being continuously interconnected with a member of said planetary gear sets, and said output shaft being continuously interconnected with another member of said planetary gear sets;

a first interconnecting member continuously interconnecting said first member of said first planetary gear set and said first member of said second planetary gear set;

said second member of said first planetary gear set being continuously connected with a transmission housing;

a first torque-transmitting mechanism selectively interconnecting a member of said first planetary gear set with a member of said second or third planetary gear set;

a second torque-transmitting mechanism selectively interconnecting a member of said second planetary gear set with a member of said first or third planetary gear set;

a third torque-transmitting mechanism selectively interconnecting a member of said third planetary gear set with a member of said first or second planetary gear set;

a fourth torque-transmitting mechanism selectively interconnecting a member of said first or second planetary gear set with another member of said first, second or third planetary gear set;

a fifth torque-transmitting mechanism selectively interconnecting a member of said first, second or third planetary gear set with another member of said second or third planetary gear set, or with said transmission housing; and

a sixth torque-transmitting mechanism selectively interconnecting a member of the first, second or third planetary gear set with another member of said first or third planetary gear set, or with said transmission housing;

said torque-transmitting mechanisms being engaged in combinations of three to establish at least seven forward speed ratios and a reverse speed ratio between said input shaft and said output shaft.

2. The family of transmissions defined in claim 1, wherein said first, second, third, fourth and fifth torque-transmitting mechanisms comprise clutches, and said sixth torque-transmitting mechanism comprises a brake.

3. The family of transmissions defined in claim 1, wherein said first, second, third and fourth torque-transmitting mechanisms comprise clutches, and said fifth and sixth torque-transmitting mechanisms comprise brakes.

4. The family of transmissions defined in claim 1, wherein planet carrier assembly members of each of said planetary gear sets are of the single-pinion type.

5. The family of transmissions defined in claim 1, wherein at least one planet carrier assembly member of said planetary gear sets is of the double-pinion type.

6. A family of transmissions having a plurality of family members wherein each family member comprises:

an input shaft;

an output shaft;

a planetary gear arrangement having first, second and third planetary gear sets, each planetary gear set having first, second and third members;

said input shaft being continuously interconnected with a member of said planetary gear sets, and said output shaft being continuously interconnected with another member of said planetary gear sets;

a first interconnecting member continuously interconnecting said first member of said first planetary gear set and said first member of said second planetary gear set;

said second member of said first planetary gear set being continuously connected with a transmission housing; and

six torque-transmitting mechanisms for selectively interconnecting said members of said first, second or third planetary gear sets with said transmission housing or with other members of said planetary gear sets, said six torque-transmitting mechanisms being engaged in combinations of three to establish at least seven forward speed ratios and one reverse speed ratio between said input shaft and said output shaft.

7. The family of transmissions defined in claim 6, wherein a first of said six torque-transmitting mechanisms is operable for selectively interconnecting a member of said first planetary gear set with a member of said second or third planetary gear set.

8. The family of transmissions defined in claim 6, wherein a second of said six torque-transmitting mechanisms is operable for selectively interconnecting a member of said second planetary gear set with a member of said first or third planetary gear set.

9. The family of transmissions defined in claim 6, wherein a third of said six torque-transmitting mechanisms is selectively operable for interconnecting a member of said third planetary gear set with a member of said first or second planetary gear set.

10. The family of transmissions defined in claim 6, wherein a fourth of said six torque-transmitting mechanisms is selectively operable for interconnecting a member of said first or second planetary gear set with another member of said first, second or third planetary gear set.

11. The family of transmissions defined in claim 6, wherein a fifth of said six torque-transmitting mechanisms is

selectively operable for interconnecting a member of said first, second or third planetary gear set with another member of said second or third planetary gear set, or with said transmission housing.

12. The family of transmissions defined in claim 6, wherein a sixth of said six torque-transmitting mechanisms selectively interconnects a member of said first, second or third planetary gear set with another member of said first or third planetary gear set, or with said transmission housing.

13. The family of transmissions defined in claim 6, wherein a sixth of said six torque-transmitting mechanisms selectively interconnects a member said first, second or third planetary gear set with said transmission housing.

14. The family of transmissions in claim 6, wherein planet carrier assembly members of each of said planetary gear sets are of the single-pinion type.

15. The family of transmissions in claim 6, wherein at least one planet carrier assembly member of said planetary gear sets is of the double-pinion type.

* * * * *