


US 20040138786A1

(19) **United States**(12) **Patent Application Publication**
Blackett et al.(10) **Pub. No.: US 2004/0138786 A1**(43) **Pub. Date: Jul. 15, 2004**(54) **METHOD AND SYSTEM FOR MASTER
SLAVE PROTOCOL COMMUNICATION IN
AN INTELLIGENT ELECTRONIC DEVICE****Publication Classification**(51) **Int. Cl.⁷ G05D 17/00**(52) **U.S. Cl. 700/295**(75) Inventors: **Andrew W. Blackett**, Victoria (CA);
Bryan J. Gilbert, Victoria (CA);
Martin A. Hancock, Victoria (CA)(57) **ABSTRACT**

Correspondence Address:

BRINKS HOFER GILSON & LIONE
P.O. BOX 10395
CHICAGO, IL 60610 (US)(73) Assignee: **Power Measurement, Ltd.**(21) Appl. No.: **10/024,896**(22) Filed: **Dec. 17, 2001****Related U.S. Application Data**(63) Continuation-in-part of application No. 09/723,564,
filed on Nov. 28, 2000.

A power management architecture for an electrical power distribution system, or portion thereof, is disclosed. The architecture includes intelligent electronic devices ("IED's") with the capability to monitor and control attached slave devices, and provide capability to communicate between multiple devices in a variety of communication protocols. A master IED in the master/slave architecture performs power management functions on the data received from the slave IED's. Further, the IED's with master functionality provide web server capabilities, allowing a user to view processed data over an open Internet protocol, such as HTTP ("Hyper Text Transfer Protocol").






Figure 1a




Figure 1b




Figure 1c




Figure 1d




Figure 1e




Figure 2




Figure 3




Figure 4a




Figure 4b




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9

METHOD AND SYSTEM FOR MASTER SLAVE PROTOCOL COMMUNICATION IN AN INTELLIGENT ELECTRONIC DEVICE

RELATED APPLICATIONS

[0001] This application is a continuation-in-part under 37 C.F.R. § 1.53(b) of U.S. patent application Ser. No. 09/723, 564, entitled "INTRA-DEVICE COMMUNICATIONS ARCHITECTURE FOR MANAGING ELECTRICAL POWER DISTRIBUTION AND CONSUMPTION", filed Nov. 28, 2000 (Attorney Docket No. 6270/48) now U.S. Pat. No. _____, the entire disclosure of which is hereby incorporated by reference.

BACKGROUND

[0002] The monitoring of electric parameters, such as current, voltage, energy, power, etc., and particularly the measuring and calculating of electric parameters, provides valuable information for power utilities and their customers. Monitoring electric power is important to ensure that the electric power is effectively and efficiently generated, distributed and utilized. Knowledge about power parameters such as volts, amps, watts, phase relationship between waveforms, KWH, KVAR, KVARH, KVA, KVAH, power factor, frequency, etc., is a concern for utilities and industrial power users. In addition, monitoring electricity can be used for control and protection purposes.

[0003] Many metering functions in a power distribution system require concurrent knowledge of the states of multiple circuits or devices in the system to be communicated to a central command and control entity in order to work efficiently and effectively. However, a given power system rarely contains equipment from just one, or even just two, manufacturers. Within the power distribution or monitoring system, the various devices are often provided by multiple manufacturers and are configured to communicate with multiple different protocols.

[0004] Further, current metering devices in use are typically legacy or slave devices which are difficult to interface with and retrieve data from. These devices often require proprietary or custom software running on a central server or computer and thus data retrieval can often be complex or costly. In addition, such slave devices, as well as legacy devices, lack the advanced hardware or software, as well as the capability to be upgraded, to communicate in a modern client/server environment and interact using the open and non-proprietary protocols widely in use today.

[0005] Accordingly, there is a need to provide a system that overcomes the disadvantages of the prior art by integrating and consolidating the operations, communications and interactions of an electrical distribution system including a heterogeneous suite of inter-networked electrical metering devices as well as slave devices and loads, including legacy devices, for the purposes of protection, control and/or the metering of electricity.

SUMMARY

[0006] The present invention is defined by the following claims, and nothing in this section should be taken as a limitation on those claims. By way of introduction, the preferred embodiments described below relate to an electrical

distribution system architecture of electrical metering devices which are interconnected on a network. The metering devices further include capability to monitor and control attached slave devices, and provide capability to communicate between multiple devices in a variety of communication protocols.

[0007] The energy meter includes one or more sensors which are coupled with an electric circuit, the sensors operative to sense the electrical parameters in the circuit and generate analog signals which are representative of the electrical parameters. The analog signals are converted into digital samples using an analog to digital converter and a communications port facilitates communication of the digital signals to slave devices using a first protocol. The energy meter also includes a server module which allows for communication of the digital samples onto a digital network using a second protocol. In one embodiment the first and second protocols are the same and in an alternate embodiment the conversion between the first and second protocols is done on a processor internal to the energy meter.

[0008] According to a further aspect, there is provided a system for monitoring and controlling the distribution of electrical energy in an electric circuit. The system comprises a communications bus, a digital network and a master device. The master device comprises one or more sensors which are coupled with an electric circuit. The sensors are operative to sense the electrical parameters in the circuit and generate analog signals which are representative of the electrical parameters. The analog signals are converted into digital samples using an analog to digital converter and a communications port facilitates communication of the digital signals into a first protocol. The master device also includes a server module which allows for communication of the digital samples onto the digital network using a second protocol. The conversion between the first and second protocols is done on a processor internal to the master device. According to a further aspect, the system also includes the slave device.

[0009] Further aspects and advantages of the invention are discussed below in conjunction with preferred embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1a illustrates the block diagram of a Modbus RTU packet;

[0011] FIG. 1b illustrates the block diagram of an DNP packet;

[0012] FIG. 1c illustrates the block diagram of a the Header frame within a DNP packet;

[0013] FIG. 1d illustrates the block diagram of an ION packet;

[0014] FIG. 1e illustrates the block diagram of an Ethernet packet;

[0015] FIG. 2 illustrates an IED connected to a network, a slave device and a power system;

[0016] FIG. 3 illustrates an block diagram of the preferred embodiment;

[0017] FIG. 4a illustrates an IED block diagram of the hardware of the preferred embodiment.

[0018] FIG. 4b illustrates an IED connected to a power system;

[0019] FIG. 5 illustrates a master IED coupled with several slave devices and a viewing device attached to one network;

[0020] FIG. 6 illustrates a master IED coupled with several slave devices and a viewing device attached to a separate network;

[0021] FIG. 7 illustrates a master IED coupled with multiple networks, each network having its own protocol;

[0022] FIG. 8 illustrates a preferred embodiment with a master IED coupled to multiple networks, the master IED providing protocol translation or conversion between the networks;

[0023] FIG. 9 illustrates a preferred embodiment of a device with both master/slave functionality.

DETAILED DESCRIPTION

[0024] Intelligent electronic devices ("IED's") such as programmable logic controllers ("PLC's"), Remote Terminal Units ("RTU's"), electric/watt hour meters, protection relays or fault recorders are available that make use of memory and microprocessors to provide increased versatility and additional functionality. Such functionality includes the ability to communicate with remote computing systems, either via a direct connection or via a network. In particular, the monitoring of electrical power, especially the measuring and calculating of electrical/power system parameters, provides valuable information for power utilities and their customers. The monitoring of electrical power is important to ensure that the electrical power is effectively and efficiently generated, distributed and utilized. Various different arrangements are available for monitoring, measuring, and controlling power system parameters.

[0025] Typically, an IED, such as an individual power measuring device, is placed on a given branch or line proximate to one or more loads which are coupled with the branch or line in order to measure, monitor or control power system parameters. Herein, the phrase "coupled with" is defined to mean directly connected to or indirectly connected through one or more intermediate components. Such intermediate components may include both hardware and software based components. In addition to monitoring power parameters of a certain load(s), such power monitoring devices have a variety of other applications, such as control applications. For example, power monitoring devices can be used in supervisory control and data acquisition ("SCADA") systems such as the XA/21 Energy Management System manufactured by GE Harris Energy Control Systems located in Melbourne, Fla.

[0026] In a typical SCADA application, IED's or other power monitoring devices individually dial-in to a central SCADA computer system via a modem. These dial in systems are often "stand alone" and require a secondary device, such as a dedicated computer, to send data in a predefined, typically proprietary, protocol. The resulting SCADA data is typically not easily/readily accessible by an external user using off the shelf computers. The ability to use an open, non-proprietary computer network infrastructure, such as the Internet, allows for the use of power parameter

and data transmission and reporting on a large scale utilizing standard, open and non-proprietary protocols. The Internet provides a connectionless point-to-point communications medium that is capable of supporting standard protocols which are available in virtually every computer connected to the Internet.

[0027] As used herein, Intelligent electronic devices ("IED's") include Programmable Logic Controllers ("PLC's"), Remote Terminal Units ("RTU's"), electric power meters, protective relays, fault recorders or other devices which are coupled with power distribution networks to manage and control the distribution and consumption of electrical power. Such devices typically utilize memory and microprocessors executing software to implement one or more desired power management functions. IED's include on-site devices coupled with particular loads or portions of an electrical distribution system and are used to monitor and manage power generation, distribution and consumption. IED's are also referred herein as power management devices ("PMD's").

[0028] A Remote Terminal Unit ("RTU") is a field device installed on an electrical power distribution system at the desired point of metering. It is equipped with input channels (for sensing or metering), output channels (for control, indication or alarms) and a communications port. Metered information is typically available through a communication protocol via a serial communication port. An exemplary RTU is the XP Series, manufactured by Quindar Productions Ltd. in Mississauga, Ontario, Canada.

[0029] A Programmable Logic Controller ("PLC") is a solid-state control system that has a user-programmable memory for storage of instructions to implement specific functions such as Input/Output (I/O) control, logic, timing, counting, report generation, communication, arithmetic, and data file manipulation. A PLC consists of a central processor, I/O interface, and memory. A PLC is designed as an industrial control system. An exemplary PLC is the SLC 500 Series, manufactured by Allen-Bradley in Milwaukee, Wis.

[0030] A meter is a device that records and measures power events, power quality, current, voltage waveforms, harmonics, transients and other power disturbances, in addition to measuring the amount of electrical power delivered/consumed. Revenue accurate meters ("revenue meters") relate to revenue accuracy electrical power metering devices with the ability to detect, monitor, report, quantify and communicate power quality information, as well as revenue accurate information, about the power which they are metering. An exemplary meter is the model 8500 meter, manufactured by Power Measurement Ltd, in Saanichton, B.C. Canada.

[0031] A protective relay is an electrical device that is designed to interpret input conditions in a prescribed manner, and after specified conditions are met, to cause contact operation or similar abrupt change in associated electric circuits. A relay may consist of several relay units, each responsive to a specified input, with the combination of units providing the desired overall performance characteristics of the relay. Inputs are usually electric but may be mechanical, thermal or otherwise, or a combination thereof. An exemplary relay is the type N and KC, manufactured by ABB in Raleigh, N.C.

[0032] A fault recorder is a device that records the waveform and digital inputs, such as breaker status which result

from a fault in a line, such as a fault caused by a break in the line. An exemplary fault recorder is the IDM, manufactured by Hathaway Corp in Littleton, Colo.

[0033] IED's can also be created from existing/legacy electromechanical meters or solid-state devices by the addition of a monitoring and control device which converts the mechanical output, such as the rotation of the rotary counter, or pulse output into electrical pulses/digital data. An exemplary electromechanical meter is the AB1 Meter manufactured by ABB in Raleigh, N.C. Such conversion devices are known in the art. Herein, legacy refers to devices or platforms inherited from technology earlier than current technology.

[0034] A system and way are disclosed herein that can bridge the gap between modern and legacy networks and protocols and expand the capability of the aforementioned devices and their proprietary communication protocols and solutions. The disclosed embodiments relate to a communications architecture that can be used for monitoring, protection and control of devices and electrical power distribution in an electrical power distribution system, where master IED's interact with other slave IED's and attached devices, legacy or otherwise, and provide measured or computed data over a network. These master IED's, which typically have IED capabilities as well, offer both a connection between modern and legacy network protocols as well as server capabilities. Further, server capabilities include web, HTTP, FTP, NNTP, instant messaging, email and other network based servers. The server capabilities will be described in detail below. Also described in more detail below is a power management architecture for an electrical power distribution system, or portion thereof. The architecture is also described in the above captioned related application. The architecture provides a medium for a master device to communicate with several slave or peer devices and provide data, formatted or otherwise, retrieved therefrom, via alternate readily accessible formats and protocols.

[0035] Further, the architecture allows for a master IED to operate or manage the distribution and consumption of electrical power of devices through one or more intermediate slave devices. This architecture is created with IED's distributed throughout the power distribution system to monitor and control the flow of electrical power. IED's may be positioned along the supplier's distribution path and/or within a customer's internal distribution system. IED's include revenue electric watt-hour meters, protection relays, programmable logic controllers, remote terminal units, fault recorders and other devices, as described above, used to monitor and/or control electrical power distribution, generation, transmission and consumption. As was noted, IED's also include legacy mechanical or electromechanical devices which have been retrofitted with appropriate hardware and/or software so as to be able to integrate with the power management architecture.

[0036] Typically, an IED is associated with a particular load or set of loads which are drawing electrical power from the power distribution system. As was described above, the IED may also be capable of receiving data from or sending data to its associated load for the purposes of monitoring and control. Depending on the type of IED and the type of load the IED may be associated with, the IED implements/performs one or more power management functions such as

measuring power consumption, controlling power distribution such as a relay function, monitoring power quality, measuring power parameters such as phasor components, voltage or current, controlling power generation facilities, scaling values or combinations thereof. For functions which produce data or other results, the IED can push the data onto the network to another IED, central server, or web browser client, automatically or event driven, or the IED can wait for a polling communication which requests that the data be transmitted to the requester. A power management function is typically a self-contained function capable of being performed or directed by a single IED.

[0037] In addition, the IED is also capable of implementing an application component of a power management application or module utilizing the architecture. As further described below, a power management application includes components which are implemented on different portions of the power management architecture and communicate with one another via the architecture network. The operation of the power management application components and their interactions/communications implement the power management application. One or more power management applications may be utilizing the architecture at any given time and therefore, the IED may implement one or more power management application components at any given time. An exemplary power management application may be a system wide billing application which collects usage information from multiple locations throughout the power distribution system and aggregates the total usage for the purposes of billing the consumer. In this example, an application component to collect usage from an individual location and transmit it to a central billing server may be operating on each IED while another application component which collects and aggregates the usage information may be executing on the central billing server. The combination of these application components implements the overall billing application.

[0038] The architecture further includes a communications network. Preferably, the communication network is a publicly accessible data network such as the Internet or other network or combination of sub-networks that transmit data utilizing the transmission control protocol/Internet protocol ("TCP/IP") protocol suite. Such networks include private intranet networks, virtual private networks, extranets or combinations thereof and combinations which include the Internet. Alternatively, other communications network architectures may also be used. Each IED preferably includes the software and/or hardware necessary to facilitate communications over the communications network by the hardware and/or software which implements the power management functions and power management application components.

[0039] The hardware and/or software which facilitate network communications preferably include a communications protocol stack which provides a standard interface to which the power management functions hardware/software and power management application components hardware/software interact. As will be discussed in more detail below, in one embodiment, the communications protocol stack is a layered architecture of software components. In the preferred embodiments these layers or software components include an applications layer, a transport layer, a routing layer, a switching layer and an interface layer.

[0040] The applications layer includes the software which implements power management functions and the power management applications components. Further, the applications layer also includes the communication software applications which support the available methods of network communications. Typically, power management function software interacts with power management hardware to monitor and/or control the portion of the power distribution system and/or the load coupled with the IED. The application component further interacts with the power management function software to control the power management function or process data monitored by the power management function. One or both of the power management function software and the power management application component software interacts with the communication software applications in order to communicate over the network with other devices.

[0041] The communications software applications include electronic mail client applications such as applications which support SMTP, MIME or POP network communications protocols, security client applications such as encryption/decryption or authentication applications such as secure-HTTP or secure sockets layer ("SSL"), or other clients which support standard network communications protocols such as telnet, hypertext transfer protocol ("HTTP"), file transfer protocol ("FTP"), network news transfer protocol ("NNTP"), instant messaging client applications, or combinations thereof. Other client application protocols include extensible markup language ("XML") client protocol and associated protocols such as Simple Object Access Protocol ("SOAP"). Further, the communications software applications may also include client software applications which support peer to peer or instant messaging based communications. All of the communications software applications preferably include the ability to communicate via the security client software applications to secure the communications transmitted via the network from unauthorized access and to ensure that received communications are authentic, not compromised and received by the intended recipient. Further, the communications software applications include the ability for redundant operation through the use of one or more interface layer components, error detection and correction and the ability to communicate through firewalls or similar private network protection devices.

[0042] The communication software applications further include support for master protocols, also known as a master/slave protocols, which use a master device or application to control a network of slave devices. A master/slave protocol interaction typically involves the master initiating transactions and the slaves responding with the requested data or action. Slave devices are both legacy and modern devices which typically do not have their own capability to communicate on the power management architecture. However, it can be appreciated that a slave device may also be another IED, such as an energy meter, with the capability to communicate on the power management architecture, but which operates in a slave mode. A device with master functionality is utilized to connect with slave devices for several reasons. Master devices are utilized for providing a primary operator interface and managing overall system functions, collecting and analyzing data and initiating control actions to slave devices. Many slave devices may be legacy devices which may be only capable of monitoring

their equipment, not controlling or performing functions in reaction to the measured data. Further, device cost, which may include equipment downtime or added maintenance, may deter an individual from replacing a legacy device with an alternate device or installing higher-cost master devices at every location. It therefore may be more feasible, from both a cost and functionality point, to control the slave devices or legacy device and their associated equipment with a master device. Additionally, a master device may be utilized to control several slave devices within a system. For example a user may want to monitor the usage of separate devices and aggregate the load usage. Connecting the two slave devices to a master device can offer this functionality.

[0043] Further, master device functionality offers several advantages, such as improved network response speed, particularly over an Ethernet connection. The response time to a master device request is typically faster because the master device typically has the data requested available, having already retrieved it from the slave device. This reduces the network latency added by having to communicate all the way to the slave device. This also offers improved network scalability by reducing the load on centralized applications because each master device becomes responsible for polling its network of slave devices and providing the concentrated and/or aggregated data rather than having a centralized application responsible for polling every device on the network. Further, by providing intermediate data concentration and/or aggregation points with the master devices, overall Ethernet network bandwidth is reduced. The improved network response further offers improved security because master devices can poll slave devices in a particular period of time, as well as there are fewer expected communication timeouts in the slave devices with the reduced response time. Additionally, functions performed on the master device reduce network traffic. Further, master device functionality offers improved timing for display of data associated with slave devices. Master devices which offer the ability to make command and control decisions remove the time delay associated with transport of the data to a secondary or intermediate device. Further, master device functionality removes a failure point in the data logging. Further, the master device functionality allows for improved command and control by allowing the meter to directly control without the need to communicate over Ethernet.

[0044] Master protocols include industrial networking protocols such as Modbus RTU or other Modbus protocols such as Modbus Plus, Modbus TCP or Modbus ASCII, all developed and available from Modicon Corporation, now Schneider Electric, located in Andover, Mass. The Modbus protocol is an open and published protocol that requires a royalty-free license, which is widely used to establish communication between intelligent devices. Modbus generally defines a message structure that controllers recognize and use regardless of the type of network they communicate over. The Modbus messaging structure is independent of the physical layer, i.e. network hardware, and is commonly implemented using RS232, RS422 or RS485 serial protocols. Modicon® devices using Modbus RTU can communicate with each other and with any other devices over a variety of networks, such as an Ethernet or RS485 network.

[0045] The Modbus network, as defined by the protocol, is a single master, multi-drop (more than one device) system

that supports up to 247 slave devices. Other examples of master protocols include Integrated Object Network (“ION”), Distributed Network Protocol (“DNP”), Lonworks, BACnet, Profibus or IEC 870 standard protocols. These master/slave protocols enable devices to communicate with each other and with other devices over a variety of networks. The master/slave protocol can also be applied in the peer-to-peer architecture where one device requests information from another peer.

[0046] All of these protocols define a message structure, i.e. a data format consisting of a defined ordering of binary data, and rules for communication interaction that controllers recognize and use regardless of the type of network they communicate over. These protocols are media independent. It will be appreciated by one skilled in the art that a master protocol can be transmitted over TCP/IP by wrapping/encapsulating it in the appropriate manner, however a master protocol master can also communicate directly over a particular media without using TCP/IP. For example, a ION protocol can be transmitted over a RS232 connection without the additional need for protocol wrapping.

[0047] Modbus master devices, also referred to as master devices, are usually software programs executing on computer workstations, such as Distributed Control Systems (“DCS”). Modbus master devices can also be devices such as Remote Terminal Units. Modbus slave devices are devices such as Programmable Logic Controllers, I/O monitoring devices, relays and meters. Software programs executing on computer workstations can also act as slave devices. A Modbus message sent from a master to a slave contains the address of the slave, a command, the requisite data and an error checksum (cyclic redundancy check (“CRC”)).

[0048] Modbus comes in variants, the most common of which are Modbus RTU, Modbus ASCII, Modbus Plus and Modbus/TCP. Modbus RTU (binary) and Modbus ASCII are the two basic forms of the Modbus protocol. The ASCII form transmits each 8 bit byte using two ASCII characters from the ASCII character set (‘0-9’ and ‘A-F’). The RTU form transmits all bytes in binary format, i.e. each byte is transmitted as 2 four bit hexadecimal characters making the protocol faster and more efficient. Both forms utilize the serial RS-232/RS-485 protocols as the networking medium. Known limitations of these serial protocols, such as limited inter-device distances, have reduced the effectiveness of the Modbus RTU and ASCII protocols in modern industrial networking. Modbus Plus is a Modicon® proprietary protocol used in industrial networking systems. It uses token-passing peer-to-peer communications over a proprietary networking medium at data transfer rates of one megabit per second (high-speed passing of groups of bits within a layer). Typically the network medium is a shielded twisted-pair cable. The structure of Modbus/TCP is similar to the Modbus RTU packet except that it has an extra six-byte header and does not use the cyclic redundancy check (“CRC”). Modbus/TCP defines the packet structure and connection port for the industry standard TCP/IP protocol. Modbus/TCP retains the Modbus RTU limit of 256 bytes to a packet. A protocol variant referred to as Enhanced Modbus/TCP removes this limitation to allow a higher throughput is also utilized.

[0049] FIG. 1a illustrates a block diagram of a Modbus RTU Packet. The Modbus data packet 100 includes an

ADDRESS field 104, a FUNCTION code field 106, a DATA field 108 and a cyclic redundancy check (“CRC”) field 112. The ADDRESS field 104 contains either two characters (Modbus ASCII) or eight bits (Modbus RTU). An assigned slave device address is in the range of 1-247 decimal. A master addresses a slave by placing the slave address in the field of the message. When a slave responds it places its own address in the address field to let the master know which slave is responding.

[0050] The FUNCTION code field 106 contains either two characters (Modbus ASCII) or eight bits (Modbus RTU). Valid function codes are in the range of 1-255 decimal, each code in the range referring to an action the slave is to perform. Conversely, when the slave responds to the master, the function code field is utilized to indicate either a normal or error response. In operation the normal response echo’s the original function code except that the error response, also referred to as the exception response, returns a code that is equivalent to the function code with it’s most significant bit set to a logic 1.

[0051] The DATA field 108 is constructed using a set of two hexadecimal digits in the range of 00 to FF hex. Depending on the protocol variant, i.e. ASCII or RTU, they can be made from a pair of ASCII characters or from one RTU character. Typically the data field 108 is 16 bits in length for a RTU character but alternately the data field 108 can be zero length, or non-existent. For example the function code alone may specify the action and the slave does not require any additional data or information.

[0052] The Distributed Network Protocol (“DNP”) is an open SCADA protocol which is used for communications and interoperability among substation computers, IED’s and Master Stations. Originally developed by Harris, Distributed Automation Products in 1993, ownership has been given to the DNP3 Users Group, a group composed of utilities and vendors who are utilizing the protocol. Harris Distributed Automation is located in Melbourne, Fla. DNP is used for substation automation such as reclosing schemes automation, adaptive relaying, capacitor bank control, auto load transfer and bus tie control. DNP is not a general purpose protocol for transmitting hypertext, multimedia or huge files. DNP Version 3.0, or DNP3, is structured similarly to the Modbus protocol. The basic structure of a DNP3 packet is shown in FIG. 1b and contains a header frame 114 and a data frame 118. The header frame 114 structure is shown in FIG. 1c and includes a SYNC field 120, a length field 122, a link control field 124, a destination address 126, a source address 128 and a error check sum (“CRC”) 130.

[0053] The SYNC frame 120 is two bytes and helps the receivers determine where the frame begins. The LENGTH 122 specifies the number of octets in the remainder of the frame, not including the CRC check octets 130. The LINK CONTROL octet 124 is used between sending and receiving link layers to coordinate their activities. A DESTINATION ADDRESS 126 specifies which DNP device should process the data and the SOURCE ADDRESS 128 identifies which DNP device sent the message. Every DNP device must have a unique address within the collection of devices sending and receiving messages to and from one another. As in the Modbus protocol, a CRC check provides a higher degree of assurance that communication errors are detected.

[0054] The Integrated Object Network (“ION”) protocol is another open protocol designed by Power Measurement Ltd., located in Saanichton, British Columbia. The ION packet, as shown in the block diagram in **FIG. 1d**, contains a CRC field **134**, an Application layer **136**, a Network layer **138** and a Data Link layer **140**. For reference, a block diagram of an Ethernet packet is also shown in **FIG. 1e**.

[0055] Other protocols include the International Electrical Commission 870 part 5 (“IEC 870”) protocol standard and the Building Automation and Control Network (“BACnet”) protocol. The IEC 870 protocol supports telecontrol equipment and systems with coded bit serial data transmissions for monitoring and controlling processes. The BACnet protocol is adopted and supported by the American National Standards Institute (“ANSI”) and the American Society of Heating Refrigeration and Air-Conditioning Engineers (“ASHRAE”). BACnet is a non-proprietary open protocol communication standard conceived by a consortium of building management, system users and manufactures.

[0056] As described above, the internal software of the IED includes a TCP/IP protocol stack including the transport layer, routing layer, switching layer and the interface layer. The transport layer interfaces the applications layer to the routing layer and accepts communications from the applications layer that are to be transmitted over the network. The transport layer breaks up the communications into one or more packets, augments each packet with sequencing and addressing data and hands each packet to the routing layer. Similarly, packets which are received from the network are reassembled by the transport layer and the re-constructed communications are then handed up to the applications layer and the appropriate communications application client. The transport layer also ensures that all packets which make up a given transmission are sent or received by the intended destination. Missing or damaged packets are re-requested by the transport layer from the source of the communication. In the preferred embodiment, the transport layer implements the transport control protocol (“TCP”).

[0057] The routing layer interfaces the transport layer to the switching layer. The routing layer routes each packet received from the transport layer over the network. The routing layer augments each packet with the source and destination address information. In the preferred embodiment, the routing layer implements the Internet protocol (“IP”). It will be appreciated that the TCP/IP protocols implement a connectionless packet switching network which facilitates scalable substantially simultaneous communications among multiple devices. The switching layer interfaces the routing layer to the interface layer. The switching layer and interface layer are typically integrated. The interface layer comprises the actual hardware interface to the network. The interface layer may include an Ethernet interface, a modem, such as a wired modem using the serial line interface protocol (“SLIP”) or point to point protocol (“PPP”), a wired modem which may be an analog or digital modem such as an integrated services digital network (“ISDN”) modem or digital subscriber line (“DSL”) modem, or a cellular modem. Further, other wireless interfaces, such as satellite, Bluetooth or 802.11b compliant devices, may also be used. In addition, AC power line or network power line carrier data network interface may also be used. Cellular modems further provide the functionality to determine the geographic location of the IED using cellular RF triangulation.

Such location information can be transmitted along with other power management data as one factor used in authenticating the transmitted data. In the preferred embodiments, the provided interface layer allows for redundant communication capabilities. The interface layer couples the IED with a local area network, such as provided at the customer or utility site. Alternatively, the interface layer can couple the IED with a point of presence provided by a local network provider such as an Internet service provider (“ISP”).

[0058] **FIG. 2** illustrates a system overview of a preferred embodiment and **FIG. 3** illustrates a flow diagram of how the master device makes data available to the client application. **FIG. 2** shows an exemplary IED **200** having master/slave communication capabilities. The IED **200** is coupled with a load/power system **201** for the purpose of monitoring and/or control. Further, the IED **200** is coupled with a slave device **235** via a closed/proprietary network/protocol **209** such as ION or Modbus RTU. The slave device **235** is further coupled with a load for the purpose of monitoring and/or control. The IED **200** is also coupled with an open/non-proprietary network **207** such as the Internet for the purpose of communicating with remote devices and/or applications **220**.

[0059] The IED master/slave device **200** further contains device circuitry **210** and a server module **230**. The device circuitry **210** will be described in detail later. The server module **230** contains communications capability and web server capability, and interacts with internal hardware and/or software, such as software applications, in the device circuitry **210**. It will be appreciated that there may be more than one server module **230** supporting one or more of the TCP/IP based networking protocols described above. The circuitry **210** connects with a slave device **235** over a closed network **209**, which communicates using a proprietary or closed master/slave protocol such as ION or Modbus RTU. It will be appreciated that there may be more than one circuitry **210** for connecting with more than one slave device **235** or the circuitry **210** may be capable of connecting with more than one slave device **235**. The server module **230** connects with a client application **220**, such as a web browser, over an open network **207**, which communicates using an open non-proprietary protocol such as HTTP. It will be appreciated that the server module **230** may also have the capability to connect with the slave device **235**, depending on the circuitry **210** configuration.

[0060] Referring to **FIG. 3**, in operation the slave device **235** monitors or collects data from the load **240**. The master/slave device **200** requests data from the slave device **235** over the closed protocol network **209** (block **300**). The slave device collects the data (block **305**), such as monitoring or measurement, etc., and sends the requested data to the master/slave device **200** over the closed protocol network **209** (block **310**) using a first protocol. The data is received by the device circuitry **210**, which includes a processor (not shown) which is further configured to process both data from the load/power system **201** and incoming data from slave devices (block **315**). Upon receipt of the data, a function is performed on the data (block **320**). This function may include, for example, a power management function, and will be explained in detail later on. The master/slave device **200** then converts the processed data into an open non-proprietary protocol (block **330**), com-

monly referred to as open protocols to one skilled in the art, such as HTTP. The data is then passed to the server module 230 where the server makes the new data available (block 340), for viewing, retrieval or transmission.

[0061] A client application 220, such as a web browser, can then view the data over an open protocol network 207 from the server module 230 (block 350). For example, the server module 230 may receive a request from the client application 220 to view the aggregated usage data from load 201 and load 240. The server module 230 receives and processes the request. If the data is available, the server module 230 serves it to the client application 220 via the network 207. If the data is not available, the server module 230 passes the request to the device circuitry 210. The device circuitry 210 then requests the current usage data for load 240 from the slave device 235 using the closed network 209. The slave device then responds with the requested data. The device circuitry 210 also obtains the usage data for load 201. The usage data for load 240 and 201 is then aggregated and the combined usage data is passed back to the server module 230 which then serves it to the client application 220.

[0062] In a second embodiment, a local display client 250 is provided on the master device 200 and is configured to view the data from the server module 230 using an open protocol. The local display client 250 may include a LCD display for display a graphic user interface. For example, the local display client 250 may be configured to operate Internet Explorer™, or a derivative thereof, manufactured by Microsoft Corporation, located in Redmond Wash., and thus provide the user with local viewing of the data associated with the attached slave device 235.

[0063] In a third embodiment the server module 230 is further capable of serving email, FTP file transfers, NNTP, instant messaging and building and publishing web pages. Further, a domain name system ("DNS") address for the server is also utilized. Both static and dynamic DNS service can be utilized by the server module 230.

[0064] In a fourth embodiment the Master Device receives data in a first protocol (block 310), such as ION protocol, performs a function on the data (block 320) and converts the new processed data back into the first protocol (block 335). As described above the data is then passed to the server module 230 where the server makes the new data available (block 340), for viewing, retrieval or transmission. A client application 220 can then view the data over the open protocol network 207 from the server module 230 (block 350).

[0065] Referring to FIG. 4a, a second embodiment of an IED 400 which can detect, record and report power quality events is illustrated. The second embodiment includes an energy meter and includes both hardware and software. FIG. 4a shows a typical hardware configuration where the meter 400 is connected to a three phase electric circuit 455. The meter 400 includes transducers 460 which sense the current and voltage in each phase of the electric circuit 455 and a power supply 457 which supplies power for the meter electronics. The transducers 460 are also connected to an analog to digital ("A/D") converter 462 which samples the current and voltage in each phase of the electric circuit 455. Further, the digital output of the A/D converter 462 is connected to a digital signal processor 465 ("DSP"). The

DSP 465 is connected to DSP memory 467 and to a central processing unit 470 ("CPU"). The DSP 465 in conjunction with the CPU 470 executes the power quality event detection and reporting algorithms as detailed below.

[0066] Preferred embodiment algorithms detailed below operate on signal samples as provided by the DSP 465 and CPU 470. The algorithms may operate on all samples provided or a subset of them. Typically, they operate utilizing 64 samples which represents ½ cycle. It will be appreciated however, that these computations can be performed with a greater or lesser number of samples (with the corresponding buffers adjusted accordingly), e.g. representing a quarter cycle or eighth of a cycle, down to a single sample. The processing power of the DSP 465 and CPU 470 is a limiting factor. The CPU 470, DSP 465, DSP memory 467 form part of the device circuitry 405 as is mentioned both earlier and later on.

[0067] The CPU 470 is also connected to a user interface 472 which allows users to program the meter 400 or retrieve revenue or power quality data and generally interact with the meter 400. In the preferred embodiment, the user interface 472 includes a graphical display and a keypad as well as LED, infrared and optical interfaces. It will be appreciated by those skilled in the art that the power quality detection and reporting algorithms detailed herein can be executed by a variety of hardware configurations, all of which are known in the art. It can be appreciated that further communications circuitry is coupled with the CPU 470, such as modem or Ethernet circuitry. An exemplary meter is a type 8500 manufactured by Power Measurement Ltd, located in Saanichton, B.C., Canada.

[0068] FIG. 4b illustrates a third embodiment of an IED 400 for use in a power management or control architecture. It will be appreciated that the IED 400 contains the device circuitry 405 as shown in FIG. 4a, but with additional components, as will be described later. The IED 400 is preferably coupled with a load 401 via a power distribution system 410, or portion thereof. The IED 400 includes device circuitry 405 and is further coupled with a network 407. A device, such as a computer, executing a web/HTML browser program 420, such as Internet Explorer™ is also attached to the network 407. In the preferred embodiment the web browser 420 is located on a computer, such as a personal computer having at least 32 MB memory and 1 GB hard disk with a Pentium™ or equivalent processor or better, executing the Microsoft Windows 98™ operating system and Microsoft Explorer™ or equivalent.

[0069] The device circuitry 405 includes the internal hardware and software of the device, such as the CPU 405a, memory 405c, firmware and software applications 405d, data measurement functions 405b and communications protocol stack 405e. The master communication module 406 couples the components of the device circuitry 405 of the IED 400 with the communications network 407. Alternate embodiments may have power management control functions 405b in place of or in addition to data measurement circuitry. For example, a relay may include a control device and corresponding control functions that regulate electricity flow to a load based on preset parameters. Alternatively, a revenue meter may include data measurement circuitry that logs and processes data from a connected load or other slave devices. IED's may contain one or the other or combinations

of such circuitry. In an alternate embodiment the circuitry includes phasor monitoring circuits (not shown) which comprise phasor transducers that receive analog signals representative of parameters of electricity in a circuit over the power distribution system.

[0070] The device circuitry **405** interacts with a master communications module **406** which gives the device **400** master device functionality. The master communications module **406** includes software and/or hardware which allows the device **400** to communicate using a master protocol to other slave devices (not shown) attached to the network **407** or a secondary network (not shown). The device circuitry **405** converts the master protocol communication to a format which is readable using an open internet based protocol, such as HTTP. As described above, the device circuitry **405** is configured to process the data contained within the master protocol communication format before reconfiguring the data into the second protocol. Data processing may include power management functions such as data aggregation, data scaling, measuring power consumption, controlling power distribution such as a relay function, monitoring power quality, measuring power parameters such as phasor components, voltage or current, frequency, energy, power, controlling power generation facilities, or combinations thereof. Other power management commands and functions or data processing functions are known to those skilled in the art. An exemplary device that provides such power management functions is the model 8500 meter, manufactured by Power Measurement Ltd, in Saanichton, B.C. Canada.

[0071] Further, the device circuitry **405** is also coupled with a web module **408** which performs web server functionality. A web server is a program that, using the client/server model and HTTP, serves files, which include data, from the web server to a user as web pages. Web servers also allow functionality such as serving email, instant messaging, FTP file transfers and building and publishing web pages. A client/server model describes the relationship between two connecting devices in which one program, the client, makes a request from another program, the server, which fulfills the request. The client/server model provides a way to interconnect devices and programs that are distributed across different locations. The web module's **408** server functionality further facilitates two way communications between a non-proprietary client application and the slave device. In one embodiment the web module **408** allows the device **400** to communicate using a non-proprietary protocol over the network **407**. Referring to **FIG. 4** the device **400** acts as the server and the web browser **420** acts as the client. The circuitry also allows for manipulation and/or processing of the data received from the slave devices before communication over the network with the open protocol. The open protocol is a standard communication/application layer protocol such as HTTP, SOAP or XML which is compatible with an Ethernet network protocol, such as a TCP/IP communications protocol, which is commonly utilized on a web browser **420**. It will be appreciated that other network interfaces, such as wireless networks, may be utilized.

[0072] **FIG. 5** illustrates a device **500**, including a master communications module as described above, with several slave devices **505**, **510**, **515**, all attached to a network **507**. In the preferred embodiment a master meter **500** is coupled with a network **507**, the master meter **500** having the functionality to send, receive or communicate with the slave

devices **505**, **510**, **515** using a master protocol. It will be appreciated that the slave devices **505**, **510**, **515** may be connected to corresponding loads or power systems, for example, load **516** is coupled with slave device **515**. As discussed earlier master protocols include protocols such as Modbus Master, ION, DNP, Lonworks™ or IEC 870 standard protocols. The master meter **500** is further coupled with a viewing device **520**, such as a web browser. The master meter **500** utilizes a server to communicate with the viewing device **520** using a standard viewing protocol, the viewing protocol different from the master protocol. A user may utilize the viewing device **520** which enables them to view data from a slave device **505** through the master meter **500** without requiring the ability of the viewing device **520** to communicate in the master protocol. In one embodiment the network **507** is an Ethernet network which allows the slave devices **505**, **510**, **515**, the master meter **500** and the viewing device **520** capability to communicate over a singular network.

[0073] Alternately, as shown in **FIG. 6**, the slave devices **605**, **615**, **620** and the master device **600** are connected on a single serial network **625**, such as an RS232 or RS485 network, where the devices communicate with a master protocol such as Modbus master. An Internet network **630**, such as a TCP/IP based network, allows the viewing device **620** to communicate with the master device **600**.

[0074] In operation, the master device **600** utilizes two ways of gathering data from slave devices. The first is "poll and display" where the master device **600** continuously contacts the slave devices and requests updates of their measured/sensed data. In operation the meter polls for data from the slave devices using the necessary protocol. The slave device responds and provides the requested data. The meter processes the received data and converts it to a second, more readily accessible format, such as HTML. The data is then made available via the meter's internal web server for any HTML client program to access and view. Alternately the master device **600** "polls and stores" data, also continuously contacting the slave devices to request their data and then processing and storing the processed data. Storing the processed data on the master device **600** for later retrieval reduces the need for the master device **600** to continuously post the data with its web server and allows the data to be requested or retrieved by a secondary device via the web server. It will be appreciated that retrieval of the stored data may be done via the secondary viewing device directly or done via a transmission device, such as an email server.

[0075] The second way the master device **600** facilitates the transferring of data is when it is activated by the viewing device **620**. In operation, a user operates a web browser, such as Microsoft Internet Explorer™, and requests data from the load **616** which presents data to the slave device **615**, then to the master device **600**. The data transmission is done using a master protocol and upon receipt by the master device **600**, the data is extracted from the transmission. The master device performs a function, described below, on the data and then converts the new data into a protocol viewable by the web browser, such as HTML. As described earlier a function, such as a power monitoring or measurement function, may include data aggregation, measuring power consumption, controlling power distribution such as a relay function, monitoring power quality, measuring power

parameters such as phasor components, voltage or current, controlling power generation facilities, or other computations or combinations thereof. It will also be appreciated that control commands, such as disconnect the load **616**, can be issued from the web browser **620** in a protocol or format such as XML or SOAP, which are routed to the master device **600** and converted into the master protocol in which the slave device **615** communicates. Standard web client software is onboard the master device, which is accessible by an Internet connection.

[0076] **FIG. 7** illustrates an alternate embodiment where a master device is coupled with several smaller networks, each network having its own protocol. In this embodiment the communication module on the master device **700** facilitates two way communications between the non-proprietary client application **740** and the slave device **705, 710, 715, 720**. For example, the first network **725** communicates between devices **705, 710** using a Modbus protocol and the second network **730** communicates between devices **715, 720** using the ION protocol. The master device **700** communication circuitry is coupled with the slave devices **705, 710, 715, 720** on either network **725, 730**, thereby allowing the master device **700** to send, receive or respond to data or commands sent from the slave devices. As described earlier the device circuitry converts and processes the data or commands from the proprietary protocol such as the Modbus protocol or the ION protocol, to a third common Internet network open protocol, such as HTTP. The master device's **700** web server allows the viewing device **700** to view the data over the network **735**. It will be appreciated by one skilled in the art that the data or command communication between slave devices **705, 710, 715**, the master device **735** and the viewing device **740** can be bi-directional.

[0077] In operation, the master device **700** is configured to "poll and display" data from the first network **725** and its associated slave devices **705, 710**, continuously requesting the data from the slave devices **705, 710**, processing the data and transmitting the data on a third network **735** to a users viewing device such as a web browser **740**. The second network **730**, which communicates data or commands in a different protocol from the first network **725**, is also connected to the master device **700**. The master device **700** continuously contacts the slave device **715** on the second network **730** requesting data. It will be appreciated that the master device **700** offers a user the opportunity to access data or send commands to all slave devices **705, 710, 715**, while three separate networks and three separate protocols are utilized.

[0078] The master meter **700** is further configured to respond to a slave device's data with a power management function. For example, the slave device **715** is connected to an associated load **717** and the master device **700** continuously requests the measured parameters of the load **717** which the slave device **710** is configured to measure. These parameters are, for example, current, voltage, energy, power, peak power demand, current demand, peak current demand, frequency, power factor, per phase power or power factor, reactive and apparent energy, reactive and apparent power or power reliability, or combinations thereof. A power management function may involve, for example, a test and response to one of the measured parameters or processed pieces of data or a general command or control instruction issued to a device. For example the master device **700**

continuously requests the voltage usage data of the load **717** from the slave device. The master device **700** is also configured to employ a power or energy management command or function, such as to indicate an alarm to a user and initiate a load shedding command when the measured voltage of the load exceeds a predefined level.

[0079] Other power management functions include either one or combinations of alert functions, reporting functions, load control functions, data collection functions, device management functions, billing or revenue management functions, distributed power management functions, centralized power management functions, power reliability functions, usage or consumption management functions, electrical power generation management functions, device maintenance functions, device fraud detection functions, power outage functions or power quality monitoring or measurement functions. It will be appreciated that these functions can be initiated or controlled by the master device, the master device being accessible from a viewing device, such as a web browser. In one embodiment the IED's functionality is controlled using object oriented program modules. Object oriented programming, known in the art, allows users to manipulate or perform functions or data in relation to each other. An IED utilizing object oriented programming is described in U.S. Pat. No 5,650,936.

[0080] In an alternate embodiment the master device allows protocol translation or conversion between two systems, as well as their associated devices. For example, as shown in **FIG. 8**, a master device **800**, or meter with a protocol conversion module (not shown) within the meter circuitry, is coupled with a relay **805** via the relay network **802**. The relay network **802** is a serial RS232 connection which communicates using the Modbus protocol, the master meter **800** continuously requests and receives data from the relay **805** using the Modbus protocol. A user may view the relay data in two locations. First, the master meter's protocol conversion module receives the data from the relay **805** in a Modbus protocol and converts the data into the ION protocol and communicates with the main system viewer **810**. In one embodiment the main system viewer **810** is an operating program, such as ION Enterprise™ or Pegasys™ manufactured by Power Measurement Ltd., which allows the user to both monitor and control both the master meter **800** and all associated loads or connected devices. Second, the user may view or control the data via a network **822** connection, such as an Ethernet connection, in a browser **825**. In one embodiment the master meter **800** converting the data from the Modbus protocol into a common Internet protocol such as XML or HTML. The master meter **800** also allows a secondary system viewer **850**, which communicates with an alternate protocol, such as BACnet to access the data. In one embodiment the master meter **800** processes and converts the data in the Modbus protocol on the relay network **802** to the alternate BACnet protocol in the secondary system network **860**. The secondary system is, for example, a building air conditioning system which contains air conditioner devices **855**. In an alternate embodiment the master meter **800** converts the data in the Modbus protocol on the relay network **802** to HTML, thereby allowing the browser **825** to view the data over the network **822**. The master meter **800** further converts the HTML protocol to the BACnet protocol, thereby allowing the secondary system viewer **850** access to the data or commands. Thus, the master meter **800** acts as a protocol conversion device between multiple

protocols and multiple networks while monitoring, measuring and implementing power management functions on connected devices.

[0081] It will also be appreciated that a slave device can also contain master device functionality. A device with master/slave functionality, as shown in **FIG. 9**, utilizes master functionality to aggregate and process data within sub-networks. For example, a master/slave device **955** is connected to several slave devices **945, 950** on a network **935**. Another master/slave device **905** is also connected to slave devices **910, 915, 920** within another network **930**. Both master/slave devices **905, 955** utilize master functionality, as described earlier, polling the data from the associated slave devices and performing functions, such as aggregation functions, on the data. Alternately, when the master device **900** requests data from the master/slave devices **905, 945**, the master/slave devices **905, 945** utilize slave functionality. The master device **600** is configured to poll the data from only the master/slave devices **905, 955**, thereby reducing the amount of connections and processing power that is required by the master device **900**.

[0082] It is therefore intended that the foregoing detailed description be regarded as illustrative rather than limiting, and that it be understood that it is the following claims, including all equivalents, that are intended to define the spirit and scope of this invention.

We claim:

1) An energy meter for monitoring and controlling the distribution of electrical energy, said meter comprising:

at least one sensor coupled with an electric circuit and operative to sense at least one electrical parameter in said electric circuit and generate at least one analog signal indicative thereof;

at least one analog to digital converter coupled with said sensor and operative to convert said analog signal to at least one first digital signal;

a communications port operative to facilitate communications of at least one second digital signal between said energy meter and a slave device coupled with said energy meter using a first protocol;

a processor coupled with said analog to digital converter and further coupled with said communications port, said processor operative to perform a power management function on said at least one second digital signal and generate an output result; and

a server module coupled with said processor and operative to facilitate communication of said output result to a client application over a digital network using a second protocol.

2) The energy meter of claim 1 wherein said first protocol comprises a master protocol.

3) The energy meter of claim 2 wherein said master protocol comprises the Modbus RTU protocol.

4) The energy meter of claim 2 wherein said master protocol comprises ION protocol.

5) The energy meter of claim 2 wherein said master protocol comprises distributed networking protocol ("DNP").

6) The energy meter of claim 1 wherein said second protocol comprises a hyper text transfer protocol ("HTTP") based protocol.

7) The energy meter of claim 6 wherein said HTTP based protocol comprises hypertext markup language ("HTML").

8) The energy meter of claim 6 wherein said HTTP based protocol comprises extensible markup language ("XML").

9) The energy meter of claim 6 wherein said HTTP based protocol comprises simple mail transport protocol ("SMTP").

10) The energy meter of claim 1 wherein said first protocol and said second protocol comprise substantially similar protocols.

11) The energy meter of claim 1 wherein said digital network comprises an Ethernet network.

12) The energy meter of claim 1 wherein said digital network comprises a wireless network.

13) The energy meter of claim 1 wherein said energy meter comprises at least one object oriented program module.

14) The energy meter of claim 1 wherein said meter is operative to request first digital data from said slave device, said slave device operative to provide said first digital data upon request.

15) The energy meter of claim 13 wherein said meter is further operative to request second digital data from at least a second slave device coupled with said meter, said second slave device being operative to provide said second digital data upon request.

16) The energy meter of claim 1 wherein said at least one second digital signal comprises digital data generated by said slave device.

17) A system for monitoring and controlling the distribution of electrical energy in an electric circuit, said system comprising:

(a) a first digital network comprising a first protocol;

(b) a second digital network comprising a second protocol different from said first protocol;

(c) a first slave device coupled with said first digital network, said first slave device operative to facilitate communication of digital data onto said first digital network using said first protocol;

(d) a master device coupled with said first digital network and said second digital network and further comprising:

(i) at least one sensor coupled with said electric circuit and operative to sense at least one electrical parameter in said electric circuit and generate at least one analog signal indicative thereof;

(ii) at least one analog to digital converter coupled with said sensor and operative to convert said at least one analog signal to a digital signal representative thereof;

(iii) a communications port operative to couple said master device with said first digital network and to facilitate receipt of said digital data from said first digital network using said first protocol;

(iv) a processor coupled with said analog to digital converter and further coupled with said communications port, said processor operative to perform a power management function on said digital data and generate an output result therefrom; and

(v) a server module coupled with said processor and operative to facilitate communication of said output result over said second digital network using said second protocol.

18) The system of claim 17 further comprising a second slave device coupled with said first digital network and further operative to communicate with said master device using said first protocol.

19) The system of claim 18 wherein said master device receives a plurality of said digital data from both said first slave device and said second slave device, said processor operative to perform said power management function on said digital data and generate said output result.

20) The system of claim 17 wherein said power management function comprises generating an alarm message.

21) The system of claim 17 wherein said power management function comprises generating a load shedding command.

22) The system of claim 17 wherein said power management function comprises generating a power factor control command.

23) The system of claim 17 wherein said first slave device comprises an energy meter.

24) The system of claim 17 further wherein said first slave device facilitates communication of said digital data in response to a request from said master device.

25) The system of claim 17 wherein said first slave device is further coupled with a load, said slave device operative to at least one of monitor and control said load.

26) A system for monitoring and controlling the distribution of electrical energy in an electric circuit, said system comprising:

- (a) a digital network;
- (b) a master device and a slave device each coupled with said digital network and each further comprising:
 - (i) at least one sensor coupled with said electric circuit and operative to sense at least one electrical parameter in said electric circuit and generate at least one analog signal indicative thereof;
 - (ii) at least one analog to digital converter coupled with said sensors and operative to convert said at least one analog signal to digital data representative thereof;
 - (iii) a communications port coupled with said analog to digital converter and operative to facilitate communication of said digital data onto said digital network;
 - (iv) a processor coupled with said analog to digital converter, said processor operative to perform a function on said digital data and generate an output result;

wherein said master device further comprises a server module coupled with said processor of said master device and operative to facilitate communication of said output result on a second digital network using a first protocol, said first protocol comprising an open protocol.

27) The system of claim 26 wherein said master device comprises a revenue meter.

28) The system of claim 26 wherein said master device is operative to communicate with a plurality of slave devices.

29) The system of claim 26 wherein said master device is operative to communicate with a plurality of slave devices using an RS232 protocol.

30) The system of claim 25 wherein said master device is operative to communicate with a plurality of slave devices using an RS485 protocol.

31) The system of claim 26 wherein said slave device facilitates communication using a second protocol, said second protocol different from said first protocol, further wherein said second protocol comprising a closed protocol.

32) The system of claim 31 wherein said closed protocol comprises Modbus RTU protocol.

33) The system of claim 31 wherein said closed protocol comprises ION protocol.

34) The system of claim 31 wherein said closed protocol comprises DNP.

35) The system of claim 26 wherein said open protocol comprises a HTTP based protocol.

36) The system of claim 35 wherein said HTTP based protocol comprises XML.

37) The system of claim 35 wherein said HTTP based protocol comprises HTML.

38) The system of claim 35 wherein said HTTP based protocol comprises SMTP.

39) The system of claim 26 wherein said master device is operative to export said output result to a third device.

40) The system of claim 39 wherein said third device is operative to perform a power management function on said digital data.

41) The system of claim 40 wherein said power management function comprises an aggregation function.

42) The system of claim 40 wherein said power management function comprises a billing function.

43) The system of claim 40 wherein said power management function comprises a protection function.

44) The system of claim 40 wherein said power management function comprises a control function.

45) The system of claim 26 wherein said first digital network is coupled with said second digital network.

46) A method for monitoring and controlling the distribution of electrical energy in an electric circuit, said method comprising:

- (a) computing a first data value in a slave device coupled with a first network, said first network implementing a master protocol;
- (b) transmitting said first data value to a master device from said slave device over said first network;
- (c) receiving said first data value by said master device;
- (d) receiving at least one analog parameter from a power distribution network coupled with said master device;
- (e) performing at least one power management function on said first data value and generating a result; and
- (f) providing said result to a client application coupled with a second network, said second network implementing an internet protocol.

47) The method of claim 46, wherein (a) further comprises receiving a command via said first network from a master device coupled with said first network.

48) The method of claim 46, wherein (b) is in response to a said command.