

US 20040207136A1


(19) **United States**(12) **Patent Application Publication**  
**Adoline et al.**(10) **Pub. No.: US 2004/0207136 A1**(43) **Pub. Date: Oct. 21, 2004**(54) **COMPRESSION SPRING ROD****Publication Classification**(75) Inventors: **Jack W. Adoline**, Toledo, OH (US);  
**Thomas J. Fischer**, Whitehouse, OH  
(US)(51) **Int. Cl.<sup>7</sup>** ..... **F16F 5/00**(52) **U.S. Cl.** ..... **267/168**



Correspondence Address:


**FAY, SHARPE, FAGAN, MINNICH & McKEE**  
**Seventh Floor**  
**1100 Superior Avenue**  
**Cleveland, OH 44114-2579 (US)**(57) **ABSTRACT**(73) Assignee: **Barnes Group Inc., a Delaware corporation**(21) Appl. No.: **10/838,739**(22) Filed: **May 4, 2004****Related U.S. Application Data**

(62) Division of application No. 10/056,941, filed on Jan. 28, 2002, now Pat. No. 6,773,002.

A compression spring rod for relatively displacing elements attached to end mounts of the rod assembly comprises a housing having a rod member moveable between extended and retracted positions relative thereto, and a first compression spring in the housing surrounded by a second compression spring for biasing the rod member to one of an extended or retracted position relative to the housing. The two springs are oppositely wound, of different length, of different outside diameter, and of different wire diameter whereby, from a compressed condition, the spring rod exerts an expansion force which increases at a linear rate. Two sets of the springs can be arranged for biasing the rod member to a central position relative to the housing.










FIG. 5




FIG. 6





FIG. 7



ॐ  
ॐ  
ॐ




FIG. 11




FIG. 9




FIG. 10




FIG. 12




FIG. 13

## COMPRESSION SPRING ROD

### BACKGROUND OF THE INVENTION

[0001] The present invention relates to compression spring rods, and more particularly, to a spring and rod assembly that exerts an expansional force which increases at a linear rate.

[0002] The invention relates to a mechanism for biasing hoods, tops, doors, hinged covers, and other elements from a closed to an open position. The invention involves the use of springs in conjunction with a rod member to exert the driving force on the elements to be displaced. The following patents are incorporated herein by reference as background information with regard to spring mechanisms: U.S. Pat. No. 6,199,843 to DeGrace; U.S. Pat. No. 5,810,339 to Küspert, et al.; and U.S. Pat. No. 4,962,916 to Palinkas.

[0003] Compression spring rods are used in various applications, for example, to assist in lifting, opening, and damping. Typical applications include lifting a lid hinged to a stationary base. Other applications include lifting and/or balancing elements for the trunk or hatchback of an automobile. Still another application includes a damping spring for closing a door hinged to a stationary frame. Most applications involve the use of a pneumatic or gas spring to assist the opening motion. Many of these types of compression spring assemblies contain either gas or hydraulic fluid to control forces and piston speeds. Consequently, because these products contain a gas and/or fluid, they are subject to premature failure, due to the leakage of the gas or fluid over time. The leakage results in a loss of control forces and a subsequent loss of spring life.

### SUMMARY OF THE INVENTION

[0004] The present invention provides an improved compression spring rod which overcomes the above referred-to difficulties and others with regard to such rods heretofore available. More particularly in this respect, a compression spring rod in accordance with the invention is particularly adapted for lifting or pivoting one component relative to another component at a controlled rate. In accordance with one aspect, the invention provides a lift mechanism for hinged covers and the like that operates automatically upon release of the cover, or a lift mechanism for a loaded platform wherein the platform is elevated, progressively, as the load thereon is reduced. Advantageously, the compression spring assembly applies a constant and controlled force to open the cover or lift the platform. The mechanism is able to support significant loads while maintaining strength over a greater number of operating cycles than existing pneumatic or gas spring designs. Further, the invention provides a purely mechanical compression rod assembly that can yield controllable forces over a long period of use and control the spring forces during both extension and compression.

[0005] A compression spring rod according to the invention is comprised of multiple compression springs. The compression spring rod assembly includes a rod which is adapted to extend and retract relative to a housing. In one application, for example, the compression springs will build potential force as the springs are compressed, and release that force once the springs are allowed to expand. This extension of the springs imparts a force to the parts con-

nected to the ends of the rod and housing and, advantageously, multiple end configurations can be used to adapt the spring rod to a variety of mounting applications. The compression springs of a spring rod according to the invention are interrelated to produce a linear load versus deflection curve. The encased springs minimize load losses over time, and the mechanism does not contain any fluid or gases within the lift body. This advantageously eliminates the inevitable problem of leakage and subsequent loss of utility.

[0006] It is accordingly an outstanding object of the present invention to provide an improved compression spring rod for exerting an operating force on a displaceable member at a controlled rate.

[0007] Another object of the invention is the provision of a compression spring rod that supplies a consistent force over an extended period of time and maintains strength over a greater number of cycles compared to compression spring rods heretofore available.

[0008] Yet another object of the invention is the provision of a compression spring rod having at least two compression springs interrelated to produce a linear load versus deflection curve.

[0009] Yet another object of the invention is the provision of a compression spring rod having at least two compression springs interrelated to minimize load losses over time.

[0010] A further object of the invention is the provision of a mechanical compression spring rod assembly that provides an operating force that increases at a linear rate.

[0011] Yet a further object of the invention is to provide a mechanical compression spring assembly that can accommodate, selectively, multiple end configurations, thus adapting the assembly for mounting in a wide variety of use applications.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The foregoing and other objects and advantages will in part be obvious and in part pointed out in the following description taken together with the accompanying drawings in which:

[0013] FIG. 1 is a side elevation view, partially in section, of a compression spring rod according to the invention in the extended position;

[0014] FIG. 2 is a longitudinal cross section view of the compression spring rod in the compressed position;

[0015] FIG. 3 is a cross sectional view taken along line 3-3 of FIG. 2;

[0016] FIG. 4 is an exploded perspective view of the component parts of the compression spring rod shown in FIGS. 1-3;

[0017] FIG. 5 is a side elevation view of the compression springs of the compression spring rod;

[0018] FIG. 6 is a graph illustrating the relationship between spring force and compression of the compression spring rod assembly;

[0019] FIG. 7 is a perspective view of a box with a lid pivotable about a horizontal axis and compression spring rod elements shown in FIGS. 1-3 between the box and lid;

[0020] FIG. 8 is a side elevation view, in section, of a spring rod in accordance with a second embodiment of the invention;

[0021] FIG. 9 is an exploded perspective view of the component parts of the compression spring rod shown in FIG. 8;

[0022] FIG. 10 is a perspective view illustrating a use of the compression spring rod of FIGS. 8 and 9;

[0023] FIG. 11 is a side elevation view, in section, of a spring rod in accordance with another embodiment of the invention;

[0024] FIG. 12 is an exploded perspective view of the component parts of the compression spring rod shown in FIG. 11; and,

[0025] FIG. 13 is an illustration of an application of the compression spring rod of FIGS. 11 and 12.

#### DESCRIPTION OF PREFERRED EMBODIMENTS OF THE INVENTION

[0026] Referring now in greater detail to the drawings, wherein the showings are for the purpose of illustrating preferred embodiments of the invention only, and not for the purpose of limiting the invention, a compression spring rod 10, in accordance with the invention, as shown in FIGS. 1-6, has an axis 11 and includes a rod member 22 which is axially extendable and retractable relative to a one-piece tubular housing 24. Rod 22 has an outer end 22a and an inner end 22b connected to a guide rod 26 as set forth more fully hereinafter. Guide rod 26 extends axially inwardly of inner end 22b of rod 22 and is surrounded by a first compression spring 28 which is supported by the exterior surface 46 of guide rod 26 against buckling. First compression spring 28 is surrounded by a second compression spring 30 which is supported against buckling by the interior surface 48 of housing 24. Alignment of compression springs 28 and 30 relative to one another and axis 11 is maintained by the exterior surface 46 of guide rod 26 in conjunction with the interior surface 48 of housing 24. Housing 24 has a mounting end 23 and an outer or opposite end 25, and compression springs 28 and 30 are axially captured between a tail bushing 38 at mounting end 23 and a guide member 34 mounted between guide rod 26 and the inner end 22b of rod 22 as set forth hereinafter. Tail bushing 38 is supported in housing 24 by bending the endmost portion of the housing radially inwardly to define a retaining flange 39.

[0027] Compression spring rod 10 involves the use of a one-piece housing 24 which facilitates smooth movement of lift rod 22 and compression springs 28 and 30 during operation of the spring rod. As shown in the exploded view of FIG. 4, tail bushing 38 includes a neck portion 42 having a diameter sized to be received in the interior of compression spring 28. Tail bushing 38 also has a threaded stud 44 distal to the neck portion 42 which is received in a threaded recess 17 in a mounting element 18. Guide rod 26 includes a threaded stud 52 at the outer end thereof which passes through an opening 58 in guide member 34 and into a threaded bore 54 provided therefor in rod 22. Lift rod 22 passes through an opening 72 through a rod bushing 32 at outer end 25 of housing 24, and has a threaded stud 70 on outer end 22a thereof which is received in a threaded recess 27 provided therefor in a mounting element 20. Mounting

elements 18 and 20 have openings 19 and 21 therethrough, respectively, for receiving a variety of different mounting components common in the industry including, for example, pins, bolts, swivels, and the like. Advantageously, the threaded studs 44 and 70 at opposite ends of the spring rod assembly provide for accommodating the use of different mounting elements than those shown so as to modify the assembly for use in a variety of structural environments.

[0028] Guide member 34 is slidable in housing 24 and includes a guide ring 35 of suitable material to facilitate such sliding movement. Rod 22 is slidably supported at end 25 of housing 24 by rod bushing 32 which is secured to the housing by a pair of set screws 40 having inner ends received in an annular recess 41 in the rod bushing. Rod bushing 32 is further axially retained in housing 24 by bending the outermost part of end 25 radially inwardly to provide a retaining flange 33. At full extension, rod 22 is cushioned by rod bushing 32 and an impact absorbing metal spring ring 36 received in a recess 55 at inner end 22b of rod 22 adjacent the axially outer face of guide member 34. When rod 22 is fully extended, spring ring 36 engages in a recess 51 in the axially inner end of rod bushing 32. Lubrication can be provided in housing 24 to facilitate the sliding movement of guide member 34 therein. As will be appreciated from the foregoing description, guide member 34 and rod bushing 32 support rod 22 for reciprocation in housing 24 such as to maintain minimal breakaway forces for rod 22. Additionally, guide member 34 and rod bushing 32 keep rod 22 coaxial with axis 11 and decrease the effect of side loading on the assembly.

[0029] Compression spring rod 10, through the multiple spring rate characteristics of compression springs 28 and 30, serves to provide smooth extension forces to the movement of lift rod 22 from the retracted to the extended position thereof relative to housing 24. Depending upon the application, the appropriate load versus deflection can be determined and the corresponding physical and elastic properties of the combination of compression springs 28 and 30 can then be ascertained. The compression springs 28 and 30 can each be fabricated from spring material, such as music wire, and, for example, ASTM A228 or 302 stainless steel.

[0030] Each compression spring 28 and 30 has a different stress and strain characteristic. If the spring is considered to be a one-dimensional object, the only stress will be extensional (or compressional, which will be the negative of extensional) and the units of stress will be force per unit of extension. Within a range of compression, each spring obeys "Hook's Law", which states that for forces in a defined range, the stretch of a material is proportional to the applied force:

$$F = -k\Delta L$$

[0031] The proportionality constant, k, is known as the spring constant with dimensions of force over length, and  $\Delta L$  is the amount of compression. The negative sign indicates that the force is in the opposite direction of extension: if the spring is extended, the force tries to restore it to its original length. Likewise, if the spring is compressed ( $\Delta L < 0$ ), the force attempts to expand the spring, again to its original length. The spring constant depends on both physical and elastic properties of the material being stretched. Hook's Law is fairly intuitive at a basic level, and can be illustrated by everyday experience in which it is known that

a thin wire will stretch more than a thick wire or rod of the same material when the same stretching force is applied to both. The formula  $U = \frac{1}{2}k(\Delta L)^2$ , gives the work of extension (U) or alternatively, the amount of potential energy stored in the spring.

[0032] As shown in **FIGS. 3 and 5**, compression spring **28** has a free length  $L_1$  which is greater than the free length  $L_2$  of spring **30**, and spring **28** has an outer diameter greater than that of compression spring **30**. Also, the wire diameter of spring **28** is less than that of spring **30**, and the spring rate of spring **28** is less than that of spring **30**. As an example of one particular application, the specific physical characteristics of compression spring **28** are: wire diameter 0.055", inside diameter 0.5444", outside diameter 0.6544", free length 17.2", and a spring rate of 0.95 lbs./inch; and the physical characteristics of compression spring **30** are: wire diameter 0.081", inside diameter 0.675", outside diameter 0.837", free length 13.8", and a spring rate of 3.37 lbs./inch. **FIG. 6** displays the load versus deflection curve for compression springs **28** and **30** having the foregoing specifications, and for the combined springs in the assembly shown in **FIGS. 1 and 2**. It is to be noted that springs **28** and **30** are oppositely wound and that this interrelationship together with the dimensional characteristics of the springs produces the combined linear load versus deflection graph depicted in **FIG. 6**. The different free lengths, as shown in **FIG. 5**, of springs **28** and **30** is one component that helps to control the forces and stabilize the guide member **34** and rod **22** during initial displacement thereof from the position shown in **FIG. 1** to the position shown in **FIG. 2** and during the termination of the movement from the position shown in **FIG. 2** to the position shown in **FIG. 1**. In this respect, the longer spring **28** is, in the free state of the spring **30** shown in **FIG. 1**, slightly compressed to the length of the latter spring and, therefore, exerts a stabilizing force on the components which eliminates any free play during initial and terminal displacement thereof during use.

[0033] **FIG. 7** illustrates two compression spring rods **10** according to the invention connected between a box **12** and a lid **14** therefor. While not shown in detail, lid **14** is suitably mounted on box **12**, such as by hinges, to be pivotable about an axis A relative thereto. The mounting elements **18** and **20** of compression spring rods **10** are suitably secured to box **12** and lid **14**, respectively. A latch **15** is shown on lid **14** for engagement with a keeper **16** on box **12** to releasably hold the lid closed relative to box **12**. Latch **15** may be of various types common in the industry, and the method for releasing latch **15** may be by hand, foot, key, remote, etc. Subsequent to releasing the latch **15**, compression spring rods **10** automatically extend from the position shown in **FIG. 2** to the position as shown in **FIG. 1**, during which the spring rods **10** expand, releasing the stored compressive force in compression springs **28** and **30** to displace lid **14** from the closed to the open position thereof.

[0034] **FIGS. 8 and 9** illustrate another embodiment of a compression spring assembly according to the invention. In this embodiment, compression spring rod **100** has an axis **101** and includes a rod **102** which is axially extendable and retractable relative to a one-piece tubular housing **104**. Rod **102** has an outer end **102a** and an inner end **102b** connected to a guide rod **106** as set forth more fully hereinafter. Guide rod **106** extends axially inwardly of inner end **102b** of rod **102**. A first compression spring **108** is supported against

buckling by the exterior surface **103** of rod **102**. Spring **108** is surrounded by a second compression spring **110** which is supported against buckling by the interior surface **105** of housing **104**. Coaxial alignment of compression springs **108** and **110** relative to one another and axis **101** is maintained by the exterior surface **103** of rod **102** in conjunction with the interior surface **105** of housing **104**. When assembled, compression springs **108** and **110** are axially captured between a rod bushing **112** at end **114** of housing **104** and a guide member **116** secured to inner end **102b** of the rod between the latter and guide rod **106**. Guide rod **106** includes a threaded stud **107** at the outer end thereof which passes through an opening **115** in guide member **116** and into a threaded bore **137** provided therefor in rod **102**. A tail bushing **120** is supported in end **124** of housing **104** by set screws **122** received in an annular recess **126** in the tail bushing **120**. For the purpose set forth hereinafter, the component parts of spring rod **100** are cushioned during operation of the compression spring assembly by a cushioning spring **130** which surrounds guide rod **106**. Spring **130** is axially captured between the tail bushing **120** at end **124** and the guide member **116**. Tail bushing **120** includes a neck portion **123** having a diameter sized to be received in the interior of cushioning spring **130**. Tail bushing **120** also has a threaded stud **125** distal to neck portion **123** which is received in a threaded recess **127** in a mounting element **132**. Guide member **116** is slidable in housing **104** and includes a guide ring **117** of suitable material to facilitate such sliding movement. Rod **102** is slidably supported at end **114** of housing **104** by rod bushing **112** which is secured to housing **104** by a pair of set screws **122** having inner ends received in an annular recess **113** in bushing **112**. Rod **102** passes through an opening **111** in bushing **112** at outer end **114** of housing **104**, and has a threaded stud **139** on outer end **102a** thereof which is received in a threaded recess **140** provided therefor in a mounting element **134**. As will be appreciated from the foregoing description, guide member **116** and rod bushing **112** support rod **102** for reciprocation in housing **104** such as to maintain minimal breakaway forces for rod **102**. Mounting elements **132** and **134** have openings **133** and **135** therethrough, respectively, for receiving a variety of different mounting components common in the industry including, for example, pins, bolts, swivels, and the like. Mounting element **132** is fixedly attached to tail bushing **120** for mounting the compression spring assembly to a work supporting surface.

[0035] **FIG. 10** illustrates four compression spring rods **100** each connected between a corresponding fixed support **142** and a platform or work supporting table **140**. The spring rods **100**, as shown in **FIG. 10**, are designed to expand in the direction of arrow **z** in response to a load applied to platform **140**, thus compressing springs **108** and **110**. Compression springs **108** and **110** then expand and retract the spring rods in the direction of arrow **y** as the load is progressively removed from platform **140**. Compression springs **108** and **110** have the same physical characteristics as compression springs **28** and **30** described in the first embodiment. The arrangement of spring rods **100** and platform **140** as shown in **FIG. 10** is suitable, for example, as a progressive load lifter, such as for metal plates. As plates are progressively stacked on platform **140**, the spring rods **100** extend in the direction of arrow **z**, whereby the compression springs **108** and **110** are progressively compressed. As stated, when the springs are compressed ( $\Delta L < 0$ ) the resultant force attempts

to expand the spring rod to its original length. Thus, as the plates are progressively removed from the platform, the compression springs **108** and **110** expand thereby causing the platform **140** to move in the direction of arrow *y*. In this manner, the springs provide controlled forces by which the top plate in the stack on the platform remains at a given level as the platform moves first in the *z* direction and then in the *y* direction. If the entire load is suddenly removed from the platform, the spring rods retract rapidly and cushioning spring **130** cushions the retracting movement to protect the spring rods against damage. Additionally, it will be appreciated that this embodiment is particularly well suited as a counterbalance system, conveyor chain tensioner, door lift assist, and dampener.

[0036] FIGS. 11 and 12 illustrate another embodiment of a compression spring assembly according to the invention. In this embodiment, compression spring rod **180** has an axis **181** and includes two rods **182** and **184** which are alternately axially extendable and retractable together relative to a one-piece tubular housing **186**. Rod **182** has an outer end **182a** and an inner end **182b** and rod **184** has an outer end **184a** and an inner end **184b** connected to inner end **182b** of rod **182** together with a guide member **200** as set forth more fully hereinafter. Rod **182** extends axially inwardly of end **186a** of housing **186** and is surrounded by a first compression spring **188** which is supported by the exterior surface **183** of rod **182** against buckling. First compression spring **188** is surrounded by a second compression spring **190** which is supported against buckling by the interior surface **187** of housing **186**. Rod **184** extends axially inwardly of opposite end **186b** of housing **186** and is surrounded by a third compression spring **192** which is supported by the exterior surface **185** of rod **184** against buckling. Third compression spring **192** is surrounded by a fourth compression spring **194** which is supported against buckling by the interior surface **187** of housing **186**. Alignment of compression springs **188**, **190**, **192**, and **194** relative to one another and axis **181** is maintained by the exterior surfaces **183** and **185** of rods **182** and **184**, respectively, in conjunction with the interior surface **187** of housing **186**. Compression springs **188** and **190** are axially captured between a rod bushing **196** at end **186a** and the guide member **200**, and compression springs **192** and **194** are axially captured between a rod bushing **202** at end **186b** of the housing and the guide member. Rod bushing **196** is supported in housing **186** by set screws **206** at end **186a** thereof which extend into an annular recess **197** in bushing **196**. Similarly, rod bushing **202** is supported in housing **186** by set screws **206** at end **186b** thereof which extend into an annular recess **203** in the bushing. Axial retention of bushings **196** and **202** is further enhanced by bending the corresponding end of housing **186** radially inwardly of the bushings.

[0037] The compression spring rod **180** involves the use of a one-piece housing **186** which facilitates smooth movement of rods **182** and **184** and compression springs **188**, **190**, **192**, and **194** during operation of the spring rod. As shown in the exploded view of FIG. 12, rod **184** includes threads **230** and **231** at opposite ends of the rod. Threads **230** are received in a threaded recess **232** in a mounting element **220**. Threads **231** pass through an opening in spring ring **210**, an opening through guide member **200**, and an opening in spring ring **208** and are received in a threaded recess **235** in rod **182**. Rod **182** includes threads **234** distal to recess **235**, which are received in a threaded recess **233** in a mounting element **222**.

As will be appreciated from the foregoing description, guide member **200** and rod bushings **196** and **202** support rods **182** and **184**, respectively, for reciprocation in housing **186** such as to maintain minimal breakaway forces for rods **182** and **184** in use of the spring assembly.

[0038] Spring rod assembly **180** is adapted to apply an extension force, alternately, in axially opposite directions at a controllable rate. At full extension from housing **186**, rods **182** and **184** are cushioned by rod bushings **196** and **202**, respectively. In addition, impact in the direction of extension is absorbed by metal spring rings **208** and **210** which are received in recesses **212** and **214**, respectively, at inner end **182b** of rod **182** and inner end **184b** of rod **184**. Spring rings **208** and **210** are adjacent the axially outer faces of guide member **200** and respectively engage rod bushings **196** and **202** upon full extension of the rods in the respective direction of extension. Lubrication can be provided in housing **186** to facilitate the sliding movement of guide member **200** therein.

[0039] As shown in FIG. 13, spring rod assembly **180** is capable of self-centering a load which, as illustrated by way of example only, is in the form of two workpieces **230** and **232** having ends **230a** and **232a** pivotally attached to a fixed support member **231**. Spring rod **180** has the outer ends of rods **182** and **184** thereof respectively pivotally connected to ends **232b** and **230a** of the workpieces. Spring rod **180** is supported centrally between workpieces **230** and **232** by a bracket **224** rigidly secured to support member **231** by a support arm **225**. The springs of each pair of compression springs **188** and **190** and **192** and **194** have the same physical characteristics as compression springs **28** and **30** described in the first embodiment. In the arrangement shown in FIG. 13, spring rod **180** is a load centering assembly. In this respect, it will be appreciated that if either workpiece **230** or **232** is displaced in the direction of arrow *c*, rod **184** extends relative to housing **186** and the springs **192** and **194** are compressed. The resultant force of springs **192** and **194** in the direction of arrow *e* attempts to expand the springs to their original length. It will be appreciated that the opposite is true when either workpiece is displaced in the direction of arrow *d*. In this respect, springs **188** and **190** are compressed and springs **192** and **194** are totally relaxed. The resultant force in the direction of arrow *e* attempts to expand springs **188** and **190** to their original length. During return movement of workpieces **230** and **232** to the central position thereof, the relaxed pair of springs cushion the return movement. As with the earlier embodiments, the springs **188** and **190** and **192** and **194** provide controlled forces to self-center workpieces **230** and **232** when either is deflected from the neutral position. It will be appreciated that this embodiment is particularly well suited as a centering device in a steering mechanism, linkage mechanism, gating mechanism, and dampener.

[0040] While considerable emphasis has been placed herein on the structures and configurations of the preferred embodiments of the invention, it will be appreciated that other embodiments, as well as modifications of the embodiments disclosed herein, can be made without departing from the principles of the invention. In this respect, it will be appreciated that the spring rod can be used in applications other than those disclosed herein. Similarly, multiple combinations of coaxial and surrounding springs (i.e. three, four, etc.) may be configured to meet the desired load versus

deflection for a particular application. Likewise, it will be appreciated that a spring rod according to the invention can be secured to relatively displaceable components in any number of different ways. These and other modifications of the preferred embodiments, as well as other embodiments of the invention, will be obvious and suggested to those skilled in the art from the disclosure herein, whereby it is to be distinctly understood that the foregoing descriptive matter is to be interpreted merely as illustrative of the present invention and not as a limitation thereof.

1-27 (Canceled).

**28.** A compression spring rod comprising a housing having an axis and axially opposite ends, a rod member coaxial with said axis and having an inner end in said housing and an outer end axially outwardly of one of said opposite ends, means including a guide member on said inner end of said rod member and a bushing at said one of said opposite ends supporting said rod for reciprocation axially of said housing between retracted and extended positions relative thereto, and first and second compression springs each extending between said guide member and said rod bushing coaxial with said axis for biasing said rod toward the retracted position thereof.

**29.** The compression spring rod of claim 28, wherein the direction of winding of said first compression spring is opposite to the direction of winding of said at least second compression spring.

**30.** The compression spring rod of claim 28, wherein the length of said first compression spring is unequal to the length of said second compression spring.

**31.** The compression spring rod of claim 28, wherein the outside diameter of said first compression spring is less than the outside diameter of said second compression spring.

**32.** The compression spring rod of claim 28, wherein the wire diameter of said first compression spring is less than the wire diameter of said second compression spring.

**33.** The compression spring rod of claim 28, wherein the outside diameter and wire diameter of said first compression spring are respectively less than the outside diameter and wire diameter of said second compression spring.

**34.** The compression spring rod of claim 28, wherein a guide rod extends from said guide member toward the other of said opposite ends coaxial with said axis and a cushioning spring surrounding said guide rod and extending between said guide member and said other of said opposite ends of said housing for cushioning retracting movement of said rod member.

**35.** A compression spring rod comprising a housing having an axis and axially opposite ends, first and second rods coaxial with said axis and having an inner end in said housing and an outer end axially outwardly of a different one of said opposite ends, means including a guide member interconnecting said inner ends of said rods and supporting said rods for reciprocation axially of said housing between retracted and extended positions relative thereto, first and second compression springs each extending between said guide member and one of said opposite ends of said housing coaxial with said axis, third and fourth compression springs each extending between said guide member and the other of said opposite ends of said housing coaxial with said axis, said compression springs biasing said rods toward a central position thereof relative to said housing.

**36.** The compression spring rod of claim 35, wherein the direction of winding of said first and third compression springs is opposite to the direction of winding of said second and fourth compression springs.

**37.** The compression spring rod of claim 35, wherein the length of said first and third compression springs are the same, and the lengths of said second and fourth compression springs are the same and different than the lengths of said first and third compression springs.

**38.** The compression spring rod of claim 35, wherein the outside diameters of said first and third compression springs are less respectively than the outside diameter of said second and fourth compression springs.

**39.** The compression spring rod of claim 35, wherein the wire diameters of said first and third compression springs are the same, and the wire diameters of said second and fourth compression springs are the same and greater than that of the first and third compression springs.

**40.** The compression spring rod of claim 35, wherein the outside diameters and wire diameters of said first and third compression springs are less respectively than the outside diameters and wire diameters of said second and fourth compression springs.

**41.** The compression spring rod of claim 40, wherein said outside diameters of said first and third compression springs are the same, the outside diameters of said second and fourth compression springs are the same, the wire diameters of said first and third compression springs are the same, and the wire diameters of said second and fourth compression springs are the same.

**42.** A compression spring rod comprising a housing having an axis and axially opposite ends, a first rod member coaxial with said axis and having an inner end in said housing and an outer end axially outwardly of one of said opposite ends, a guide member on said inner end of said first rod member to support said first rod member for reciprocation axially of said housing between retracted and extended positions relative thereto, first and second compression springs each extending between said guide member and said one of said opposite ends coaxial with said axis for biasing said first rod member toward the retracted position thereof; and a second rod member extending from said guide member toward the other of said opposite ends coaxial with said axis and a third spring surrounding said second rod member and extending between said guide member and the other of said opposite ends of said housing for biasing retracting movement of said first rod member.

**43.** The compression spring rod of claim 42, wherein the direction of winding of said first compression spring is opposite to the direction of winding of said at least second compression spring.

**44.** The compression spring rod of claim 42, wherein the length of said first compression spring is unequal to the length of said second compression spring.

**45.** The compression spring rod of claim 42, wherein the outside diameter of said first compression spring is less than the outside diameter of said second compression spring.

**46.** The compression spring rod of claim 42, wherein the wire diameter of said first compression spring is less than the wire diameter of said second compression spring.