

US 20040216734A1

(19) **United States**(12) **Patent Application Publication**
Lawheed(10) **Pub. No.: US 2004/0216734 A1**(43) **Pub. Date: Nov. 4, 2004**(54) **CONVERSION OF SOLAR ENERGY**(76) **Inventor: Paul Lawheed, San Diego, CA (US)**

Correspondence Address:


Lynn G. Foster**L. Grant Foster****FOSTER & FOSTER L.L.C.****602 E. 300 S.****Salt Lake City, UT 84102 (US)**(21) **Appl. No.: 10/856,025**(22) **Filed: May 27, 2004****Related U.S. Application Data**

(63) Continuation of application No. 10/458,917, filed on Jun. 10, 2003, now abandoned, which is a continuation of application No. 10/251,709, filed on Sep. 21, 2002, now Pat. No. 6,696,637, which is a continua-

tion of application No. 09/867,196, filed on May 29, 2001, now Pat. No. 6,498,290.

Publication Classification(51) **Int. Cl.⁷ F24J 2/38**(52) **U.S. Cl. 126/573; 126/600; 126/696**(57) **ABSTRACT**

An array of elongated concave parabolic trough-shaped reflectors is disclosed. The orientation of the array is biaxially kept essentially perpendicular to rays of the sun by an optical control such that sunlight is reflected and concentrated along a focal line of each elongated reflector by which (a) water in a tube disposed at the focal line is heated by reflected line focused sunlight impinged thereon and/or (b) line focused reflected sunlight is optically transformed into point focused reflected sunlight using Fresnel lenses from which electricity is generated using solar cells upon which the point focused reflected sunlight is impinged.









Fig. 1
















Fig. 5





















Fig. 18








Fig.26




Fig.27








Fig.28



CONVERSION OF SOLAR ENERGY

FIELD OF THE INVENTION

[0001] The present invention relates generally to conversion of sunlight into other forms of energy, including thermal energy and electrical energy, and, more particularly, to use of elongated concave trough-shaped reflectors connected in an array for unitary movement, and maintaining essentially perpendicularity between the reflectors and the rays of the sun to heat water with linearly-focused reflected sunlight and to create electricity with point-focused reflected sunlight derived from the line-focused reflected sunlight.

BACKGROUND

[0002] Solar energy is freely and daily available. It is a clean, non-polluting source of energy. Providing a reliable, long term, cost effective, efficient way of using sunlight to obtain electrical and thermal power has long been an unsolved problem, until the present invention.

[0003] It has been proposed that flat panel solar converters be used to convert direct sunlight into thermal or electrical energy.

[0004] Pedestal supported flat panels using direct sunlight to generate electricity were part of the Solar One project.

[0005] A circular, but concave reflector mounted on a single column or pedestal has been proposed. This approach was used on the Soleras water desalination project in Saudi Arabia and on the Solar Two project in Dagget, Calif.

[0006] Fixed position concave reflectors placed in an array and positioned in side by side rows on an incline have been proposed. See U.S. Pat. No. 4,202,322. Such an installation was made at the Federal Correctional Institution at Phoenix, Ariz.

[0007] Tilttable elongated concave reflector assemblies have been utilized, such as the one at Barstow, Calif., owned by FPL Energy SEGS VIII and IX.

[0008] Solar Systems comprising bidirectionally controlled Fresnel lens and solar cell assemblies, utilizing direct sunlight, have been proposed. See, U.S. Pat. No. 4,649,899, for example. Also see, U.S. Pat. No. 4,245,153. Optical detectors for dual axis tracking of the sun are known.

[0009] The above-identified proposals and installations have failed to provide reliable, low cost, efficient, variable capacity systems by which solar energy is converted to thermal and/or electrical energy. A long felt need has existed for energy conversion plants which are reliable, efficient, cost effective and size variable to meet both low and high capacity demands for thermal and electrical energy.

BRIEF SUMMARY AND OBJECTS OF THE PRESENT INVENTION

[0010] In brief summary, the present invention overcomes or substantially alleviates the long term problems of the prior art by which solar energy is converted to thermal energy and/or electrical energy. The present invention provides reliable, cost effective systems for such conversion, where the size of the system can be correlated to the desired capacity.

[0011] The orientation of an array of elongated concave parabolic trough-shaped reflectors is biaxially kept essentially perpendicular to rays of the sun by a control such that the sunlight is reflected and concentrated along a focal line of each elongated reflector by which (a) tube-contained water is heated at the focal line by reflected sunlight impinged thereon and/or (b) line focused reflected sunlight is optically transformed into point focused reflected sunlight from which electricity is generated using solar cells upon which the point focused reflected sunlight is impinged.

[0012] With the foregoing in mind, it is a primary object of the present invention to overcome or substantially alleviate the long term problems of the prior art by which solar energy is converted to thermal energy and/or electrical energy.

[0013] Another paramount object of the present invention is to provide reliable, cost effective systems for such conversion, where the size of any such system can be correlated to the desired capacity.

[0014] A further object of great significance is the provision of solar energy conversion systems wherein the orientation of an array of elongated concave parabolic trough-shaped reflectors is biaxially kept essentially perpendicular to rays of the sun by a control such that the sunlight is reflected and concentrated along a focal line of each elongated reflector by which (a) tube-contained water is heated at the focal line by reflected sunlight impinged thereon and/or (b) line focused reflected sunlight is optically transformed into point focused reflected sunlight from which electricity is generated using solar cells upon which the point focused reflected sunlight is impinged.

[0015] These and other objects and features of the present invention will be apparent from the detailed description taken with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 is a perspective representation, schematic in nature of one configuration embodying principles of the present invention;

[0017] FIG. 2 is a perspective of one form of the stationary lower frame forming a part of embodiments of the present invention;

[0018] FIG. 3 is a perspective representation of an upper frame embodiment which is rotated optically to follow the sun, and reflector frames, the tilt of which is adjustable in unison;

[0019] FIG. 4 is a diagrammatic representation of the manner in which the attitude and azimuth of the array of parabolic trough-shaped reflectors is displaced to maintain perpendicularity with the sun and the manner in which line-focused reflected sunlight is impinged upon a solar-to-thermal or solar-to-electricity converter;

[0020] FIG. 5 is an enlarged fragmentary perspective of two parabolic trough-shaped reflectors and reflector frames together with energy converters disposed at the line focal point of each reflector, each converter being supported by two cantilevered structural members;

[0021] FIG. 6 is a fragmentary enlarged perspective of an optical detector used to cause the upper frame, reflector

frames and reflectors to follow the sun in the sky so as to preserve perpendicularity between the reflectors and the rays of the sun;

[0022] FIG. 7 is a schematic representation of a system by which line-focused reflected sunlight is converted to thermal energy;

[0023] FIG. 8 is a diagrammatic representation of the manner in which point-focused reflected sunlight is converted to electrical energy;

[0024] FIG. 9 is an elevational view, shown partly in cross section, illustrated in the manner in which the tilt of the array of reflectors is altered to maintain perpendicularity with the sun;

[0025] FIG. 10 is a fragmentary perspective illustrating, in part, the toggle mechanism by which the tilt of the array of reflectors is changed to maintain perpendicularity with the rays of the sun;

[0026] FIG. 11 is an enlarged fragmentary representation of the toggle mechanism illustrated in FIG. 10 viewing the same from the concave side of the reflectors as opposed to the convex side;

[0027] FIG. 12 is an enlarged fragmentary perspective similar to FIG. 11 further illustrating the manner in which a screw drive is motor displaced responsive to optical signals to change the tilt of the array of reflectors to maintain the above-mentioned perpendicularity;

[0028] FIG. 13 is an enlarged perspective illustrating the manner in which the upper frame is displaced along a track of the lower to maintain said perpendicularity;

[0029] FIG. 14 is cross section taken along lines 14-14 of FIG. 13;

[0030] FIG. 15 is a cross section taken along lines 15-15 of FIG. 13;

[0031] FIG. 16 is a fragmentary enlarged perspective representation illustrating a portion of the upper, displaceable frame, the motor and differential by which the upper frame is rotated selectively upon the lower frame;

[0032] FIG. 17 is a fragmentary enlarged perspective illustrating the motor and rotational drive system by which the upper frame is rotated selectively upon the lower frame;

[0033] FIG. 18 is likewise an enlarged fragmentary perspective of the rotational drive system by which the upper frame is rotated selectively in respect to the lower frame for preserving perpendicularity with the sun;

[0034] FIG. 19 is a cross sectional view taken along line 19-19 of FIG. 2;

[0035] FIG. 20 is a fragmentary elevational view of an additional form of the present invention comprising a lower static frame supported upon columns and comprising a curved track upon which an upper frame is mounted for selective rotational displacement;

[0036] FIG. 21 is a fragmentary plan view of a relatively large embodiment of the present invention wherein the upper frame is rotatably mounted upon two or more tracks;

[0037] FIG. 22 is a plan view of a torque tube drive which may be used in lieu of a toggle mechanism when a large array of parabolic reflectors is utilized;

[0038] FIG. 23 is a cross section taken along lines 23-23 of FIG. 22;

[0039] FIGS. 24 and 25 are cross sectional views illustrating the manner in which a thermal converter disposed at the focal line of a parabolic reflector may be insulated;

[0040] FIG. 26 is a perspective representation of an energy converter adapted to be disposed at the focal line of a trough-shaped parabolic reflector to convert solar energy to electrical energy;

[0041] FIG. 27 is a plan view illustrating a different form of secondary reflector to ensure point focus impingement of reflected sunlight upon solar cells;

[0042] FIG. 28 is a cross sectional view taken along line 28-28 of FIG. 27;

[0043] FIG. 29 is a fragmentary perspective of another reflector embodiment with the support frame on the convex or back side of the reflector; and

[0044] FIGS. 30, 31 and 32 are a cross section taken along lines 30-30, 31-31 and 32-32, respectively, of FIG. 29.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[0045] The present invention utilizes the free and limitless energy of the sun to produce electricity and thermal energy. The scale of embodiments according to the present invention can be tailored to the need, ranging from small stand alone systems for residential and small business use to intermediate sized plants for plant or factory use to massive assemblies design to mitigate against if not eliminate the electrical energy crisis in California. The present photovoltaic invention is economical to install and maintain, is reliable and not maintenance-intensive, is efficient and cost effective to operate and does not pollute the environment. The sun is not a consumable resource.

[0046] Using the present invention, businesses, industrial plants, retail and office buildings, homes, farms and villages can produce some, if not all, of their own electrical and thermal power, and avoid the largest uncontrollable cost of doing business today—the ever-escalating price of purchased power generated from fossil and nuclear fuels.

[0047] This invention is capable of making significantly more energy per square foot than conventional flat plate solar collectors. And flat plate collectors are incapable of co-generating the large amounts of thermal energy that the present concentrating photovoltaic generating systems make automatically.

[0048] Until now, remote installations have been faced with a difficult choice: pay the prohibitive costs of bringing in utility power, or depend on costly, noisy, and hard to maintain pollution-creating diesel, gas or propane generators. The present invention is a third and better choice, which can be scaled or sized to produce as much electrical and/or thermal energy as needed, independently, on site; the energy needed to power a home or business, pump water, irrigate land and run remote communication installations.

[0049] Unlike centralized forms of power generation, on-site de-centralized use of solar power needs no far-flung distribution network of gigantic towers and high voltage lines. Instead it utilizes a universally available asset—

sunshine. No moving parts, except for the perpendicularity biaxial tracking system. It is noiseless, pollution-free, and requires almost no maintenance over many years of service.

[0050] Decentralized sunlight-derived electrical power can free users from the effects of peak-hour brown-outs, and from the possibility of total black-outs caused by operator error or the planned actions of groups hostile to utilities or nations.

[0051] The cost of the generating equipment itself—through the production of power for a building can be amortized over the life of the building, as part of debt financing (mortgage). Amazing as it may seem, one of the largest and most uncontrollable costs a building owner faces is the ever-escalating cost of power. Using the present invention, one actually has the ability to eliminate most of the cost of purchased power now and for years to come.

[0052] When land and water were plentiful and labor was cheap, little was known about the delicate balance existing between the environment and the extraction, burning, and wastes of non-renewable fuels. Now it is all too apparent that our supply of fossil fuels is limited—and that these sources are causing damage to our atmosphere, water supplies, and food chain—damage that is or may soon become irreversible. The costs, too, for fossil fuels continue upward as the more accessible fuel deposits are consumed, and as the costs for machinery, labor, and transportation continue to rise around the world.

[0053] Ironically, the best answer to the world's need for energy has always been the sun. The sun can satisfy a significant percentage of our energy requirements while helping us to become independent of the negative aspects inherent in conventional power generation. Switching to solar-derived power will reduce the pollution produced by coal, oil and nuclear fuels. It will also slow the use of oil and allow us to conserve it for more valuable uses, such as chemical feedstocks and plastics. The rate of coal usage would also be slowed. Harnessing the sun will also reduce, or eliminate, the need for nuclear power and mitigate its many risks and problems.

[0054] Even though the sun is just beginning to contribute to satisfying the world's energy demands on a large scale, direct sunlight has been powering satellites and spacecraft since 1958. In the 1970's the first terrestrially-directed sunlight photovoltaics supplied power to locations too remote to have ties to utility lines. Then, as the solar industry developed more efficient silicon cells and generators, larger grid-connected direct sunlight installations became practical.

[0055] The present invention is not space-intensive. One embodiment of the present invention can be mounted on an existing rooftop so that it essentially takes up no additional space at all. Ground-mounted systems on a pad or the like is also an option as well. Column mounting is a further option.

[0056] Various embodiments of the present invention may be used in conjunction with residences) office buildings, manufacturing facilities, apartment buildings, schools, hospitals, remote communications, telemetry facilities, offshore platforms, water pumping stations, desalination systems, disinfection systems, wilderness camping, headquarters installations, remote medical facilities, refrigeration sys-

tems, farms and dairies, remote villages, weather stations, and air conditioning systems, to name a few.

[0057] The present invention is also useful in: (a) providing cathodic protection against galvanite corrosion, (b) storage of electrical energy in batteries and (c) generation and sale of electricity to utility companies.

[0058] The sun is an energy source that, unlike fossil fuels, is free each day to whatever generation site is selected. It does not need to be mined, transported, refined, burned or purchased. So the costs for all these steps to produce energy are eliminated. Gone, too, are all forms of pollution. There are no particulates or gases vented into the atmosphere. Nor is there a need for millions of gallons of cooling water. (The small amount of water used to cool the solar cells actually becomes a second form of co-generated power, i.e. production of thermal energy, that has dozens of residential and commercial uses.) So water is conserved. There are no massive discharges of hot water into coastal waters to elevate the normal temperature and alter and perhaps destroy the habitats and food chains of coastal marine life. With solar energy, there are no wastes of any kind to be removed or buried in mines or deep at sea, so there are few, if any, health risks to our generation or future generations. Various embodiments of the invention are modular, allowing any installation to be as large or as small to meet exactly the needs of the installation for electrical and/or thermal energy. The electricity produced is direct current (DC), which, when appropriate, may be transformed into alternating current (AC) using an inverter or DC-to-AC converter.

[0059] At the heart of the present invention is the utilization of a system which biaxially tracks the location of the sun in the sky to maintain a perpendicularity between an array of parabolic trough-shaped reflectors and the rays of the sun so that reflected line or point focused sunlight may be efficiently converted into thermal and/or electrical energy.

[0060] FIG. 1 is a diagrammatic representation of one configuration or system according to the present invention, which system is generally designated 40. System 40 comprises a lower stationary or static frame 42, an upper rotatable frame 44, mounted for movement upon the stationary frame 42, an array of parabolic trough-shaped reflectors, generally designated 46, carried by the upper frame 44, an optical sun-locating control, generally designated 48, carried by the upper frame 44, a rotational drive mechanism, generally designated 50, by which the upper frame 44 is rotated about the lower frame 42 to maintain perpendicularity between the rays of the sun and the reflective surfaces of the parabolic reflectors comprising the array 46 under control of the optical sensor 48, a toggle reflector-tilting mechanism, generally designated 52, by which the angle of tilt of the parabolic reflectors of the array 46 is altered to maintain said perpendicularity as the sun travels across the sky and energy converters 54, one being disposed along the focal line of each parabolic reflector for converting reflected, concentrated sunlight into thermal and/or electrical energy.

[0061] An advantage of the present invention, when disposed in the form of apparatus 40, is that it is modular, i.e. the number of reflectors can vary, ranging from a relatively small number to a relatively large number, depending upon the needs of a given facility.

[0062] In the form shown in FIG. 1, the lower frame 42 comprises a curvilinear, preferably circular, track, generally

designated **56**, which, in cross section, is in the form of an I-beam comprising an upper flange **58**, a lower flange **60** and a web **62**. The track **56** is preferably made of steel and may be formed into the configuration shown in **FIG. 1** using roller technology available at a conventional steel plant. The track **56** is supported upon a plurality of floor, roof or ground-engaging legs **64**. Legs **64** may be of any desirable type. All or some of the legs **64** may be adjustable in length to provide for leveling, as herein described in greater detail, or of fixed length, where leveling is not a consideration in order to place the track **56** in essentially a horizontal orientation. The leg **64** may be made of steel construction, or some other suitable material may be used. Of course, the lower frame may be varied in its construction from that illustrated in **FIG. 1** without departing from the spirit or essential characteristics of the present invention, so long as a tracking of the sun and adequate capacity are provided.

[0063] With continued reference to **FIG. 1**, the upper frame **44** is shown schematically as comprising a rectangular member **66**, formed of hollow bar stock which is rectangular in cross section, for example, with interconnecting cross members **68** integrally joined at the ends thereof to the rectangular member **66**, as by welding or use of conventional connectors comprising, for example, screw or nut and bolt fasteners. Upper frame **44**, as illustrated in **FIG. 1**, is intended to be fundamentally diagrammatic, to illustrate principles associated with the present invention.

[0064] While not shown in detail in **FIG. 1**, the upper frame **44** is rotatably associated with the lower fixed frame **42** in such a way, for example, that rollers traverse the track **56** to and fro for the purpose of maintaining perpendicular azimuth alignment between the rays of the sun and the disposition of each reflectors **46** of the array. Rotational displacement of the upper frame **44** in respect to the lower frame **42**, in this regard, is achieved by the motor and rotational drive assembly **50**, responsive to signals from the optical detector **48**, as explained herein in greater detail. The optical detector **48** is illustrated and is being mounted to a reflector frame associated with one of the reflectors **76**, at site **70**, in **FIG. 1**.

[0065] The toggle tilting mechanism comprises a motor-driven, reversible screw jack **72**, the proximal cylinder end of which is connected to the upper frame **44** and the exposed distal piston end **74** thereof is pivotally connected at site **78** to one or more reflector frame members which support the assemblage or array of reflectors **76** for unitary variation in tilting to maintain altitude perpendicularity with the sun. As the piston rod **74** is extended and retracted, the reflectors **76** are tilted in unison by a toggle mechanism **80**. The tilting mechanism **52** and toggle mechanism **80** are illustrated diagrammatically in **FIG. 1**. Each reflector **76** in a line or tandem of reflectors is non-rotatably connected to one or two adjacent reflectors by structural members **83** which accommodate the above-mentioned unitary tilting of the reflectors.

[0066] From the foregoing, it is clear that the upper frame **44** is, selectively rotated upon lower frame **42** pursuant to optical control signals and the trough-shaped parallel reflectors **76** are adjusted in the angularity of their tilt, so that each reflector **76** is essentially perpendicular to the rays of the sun at all times during daylight hours. It is the use of reflected line and point focused sunlight that significantly distinguishes the present invention.

[0067] With reference to **FIG. 2**, a somewhat modified lower frame **42'** is illustrated. This embodiment illustrates the previously described circular track **56**. A drive chain **90** rests upon the lower flange **60** of the erect I-beam track **56** to accommodate selective rotation of the upper frame in respect to the lower frame **42'** in the manner explained above. In lieu of leg **64**, telescopic legs, generally designated **64'**, are provided. Each leg **64'** is illustrated as comprising sequential aligned leg segments **92** and **94** which are telescopically interrelated so that the overall length may be adjusted to level the track **56**. To do this, a set screw **96** is loosened, the correct collective length for the leg segments **92** and **94** established and the set screw **96** threadably tightened through the leg segment **92** against the leg segment **94** to maintain the desired collective length. For added structural load-transferring stability, diagonal braces **98** are provided. The top of tube **92** and the top of each brace **94** is welded or otherwise suitably secured to the underside of lower track flange **60**. The lower end of each diagonal brace **98** is welded or otherwise suitably secured to the associated tube **92**.

[0068] The lower end of each tube **94** is illustrated as being welded to a plate or pedestal **100**, which may be apertured so as to receive nut and bolt assemblies **102**, with the lower heads thereof being imbedded in concrete for stability.

[0069] With reference to **FIG. 3**, one type of suitable upper frame, generally designated **44'**, is shown, which implements principles of the present invention. The upper frame **44'** is superimposed upon the circular track **56** and supports aligned pairs of reflector frames, each generally designated **110**, by which the parabolic reflectors are rotated in unison to adjust their angle of tilt.

[0070] The upper frame **44'** is relatively small in overall size, as is the track **56**. The frame **44'** can be expanded to accommodate essentially as many reflectors as necessary for any desired facility by which reflected, line and point focused sunlight is transformed into thermal and/or electrical energy.

[0071] The upper rotatable frame **44'**, illustrated in **FIG. 3**, is shown as comprising end beams, or trusses, preferably of steel, each generally designated **112**, and an interior beam of steel, generally designated **114**. Other types of suitable trusses or beams could be used.

[0072] Each end beam **112** is illustrated as comprising upper and lower horizontal bars **116** and **118**, which are integrally connected as by welded to several vertical cross-bars **120**. The interior beam **114** comprises a plurality of horizontal members **122** and two vertical members **124**, such that the horizontal members **122** and the vertical members **124** are welded together. A plurality of beams, generally designated **130**, transversely connect to the end beams **112** and the intermediate beam or beams **114** so that the upper rotatable frame **44'** is a rigid structure, providing ample support for the reflectors, the energy converters and the reflector frames.

[0073] As best illustrated in **FIG. 3**, each parabolic trough-shaped reflector **76** is supported by a reflector frame, generally designated **140**. While only eight reflector frames **140** are illustrated in **FIG. 3**, as mentioned previously, the number of reflectors and, accordingly, the number of reflector frames can be expanded significantly beyond the small array illustrated in **FIG. 3**.

[0074] Each reflector frame 140 is essentially rigid and comprises top and bottom longitudinally-directed bars 142 and 144, connected by three trusses, each generally designated 146. Each truss 146 comprises a linear bar 148, a parabolic bar 150 and a plurality of cross bars 152, transversely spanning between bars 148 and 150, all ends of members 148, 150 and 152 being integrally connected as by welding.

[0075] Each reflector frame 140 also comprises at least one central longitudinally-directed support bar 154, welded to two end plates 156, by which the collective tilt of the reflectors is rotationally adjusted in respect to the rotatable upper frame 44', as hereinafter explained in greater detail. End axle journals 158 span between each outside end plate 156 and one of the end frames 112 and function as explained hereinafter in greater detail. Adjacent interior plates 156 are also connected one to another by a journal mechanism, explained hereinafter in greater detail, by which joint tilting rotation of adjacent reflectors and reflector frames is accommodated.

[0076] The previously mentioned energy converters 54, one of which is carried by each reflector frame 110 at the focal line of the associated parabolic reflector, is supported by two cantilever arms 160 one disposed at each end of the converter 54. Each arm 160 is connected by welding or the like to the central bar 154 and one end truss 146 to rigidly hold the associated converter 54 at the focal line of the associated reflector 76, the energy converter 54 bidirectional turning with the reflector as it is turned utilizing the power toggle mechanism 52.

[0077] Each reflector 76, none of which is shown in FIG. 3, is attached to each of the three associated parabolic members 150, spanning the full length and width of the associated reflector support frame 110. Rivets or other suitable fasteners may be used to connect the reflector to the associated parabolic members 150. Each reflector 76 is preferably comprised of polished sheet aluminum or other suitable highly reflective material.

[0078] The energy converter 54 for each reflector 76 is supported at the respective ends thereof by arm 160, which not only rigidly connects to one of the ends of the associated converter 54 but also at sites 151 and 153 (FIG. 5) to the associated reflector frame 140, as by welding.

[0079] Each converter 54 and the associated support arms 160 are typically hollow to accommodate liquid flow within a pipe to, through and from the converter 54 for the purpose of converting line focused or point focused reflected sunlight to thermal energy per se or in conjunction with the cooling of solar cells, which are exposed to very high temperatures during conversion of reflected point focused sunlight to electrical energy, as hereinafter explained in greater detail.

[0080] From the foregoing, the significance of the illustration comprising FIG. 4 should be readily apparent, namely that the tracking optical sun detector 48 continuously senses the location of the sun in the sky relative to the azimuth and altitude of the array of reflectors 76 and, to the extent, the reflectors 76 are not collectively perpendicular to the sun, the differential is detected by the bidirectional optical sensor 48 and signals are issued to the motor and rotational drive 50 to place the axes of the reflectors into a position of perpendicularity with the sun. In addition, signals

are issued by the detector 48 to the motor and toggle tilting mechanism 52 by which the tilt of the parabolic reflectors is placed in a perpendicular relationship with the rays of the sun, perpendicularity being intersection of the rays of the sun with a line drawn between the upper and lower edges 170 and 172 (FIG. 4) of each reflector.

[0081] Thus, both from altitude and an azimuth point of view, the reflectors 76 are continuously adjusted so that reflector perpendicularity is maintained with the rays of sunshine striking each parabolic trough-shaped reflector. As a consequence, sunlight reflected from each reflector 76 is line-focused upon the associated energy converter 54, where the reflected, line-focused solar energy is either converted to thermal energy or point-focused and converted to electrical energy, as explained herein in greater detail.

[0082] The relationship between the reflector trusses 150 and the trough-shaped parabolic reflectors 76 is best illustrated in FIG. 5, in enlarged fragmentary perspective. In the configuration of FIG. 5, two central longitudinal reinforcing bars 154 and 154' are provided, in lieu of one, to enhance structural integrity.

[0083] In reference to FIG. 6, the optical detector 48 is illustrated in greater detail. Detector 48 comprises an external housing 170 which supports two shadow devices 172 and 174. Shadow bar device 172 comprises a shadow bar 173, by which lack of perpendicular alignment between the rays of the sun and the altitude or tilt angle of the reflectors is detected by one or more internal photocells. Shadow bar detector 174 comprises a shadow bar 175, by which lack of perpendicular azimuth or rotational alignment is detected by one or more internal photocells. When the internal photo cells detect a lack of either altitude or azimuth alignment via shadows caused by rays of the sun striking the shadow bars 173 and/or 175, signals are issued to the motor and rotational drive 50 and/or motor and toggle tilting mechanism 52 to bring the rotational position and the tilt position of the array of reflectors again into perpendicularity with the rays of the sun, after which the detector signals cease because no detectable shadow exists and rational and/or tilt adjustments stop.

[0084] Reference is made now to FIGS. 7 and 8 with particularity in respect to the types of energy converters which may be disposed at converter site 54. FIG. 7 illustrates a converter by which solar energy is transformed into thermal energy, while FIG. 8 illustrates an embodiment by which solar energy may be reflected and point focused for conversion into electrical energy. In respect to FIG. 7, a tube 176 is disposed at the focal line of reflector 76 so that the rays of line focused, reflected sunlight 178 impinge directly in concentrated form upon the thermally conductive material, such as copper, from which the tube 176 is formed.

[0085] As the rays of reflected, line focused sunshine heat the tube 176, liquid is displaced from source 178 through the tube 176 at a flow rate controlled by flow control 180. The liquid so displaced is heated by the elevated temperature of the tube 176, typically to a very high temperature along the focal line at 54, with the effluent hot water or steam being delivered, for example, to a heat exchanger 182, where the liquid or steam emerging from tube 176 is used to heat another segregated liquid, which is discharged from the heat exchanger as effluent from tube 184. The liquid entering the

heat exchange **182** as influent is, after the heat exchanged process, discharged along tube **186**, and is returned to the source **178**.

[0086] The liquid contained within source **178** and circulated as indicated above may be, in selected instances, water and, in other instances, a mixture of alcohol and water, as chosen by one skilled in the art. Other suitable liquids may be used.

[0087] With specific reference to **FIG. 8**, the line focused reflected solar energy **188** is caused to be point focused, for example by a series of Fresnel lenses, as shown diagrammatically at **188** in **FIG. 8**. The point focused rays **188** of sunlight are impinged upon a series of solar cells **190**, the characteristic of which transforms the point of focus reflected sunlight **188** into direct current electrical energy, which may be sold, stored or directly utilized. In the alternative, the DC electricity can be passed through a DC/AC converter **192** to create alternating current electricity, which may be stored, sold or directly utilized.

[0088] While not shown in **FIG. 8**, it is to be appreciated that the solar cells **190** typically are mounted or otherwise made contiguous to the external surface of a cooling tube to hold the temperature of the solar cells **190** within a lower acceptable temperature range. As a consequence, liquid contained within the cooling tube is heated, which heated liquid may be utilized in any suitable fashion including but not limited to the one described above in respect to **FIG. 7**.

[0089] As mentioned earlier, in conjunction with **FIG. 3**, the reflector frames **140** are collectively assembled so as to rotate in unison around journals, such as end axle/journals assemblies **158**, the journals/assemblies axles, of any string or tandem of aligned reflector frames **140** being disposed along a common axis. Each journal/axle assembly **158** essentially comprise a central short axle such that diametrically reduced ends of the axle fit within opposed sleeves at opposite ends of the axle. Each axle is stably secured to the upper frame **44, 44**; while the sleeves rotate around the associated axle with the reflector frames.

[0090] Similarly, journals/axle assemblies **194** (**FIG. 9**) are interposed between sequential aligned reflectors **76** and comprise outer sleeves **196** at each end of the journal and a central short axle comprising reduced diameter ends **198** rotatably disposed within the sleeves **196**. The axles comprising ends **198** are rigidly connected to the upper frame **44, 44**; while the sleeves **196** are connected to and rotate with the reflector frames **140**. As can be seen from inspection of **FIG. 9**, the aligned axles of any aligned group of reflector **76** creates an axis of rotation. The previously mentioned toggle mechanism **52** may comprise a motor-driven screw drive, generally designated **200**, which comprises an internally helically threaded cylinder **202** and a rod **204**, the internal end of which is threadedly engaged with the interior threads of the cylinder **202**, to accommodate extension and retraction. The distal end **206** of the rod **204** is pivotally connected, at **208**, to a bracket comprising a pair of lugs **210**. Lugs **210** are integrally connected, by welding, fasteners or the like to a pair of toggle displacement bars **212** (only one of which is seen in **FIG. 9**), which are reciprocated to and fro by the motor-driven extension and retraction of rod **204**. The distal ends **214** of the two toggle bars **212** are respectively connected pivotally at **216** to, adjacent anchor plates **218** welded or otherwise secured to juxtaposed parallel trusses

146. The connection site **216** is eccentrically located to facility rotation of the reflector frames **140** around the axles.

[0091] Thus, as detector **48** at shadow bar **173** photoelectrically determines the need to adjust the tilt of the array of reflectors, a signal is sent to the screw drive motor **230** (**FIG. 12**), which in turn causes extension or retraction of the rod **104**, which in turn displaces the toggle bars **212** fore or aft to pivot the array of reflectors in unison around the axles upon which the reflector frames **140** are rotatably mounted. See **FIG. 9**. The toggle bars **212** consecutively pivotally and eccentrically connect at **216** to one of each line of reflector frames **140**, as best illustrated in **FIG. 9**, so that all reflector frames **140** and all reflectors **76** rotate together around parallel horizontal axes.

[0092] Keep in mind that the detector **48** (**FIG. 6**) is mounted to one of the trusses **146** (**FIG. 6**) so that the shadow bars **173** and **175** are in a plane essentially parallel to the plane containing bar **148** of the truss **146** which supports the detector **48**.

[0093] Specific reference is now made to **FIG. 10** through **12**, which illustrate one way in which the toggle mechanism **52** may be connected to adjacent reflector frames **146**. The two toggle bars **212** are illustrated as being parallel and hollow structural members having a rectangular cross section (**FIG. 10**). The toggle connection plates **218** are illustrated in **FIG. 10** as extending beyond the two adjacent reflectors **76**, as does the distal ends of each toggle bar **212**. The pivotal connectors **216** are illustrated as being nut and bolt assemblies pivotally passing through, in each case, the associated toggle bar **212** and the connection plate **218**, to accommodate the previously mentioned changes in the tilt angle of the array of reflectors **76** and reflector frame **140**.

[0094] **FIG. 11** is similar to **FIG. 10**, but illustrates the motorized tilt adjusting mechanism **52** for the array of reflectors **76** from a perspective essential opposite to perspective of **FIG. 10**.

[0095] The screw drive **200** is again illustrated in **FIG. 12**, which further depicts motor **230**, conventionally connected to transmission or differential **232**, so that when the reversible motor **230** is actuated by a signal from the optical detector **48** (**FIG. 6**) to unitarily alter the angular relationship of the array of reflectors in respect to the vertical, the screw drive **200** is extended or retracted, depending upon the displacement necessary to restore the angle of tilt of the reflectors to perpendicularity with the rays of the sun.

[0096] As mentioned earlier in conjunction with **FIG. 1**, the upper frame **44** is rotatably mounted upon the curved track **56**, which track, as illustrated, is in the form of a circular I-beam. More specifically, the upper rotatable frame **44** is made selectively rotatable in respect to the stationary track **56** using a plurality of load-transferring trucks **250**, one of which is illustrated in **FIG. 13**. Each truck **250**, as illustrated, comprises a U-shaped frame, generally designated **252**, preferably formed of steel comprising two pairs of lugs or ears **254** and a U-shaped bridge **256**. The lugs **254** and the bridge **256** are held in spaced relation in respect to the I-beam track **56**, as best illustrated in **FIGS. 14 and 15**. An upper frame displacement roller **258** is rotatably supported by each lug **254** upon a shaft **260**. Each shaft **260** is non-rotatably carried by the associated lug **254** in the manner illustrated in **FIG. 14**. As best seen in **FIGS. 13 and**

14, each of the four rollers or casters **258** frictionally engage and rotatably travel along the upper surface of lower flange **60** of the I-beam track **56**.

[0097] Each truck **252** is rigidly connected to the upper, rotatable frame **44**. This may be as illustrated in **FIG. 13**, i.e., by use of two angle irons welded in spaced relation to the upper horizontal surface of the associated bridge **256**. See **FIGS. 13 and 15**, specifically. The spacing between the vertically directed legs of the angles **262**, shown at **264** (**FIG. 15**) accommodates snug reception of one horizontal member **45** of the upper frame **44**. Nut and bolt assemblies **266** (**FIG. 13**) are illustrated as being utilized to fasten each angle piece **262** to the upper frame member **45**.

[0098] Thus, a plurality of idler trucks **250** are used to provide load transfer to the lower flange **60** of the I-beam track **56** and to accommodate rotation of the upper frame **44** in respect to the lower frame responsive to location correcting signals issued from the optical detector **48**.

[0099] To prevent the upper frame from jumping the track **56**, each truck **250** is equipped with vertically directed, web-engaging opposed rollers **268**. See **FIG. 15**. These rollers maintain appropriate alignment between the upper frame and the trucks **250** in respect to the lower frame and circular track **56**. The rollers **268** contiguously engage the opposite surfaces of the web **52** of the I-beam **56**, each being rotatably mounted upon L-shaped axle **270**, which accommodates rotational travel by the rollers **268** along the web **62** as the rollers **258** correspondingly travel along the upper surface of the lower flange **60** of the I-beam **56**.

[0100] Reference is now made to **FIGS. 2 and 16** through **19**, which collectively illustrate the motor and rotational drive mechanism **50**. The mechanism **50** comprises a reversible motor **280**, which is activated and deactivated by signals derived from the optical sensor **48** by which the array of reflectors are maintained, from an azimuth point of view, in a perpendicular orientation with respect to the rays of the sun.

[0101] Reversible motor **280** rotates a differential or gear transfer box **282**, which in turn rotates an external drive shaft **284** (**FIG. 18**), which turns a drive sprocket **286**, non-rotatably secured to the shaft **284**. The sprocket **286** turns to engage successive links **288** of the previously mentioned drive chain (**FIG. 2**) **90**. The chain drive **90** is statically secured, as by welding, at its distal and proximal ends to the static I-beam track **56**, providing enough length to accommodate engagement with the sprocket **286**. Rotational displacement of the sprocket **286** causes the sprocket to walk, in one direction or the other, along the links **288** of the chain **90** to rotate the upper frame **44** upon the lower frame **42** to maintain reflector perpendicularity with the sun from sunrise to sunset during the longest day of the year in any location upon the face of the earth. The chain **90**, between welded ends, rests upon the top surface of the lower flange **60**, as shown in **FIGS. 2**, and **17-19**. Thus, the chain drive **90** is loose at all locations, except where it is welded to the track **56** at its opposed ends. The length of the chain drive **90** is selected so as to snugly pass around the sprocket **286** in taut relation.

[0102] Thus, rotation by motor **280** of the shaft **284** and the sprocket **286**, either clockwise or counterclockwise, will result in the upper frame **44** turning in respect to the lower

frame, in one direction or the other, to maintain azimuth perpendicularity with the sun, in the manner described earlier. Note that the motor **280** and the differential **282** are statically mounted upon a mounting plate **292** of the upper frame **44**. Mounting plate **292** is preferably formed of steel and is bolted, welded or both to the upper frame **44**. Signals from the optical detector **48** turn the reversible motor **280** on and off in one direction or the other consistent with optical detection of non-azimuth perpendicularity between the array of reflectors and the location of the sun in the sky.

[0103] As seen best in **FIGS. 17 and 18**, the chain **90** comprises a U-shaped segment, generally designated **300**, which passes tautly around the sprocket **286**. The sprocket contains teeth, sized and shaped to engage hollow spaces within each link **288** of the chain **90**. Accordingly, as the sprocket **286** is rotated by motor **280**, the differential **282** and the shaft **284**, successive links **288** of the chain drive **90** are engaged by the sprocket teeth causing the upper frame **44** to rotate along the track **56** in the manner explained above to preserve the mentioned perpendicularity. The motor **280** is reversible and, therefore, shaft **284** may be turned in either direction to move the upper frame **44** clockwise or counterclockwise along the lower stationary track **56**.

[0104] The present invention is not confined to any specific form for the lower stationary frame and/or the upper displaceable frame. Similarly, the present invention may be implemented by placing it above the roof of an existing building supported by columns, on an existing flat or sloped roof of an existing building, on or immediately above an existing surface, such as a parking lot, for example, on columns above an existing surface (to allow traffic underneath) or in any other suitable location.

[0105] Reference is made to **FIG. 20**, which illustrates one way of mounting an embodiment of the present invention comprising a lower static frame **42'** comprising a curved track **56'**, which is also static, supported upon a plurality of columns **310** (only one of which is illustrated), wherein the proximal end **312** of each column extend into the ground and is encased in concrete **314**, for stability.

[0106] Each column **310** is secured as by welding at sites **314** to the lower static truss **42'**. Frame **42'** is illustrated as comprising a plurality of members **316**, arranged conventionally to form triangular supports. The structural members **316** may be of any appropriate cross sectional shape, preferably formed of steel.

[0107] The track **56'** is illustrated as being circularly disposed with the flanges **58'** and **60'** being vertically not horizontally directed and the web **62'** being horizontally directed. The lower edges of the flanges **58'** and **60'** contiguously engage and are secured to the lower frame **42'**, as by welding. The load comprising the reflectors, the reflector frames, the upper rotatable frame **44'** wind and/or snow comprise a substantial load transferred through a plurality of trucks **252'** and rollers **258'** to the web **62'** of the track **56'**.

[0108] Reference is now made to **FIG. 21** which illustrates one way in which large installations in accordance with the present invention may be implemented. More specifically, two or more static tracks **56**, of the type previously described, are concentrically provided so that a large array of reflectors and reflector frames carried upon a displaceable upper frame may rotate in unison along the

plurality of tracks **56** as earlier described. Thus, the size of any installation utilizing the present invention is flexible, ranging from a very small installation comprising a few reflectors to an extremely large installation comprising a large number of reflectors.

[0109] Where a sequence of reflectors and reflector frames aligned longitudinally one with another is utilized, in lieu of the motor and toggle tilting mechanism **52**, described above, a torque tube, generally designated **330** in **FIG. 22** may be used. The torque tube **330** may be of hollow tubular steel construction to which is attached a plurality of tracking arms **332**, joined, respectively, in an eccentric disposition to each reflector frame **140** of a line of such frames. Rotation of the torque tube **330** will in turn alter the tilt angle of the associated reflectors **76** and reflector frames **140**. This rotation is achieved by one or more drive arms **334** integrally connected as by welding to the tube **330**. The distal end **336** is pivotally connected to the distal end of the previously described rod **204** of the screw drive **200** so that extension and retraction of the rod **204** rotates the torque tube **330** through the drive arm **334** clockwise and counterclockwise, respectively, for the purpose of adjusting the tilt of the related reflectors to preserve perpendicularity with the rays of the sun, as mentioned earlier. A plurality of torque tubes may be used as would be appropriate. More than one screw drive **200** may be used in conjunction with any given torque tube without departing from the spirit of the present invention.

[0110] As mentioned previously, when the energy converter **54** transforms solar energy into thermal energy, a hollow tube **340** (**FIG. 24**) may be located at the focal line of the associated reflector. Tube **340** may be of any thermally conductive material, such as copper. A liquid is displaced through the hollow interior **342** as the line-focused sunlight **344** impinges upon and heats the tube **340**, causing the liquid contained in the tube **340** to be heated from one temperature to a significantly higher temperature.

[0111] In the configuration of **FIG. 24**, a U-shaped housing **345** of suitable material, such as sheet metal or, plastic surrounds part of the tube **340** within the housing **345**. The housing **345** comprises opposed lower lips **346**, which accommodate sheet reception and retention of transparent lens **348**, which may be glass or synthetic resinous material. The tube **340** is illustrated as being imbedded, in part, in a block of insulation **350**, so that the heated liquid within the hollow interior **342** of the tube **340** does not undesirably or prematurely cool. The block of insulation **350** is illustrated in **FIG. 24** as surrounding approximately 260 degrees of the tube **340** when viewed in cross section, i.e., the top and most of the two sides, leaving the bottom of the tube **340** open for impingement of the reflected line-focused rays **344** of the sun through the lens **348** directly upon the exterior of the tube **340**.

[0112] In lieu of the configuration illustrated in **FIG. 24**, the embodiment of **FIG. 25** may be utilized wherein the block of insulation **350'** extends only along 180 degrees of the exterior tube **340** when viewed in cross section.

[0113] As mentioned earlier, some or all of the focus lines of the parabolic trough-shaped reflectors **76** may be equipped with solar-to-electricity converters. More specifically, in reference to **FIG. 26**, converter **54** may comprise a housing **360** having a tapered hollow interior. The top of **362**

may be equipped with a plurality of aligned Fresnel lenses **364**. Each Fresnel lens **264** comprises concentric grooves upon which is impinged the reflected line-focused sunshine **366**. The grooves of each Fresnel lens converts the reflected line-focused sunshine **366** to reflected point-focused sunlight **368**. Each segment of point-focused sunlight is impinged upon one of the solar cells **190**.

[0114] Several commercially available solar cells exist any of which may be used as solar cells **190**. While the input to each solar cell **190** is solar energy, the output is electrical energy, communicated from the solar-to-electricity converter **54** upon electrical leads **370**. This electrical energy is direct current electricity. If alternating current electricity is desired, DC/AC converter **192** may be utilized from which conventional household electricity may be derived.

[0115] Continued reference is made to **FIG. 26**, which illustrates a circular funnel-shaped secondary solar energy reflector **372** disposed above each solar cell **190**, by which any stray solar energy is reflected so that all sunlight passing through the associated Fresnel lens **264** is caused to impinge upon the associated solar cell **190**.

[0116] As mentioned earlier, it is ordinarily appropriate to cool the solar cells **190**. This may be done by placing each solar cell contiguously on the exterior of a cooling tube **374**, through which liquid coolant is displaced to not only cool the solar cells **190** but to convert the heat so transferred to useable thermal energy.

[0117] In lieu of the circular funnel-shaped secondary reflectors **372**, the reflectors **380** of **FIGS. 27 and 28** may be used. Each reflector **380** is rectangular in cross section with four downwardly tapered flat walls intersecting at diagonally-disposed corners, with a solar cell at the bottom of each reflector **380**. In either case, the internal surface of secondary reflectors **372** and/or **380** is selected to accommodate full reflection of any stray sunlight so that all sunlight passing through any Fresnel lens **364** is caused to impinge upon the associated solar cell **190**.

[0118] Reference is now made to **FIGS. 29 and 30**, which illustrate another reflector embodiment of the present invention with the support frame on the convex or back side of the reflector, as opposed to being on the front or concave side. More specifically, all or any one of the parabolic trough-shaped reflectors **76** may be supported on the back or reverse side thereof to provide a slightly more unencumbered reflective surface. As shown in **FIG. 29**, reflector **76** is supported by a reflector frame **400**. Reflector frame **400** comprises the previously described upper and lower longitudinal reinforcement of members **142** and **144**. Midway between the members **142** and **144**, on the back side of the reflector **76**, are two contiguous longitudinally extending rectangular supports **154''** comprising, at each end, blunt edges **155** essentially aligned with the adjacent end edge of the associated reflector **76**.

[0119] A plurality of parabolically shaped ribs, each generally designated **402**, span, at spaced intervals, between respectively member **142** and one of the two central members **154''** and between member **144** and the other of the two central support members **154'**, as illustrated in **FIG. 29**.

[0120] Each rib **402**, as best illustrated in **FIG. 30**, comprises a U-shaped brace having opposed outwardly directed flanges **404**, which are contiguous with and adhered by a

simple bonding agent or the like to the back surface of reflector **76** at interface sites **406**. The each rib **402** further comprises opposed parallel side walls **408**, which respectively merge with the associated one of the two flanges **404** essentially through a 90 degree angle. The spaced side walls **408** merge respectively at 90 degree comers with a back wall **410**, which is cut at opposite ends into integral end tabs **412** and **414**. Each end tab **412** is contiguous with and bonded to member **142** or member **144**, depending upon whether the rib is a top rib or a bottom rib. See **FIGS. 31 and 32**.

[0121] In addition to the foregoing, the reflector frame **402** will be rotatably connected to the previously described axle structure and eccentrically to the previously described toggle mechanism to accommodate rotation around a horizontal axis to accommodate periodic changes in the tilt of the reflector **76** to preserve perpendicularity with the rays of the sun, for the purposes set forth above.

[0122] The invention may be embodied in other specific forms without departing from the spirit of the central characteristics thereof. The present embodiments therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

What is claimed and desired to be secured by Letters Patent is:

1. A method of transforming solar energy to thermal energy comprising the acts of:

- (a) impinging rays of sunshine upon an array of linear line-focusing parabolic trough reflectors arranged in series and parallel;
- (b) mechanically tilting the reflectors around at least one essentially horizontal axis and mechanically turning the reflectors collectively along a curved track in respect to an essentially vertical axis so that the reflectors individually and collectively are essentially perpendicular to the rays of sunshine;
- (c) correcting the tilt of the reflectors and the track positions of the reflectors around the essentially horizontal axis and the essentially vertical axis, respectively, to retain said perpendicular relationship;
- (d) heating influent water in a tube with reflected sunlight at a focal line of each reflector;
- (e) discharging the tube-heated water as effluent for subsequent use.

- 2. (Cancelled)
- 3. (Cancelled)
- 4. (Cancelled)
- 5. (Cancelled)
- 6. (Cancelled)
- 7. (Cancelled)
- 8. (Cancelled)
- 9. (Cancelled)
- 10. (Cancelled)
- 11. (Cancelled)
- 12. (Cancelled)
- 13. (Cancelled)
- 14. (Cancelled)

- 15. (Cancelled)
- 16. (Cancelled)
- 17. (Cancelled)
- 18. (Cancelled)
- 19. (Cancelled)
- 20. (Cancelled)
- 21. (Cancelled)
- 22. (Cancelled)
- 23. (Cancelled)
- 24. (Cancelled)
- 25. (Cancelled)
- 26. (Cancelled)
- 27. (Cancelled)
- 28. (Cancelled)
- 29. (Cancelled)
- 30. (Cancelled)
- 31. (Cancelled)
- 32. (Cancelled)
- 33. (Cancelled)
- 34. (Cancelled)
- 35. (Cancelled)
- 36. (Cancelled)
- 37. (Cancelled)
- 38. (Cancelled)
- 39. (Cancelled)
- 40. (Cancelled)
- 41. (Cancelled)
- 42. (Cancelled)
- 43. (Cancelled)
- 44. (Cancelled)
- 45. (Cancelled)
- 46. (Cancelled)
- 47. (Cancelled)
- 48. (Cancelled)
- 49. (Cancelled)
- 50. (Cancelled)
- 51. (Cancelled)
- 52. (Cancelled)
- 53. (Cancelled)
- 54. (Cancelled)
- 55. (Cancelled)
- 56. (Cancelled)
- 57. (Cancelled)
- 58. (Cancelled)
- 59. (Cancelled)
- 60. (Cancelled)
- 61. (Cancelled)
- 62. (Cancelled)
- 63. (Cancelled)
- 64. (Cancelled)
- 65. (Cancelled)
- 66. (Cancelled)

67. A method of converting solar energy to electrical energy comprising the acts of:

automatically progressively and collectively turning and tilting an array of Fresnel lenses to maintain an essentially perpendicular relationship between rays of sunlight and all Fresnel lenses while converting at solar cells point focused rays of sunlight primarily via the Fresnel lenses and secondarily via a stray of sunlight concentrator interposed between each Fresnel lens and each solar cell.

68. A method of converting solar energy to electrical energy comprising acts of:

positioning at least one device by which sunlight is transformed into electricity so that the at least one device is and remains essentially perpendicular to rays of sunlight;

concentrating adjacent rays of sunlight which would otherwise not impinge upon the at least one device by redirecting the path of the adjacent rays to impinge upon the at least one device, whereby the device generates a greater amount of electricity.

* * * * *