

US 20060093528A1

(19) **United States**

(12) **Patent Application Publication**
Banerjee et al.

(10) **Pub. No.: US 2006/0093528 A1**

(43) **Pub. Date: May 4, 2006**

(54) **DEVICE INCLUDING A DISSOLVABLE STRUCTURE FOR FLOW CONTROL**

Publication Classification

(75) Inventors: **Debjoyti Banerjee**, Fremont, CA (US);
Konrad Faulstich, San Jose, CA (US);
Aldrich N. K. Lau, Palo Alto, CA (US);
Umberto Ulmanella, San Mateo, CA (US);
Jun Xie, Pasadena, CA (US)

(51) **Int. Cl.**
B01L 3/00 (2006.01)
(52) **U.S. Cl.** **422/103; 251/12**

(57) **ABSTRACT**

Correspondence Address:
KILYK & BOWERSOX, P.L.L.C.
3603 CHAIN BRIDGE ROAD
SUITE E
FAIRFAX, VA 22030 (US)

A diagnostic device is provided that includes a plurality of retainment regions, with the retainment regions that are separated by at least one dissolvable barrier. The retainment regions can be interconnected through at least one fluid processing passageway. A retainment region can include a container such as a retainment region, well, chamber, or other receptacle, or a retainment region such as a surface on which the material is retained. The retainment regions can include a reaction retainment region, one or more reagent retainment regions, each containing unreacted reagents, and a sample retainment region. A pressure-actuated valve can be positioned in each fluid processing passageway interconnecting the one or more reagent retainment regions with the respective intermediate retainment regions interposed between each of the one or more reagent retainment regions and the reaction retainment region. The dissolvable barrier can be a fluid flow modulator in the at least one fluid processing passageway.


(73) Assignee: **Applera Corporation**, Foster City, CA

(21) Appl. No.: **11/252,821**

(22) Filed: **Oct. 18, 2005**

Related U.S. Application Data

(60) Provisional application No. 60/619,731, filed on Oct. 18, 2004. Provisional application No. 60/619,677, filed on Oct. 18, 2004. Provisional application No. 60/619,623, filed on Oct. 18, 2004.






FIG. 1(a)




FIG. 1(b)




FIG. 1(c)




FIG.2




FIG. 3




FIG. 4A




FIG.4B




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 4H




FIG. 4I




FIG. 4J




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 5G




FIG. 5H




FIG. 51




FIG. 5J




FIG. 6






FIG. 8

FIG. 7






FIG. 11

DEVICE INCLUDING A DISSOLVABLE STRUCTURE FOR FLOW CONTROL

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims benefit under 35 U.S.C. Section 119(e) from earlier U.S. Provisional Patent Applications Nos. 60/619,731, 60/619,677, and 60/619,623, all of which were filed Oct. 18, 2004, and all of which are incorporated herein in their entireties by reference.

INTRODUCTION

[0002] The present teachings relate to a diagnostic device and method providing automatically controlled interconnection between a plurality of retainment regions.

[0003] A portable or nonportable diagnostic device or method can perform a set of predetermined assays by providing for controlled interaction between various fluids initially present in separate retainment regions. A device and method compatible with nucleic acid sequence reactions, and detecting such reactions, is desirable.

SUMMARY

[0004] According to various embodiments, a diagnostic device is provided that includes a plurality of retainment regions, as exemplified below, with the retainment regions being interconnected through a plurality of fluid communications, fluid processing passageways, and/or channels. Herein the phrase "retainment region" means a retainment or containment feature such as a well, a fluid retainment region, a reservoir, a channel, a vial, a compartment, another receptacle, a surface on which a material is retained, or the like. The following discussion with regard to retainment regions would be equally applicable to any of the above-mentioned features or their equivalents.

[0005] The retainment regions can include a reaction retainment region, one or more reagent retainment regions each containing reagents, and a sample retainment region. A pressure-actuated valve can be positioned in each of the fluid processing passageways interconnecting the one or more reagent retainment regions with respective intermediate retainment regions interposed between each of the one or more reagent retainment regions and the reaction retainment region. A barrier or fluid flow modulator, as exemplified below with reference to a valve, can be provided in one or more of the fluid processing passageways interconnecting the reagent retainment regions with the reaction retainment region or intermediate retainment regions, or interconnecting the intermediate retainment regions and the reaction retainment region.

[0006] According to various embodiments, a method of performing a set of predetermined assays is provided. The method can include providing a plurality of retainment regions in a closed, and if desired, disposable cuvette, with the retainment regions being interconnected by fluid processing passageways but closed to fluid flow to or from locations outside of the cuvette. First retainment regions can be selectively closed off from fluid communication with second retainment regions with which they are interconnected by first channels including pressure-actuated valves positioned therein. The pressure-actuated valves can com-

prise a burstable or tearable diaphragm, or other frangible seal that can rupture, tear, break, or the like, when exposed to a change in pressure, for example, an increase or decrease in pressure. One or more third retainment regions can be selectively closed off from fluid communication with at least the second retainment regions with which they are interconnected by second channels by valves positioned in the second channels. Pressure can be applied to the pressure actuated valves in the first channel sufficient to provide fluid communication between the first and second retainment regions. A sample to be tested or otherwise processed can be introduced into the one or more third retainment regions, and fluid communication can be established between the second retainment regions and the one or more third retainment regions at a controlled rate that can be a function of any one of a number of stimuli and/or characteristics of at least one of the sample in the one or more third retainment regions and a fluid within the second retainment regions. The characteristics of at least one of the sample in the one or more third retainment regions and a fluid within the second retainment region can include, but are not limited to water content, pH, chemical composition, temperature, electrical charge, magnetic properties, or the like.

[0007] The closed, and if desired, disposable cuvette, can be provided as a substrate that is fabricated from a single piece or more than one piece. The retainment regions, interconnecting fluid processing passageways, and/or valves can be fabricated all in the single piece substrate, or if desired, can be fabricated in one or more different pieces, which can then be combined to form the cuvette.

[0008] According to some embodiments, the device can comprise no vent, at least one vent, or a plurality of vents, to relieve pressure resulting from a flow of a fluid and its communication. A vent can comprise a vent channel configured to relieve such pressure. A vent can be provided in communication with a retainment region, such that upon fluid flow resultant pressure is released. A vent channel can comprise a hydrophobic vent channel that allows air to travel through the channel but does not allow the flow of an aqueous fluid.

[0009] According to some embodiments, a device is provided that can comprise no vent and can be manufactured and sealed under vacuum whereby the device can comprise a low internal gas pressure relative to the external ambient pressure.

[0010] Additional features and advantages of various embodiments will be set forth in part in the description that follows, and in part will be apparent from the description, or can be learned by practice of various embodiments. Other advantages of the various embodiments will be realized and attained by means of the elements and combinations exemplified in the application.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Various embodiments of the present teachings are exemplified in the accompanying drawings. The teachings are not limited to the embodiments depicted in the drawings, and include equivalent structures and methods, as set forth in the following description and as would be known to those of ordinary skill in the art in view of the present teachings.

[0012] FIGS. 1(a), 1(b), and 1(c) schematically illustrate various stages in the operation of a valve according to various embodiments.

[0013] FIG. 2 is a schematic illustration of a diagnostic device according to various embodiments.

[0014] FIG. 3 is a schematic illustration of a diagnostic device according to various embodiments.

[0015] FIGS. 4A-4J schematically illustrate various stages in the operation of a diagnostic device according to an embodiment.

[0016] FIGS. 5A-5J schematically illustrate various stages in the operation of a diagnostic device according to an embodiment.

[0017] FIG. 6 illustrates the assembly of a diagnostic device from two separate pieces.

[0018] FIG. 7 illustrates the effect of misalignment of the pieces shown in FIG. 6 for an embodiment of the device as shown in FIG. 3.

[0019] FIG. 8 illustrates the effect of misalignment of the pieces shown in FIG. 6 for an embodiment of the device as shown in FIG. 2.

[0020] FIG. 9 illustrates an arrangement of retainment regions and a valve according to various embodiments.

[0021] FIG. 10 illustrates an arrangement of retainment regions and a valve according to various embodiments.

[0022] FIG. 11 illustrates an arrangement of retainment regions and a valve according to various embodiments.

[0023] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are intended to provide a further explanation of the various embodiments of the present teachings.

DESCRIPTION OF VARIOUS EMBODIMENTS

[0024] According to various embodiments, a diagnostic device, that can be either portable or nonportable, is provided to perform one or more predetermined assays as desired, for example, in nucleic acid sequence detection technology. For a given assay, the assay protocol can involve a set of fluid handling steps such as mixing, incubation, washing, and the like, which are desirably performed in a given sequence of steps and for specified time periods for samples and reagents in specified volumes or proportions. The device can be miniaturized to the point that it can be used as a handheld portable diagnostic device. As shown in the exemplary embodiments illustrated in FIG. 2 and FIG. 3, the diagnostic device can include a plurality of retainment regions, as exemplified below, interconnected by fluid processing passageways. The plurality of retainment regions can be included within a closed, disposable cuvette such that all of the retainment regions are closed to fluid flow to or from locations outside of the cuvette. The plurality of retainment regions in the cuvette can include a reaction retainment region, one or more reagent retainment regions, each containing unreacted reagents, and a sample retainment region that can contain or receive a sample to be reacted with the unreacted reagents. The unreacted reagents, which can include enzymes, buffers, catalysts, or other reaction components, can be contained in a first set of retainment regions that are interconnected with an intermediate set of retainment regions by fluid processing passageways containing pressure-actuated valves. The intermediate retainment

regions can also be connected through fluid processing passageways to a reaction retainment region, with the fluid processing passageways that connect the intermediate retainment regions to the reaction retainment region comprising a material that is adapted to reduce in volume within the fluid processing passageway when brought into contact with fluids from the intermediate retainment regions, or when brought into contact with a sample after the sample has been added to the sample retainment region.

[0025] The term “fluid processing passageway” means any area, a structure, or communication, that allows for fluid communication between at least two retainment regions, for example, a channel connecting two regions. One or more fluid processing passageways according to the present teachings can be configured or adapted to provide capillary driven flow. One or more fluid processing passageways according to the present teachings can be configured or adapted to provide electrokinetic driven flow. One or more of the fluid processing passageways according to the present teachings can be configured or adapted to control the rate and timing of fluid flow by varying the dimensions of the fluid processing passageway.

[0026] The terms “fluid processing passageway,” “a fluid communication,” “fluid flow channel,” “fluid processing passageway,” “flow channel,” “flow control channel,” and “flow control passageway,” are each used synonymous with the term “fluid passageway,” as herein defined.

[0027] According to various embodiments, the term “fluid” means a gas, an aqueous fluid, a non-aqueous fluid, a vacuum, or a partial vacuum. A gas can comprise, for example, air. Where two retainment regions are separated by a fluid flow modulator, one retainment region can comprise, for example, an aqueous or non-aqueous fluid retained therein, while the other retainment region can comprise a gas or a vacuum or partial vacuum, contained therein. In various embodiments, the device can be manufactured to provide a vacuum on one or more sides of a dissolvable valve, for example, to achieve a pressure of from about 0.01 to about 0.99 atm, or from about 0.1 to about 0.5 atm.

[0028] The term “retainment region” means any area that can comprise a reagent or other reaction component for a reaction where the retainment region is in fluid communication with, fully separate from, or partially separate from, another retainment region that can comprise another reagent or reaction component for the reaction that is the same as or different from the first reagent. A first retainment region can be separate from a second retainment region, or a first retainment region can be surrounded by a second retainment region, where the first and second retainment regions are separated by a barrier comprising a shaped-wall.

[0029] A retainment region can comprise any area, structure, or form, capable of retaining a volume of fluid. A retainment region can be used, for example, to retain, process, react, store, incubate, transfer, purify, or the like, a fluid sample. A retainment region can comprise a surface area, an area, a recess, a reservoir, a chamber, a depression, a well, a space, or the like. According to some embodiments, a retainment region can comprise, for example, a flat surfaces with hydrophobic regions surrounding hydrophilic loci for receiving, containing, retaining, or binding a sample. A retainment region can comprise any shape, for example, round, teardrop, square, polygon, star, irregular, ovoid, rect-

angular, or the like. A retainment region or fluid processing passageway can comprise any cross-section configuration, for example, square, round, ovoid, irregular, trapezoid, or the like.

[0030] The terms “reservoir,” “retainment region,” and “region,” are used synonymously herein.

[0031] The term “reagent for reaction,” means one or more reagents or components necessary or desirable for use in one or more reactions or processes, for example, one or more components that in any way affect how a desired reaction can proceed. The reagent for reaction can comprise a reactive component. However, it is not necessary that the reagent participate in the reaction. The reagent for reaction can comprise a non-reactive component. The reagent for reaction can comprise a recoverable component comprising for example, a solvent and/or a catalyst. The reagent for reaction can comprise a promoter, accelerant, or retardant that is not necessary for a reaction but affects the reaction, for example, affects the rate of the reaction. The reagent for reaction can comprise one or more of a solid reagent for reaction and a fluid reagent for reaction. The term “reaction component” is used synonymous with the term “reagent for reaction,” as herein defined. The reagent for reaction can comprise one or more of a fluid and a solid. A retainment region can be pre-loaded with one or more reagents for reaction.

[0032] The term “vent” means any configuration or structure that relieves vacuum and/or back pressure, or equalizes pressure in a fluid processing device. A vent can comprise a channel or a microchannel. A vent can comprise a non-flow through vent in which gas that is displaced by a fluid can collect. A non-flow through vent can comprise, for example, a hydrophobic vent.

[0033] According to various embodiments, suitable reactions or processes can comprise one or more of a sample preparation process, a washing process, a sample purification process, a pre-amplification process, a pre-amplified product purification process, an amplification process, an amplified product purification process, a separation process, a sequencing process, a sequencing product purification process, a labeling process, a detecting process, or the like. Processing components can comprise sample preparation components, purification components, pre-amplification reaction components, amplification reaction components, sequencing reaction components, or the like. The skilled artisan can readily select and employ suitable components for a desired reaction or process, without undue experimentation.

[0034] According to some embodiments, processing or reaction components can be disposed in one or more retainment regions, channels, or fluid processing passageways, using any methods known in the art. For example, components can be sprayed and dried, delivered using a diluent, injected using a capillary, a pipette, and/or a robotic pipette, or otherwise disposed in the regions or fluid processing passageways.

[0035] According to various embodiments, a fluid processing device is provided that can comprise one or more fluid processing passageways that can comprise one or more elements, for example, one or more of a channel, a branch channel, a valve, a flow splitter, a vent, a port, an access area, a via, a bead, a reagent containing bead, a cover layer, a

reaction component, any combination thereof, and the like. Any element can be in fluid communication with another element.

[0036] The term “fluid communication” means either direct fluid communication, for example, two regions can be in fluid communication with each other via an unobstructed fluid processing passageway connecting the two regions or can be capable of being in fluid communication, for example, two regions can be capable of fluid communication with each other when they are connected via a fluid processing passageway that can comprise a valve disposed therein, wherein fluid communication can be established between the two regions upon actuating the valve, for example, by dissolving a dissolvable valve disposed in the fluid processing passageway.

[0037] The term “in fluid communication” refers to in direct fluid communication and/or capable of direct fluid communication, unless otherwise expressly stated. The term “in valved fluid communication” refers to elements wherein a valve is disposed between the elements, such that upon opening or actuating the valve, fluid communication between the elements is established.

[0038] According to some embodiments, the term “capillary flow” means passive flow resulting from a capillary potential gradient or a surface potential gradient, created during device fabrication that can direct the flow of liquid via capillary effect (surface tension).

[0039] According to some embodiments a fluid processing device is provided. The device can comprise a substrate that can comprise, for example, a top or a first surface, and one or more fluid processing passageways that can be provided in communication with and/or can be defined by, for example, at least a portion of the top or first surface of the substrate. The one or more fluid processing passageways can be provided, for example, in a top or first surface of a substrate, on a top or first surface of a substrate, in a bottom or second surface of a substrate, on a bottom or second surface of a substrate, in an edge of a substrate, on an edge of a substrate, or any combination thereof. A fluid processing device can comprise different levels and layers of fluid processing passageways that can comprise, for example, different levels and layers of fluid processing passageways and regions. For example, a tiered, multi-channel device can comprise one or more fluid processing passageways that traverse different heights or levels in the substrate.

[0040] Throughout the application, descriptions of various embodiments use “comprising” language; however, it will be understood by one of skill in the art, that in some specific instances, an embodiment can alternatively be described using the language “consisting essentially of” or “consisting of.”

[0041] For purposes of better understanding the present teachings and in no way limiting the scope of the teachings, it will be clear to one of skill in the art that the use of the singular includes the plural unless specifically stated otherwise. Therefore, the terms “a,” “an” and “at least one” are used interchangeably in this application.

[0042] Unless otherwise indicated, all numbers expressing quantities, percentages or proportions, and other numerical values used in the specification and claims, are to be

understood as being modified in all instances by the term “about.” Accordingly, unless indicated to the contrary, the numerical parameters set forth in the following specification and attached claims are approximations that may vary depending upon the desired properties sought to be obtained. In some instances, “about” can be understood to mean a given value $\pm 5\%$. Therefore, for example, about 100 nl, could mean 95-105 nl. At the very least, each numerical parameter should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

[0043] As used herein, the term “plurality” means “two or more.” Herein, the term “two or more” is used synonymously with the term “plurality.”

[0044] A user can operate the diagnostic device by injecting a sample into the sample retainment region, prior to, at the same time as, or subsequent to pushing a button or otherwise applying pressure to the retainment regions that contain unreacted reagents. For example, a user can inject a sample and then push a button or other feature or area of the device. As an example of an assay performed with a device according to various embodiments, a typical ligation assay for detection of oligo-nucleotides can include constituents comprising the sample, a ligation oligomer, ligation reagent which can be a mixture of enzyme and buffer, a wash buffer, and extension and detection reagents. The sample, the ligation oligomer, and the ligation reagent can be allowed to mix and react along with wash buffers and the extension and detection reagents in an automatically controlled process. The process can occur after a user has injected the sample into the sample retainment region and has released the reagents from the unreacted reagent retainment regions by applying pressure to those retainment regions.

[0045] According to various embodiments, a diagnostic device can be provided that uses capillary driven flow for fluid actuation. The flow cross-section of the fluid processing passageways interconnecting the various retainment regions can contribute to the rate at which the reagents and sample are mixed in the reaction retainment region. Valves placed within the flow control fluid processing passageways interconnecting the retainment regions can provide automatic flow control and timing of the fluid actuation.

[0046] According to various embodiments, a fluid flow modulator, as exemplified below with reference to a valve in a flow control passageway interconnecting retainment regions, can comprise a material that dissolves when brought into contact with a fluid having desired characteristics. Herein, the phrase “dissolvable valve” will be used interchangeably with the phrase “solute bridge valve.” The solute bridge valve can automatically control flow through the fluid processing passageway interconnecting the retainment regions and control the timing of fluid actuation by exploiting the time it takes to dissolve, melt, or otherwise wash-away or reduce the volume of the material making up the solute bridge valve.

[0047] According to various embodiments, the fluid processing device can comprise a fluid processing passageway, a plurality of retainment regions with at least two of the retainment regions each being in fluid communication with the fluid processing passageway, and a fluid flow modulator arranged in the fluid processing passageway and adapted to open and form, or to increase in size, a fluid communication

between the at least two retainment regions. The fluid flow modulator can comprise at least one of a polyethylene glycol material, a derivative of a polyethylene glycol material, or a combination thereof. The fluid flow modulator can comprise a material that is adapted to dissolve when contacted with water at room temperature. At least one of the plurality of retainment regions can comprise an aqueous fluid retained therein.

[0048] According to various embodiments, the fluid processing device comprises a fluid flow modulator in the form of a valve. The valve can block fluid flow through a fluid processing passageway.

[0049] The fluid flow modulator can be in the form of a valve that only partially blocks fluid flow through the fluid processing passageway.

[0050] According to various embodiments, the fluid flow modulator can comprise at least one of a polyethylene glycol material and a derivative of a polyethylene glycol material, having a molecular weight of from about 500 Daltons to about 5,000,000 Daltons. The fluid flow modulator can comprise at least one of a polyethylene glycol material and a derivative of a polyethylene glycol material, having a melting point of from about 35° C. and about 65° C.

[0051] According to various embodiments, the fluid processing device comprises a fluid processing passageway dimensioned so that a flow of fluid from at least one of two or more retainment regions and through the fluid processing passageway, can occur by capillary action. One or more maximum dimensions of about 5 millimeter or less, for example, about 2 millimeters or less, or about 1 millimeter or less.

[0052] According to various embodiments, the fluid processing device comprises a fluid processing passageway dimensioned so that a migration of charged components in a fluid, from at least one of the retainment regions through the fluid processing passageway, is capable of migration by electrokinetic action. One or more maximum dimensions of about 5 millimeter or less, for example, about 2 millimeters or less, or about 1 millimeter or less.

[0053] According to various embodiments, the fluid processing device can comprise at least two electrodes disposed in the device with a fluid processing passageway therebetween. A system can be provided that includes electrical leads that can be electrically connected to the electrodes.

[0054] According to various embodiments, the fluid processing device can further comprise at least one additional retainment region, at least one additional fluid processing passageway, and at least one pressure-actuatable valve arranged in the at least one additional fluid processing passageway. The additional fluid processing passageway can be in fluid communication with the additional retainment region and one or more other retainment regions. The pressure-actuatable valve can comprise a frangible diaphragm. The frangible diaphragm can comprise a material that is insoluble in water at room temperature. The pressure-actuatable valve can comprise a burstable valve that is adapted to open and establish fluid communication only upon receiving pressure of at least about 0.1 psig, for example, at least about 0.5 psig, at least about 1 psig, or at least about 3 psig from a fluid in at least one additional

retainment region. The device can comprise a liquid retained in at least one additional retainment region.

[0055] According to various embodiments, the fluid processing device can comprise at least one heat-actuatable valve arranged in at least one additional fluid processing passageway. The at least one additional fluid processing passageway can be in fluid communication with at least one additional retainment region and at least one of the plurality of retainment regions. The heat-actuatable valve can comprise at least one material selected from a rubber, a plastic, a wax, a paraffin, a polyethylene glycol material, a derivative of a polyethylene glycol material, a polysaccharide, a derivative of polysaccharide, and combinations thereof. The heat-actuatable valve can comprise a material that is insoluble in water at room temperature. The heat-actuatable valve can comprise a material that has a melting point of from about 35° C. to about 95° C., for example, from about 35° C. to about 70° C., from about 35° C. to about 65° C., or from about 35° C. to about 50° C.

[0056] According to various embodiments, the fluid processing device can comprise a liquid retained in at least one retainment region. The fluid processing device can comprise a first reagent for a reaction, retained in at least a first one of the plurality of retainment regions. The fluid processing device can comprise a second reagent for the reaction retained in at least a second one of the plurality of retainment regions. The second reagent can be the same as, or can differ from, the first reagent.

[0057] According to various embodiments, the fluid processing device comprises a fluid flow modulator that comprises a substituted polyethylene glycol material. An exemplary substituted polyethylene glycol comprises poly(ethylene glycol) methyl ether. The fluid flow modulator comprises a polyethylene glycol derivative. An exemplary polyethylene glycol derivative can comprise a triblock copolymer of polyethylene oxide and polypropylene oxide. The fluid flow modulator can comprise a branched polyethylene glycol or derivative thereof. Exemplary substituted polyethylene glycol materials are shown in Table 1 below:

TABLE 1

Examples for Substituted Poly(ethylene glycol)s													
$R_1-Q-(CH_2)_p-(OCH_2CH_2)_m-(CH_2)_q-G-R_2$													
#	Trade Name	Chemical Name	R ₁	R ₂	G	Q	m	p	q	mp (° C.)	Ca. M _n (Da)	HLB	Supplier
1	Brij® 56	poly(ethyleneglycol) cetyl ether	C ₁₆ H ₃₃	H	O	O	—	zero	zero	32–34	683	12.9	ICI Americas, Norwich, NY
2	Brij® 58	poly(ethyleneglycol) cetyl ether	C ₁₆ H ₃₃	H	O	O	—	zero	zero	38–43	1124	15.7	ICI Americas, Norwich, NY
3	Brij® 76	poly(ethyleneglycol) stearyl ether	C ₁₈ H ₃₇	H	O	O	—	zero	zero	37–39	711	12.4	ICI Americas, Norwich, NY
4	Brij® 78	poly(ethyleneglycol) stearyl ether	C ₁₈ H ₃₇	H	O	O	—	zero	zero	44–66	1152	15.3	ICI Americas, Norwich, NY
5	Brij® 700	poly(ethyleneglycol) stearyl ether	C ₁₈ H ₃₇	H	O	O	—	zero	zero	51–54	4670	18.8	ICI Americas, Norwich, NY
6	—	Poly(ethylene glycol) distearate	C ₁₇ H ₃₅ CO	OCC ₁₇ H ₃₅	O	O	—	2	2	35–37	930	—	Aldrich Chemical, Milwaukee, WI
7	—	Poly(ethylene glycol) distearate	C ₁₇ H ₃₅ CO	OCC ₁₇ H ₃₅	O	O	—	2	2	52–57	12500	—	Polysciences, Warrington, PA
8	—	Poly(ethylene glycol) bis(3-aminopropyl) ether	H ₂ N(CH ₂) ₃	H ₂ N(CH ₂) ₃	O	single bond	~34	zero	zero	49	—	—	Aldrich Chemical, Milwaukee, WI
9	—	Poly(ethylene glycol) bis(carboxymethyl) ether	HO ₂ CCH ₂	CH ₂ CO ₂ H	O	single bond	—	zero	zero	—	600	—	Aldrich Chemical, Milwaukee, WI
10	—	Poly(ethylene glycol) methyl ether	CH ₃	H	O	O	—	zero	zero	20	550	—	Aldrich Chemical Milwaukee, WI

TABLE 1-continued

Examples for Substituted Poly(ethylene glycol)s													
$R_1-Q-(CH_2)_p-(OCH_2CH_2)_m-(CH_2)_q-G-R_2$													
#	Trade Name	Chemical Name	R ₁	R ₂	G	Q	m	p	q	mp (° C.)	Ca. M _n (Da)	HLB	Supplier
11	—	Poly(ethylene glycol) methyl ether	CH ₃	H	O	O	—	zero	zero	30	750	—	Aldrich Chemical, Milwaukee, WI
12	—	Poly(ethylene glycol) methyl ether	CH ₃	H	O	O	—	zero	zero	52	2000	—	Aldrich Chemical, Milwaukee, WI
13	—	Poly(ethylene glycol) methyl ether	CH ₃	H	O	O	—	zero	zero	59	5000	—	Aldrich Chemical Milwaukee, WI
14	—	Poly(ethylene glycol) methyl ether	CH ₃	CH ₃	O	O	—	zero	zero	42	1000	—	Aldrich Chemical, Milwaukee, WI

[0058] Exemplary derivatives of PEG can include those shown in the Table 2 below:


TABLE 2

Derivatives of PEG*			
$HO-(CH_2CH_2O)_x-(CH_2\overset{\text{CH}_3}{\underset{ }{\text{CHO}}})_n-(CH_2CH_2O)_y-H$			
Trade name	Average Molecular Weight	Melting Pt (° C.)	HLB
Pluronic ®F38	4700	48	>24
Pluronic ®F77	6600	48	>24
Pluronic ®F87	7700	49	>24
Pluronic ®F68	8400	52	>24
Pluronic ®F88	11400	54	>24
Pluronic ®F127	12600	56	18-23
Pluronic ®F108	14600	57	>24
Pluronic ®F98	13000	58	>24

*Triblock copolymers of PEO and PPO (BASF, Mount Olive, NJ)


[0059] The fluid processing device can comprise a plurality of fluid flow modulators, wherein each fluid flow modulator comprises at least one of a polyethylene glycol material, a derivative of a polyethylene glycol material, and a combination thereof. Each of the plurality of fluid flow modulators can be adapted to dissolve when contacted with water at room temperature.

[0060] According to various embodiments, a barrier or fluid flow modulator can comprise a material having the formula:




wherein:

G and Q are each independently a single bond, O, N,



R₁ and R₂ are each independently H, OH, NH₂, O(C_nH_{2n+1}), O(C_nH_{2n-1}), CH₂OH,



R₉, R₁₀, R₁₁, R₁₂, R₁₃, and R₁₄, are each independently O, S, or NH;

p and q are each independently 0, 1, 2; or 3,


m is an integer from 0 to about 10,000;

at least one of p, q, and m is an integer greater than 0;

g is an integer from 2 to about 20; and


n is an integer from 1 to about 20. The barrier or fluid flow modulator can comprise a material having the formula:

Formula 2



wherein:

R_4 , R_5 , and R_6 are each independently H, OH, NH_2 , $O(C_nH_{2n+1})$, $O(C_nH_{2n-1})$, CH_2OH ,




u is an integer from 0 to about 10,000;

g is an integer from 2 to about 20;

n is an integer from 1 to about 20;


t , v , and z are each independently an integer from 0 to about 10,000; and

at least one of t , u , and v , is an integer greater than 0. The barrier or fluid flow modulator can comprise a material having the formula:




wherein:

A and B are each independently a single bond, O, N,



R_7 and R_8 are each independently H, OH, NH_2 , $O(C_nH_{2n+1})$, $O(C_nH_{2n-1})$, CH_2OH



R_3 is C_nH_{2n} , C_nH_{2n-2} , or $CH_2CH(CH_3)O$;


R_9 , R_{10} , R_{11} , R_{12} , R_{13} and R_{14} , can each independently be O, S, or NH;

a , b , r , and s are each independently 0, 1, 2; or 3,

x and y are each independently an integer from 1 to about 10,000;



g is an integer from 2 to about 20; and

n is an integer from 1 to about 20. The barrier or fluid flow modulator can comprise a material having the formula:




wherein:

A , G , and Q are each independently a single bond, O, N,



R_1 , R_2 , R_4 , and R_5 are each independently H, OH, NH_2 , $O(C_nH_{2n+1})$, $O(C_nH_{2n-1})$, CH_2OH ,



SO_4H ;

R_9 , R_{10} , R_{11} , R_{12} , R_{13} , and R_{14} , are each independently O, S, or NH;

f is an integer from 1 to about 10,000;

p and q are each independently 0, 1, 2, or 3;

m is an integer from 0 to about 10,000;

at least one of p , q , and m is an integer greater than 0;

g is an integer from 2 to about 20; and

n is an integer from 1 to about 20.

[0061] According to various embodiments, a fluid processing device can comprise a substrate, a plurality of retainment regions formed in or on the substrate, and a barrier at least partially separating a first retainment region from a second retainment region. The barrier can comprise at least one of a polyethylene glycol material, a derivative of a polyethylene glycol material, and a combination thereof, as described above with reference to the fluid flow modulator. The barrier can be adapted to dissolve when contacted with water at room temperature. The barrier can be included in a device as described above with reference to devices including a fluid flow modulator, in place of, or in addition to one or more fluid flow modulators. The barrier can be in the form of a fluid flow modulator.

[0062] According to various embodiments, a method is provided that comprises processing a fluid processing device that comprises at least a first retainment region and a second retainment region, and a barrier arranged between them. At least one of the first and second retainment regions retains an aqueous solution. The barrier can comprise at least one of a polyethylene glycol material, a derivative of a polyethylene glycol material, and a combination thereof. The barrier is adapted to dissolve when contacted with the aqueous solution. According to various embodiments, the method includes contacting the barrier with the aqueous solution to dissolve at least a portion of the barrier and form, or increase the size of, a fluid communication between the first retainment region and the second retainment region. The fluid processing device can comprise at least one additional retainment region, at least one fluid processing passageway, and at least one pressure-actuable valve arranged in the at least one fluid processing passageway. The at least one fluid processing passageway can be in fluid communication with the at least one additional retainment region and at least one of the first retainment region and the second retainment region. The method can comprise opening the pressure-actuable valve. The pressure-actuable valve can com-

prise a diaphragm and the method can comprise bursting the diaphragm by applying pressure to the diaphragm. A heat-actuable valve can be actuated instead of, or in addition to, actuation of a pressure-actuable valve.

[0063] According to various embodiments, the method can comprise migrating charged components in a sample from at least one of the at least two retainment regions, through the fluid processing passageway, by electrokinetic motion. Migration of the charged components can be accomplished by creating an electric field in the device. A system can be provided that includes an electric field generator.

[0064] According to various embodiments, a method can comprise creating a pressure differential between a first retainment region and a second retainment region, and moving, with the pressure differential, a fluid from one of the first retainment region and the second retainment region into the other of the first retainment region and the second retainment region. The pressure differential can be generated by activating a pump. The pressure differential can comprise a positive-pressure differential or negative-pressure differential. A positive pressure means a pressure at or greater than atmospheric pressure, i.e., 1 atm. A negative pressure means a pressure less than atmospheric pressure, i.e. less than 1 atm.

[0065] According to various embodiments, the method can comprise creating a magnetic field across a first retainment region and a second retainment region, and moving, with the magnetic field, magnetically attractable materials from one of the retainment regions toward the other retainment region.

[0066] According to various embodiments, the method can comprise performing a set of predetermined assays in a plurality of retainment regions, for example, retainment regions, in a closed, disposable device. An exemplary device is a cuvette. The retainment regions can be interconnected by fluid processing passageways but closed to fluid flow to or from locations outside of the cuvette. The first retainment regions can be selectively closed-off from fluid communication with second retainment regions through first channels that interconnect them. Selective closing-off can be provided by pressure-actuated valves positioned in the first channels. The second retainment regions can be interconnected to third retainment regions by second channels. Flow through the second channels can be controlled by fluid flow modulators positioned in the second channels, which can also provide selective closing-off. The method can comprise applying pressure to a pressure-actuated valve in a first channel sufficient to break the valve and provide fluid communication between the first and second retainment regions. Such a method can be used to introduce a sample for testing or other processing into one or more third retainment regions and/or establishing fluid communication between the second retainment regions and one or more third retainment regions, at a controlled rate. The controlled rate can be a function of characteristics of at least one of, a fluid in a third retainment region and a fluid within the second retainment regions.

[0067] According to various embodiments, a system is provided that comprises a fluid processing device as described herein, and a pump, wherein the pump is arranged in fluid communication with at least one of a fluid processing passageway and one or more retainment regions.

[0068] A system can be provided that comprises a fluid processing device as described herein, a power source, and at least two electrical leads forming electrical connections, respectively, between the power source and the at least two electrodes. A system can be provided that comprises a fluid processing device as described herein, and a magnet, wherein the magnet generates a magnetic field and the fluid processing device is arranged at least partially within the magnetic field.

[0069] Exemplary devices and methods according to various embodiments are described below with reference to the drawings. The present teachings are not limited to the embodiments depicted in the drawings.

[0070] Referring to FIGS. 1(a)-1(c), a schematic illustration of the process by which a solute bridge valve establishes fluid communication between two passageways, according to various embodiments, is shown. FIG. 1(a) shows two retainment regions 20, 24 containing fluids 30, 32, respectively, with the two retainment regions 20, 24 being interconnected through a fluid processing passageway 26. A solute bridge valve 22 can consist of a plug of material that completely or partially blocks the flow fluid processing passageway 26 and separates the fluids, e.g. solvents, reagents or other materials, in the respective retainment regions 20, 24. In some embodiments, one or both of fluids 30 or 32, can, at least initially, comprise a gas, a vacuum, a partial vacuum, and/or a pressurized fluid.

[0071] FIG. 1(b) shows the size of the solute bridge valve 22 decreasing as the material that makes up the solute bridge valve gradually dissolves into one or both of the fluids 30, 32 in retainment regions 20, 24. FIG. 1(c) shows that the fluids 30, 32 have come into contact with each other when the material making up solute bridge valve 22 has completely dissolved. The time required to completely dissolve the solute bridge valve 22 can be determined by the cross-sectional area and/or shape of the capillary flow passage 26 and the length and dissolvability of the solute bridge valve 22. By controlling the material and/or size of the solute bridge valve 22, it is also possible to control the length of the time elapsed before the solute bridge valve has completely dissolved to allow mixing of the fluids 30, 32.

[0072] It is desirable for the material that makes up the solute bridge valve 22 to be a material that dissolves into the fluids 30, 32. The material of the solute bridge valve also is desirably compatible with the assay to be conducted, and would not adversely affect the assay condition. The solute bridge valve material could also be an active ingredient that might catalyze or react with constituents of the assay. Examples of material that can be used to make up the solute bridge valve 22 include polyethyleneglycol (PEG) and derivatives of polyethyleneglycol, together referred to herein as PEG. PEG has desirable properties and some PEG materials can dissolve in aqueous liquids, such as those typically used in many biological assays. PEG is generally inert and generally does not affect biological assays. PEG is easy to pattern using microfabrication techniques. PEG can be formulated that melts at relatively low temperatures, i.e. 35-50° C., and can be used as a thermal "wax." PEG solutions are known to prevent non-specific binding and precipitation of proteins and peptides on walls of the fluid processing passageways. PEG is hygroscopic and stabilizes proteins in solutions.

[0073] According to various embodiments, the solute bridge valve 22 can be made from a material that partially or completely separates the retainment regions 20, 24 in the diagnostic device. Flow control through the fluid processing passageway 26 can be affected by the change in the open cross-sectional area of the fluid processing passageway between the two retainment regions, subsequent to the change in volume of the material. The actuation of the solute bridge valve 22 can comprise the volumetric change of the material resulting from contact with the solution or solutions in the retainment regions 20, 24. A change in volume of the material can result from other characteristics of the solution or solutions, such as temperature, water content, chemical composition, electrical charge, magnetic properties, or the like. If the material making up the solute bridge valve 22 completely blocks the fluid processing passageway 26, the two retainment regions 20, 24 are completely separated and the valve is closed.

[0074] FIG. 2 shows an embodiment of an assay device that uses capillary driven flow and solute bridge valves to control a specific sequence of fluid actuation steps. The device shown in FIG. 2 can be constructed as a microfluidic chip manufactured using microfabrication techniques. According to various embodiments, the chip can comprise a set of fluid retainment regions and microchannels for housing different liquids such as reagents, samples, etc., and for mixing and reacting the various liquids. FIG. 2 shows a device according to various embodiments having a sample fluid retainment region 90 connected through a fluid flow passage 80 to a reaction retainment region 48. An intermediate retainment region or retainment regions is/are connected through a fluid processing passageway 170 containing a valve 70 to the reaction retainment region 48. A second intermediate retainment region 46 is connected through a fluid processing passageway 172 containing a valve 72 to the reaction retainment region 48. A first reagent retainment region 40 for containing unreacted reagents 120 can be connected through a fluid flow passage 160 containing a valve 60 to one intermediate retainment region 44, while a second reagent retainment region 42 containing unreacted reagents 124 can be connected through a fluid flow passage 162 containing a valve 62 to the second intermediate retainment region 46. The reaction retainment region 48 is connected through a fluid processing passageway 174 containing a valve 74 to a first waste retainment region 50. The waste retainment region 50 can also be connected, through another fluid processing passageway 176 containing a valve 76, to a second waste retainment region 52.

[0075] Reagent retainment regions 40, 42 can be selectively separated from the intermediate retainment regions 44, 46 by the pressure actuated valves 60, 62 placed within the fluid flow passages 160, 162. According to various embodiments, the pressure actuated valves 60, 62 within fluid processing passageways 160, 162 can be diaphragms that are burstable upon pressure being applied to the reagent retainment regions 40, 42.

[0076] The intermediate retainment regions 44, 46 can be in turn connected through the fluid flow passages 170, 172 containing valves 70, 72 to the reaction retainment region 48. Fluid communication through the fluid flow passages 170, 172 containing valves 70, 72 can be controlled by the fluid flow cross-sectional area of the passages 170, 172 as well as the positioning of solute bridge valves 70, 72 as

discussed above, within the fluid flow passages 170, 172. The solute bridge valves 70, 72 contained within the fluid flow passages 170, 172 can provide automatic control of the fluid communication between the intermediate retainment regions 44, 46 and the reaction retainment region 48 as a result of their responsiveness to stimuli such as the chemical composition of the fluids within retainment regions 44, 46 and within reaction retainment region 48. Each of regions 90, 48, 40, 42, 50, and 52, can optionally comprise a vent 91, 49, 41, 43, 51, and 53, respectively.

[0077] FIG. 3 illustrates an embodiment wherein the retainment regions and fluid processing passageways are arranged such that solute bridge valves 70a, 72a, 74a, 76a corresponding to solute bridge valves 70, 72, 74, 76 of the embodiment shown in FIG. 2, are arranged in a line for ease of manufacture. Each of regions 90a, 48a, 40a, 42a, 50a, and 52a, can optionally comprise a vent 91a, 49a, 41a, 43a, 51a, and 53a, respectively.

[0078] FIGS. 4A-4J illustrate a sequence of events that can occur during operation of a diagnostic device according to various embodiments, such as exemplified in FIG. 2. FIGS. 4A-4J are explained in greater detail below. Each of regions 90, 48, 40, 42, 50, and 52, can optionally comprise a vent 91, 49, 41, 43, 51, and 53, respectively.

[0079] FIGS. 5A-5J illustrate a sequence of events that can occur during operation of a diagnostic device according to various embodiments, such as exemplified in FIG. 3. FIGS. 5A-5J are explained in greater detail below. Each of regions 90a, 48a, 40a, 42a, 50a, and 52a, can optionally comprise a vent 91a, 49a, 41a, 43a, 51a, and 53a, respectively.

[0080] In FIG. 4A a diagnostic device according to various embodiments is provided with retainment regions 40, 42 prefilled with, for example, a wash buffer 124 in retainment region 42 and a detection reagent 120 within retainment region 40. Pressure actuated valves 60, 62, such as burstable or tearable diaphragms, can be provided within the fluid flow passages 160, 162 separating retainment regions 40, 42 from intermediate retainment regions 44, 46.

[0081] In FIG. 4B a user can apply pressure to the retainment regions 40, 42, thereby actuating or bursting the valves 60, 62 within fluid flow passages 160, 162. Bursting valves 60, 62 can cause a flow of the buffers and/or reagents within the retainment regions 40, 42 into intermediate retainment regions 44, 46.

[0082] As shown in FIG. 4C a user can then inject a sample 126 into the sample retainment region 90, which is connected to the reaction retainment region 48 through a fluid flow passage 80. Sample injection could alternatively occur before or at the same time as bursting the valves. Fluid flow passages 170, 172 and 80 can be provided with fluid flow modulators, exemplified below with reference to a solute bridge valve, such as a plug of material that can change volume when exposed to certain stimuli. The solute bridge valves can control the fluid communication between intermediate retainment regions 44, 46 and reaction retainment region 48, as well as the fluid communication between the sample retainment region 90 and the reaction retainment region 48. Fluid flow of the sample from sample retainment region 90 into reaction retainment region 48 can also be automatically controlled as a result of the dimensions of the

fluid flow passage **80**. For example, the fluid flow passage **80** can be provided as a capillary passage such that the sample material from sample retainment region **90** gradually wicks into the reaction retainment region **48**, without the need for a solute bridge valve to control this flow through fluid flow passage **80**. Pressure can be relieved or equalized via vent **91** and/or **49**.

[0083] As shown in **FIG. 4D**, the sample material that is now in reaction retainment region **48** contacts the solute bridge valve **72** on one side of the valve **72** in fluid flow passage **172**, while the reagent in intermediate retainment region **46** contacts the solute bridge valve **72** from the opposite side of the valve. One or more of the reagent in retainment region **46** and/or the sample in reaction retainment region **48** begin to dissolve or otherwise affect the volume of the material making up the solute bridge valve **72**. After a certain amount of time that is automatically controlled by at least one of the flow cross-section of passage **172**, or the volume or composition of material at least partially making-up the solute bridge valve **72**, the solute bridge valve **72** no longer prevents the reagent in retainment region **46** from gradually diffusing into the sample **126** in reaction retainment region **48**, as shown in **FIG. 4E**. Pressure can be relieved and/or equalized via vent **43**.

[0084] The flow passage **174** leading from the reaction retainment region **48** into waste retainment region **50** can also be provided with dimensions that allow for capillary action, and a solute bridge valve **74** that will gradually dissolve or otherwise change volume as a result of contact with the fluid from reaction retainment region **48**. As shown in **FIG. 4F**, the effect of the fluid within reaction retainment region **48** on the solute bridge valve **74** within flow passage **174** gradually opens the flow passage **174** within which the valve **74** is positioned to allow fluid communication between the reaction retainment region **48** and the first waste retainment region **50**. The flow of fluid from reaction region **48** into waste region **50** through fluid processing passageway **174** contributes to a capillary flow of more reagent from reagent region **42** through fluid processing passageway **162** and intermediate region **46** into reaction region **48**. Pressure resulting from such flow can be relieved via vent **43** and/or vent **49**. Flow of fluid from reaction region **48** into waste region **50**, as shown in **FIG. 4G**, can also cause more of sample **126** to flow from sample region **90** into reaction region **48**. Pressure resulting from the flow of fluid from reaction region **48** into waste region **50**, can be relieved via vent **49** and/or vent **51**. According to various embodiments, the relative dimensions of the flow passages such as flow passage **80** leading from sample retainment region **90** into reaction retainment region **48**, and the flow passage **172** within which valve **72** is positioned leading from intermediate retainment region **46** into reaction retainment region **48**, can be selected in order to contribute to a preferential flow of fluid from the intermediate retainment region **46** into reaction retainment region **48**. A smaller flow cross-section through passage **80** than the flow cross-section through passage **172** would result in more fluid flowing from the reagent retainment region **42** and intermediate retainment region **46** into reaction retainment region **48** than the amount of sample flowing from sample retainment region **90** into the reaction retainment region **48**.

[0085] After a predetermined amount of time, solute bridge valve **70** provided in the flow passage **170** between

intermediate retainment region **44** and reaction retainment region **48** can also begin to dissolve, melt, or otherwise change in volume such that reagent **120** flows from reagent retainment region **40** through intermediate retainment region **44** and into the reaction retainment region **48**, as shown in **FIG. 4H**. The relative cross-sectional flow areas of the various flow passages connecting retainment regions as well as the amount of material provided in the solute bridge valves within the flow passages can be varied in order to control the amount of time it takes for the reagents and other fluids within the retainment regions to move from one retainment region to the next, thereby providing a control of the fluid handling steps.

[0086] After more time has passed, solute bridge valve **76** in flow passage **176** leading to a second waste retainment region **52** can begin to dissolve, melt, or otherwise change in volume such that fluid can flow from waste retainment region **50** into second waste retainment region **52**, as shown in **FIGS. 4I and 4J**. This flow can cause more of the reagents and sample to flow from regions **44**, **46** and **90** into reaction region **48**. Pressure can be relieved via vent **49** and/or vent **91**.

[0087] In an alternative embodiment, as exemplified in **FIG. 3** and **FIGS. 5A-5J**, the diagnostic device can comprise a set of retainment regions and microchannels corresponding to the retainment regions and microchannels of the embodiment exemplified in **FIGS. 2 and 4A-4J**, but with the solute bridge valves **72a**, **70a**, **74a**, and **76a** being aligned so that they can be formed as a single, extended length of solute bridge valve material. The length of the solute bridge valve material can include different portions of different respective composition. The process by which mixing of buffer and/or reagent from retainment regions **40a**, **42a**, and sample from sample retainment region **90a** is controlled automatically corresponds with the process described above for the embodiment shown in **FIG. 2** and **FIGS. 4A-4J**.

[0088] A sample solution can be added to sample retainment region **90a**, and supplied to a reaction retainment region **48a** through a capillary flow passage **80a**, as shown in **FIGS. 5C and 5D**. Solutions, such as reagents and/or wash buffers, can be dispensed from retainment regions **40a**, **42a** by pressing on the clear layer of film or other flexible covering over the retainment regions to cause pressure-actuated valves **60a**, **62a** in passageways **160a**, **162a** to burst and allow the solutions to move into intermediate retainment regions **44a**, **46a**. Solution from intermediate retainment region **46a** then begins to act on solute bridge valve **72a** in fluid flow passage **172a**, opening up a passageway for the solution to enter passage **80a** and reaction retainment region **48a**, as shown in **FIGS. 5D, 5E, 5F and 5G**. **FIG. 5H** illustrates solution from retainment region **44a** dissolving, or otherwise reducing the volume of solute bridge valve **70a** in passageway **170a**. Solute bridge valve **74a** in passageway **174a** has also dissolved in **FIG. 5H** to allow solution from the reaction retainment region **48a** to pass to a waste retainment region **50a**. As described above with regard to the embodiment of **FIG. 2**, the flow of solution from reaction region **48a** to waste region **50a** can create a suction that can draw more solution from region **46a** through fluid processing passageway **172a** and capillary fluid processing passageway **80a** into the reaction region **48a**, as shown in **FIG. 5I**. Solute bridge valve **76a** in fluid processing passageway **176a** then dissolves, allowing solution to flow to

waste region **52a**, and can create suction that can draw solution from region **44a** into reaction region **48a**, as well as drawing additional solution from region **46a** and additional sample from region **90a**, as shown in **FIG. 5J**. For example, vents **41** and **43** are needed in **40** and **42**, respectively, (**FIG. 4A**) in order to allow **120** and **124** to flow into **44** and **46**, respectively. Likewise, vent **91** is needed in communication with region **90**. A vent **49** can be provided in communication with regions **48** (**FIG. 4D**) such that **120**, **124** and **126** can flow into it. Without a vent, the air trapped in **48** can prevent any inflow of liquid. The same can apply to regions **50** and **52**.

[0089] The arrangement of retainment regions, passageways and valves of the various embodiments exemplified in **FIG. 3** provides for ease of manufacturing. As shown in **FIG. 3** and **FIGS. 5A-5J**, the solute bridge valves **70a**, **72a**, **74a**, and **76a** can be aligned with each other such that the solute bridge valves can be formed as one length of material. The diagnostic device **130** shown in **FIG. 6** exemplifies an embodiment wherein the solute bridge valves are formed as one extended length of solute bridge valve material **270** in a substrate **134** separate from a substrate **132**, within which various retainment regions such as retainment regions **140** and **142** are formed. When the two substrates **132** and **134** are sandwiched together to form the device **130**, the length of solute bridge valve material **270** can connect to passageways **260**, **262**, **264**, and **266**, as shown in **FIG. 7**, which passageways are connected to various retainment regions. As illustrated in **FIG. 7**, even if the two substrates **132**, **134** are not perfectly aligned, the length of solute bridge valve material **270** will still connect with the passageways **260**, **262**, **264**, and **266**. **FIG. 8** illustrates a situation wherein separate substrates for solute bridge valves **370**, **372** and passageways **360**, **362**, **364**, and **366**, are not perfectly aligned when forming a device as exemplified in the embodiment of **FIG. 2**. In this situation the solute bridge valves **370**, **372** would not connect to passageways **360**, **362**, and **364**, **366**.

[0090] Referring to **FIG. 9**, and according to various embodiments, retainment regions **444**, **446**, and **448** can be formed in a substrate **440**, with retainment region **444** interconnected with retainment region **448** through a passageway **470**, and retainment region **446** interconnected with retainment region **448** through a passageway **472**. Solution such as reagents and/or wash buffers can be retained in the retainment regions **444** and **446** by a flexible sheet of material **460** applied over the top surface of substrate **440** and adhered to the top surface by an adhesive layer **462**. Pressure actuated valves **470a**, **472a** can be positioned in the passageways **470**, **472** such that pressure applied to the solutions in retainment regions **444**, **446** by pressing down on the flexible sheet **460** over the respective retainment regions will dispense the solutions through passages **470**, **472** into the retainment region **448**. A barrier **450** can define an inner retainment region **430** and provide an automatically controlled interaction between the solution or solutions **442** in the retainment region **448** and a solution retained in the inner retainment region **430**. If desired, the barrier **450** can be formed from a solute material such as PEG that will gradually dissolve and thereby control the interaction between the solution or solutions **442** in outer retainment region **448** and a solution retained in the inner retainment region **430**.

[0091] According to various embodiments, and as exemplified by the embodiment shown in **FIG. 10**, a device can be provided that comprises a substrate **540** having a retainment region **542** formed in the substrate and covered by a sheet **560** that is adhered to the top surface of the substrate **540** by an adhesive **562**. An inner retainment region **530** can be defined within the retainment region **542** by a barrier **550** that can act as a fluid flow modulator between a solution in the outer retainment region **542** and a solution or material in the inner retainment region **530**. The barrier **550** can comprise a portion **552** made from a soluble material, and a portion **554** made from an insoluble material to provide a further degree of automatic control of the interaction between the solutions or other ingredients in retainment regions **542** and **530**. Sample and/or reagents can be injected into retainment regions **542** to initiate a process. A septum (not shown) can be provided as an injection port.

[0092] According to various embodiments, and as exemplified in the embodiment shown in **FIG. 11**, the substrate **700** can be provided with a retainment region **740** connected through a passage **770** having a pressure actuated valve **772** to a second retainment region **742**. Similarly, another retainment region **740a** can be connected through a passage **770a** having a pressure actuated valve **772a** to the second retainment region **742**. A star-shaped or otherwise polygonal retainment region **730** can be defined inside of the second retainment region **742** by a barrier **750**. All of the retainment regions can be covered by a sheet **760** adhered to the top surface of substrate **700** by an adhesive layer **762**. A solution within retainment region **740** can be dispensed through passage **770** by applying pressure to the sheet **760** over the retainment region **740** to force the liquid past the pressure actuated valve **772** into the second retainment region **742**. The barrier **750** can comprise a material such as PEG that gradually dissolves or melts in response to a stimuli such as characteristics of the solution that has been introduced to the second retainment region **742**, thereby providing an automatically controlled interaction between the solution in second retainment region **742** and the solution in retainment region **730**. In an exemplary device, fluid processing passageways could interconnect with each respective point of the star shape shown.

[0093] According to various embodiments, further control of the fluid handling steps can be provided by including various solute structures within the fluid processing passageways and/or the retainment regions. The solute structures can be selected to dissolve over a finite amount of time and change the flow properties of the fluidic circuit. As an example, raised structures (such as pillars of different aspect ratios) made from solute material (such as PEG) can be fabricated by photolithography inside the various retainment regions, retainment regions, and/or fluid processing passageways. The incorporation of these structures can cause the flow paths to have different capillarity and can cause capillary suction pressures of different magnitudes in different parts of the fluidic circuit. The structures can also introduce additional flow resistance, with a variation in the flow resistance depending on the dissolution of the solute structures.

[0094] In one example, an array of pillars made of PEG could be fabricated inside of the waste retainment regions **50**, **52**, in the embodiment of **FIG. 2**, or **50a**, **52a** in the embodiment of **FIG. 3**, which could, for example, cause

higher suction pressure in waste retainment region 50 or 50a by capillary action as compared to the suction pressure in reaction retainment region 48 or 48a. Over time, the solute structures within waste retainment region 50 or 50a would dissolve in the liquid, which could result in the capillary suction pressure into retainment region 50 or 50a reducing over time. Subsequent dissolution of a solute within fluid processing passageway 176 between waste retainment region 50 and waste retainment region 52, for example, could then result in the liquid in waste retainment region 50 being pulled into waste retainment region 52. The pulling can be as a result of a larger capillary suction pressure in waste retainment region 52 caused by solute structures in retainment region 52. The PEG cannot operate until 74 and 76 in FIG. 2 and 170a, 172a and 174a in FIG. 3 are open. The flow of 120, 125 and 126 in FIG. 2 into 44, 46, and 48, respectively, relies on capillary effect alone, and does not rely on vacuum created by the PEG in 50 or 52 because neither 76 nor 74 are open. PEG can facilitate fluid flow from 48 into 50 and/or 52 without a vent. The flow of 120, 124 or 126 into 44, 46, or 48, respectively, relies on capillary effect that requires air vents to prevent pressure build up.

[0095] Those skilled in the art can appreciate from the foregoing description that the present teachings can be implemented in a variety of forms. Therefore, while these teachings have been described in connection with particular embodiments and examples thereof, the true scope of the present teachings should not be so limited. Various changes and modifications can be made without departing from the scope of the teachings herein.

What is claimed:

1. A fluid processing device comprising:
 - a fluid processing passageway;
 - a plurality of retainment regions, at least two of the retainment regions each being in fluid communication with the fluid processing passageway; and
 - at least one fluid flow modulator arranged in the fluid processing passageway and being adapted to open to form, or to increase in size, a fluid communication between the at least two retainment regions, the fluid flow modulator comprising at least one of a polyethylene glycol material, a derivative of a polyethylene glycol material, and a combination thereof, and being adapted to dissolve when contacted with water at room temperature.
2. The fluid processing device of claim 1, wherein at least one of the plurality of retainment regions comprises aqueous fluid retained therein.
3. The fluid processing device of claim 1, wherein the at least one fluid flow modulator comprises at least one of a polyethylene glycol material and a derivative of a polyethylene glycol material, having a melting point of from about 35° C. and about 65° C.
4. The fluid processing device of claim 1, wherein the fluid processing passageway is dimensioned sufficient to cause capillary flow of a fluid from at least one of the at least two retainment regions through the fluid processing passageway.
5. The fluid processing device of claim 1, wherein the fluid processing passageway is dimensioned sufficient to cause electrokinetic migration of charged components in a

fluid, from at least one of the at least two retainment regions through the fluid processing passageway.

6. The fluid processing device of claim 5, further comprising at least two electrodes disposed in the device with the fluid processing passageway therebetween.

7. The fluid processing device of claim 1, further comprising:

at least one additional retainment region;


at least one additional fluid processing passageway; and

at least one valve comprising one or more of a pressure-actuable valve and a heat-actuable valve arranged in the at least one additional fluid processing passageway, wherein the at least one additional fluid processing passageway is in fluid communication with the at least one additional retainment region and at least one of the plurality of retainment regions.

8. A system comprising the fluid processing device of claim 1, and a pump, wherein the pump is arranged in fluid communication with at least one of the fluid processing passageway and one or more of the plurality of retainment regions.


9. A system comprising the fluid processing device of claim 6, a power source, and at least two electrical leads forming electrical connections, respectively, between the power source and the at least two electrodes.

10. The fluid processing device of claim 1, wherein the at least one fluid flow modulator comprises a material having the formula:




wherein

G and Q are each independently a single bond, O, N,



R₁ and R₂ are each independently H, OH, NH₂, O(C_nH_{2n+1}), O(C_nH_{2n-1}), CH₂OH,



R₉, R₁₀, R₁₁, R₁₂, R₁₃, and R₁₄, are each independently O, S, or NH,

p and q are each independently 0, 1, 2, or 3,


m is an integer from 0 to about 10,00,

at least one of p, q, and m is an integer greater than 0,


g is an integer from 2 to about 20, and

n is an integer from 1 to about 20;

Formula 2



R_4 , R_5 , and R_6 are each independently H, OH, NH_2 , $O(C_nH_{2n+1})$, $O(C_nH_{2n-1})$, CH_2OH ,




u is an integer from 0 to about 10,000,

g is an integer from 2 to about 20,

n is an integer from 1 to about 20,


t , v , and z are each independently an integer from 0 to about 10,000, and

at least one of t , u , and v , is an integer greater than 0;




wherein

A and B are each independently a single bond, O, N,



R_7 and R_8 are each independently H, OH, NH_2 , $O(C_nH_{2n+1})$, $O(C_nH_{2n-1})$, CH_2OH ,



R_3 is C_nH_{2n} , C_nH_{2n-2} , or $CH_2CH(CH_3)O$,

R_9 , R_{10} , R_{11} , R_{12} , R_{13} , and R_{14} , can each independently be O, S, or NH,


a , b , r , and s are each independently 0, 1, 2, or 3,

x and y are each independently an integer from 1 to about 10,000,

g is an integer from 2 to about 20, and


n is an integer from 1 to about 20; or

Formula 4




wherein:

A , G , and Q are each independently a single bond, O, N,



R_1 , R_2 , R_4 , and R_5 are each independently H, OH, NH_2 , $O(C_nH_{2n+1})$, $O(C_nH_{2n-1})$, CH_2OH ,



R_9 , R_{10} , R_{11} , R_{12} , R_{13} , and R_{14} , are each independently O, S, or NH,

f is an integer from 1 to about 10,000,

p and q are each independently 0, 1, 2, or 3,

m is an integer from 0 to about 10,000,

at least one of p , q , and m is an integer greater than 0,


g is an integer from 2 to about 20, and

n is an integer from 1 to about 20.

11. A fluid processing device comprising:


a fluid processing passageway; and

at least one fluid flow modulator arranged in the fluid processing passageway and being adapted to open to form, or increase the size of, a fluid communication through the fluid processing passageway, the at least one fluid flow modulator being adapted to dissolve when contacted with water at room temperature, and having the formula:




wherein

G and Q are each independently a single bond, O, N,



R_1 and R_2 are each independently H, OH, NH_2 , $O(C_nH_{2n+1})$, $O(C_nH_{2n-1})$, CH_2OH ,




R_9 , R_{10} , R_{11} , R_{12} , R_{13} , and R_{14} , are each independently O, S, or NH,

p and q are each independently 0, 1, 2, or 3,


m is an integer from 0 to about 10,000,
at least one of p, q, and m is an integer greater than 0,
g is an integer from 2 to about 20, and
n is an integer from 1 to about 20;

Formula 2



wherein

R₄, R₅, and R₆ are each independently H, OH, NH₂, O(C_nH_{2n+1}), O(C_nH_{2n-1}), CH₂OH,




u is an integer from 0 to about 10,000,

g is an integer from 2 to about 20,

n is an integer from 1 to about 20,

t, v, and z are each independently an integer from 0 to about 10,000, and


at least one of t, u, and v, is an integer greater than 0;




Formula 3

wherein

A and B are each independently a single bond, O, N,



R₇ and R₈ are each independently H, OH, NH₂, O(C_nH_{2n+1}), O(C_nH_{2n-1}), CH₂OH,



R₃ is C_nH_{2n}, C_nH_{2n-2}, or CH₂CH(CH₃)O,

R₉, R₁₀, R₁₁, R₁₂, R₁₃, and R₁₄, can each independently be O, S, or NH,


a, b, r, and s are each independently 0, 1, 2, or 3,

x and y are each independently an integer from 1 to about 10,000,

g is an integer from 2 to about 20, and




n is an integer from 1 to about 20; or

Formula 4




wherein

A, G, and Q are each independently a single bond, O, N,



R₁, R₂, R₄, and R₅ are each independently H, OH, NH₂, O(C_nH_{2n+1}), O(C_nH_{2n-1}), CH₂OH,



SO₄H;

R₉, R₁₀, R₁₁, R₁₂, R₁₃, and R₁₄, are each independently O, S, or NH,

f is an integer from 1 to about 10,000,

p and q are each independently 0, 1, 2, or 3,

m is an integer from 0 to about 10,000,

at least one of p, q, and m is an integer greater than 0,

g is an integer from 2 to about 20, and

n is an integer from 1 to about 20.

12. A fluid processing device comprising:

a substrate;

a plurality of retainment regions formed in or on the substrate, comprising at least a first retainment region and a second retainment region; and

a barrier at least partially separating the first retainment region from the second retainment region, wherein said barrier comprises at least one of a polyethylene glycol material, a derivative of a polyethylene glycol material, and a combination thereof, and being adapted to dissolve when contacted with water at room temperature.

13. The fluid processing device claim 12, wherein said barrier completely separates the first retainment region from fluid communication with the second retainment region.

14. The fluid processing device claim 12, wherein the barrier comprises at least one of a polyethylene glycol material and a derivative of a polyethylene glycol material, having a molecular weight of from about 500 Daltons to about 5,000,000 Daltons.

15. The fluid processing device of claim 12, further comprising:

at least one additional retainment region;


at least one fluid processing passageway; and

at least one valve comprising a pressure-actuatable valve or a heat-actuatable valve arranged in the at least one fluid processing passageway, wherein the at least one fluid processing passageway is in fluid communication with the at least one additional retainment region and at least one of the plurality of retainment regions.

16. The fluid processing device of claim 15, wherein the at least one valve comprises at least one pressure-actuatable valve comprising a burstable valve that is adapted to open and establish fluid communication only upon receiving pressure of at least about 1 psig from a fluid in the at least one additional retainment region.


17. The fluid processing device of claim 12, wherein the barrier comprises one or more of a substituted polyethylene glycol material, a polyethylene glycol derivative, and a branched polyethylene glycol, a derivative of a branched polyethylene glycol, and a combination thereof.

18. The fluid processing device of claim 12, wherein the barrier comprises a material having the formula:




wherein

G and Q are each independently a single bond, O, N,



R₁ and R₂ are each independently H, OH, NH₂, CH₃, C₂H₅, OCH₃, OC₂H₅, CH₂OH,



R₉, R₁₀, R₁₁, R₁₂, R₁₃, and R₁₄, are each independently O, S, or NH,

p and q are each independently 0, 1, 2, or 3,


m is an integer from 0 to about 10,000;

at least one of p, q, and m is an integer greater than 0,

g is an integer from 2 to about 20, and


n is an integer from 1 to about 20;

Formula 2



wherein

R₄, R₅, and R₆ are each independently H, OH, NH₂, CH₃, C₂H₅, OCH₃, OC₂H₅, CH₂OH,




u is an integer from 0 to about 10,000,

g is an integer from 2 to about 20,

n is an integer from 1 to about 20,


t, v, and z are each independently an integer from 0 to about 10,000, and

at least one of t, u, and v, is an integer greater than 0;




wherein

A and B are each independently a single bond, O, N,



R₇ and R₈ are each independently H, OH, NH₂, CH₃, C₂H₅, OCH₃, OC₂H₅, CH₂OH,



R₃ is C_nH_{2n}, C_nH_{2n-2}, or CH₂CH(CH₃)O,

R₉, R₁₀, R₁₁, R₁₂, R₁₃, and R₁₄, can each independently be O, S, or NH,


a, b, r, and s are each independently 0, 1, 2, or 3,

x and y are each independently an integer from 1 to about 10,000,

g is an integer from 2 to about 20, and


n is an integer from 1 to about 20; or


Formula 4



wherein:

A, G, and Q are each independently a single bond, O, N,





R₁, R₂, R₄, and R₅ are each independently H, OH, NH₂, CH₃, C₂H₅, OCH₃, OC₂H₅, CH₂OH,

$-(\text{---CH}_2\text{CH}_2\text{O---})_n\text{---H}$, CH₂CH₂CH₂NH₂,
CH₂CO₂H, C_gH_{2g-1}, or C_nH_{2n+1},

R₉, R₁₀, R₁₁, R₁₂, R₁₃, and R₁₄, are each independently O, S, or NH,

f is an integer from 1 to about 10,000,

p and q are each independently 0, 1, 2, or 3

m is an integer from 0 to about 10,000,

at least one of p, q, and m is an integer greater than 0,

g is an integer from 2 to about 20, and

n is an integer from 1 to about 20.

19. A method comprising:

providing a fluid processing device comprising at least a first retainment region and a second retainment region, and a barrier arranged between the first retainment region and the second retainment region, wherein at least one of the first and second retainment regions retains an aqueous solution, the barrier comprises at least one of a polyethylene glycol material, a derivative of a polyethylene glycol material, and a combination thereof, and the barrier is adapted to dissolve when contacted with the aqueous solution; and

contacting the barrier with the aqueous solution to dissolve at least a portion of the barrier and form, or

increase the size of, a fluid communication between the first retainment region and the second retainment region.

20. A method of performing a set of predetermined assays, comprising:

providing a plurality of retainment regions in a closed, disposable cuvette, the retainment regions interconnected by fluid processing passageways but closed to fluid flow to or from locations outside of the cuvette, the cuvette including:

first retainment regions;

second retainment regions;

first fluid processing passageways interconnecting the first retainment regions from the second retainment regions, wherein the first retainment regions are selectively closed-off from fluid communication with the second retainment regions by pressure-actuated valves positioned in the first fluid processing passageways;

one or more third retainment regions interconnected by second fluid processing passageways with at least the second retainment regions; and

fluid flow modulators positioned in the second fluid processing passageways;

applying pressure to the pressure actuated valves in the first fluid processing passageways sufficient to provide fluid communication between the first and second retainment regions;

introducing a sample for testing or other processing into the one or more third retainment regions; and

establishing fluid communication between the second retainment regions and the one or more third retainment regions at a controlled rate that is a function of characteristics of at least one of the sample in the one or more third retainment regions and a fluid within the second retainment regions.

* * * * *