US 20060195564A1

(19) **United States**

(12) **Patent Application Publication**

Accardi et al.

(10) **Pub. No.: US 2006/0195564 A1**

(43) **Pub. Date: Aug. 31, 2006**

(54) **MEDICAL DIAGNOSTIC SYSTEM SERVICE METHOD AND APPARATUS**

(76) Inventors: **Kenneth Lawrence Accardi**, Pewaukee, WI (US); **Deborah Ann Babula**, Franklin, WI (US); **George Peter Gesior**, Waukesha, WI (US); **Henry John Hummel JR.**, Waukesha, WI (US); **Ianne Mae Howards Koritzinsky**, Glendale, WI (US); **Scott Matt McOlash**, Wauwatosa, WI (US); **George Tzortzos**, Brookfield, WI (US); **Hubert Anthony Zettel**, Waukesha, WI (US)

Correspondence Address:
Patrick S. Yoder
FLETCHER YODER
P.O. Box 692289
Houston, TX 77269-2289 (US)

(21) Appl. No.: **11/416,778**

(22) Filed: **May 3, 2006**

Related U.S. Application Data

(63) Continuation of application No. 09/199,506, filed on Nov. 25, 1998.

Publication Classification

(51) **Int. Cl.**
G06F 15/173 (2006.01)

(52) **U.S. Cl.** **709/223**

(57) **ABSTRACT**

A system is provided for remotely servicing medical diagnostic systems. The diagnostic systems may include a range of modalities and system types. A remote service facility may be contacted by the diagnostic systems, or may contact the diagnostic systems via a network link. Service requests, messages, protocols, data and log files, and so forth, may be transmitted between the diagnostic systems and the service facility. The service requests are handled by the service facility interactively with the medical diagnostic systems. The diagnostic systems are thereby apprised of the status of service requests, service reports, and so forth. A uniform interface and platform are provided for facilitating interactive communications of service requests and data between the diagnostic systems and the service facility.




22
W
86
PS
84
DB
88
COMM.
82
NET
80
24
24
WS
72
78
74
70
76
48
62
COMM.
COMM.
32
COMM.
56
52
40
60
C
C
C
36
50
54
46
34
38
30
20
58
64
44
28
66
68
42
16
26
C
C
G
18
12
12
14
12
10

FIG. 1


104
F
88
DB
84
SERVICE CENTER PROCESSING SYSTEM
102
LOCAL DB
86
W
22
100
ROUTER
98
M
96
80
NET
70
WS
90
92
DIAG. SYS. 3
DIAG. SYS. 2
DIAG. SYS. 1
20
FE
18
16
12
14
24

FIG. 2


90
92
F
126
NET/ PPP
128
COMM. MOD.
106
124
CON. INTER
134
108
WB
WS
WP
110
112
WP
132
130
114
LIC MOD.
116
ADAPT MOD.
118
T
118
T
118
T
120
MODALITY C
122
SUB MOD.
122
SUB MOD.
122
SUB MOD.
12
DIAG. SYS.
DIAG. SYS.
DIAG. SYS.
12

FIG. 3


158
DEL
TO ROUTER 100
156
DB
104
FAX
REP SERV.
MESS SERV.
SOFT SERV.
TO ROUTER 100
150
152
154
148
SCH.
84
22
142
AN. SERV.
140
HTTP SERV.
144
LIC. SERV.
146
LIC. DB
136
AUTO SERV.
ENG. WS
86
138
94
HTTP SERV.
100
ROUTER
98
M
96

FIG. 4


160
VAL. MOD.
162
INFO MOD.
144
146
LIC. DB
POP. MOD.
164
168
POP. MOD.
SYS. INFO
166

FIG. 4A

FIG. 4B


170
172
REP. GEN MOD.
REP. ACC.
150
REP. STORE
174
DATA GATH.
176


92
F
128
COMM. MOD.
106
126
NET / PPP
124
CON. INTER
108
WB
WS
WP
112
WP
132
130
110
ACCESS MOD.
114A
116
ADAPT MOD.
180
FIELD SERV. APP.
180
FIELD SERV. APP.
24

FIG. 5

FIG. 6


180
SERVICE REQUEST
182
APPLICATIONS
184
SYSTEM REPORTS
186
MESSAGES
187
HELP
188
CLOSE
178
190
MOST RECENT MESSAGE
WHEN: WED JUL 29 17:15:45 CDT 2000
WHO: OLC, AUTOMATIC ACKNOWLEDGEMENT
MESSAGE: YOUR REQUEST FOR A SERVICE ENGINEER HAS BEEN RECEIVED. YOUR REFERENCE NUMBER IS: 123456
NEW MESSAGES: 1
110

FIG. 7


APPLICATIONS
REMOTE SERVICE
TIPS & WORKAROUNDS
194
MAIN SCREEN
180
SERVICE REQUEST
196
DOCUMENTS
198
PROTOCOLS
178
HELP
192
PROTOCOL DESCRIPTION:
DESCRIPTIONS OF THE DEFAULT PROTOCOLS ON YOUR SYSTEM.
TIPS NEWSLETTER:
TIPS ON HOW TO USE YOUR SYSTEM.
FREQUENT QUESTIONS:
20 MOST FREQUENTLY ASKED QUESTIONS ABOUT YOUR SYSTEM TYPE.
WORKAROUNDS:
TIPS AND RELEASE NOTES ABOUT YOUR SYSTEM TYPE.
200

FIG. 8


SERVICE REQUEST
REMOTE SERVICE
...YOUR FASTEST CONNECTION TO A REMOTE SERVICE ENGINEER...
MAIN SCREEN
194
180
SERVICE REQUEST
178
SERVICE CENTER PHONE
HELP
REASON FOR CONTACTING SERVICE FACILITY:
URGENT PROBLEM
APPS QUESTION
204
PROBLEM AREA
PRESCRIPTION
ARCHIVAL
IMAGE QUALITY
206
ACQUISITION
FILMING
OTHER
DISPLAY
NETWORKING
208
SUBMITTER:
SELECT NAME
OTHER:
PHONE:
SELECT PHONE NUMBER
OTHER:
IMAGE (EXAM /SERIES /IMAGE) ==>E
S
I
210
PROBLEM DESCRIPTION:
212
PROBLEM DATE /TIME:
8 /27 /00 13:21
214
216
SEND TO SERVICE CENTER
202

FIG. 9


SYSTEM REPORTS
REMOTE SERVICE
194
MAIN SCREEN
220
SERVICE HISTORY
224
SYSTEM USAGE
228
TUBE USAGE
226
MONITORING
HELP
178
218
SERVICE HISTORY
222
DESCRIPTION
TYPE
REFERENCE NUMBER
DATE
PM WAS COMPLETED.
FE
12345678
MAY 24 2000
SYSTEM DISK IS FULL.
REMOTE
910111213
JUN 09 2000
GANTRY TEMPERATURE ADJUSTMENT.
FE
141516171
JUN 22 2000
MAGNET WAS FILLED.
MAGNET MONITORING
81920212
JUL 03 2000

FIG. 10


MESSAGES
REMOTE SERVICE
194
MAIN SCREEN
CURRENT MESSAGES
232
SUBJECT
SOURCE
DATE
PM COMPLETED.
AUTOMATIC SERVICE MESSAGE
07 /22 /00 17:55
REPORTS AVAILABLE.
AUTOMATIC SERVICE MESSAGE
07 /29 /00 07:12
REFERENCE NUMBER ASSIGNED.
CONTACT SERVICE CENTER RESPONSE
07 /29 /00 17:15
CURRENT MESSAGES
SAVED MESSAGES
178
HELP
DATE: WED JUL 29 17:15:45 CDT 2000
SOURCE: "CONTACT SERVICE CENTER" RESPONSE
MESSAGE:
YOUR REQUEST FOR A SERVICE ENGINEER HAS BEEN RECEIVED.
YOUR REFERENCE NUMBER IS: GJD092265
YOU SHOULD RECEIVE A RESPONSE FROM AN ENGINEER WITHIN FIVE (5) MINUTES.
SAVE
DELETE
234
230

FIG. 11


REMOTE SERVICE
PROTOCOLS
CLICK ON THE IMAGE OF THE DESIRED PROTOCOL
238
MAIN SCREEN
194
SERVICE REQUEST
180
DOCUMENTS
196
PROTOCOLS
148
HELP
178
DESCRIPTION OF PROTOCOL NO. 1 AND PARAMETERS
242
DESCRIPTION OF PROTOCOL NO. 2 AND PARAMETERS
240
DESCRIPTION OF PROTOCOL NO. 3 AND PARAMETERS
242
DESCRIPTION OF PROTOCOL NO. 4 AND PARAMETERS
240
DESCRIPTION OF PROTOCOL NO. 5 AND PARAMETERS
242
DESCRIPTION OF PROTOCOL NO. 6 AND PARAMETERS
240
236

FIG. 12


252
ACCESS SERVICE PAGE
254
CHECK SUBSCRIBER STATUS
256
DIAL AND CONNECT
258
COMPOSE SERVICE REQ.
260
DATA REQ'D ?
YES
262
LOCATE AND STORE DATA
NO
264
FORMAT MESSAGE
266
PLACE MESSAGE IN QUEUE
268
TRANSMIT
270
RECEIVE ACKNOWLEDGEMENT
272
TRANSMIT DATA
250
274
DISPLAY MESSAGE
276
DISCONNECT
278
RECEIVE DATA PULL REQUEST, ACCESS STORED FILES & SEND

FIG. 13


282
RECEIVE REQUEST
284
DISPATCH OPEN ?
NO
YES
286
CREATE DISPATCH PLACE IN QUEUE
288
DISPATCH ASSIGNED ?
NO
YES
290
APPEND NOTE
304
CREATE DISPATCH
306
SEND MESSAGE WITH STATUS
308
POP-UP BOX TO ASSIGNED ENG.
310
ENG. ACCEPTED ?
NO
YES
312
ASSIGN TO SAME
292
SEND MESSAGE WITH NO./STATUS
294
NOTIFY MODALITY SERVICE ENG.
296
AUTO CALLBACK FOR SERVICE DATA
298
ACCESS, TRANSMIT, STORE DATA
300
CONNECT TO SERVICES FACILITY DATABASE
302
ACCESS, TRANSMIT, STORE DATA
280

FIG. 14


312
SITE REPORT REQUEST
314
FE REPORT REQUEST
316
TRANSMIT REQUEST
318
ACKNOWLEDGE
320
FEE FOR REPORT ?
NO
YES
322
PERFORM FEE / SUBSCR. LOGIC
324
CONNECT TO SYSTEM
326
PERIODIC TRIGGER
328
SWEEP FOR DATA
330
TRANSMIT SYS. DATA
332
UPDATE SERVICE DATA
334
DISCONNECT
336
PROCESS DATA
338
COMPLETE REPORT
340
CONNECT & NOTIFY / PUSH REPORT
342
SITE / FE PULL REPORT
310

FIG. 15


TRIGGER SUBSCRIP. SWEEP
352
ACCESS SITE SUBSCRIP. MANAGER
354
356
STATUS OK ?
NO
358
MODIFY / MESSAGE
YES
360
CONTINUE
362
CONNECT
364
TRANSMIT SERV. REQ./MESS.
366
ACCESS SUBSCRIP. REQ'M'T
368
ACCESS SITE SUBSCRIP. INDEX
370
SUBSCRIP. CHECK STATUS FLAG
372
STATUS OK ?
YES
NO
374
CONNECT
376
UPDATE NEEDED ?
YES
378
UPDATE
NO
380
STATUS OK ?
YES
382
CONTINUE
NO
384
NOTIFY
386
ORDER
388
VERIFY
390
UPDATE SUBSCRIP. INDEX
392
CONTINUE
350

FIG. 16


400
402
DEFINE PROGRAM
404
STORE PROGRAM
406
PUSH OR PULL ?
PULL
PUSH
412
DETERMINE SUBSCRIP. STATUS
COMPOSE MESSAGE(S)
414
408
DETERMINE SUBSCRIP. STATUS
410
COMPOSE MESSAGE(S)
416
CONNECT
420
REQUEST PROGRAM
422
CHECK SUBSCRIP. REQ'M'T
424
ACCESS SUBSCRIP. MANAG.
426
STATUS OK ?
NO
428
NOTIFY
YES
CONTINUE
430
CONNECT
432
TRANSMIT PROGRAM REQUEST
434
ACCESS SITE SUBSCRIP. INDEX
436
438
STATUS OK ?
NO
440
NOTIFY
YES
418
TRANSMIT MESSAGE (AND PROGRAM)
442
INSTALL
444
UPDATE SUBSCRIP. DATA
446
DISCONNECT
448
POST MESSAGE
450
DELAYED SEND OR SUBSCRIBER PULL
452
INSTALL
454
UPDATE SUBSCRIP. DATA

MEDICAL DIAGNOSTIC SYSTEM SERVICE METHOD AND APPARATUS

FIELD OF THE INVENTION

[0001] The present invention relates generally to the field of medical diagnostic and imaging systems. More particularly, the invention relates to interactive servicing of such systems, such as via remote service facilities, in which system configurations, image data and other files, protocols, service requests, reports and other useful information can be exchanged interactively between a remote service facility and the diagnostic system.

BACKGROUND OF THE INVENTION

[0002] Medical diagnostic and imaging systems are ubiquitous in modern health care facilities. Such systems provide valuable tools for identifying, diagnosing and treating physical conditions and greatly reduce the need for surgical diagnostic intervention. In many instances, final diagnosis and treatment proceed only after an attending physician or radiologist has complemented conventional examinations with detailed images of relevant areas and tissues via one or more imaging modalities.

[0003] Currently, a number of modalities exist for medical diagnostic and imaging systems. These include computed tomography (CT) systems, x-ray systems (including both conventional and digital or digitized imaging systems), magnetic resonance (MR) systems, positron emission tomography (PET) systems, ultrasound systems, nuclear medicine systems, and so forth. In many instances, these modalities complement one another and offer the physician a range of techniques for imaging particular types of tissue, organs, and physiological systems and phenomena. Health care institutions often dispose of several such imaging systems at a single or multiple facilities, permitting its physicians to draw upon such resources as required by particular patient needs.

[0004] Modern medical diagnostic systems typically include circuitry for acquiring image data and for transforming the data into a useable form which is then processed to create a reconstructed image of features of interest within the patient. The image data acquisition and processing circuitry is often referred to as a "scanner" regardless of the modality, because some sort of physical or electronic scanning often occurs in the imaging process. The particular components of the system and related circuitry, of course, differ greatly between modalities due to their particular physics and data processing requirements.

[0005] Medical diagnostic systems of the type described above are often called upon to produce reliable and understandable images within demanding schedules and over a considerable useful life. To ensure proper operation, the systems are serviced regularly by highly trained personnel who address imaging problems, configure and calibrate the systems, and perform periodic system checks and software updates. Moreover, service offerings have been supplemented in recent years by remote service centers capable of contacting scanners at subscribing institutions directly without the need for intervention on the part of the institution personnel. Such remote servicing is intended to maintain the diagnostic systems in good operational order without necessitating the attention of physicians or radiologists, and is often quite transparent to the institution.

[0006] While such service techniques have proven extremely valuable in maintaining diagnostic systems, further improvements are still needed. For example, in conventional service systems, contact between the scanners and a centralized service center most often originates with the service center. The scanners are provided with only limited functionality in the ability to identify and define service needs. Even where the scanners have permitted some limited ability to contact networked service providers, intermittent conditions indicative of a potentially serviceable problem may cease by the time the service provider is contacted or recontacts the scanner after a service call. Moreover, although the transparency of interactions between scanners and service centers avoids unnecessarily distracting medical personnel with service updates, it has become apparent that some degree of interaction between service centers and institutions would be highly desirable. In particular, an interactive service system would facilitate valuable exchanges of information, including reports of system performance, feedback on particular incidents requiring attention, updates of system licenses, software, imaging protocols, and so forth. Currently available service systems do not permit such interactive exchanges.

[0007] In addition to the foregoing drawbacks, conventional scanners are not suitably adapted to support user-friendly, scanner-based service exchanges. User interfaces in such scanners typically only permit limited access to service information, and do not provide a particularly useful interface for identifying and defining serviceable conditions as they occur. Moreover, software platforms and interfaces in conventional scanners are not suitable for interaction with service centers, and generally exclude the user from communications between the scanner and the service center or, conversely, impose unnecessarily on the user by requiring intervention for certain service functions such as software updates or downloads. Furthermore, platforms have yet to be developed that can serve as a basis for interactive servicing needs of different modalities. Rather, such platforms have traditionally been specifically designed for the needs of a particular modality or even a particular scanner with little cross utility between systems or modalities.

[0008] While improvements in diagnostic stations has been made for certain modalities, these are still insufficient to satisfy the current need. For example, graphical user interfaces are available for specific modality scanners, such as ultrasound scanners, which enable software downloads and remote access to images. The remote access features are, however, generally limited to transmitting image configurations and image data for reconstruction between remote physician workstations and the scanner. At present, available systems do not provide for exchanging information on possible service problems with the scanners, or information or data log files for the purpose of providing remote service of the scanner itself.

SUMMARY OF THE INVENTION

[0009] The present invention provides an interactive servicing technique for medical diagnostic equipment designed to respond to these needs. The technique offers a straightforward and user-friendly environment for identifying and

requesting service for potential problems occurring at the scanner, which may be either recurring in nature or intermittent. The technique may be applied on a variety of scanner modalities, and offers a uniform interface, platform and system architecture across modalities. Thus, the system may be easily adapted to permit a remote service center to provide high quality service to various diagnostic equipment regardless of the modality, model or even the manufacturer. Moreover, a wide array of service functions may be incorporated into systems based upon the technique. For example, service functions such as imaging system trouble shooting and exchange of service call requests and results may be a basic feature provided in the systems. In addition, messaging functions permitting two-way communication directly from the scanner or from a centralized radiology management station at an institution are facilitated. Such messaging may be used for communicating the requests and service call results, providing reports on both technical and business or financial data, reviewing, renewing or extending licenses, updating or downloading new system software and imaging protocols, accessing remote training schedules and programs, and so forth.

[0010] In a presently preferred system architecture, the technique provides an interactive interface installed at the scanner. The interface permits the user to navigate through pages for identifying and reporting serviceable problems at the scanner. The interface also may permit the user to request information such as training programs, software updates, imaging protocols, and so forth.

[0011] Service requests and other messages from the scanner are transmitted to a centralized service center via a remote networking system, such as an intranet or internet. The service center receives such messages and interacts with the scanner to inform the scanner that the request has been received and is being processed. The software platform at the scanner then facilitates the exchange of image and other file data with the remote service center for analysis of system parameters, imaging problems, and so forth. Results of the analyses can then be transmitted directly to the scanner to inform the institution of the causes and possible corrective actions.

[0012] The system also allows the service center to execute proactive or reactive sweeps of scanners to collect information useful to analyze the performance of the scanner as well as to compare its performance to that of other scanners. Moreover, such sweeps may be used to collect information useful in predicting future service needs, such as x-ray tube replacement and so forth.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] **FIG. 1** is a diagrammatical representation of a series of medical diagnostic systems coupled to a service facility via a network connection for providing remote service and data interchange between the diagnostic systems and the service facility;

[0014] **FIG. 2** is a block diagram of the systems shown in **FIG. 1** illustrating certain functional components of the diagnostic systems and the service facility;

[0015] **FIG. 3** is a block diagram of certain functional components within a diagnostic system of the type shown in **FIG. 1** and **FIG. 2** for facilitating interactive remote servicing of the diagnostic system;

[0016] **FIG. 4** is a block diagram of certain of the functional components of the service facility illustrated in **FIG. 1** and **FIG. 2** for rendering interactive remote service to a plurality of medical diagnostic systems;

[0017] **FIG. 4**(A) and **4**(B) illustrate sub-components for license and report servers included in the processing system shown in **FIG. 4**;

[0018] **FIG. 5** is a block diagram of functional components within a field service unit which can be coupled to the diagnostic systems and to the service facility for exchanging service information with a field service engineer;

[0019] **FIG. 6** is an exemplary user interface page incorporated in the diagnostic system for placing service requests, and sending and receiving service data between the diagnostic system and a remote service facility;

[0020] **FIG. 7** is a second user interface page for conveying service information to the scanner operator from the service facility;

[0021] **FIG. 8** is an interface page for generating a particular type of service request at the scanner and for conveying the service request to the service facility;

[0022] **FIG. 9** is an interface page for requesting, compiling and transmitting reports regarding service activities provided by the service facility to the scanner;

[0023] **FIG. 10** is an interface page for transmitting and viewing service-related messages from the service facility at the scanner;

[0024] **FIG. 11** is an interface page including descriptions of software routines, such as imaging protocols, at the diagnostic system scanner which are installed at the scanner or available from a service facility or library;

[0025] **FIG. 12** is a flow chart illustrating exemplary logic implemented by the diagnostic systems for requesting one type of analysis and service from a remote service facility;

[0026] **FIG. 13** is a flow chart illustrating exemplary logic in handling such service requests by the service facility;

[0027] **FIG. 14** is a flow chart illustrating exemplary logic for reporting service activities, updates, alerts, and so forth from the service facility to a diagnostic system;

[0028] **FIG. 15** is a flow chart illustrating exemplary logic for verifying and controlling financial and management arrangements between the service facility and the diagnostic systems, such as licensing arrangements, subscription arrangements, pay-per-use arrangements, and so forth; and, **FIG. 16** is a flow chart illustrating exemplary control logic for accessing diagnostic protocols both from a local storage source at the diagnostic system, as well as from a remote library.

DETAILED DESCRIPTION OF THE INVENTION

[0029] Turning now to the drawings, and referring first to **FIG. 1**, a service system **10** is illustrated for providing remote service to a plurality of medical diagnostic systems **12**. In the embodiment illustrated in **FIG. 1**, the medical diagnostic systems include a magnetic resonance imaging (MRI) system **14**, a computed tomography (CT) system **16**, and an ultrasound imaging system **18**. The diagnostic sys-

tems may be positioned in a single location or facility, such as a medical facility **20**, or may be remote from one another as shown in the case of ultrasound system **18**. The diagnostic systems are serviced from a centralized service facility **22**. Moreover, a plurality of field service units **24** may be coupled in the service system for transmitting service requests, verifying service status, transmitting service data and so forth as described more fully below.

[**0030**] In the exemplary embodiment of **FIG. 1**, several different system modalities are provided with remote service by the service facility. These and other modalities may be similarly serviced by the service facility, depending upon the capabilities of the service facility, the types of diagnostic systems subscribing to service contracts with the facility, as well as other factors. In general, however, the present technique is particularly well suited to providing remote service to a wide variety of medical diagnostic system modalities, including MRI systems, CT systems, ultrasound systems, positron emission tomography (PET) systems, nuclear medicine systems, and so forth. Moreover, the various modality systems serviced in accordance with the present techniques may be of different type, manufacture, and model. Service requests and data transmitted between the systems and the service facility includes data for identifying the type and modality of the serviced system, as well as data specifically adapted to the system modality and model. It should also be noted that, as used herein, the term "service request" is intended to include a wide range of inquiries, comments, suggestions and other queries or messages generated by a diagnostic system or an institution in which a system is disposed or managed. In particular, such requests may relate to problems occurring on systems, applications questions, questions of a general nature, questions relating to financial or subscription arrangements, information sharing, reports, applications, protocols, and so forth.

[**0031**] Depending upon the modality of the systems, various subcomponents or subsystems will be included. In the case of MRI system **14**, such systems will generally include a scanner **26** for generating pulsed magnetic fields and for collecting signals from emissions by gyromagnetic material within a subject of interest. The scanner is coupled to a control and signal detection circuit **28** which, in turn, is coupled to a system controller **30**. System controller **30** includes a uniform platform for interactively exchanging service requests, messages and data with service facility **22** as described more fully below. System controller **30** is linked to a communications module **32**, which may be included in a single or separate physical package from system controller **30**. System controller **30** is also linked to an operator station **34** which will typically include a computer monitor **36**, a keyboard **38**, as well as other input devices **40**, such as a mouse. In a typical system, additional components may be included in system **14**, such as a printer or photographic system for producing reconstructed images based upon data collected from scanner **14**. Although reference is made herein generally to "scanners" in diagnostic systems, that term should be understood to include medical diagnostic data acquisition equipment generally, not limited to image data acquisition, as well as to picture archiving communications and retrieval systems, image management systems, facility or institution management systems, viewing systems and the like, in the field of medical diagnostics. More particularly, equipment benefiting from the present techniques may include imaging systems, clinical diagnostic systems, physiological monitoring systems and so forth.

[**0032**] Similarly, CT system **16** will typically include a scanner **42** which detects portions of x-ray radiation directed through a subject of interest. Scanner **42** is coupled to a generator and controller, as well as to a signal acquisition unit, represented collectively at reference numeral **44**, for controlling operation of an x-ray source and gantry within scanner **42**, and for receiving signals produced by a detector array moveable within the scanner. The circuitry within the controller and signal acquisition components is coupled to a system controller **46** which, like controller **30** mentioned above, includes circuitry for commanding operation of the scanner and for processing and reconstructing image data based upon the acquired signals. System controller **46** is linked to a communications module **48**, generally similar to communications module **32** of MRI system **14**, for transmitting and receiving data for remote service of system **16**. Also, system controller **46** is coupled to an operator station **50** which includes a computer monitor **52**, a keyboard **54**, as well as other input devices **56**, such as a mouse. Moreover, like MRI system **14**, CT system **16** will generally include a printer or similar device for outputting reconstructed images based upon data collected by scanner **42**.

[**0033**] Other modality devices will include circuitry and hardware particularly configured for acquiring or producing signals in accordance with their particular design. In particular, in the case of ultrasound system **18**, such systems will generally include a scanner and data processing unit **58** for transmitting ultrasound signals into a subject of interest, and for acquiring resultant signals which are processed for reconstructing a useful image. The system includes a system controller **60** which regulates operation of scanner **58** and which processes acquired signals to reconstruct the image. Moreover, system **18** includes a communications. module **62** for transmitting service requests, messages and data between system controller **60** and service facility **22**. System **18** also includes an operators station **64**, including a monitor **66**, as well as input devices such as a keyboard **68**.

[**0034**] Where more than one medical diagnostic system is provided in a single facility or location, as indicated in the case of MRI and CT systems **14** and **16** in **FIG. 1**, these may be coupled to a management station **70**, such as in a radiology department of a hospital or clinic. The management station may be linked directly to controllers for the various diagnostic systems, such as controllers **30** and **46** in the illustrated embodiment. The management system may include a computer workstation or personal computer **72** coupled to the system controllers in an intranet configuration, in a file sharing configuration, a client/server arrangement, or in any other suitable manner. Moreover, management station **70** will typically include a monitor **74** for viewing system operational parameters, analyzing system utilization, and exchanging service requests and data between the facility **20** and the service facility **22**. Input devices, such as a standard computer keyboard **76** and mouse **78**, may also be provided to facilitate the user interface. It should be noted that, alternatively, the management system, or other diagnostic system components, may be "stand-alone" or not coupled directly to a diagnostic system. In such cases, the service platform described herein, and some or all of the service functionality nevertheless be provided on the management system. Similarly, in certain

applications, a diagnostic system may consist of a stand-alone or networked picture archiving communications and retrieval system or a viewing station provided with some or all of the functionality described herein.

[0035] The communication modules mentioned above, as well as workstation **72** and field service units **24** may be linked to service facility **22** via a remote access network **80**. For this purpose, any suitable network connection may be employed. Presently preferred network configurations include both proprietary or dedicated networks, as well as open networks, such as the Internet. Data may be exchanged between the diagnostic systems, field service units, and remote service facility **22** in any suitable format, such as in accordance with the Internet Protocol (IP), the Transmission Control Protocol (TCP), or other known protocols. Moreover, certain of the data may be transmitted or formatted via marktip languages such as the HyperText Markup Language (HTML), or other standard languages. The presently preferred interface structures and communications components are described in greater detail below.

[0036] Within service facility **22**, messages, service requests and data are received by communication components as indicated generally at reference numeral **82**. Components **82** transmit the service data to a service center processing system, represented generally at reference numeral **84** in **FIG. 1**. The processing system manages the receipt, handling and transmission of service data to and from the service facility. In general, processing system **84** may include one or a plurality of computers, as well as dedicated hardware or software servers for processing the various service requests and for receiving and transmitting the service data as described more fully below. Service facility **22** also includes a bank of operator workstations **86** which may be staffed by service engineers who address the service requests and provide off and on-line service to the diagnostic systems in response to the service requests. Also, processing system **84** may be linked to a system of databases or other processing systems **88** at or remote from the service facility **22**. Such databases and processing systems may include extensive database information on operating parameters, service histories, and so forth, both for particular subscribing scanners, as well as for extended populations of diagnostic equipment. As described below, such databases may be employed both for servicing of particular diagnostic systems and for tracking such servicing, as well as for deriving comparison data for use in servicing a particular system or a family of systems.

[0037] **FIG. 2** is a block diagram illustrating the foregoing system components in a functional view. As shown in **FIG. 2**, the field service units **24** and the diagnostic systems **12** can be linked to the service facility **22** via a network connection as illustrated generally at reference numeral **80**. Within each diagnostic system **12**, a uniform service platform **90** is provided. Platform **90**, which is described in greater detail below with particular reference to **FIG. 3**, includes hardware, firmware, and software components adapted for composing service requests, transmitting and receiving service data, establishing network connections and managing financial or subscriber arrangements between diagnostic systems and the service facility. Moreover, the platforms provide a uniform graphical user interface at each diagnostic system, which can be adapted to various system modalities to facilitate interaction of clinicians and radiologists with the various diagnostic systems for service functions. The platforms enable the scanner designer to interface directly with the control circuitry of the individual scanners, as well as with memory devices at the scanners, to access image, log and similar files needed for rendering requested or subscribed services. Where a management station **70** is provided, a similar uniform platform is preferably loaded on the management station to facilitate direct interfacing between the management station and the service facility. In addition to the uniform service platform **90**, each diagnostic system is preferably provided with an alternative communications module **92**, such as a facsimile transmission module for sending and receiving facsimile messages between the scanner and remote service facilities.

[0038] Messages and data transmitted between the diagnostic systems and the service facility traverse a security barrier or "firewall" contained within processing system **84** as discussed below, which prevents unauthorized access to the service facility in a manner generally known in the art. A modem rack **96**, including a series of modems **98**, receives the incoming data, and transmits outgoing data through a router **100** which manages data traffic between the modems and the service center processing system **84**.

[0039] As mentioned above, processing system **84** receives and processes the service requests and data, and interfaces with additional service components, both at the service facility and remote from the facility. In the diagram of **FIG. 2**, operator workstations **86** are coupled to the processing system, as are remote databases or computers **88**. In addition, at least one local service database **102** is provided for verifying license and contract arrangements, storing service record flies, log files, and so forth. Moreover, one or more communication modules **104** are linked to processing system **84** to send and receive facsimile transmissions between the service facility and the diagnostic systems or field service units.

[0040] **FIG. 3** illustrates diagrammatically the various functional components comprising the uniform service platform **90** within each diagnostic system **12**. As shown in **FIG. 3**, the uniform platform includes a device connectivity module **106**, as well as a network connectivity module **108**. Network connectivity module **108** accesses a main web page **110** which, as mentioned above, is preferably a markup language page, such as an HTML page displayed for the system user on a monitor at the diagnostic system. Main web page **110** is preferably accessible from a normal operating page in which tile user will configure examination requests, view the results of examinations, and so forth such as via an on-screen icon. Through main web page **110**, a series of additional web pages **112** are accessible. Such web pages permit service requests to be composed and transmitted to the remote service facility, and facilitate the exchange of other messages, reports, software, protocols, and so forth as described more fully below. It should be noted that as used herein the term "page" includes a user interface screen or similar arrangement which can be viewed by a user of the diagnostic system, such as screens providing graphical or textual representations of data, messages, reports and so forth. Moreover, such pages may be defined by a markup language or a programming language such as Java, perl, java script, or any other suitable language.

[0041] Network connectivity module **108** is coupled to a license module **114** for verifying the status of license, fee or

contractual subscriptions between the diagnostic system and the service facility. As used herein, the term "subscription" should be understood to include various arrangements, contractual, commercial or otherwise for the provision of services, information, software, and the like, both accompanies with or without payment of a fee. Moreover, the particular arrangements manages by systems as described below may include several different types of subscriptions, including time-expiring arrangements, one-time fee arrangements, and so-called "pay per use" arrangements, to mention but a few.

[0042] License module **114** is, in turn, coupled to one or more adapter utilities **116** for interfacing the browser, server, and communications components with modality interface tools **118**. In a presently preferred configuration, several such interface tools are provided for exchanging data between the system scanner and the service platform. For example, modality interface tools **118** may include applets or servlets for building modality-specific applications, as well as configuration templates, graphical user interface customization code, and so forth. Adapters **116** may interact with such components, or directly with a modality controller **120** which is coupled to modality-specific subcomponents **122**. The modality controller **120** and modality-specific subcomponents **122** will typically include a preconfigured processor or computer for executing examinations, and memory circuitry for storing image data files, log files, error files, and so forth. Adapter **116** may interface with such circuitry to convert the stored data to and from desired protocols, such as between the HyperText Transfer Protocol (HTTP) and DICOM, a medical imaging standard for data presentation. Moreover, transfer of files and data as described below may be performed via any suitable protocol, such as a file transfer protocol (FTP) or other network protocol.

[0043] In the illustrated embodiment, device connectivity module **106** includes several components for providing data exchange between the diagnostic system and the remote service facility. In particular, a connectivity service module **124** provides for interfacing with network connectivity module **108**. A Point-to-Point Protocol (PPP) module **126** is also provided for transmitting Internet Protocol (IP) packets over remote communication connections. Finally, a modem **128** is provided for receiving and transmitting data between the diagnostic system and the remote service facility. As will be appreciated by those skilled in the art, various other network protocols and components may be employed within device connectivity module **106** for facilitating such data exchange.

[0044] Network connectivity module **108** preferably includes a server **130** and a browser **132**. Server **130** facilitates data exchange between the diagnostic system and the service facility, and permits a series of web pages **110** and **112** to be viewed via browser **132**. In a presently preferred embodiment, server **130** and browser **132** support HTTP applications and the browser supports java applications. Other servers and browsers, or similar software packages may, of course, be employed for exchanging data, service requests, messages, and software between the diagnostic system, the operator and the remote service facility. Finally, a direct network connection **134** may be provided between server **130** and an operator workstation, such as management station **70** within the medical facility (see **FIGS. 1 and 2**).

[0045] In a present embodiment, the components comprising network connectivity module may be configured via an application stored as part of the uniform platform. In particular, a Java application licensed to a service engineer enables the engineer to configure the device connectivity at the diagnostic system to permit it to connect with the service facility. Features of the application are segmented into separate tabbed pages accessible by the service engineer. The application is entered via a license agreement screen. Once accepted, the service engineer can configure parameters of the system modem, the schedule for running automatic diagnostic checks, and establish electronic messaging, such as for automatic service report generation. Once the modem is configured, the service engineer establishes contact with the service facility and provides data enabling the service facility to download any remaining data needed for secure communication between the system and the service center. Upon exit from the application, a configuration status is presented to the service engineer, including status of an automatic test of connectivity between the sites.

[0046] **FIG. 4** illustrates exemplary functional components for service facility **22**. As indicated above, service facility **22** includes a modem rack **96** comprising a plurality of modems **98** coupled to a router **100** for coordinating data communications with the service facility. An HTTP service server **94** receives and directs incoming and outgoing transactions with the facility. Server **94** is coupled to the other components of the facility through a firewall **138** for system security. Operator workstations **86** are coupled to the port manager for handling service requests and transmitting messages and reports in response to such requests. An automated service unit **136** may also be included in the service facility for automatically responding to certain service requests, sweeping subscribing diagnostic systems for operational parameter data, and so forth, as described below. In a presently preferred embodiment, the automated service unit may operate independently of or in conjunction with the interactive service components comprising processing system **84**. It should be noted that other network or communications schemes may be provided for enabling the service facility to communicate and exchange data and messages with diagnostic systems and remote service units, such as systems including outside Internet service providers (ISP's), virtual private networks (VPN's) and so forth.

[0047] Behind firewall **138**, an HTTP application server **140** coordinates handling of service requests, messaging, reporting, software transfers and so forth. Other servers may be coupled to HTTP server **140**, such as service analysis servers **142** configured to address specific types of service requests, as described more fully below. In the illustrated embodiment, processing system **84** also includes a license server **144** which is coupled to a license database **146** for storing, updating and verifying the status of diagnostic system service subscriptions. Alternatively, where desired, license server **144** may be placed outside of fire wall **138** to verify subscription status prior to admission to the service facility.

[0048] Handling of service requests, messaging, and reporting is further coordinated by a scheduler module **148** coupled to HTTP server **140**. Scheduler module **148** coordinates activities of other servers comprising the processing system, such as a report server **150**, a message server **152**, and a software download server **154**. As will be appreciated

by those skilled in the art, servers **150**, **152** and **154** are coupled to memory devices (not shown) for storing data such as addresses, log files, message and report files, applications software, and so forth. In particular, as illustrated in **FIG. 4**, software server **154** is coupled via one or more data channels to a storage device **156** for containing transmittable software packages which may be sent directly to the diagnostic systems, accessed by the diagnostic systems, or supplied on pay-per-use or purchase basis. Message and report servers **152** and **154** are further coupled, along with communications module **104**, to a delivery handling module **158**, which is configured to receive outgoing messages, insure proper connectivity with diagnostic systems, and coordinate transmission of the messages.

[**0049**] The foregoing components may, of course, include further subcomponents for executing specific functions in the processing system. **FIGS. 4A and 4B** illustrate such subcomponents for license server **144** and report server **150**. As shown in **FIG. 4A**, license server **144** includes a validity check module **160** linked to license database **146**. The license database is further linked to a key information module **162**, a contract population process module **164**, and a site population process module **166**. The latter module is further coupled to systemic information databases **168**. As described more fully below, validity check module **160** receives site information, verifies site and license information with license database **146**, and accesses resulting status information from the database. Module **160** then may output the site status and license status information to the HTTP server within the processing system for enabling consideration and response to a service request or for otherwise addressing the service request. Module **162** receives key information and site information regarding the particular diagnostic system requesting service, and transmits site identification, configuration, and similar information to other system components through the intermediary of database **146**. Similarly, population process modules **164** and **166** store and provide general contract status data, service security keys, site demographic information, and so forth.

[**0050**] The functional components of report server **150**, as shown in **FIG. 4B**, may include a report generation module **170**, coupled to a report access module **172**, a report storage device **174**, and an automated data gathering module **176**. Automated data gathering module **176** may include all or a portion of an automated service unit **136** as shown in **FIG. 4**. As described more fully below, the components of the report server receive scanner data, service information, warehouse information, and the like, and generate system-specific reports based upon this and collected information, such as from gathering module **176**. Such reports may also include information on entire populations of similar diagnostic systems, such as for comparison purposes, component life predictions and so forth. The reports may be stored and accessed remotely by the diagnostic system as described below.

[**0051**] **FIG. 5** illustrates certain of the functional components contained within an exemplary field service unit **24**. Field service unit **24** may include a portable computer designed for use by remote service engineers. The unit includes a service platform which includes certain functional circuitry for establishing a uniform service base as discussed above for the diagnostic systems themselves. Moreover, the service units include specific service tools which enable the field engineer to request and receive remote service messages, reports on specific diagnostic systems, service schedules, and so forth. Through the service platform, therefore, the field engineer may access system configurations, historic log information, system network information, analysis logs and data, and so forth. In addition, the field service unit described below, in conjunction with the system platform and the service facility components, permits such information to be accessed either by the field engineer on the field service unit, or at the diagnostic system itself (e.g. when the service engineer is on-site), or from the remote service facility. The field engineer may also update service records either from the field service unit or from the diagnostic system, as desired.

[**0052**] Thus, as shown in **FIG. 5**, an exemplary field service unit includes a device connectivity module **106** and a network connectivity module **108**. Device connectivity module **106** may include connectivity interface circuitry **124**, a network or PPP module **126**, and a modem **128**, as described above for the diagnostic system with reference to **FIG. 3**. The network connectivity module **108** may, in turn, include a server **130** and browser **132** substantially identical to those of the diagnostic systems, enabling the field engineer to receive, view and compose messages, reports, and so forth via a main web page **110** and a series of web pages **112**. Moreover, an access module **114**A is provided for allowing the service facility to verify the license and security status of the field service unit. For example, the access module, in cooperation with circuitry at the service facility, may permit a field service engineer to access data or applications providing some or all of the functionality offered to service engineers at the service facility. Such functionalities may be similar to those provided at the diagnostic systems themselves, or may offer the service engineer a wider range of service options. One or more adapter modules **116** provide for interfacing the network circuitry with various field service tools. In particular, the field service unit may be equipped with service applications, as indicated at blocks **180**, such as for analyzing diagnostic system performance data, scheduling regular or special service calls, scheduling for shipment of replacement parts, and so forth. Other service applications may include applications generally similar to those executed on the operator workstations **86** of the service facility (see, e.g. **FIG. 4**). Such applications may permit the field service engineer to address service requests at the diagnostic system site, or remote from the site as required, and transmit service messages and updates via the remote field service unit.

[**0053**] In a presently preferred embodiment, the foregoing functional circuitry may be configured as hardware, firmware, or software on any appropriate computer platform. For example, the functional circuitry of the diagnostic systems may be programmed as appropriate code in a personnel computer or workstation either incorporated entirely in or added to the system scanner. The functional circuitry of the service facility may include additional personal computers or workstations, in addition to a main frame computer in which one or more of the servers, the scheduler, and so forth, are configured. Finally, the field service units may comprise personal computers or laptop computers of any suitable processor platform. It should also be noted that the foregoing functional circuitry may be adapted in a variety of manners for executing the functions described herein. In general, the functional circuitry facilitates the exchange of service data

between the diagnostic systems and a remote service facility, which is preferably implemented in an interactive manner to provide regular updates to the diagnostic systems of service activities.

[0054] As described above, both the diagnostic systems and the field service units preferably facilitate interfacing between a variety of diagnostic system modalities and the remote service facility via a series of interactive user-viewable pages. **FIGS. 6 through 11** illustrate exemplary pages for providing interactive information, composing service requests, selecting and transferring messages, reports and diagnostic system software, and so forth. It should be noted that through the following discussion, reference is made to viewable pages for interfacing in the language of the present description. However, in a presently preferred embodiment, the platform may be configured to present such interface pages in several different languages, depending upon the country in which the system is installed. As illustrated first in **FIG. 6**, a main web page **110** is accessible from a normal diagnostic system screen viewable on the diagnostic system monitor **36**, **52** or **66**. Main web page **110** may therefore be viewable by clicking an input device such as a mouse on an icon (not shown) on the normal operational screen. Main web page **110** includes a series of navigation devices **178** in the form of graphical buttons for accessing other interface pages in the graphical user interface. In the illustrated embodiment, these graphical devices include a service request button **180** for accessing a service request page, an applications button **182** for accessing an applications page, a system reports button **184** for accessing service reports, and a messages button **186** for sending and receiving interactive service messages. A help button **187** is provided for accessing user information, help topics and so forth, which may be resident on the system, or available through on-line sources viewable through the system browser. A close or exit button **188** is provided for returning to the normal scanner interface page. In addition to these navigational devices, main page **110** includes a message area **190** in which information regarding the most recent messages is displayed. This information may include identification of the time and date received, the originator of the message, and a brief summary of the message content or title. Thus, upon accessing main page **110**, the system user is made aware of service activities carried out by the remote service facility or field service engineer.

[0055] **FIG. 7** illustrates the applications page **192** accessed by actuation of the applications button **182** in the main page. As in the main page, the applications page includes a series of graphical buttons **178** for navigating through the other pages of the graphical user interface, including a main screen button **194** for returning to the main screen shown in **FIG. 6**. Moreover, additional web pages may be accessible through the applications page, such as a documentation or a help page or series of pages, accessible through a graphical button **196**. A protocols page is accessible through a graphical button **198**. Moreover, page **192** is provided with a text area **200** in which text describing various service documentation, messages, modality equipment, operational instructions, and so forth may be displayed.

[0056] It should be noted that in a presently preferred configuration, the information displayed within text area **200** is specifically designed for the particular modality and type of diagnostic system on which the uniform platform is installed. Thus, as described below, when the service center is placed into network contact with the diagnostic system, the identification of the diagnostic system to the service center allows the service center to transmit and display modality-specific information in the text area. In the embodiment illustrated in **FIG. 7**, such text includes documentation on imaging protocol or examination descriptions, a system newsletter specifically adapted for the modality and system type, updated questions and answers, and instructional suggestions for operation of the diagnostic system. The user can access the specific documents described in the text area by selection of all or a portion of the text describing the documents. In the presently preferred embodiment, the accessed documents may be stored in local memory devices within the diagnostic system, or selection of the text may result in loading of a uniform resource locator (URL) for accessing a remote computer or server via a network link.

[0057] As mentioned above, the uniform graphical user interface facilitates formulation of service requests and enables system designers to permit such service requests in a similar manner across several diagnostic system modalities. **FIG. 8** illustrates an exemplary interface page for formulating such service requests. In the page shown in **FIG. 8**, a "snap shot" or current system state may be captured as the basis for the service request. The service request page would be accessed from the normal operating page at the scanner, through the service request button **180** in the main web page or one of the other web pages. With the system state remaining at its condition just prior to accessing the service request page, image data files, log files, error files, and so forth may be identified, captured, stored and transmitted to the service facility for evaluation of potential problems in the diagnostic system. As will be appreciated by those skilled in the art, the service request therefore enables the user to identify potential imaging system difficulties that may not be apparent in subsequent examinations, or may not reoccur on a predictable basis. It should be noted that the service requests formulated via a page such as that shown in **FIG. 8** and described below are not limited to identifying image acquisition or processing problems, or to capturing image files only. Such requests may relate to general or system-specific questions, or may identify data files containing system configuration data, and data indicative of historical operational parameters or events. Such events may include parameter limits exceeded, timeouts, protocol configurations, hardware and software configurations, work queues, and so forth. Similarly, image data identified for evaluation may include both processed, partially processed and raw data from which images are subsequently reconstructed.

[0058] The service request page **202**, as shown in **FIG. 8**, includes graphical buttons **204** which permit the user to identify whether the service request is urgent or whether the request entails simply an applications question or non-urgent inquiry. In the illustrated embodiment, a series of interactive selections **206** are available, permitting the user to identify, if possible, the type of problem which may be occurring. Furthermore, a series of identification areas **208** allow the user to insert text to identify both the user, the user's location or telephone number, and other contact information. It should be noted that the server included in the uniform platform already includes unique system identification data which supplements the information input by the user. Such

information may be input by a user, or may be supplied automatically by the system. Where the service request involves a specific image or examination sequence, the user may input such identifying data in a series of examination identification areas **210**. Where the examination request involves an examination which has just been attempted or is underway, the data required in areas **210** may be transmitted directly from the modality controller. A further area **212** permits the user to identify or describe the type of service problem being experienced. A date stamp area **214** provides an identification of the date and time of the serviceable problem or question. In appropriate situations, a default time drawn from a system clock may be provided in this area, or the default time may be overridden by the user. Finally, in the embodiment illustrated in **FIG. 8**, the user may complete and submit the service request by selecting a graphical send button **216**. It should also be noted that in the illustrated embodiment, a graphical service center telephone directory button **218** is provided, by which the user may access numbers for immediately contacting the remote service facility.

[**0059**] **FIG. 9** illustrates a further interface page for informing the system operator of the current and past state of service activities, and for transmitting reports to the diagnostic system from the remote service facility. The system reports page **218** includes a series of graphical buttons **178**, including certain options which may be provided across a number of modalities, such as a service history button. When the service history button is selected, text appears in a text area **222** which identifies the type of service performed on the diagnostic system, either locally by a service engineer or remotely by the remote service facility. The text may also indicate the nature of the organization performing the service, applicable reference numbers, and the date on which the service was performed. The diagnostic system operator is thereby apprised of all service activities provided to the diagnostic system, and maintains and up-to-date, comprehensive list of the service activities.

[**0060**] Other selections available in the system reports page may include system usage, accessible through a graphical button **224**, and monitoring activities accessible through a button **226**. It should be noted that the specific information accessed through selection of one of the graphical buttons will be adapted not only for the modality and system type, but for the specific system in which the user interface is installed. Thus, under a system usage page (not shown) a CT system may include data indicative of the performance of an x-ray radiation source, while in an MRI system, the same graphical button may access information on cryogen levels and temperatures. It should also be noted that specific modality or system buttons may be provided, such as a tube usage button **228** in **FIG. 9**, suitable for x-ray and CT systems. Although such additional interface access devices are configured in individual systems, they are preferably provided in a uniform location and lay out which can be easily learned and used by operations personnel.

[**0061**] **FIG. 10** illustrates a messages page for the uniform platform and graphical user interface. Messages page **230** is accessible through the main page shown in **FIG. 6**. Upon accessing the messages page, the system user is provided with information on service and other messages received by the diagnostic system via a network connection. A pair of graphical buttons are provided for selecting either current messages or saved messages received by the system. Upon selection of either the current or saved messages button, the user is provided with a list of messages in a text area **232**, identifying the subject of the message, the originator, and the date received. The body of the message, and graphical symbols indicating possible attachments (none shown) are also provided in the text area **232**. The user may select a particular message for viewing by selection of the entire or a portion of the text defined in the tabulated message list.

[**0062**] As described more fully below, when a service request is composed and transmitted to the remote service center, an acknowledgment message is generated and returned to the diagnostic system, indicating that the service request has been received and is being processed. Moreover, where reports are generated, based either on a service request or on an automatic or a periodic basis, the availability of such reports may be flagged through the message page. Both the message and the report may then be accessed by appropriate selection of the message title in the tabulated list. The user may save or delete each message by selection of an appropriate save or delete graphical button **234**.

[**0063**] As illustrated in **FIG. 11**, further interface pages may be provided for listing available software, uploading such software into the particular modality controller, or downloading the software from a library or service facility. In the embodiment illustrated in **FIG. 11**, such software includes a series of examination or imaging protocols. As will be appreciated by those skilled in the art, such protocols define configuration parameters for specific examination sequences. In general, however, as used herein, the term "protocols" generally refers to instructions or parameters for acquiring, manipulating, displaying, archiving or managing medical diagnostic data. The protocols are specifically adapted for the modality of the diagnostic system, and may be further adapted for specific system types and capabilities. In presently preferred configurations, the protocols may be stored locally at the particular diagnostic system, or may be available at the diagnostic system via a variety of transfer options or memory support devices, such as CD ROM storage discs. It should be noted, however, that interface pages such as that shown in **FIG. 11**, and the processing described below, are not limited to transfer of protocols, but may include transfer of a wide range of programs.

[**0064**] The available software routines are listed and described briefly in the user-viewable page. In **FIG. 11**, the protocol screen **236** lists a series of imaging protocols within a text area **238**. For each protocol provided in the listing, a brief description of the protocol and its configuration parameters is provided as indicated at reference numeral **240**, as is a condensed image or thumbnail sketch of the type of image available through application of the protocol, as indicated at reference numeral **242**. Additional protocols may be made available by paging down the list in a conventional manner. Also, in a preferred embodiment, protocols presented in a menu may be sorted, such as by anatomy, imaging or acquisition technique, physiological condition or pathology, and so forth. As described in greater detail below, in a preferred embodiment, not only are the protocols displayed for reference purposes at the diagnostic system, but new or additional protocols may be added to the listing from time to time, such as by downloading from the service facility. Moreover, certain of the protocols may be made available on a fee-per-use, one-time payment, or a license basis. Further-

more, the user may upload examination configurations by selecting the thumbnail image or text associated with a particular protocol. Thus, the uniform user interface and platform facilitate not only viewing and listing such routines and protocols, but assist in the examination configurations themselves.

[0065] **FIGS. 12 through 16** illustrate exemplary control logic implemented by the functional components described above at the diagnostic systems, the service facility, and remote field service units. In particular, **FIG. 12** illustrates exemplary logic for composing and transmitting a service request via the graphical user interface and uniform platform. The control logic, indicated generally by reference numeral **250**, begins at step **252** wherein a service page is accessed from a normal operating page at the diagnostic system or at a management station. The logical steps illustrated in **FIG. 12** are particularly adapted for composing service requests based on specific instances of malfunctions or specific questions on examination sequences. Thus, at step **252** a service request page such as that shown in **FIG. 8** is accessed. At step **254** the diagnostic system may verify a subscriber status required for the requested service. In particular, the various service requests may be categorized by type, and associated with specific contract types, subscriber services, licenses, and so forth. Such subscriber data will be stored in a license module such as module **114** shown in **FIG. 3**. Where the service requests are freely made by the scanner, this step may be eliminated. However, where specific service subscriptions are required, a comparison is made at step **254** between the required contractual arrangement or subscriber license and the similar information on file for the diagnostic system. At step **256** in **FIG. 12**, the diagnostic system connectivity module dials and connects the diagnostic system to the service facility. At step **258** the service request is composed, such as by selecting or inputting the question description, user identification, problem description and other information as described above with respect to **FIG. 8**.

[0066] At step **260**, the diagnostic system server **130** (see **FIG. 3**) determines the type and location of data that may be required for addressing the service request. For example, for service requests regarding imaging sequences, acquired image data files may be identified, along with scanner log files, error files, and so forth. More particularly, the data identified (and later transmitted if required) may include both raw or processed image data, software configuration information, systems data (e.g. hardware and software identification and configuration), and so forth. Certain of the data may be specific to the modality of the system (such as data in a DICOM format), and may be defined by modality through adaptation of the uniform platform via the modality interface components. Where such data is required for properly addressing the service request, the data files are located as indicated at step **262**. The files may be backed up or stored from the modality-specific circuitry through the intermediary of adapter modules, such as adapter module **116** (see **FIG. 3**). These steps in the exemplary logic therefore permit the user to configure a service request which effectively captures a state of the diagnostic system which gave rise to the service request. The request may be thereby linked to the specific problem for which service is needed.

[0067] At step **264** a message is formatted based upon the service request. The message formatting will typically include identification of the diagnostic system, a facility in which the system is located, and so forth. It should be noted that in the preferred embodiment, the service request and the message is stripped of information relating to specific patient identifications. Other data, such as financial or account information may be included with the message or may similarly be stripped from the request. Where the requested service is permitted by the subscriber arrangement, the logic proceeds to step **266** where the request is placed in a message queue at the diagnostic system. If the subscription arrangement does not permit the specific type of request, the logic may produce a message notifying the system user of this fact, may proceed based upon an exception to the subscriber arrangements, or both.

[0068] At step **268** the service request message is transmitted. The service facility receives the service request and processes the request as summarized below. In the preferred embodiment a request acknowledgment signal is immediately transmitted by the service facility back to the diagnostic system and is received by the diagnostic system at step **270**. The diagnostic system operator is thereby immediately provided with feedback on the status of the service request, including information relating to a reference code and estimated handling time. At step **272** a portion or all of the data files may be transmitted by the diagnostic system to the service facility. Alternatively, transmission of all or some of the data files may be delayed until a subsequent service connection session. At step **274**, the acknowledgment message is posted on the message page of the graphical user interface, and a notification that the message has been received may be posted on the interface page which is currently being viewed at the diagnostic system. At step **276** the diagnostic system may disconnect from the service facility. Alternatively, additional messages, service requests, and so forth may be transmitted, or other remote activities may be performed at this stage. When certain of the data required to address the service request is not transmitted immediately, the service facility may recontact the medical diagnostic system at a subsequent time. As indicated at step **278**, a data file pull request may be transmitted by the service facility, and, in response to the request, the platform at the diagnostic system will access the required files and transmit the data to the service facility for analysis.

[0069] **FIG. 13** illustrates steps in exemplary control logic for addressing the service request at the remote service facility. This request handling logic, indicated generally by reference numeral **280**, begins with receipt of the request as indicated at step **282**. The request is received via the network connectivity modules of the service facility and is handled by the service center processing system including the HTTP server **140** and the analysis server **142** (see **FIG. 4**). In addition to the steps illustrated in **FIG. 13**, the service facility servers will verify license or other subscriber data for the diagnostic system or site requesting the service as described more fully below with reference to **FIG. 14**.

[0070] Upon receipt of the service request and subscriber clearance, the service facility processing system determines, at step **284**, whether a service dispatch has been opened. As used herein, the term "dispatch" refers generally to a service request tracking or handling technique, such as for referencing a service request or identifying the service request or

response at a later time. The logical steps executed at step **284** may include comparison of the origin and nature of the service request with service requests already received and being handled by the service facility. If, through this comparison, it is determined that no dispatch has been opened for the particular request, a dispatch is created at step **286** and the service request is placed in a handling queue. If a dispatch has already been created, it is determined at step **288** whether the dispatch has been assigned to a service facility engineer for handling. If the dispatch has not yet been assigned, a note is appended to the dispatch at step **290** indicating that the service request has been repeated. From either step **284** or step **290**, a message is generated at step **292** including the reference number of the dispatch in the service facility or an update on the status of the preexisting dispatch. This message is then transmitted to the requesting diagnostic system or site and is received and posted by the site as described above with respect to **FIG. 12**.

[**0071**] Following transmission of the acknowledgment message at step **292**, a modality service engineer is notified of the service request at step **294**. Because in the present technique the service facility may provide interactive service to a variety of system modalities, at step **294** a service engineer, typically staffing a workstation **86** (see **FIG. 4**) in the service facility is assigned service requests according to the particular modality of the diagnostic system. It should be noted, however, that the modality service engineer assigned the service request may be remote from the service facility, and may be a field service engineer accessible through a field service unit **24** (see **FIGS. 1 and 2**). At this point in the control logic, the service facility may be disconnected from the requesting diagnostic system.

[**0072**] Where the service request requires data, such as image data files, log files, and so forth, from the diagnostic system, this data may be transmitted along with the request. However, where voluminous files are needed, or where files are identified by the service facility or by a service engineer subsequent to receipt of the request, the diagnostic system may be recontacted by the service facility as indicated at step **296** to locate and transmit the needed data. At step **298** the data is accessed, transmitted and stored. The steps involved in recontacting the medical diagnostic system and transmitting the needed data files may require prompting of operations personnel for the input of specific information, or may be essentially transparent to the diagnostic systems operations personnel. Thus, the service facility server or servers may contact the diagnostic system server directly to access and transmit the needed data without intervention from the operations personnel at the diagnostic system facility.

[**0073**] Depending upon the nature of the service request, the service facility engineer will perform analysis of the service issues and recontact the diagnostic system either in person, by telephone, or directly through the network connection and user interface. For particular service requests, the service facility database may be utilized as indicated at step **300** in **FIG. 13**. Such databases will be called into play in reviewing or updating service history for the particular diagnostic system or site, as well as for referring to configuration parameters, operating parameters, reference values, and so forth for the particular modality and system type. The databases accessed at step **300** may also include information relating to populations of diagnostic systems. Such information may be used by the service facility for comparison purposes, predicting possible future service needs, predicting component failure or degradation, and so forth. Moreover, the access to the databases at step **300** may include access to new or updated routines, protocols, instructional documentation and courses, schedules for training, and so forth. Where such information is located for the diagnostic system modality and type, the data may be included in messages formulated by the service facility and retransmitted to the diagnostic system. At step **302** the database information is therefore accessed, transmitted and stored for responding to the service request.

[**0074**] Returning to step **288**, if at this step it is determined that a dispatch has been assigned, a further dispatch may be created at step **304**. A message, including the update regarding the dispatch, is formulated and sent at step **306** to inform the diagnostic system operations personnel of the status of the service request. A "pop up" box message is then addressed to the assigned service engineer at step **308**. At step **310** the processing system determines whether the assigned engineer has accepted the dispatch. If no engineer accepts the dispatch or a predetermined interval lapses following display of the notification at step **308**, the logic proceeds to step **294** wherein a modality service engineer is notified of the service request. Subsequent logic follows step **294** as described above. If upon displaying the notice at step **308** a particular service engineer accepts the service request, the request is assigned to the engineer at step **312** and the logic may proceed to step **296** as described above.

[**0075**] In general, substantive responses to service requests will vary depending upon the tenor of the request. For example, the response may include suggestions for operating the diagnostic system or a medical institution in which the system is installed. Such information may provide "best practices" type information for the particular system type or modality, as well as instructional information on user or care for the system. The information may also include alerts, such as for anticipated service needs, scheduled or available training sessions and so forth. As described below, the response may further include programs or protocols or reports of system operation. It should be noted that the same type of information may be provided to the diagnostic system at the initiation of a remote service facility as part of a service program or otherwise.

[**0076**] **FIG. 14** illustrates steps in exemplary control logic executed by the service system for requesting, compiling and transmitting reports relating to service activities and operation of the medical diagnostic systems. The control logic, indicated generally by reference numeral **310**, may begin in one of several manners, depending upon whether the report is being generated automatically, or upon request by a particular diagnostic system, or by a field engineer. Where the report is specifically requested by a diagnostic system, the report request is produced at step **312** by the system operator or manager via the uniform graphical user interface described above. Various types of reports may be produced, including reports relating to recent or historical service activities, reports of the state of the diagnostic system, including numbers and types of examinations performed, errors or problems encountered, anticipated service needs, and so forth. For example, in x-ray and CT modalities, reports may relate to the operational status of the x-ray tubes, while in MRI systems, reports may include data relating to cryogen levels and temperatures. Moreover,

reports may be requested for financial, subscription, or other management functions, including listings of current license subscriptions, accumulated fees for specific accounts (e.g. resulting from pay-per-use or one-time fee arrangements), and so forth. Similar reports may be requested by field service engineers and technicians as indicated at step **314**.

[**0077**] At step **316** the report request is transmitted to the service facility. The report request will typically be transmitted in the form of a service request message as described above with reference to **FIG. 12**. At step **318** the transmitted request is acknowledged by a return acknowledgment message from the service facility, providing an indication of receipt and confirmation of handling of the report.

[**0078**] Certain of the reports available through the system may be provided free of charge, or based upon specific subscription types, or for a fee. Thus, as shown in **FIG. 14** at step **320**, following acknowledgment of receipt of the report request, the service facility processing system may evaluate the request to determine whether a fee is applicable. If a fee is associated with the report requested by the diagnostic system user, a fee/subscription routine is performed as indicated at step **322**. Exemplary control logic involved in the fee/subscription routine is described below with reference to **FIG. 15**.

[**0079**] Following either step **320** or step **322**, the service facility is contacted via a network connection as indicated at step **324**. It should be noted that while the fee verification steps indicated at steps **320** and **322** may be performed in the medical diagnostic system, similar steps may be performed in the service facility following step **324**, or between the diagnostic system and the service facility interactively, depending upon the particular fee arrangement and the data required for authorization of the fee structure. As indicated above, the reports generated by the service system may result from triggering events other than a specific request. In particular, certain reports may be generated on a periodic basis, such as weekly or monthly, and the service facility or the medical diagnostic system may generate a prompt for a report based upon a preestablished calendar or routine. Thus, as indicated at step **326**, a periodic trigger may give rise to either the medical diagnostic system contacting the service facility, or vice-versa.

[**0080**] Once the diagnostic system and service facility are linked, the service facility may sweep the diagnostic system for data required for the desired report as indicated at step **328**. As used herein, the term "sweep" refers generally to a process of connecting system components, such as via a network connection, identifying desired data, and transmitting the data, either in an "upload" or a "download" scenario, depending upon the nature of the data and its use in servicing a system. Such sweeps may occur on regularly scheduled bases, at desired times (e.g., at off-peak utilization times) or on demand by a system user or a system application. The system data may be stored in specific data files which are accessed either through intervention of a service engineer, or automatically by the service facility processing system. Once the data is accessed, it is transmitted to the service facility as indicated at step **330**. At step **332** the service data records for the particular diagnostic system, as well as records kept for specific populations of similar diagnostic systems is updated as indicated at step **332**. Subsequently, the service facility may disconnect from the diagnostic system as indicated at step **334**. In situations in which no further data from the diagnostic system is needed for generation of the requested report, the steps of data collection and transmission may be eliminated. Moreover, the service facility may perform periodic data sweeps of subscribing systems without immediately generating a report through the subsequent logical steps.

[**0081**] Where a report is to be generated based upon the acquired and historical data, the data is processed as indicated at step **336**. As will be appreciated by those skilled in the art, the specific processing performed at this step may vary widely depending upon the nature of the diagnostic system, the data being processed, the type of report being generated, and so forth. For example, the data processing may include statistical analysis of the acquired data, categorization of data, as well as failure prediction analyses based upon the data, and so forth. The processed data is then compiled into the desired report as indicated at step **338**. The report may include tabulated presentations, but may also include compilations of data into graphical formats, such as charts, graphs, and so forth, which may be accessible through a series of interactive pages viewable by the diagnostic system user via the local browser.

[**0082**] At step **340** connection is reestablished with the diagnostic system and a notification of the availability of the report is transmitted. Several scenarios are available for transmission of the requested reports. As indicated at step **340**, the requested report may be transmitted with the notification message in a "push" scenario. In general, such techniques will append the report to a notification message which is transmitted and displayed at the diagnostic system. The user may then access the report by appropriately selecting the message or an icon or text associated with the message. Where desired, however, reports may be compiled and a notification message provided at step **340**, requiring the diagnostic system or the site to recontact the service facility and to "pull" the report as indicated at step **342**. Where the report was requested by a field service engineer, similar steps are performed for transmitting the desired report to tile field service engineer, or for permitting the field service engineer to pull the report based on a notification message. Moreover, where reports are requested by or transmitted to specific diagnostic systems or sites, the field service engineer may be notified of the request or the report at the same time as the report is transmitted to the diagnostic system. It should be noted that, when desired, a report maybe stored at a location remote from the diagnostic system, and nevertheless be viewed at the diagnostic system, such as via a browser interface (e.g. as a series of web pages). Moreover, where desired, a report may be requested by the system to be delivered via facsimile. In such cases, the report is requested and compiled as described above, then transmitted via facsimile to the institution in which the system is installed or, in appropriate applications, directly to the requesting system.

[**0083**] **FIG. 15** illustrates exemplary control logic for verifying and controlling financial and management arrangements between the service facility and diagnostic systems. As mentioned above, the logic illustrated in **FIG. 15**, designated generally by the reference numeral **350**, may be triggered in a variety of manners. For example, verification of license or subscriber status may be triggered each time the service application is accessed at the medical

diagnostic system. Similar triggering may occur upon request for specific types of service at the remote service facility. Moreover, both the diagnostic system and the remote service facility may include routines designed to trigger an alert upon expiration or anticipated expiration of a dated subscription. Furthermore, subscription or license verifications may relate to all or a part of the platform or configuration of the diagnostic system, such as particular programs, applications, protocols and so forth. In a presently preferred embodiment, other security checks may be performed in addition to such subscription verifications to prevent tampering. For example, when the service platform is started, a coded check sum for files is compared to a reference (e.g., created upon installation or subsequent updating) If the comparison reveals possible tampering, a note is made in a log file which can be monitored remotely.

[**0084**] In the presently contemplated embodiment, several types of fee or financial management arrangements may be provided in parallel. Firstly, a service subscription may exist for certain levels of service. The service subscription may time out periodically or may be permanent, such as lifetime or non-expiring warranty service. Secondly, certain of the services provided remotely may be offered on a pay-per-use basis. In such cases, the logic of **FIG. 15**, or other financial management logic may be triggered upon generation of a service request, receipt of the service request, or fulfillment of a service order. Finally, certain services or service data may be provided based on a purchase arrangement, in which the diagnostic system operator orders service or data and the associated fee is invoiced or debited to the diagnostic system account. Such arrangements may be employed, for example, for the transfer of new examination protocols, software, and so forth.

[**0085**] The logic of **FIG. 15** begins at step **352** with the triggering of a subscription check. As used herein, the term subscription should be understood to encompass both ongoing and periodically expiring licenses, pay-per-use arrangements, purchase arrangements, and other service and distribution arrangements. As illustrated in **FIG. 15**, step **352** will generally occur at the diagnostic system. At step **354** a subscription manager module contained within the license module **114** of the diagnostic system is accessed. The subscription manager module will include data relating to specific applications or services to which the diagnostic system holds rights or subscriptions, as well as data relating to expiration dates, levels of service, system identification, and so forth. At step **356**, the system determines whether the status of the various subscriptions is up-to-date or whether certain of the subscriptions may be expired. If any such problems with the service subscriptions is detected at step **356**, operation of the service platform or interface may be modified as indicated at step **358**. Rather, or in addition to such modification in the service platform presentation or operation, a message may be generated and displayed at the diagnostic system indicating the need to contact a field service engineer or the service facility, or to update the subscription. Following step **358**, the service activities may continue as indicated at step **360**. Step **360** is also reached where the status of the subscriptions checked at step **356** are found to conform to the needed status for the service activities desired by the user.

[**0086**] Following the local verification of the subscription status, the diagnostic system may be connected to the service facility as indicated at step **362**. At step **364** any service requests or messages composed at the diagnostic system may be transmitted to the service facility as described above. Based upon such service requests and messages, a further subscription review may be performed in conjunction with the service facility. In particular, as indicated at step **366**, certain of the service or data requests transmitted from the diagnostic system may require payment or authorization of a fee. Such requirements are identified at step **366**. At step **368** a site subscription index maintained at the service facility is accessed. The site subscription index will typically be stored in a license database **146** (see **FIG. 4A**). The index includes up-to-date information regarding current subscriptions, account data, system identification, authorization data, and so forth, for the specific diagnostic system and the services to which the diagnostic system either holds rights or licenses. The subscription index information is used by the service facility to update the data at the diagnostic system, as well as to authorize the requested service, or to perform accounting functions for debiting appropriate accounts for paid services. Where desired, subscription authorizations may also be automated between the service facility and diagnostic systems or medical institutions.

[**0087**] As indicated above, certain financial arrangements may be verified periodically either at the diagnostic system or by the service facility processing system. Step **370** in **FIG. 15** indicates a periodic subscription check or status flag which may occur based upon such periodic license checking routines. When a periodic license check is triggered, the status of applicable licenses is verified at step **372**. If the statuses are current (e.g. no expired license flags are identified), normal operation may continue. However, where the status check indicates that certain subscriptions have expired or will expire, the specific diagnostic system involved may be contacted by connecting to the service facility network as indicated at step **374**. Following the connection, the site subscription index is again accessed at step **368** as summarized above.

[**0088**] The site subscription index accessed at step **368** provides a basis for verifying and updating corresponding status data with the diagnostic system. Thus, at step **376**, the subscription index is compared to similar subscription information stored at the diagnostic system, and it is determined whether an update is required. In general, it is presently contemplated that the master version of such information will be stored at the service facility. In practice, portions of the indices or subscription files may be compared, or data derived from the indices or files may be compared for this purpose. Moreover, security devices may be included in the system to prevent unauthorized modification of the subscription data at the diagnostic system. Thus, if at step **376** the diagnostic system data is found not to conform to the information at the service facility, it is assumed that the diagnostic system is to be updated, and such updates are performed as indicated at step **378**. Following either step **376** or **378**, the status of the particular subscriptions are verified at step **380**. This status verification may include, again, comparison of the current system subscriptions with the subscriptions necessary for the requested service. Moreover, the status check may verify whether the requested service is a pay-per-use service, a one-time fee service, and so forth. If the current subscription or financial arrangement

is found to be in place at step **380**, the system may continue with the handling of the service request as indicated at step **382**.

[**0089**] If at step **380** updating or fee authorization is required, a notification to this effect may be generated as indicated at step **384**. Such notification will generally take the form of a message transmitted from the service facility to the diagnostic system as described above. Moreover, the notification may include one or more interactive pages for ordering or authorizing the required fee arrangement. Upon completion of such information or authorizations, the requested service may be ordered as indicated at step **386**. Where the authorization is not received, the request handling may be aborted at this stage. Upon transmission and receipt of the order or authorization data from the diagnostic system to the service facility, the service facility may perform verification routines as indicated at step **388**, such as by comparing authorization codes with established codes stored within the subscription index. The subscription index is updated at step **390**. Such updating will typically include indication of new expiration or renewal dates, addition of the authorization or fee arrangement to service history databases, and addition of the requested and authorized fees to accounting databases for debiting or invoicing purposes. Finally, once the required financial arrangement is established or verified, the handling of the service request may continue as indicated at step **392**.

[**0090**] **FIG. 16** illustrates exemplary logical steps for transmitting service and diagnostic programs from the service facility to diagnostic systems. As mentioned above, such programs may include new or revised examination sequences, protocols, and the like. While such protocols may be distributed on supports such as CD ROM discs, they may alternatively be supplied via the network connection established between the service facility and the diagnostic systems. As used herein, the term program also refers to prerecorded or live transmissions such as video and audio transmissions employed by the facilities housing the diagnostic systems for personnel training purposes and the like. Such programs may be stored for distribution over a network as scheduled by the diagnostic system personnel, or may be prescheduled, such as through a preestablished training program or periodic training sessions.

[**0091**] The logical steps depicted in **FIG. 16**, denoted generally by the reference numeral **400**, begin with definition of the program at step **402**. In general, and in particular for diagnostic system protocols, such programs will be defined specifically for the particular modality of the diagnostic systems, and, where appropriate with additional specificity according to the system type, model, and so forth. Such program content may be defined by the service facility or by other content providers. At step **404**, the program is stored, such as in a database **156** or other storage device accessible to the service facility (see **FIG. 4**).

[**0092**] Several scenarios are presently envisioned for distribution of the programs via the service system described above. In particular, such programs may be distributed at the initiation of the service facility, or upon request by the diagnostic system. Where the service facility makes such programs available, the programs may be distributed via a "push" or "pull" scenario. In the former case, the programs are downloaded at the initiation of the service facility as described below. In the latter case, the diagnostic system is notified of the availability of the program, and may download or upgrade the system at will by recontacting the service facility. In either case, notification is displayed at the diagnostic system through the interactive interface to inform the operations personnel of the availability or the presence of the program. For example, in the case of examination protocols, notification may be provided via the protocol page illustrated in **FIG. 11**, with the new examination protocol either stored locally at the diagnostic system, or available upon request from the service facility, or from a library or other resource to which the service facility or diagnostic system browser may connect the diagnostic system. Such connections may be implemented through conventional Uniform Resource Locator (URL) links.

[**0093**] At step **406** of **FIG. 16**, the service facility processing system determines whether the program is to be distributed via a "push" or "pull" scenario. If the program is to be downloaded directly via a "push" scenario, subscription records are obtained from the service facility databases at step **408** to determine the present status of service subscriptions, and to compose a list of subscribing diagnostic systems to which the program is applicable and should be distributed. At step **410** one or more messages to such systems are composed. Where programs are available or may be used by various system types or models, several messages may be composed at step **410** specifically adapted to the variations between the system types. Returning to step **406**, where a "pull" scenario is to be employed for the program distribution, the subscription records of the service facility are again consulted at step **412** to develop a subscriber list to which the program should be made available. In general, such pull lists may be compiled where specific programs, including training sessions, protocols, and so forth, will be made available on a pay-per-use, one-time payment basis, or similar arrangements. At step **414**, one or more messages are composed for the subscriber list generated at step **412**. From either step **410** or **414**, the service facility may proceed to contact the diagnostic systems and to establish the network connection described above, as indicated at step **416**. At step **418** a message notifying the diagnostic system personnel of the existence and availability of the program is transmitted to the connected diagnostic system. Where the "push" distribution scenario is employed, step **418** may include loading of the program on the diagnostic system without requiring the intervention of the system operations personnel, but including notification of the presence of the new program.

[**0094**] As mentioned above, in lieu of the service facility-initiated distribution mechanism, the diagnostic system itself may originate program requests. Thus, as indicated at step **420**, such request may be formulated, typically as a service request as described above. At step **422** a subscription requirement associated with the program may be checked, if such a requirement is stored locally at the diagnostic system. Where such a requirement is stored at the diagnostic system, the subscription manager module of the system may be accessed as indicated at step **424**, and the requirement and status compared as indicated at step **426**. If the comparison made at step **426** determines that the program requires a subscription status or other arrangement or authorization which is not currently held by the diagnostic system, notification to the user is provided as indicated at step **428**. From either step **426** or step **428**, the system may continue with the

program request procedure, or other interactive service procedures as noted at step **430**. As mentioned above, such subscriptions, including for programs and protocols, may be of set to expire at particular times or after fixed durations. In addition to the subscription verification, comparisons made at step **426** may include verifications of hardware or software configurations to ensure that particular programs or protocols are suitable for the requesting system.

[**0095**] Where the foregoing logic allows the diagnostic system to proceed with ordering the requested program, a connection is established at step **432** with the service facility. At step **434** the program request is transmitted, such as in the same manner as other service requests. At step **436** the service facility processing system may access the site subscription index, in much the same manner as described above with respect to the steps of **FIG. 15** (see, e.g., step **368**). The subscription index data is then compared with the similar data from the diagnostic system, as well as with requirements imposed by the particular program being requested. At step **438** this status is compared, and if additional subscriptions, data, or fee authorization is required, notification is provided via a return message to the diagnostic system as indicated at step **440**. Where the foregoing steps permit transmission of the program according to the request, a message indicating its availability is transmitted at step **418** as described above. Again, the message may be accompanied with the program data in accordance with a "push" scenario or may be transmitted at a subsequent time.

[**0096**] Where the program data is transmitted at step **418**, an installation step follows as shown at step **442**. The installation step may include expanding of program files, modification of resident files at the diagnostic system, enabling of software applications, and so forth. Where the requested program includes audio or video training sessions, other steps may be included at this installation stage, such as routing the requested program to a predetermined location or locations. In addition to the installation step the subscription data, both at the diagnostic system and the service facility, is updated at step **444**. For program distribution on such fee arrangements as pay-per-use, one-time payment, or expanded fee-based subscription services is provided, the updating performed at step **444** may include both updating of subscription manager and subscription index files, as well as updating of accounting files for debiting or invoicing the subscribers account. At step **446** the service facility may be disconnected from the diagnostic system.

[**0097**] As noted above, the interactive nature of the program distribution permits notification of the diagnostic system user by means of visual or auditory messages at the diagnostic system. Thus, as indicated at step **448**, a message is posted at the diagnostic system, indicating the availability or transfer of the program at the initiation of the service facility or in response to a request from the diagnostic system. Where the program is made available, but is not immediately transferred to the diagnostic system, a delayed transmission or subscriber "pull" step may be included as indicated at step **450**. The logic involved in such delayed transmission will typically follow the foregoing steps, including establishing a network connection between the diagnostic system and the service facility, verification of subscriber status, and transmission of the program. Once the program has been transmitted to the diagnostic system, it is installed as indicated at step **452**. Again, the subscription data, both at the diagnostic system and at the service facility, is updated to indicate the current status of the program at step **454** as described above.

1.-**44**. (canceled)

45. A method for providing remote service to a medical diagnostic system, the method comprising the steps of:

originating a service request for operational servicing of the medical diagnostic system via a user interface in the medical diagnostic system;

transmitting the service request to a service facility via a network connection;

acknowledging receipt of the service request automatically by the service facility via an electronic message to the medical diagnostic system.

46. The method of claim **22**, comprising the further step of transmitting operational data from the medical diagnostic system to the service facility representative of a potential operational malfunction of the medical diagnostic system.

47. The method of claim **23**, wherein the operational data is transmitted from the medical diagnostic system to the service facility in response to a prompt by the service facility.

48. The method of claim **24**, wherein the prompt is generated by the service facility automatically in response to the service request.

49. The method of claim **22**, comprising the further step of transmitting from the medical diagnostic system data representative of the medical diagnostic system type and identification.

50. The method of claim **22**, wherein the service request is generated through a preconfigured browser page accessible on the user interface.

51. The method of claim **22**, comprising the further step of displaying a visual indicia at the medical diagnostic system indicating receipt of the electronic message from the service facility.

52. A method for exchanging service data between a plurality of medical diagnostic systems and a central service facility, the method comprising the steps of:

composing a service message on a medical diagnostic system, the service message relating to operational servicing of the medical diagnostic system;

linking the medical diagnostic system to a remote service facility via a network connection;

transmitting the service message from the medical diagnostic system to the remote service facility for remote operational servicing of the medical diagnostic system; and

automatically replying to the service message by the service facility to the medical diagnostic system via a return electronic message.

53. The method of claim **29**, wherein the service message is composed via a user interface.

54. The method of claim **29**, wherein the service message includes data uniquely identifying the medical diagnostic system.

55. The method of claim **31**, comprising the further step of automatically accessing electronic records relating to the medical diagnostic system by the service facility in response to the service message.

56. The method of claim **32**, wherein the electronic records include data representative of an operational service subscriber status of the medical diagnostic system.

57. The method of claim **32**, wherein the electronic records include data representative of operational service history for the medical diagnostic system.

58. The method of claim **29**, comprising the further steps of:

determining at the service facility log data required to reply to the service message;

automatically linking the service facility to the medical diagnostic system via a network connection; and

transmitting the log data from the medical diagnostic system to the service facility.

* * * * *