



US 2006020779A1

(19) **United States**

(12) **Patent Application Publication**
Yu

(10) **Pub. No.: US 2006/0207799 A1**

(43) **Pub. Date: Sep. 21, 2006**

(54) **DRILLING TOOL FOR DRILLING WEB OF CHANNELS FOR HYDROCARBON RECOVERY**

Related U.S. Application Data

(62) Division of application No. 10/652,351, filed on Aug. 29, 2003, now Pat. No. 7,073,577.

(75) Inventor: **Andrew Dingan Yu**, Martinez, GA (US)

Publication Classification

(51) **Int. Cl.**
E21B 7/00 (2006.01)
(52) **U.S. Cl.** **175/78**; 175/62; 166/50

Correspondence Address:
Ashok K. Janah
Janah & Associates, P.C.
Suite 106
650 Delancey Street
San Francisco, CA 94107 (US)


(57) **ABSTRACT**

Hydrocarbons can be recovered from a subterranean reservoir by drilling an injection well bore having an outlet in the reservoir and drilling a production well bore spaced apart from the injection well bore and having an inlet in the reservoir. A drilling tool is capable of being inserted into a well bore to drill a web of channels to form a permeable zone in the reservoir. The drilling tool comprises a drill head adapted to drill a web of channels that radiate out from the well bore to form the permeable zone, and a power source to supply power to the drill head.

(73) Assignee: **Applied Geotech, Inc.**

(21) Appl. No.: **11/441,303**

(22) Filed: **May 25, 2006**






Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

DRILLING TOOL FOR DRILLING WEB OF CHANNELS FOR HYDROCARBON RECOVERY

CROSS REFERENCE

[0001] This application is a divisional application of U.S. Pat. No. _____, application Ser. No. 10/652,351, filed on Aug. 29, 2003, which is incorporated by reference herein in its entirety.

BACKGROUND

[0002] Embodiments of the present invention relate to the recovery of hydrocarbons from a subterranean reservoir.

[0003] Hydrocarbons that are recovered from a subterranean reservoir include oil, gases, gas condensates, shale oil and bitumen. To recover a hydrocarbon, such as oil, from a subterranean formation, a well is typically drilled down to the subterranean oil reservoir and the oil is collected at the well head. The recovery of hydrocarbons that are very heavy or dense, such as for example, the recovery of bitumen from oil sands, are especially difficult as these materials are often thick and viscous at reservoir temperatures, so it is even more difficult to extract them from the subterranean reservoir. For example, bitumen can have a viscosity of greater than 100,000 centipoises, which makes it difficult to flow. Suitable methods for the recovery of these heavier viscous hydrocarbons are desirable to increase the world's supply of energy. Methods for recovering bitumen are particularly desirable because there are several trillion barrels of bitumen deposits in the world, of which only about 20% or so are recoverable with currently available technology.

[0004] A conventional method of recovering hydrocarbons from a subterranean oil reservoir is by utilizing both a production well and an injection well. In this method, a vertical production well is drilled down to a hydrocarbon reservoir, and a vertical injection well is drilled at a region spaced apart from the production well. A fluid is injected into the hydrocarbon reservoir via the injection well, and the fluid promotes the flow of hydrocarbons through the reservoir formation and towards the production well for collection. However, a problem with this method is that the injected fluids tend to find a relatively short and direct path between the injection and production wells, and therefore, bypass a significant amount of oil in the so called "blind spot". Furthermore, if the injected fluid, such as steam, is lighter than the reservoir oil, the injected fluid tends to flow through the upper portion of the reservoir and thus bypass a significant amount of oil at the bottom of the reservoir. Due to these unfavorable mechanisms, injected fluids tend to reach the production well at a relatively early time. When this "early breakthrough" of the fluids occurs, the steam-oil ratio increases rapidly and recovery efficiency of the hydrocarbons is reduced.

[0005] In one method of improving the recovery of hydrocarbons using vertical injection and production wells, a horizontal high-permeability web is formed at the bottom of the production well to increase the hydrocarbon recovery area at that region, as described in U.S. Pat. No. 6,012,520, which is incorporated herein by reference in its entirety. The high-permeability web has multiple channels or fracture zones that are formed horizontally about a receiving region of the production well located near the bottom of the reservoir. To recover the hydrocarbons, a neighboring injection well injects steam into a top portion of the reservoir via an injection inlet. The injected steam heats the hydrocarbons in the reservoir, and pushes the hydrocarbons downwards for collection by the high-permeability web of the production well.

[0006] However, while this method increases the recovery area immediately about the production well and displaces the oil in a "gravity stable" manner, its extraction efficiency per unit area is low for subterranean reservoirs having viscous hydrocarbons that are difficult to flow under typical injection pressures. Oil recovery from these reservoirs, such as oil sands reservoirs, remains difficult and yet highly desirable.

[0007] In one version of a conventional recovery method, a "huff and puff" process is used to recover bitumen from a subterranean oil sands reservoir. In this method, a vertical well bore is drilled to the reservoir and steam is injected towards the bottom of the bore and into the surrounding reservoir. The steam heats the bitumen about the well bore to reduce its viscosity and cause it to flow back to the well bore. When a desired amount of the bitumen has been collected in the bottom of the well bore, the well is pumped off and the oil is collected at the well head. However, the steam typically traverses only the area immediately around the vicinity of well bore which may be only a small portion of the underground reservoir. Thus the amount of oil recovered is limited by the distance the steam can travel before it cools and condenses, and a large portion of the reservoir may not be reached by steam using this method.

[0008] In another conventional method, a Steam Assisted Gravity Drainage (SAGD) process is used to recover bitumen from a subterranean reservoir. In this method, a horizontal production well bore is formed near the bottom of the reservoir. A horizontal steam injection well is formed parallel and above the production well bore. The injected steam heats the bitumen between the wells, as well as above the injection well, and gravitational forces drain the heated bitumen fluids down to the production well for collection. However, this method has problems that are similar to those of the huff and puff method. Namely, after the steam from the injection well reaches the top of the reservoir, the bitumen production becomes limited by the extent to which the steam can laterally expand. As heat losses from the steam to the overburden above the reservoir are high, the lateral expansion is restricted, and a large amount of the reservoir may not be reached by the heated steam.

[0009] Thus, it is desirable to efficiently recover hydrocarbons from a large area of a subterranean reservoir. It is furthermore desirable to recover dense or viscous hydrocarbons with injection and production wells that provide a heated fluid to the subterranean reservoir.

DRAWINGS

[0010] These features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings, which illustrate examples of the invention. However, it is to be understood that each of the features can be used in the invention in general, not merely in the context of the particular drawings, and the invention includes any combination of these features, where:

[0011] FIG. 1 is a schematic sectional side view of an embodiment of an injection and a production well connected by a permeable zone having a predetermined shape;

[0012] FIG. 2 is a schematic top view of an embodiment of a well pattern showing injection and production wells connected by a permeable zone;

[0013] FIG. 3 is a schematic top view of a 5-spot well pattern having injection and production wells connected by a permeable zone;

[0014] FIG. 4 is a schematic sectional side view of another embodiment of a well having a permeable zone;

[0015] FIG. 5 is a schematic sectional side view of an embodiment of a channel having a porous liner; and

[0016] FIG. 6 is a schematic top view of a drilling tool adapted to drill multiple conduits to form a permeable zone having a predetermined shape.

DESCRIPTION

[0017] The present invention is used to recover hydrocarbons from a subterranean hydrocarbon reservoir 11. The hydrocarbons can be in the form of oil, gas, gas condensate, shale oil and bitumen. The recovery method may be particularly beneficial in the recovery of dense hydrocarbons, such as bitumen.

[0018] To recover hydrocarbons from a subterranean hydrocarbon reservoir 11, a substantially vertical production well 31 is drilled into the ground to receive and recover the hydrocarbons, as shown in FIG. 1. The production well 31 comprises a well bore 32 drilled through one or more overlying layers, such as an overburden 12 to a desired depth in or beneath the subterranean hydrocarbon reservoir 11. A well casing 33 can extend at least partially along the length of the well bore 32 to structurally support the bore 32. The well bore 32 comprises a hydrocarbon receiving zone 34 having one or more receiving inlets 35 in or about the subterranean reservoir 11, the inlets 35 comprising, for example, perforations in the well casing 33, or a portion of the well bore 32 that is otherwise open to the surrounding subterranean formation, such as an open lower end of the well bore 32. The inlets 35 into the well bore 32 are desirably located towards the bottom of and even underneath the hydrocarbon reservoir 11.

[0019] Hydrocarbons are collected from the well 31 through a tubing 36 that extends through the well bore 32 to a well head 37 located towards the top of the well bore 32. The hydrocarbons can be lifted through the tubing 36 by natural pressure, induced pressure from injected steams, or with the assistance of a pump (not shown) to pump the hydrocarbons from the bottom of the bore 32 to the well head.

[0020] A substantially vertical injection well 21 is provided to inject a fluid into at least a portion of the subterranean reservoir 11 to mobilize and promote the flow of hydrocarbons towards the production well 31. The injection well 21 comprises an injection well bore 22 that is drilled at a location that is spaced apart from the production well 31. The injection well bore 22 can be drilled to a desired depth in or beneath the hydrocarbon reservoir 11, and a well casing 23 can be provided that extends along at least a portion of the bore 22 to structurally support the well bore 22. The

injection well bore 22 comprises an injection zone 24 having one or more injection outlets 25 that may be, for example, perforations in the well casing 23 or portions of the well bore that are otherwise open to the surrounding subterranean formation. The injection outlets 25 are desirably located adjacent to the reservoir 11 to provide fluid to the reservoir 11, and may be near the bottom of the reservoir 11.

[0021] Typically, a heated fluid is injected by the injection well 21 to heat the hydrocarbons in the reservoir 11, thereby reducing the viscosity of and mobilizing the hydrocarbons so the hydrocarbons flow through the subterranean reservoir 11 towards the receiving zone 34 of the production well 31. For example, the heated fluid can comprise a vaporized liquid such as steam that is supplied by an injection fluid supply 27 such as a steam generator, and injected into the subterranean reservoir 11 via tubing 26. The steam can also be super-heated to provide more thermal energy. As another example, the injected fluid can comprise an oxygen-containing fluid. In this version, an oxygen-containing fluid, such as oxygen gas or air, is supplied by injection fluid supply 27 and is injected into the subterranean reservoir 11 at the injection zone 24. The combustible fluid and reservoir hydrocarbons can be ignited, for example, by lowering an igniter to the injection zone 24. Burning hydrocarbons in the reservoir 11 generates heat that reduces the viscosity of the remaining hydrocarbons. Also, the pyrolysis of the hydrocarbons can decompose heavy hydrocarbons into smaller hydrocarbon molecules that flow more easily to the production well 31, and can also dilute heavier hydrocarbons to promote their flow. The injection fluid may also comprise light hydrocarbons that are easier to ignite to facilitate initiation of the combustion and hydrocarbon burn.

[0022] To improve the recovery of the hydrocarbons, a permeable zone 13 is formed to connect the injection and production wells 21, 31. The permeable zone 13 comprises a patterned web of channels 15 in the subterranean reservoir 11 that radiate outwardly from the outlet 25 of the injection well 21 and connect to the inlet 35 of the production well 31. For example, the permeable zone 13 can comprise a first patterned web of channels 17a that radiates out from the outlet 25 of the injection well 21 and connects to a second patterned web of channels 17b that radiates out from the inlet 35 of the production well 31. The permeable zone 13 having the patterned web of channels 15 increases the flow of hydrocarbons to the production well 31 by providing a highly permeable and accessible pathway in which the hydrocarbons from the reservoir 11 can flow towards the production well 31. The permeable zone 13 also provides an extended heated fluid flow area adjacent to the hydrocarbon reservoir 11 to allow heating of a larger portion of the reservoir 11, and thus, provides for the recovery of a greater number of hydrocarbons from the reservoir 11. For example, as shown in FIG. 1, the permeable zone 13 is formed in a lower section of the subterranean hydrocarbon reservoir 11 such that the hydrocarbons above the permeable zone 13 in the extended region between the injection and production wells 21, 31 are heated by the fluids injected into the permeable zone 13. The heated hydrocarbons in the reservoir 11 above the permeable zone 13 are drained via gravity into the zone 13, in which the heated hydrocarbons flow through to the receiving zone 34 of the connecting production well 31. Thus, the permeable zone 13 provides enhanced heating of an extended area of the hydrocarbon

reservoir 11 and improves flow of the heated hydrocarbons to the production well 31 to increase recovery of the hydrocarbons.

[0023] The permeable zone 13 can have a patterned web of channels 15 with a predetermined shape that induces a gravity flow of the mobilized hydrocarbons towards the production well 31. For example, the permeable zone 13 can be formed about a plane that is angled downwardly from the injection well bore 22 to the production well bore 32. A suitable angle may be a vertical angle θ , as shown in FIG. 1, of from 0° to about 30° , such as at least about 5° , and even from about 5° to about 20° . To provide a connecting permeable zone 13 having a steeper angle, the injection outlets 25 can be located at positions along the injection well bore 22 that are above the receiving inlets 35 of the production well bore 32. The production well bore 32 can also be drilled into a region below the subterranean reservoir 11, such as in an underburden 14, to provide the desired angle.

[0024] The permeable zone 13 also desirably fans out from at least one and preferably both of the wells 21, 31 to provide one or more wedge-like shapes that increase in width with increasing distance from the bore to cover a larger area of the reservoir 11, as shown in FIGS. 2 and 3. By forming a zone 13 that radiates out from the bores with increasing width, an increased area of the hydrocarbon reservoir 11 can be heated by the fluid passed through the fluid flow zone 13. For example, the permeable zone 13 can fan out from at least one of the well bores 22, 32 to cover an extended area between the wells 21, 31, such as an area about a "blind spot" between the wells. A horizontal angle ϕ carved out by the radiating permeable zone 13, as shown in FIG. 2, may be from about 0° to about 90° , and even from about 30° to about 60° . In one version, as shown in FIGS. 2 and 3, the permeable zone 13 comprises a first radiating section 13a having a first patterned web of channels 17a connected to the injection well bore 22 of well 21, and a second radiating section 13b having a second patterned web of channels 17b connected to the production well bore 32 of well 31. The first and second sections 13a and 13b of the permeable zone 13 are connected together at a point where the sections 13a, 13b are fairly wide, thus, enhancing heating of the regions between the wells 21, 31.

[0025] The permeable zone 13 can also comprise a predetermined shape that connects the injection wells and production wells to form a convoluted and indirect path, such that the permeable zone 13 extends to cover a larger portion of the hydrocarbon reservoir 11. For example, as shown in FIG. 2, the permeable zone 13 can comprise first and second sections 13a, 13b that are angled with respect to each other such that section 13a bisects section 13b with a horizontal angle α of from about 90° to about 180° degrees, such as about 90° degrees to about 150° degrees. The vertical angle can be from about 0° to about 30° degrees, such as from example, about 5° to about 20° degrees. This circuitous and indirect route between the injection and production wells 21, 31 allows the fluids flowing in the permeable zone 13 to heat regions of the reservoir 11 that are remote from the wells 21, 31 and that otherwise could be difficult to reach.

[0026] The method of recovering hydrocarbons by passing a heated fluid through the permeable zone 13 can be applied to various injection and production well patterns 41. For

example, the method of hydrocarbon recovery can be applied to a 5-spot well pattern 41, as shown in FIG. 3. Although the 5-spot well pattern 41 is used as an example, similar principles could be used to apply the recovery method comprising the permeable zone 13 to configurations having only one or two wells, and also configurations having wells in a 4, 7 or 9 spot pattern. In the exemplary 5-spot well pattern 41, alternating production and injection wells 31, 21 are drilled to form an array of wells disposed at the intersection points of an ordered grid pattern 42, for example, with the wells 31, 21 located at the intersection points 43 of the pattern 42. The grid pattern 42 provides extended coverage of a reservoir 11 with multiple hydrocarbon recovery points to increase hydrocarbon production. The intersection points of the grid pattern 42 form one or more squares 46, and each square, such as the first square 46a, has the injection and production wells 21a,e, 31a,b arranged in an alternating fashion at the vertices of the square 46a such that the production wells 31a, 31b lie facing each other along one diagonal of the square and the injection wells 21a, 21e lie facing each other along the other diagonal. In the version shown in FIG. 3, four squares 46a-d having this pattern of injection and production wells 21a-21e, 31a-31d are placed together to form the well pattern 41, with one of the injection wells 21e forming a common vertex or intersection point 43 of all four squares 46a-d.

[0027] The pairs of injection wells and production wells in each square 46a-d are connected together via one or more permeable zones 13. The wells can be each interconnected to the others via the permeable zone 13, as shown in FIG. 3. Desirably, the permeable zone 13 connects the injection and production wells in each square 46a-46d in an indirect manner to form a convoluted path therebetween. For example, as shown in FIG. 3, each square 46a-d comprises a permeable zone 13 having first through eighth triangular sections 13a-h. Each section 13a-h fans out with increasing width from a single well 21a, 21e, 31a, 31b, and pairs of sections of adjacent injection and productions such as 13a and 13b abut together along a base 44 of each triangular section about the interior region 16a of the square 46a, also called the blind spot, to form an interconnected zone 13. Thus, the sections 13a-h of the permeable zone 13 form a convoluted and circuitous highly-permeable route to allow the fluids flowing in the permeable zone 13 to reach the interior region 16a, and thereby heat even remote regions 16, such as the blind spots.

[0028] The permeable zones 13 in each square 46a-d form relatively "open" region of the reservoir 11, through which the heated fluid can readily pass, and which are spaced apart from one another in the grid pattern 42 by relatively "closed" and unexcavated regions 45 of the reservoir 11 that remain in the areas of each square 46 where the permeable zone 13 has not been formed. The unexcavated regions 45 are typically in areas where the path between the production well 31 and injection well 21 is relatively short and direct, such as along a side 47 of the square 46a. For example, the unexcavated regions 45 can comprise obtuse triangles bounded in each square 46a by two sections 13a,b of the permeable zone 13 and the side 47 of the square 46a. The relatively closed unexcavated regions 45 force the heated fluid to primarily take a more convoluted path between the wells via the permeable zone 13, and thereby sweep out a greater region of the reservoir 11. However, because the distance between the wells in the unexcavated regions 45 is

relatively short, the heated fluid gradually seeps into the unexcavated regions **45** and recovers hydrocarbons from these regions as well. Thus, the well pattern **41** having the permeable zones **13** and unexcavated regions **45** of **FIG. 3** provides for the recovery of hydrocarbons from a maximized area in the subterranean reservoir **11** by facilitating the flow of heated fluid to remote or hard to reach areas and controlling a flow of the heated fluid to the more easily accessible areas. This novel configuration prevents the steam from initially taking the shortest path between the outlet of the injection well and the inlet of production well, and instead forces the steam to access a larger area between the wells. At the same time, it allows hydrocarbons in the closed regions to be gradually swept as the open regions expand into them. Thus, the array of wells in a grid pattern with permeable zones therebetween efficiently recovers hydrocarbons from the subterranean region.

[0029] In another version, which can be applied, for example, to a “huff and puff” process, a well **71** is setup to operate as both an injection and production well, as shown in **FIG. 4**. The well **71** comprises a well bore **72**, such as a substantially vertical well bore **72**, that extends into the subterranean hydrocarbon reservoir **11**. The well **71** can comprise a well casing **73** and a tubing **76** through which fluids such as steam, oxygen, other gases and hydrocarbons, are flowed. A permeable zone **13** having a predetermined shape is formed that extends upwardly from an injection outlet **75** in an injection and receiving zone **74** of the well bore **72** into the subterranean hydrocarbon reservoir **11**. A suitable vertical angle of the permeable zone **13** may be at least about 5° , such as from about 5° to about 30° , and even from about 10° to about 20° . In operation, heated fluids, such as for example steam or oxygen-containing gases, are introduced into the permeable zone **13** via the injection outlet **75**. The heated fluids are “shut in” the well **71**, to allow heating of the hydrocarbons above the permeable zone **13**. The heated hydrocarbons flow into the permeable zone **13** and drain via gravitational forces along the angled zone **13** into the injection and receiving zone **74** of the well bore **72**. Once a sufficient volume of hydrocarbons has been collected in the bottom of the well bore **72**, the hydrocarbons are produced to a well head **77** of the well **31**, for example by pumping off the well **71**, to allow recovery of the hydrocarbons. The method allows for an extended region of the subterranean reservoir **11** about the well bore **72** to be heated, thereby increasing the recovery of the hydrocarbons from the reservoir **11**.

[0030] Methods of forming the permeable zone **13** include, for example, high-power microwave irradiation, high-pressure water jet drilling, mechanical drilling, explosive fracturing, hydraulic fracturing and drilling with lasers. In one version of a microwave irradiation method, a microwave irradiation device such as a high-power microwave antenna is lowered into one or more of the production and injection well bores **32**, **22**. The microwave irradiation device generates microwave beams that irradiate regions of the subterranean reservoir **11** adjacent to the well bore, and the water in the irradiated regions is quickly vaporized by the microwave energy. This rapid generation of large amounts of water vapor induces fractures in the regions irradiated by the microwave beams, causing increases in the permeability of the irradiated region and thereby forming a highly permeable zone **13** comprising a patterned web of channels **15** radiating out from the well bore. The frequen-

cies, directions, intensities, angles and durations of the microwave beams are selected to provide desired characteristics of the permeable zone **13**, such as the desired predetermined shape, including the direction and angle of the permeable zone **13**, and the desired permeability of the zone **13**. A suitable permeability of the irradiated region, and thus the permeable zone **13**, is for example more than about one Darcy. Multiple radiating permeable zones **13** can also be provided by irradiating the subterranean reservoir **11** from the bore in multiple different directions, for example to connect wells in adjacent 5-spot patterns. Microwave methods of irradiation are described in U.S. Pat. No. 5,299,887 to Ensley et al, herein incorporated by reference in its entirety and U.S. Pat. No. 6,012,520 to Yu et al., herein incorporated by reference in its entirety.

[0031] The permeable zone **13** can also be formed by at least one of a mechanical and a high pressure water jet drilling method. Methods of drilling with a high pressure water jet drill are described in U.S. Pat. No. 5,413,184 to Landers et al., and U.S. Pat. No. 6,012,520 to Yu et al., both of which are herein incorporated by reference in their entirety. In a method of drilling the permeable zone **13**, a drilling tool is lowered into one or more of the injection well bore **22** and the production well bore **32**. The drilling tool drills multiple channels **15** radiating out from the well bores **22**, **32**, to form a permeable zone **13** having a patterned web of channels, as shown for example in **FIGS. 2 and 3**. The multiple channels **15** provide a highly permeable and extended area into which the hydrocarbons and fluids can flow.

[0032] The multiple channels **15** of the patterned web can be formed in the predetermined shape, for example upwardly or downwardly angled, and can also be formed such that a horizontal angle ϕ formed between outermost channels **15a**, **15b** is from about 0° to about 90° , and even from about 30° to about 60° . The multiple channels **15** are desirably large enough to provide a good flow of hydrocarbons and fluids through the channels **15**, while remaining small enough such that the portions of the reservoir **11** above the permeable zone **13** are not destabilized. A suitable thickness of a channel **15** may be, for example, from about 1 inch to about 12 inches, such as from about 2 inches to about 6 inches.

[0033] The channels **15** can further be stabilized by providing a liner **51** about at least a portion of the channel **15**, as shown for example in **FIG. 5**. The liner **51** may be desirable as the drilling and depletion of the hydrocarbons can lead to unstable conditions in the subterranean reservoir **11**. The liners **51** can be inserted into the channel **15** by lowering the liner **51** into the well bore and extending the liner from the well bore into the channel **15**. The liner **51** comprises a top section **52** that is permeable to the hydrocarbons and fluids, for example the top section **52** can comprise a permeable material such as a highly porous net, a flexible plastic sheet with holes or a synthetic porous media. A bottom section **53** of the liner **51** is shaped to improve the fluid flow through the channel **15**, for example, the bottom section **53** can comprise a substantially impermeable and flexible plastic sheet with a groove **54** to facilitate gravity drainage of the fluids. The two sections **52** and **53** are separated by spaced apart braces **55** that provide structural support for the liner **51** and channel **15**.

[0034] An example of a drilling tool 61 suitable for forming the permeable zone 13 is shown in FIG. 6. The drilling tool 61 comprises a drill head 62 that is capable of being inserted into the well bores 22, 32 and positioned adjacent to the injection zone 24 or receiving zone 34. The drill head 62 is adapted to drill a permeable zone 13 having the desired predetermined shape, such as a permeable zone 13 that fans out from the well bore 22, 32 at a horizontal angle of from about 30 degrees to about 60 degrees. The drill head 62 can also be adapted to drill a permeable zone 13 that is angled upwardly or downwardly at an angle of at least about 5 degrees. In one version, the drill head 62 comprises multiple high-pressure water jet nozzles 63 that are positioned to simultaneously drill multiple channels 15 along a predetermined arc of a bore wall 64 by shooting high-pressure water jets at predetermined points along the arc. In another version, the drill head 62 comprises multiple rotating drilling bits 63 that are adapted to simultaneously drill the multiple channels 15 along the arc in the bore wall 64 to form the permeable zone 13 having the predetermined shape. A drilling tool power source 65 supplies power to the drill head 62 to drill the channels 15.

EXAMPLE

[0035] The following example demonstrates the advantageous process economics of bitumen recovery using a 5-spot well pattern having the permeable zone 13. In this example, the estimated total reservoir volume within a pattern region that is 25 meters thick and with a distance of about 330 feet between adjacent injection and production wells, as is typical for oil sands in Alberta Canada, is $330 \text{ ft} \times 330 \text{ ft} \times 25 \text{ m} \times 3.28 \text{ ft/m} = 9 \times 10^6 \text{ ft}^3$. The bitumen content is typically 25% by volume of the reservoir region, or $2.2 \times 10^6 \text{ ft}^3$ or $4 \times 10^5 \text{ bbl}$. The heat of combustion of the bitumen is 19,000 BTU/lb and the density of the bitumen is 62 lb/ft³. Thus, the total heat content of the bitumen in a pattern = $19000 \text{ BTU/lb} \times 62 \text{ lb/ft}^3 \times 2.2 \times 10^6 \text{ ft}^3 = 2.6 \times 10^{12} \text{ BTU}$.

[0036] The energy required to heat the reservoir via a steam driven recovery process can also be estimated. The oil sands comprising the bitumen typically contain 10% water, 25% bitum and 65% sand grains by volume. The steam driven recovery process operates under a reservoir temperature of 300° F. The enthalpies for steam at 300° F. and water at 70° F. are 1180 and 38 BTU/lb, respectively. The heat capacities for bitumen and sand are 0.60 and 0.19 BTU/lb/° F. Thus, the energy required to heat the reservoir can be estimated as:

$$\text{Water} = 0.1 \times 62 \text{ lb/ft}^3 \times 2.2 \times 10^6 \text{ ft}^3 \times (1180 - 38) \text{ BTU/lb} = 1.6 \times 10^{10} \text{ BTU}$$

$$\text{Bitumen} = 0.25 \times 62 \text{ lb/ft}^3 \times 2.2 \times 10^6 \text{ ft}^3 \times 0.6 \text{ BTU/lb/}^\circ \text{F} \times (300 - 70)^\circ \text{F} = 4.3 \times 10^{10} \text{ BTU}$$

$$\text{Sand} = 0.65 \times 164 \text{ lb/ft}^3 \times 2.2 \times 10^6 \text{ ft}^3 \times 0.19 \text{ BTU/lb/}^\circ \text{F} \times (300 - 70)^\circ \text{F} = 1.0 \times 10^{10} \text{ BTU}$$

[0037] So the total energy is $3.0 \times 10^{10} \text{ BTU}$, which is only about 1.2% of the total heat content of the in-place bitumen.

[0038] For a recovery process involving combustion, the reservoir is assumed to operate at a temperature of about 550° C., which is about 1000° F. So the extra energy required for the combustion process over the steam process is approximately:

$$(0.1 \times 10 \times 62 + 0.25 \times 0.6 \times 62 + 0.65 \times 0.19 \times 164) \times 2.2 \times 10^6 \times (1000 - 300) = 5.5 \times 10^{10} \text{ BTU}$$

[0039] So the total energy required for the combustible fluid process is $8.5 \times 10^{10} \text{ BTU}$. Overall, a safe estimate of the energy required for a recovery process with steam or combustion is $1.0 \times 10^{11} \text{ BTU}$, or about 4% of the energy of the bitumen in the reservoir.

[0040] The cost of fabricating the permeable zones 13 can also be estimated. The energy required to fabricate a zone 13 for a 2.5-acre 5-spot well pattern by a high-power microwave method is estimated to be less than about 1% of the energy of the in-place bitumen. As oil sands having bitumen are typically fairly shallow and the unconsolidated sands are easy to drill, the costs of forming a zone 13 via mechanical drilling or high pressure water jet is not expected to exceed 2.5% of the energy of the in-place bitumen. Thus, the process of flowing steam or combustion through a permeable zone 13 in the reservoir is expected to be a highly cost-effective and efficient means of bitumen recovery.

[0041] The above description and examples show an improved method and well configuration for the recovery of dense hydrocarbons, such as bitumen, from a subterranean reservoir 11, by providing a highly permeable zone 13 having a patterned web of channels radiating out from and connecting injection and production wells 21, 31. The highly permeable zone 13 provides better heating of the hydrocarbons in the reservoir 11 by forming an extended heating area adjacent to and beneath portions of the reservoir 11 to quickly and efficiently heat a larger volume of the reservoir 11. Furthermore, a patterned grid 42 of wells can be provided having interconnecting permeable zones 13 with convoluted flow paths and spaced apart "open" and closed regions to control the flow of the fluids to areas in the reservoir 11 to maximize the recovery of hydrocarbons from the reservoir 11. Because the cost and energy of fabricating the permeable zone 13 and performing the recovery process is expected to be a small percentage of the overall value and energy content of the hydrocarbons in the reservoir 11, the permeable zone 13 is expected to provide a highly cost-effective and energy efficient means of recovering the hydrocarbons from the reservoir 11.

[0042] Although exemplary embodiments of the present invention are shown and described, those of ordinary skill in the art may devise other embodiments which incorporate the present invention, and which are also within the scope of the present invention. For example, other versions of web patterns can be used depending upon terrain, topography, and the viscosity of the hydrocarbon deposits. Therefore, the appended claims should not be limited to the descriptions of the preferred versions, materials, or spatial arrangements described herein to illustrate the invention.

What is claimed is:

1. A drilling tool capable of being inserted into a well bore to drill a web of channels to form a permeable zone in a subterranean reservoir, the drilling tool comprising:

(a) a drill head adapted to drill a web of channels that radiate out from the well bore to form a permeable zone; and

(b) a power source to supply power to the drill head.

2. A tool according to claim 1 wherein the drill head is adapted to drill a permeable zone that fans out from the well bore at a horizontal angle of from about 0° to about 90°.

3. A tool according to claim 2 wherein the drill head is adapted to drill a permeable zone that fans out from the well bore at a horizontal angle of from about 30° to about 60°.

4. A tool according to claim 1 wherein the drill head is adapted to drill a permeable zone that is angled upwardly or downwardly at an angle of at least about 5°.

5. A tool according to claim 1 wherein the drill head is adapted to drill channels having a thickness of from about 1 to about 12 inches.

6. A tool according to claim 4 wherein the drill head is adapted to drill channels having a thickness of from about 2 to about 6 inches.

7. A tool according to claim 1 wherein the drill head comprises rotating drill bits.

8. A tool according to claim 1 wherein the drill head comprises a plurality of rotating drilling bits that are adapted to simultaneously drill multiple channels along an arc of a wall of the bore well.

9. A tool according to claim 1 wherein the drill head comprises a high pressure water jet.

10. A tool according to claim 1 wherein the drill head comprises multiple high-pressure water jet nozzles that are positioned to simultaneously drill multiple channels along a predetermined arc of a wall of the bore well.

11. A tool according to claim 1 wherein the drill head comprises a microwave antenna.

12. A tool according to claim 1 wherein the drill head comprises a laser drill.

13. A drilling tool capable of being inserted into a well bore to drill a web of channels in a subterranean reservoir, the drilling tool comprising:

(a) a drill head adapted to drill a web of channels that radiate out from the well bore such that the horizontal angle formed between outermost channels is from about 0° to about 90°, and the web of channels is at an upward or downward angle of from 0° degree to about 30°; and

(b) a power source to supply power to the drill head.

14. A tool according to claim 13 wherein the drill head is adapted to drill a permeable zone that is angled upwardly or downwardly at an angle of at least about 5°.

15. A tool according to claim 13 wherein the drill head is adapted to drill channels having a thickness of from about 1 to about 12 inches.

16. A tool according to claim 13 wherein the drill head comprises a plurality of rotating drilling bits that are adapted to simultaneously drill multiple channels along an arc of a wall of the bore well.

17. A tool according to claim 13 wherein the drill head comprises a high pressure water jet.

18. A tool according to claim 13 wherein the drill head comprises multiple high-pressure water jet nozzles that are positioned to simultaneously drill multiple channels along a predetermined arc of a wall of the bore well.

19. A tool according to claim 13 wherein the drill head comprises a microwave antenna.

20. A tool according to claim 13 wherein the drill head comprises a laser drill.

* * * * *