


US 20070245735A1

(19) **United States**(12) **Patent Application Publication**
Ashikian(10) **Pub. No.: US 2007/0245735 A1**(43) **Pub. Date: Oct. 25, 2007**(54) **SYSTEM AND METHOD FOR STORING,
DISSEMINATING, AND UTILIZING ENERGY
IN THE FORM OF GAS COMPRESSION AND
EXPANSION INCLUDING A
THERMO-DYNAMIC BATTERY****Publication Classification**(51) **Int. Cl.**
F01K 3/00 (2006.01)(52) **U.S. Cl.** **60/659**(76) **Inventor: Daniel Ashikian, (US)**Correspondence Address:
DANIEL ASHIKIAN
1638 N. SAN FERNANDO BLV.
BURBANK, CA 91504 (US)(21) **Appl. No.: 11/805,093**(22) **Filed: Jul. 5, 2007****Related U.S. Application Data**

(63) Continuation-in-part of application No. 11/126,920, filed on May 10, 2005, which is a continuation-in-part of application No. 10/833,958, filed on Apr. 28, 2004, now abandoned, which is a continuation-in-part of application No. 09/854,682, filed on May 15, 2001, now abandoned.

(57) **ABSTRACT**

Thermo-dynamic battery is a energy storage unit for converting compressed gas energy into consumable electrical power for application uses with any device that requires electrical power to function. A method for storing electrical energy in the form of compressed gas and converting the same energy to electric power includes compressing gas and storing the compressed gas for release to drive a generator. A system and method for storing, disseminating, and utilizing energy in the form of gas compression and expansion comprises a method for expanding compressed gas in at least two stages and further provides for storing energy in the form of compressed gas through compression in at least two stages. Apparatus is provided to operate in accordance with the described procedure to contribute at or about 90% efficiency.

**SCHEMATIC VIEW OF THERMO-DYNAMIC BATTERY UNIT**




FIG. 1, SCHEMATIC VIEW OF THERMO-DYNAMIC BATTERY UNIT




FIG. 2 THERMO-DYNAMIC BATTERY

**SYSTEM AND METHOD FOR STORING,
DISSEMINATING, AND UTILIZING ENERGY IN
THE FORM OF GAS COMPRESSION AND
EXPANSION INCLUDING A THERMO-DYNAMIC
BATTERY**

[0001] This is continuation-in-part of pending patent application Ser. No. 11/126,920 filed May 10, 2005, which in turn was a continuation-in-part of patent application Ser. No. 10/833,958 filed Apr. 28, 2004, which in turn was a continuation-in-part of patent application Ser. No. 09/854,682 filed May 15, 2001, which filing date is hereby claimed.

BACKGROUND OF THE INVENTION

[0002] Generally, we mankind, have had major problems with relation to batteries that is, devices for storing energy for use when desired. The problems include: the charging of batteries, servicing of batteries, the non-reusability of batteries, and the highly dangerous, hazardous, and explosive, environmentally-polluting chemicals used in existing electrochemical batteries, and their heavy weight.

[0003] The thermo-dynamic battery unit of the invention solves all of these issues. It generates clean, usable energy, while remaining chemical and explosion free, lightweight, rapidly rechargeable, economical, and environmentally-friendly.

[0004] The present invention relates generally to a device for use in any application for providing power for any electrical device that employs battery power to function. More explicitly, the present invention discloses an innovative, high power device, which does not generate any harmful, environmentally-polluting residue. The present invention is extremely ecologically compatible in operation and design, actually replenishing clean ozone back into the atmosphere, is long lasting, and is designed to be re-usable unlike conventional units.

OBJECTS OF THE INVENTION

[0005] The present invention relates generally to a new electric power storage device. More distinctively, it provides and generation of electrical power in the form of compressed gas energy.

[0006] Another positive attribute of the present-invention is that the compressed gas is passed through a generator, which exchanges heat with the generator to increase the efficiency of the generator and its driver device. This enhances efficiency of use of energy that is stored and conserved in the thermodynamic battery unit in accordance with the invention.

[0007] Another positive attribute of the present invention is that the thermo-dynamic battery unit is modular unit comprised of, and connectable together a compressed air storage for storing energy in the form of compressed air, and Electricity Pressure Mutual Converter for converting the electricity to pressure and pressure to electricity by provided and coupled Expander-Compressor with Motor-Generator in single embodiment of apparatus.

[0008] Another positive attribute of the present invention is that by dividing and partitioning the compressed air storage tank into separate smaller modular self-contained

energy storing and producing units we can store and recover energy much more efficiently than existing compressed air energy storage systems.

[0009] Another positive attribute of the present invention is that the working pressure of compressor-expander as much as possible is smaller to gain higher efficiency, which is effortless to manufacture.

SUMMARY OF THE INVENTION

[0010] A plurality of thermodynamic battery units is connectable to store and generate electrical energy by converting electrical power in the form of compressed gas, and reversing the process by converting compressed gas into the electricity.

[0011] A system for storing and generating power from gas includes at least two (2) thermo-dynamic battery units connectable in series to one another for controllable compression and expansion of the gas to drive a compressor and generator. A method in accordance with the invention comprises providing at least two (2) thermo-dynamic battery units connectable in series with one another for controllable compression and expansion of the gas to drive a compressor and generator.

[0012] The present invention provides a unique battery system, which stores and produces, from compressed gas energy, clean usable electrical power for use in any application in any device that can employ battery power to operate. The invention is much lighter for the same energy output than existing units, can be charged in rather than hours, and operates chemical and explosion free. Environmentally safe to operate, and operates at or about 90% efficiency.

[0013] A system and method in accordance with the invention for storing, disseminating, and utilizing energy in the form of gas compression and expansion comprises a method for storing energy including the steps of providing power to compress gas in at least two stages with at least two pressure changes, to a receptacle where the gas is compressed and held for dissemination to provide power. The method provides for dissemination of stored energy when proceeding in reverse, i.e., when said compressed gas is expanded with at least two pressure changes and the output is coupled to at least one generator. A system in accordance with the invention operates in accordance with said method and employs apparatus to implement said method with at least two expanders-compressors coupleable to at least one motor-generator. When operated in the opposite manner, which is if electrical power supplied to motor-generator said system compressing gas and provides energy storage in the form of compressed gas.

BRIEF DESCRIPTION OF DRAWINGS

[0014] FIG. 1 is a schematic view of a thermo-dynamic battery unit in accordance with the invention.

[0015] FIG. 2 is a schematic view of an arrangement in accordance with the invention of a plurality of thermodynamic battery units.

**DETAILED DESCRIPTION OF THE
INVENTION**

[0016] As shown in FIG. 1, a thermo-dynamic battery unit in accordance with the invention comprises a Electricity

Pressure Mutual Converter **1** for converting electricity to compressed gas and compressed gas to electricity, a tank **2** for storing compressed gas, a Motor-Generator **7** connected with at least two Expander-Compressor sets **5, 9** in series with common shaft **6**, a heat exchanger chamber space **8** between Motor-Generator armature and rotor, four check valves **10** and a control unit **4**, including a flow control valve **3** and **11** for controlling release flow and direction of compressed gas from and to tank **2**. Tank **2**, control unit **4**, and generator **7** are of conventional type.

[0017] Electricity Pressure Mutual Converter **1** able to work in two mode; compression and expansion. In the compression mode, while the electricity applied to Motor-Generator **7**, the Motor-Generator **7** rotates the Expander-Compressor van set **5,9** toward one of two possible directions, and force the gas to compress. In the enclosed heat exchanger chamber **8** a space where the gas exchanges heat with Motor-Generator, which according under the laws of thermodynamic contributes to increase the gas pressure. The check valves **10** arranged such so the pressurized gas will be forced to flow to the direction of the tank **2** for storage. The control unit **4** controls the direction and flow rate of gas by flow control valves **3** and **11**.

[0018] In the expansion mode the gas released from tank **2** under control of unit **4** passing through first Expander-Compressor van set **5** will cause expand the gas from smaller space to larger space, which will force the common drive shaft **6** to turn towards the other direction of said two possible directions. As long as Motor-Generator rotor attached to the same common drive shaft **6** will cause Motor-Generator **7** to operate, which in turn generates electricity and some incidental heat. Generated heat expands the released gas causing the second set of fan blades Expander-Compressor van **9** to operate, which is transmitted back to Motor-Generator **7** with a common drive shaft **6** to operate Motor-Generator **7**. Check valves **10** arranged such so the expanding gas flows towards the vent.

[0019] The released gas is in thermal contact with heat exchanger chamber **108**, space between the Motor-Generator **7** armature and rotor, long enough to achieve expected results. At the same time, the released gas—which under the laws of thermodynamics cools as it expands upon release—cools Motor-Generator **7** and increases generator efficiency thereby. Generating of electricity is thus controlled by control unit **4** and flow control valve **3** and **11**.

[0020] As shown in FIG. 2, a thermo-dynamic battery system comprises a plurality of individual Electricity Pressure Mutual Converter **12**, in the case depicted herein numbering four. This number is provided for specificity; the invention in this embodiment may operate with as few as two individual units as well as with an unlimited number thereof.

[0021] Each individual unit **12** operates in the same manner as thermo-dynamic battery unit **1** described above. In the present embodiment, the respective units **12** are depicted as connected to one another within a tank **14**. Each unit **12** is held in place by conventional means and is sealed by O-rings **17**. The space between each Electricity Pressure Mutual Converter intended to store compressed gas.

[0022] Each unit **12** includes a flow control valve **18** controlled by a controller regulator **20**. In each unit **12** the

gas is compressed and released controllably and simultaneously at a predetermined different pressure levels to create equal pressure differentials between tanks. As depicted, the unit **12** at the left end of tank **14** is at the highest pressure, shown here as P_N and unit **12** at the right hand end of tank **14** is at the lowest pressure, shown herein as P_1 . The P_1 unit **12** is connectable to a vent **22** to ambient. Pressure may be 5000 psi or higher in particular applications. Pressure differential between the input and output of units **12** is as low as possible and equal each and every one, to increase the overall system efficiency.

[0023] As depicted in FIG. 2, volume of the P_N unit **12** is given as V_N . Similar considerations apply to intermediate units **12**, whose pressure and volume, respectively, are P_3 , V_3 and P_2 , V_2 . Pressure in units **12** diminishes from the highest pressure, to the lowest pressure P_1 with intermediate units **12** having diminishing pressure from left to right as shown in FIG. 2. For example, in the specific configuration depicted, P_3 is larger than P_2 , which in turn is larger than P_1 .

[0024] As further depicted in FIG. 2, each unit **12** contributes power when the system is operated as stated below. For ease of reference, said power—in this case, voltage—is symbolized by U_N through U_1 . Said individual contributions to the power may be employed in series, for increased voltage or in parallel for increased current.

[0025] A charging valve **26** controls charging of tank **14** with compressed gas for storage of energy therein. This may be employed for a fast or booster charge.

[0026] In the embodiment depicted in FIG. 2, a negative electrical terminal **23** is disposed at the high pressure end of tank **14** and a positive terminal **24** is disposed of the low pressure end of tank **14**. The phrase “high pressure end” and “low pressure end” means in this context the location in tank **14** where, respectively, the highest pressure unit **12** (the P_N unit) and the lowest pressure unit **12** (the P_1 unit **12**) are located.

[0027] In operation, controller regulator **20** is operable to regulate each and individual Electricity Pressure Mutual Converter to compress gas for storage and expand for electricity generation subject to load sensor **25** and pressure sensors **27** connected hereto. During the compression mode the electrical power applied to terminals **23** and **24** and the Electricity Pressure Mutual Converter under the influence of differential pressure simultaneously Electricity Pressure Mutual Converter will force to compress the gas and stored for power generation. Upon release of gas under the influence of differential pressure such that from each unit **12**, voltage is generated as described in connection with the system of FIG. 1. Load sensor **25** and pressure sensor **27** regulates operation of controller regulator **20** such that for a smaller load to diminish flow of gas and for higher loads to increase gas flow. Such devices are in common usage at present as, for example, in power generating facilities which seek to maximize efficiency by matching power generation to power demand.

[0028] As noted above, the individual power outputs of units **12** can be placed in parallel to provide a larger current or in series for increased voltage. In addition, each unit **12** may be arranged (not shown) outside of partitioned tank **14** connected with the pipes.

[0029] A method for storing and using energy and employing same for generating electric power includes the steps of:

(1) applying electrical power to Electricity Pressure Mutual Converter for controllably compressing gas (2) storing energy in the form of compressed gas; (3) controllably releasing said gas to operate an Electricity Pressure Mutual Converter. The gas may comprise air, and the gas may pass in thermal contact with a Motor-Generator for improved efficiency.

[0030] A method for storing energy and generating power comprises the steps of applying electrical power to Electricity Pressure Mutual Converter for controllably compressing gas, storing compressed gas for controllable release to drive an Electricity Pressure Mutual Converter and releasing the compressed gas in at least two pressure drops, thereby reducing energy loss from expansion of compressed gas. This method may be implemented by means of the apparatus depicted in FIG. 2 or similar devices. The method of the invention may be employed with a plurality of pressure drops, numbering two or more.

[0031] The foregoing-described system and method for storing, disseminating, and utilizing energy in the form of compressed gas, includes a method for storing energy in the form of gas compression by substantially reversible the foregoing-described method for generating power, using the same apparatus. Under the method, power is supplied to Electricity Pressure Mutual Converter 12 and as a result they function as motors causing the expanders therein to reverse such that air will be compressed through the above-described pressure changes for storage in tank 14.

[0032] Efficiency in the forward cycle as well as the reverse cycle is promoted by the multiple pressure change aspect of the invention.

[0033] In the foregoing manner, energy losses from expansion of compressed gases are minimized, and efficiency improved.

[0034] The within specification and drawings disclose particular embodiments of the invention, which is defined by the appended claims interpreted in light of the specification and drawings.

What is claimed:

1. A system for storing energy and generating electrical power comprising: at least one compressed gas storage device for controllably storing and releasing said gas; at least one generator for generating electricity and capable function in the same way as electric motor resulting from application of electrical power, herein it is called Motor-Generator; at least one gas expander to run electric generator resulting from receiving a flow of gas and capable function in the same way as gas compressor, herein it is called Expander-Compressor; said at least one Generator-Motor being connectable to said at least one Expander-Compressor with a common drive shaft such to compress gas into the said compressed gas storage device resulting from supply of electrical power and generate electricity resulting from receiving a flow of gas from said compressed gas storage device, herein it is called Electricity Pressure Mutual Converter; said at least one compressed gas storage device being connectable to said at least one Electricity Pressure Mutual Converter such that said compressed gas storage device supplies and receives gas flow to said at least one Electricity Pressure Mutual Converter thereby resulting in to store and generate electrical power in the form of gas compression and

expansion; said at least one Electricity Pressure Mutual Converter being operable independently substantially any external source of energy during generation of electrical energy.

2. The invention as set forth in claim 1 wherein said at least one Motor-Generator device being connectable with common drive shaft to said at least one Expander-Compressor device such that the expanding and compressing gas is passing between armature and rotor gap in direct contact with armature and rotor to obtain energy in the form of heat from said at least one Motor-Generator to expand the volume of said gas during expansion and to increase the pressure of said gas during compression.

3. The invention as set forth in claim 1, wherein said at least one Electricity Pressure Mutual Converter includes at least two Expander-Compressor members for driving said at least one Generator-Motor in response to impingement upon said at least two Expander-Compressor members of gas flow, a first Expander-Compressor member being arranged to exchange gas flow from said at least one compressed gas storage device and a second Expander-Compressor member being arranged to exchange gas flow from said at least one Generator-Motor.

4. The invention as set forth in claim 1, wherein said device for storing energy and generating electric power comprises; at least one flow control valve; at least one pressure sensor; at least four check valve and at least one controller, for controllable expansion and compression of said gas.

5. The invention as set forth in claim 1 including; at least one energy source intended for compressing gas for storage in said compressed gas storage device.

6. The invention as set forth in claim 1, wherein said power device for storing energy and generating electric power includes at least one common drive shaft for said Generator-Motor and said at least two Expander-Compressor members.

7. The invention as set forth in claim 1, wherein said gas comprises air.

8. A method for storing energy and for generating power comprising the steps of:

- (a) Supplying electrical power to Electricity Pressure Mutual Converter intended for compressing gas or providing compressed gas;
- (b) Storing said compressed gas for controllable release to drive at least one Electricity Pressure Mutual Converter to generate electrical power.

9. The method as set forth in claim 8 further including the step of releasing or compressing at least a portion of said gas thereby driving said at least one power generator Electricity Pressure Mutual Converter to provide power or to store electricity.

10. The method as set forth in claim 8 further including the step of providing means for charging compressing said gas.

11. The method as set forth in claim 8 wherein said gas is compressed air.

12. A system for storing energy and generating power comprising: At least two compressed gas storage devices comprising at least a first compressed gas storage device and at least a second compressed gas storage device, each of said gas storage devices having means for storing compressed gas and for controllably receiving and releasing said gas; at

least two Electricity Pressure Mutual Converter means capable of generating power resulting from receiving a flow of gas, and compressing gas into the compressed gas storage device resulting from supply of electrical power, said first compressed gas storage device having higher operating pressure than said second compressed gas storage device, said first compressed gas storage device and said second compressed gas storage device being connectable to one another by Electricity Pressure Mutual Converter and said second Electricity Pressure Mutual Converter being connectable to said second compressed gas storage device such that upon compression or release of gas from or to said first compressed gas storage device and from or to said second compressed gas storage device, gas flow proceeds such that the pressure drop across said first Electricity Pressure Mutual Converter and said second Electricity Pressure Mutual Converter is substantially equal for the duration of gas compression and expansion.

13. The invention as set forth in claim 12 wherein said Electricity Pressure Mutual Converter means comprises at least one Electricity Pressure Mutual Converter member connected to said first compressed gas storage device.

14. The invention as set forth in claim 12 wherein said Electricity Pressure Mutual Converter means comprises at least one Electricity Pressure Mutual Converter member disposed at least partially within said first compressed gas storage device.

15. The invention as set forth in claim 12 wherein said Electricity Pressure Mutual Converter means comprises at least one Electricity Pressure Mutual Converter member connected to said second compressed gas storage device.

16. The invention as set forth in claim 12 wherein said Electricity Pressure Mutual Converter means comprises at least one Electricity Pressure Mutual Converter member disposed at least partially within said second compressed gas storage device.

17. The invention as set forth in claim 12 further exchanging heat means to receive gas flow from said compressed gas storage device and to receive heat from said Electricity Pressure Mutual Converter means, wherein said heat expands the volume of said gas during expansion and increases pressure of gas during compression.

18. The invention as set forth in claim 12 wherein said Electricity Pressure Mutual Converter means includes at least two Expander-Compressor members for driving said Generator-Motor means in response to impingement upon said at least two Expander-Compressor members of gas flow, a first Expander-Compressor member being arranged to receive gas flow from said compressed gas storage device and a second Expander-Compressor member being arranged to receive gas flow from said Generator-Motor means.

19. The invention as set forth in claim 12 wherein said means for controllably releasing and compressing said gas from and to said compressed gas storage device comprises at least one controller member; at least four check valves; and at least one flow control valve for controllable release and compression of said gas.

20. The invention as set forth in claim 12 further including Electricity Pressure Mutual Converter means connectable to receive gas flow from said compressed gas storage device wherein said gas flows in direct contact with armature and rotor of Motor-Generator to exchange heat, which expands the volume of said released gas and increases the pressure of said compressed gas.

21. The invention as set forth in claim 20 wherein said Electricity Pressure Mutual Converter means includes at least two Expander-Compressor members for driving said Motor-Generator means in response to impingement upon said at least two Expander-Compressor members of gas flow, a first Expander-Compressor member being arranged to receive gas flow from said compressed gas storage device and a second Expander-Compressor member being arranged to receive gas flow from said Motor-Generator means, wherein said Motor-Generator drives said at least two Expander-Compressors in response to electrical power supply to compress gas, a first Expander-Compressor member being arranged to receive gas flow from Motor-Generator and second Expander-Compressor member being arranged to receive gas flow from said compressed gas storage device.

22. The invention as set forth in claim 12 wherein said means for controllably releasing and receiving said gas from said compressed gas storage device comprises at least four check valves; at least one pressure sensor; at least one controller member and at least one flow control valve for controllable release and receive of said gas.

23. The invention as set forth in claim 18, wherein said first compressed gas storage device includes at least one common drive shaft for said Generator-Motor means and said at least two Expander-Compressor members.

24. The invention as set forth in claim 21, wherein said second compressed gas storage device includes at least one common drive shaft for said Generator-Motor means and said at least two Expander-Compressor members.

25. A system for storing and generating power comprising means compressing gas in response to supply of electrical power for storing energy in the form of compressed gas and connectable to means for generating power in response to flow of gas, said means for storing energy in the form of compressed gas means compressing gas at least two different pressure stages such that pressure differentials between stages for the duration of compression is substantially equal, including means for releasing compressed gas in at least two different pressure stages such that the pressure differentials between stages for the duration of expansion of said compressed gas is substantially equal, thereby reducing energy loss during compression and from expansion of compressed gas.

26. The invention as set forth in claim 25 wherein said means for storing energy in the form of compressed gas comprises at least a first compressed gas storage member and a second compressed gas storage member, said first compressed gas storage member being connectable to said second compressed gas storage member, said first compressed gas storage member being at a different pressure from said second compressed gas storage member.

27. The invention as set forth in claim 25 wherein said means for storing energy in the form of compressed gas comprises a plurality of compressed gas storage members at differing pressures.

28. A method for storing energy and generating power comprising the steps of:

- (a) Compressing gas controllably at least two equal pressure differentials in at least two different pressure levels whereby energy loss due to gas compression is reduced;
- (b) Storing compressed gas for controllable release to drive power generator means;

(c) Releasing said compressed gas from at least two different pressure levels in at least two equal pressure differentials, whereby energy loss due to expansion of compressed gas is reduced.

29. The invention as set forth in claim 28 wherein there is a plurality of pressure differentials.

30. The invention as set forth in claim 28 wherein thermal energy released upon generation and storage of power is at least partially returned to said expanding and compressing gas to reduce energy loss.

31. The invention as set forth in claim 28 wherein said gas comprises air.

32. A system for storing power comprising means for storing energy in the form of compressed gas and connectable to means for providing power, and further including means for compressing gas through application of power from said power providing means, including means for compressing gas in at least two different pressure levels such that the pressure differentials for the duration of compression are substantially equal, thereby reducing energy loss from compression of said gas, said system being operable in substantial thermal isolation from the surrounding.

33. The invention as set forth in claim 32 wherein said means for compressing gas comprises at least a first Electricity Pressure Mutual Converter member and a second Electricity Pressure Mutual Converter member, said first Electricity Pressure Mutual Converter member and said second Electricity Pressure Mutual Converter member being connectable to one another and operating at similar differential gas pressure.

34. The invention as set forth in claim 32, wherein at least one of said Electricity Pressure Mutual Converter members is capable to function in the same way as electricity generator and mutually capable to function in the same way as a gas compressor.

35. The invention as set forth in claim 32 wherein said means for storing energy in the form of compressed gas comprises a plurality of compressed gas storage members at differing pressures.

36. The invention as set forth in claim 32 wherein said Electricity Pressure Mutual Converter means includes at least two Expander-Compressor members operable to drive said gas compression, a first Expander-Compressor member being arranged to receive gas flow from said means for storing energy in the form of compressed gas, said Motor-Generator member and said second Expander-Compressor member being arranged to receive gas flow from the first Expander-Compressor to exchange heat means included in said Electricity Pressure Mutual Converter means.

37. The invention as set forth in claim 28 exchanging heat means contributes to controlling temperature of said Motor-Generator members.

38. The invention as set forth in claim 33 further including at least two compressed gas storage devices, a first of said at least two compressed gas storage devices including said first Electricity Pressure Mutual Converter member and a second of said at least two compressed gas storage devices including said second Electricity Pressure Mutual Converter member

39. The invention as set forth in claim 38, further including means for controlling gas flow and direction from and to said first compressed gas storage device and further includ-

ing at least one flow control valve for controlling said gas flow and direction from and to said first compressed gas storage device.

40. The invention as set forth in claim 38 further including means for controlling gas flow and direction from and to said second gas storage device, other than said means for controlling gas flow and direction from and to said first compressed gas storage device and further including at least one flow control valve for controlling gas flow and direction from and to said second compressed gas storage device other than said at least one flow control valve for controlling gas flow and direction from and to said first compressed gas storage device.

41. The invention as set forth in claim 32 wherein said gas substantially comprises air.

42. The invention as set forth in claim 32 wherein said pressure of said compressed stored gas is substantially equal to or greater than 5000 psi.

43. The invention as set forth in claim 32 wherein said pressure of said compressed stored gas is substantially equal or less than 5000 psi.

44. The invention as set forth in claim 32 wherein said pressure differentials are substantially equal to one another.

45. A method for storing power in the form of compressed gas comprising the steps of:

a. providing power means;

b. providing means for compressing gas through application of power from said power means, whereby said gas is compressed in at least two different pressure levels such that the pressure differentials upon compression of said gas is substantially equal, thereby reducing energy loss.

46. The method as set forth in claim 45 wherein said means for compressing gas is operable in reverse to function as a generator.

47. The method as set forth in claim 45 wherein said pressure differentials are substantially equal to one another.

48. A system for storing energy and generating electrical power comprising:

a plurality of compressed gas storage devices for storing compressed gas at different pressure levels to create substantially equal pressure differentials between compressed gas storage devices and for controllably compressing and releasing said gas;

a tank member substantially containing said plurality of compressed gas storage devices;

means for controlling charging with compressed gas of said plurality of compressed gas storage devices;

at least one Electricity Pressure Mutual Converter capable of generating electricity resulting from receiving a flow of gas and capable of compressing gas resulting from supply of electrical power;

said plurality of compressed gas storage devices being connectable to said at least one Electricity Pressure Mutual Converter such that said compressed gas storage devices supply and receive gas flow from gas released and compressed there from to said at least one Electricity Pressure Mutual Converter thereby resulting to store and generate electrical power;

control means for controlling release of compressed gas and compressing gas;

heat exchange means exchanging heat between Motor-Generator and gas; and

load sensor means for sensing load in connection with release of compressed gas, said control means for controlling release of compressed gas being connected with said load sensor means such that for smaller loads gas flow is diminished and for higher loads gas flow is increased.

49. A system for storing energy from compressing gas comprising means for compressing gas to a selected pressure in at least two steps thereby reducing energy loss from said

gas compression, said means for compressing gas being connectable to at least one energy storage device for storing compressed gas.

50. The invention as set forth in claim 49 wherein pressure differentials in said at least two steps are substantially equal to one another.

51. The invention as set forth in claim 48 wherein said Electricity Pressure Mutual Converter had one gas input and one gas output to reduce energy losses.

52. The invention as set forth in claim 48, wherein said Expander-Compressor member is a sliding vane turbine.

53. The invention as set forth in claim 48, wherein said pressure differential is substantially equal to, less than or greater than 10 psi.

* * * * *