



(19) **United States**

(12) **Patent Application Publication**  
**Magiawala et al.**

(10) **Pub. No.: US 2007/0267220 A1**

(43) **Pub. Date: Nov. 22, 2007**

(54) **METHANE EXTRACTION METHOD AND APPARATUS USING HIGH-ENERGY DIODE LASERS OR DIODE-PUMPED SOLID STATE LASERS**

**Related U.S. Application Data**

(60) Provisional application No. 60/800,408, filed on May 16, 2006.

**Publication Classification**

(51) **Int. Cl.**  
*E21B 7/14* (2006.01)

(52) **U.S. Cl.** ..... 175/12

(57) **ABSTRACT**

A method and apparatus for extracting methane gas from methane hydrate. The method includes heating the methane hydrate with a laser apparatus. The laser apparatus includes a diode laser or a solid state laser that is pumped with a diode laser. The laser is guided to a working end of a tool with a fiber optic bundle. The tool is guided to heat the methane hydrate with the laser, which emanates from a beam expander at the working end of the tool. The tool can be modified for removing obstructions of methane hydrate in pipelines. Also, the tool can be modified for extracting methane from mined methane hydrate, which is in a container. The characteristics of diode lasers or diode-pumped solid state lasers such as efficiency, size, nature of operation, environmental impact and durability, make methane gas extraction from methane hydrate economically feasible.


(75) Inventors: **Kiran Ramanlal Magiawala**, Hawthorne, CA (US); **Jeffrey Lee Sollee**, El Segundo, CA (US); **Michael Gordon Wickham**, Rancho Palos Verdes, CA (US); **Steven Wayne Fornaca**, Torrance, CA (US)

Correspondence Address:  
**POSZ LAW GROUP, PLC**  
12040 SOUTH LAKES DRIVE, SUITE 101  
RESTON, VA 20191

(73) Assignee: **Northrop Grumman Corporation**, Los Angeles, CA (US)

(21) Appl. No.: **11/493,897**

(22) Filed: **Jul. 27, 2006**






FIG. 1






FIG. 2





**FIG. 4**



**FIG. 5**




FIG. 6




FIG. 7






FIG. 8




FIG. 9

**METHANE EXTRACTION METHOD AND  
APPARATUS USING HIGH-ENERGY DIODE  
LASERS OR DIODE-PUMPED SOLID STATE  
LASERS**

CROSS REFERENCE TO RELATED  
APPLICATIONS

[0001] This application claims the benefit of the filing date of U.S. provisional application No. 60/800,408, which was filed on May 16, 2006 and which is incorporated herein by reference.

FIELD OF THE INVENTION

[0002] This invention relates in general to a method and apparatus for methane extraction, and more particularly, to a method and apparatus for extracting methane from methane hydrate using high-energy diode lasers or solid state lasers that are pumped with diode lasers.

BACKGROUND OF THE INVENTION

[0003] At various locations around the world, there are large supplies of methane gas in the solid, frozen form of methane hydrate. Beneath the ocean bed, at various depths, methane hydrate deposits are estimated at many trillions of cubic meters. Currently, there is no cost-effective method of extracting methane from methane hydrate. However, as the cost of energy increases, extraction of methane from methane hydrate may become cost-effective. However, there is a need for an efficient method of extracting the methane from the methane hydrate.

[0004] Several proposals for extraction have been put forth. These include thermal stimulation, depressurization, and the use of chemicals, or inhibitors. However, currently proposed methods have various drawbacks that reduce their cost-effectiveness. Currently, none of these methods is considered to be commercially viable.

[0005] In particular, it has been proposed to use a chemically pumped oxygen-iodine energy transfer laser (COIL) to thermally stimulate the methane hydrate. However, such a method would require large storage structures for the chemicals that fuel the laser. Also, exhaust from the laser would create a significant environmental hazard. Therefore, large scale scrubbing equipment would be required. Further, current COILs operate continuously for only a few minutes, which is insufficient for large-scale methane extraction.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] The accompanying figures where like reference numerals refer to identical or functionally similar elements throughout the separate views and which together with the detailed description below are incorporated in and form part of the specification, serve to further illustrate various embodiments and to explain various principles and advantages all in accordance with the present invention.

[0007] FIG. 1 is a schematic block diagram of a vertical methane gas extraction operation using a high energy semiconductor laser or a solid state laser that is pumped with a semiconductor laser according to the present invention;

[0008] FIG. 2 is an enlarged schematic block diagram of a self-cleaning beam expander of the apparatus of FIG. 1;

[0009] FIG. 3 is a schematic block diagram of a vertical methane gas extraction operation using a high energy semi-

conductor laser or a solid state laser that is pumped with a semiconductor laser according to a further embodiment of the present invention;

[0010] FIG. 3A is a cross sectional schematic view taken along the plane indicated by line 3A-3A in FIG. 3;

[0011] FIG. 4 is a schematic diagram of a horizontal drilling operation using a semiconductor laser tool for extracting methane gas from a methane hydrate deposit;

[0012] FIG. 5 is a schematic block diagram showing removal of a methane hydrate obstruction in a gas pipeline with a high energy laser tool that employs a high energy semiconductor laser or a solid state laser that is pumped with a semiconductor laser;

[0013] FIG. 6 is a schematic block diagram showing a laser drill forming a bore in a methane hydrate formation;

[0014] FIG. 7 is a schematic block diagram showing a laser tool heating methane hydrate stored in a container.

[0015] FIG. 8 is a schematic block diagram showing a fiber-coupled diode laser; and

[0016] FIG. 9 is a schematic block diagram showing a fiber laser that is pumped by fiber-coupled diode lasers.

SUMMARY OF THE INVENTION

[0017] Basically, the present disclosure concerns a method and apparatus for extracting methane gas from methane hydrate. The method includes heating the methane hydrate with a laser beam of a high energy diode laser or a solid state laser that is pumped with a diode laser to release methane gas from the methane hydrate. The end of the tool is placed in the methane hydrate, and the laser is guided with an optic fiber to the end of the tool.

[0018] Preferably, the laser beam is produced with a diode laser, which is more efficient.

[0019] The laser can be operated in a pulsed mode or a continuous mode.

[0020] In a further embodiment, the invention includes a method of removing a methane hydrate obstruction in a gas pipeline by heating the methane hydrate with a laser beam of a diode laser or a laser that is pumped with a diode laser to change the phase of the obstruction.

[0021] In a further embodiment, the invention includes a method of boring through a methane hydrate formation to access a natural gas pocket that is located beneath the methane hydrate formation. The boring method includes forming a bore hole through the methane hydrate with a laser beam of a diode laser or a solid state laser that is pumped with a diode laser and placing a conventional drill in the bore hole to drill beneath the methane hydrate formation to form a second bore, which leads into the gas pocket.

[0022] The invention includes an apparatus for extracting methane from methane hydrate. The apparatus includes an extraction tool; a diode laser or a solid state laser that is pumped with a diode laser; and an optic fiber for leading a laser beam generated by the laser to a working end of the extraction tool.

[0023] The apparatus may further include a conduit for conducting extracted methane from a methane formation toward a proximal end of the extraction tool.

[0024] The apparatus may further include a beam expander for expanding the laser beam before the laser beam strikes the methane hydrate.

[0025] The apparatus may further include apparatus for forming an air curtain adjacent to a lens of the beam expander so that the lens is self-cleaning.



[0026] The apparatus may further include an air passage for delivering air to the air curtain.

[0027] The extraction tool may include a water cooling passage for cooling the optic fiber.

[0028] The extraction tool may be supported by a platform, which carries the high energy diode laser or diode-pumped solid state laser, its power source and thermal management system.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0029] FIG. 1 shows a methane extraction apparatus performing a vertical extraction operation in a body of water 101. A platform 102 is located at the water level of the body of water 101, such as the ocean. Beneath a crust 107, which forms the floor of the body of water 101 is a layer, or strata, of methane hydrate 108. An electric power plant 103 is located on the platform 102. A high-power laser 104 (diode laser or solid state laser that is pumped by a diode laser) is located on the platform as shown. Although FIG. 1 shows an extraction operation on water, the extraction can take place on dry land or ice with a drilling rig (not illustrated) that includes equipment similar to that located on the platform 102.

[0030] Extending from the platform 102 to the methane hydrate strata is a laser extractor tool 113, which includes a laser light-carrying optic fiber bundle 109, a laser head assembly 114 and a conduit 105, for transporting gas mixture 112 (methane and steam) to the platform 102. The extractor tool 113 is formed by concentric pipes, as shown. The conduit 105 is formed between the inner surface of an outer pipe and the outer surface of an inner pipe. The gas mixture 112 is delivered to a gas separator apparatus 106, which separates methane from steam and stores the separated methane in gas, liquid or solid form, as desired. Although not illustrated in FIG. 1, apparatus for cooling the fiber bundle is incorporated in the laser tool 113.

[0031] The laser head 114 can include a self-cleaning beam expander 110 from which an expanded laser beam 111 is projected. The laser beam 111 interacts with the solid methane hydrate 108 and causes a phase change. That is, the laser beam 111 heats the methane hydrate 108 and converts the methane hydrate into steam and methane gas. The beam expander 110 increases the diameter of the laser beam, which increases the area of the methane hydrate 108 to be heated, which facilitates large scale production of methane gas.

[0032] In the example of FIG. 1, the methane hydrate is located below a crust 107 of the earth. Prior to the extraction process illustrated in FIG. 1, a bore is drilled through the crust 107 with a conventional drill (not illustrated). The well can then be capped until the extractor tool 113 is inserted. The extractor tool 113 may be equipped to break a cap on a capped bore; however, such equipment is not illustrated.

[0033] FIG. 2 shows the self-cleaning laser beam expander 110 in more detail. The fiber bundle 109 is coupled to the beam expander 110 as shown. At a light exit lens of the beam expander 110 is an air curtain 204. Although it is not required to employ a self-cleaning beam expander, it is considered advantageous to maintain high production rates by reducing equipment maintenance and idle time.

[0034] Conventional equipment such as valves and pumps to control the pressure and flow inside the conduit 105 are

not illustrated for simplicity. However, such equipment is well understood to those in the field of gas drilling and will not be described here.

[0035] To minimize the loss of laser energy, it is preferred to minimize the separation between the beam expander 110 and the solid methane hydrate. That is, it is desired to minimize the size of the gas pocket surrounding the end of the extractor tool 113. Horizontal drilling can facilitate positioning the end of the drill to minimize the gas pocket and the separation distance.

[0036] The laser 104 is a high-power semiconductor laser, or diode laser, which is very efficient. In this application, "high power" means approximately one hundred kilowatts or more. Alternatively, the laser 104 can be a solid state laser that is pumped with a diode laser. Such lasers are particularly suitable for methane extraction from methane hydrate because of their extended on-time (time of continuous operation), durability, efficiency, size, power requirements, and maintenance and supply requirements. For example, the life-expectancy of diode lasers or solid state lasers that are pumped with diode lasers is approximately a few years, which is favorable for methane gas extraction, and diode lasers or solid state lasers that are pumped with diode lasers require only electricity to operate, which is favorable for methane gas extraction. Further, diode lasers or solid state lasers that are pumped with diode lasers do not produce waste materials at the work site. Therefore, diode lasers or solid state lasers that are pumped with diode lasers have little environmental impact on drilling sites.

[0037] The characteristics of diode lasers or solid state lasers that are pumped with diode lasers make them particularly suitable for extracting methane from methane hydrate. Prior to this disclosure, methane extraction from methane hydrate was generally considered to be uneconomical. However, the present method and apparatus is considered likely to render methane extraction from methane hydrate a commercially viable operation.

[0038] It is preferred that the laser beam of the methane extraction apparatus is a diode laser. Diode lasers currently have an efficiency of approximately 55-80%. Such relatively high efficiencies are required for economic methane gas production. The efficiency discussed herein is the so-called wall-plug efficiency, which is the energy in the output beam divided by the energy input to the laser.

[0039] As used in this application, the phrase "solid state laser pumped with a diode laser" refers to a laser that uses a gain medium that is a solid, rather than a liquid or a gas, and is pumped with laser diodes. Currently, such lasers have efficiencies of approximately 10-20%.

[0040] A fiber laser is one type of solid state laser that is pumped with diode lasers. In a fiber laser, the optical fiber core serves as the medium. Currently, fiber lasers have an efficiency of approximately 30-35%.

[0041] The term "solid state laser" includes diode lasers, fiber lasers, and rod or slab lasers.

[0042] Diode lasers are generally considered separately from diode-pumped lasers. Thus, in this application, the terms "diode laser" and "diode-pumped laser" refer to separate types of lasers. That is, in this application, the term "diode laser" excludes diode-pumped lasers.

[0043] Most preferably, the laser 104 is a diode laser, which more efficient than lasers that are pumped by diode lasers. Assuming an average overall efficiency of an electricity generator to be approximately 40%, the ratio of



energy in extracted methane to energy input is expected to be approximately 3 to 5 for a diode laser. Co-generating power plants, which generate both power and heat, have higher overall efficiencies (50-70%) and would improve the energy ratio.

[0044] Diode lasers or diode-pumped solid state lasers require no supplies of chemicals or fuel other than electricity, which can be produced at the drilling site. The electricity can be generated from a fraction of the methane gas produced by the well or from another energy source. In contrast, for example, a COIL requires chemical supply tanks, which greatly increase the size and cost of the platform and associated equipment. A diode laser or a diode-pumped solid state laser requires only electricity and is thus more compact and less costly. Thus, a drilling rig that uses a diode laser or a diode-pumped solid state laser is more cost effective and can tip the balance of an operation that would otherwise be economically unsound toward commercial viability.

[0045] Commercially viable gas production would require a laser that operates continually for relatively long periods of time. COILs, for example, can operate for only short periods of a few minutes, which is insufficient for economic gas production. A diode laser or a diode-pumped solid state laser can operate for sustained periods that render methane extraction by the method disclosed above economically sound.

[0046] It is contemplated that the laser 104 will be operated in either of a pulsed mode and a continuous mode. The pulsed mode may be advantageous for breaking ice, which is the naturally occurring state of methane hydrate.

[0047] The beam parameter product (BPP) of a laser beam is defined as the product of beam radius (measured at the beam waist) and the beam divergence half-angle (measured in the far field). The usual units are mm mrad (millimeters times milliradians). The BPP is often used to specify the beam quality of a laser beam: the higher the beam parameter product, the lower the beam quality. Although there is equipment available for improving the beam quality of laser beams, the beam quality is not an important consideration in heating methane hydrate. Thus, high beam quality (low BPP) is not required, which reduces the costs.

[0048] FIGS. 3 and 3A show a vertical extraction tool 302 including an air conduit 309 and a water cooling passage 308. In the embodiment of FIG. 3, an extraction is shown in a body of water 301. The extraction tool 302 includes a conduit 306 for carrying extracted methane and steam toward a platform, which is not illustrated in FIG. 3 but is like the platform shown in FIG. 1. Beneath a crust 305 is a layer of methane hydrate 304. An expanded laser beam 303 heats the methane hydrate 304 to release steam and methane gas.

[0049] As shown in FIG. 3A, optical fibers 320 are located within a cooling passage 308 of the extraction tool 302. Cooling water is pumped into the cooling passage 308 through an input passage 307. The cooling water is discharged through an output passage 310. The locations of the input passage 307 and output passage 310 are arbitrarily selected and are not necessarily as shown.

[0050] The apparatus of FIG. 3 includes a beam expander 203 as shown in FIG. 2. Located within the cooling passage 308 is the air conduit 309 for supplying air to the self-cleaning expander 203. As shown in FIG. 2, the air, which is under pressure, is used to form an air curtain 204 for cleaning an outer surface or lens of the beam expander 203.

[0051] FIG. 4 shows a horizontal drilling operation that on a body of water 401. For simplicity, the platform and associated equipment is not illustrated. A horizontal extraction tool 402 extends from the platform and through an opening in the crust of the earth 405. The distal end of the horizontal extraction tool 402 is located in a layer of methane hydrate 404. An expanded laser beam 403 converts the methane hydrate 404 into steam and methane gas as in the method illustrated in FIG. 1.

[0052] A mixture of steam and methane hydrate is conducted through a conduit in the horizontal extraction tool 402 to a separator, as in the method of FIG. 1. The horizontal drilling method is advantageous in that the tool 402 can be moved along the length of the layer of methane hydrate 404 by extending the tool 402 in the horizontal direction to increase production. Thus, horizontal movement extends the reach of the tool 402 within a horizontal layer of methane hydrate 404 to increase the efficiency of gas production.

[0053] In another embodiment, as shown in FIG. 5, a laser tool 502 can be used to remove a methane hydrate blockage, or formation, 504 in a natural gas pipeline or a methane gas and steam carrying pipeline 501. In cold climates, methane hydrate formations 504 can cause obstructions in such pipelines. The laser tool 502 includes a beam expander 203 like that shown in FIG. 2. A laser beam is directed to the beam expander through optic fibers (not illustrated in FIG. 2). Through an opening in the pipeline 501 (not illustrated) the tool 502 is guided to an obstruction of methane hydrate. The expanded laser beam 503 is then used to heat the methane hydrate 504, which converts the methane hydrate to steam and methane gas thus removing the obstruction. As in the first embodiment, the laser used in this embodiment is a diode laser or a solid state laser that is pumped by a diode laser.

[0054] As shown in FIG. 6, in another embodiment, a laser head drill 602 can be used to form a bore in a layer of methane hydrate 604 so that a conventional well drill can reach a pocket of natural gas 610 that is located below the methane hydrate layer 604. The laser head drill 602 incorporates a laser light-carrying fiber bundle, and a laser head assembly that includes a self-cleaning beam expander, like that shown in FIG. 2. The laser head drill 602 includes a conduit for carrying methane gas and steam away from a bore 606. As in the first embodiment, the laser beam 603 heats the methane hydrate 604 and converts the solid methane hydrate 604 to methane gas and steam, which is carried away through the conduit in the laser head drill 602. As in the first embodiment, the laser used in this embodiment is a diode laser or a solid state laser that is pumped by a diode laser.

[0055] Initially, a conventional drill is used to form a bore through a first crust layer 605. Then, the laser head drill 602 is deployed in the bore formed by the conventional drill to form the bore 606 through the methane hydrate layer 604. Then, a conventional drill is used again to bore through a second crust layer 607 to reach the pocket of natural gas 610.

[0056] In a further embodiment, as shown in FIG. 7, a laser tool 702 can be used to extract methane gas from methane hydrate 704 that has been mined and is located in a container 701. The laser tool 702 is preferably movable horizontally and vertically to optimize the reach of the tool 702. In this embodiment, the expanded laser beams 703 heat the methane hydrate 704 to release methane gas 705 from an opening in the container 701, as shown. As in the first



embodiment, the laser used is a diode laser or a solid state laser that is pumped with a diode laser. Also, as in the first embodiment, the laser tool 702 includes a bundle of optic fibers for carrying the laser beam from the laser to a beam expander at the distal end of the tool 702.

[0057] Water 706 will collect in the container 701 as a result of the heat from the laser beams 703. Thus, in this embodiment, a separator may not be required to separate steam from the methane gas 705. Since methane gas is lighter than steam, it will collect at the top of the container 701. Also, since methane gas exits the container through the opening in the container, it is not necessary to form a conduit in the laser tool 702 for conducting methane gas.

[0058] FIG. 8 shows a diode laser, which is the preferred type of laser for the laser 104 or the source laser of any of the illustrated embodiments. FIG. 8 illustrates a known fiber-coupled diode laser module 812. The electrical power plant 103 is coupled to the laser module 812 by a cable 810. Although FIG. 8 shows only two laser diode bars 816 any number of laser diode bars 816 may be arranged in the laser module 812 depending on the circumstances and output needs. In the illustrated embodiment, one cooling channel 814, which carries coolant, is associated with each laser diode bar 816. However, any number of cooling channels may be arranged in various configurations as long as heat is transferred from the diode laser bars.

[0059] As shown in FIG. 8, a pair of lenses 818 direct laser light to coupling and conditioning optics 820. For example, the coupling and conditioning optics can include a containing lens, half-wave plates, beam compression prisms, a polarization beam combiner, and spatial filters. A fiber port coupler 822 couples the coupling and conditioning optics 820 to a fiber 824. Laser light 826 emanates from the end of the fiber 824. Depending on the capacity, a bundle of fibers 824 may be employed.

[0060] FIG. 9 shows an alternative known fiber laser that may be used as the laser 104 in FIG. 1 or as the source laser in any of the illustrated embodiments. In FIG. 9, a master oscillator laser 910, which may be any of several types of known lasers, is coupled to an optical fiber 912. A fiber-coupled diode laser pump 914 is coupled to a light coupler 916, as illustrated. Within the laser pump 914 is an array of diode laser modules, such as that illustrated in FIG. 8, each of which is coupled to one of the illustrated optical fibers extending between the laser pump 914 and the light coupler 916.

[0061] Downstream from the light coupler 916 is an active fiber 918 that is being pumped by the fiber-coupled diode laser modules. Further downstream from the active fiber 918 are beam shaping optics 924. Laser light 926 emanates from the beam shaping optics 924 or a fiber coupled to the beam shaping optics 924.

[0062] The apparatuses and methods discussed above and the inventive principles thereof are intended to and will alleviate problems with conventional methane extraction methods and apparatuses. It is expected that one of ordinary skill given the above described principles, concepts and examples will be able to implement other alternative procedures and constructions that offer the same benefits. It is anticipated that the claims below cover many such other examples.

1. A method of extracting methane gas from methane hydrate comprising heating the methane hydrate with a laser

beam of a diode laser or a solid state laser that is pumped with a diode laser to release methane gas from the methane hydrate.

2. The method of claim 1 including;
  - guiding the laser beam with an optic fiber to and end of a tool; and
  - placing the end of the tool in the methane hydrate.
3. The method of claim 1 including expanding the laser beam with a beam expander at the end of the tool.
4. The method of claim 1, wherein the laser is a diode laser.
5. The method of claim 1 including operating the laser in a pulsed mode.
6. The method of claim 1 including operating the laser in a continuous mode.
7. A method of removing a methane hydrate obstruction in a gas pipeline comprising heating the methane hydrate with a laser beam of a diode laser or a solid state laser that is pumped with a diode laser to change the phase of the obstruction.
8. The method of claim 7 including;
  - providing a tool for supporting an optic fiber; and
  - directing the laser beam with an optic fiber toward a working end of the tool; and
  - guiding the tool to direct the laser beam toward the obstruction.
9. A method of boring through a methane hydrate formation to access a natural gas pocket that is located beneath the methane hydrate formation comprising;
  - forming a bore hole through the methane hydrate with a laser beam of a diode laser or a laser that is pumped with a diode laser; and
  - placing a drill in the bore hole to drill beneath the methane hydrate formation to access the natural gas pocket.
10. An apparatus for extracting methane from methane hydrate comprising;
  - an extraction tool;
  - a diode laser or a laser that is pumped with a diode laser; and
  - an optic fiber for leading a laser beam generated by the laser to a working end of the extraction tool.
11. The apparatus of claim 10 further comprising a conduit for conducting extracted methane from a methane formation toward a proximal end of the extraction tool.
12. The apparatus of claim 10 further comprising a beam expander for expanding the laser beam before the laser beam strikes the methane hydrate.
13. The apparatus of claim 12, wherein the beam expander includes apparatus for forming an air curtain adjacent to a lens of the beam expander so that the lens is self-cleaning.
14. The apparatus of claim 13, wherein the extraction tool includes an air passage for delivering air to the apparatus for forming an air curtain.
15. The apparatus of claim 10, wherein the laser is a diode laser.
16. The apparatus of claim 10, wherein the extraction tool includes a water cooling passage for cooling the optic fiber.
17. The apparatus of claim 10, wherein the extraction tool is supported by a platform, which carries the laser.