


US 20090000762A1

(19) **United States**(12) **Patent Application Publication**
Wilson et al.(10) **Pub. No.: US 2009/0000762 A1**(43) **Pub. Date: Jan. 1, 2009**(54) **BRUSH-SEAL AND MATRIX FOR
REGENERATIVE HEAT EXCHANGER, AND
METHOD OF ADJUSTING SAME****Publication Classification**(51) **Int. Cl.**
F23L 15/02 (2006.01)(52) **U.S. Cl.** **165/9**(57) **ABSTRACT**

Disclosed is a regenerative heat exchanger including a brush-seal configuration to prevent mixing of fluid flows. The regenerative heat exchanger includes a regenerator, and at least two conduits, each conduit having a matrix end abutting a face of the regenerator matrix. The at least two conduits carrying at least two fluid flows, the fluid flows which pass through the regenerator matrix. The regenerative heat exchanger includes a plurality of brush-seals, each brush-seal located at a matrix end of each conduit without contacting the matrix, thereby sealing around a periphery of each conduit to prevent mixing of fluid flows. Also disclosed is a method for establishing a minimal gap between a regenerator matrix of a regenerative heat exchanger and a plurality of brush-seals.

(75) **Inventors:** **David Gordon Wilson**, Winchester,
MA (US); **Jon M. Ballou**, Beverly,
MA (US); **Kelly Ward**, Peabody,
MA (US)

Correspondence Address:
CANTOR COLBURN, LLP
20 Church Street, 22nd Floor
Hartford, CT 06103 (US)

(73) **Assignee:** **WILSON TURBOPOWER, INC.**,
Woburn, MA (US)(21) **Appl. No.: 11/770,904**(22) **Filed: Jun. 29, 2007**




FIG. 1




FIG. 2




FIG. 3

BRUSH-SEAL AND MATRIX FOR REGENERATIVE HEAT EXCHANGER, AND METHOD OF ADJUSTING SAME

BACKGROUND OF THE INVENTION

[0001] This invention generally relates to heat exchangers. In particular, the present invention relates to seals for rotary regenerative heat exchangers.

[0002] A regenerative heat exchanger (regenerator) uses a heat transfer matrix which is rotated through a hot and a cold stream consecutively to transfer heat from the former to the latter. The device can also be used to transfer mass between two fluids differing in concentration in a targeted constituent and the exchange (be it mass and/or heat) can involve any number of flows greater than one.

[0003] Each of the hot and cold flows is typically carried to and from the matrix by a conduit. The flows enter and exit the matrix through a face of the matrix, and a configuration of seals is located between the conduits and the rotating matrix face to prevent leakage of the flows from the conduits into the environment or from one flow into another. Two types of seals are generally used, non-contact seals or contact seals. With non-contact seals (which do not contact the matrix face), it is a major challenge to properly adjust a gap between the matrix face and the non-contact seal minimizing leakage to maximize efficiency of the heat exchanger. Contact seals (which do contact the matrix face) ensure lower leakage which improves efficiency of the regenerator as compared to non-contact seals. Use of contact seals, however, causes increased seal wear and also reduces efficiency of the regenerator due to the increased friction between the contact seal and the matrix that must be overcome in the rotation of the matrix. Additionally, rubbing of the contact seals on the regenerator matrix can over time produce solid material (either from the matrix or the seals) which will contaminate the flow and might lead to clogging in a porous matrix.

BRIEF DESCRIPTION OF THE INVENTION

[0004] The present invention solves the aforementioned problems by providing a regenerative heat exchanger including a brush-seal configuration to prevent mixing of fluid flows. The regenerative heat exchanger includes a regenerator matrix, and at least two conduits, each conduit having a matrix end abutting a face of the regenerator matrix. At least two conduits carry at least two fluid flows which pass through the regenerator matrix. The regenerative heat exchanger includes a plurality of brush-seals. Each brush-seal is located at a matrix end of each conduit without contacting the matrix, thereby sealing around a periphery of each conduit to prevent mixing of fluid flows.

[0005] A method for establishing a minimal gap between a regenerator matrix of a regenerative heat exchanger and a plurality of brush-seals is disclosed. The method includes installing the plurality of brush-seals such that a bristle end of each brush-seal contacts a face of the regenerator matrix. The regenerator matrix is rotated at a desired speed about an axis substantially perpendicular to the face of the regenerator matrix. During rotation, friction between the bristle end and the face causes material to be removed from the bristle end. The rotation is stopped when a power required to rotate the regenerator matrix at the desired speed reaches a predetermined level. This stops the removal of material from the

bristle end and establishes a minimal gap between the bristle end and the face of the regenerator matrix.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] The above, as well as other advantages of the present invention, will become readily apparent to those skilled in the art from the following detailed description of preferred embodiments when considered in light of the accompanying drawings in which:

[0007] FIG. 1 depicts an end view of an embodiment of a regenerative heat exchanger;

[0008] FIG. 2 depicts a cross-sectional view of the regenerative heat exchanger of FIG. 1; and

[0009] FIG. 3 depicts an enlarged view of the circled portion of FIG. 2.

DETAILED DESCRIPTION OF THE INVENTION

[0010] The detailed description explains embodiments of the invention, together with advantages and features, by way of example with reference to the drawings.

[0011] Shown in FIG. 1 is an embodiment of a regenerative heat exchanger (regenerator) 10. Referring now to FIG. 2, the regenerator 10 includes a regenerator matrix 12. The matrix 12 generally comprises a body having a plurality of internal passageways (not shown) oriented in all axial direction, and may be formed of a low-thermal-conductivity and high-heat-capacity material, for example, a ceramic material. In some embodiments, the matrix 12 may include an abradable coating layer (not shown) to protect the matrix 12 material from wear. The matrix 12 in some embodiments is cylindrical in shape, but other shapes are contemplated within the scope of this invention. The matrix 12 is disposed across two or more fluid streams. Each fluid stream is carried in a conduit. In this embodiment, a cold fluid stream is carried in a first conduit 14 and a hot fluid stream is carried in a second conduit 16.

[0012] The matrix 12 is connected to a drive motor 18. The drive motor 18 causes the matrix 12 to rotate about a matrix axis 20 and transfer heat from the hot fluid stream carried through second conduit 16 to the cold fluid stream carried through first conduit 14. Because the matrix 12 moves relative to the first conduit 14 and the second conduit 16, a configuration of seals is required on a face 22 of the matrix 12 to prevent leakage, including leakage from the conduits 14 or 16, and leakage between the first conduit 14 and the second conduit 16.

[0013] Sealing between the face 22 and each of the conduits 14 and 16 is accomplished by a brush-seal configuration 24. The brush-seal configuration 24 between first conduit 14 and the face 22 is substantially identical to the brush-seal configuration 24 between second conduit 16 and the face 22, so only the brush-seal configuration 24 between first conduit 14 and the face 22 will be described herein. The brush-seal configuration 24 may be made from a variety of materials including metal, super alloys, ceramics, etc., and is chosen depending on thermal and chemical requirements of the application. As shown in FIG. 3, the brush-seal 24 extends around a periphery of the first conduit 14 at the face 22, and is fixed to a seal holder 26 at a base end 28 of the brush-seal 24 by a plurality of seal screws 30 or other means. In this example, the seal holder 26 has a U-shaped section 32 for receiving brush-seal 24. A seal screw 30 is inserted through a screw hole (not shown) in the section 32 and threaded into a seal hole (not shown) securing the brush-seal 24 to the seal holder 26.

[0014] The seal holder 26 is secured to a casing 34 by a plurality of casing screws 36. The casing 34 extends circumferentially around the first conduit 14, and is fixed relative to the first conduit 14. The casing screws 36 are inserted in a radial direction through axially-slotted holes 38 in the seal holder 26 and into threaded casing holes (not shown) in the casing 34, thereby securing the seal holder 26 to the casing 34. The slotted holes 38 allow the position of the seal holder 26 to be adjusted relative to the casing 34, and thus the position of the brush-seal 24 relative to the face 22 can be adjusted. Initially, the brush-seal 24 is positioned so the bristles 40 are in contact with the face 22. It is to be appreciated that the attachment scheme of the brush-seals 24 described herein is only an example. Other attachment schemes including, for example, adhesive attachment, are contemplated within the scope of this invention.

[0015] When the brush-seals 24 are installed, a break-in process is employed to establish a minimal gap between the brush-seals 24 and the matrix 12 at the faces 22. In one embodiment, a necessary power, P_{ref} , for rotation of the matrix 12 at a desired rotation speed is determined prior to installing the brush-seals 24. The brush-seals 24 are installed so the bristles 40 contact the matrix 12 as described above. The matrix 12 is rotated to the desired rotation speed, and a power required to rotate the matrix 12, P_{in} , is monitored. Initially, because of the contact between the bristles 40 and the matrix 12, $P_{in} > P_{ref}$. During this break-in process, the regenerator 10 is run under normal working conditions, i.e. the flows passing through the regenerator will be at the temperatures of the flows during normal operation. The friction between the bristles 40 and the matrix 12 during the break-in process increases the temperature of the bristles 40 and the matrix 12, and thus will cause slightly increased thermal expansion of the matrix 12 and the bristles 40 over that which would occur during normal operation.

[0016] As the break-in process progresses, material is worn off of the bristles 40 and/or the face 22. As material is worn off, friction between the bristles 40 and the matrix 12 is reduced. Because of the reduced friction, the temperature of bristles 40 and the matrix 12 are reduced slightly, reducing thermal expansion of the bristles 40 and the matrix 12, thus creating a slight gap between the bristles 40 and the matrix 12. The reduced friction also reduces P_{in} required for the matrix 12 to rotate at the desired speed. P_{in} is monitored until $P_{in} = P_{ref}$ at which point the break-in process is completed, leaving the desired gap between the bristles 40 and the matrix 12.

[0017] While embodiments of the invention have been described above, it will be understood that those skilled in the art, both now and in the future, may make various improvements and enhancements which fall within the scope of the claims which follow. These claims should be construed to maintain the proper protection for the invention first described.

What is claimed is:

1. A regenerative heat exchanger comprising:
 - a regenerator matrix;
 - at least two conduits, each conduit having a matrix end abutting a face of the regenerator matrix, the at least two conduits carrying at least two fluid flows, the fluid flows passing through the regenerator matrix; and
 - a plurality of brush-seals, each brush-seal disposed at a matrix end of each conduit without contacting the

matrix, thereby sealing around a periphery of each conduit to prevent mixing of fluid flows.

2. The regenerative heat exchanger of claim 1 wherein each brush-seal is affixed to a casing.

3. The regenerative heat exchanger of claim 2 wherein the plurality of brush-seals is affixed to the casing by a plurality of screws.

4. The regenerative heat exchanger of claim 3 wherein each screw is installed through a slotted hole in the casing, allowing the position of the brush-seal to be adjusted.

5. The regenerative heat exchanger of claim 2 wherein the plurality of brush-seals is affixed to the casing by adhesive.

6. The regenerative heat exchanger of claim 1 wherein the regenerator matrix includes a plurality of axially-oriented internal passageways.

7. The regenerative heat exchanger of claim 1 wherein the regenerator matrix is formed of a low-thermal-conductivity and high-heat-capacity material.

8. The regenerative heat exchanger of claim 7 wherein the regenerator matrix is formed from a ceramic material.

9. The regenerative heat exchanger of claim 1 wherein the regenerator matrix includes an abradable coating layer.

10. The regenerative heat exchanger of claim 1 wherein each brush-seal is formed from a superalloy material.

11. The regenerative heat exchanger of claim 1 wherein each brush-seal is formed from a ceramic material.

12. A method for establishing a minimal gap between a regenerator matrix of a regenerative heat exchanger and a plurality of brush-seals, the brush-seals sealing around a periphery of each conduit of a plurality of conduits carrying fluid flows which pass thorough the regenerator matrix, the method comprising:

installing the plurality of brush-seals such that a bristle end of each brush-seal contacts a face of the regenerator matrix;

rotating the regenerator matrix at a desired speed about an axis substantially perpendicular to the face of the regenerator matrix, friction between the bristle end and the face causing material to be removed from the bristle end and/or the face of the regenerator matrix;

stopping rotation of the regenerator matrix when a power required to rotate the regenerator matrix at the desired speed reaches a predetermined level, stopping the removal of material from the bristle end and/or the face of the regenerator matrix and establishing a minimal gap between the bristle end and the face of the regenerator matrix.

13. The method of claim 9 wherein the face of the regenerator matrix includes an abradable coating layer.

14. The method of claim 9 wherein the temperatures of the flows passing through the regenerator are substantially the same as at normal operation of the regenerative heat exchanger.

15. The method of claim 9 wherein the power is continuously monitored to determine when the power reaches the predetermined level.

16. The regenerative heat exchanger of claim 9 wherein the regenerator matrix is formed from a ceramic material.

17. The regenerative heat exchanger of claim 9 wherein each brush-seal is formed from a superalloy material.

18. The regenerative heat exchanger of claim 9 wherein each brush-seal is formed from a ceramic material.

* * * * *