


US 20090263771A1

(19) **United States**(12) **Patent Application Publication**
Darois et al.(10) **Pub. No.: US 2009/0263771 A1**(43) **Pub. Date: Oct. 22, 2009**(54) **CONTAMINATION DETECTION
SIMULATION SYSTEMS AND METHODS**(75) Inventors: **Eric L. Darois**, New Market, NH
(US); **Frederick P. Straccia**,
Stratham, NH (US); **James P.
Tarzia**, East Hampstead, NH (US)Correspondence Address:
MILLS & ONELLO LLP
ELEVEN BEACON STREET, SUITE 605
BOSTON, MA 02108 (US)(73) Assignee: **RADIATION SAFETY AND
CONTROL SERVICES, INC.**,
Stratham, NH (US)(21) Appl. No.: **12/426,099**(22) Filed: **Apr. 17, 2009****Related U.S. Application Data**(60) Provisional application No. 61/045,861, filed on Apr.
17, 2008.**Publication Classification**(51) **Int. Cl.**
G09B 9/00 (2006.01)
G09B 19/00 (2006.01)(52) **U.S. Cl.** **434/218**(57) **ABSTRACT**

Provided are contamination detection simulation systems and methods comprising a control unit that generates a first signal comprising data corresponding to a simulated source of contamination; a simulated detector that receives the signal from the control unit, the simulated detector positioned at a distance from a surface; a proximity detector that determines the distance between the simulated detector and the surface and outputs a distance result; and a processing unit that generates a second signal in response to the first signal and the distance result.






FIG. 1

(PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5

CONTAMINATION DETECTION SIMULATION SYSTEMS AND METHODS

RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Patent Application No. 61/045,861, filed Apr. 17, 2008, the content of which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

[0002] The present invention relates to devices and methods that improve the simulation of contamination detectors.

BACKGROUND

[0003] There is an ongoing need to address public safety concerns regarding the accidental, intentional, or natural release of contaminants from potentially hazardous materials, for example, radiation, chemicals, poisons, biological agents, and the like. While sophisticated sensing devices are available to detect such contaminants, it is important that the operators of these devices be properly trained in the use of the devices, without exposing the operators to possible contamination during operational training of these devices. Therefore, it is preferable that an operator be trained in a non-hazardous environment that simulates the detection of the contaminants, but that the operator not be exposed to potentially hazardous radioactive, chemical, or biological contamination.

[0004] Conventional hazardous material detection simulation systems often include a simulated detector, such as a training probe, that receives harmless signals, for example, radiofrequency (RF) signals or signals emitted from harmless substances, such as magnets or metallic substances, that simulate gases, vapors, or radiation from a contaminated surface. The simulated detector measures the received signals from the source and outputs the signals to a meter display, wherein the meter readings are studied by an operator trainee under the supervision of an instructor.

[0005] Other conventional training systems can include a control unit instead of a live source, which transmits a signal to a simulated detector, which responds to the signal as if it was detecting an actual source of contamination. The signal provided by the control unit includes data that simulates a dose rate or contamination level that is controlled by a control unit operator or instructor. This data is transmitted by the control unit to the simulated detector, and also to a meter, where an operator trainee takes readings of measurements.

[0006] The ability of these training systems to simulate a realistic response of the simulated detector to surface contamination depends largely on the skills of the control unit operator, since the operator needs to continually monitor the location of the simulated detector relative to a surface over which the detector is positioned, and needs to manually change the contamination level on the control unit to account for changes in its proximity to the surface. Thus, if the distance between the detector and the surface changes, and if the operator does not adjust the control unit signal to accommodate for the change in distance, the meter may not display accurate readings, since, in "real life" environments, the contamination level may be different depending on the distance to the surface. Further, it is difficult to train the operator trainee to position a detector at a proper orientation and distance from the surface when performing a survey of the sur-

face. Accordingly, the simulation may not be realistic to the operator trainee, which may affect the quality of the training received by the operator trainee.

SUMMARY OF INVENTION

[0007] In accordance with aspects of the invention, a detection simulation system comprises a control unit that generates a first signal comprising data corresponding to a simulated source of contamination; a simulated detector that receives the signal from the control unit, the simulated detector positioned at a distance from a surface; a proximity detector that determines the distance between the simulated detector and the surface and outputs a distance result; and a processing unit that generates a second signal in response to the first signal and the distance result.

[0008] In an embodiment, the simulated source of contamination comprises simulated alpha or beta radioactive particles, chemical or biological contamination.

[0009] In an embodiment, the first signal comprises data that simulates a response to a dose rate or contamination level of the source of contamination when the simulated detector is in contact with a surface.

[0010] In an embodiment, the processing unit modifies the data of the first signal based on the distance result.

[0011] In an embodiment the second signal comprises data that simulates a dose rate or contamination level of the source of contamination adjusted according to the distance result.

[0012] In an embodiment, the simulated dose rate or contamination level simulates a maximum dose rate or contamination level at a contaminated surface, and wherein the processing unit generates the second signal that simulates a response to an adjusted dose rate or contamination level based on the distance result.

[0013] In an embodiment, the system comprises a meter that receives the second signal from the processing unit. In an embodiment, the meter, in response to the second signal, simulates a response to alpha or beta radioactive particles.

[0014] In an embodiment, the simulated detector comprises a training probe, wherein the proximity detector is configured to be positioned in the training probe.

[0015] In an embodiment, the proximity detector provides a signal to the processing unit indicating whether the simulated detector is properly positioned over the surface.

[0016] In an embodiment, the proximity detector comprises a transducer that determines the distance between the simulated detector and the surface.

[0017] In an embodiment, the second signal is received by the control unit.

[0018] In accordance with other aspects of the invention, a method of simulating detection of a source of material comprises generating a first signal comprising data corresponding to a simulated source of contamination; positioning a simulated detector at a distance from a surface; determining the distance between the simulated detector and the surface; and generating a second signal in response to the first signal and the distance result.

[0019] In an embodiment, the method further comprises verifying that the detector is properly positioned at a same distance between the simulated detector and the surface during a period of time.

[0020] In an embodiment, the simulated source of contamination comprises simulated alpha or beta radioactive particles.

[0021] In an embodiment, generating the first signal comprises generating data that simulates a response to a dose rate or contamination level of the source of contamination when the simulated detector is in contact with a surface.

[0022] In an embodiment, generating the second signal comprises generating data that simulates a response to a dose rate or contamination level of the source of contamination adjusted according to the distance result.

[0023] In an embodiment, the simulated dose rate or contamination level simulates a maximum dose rate or contamination level at a contaminated surface, and wherein the processing unit generates the second signal that simulates a response to an adjusted dose rate or contamination level based on the distance result.

[0024] In an embodiment, the method comprises determining whether the simulated detector is properly positioned over the surface.

[0025] In accordance with other aspects of the invention, a method of training an operator to detect contamination in a hazardous environment comprises setting at least one simulated measurement of the detected contamination on a control unit; transmitting the at least one simulated measurement to a simulated detector; measuring a distance between the simulated detector and a surface over which the simulated detector is positioned; modifying the at least one simulated measurement in response to the distance between the simulated detector and the surface; and outputting the at least one modified simulation measurement to a display.

[0026] In an embodiment, the at least one simulated measurement comprises at least one of a simulated dose rate and a contamination level of at least one of alpha radiation and beta radiation.

[0027] In an embodiment, the display is at least one of a display of the control unit and a meter display.

[0028] In an embodiment, an instructor sets the at least one simulated measurement on the control unit and wherein the trainee has an instrument that receives the modified simulated measurement.

BRIEF DESCRIPTION OF THE DRAWINGS

[0029] The present invention will become more apparent in view of the attached drawings and accompanying detailed description. The embodiments depicted herein are provided by way of example, not by way of limitation, wherein like reference numerals refer to the same or similar elements throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating aspects of the invention. In the drawings:

[0030] FIG. 1 is a block diagram of a conventional radiation detection simulation system that simulates a radiation detector;

[0031] FIG. 2 is a block diagram of a contaminant detection simulation system, according to embodiments of the invention;

[0032] FIG. 3 is a diagram illustrating a contaminant detection simulation system including a training detector and a meter, according to embodiments of the invention;

[0033] FIG. 4 is a diagram illustrating a contaminant detection simulation system including a training detector and a simulated meter, according to embodiments of the invention; and

[0034] FIG. 5 is a flowchart of the steps used to simulate the detection of contamination on a surface in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS

[0035] Hereinafter, aspects of the present invention will be described by describing illustrative embodiments in accordance therewith, with reference to the attached drawings. While describing these embodiments, detailed descriptions of well-known items, functions, or configurations are typically omitted for conciseness.

[0036] It will be understood that, although the terms first, second, etc. are used herein to describe various elements, these elements should not be limited by these terms. These terms are used to distinguish one element from another, but not to imply a required sequence of elements. For example, a first element can be termed a second element, and, similarly, a second element can be termed a first element, without departing from the scope of the present invention. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0037] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes” and/or “including,” when used herein, specify the presence of stated features, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof.

[0038] Unless otherwise specified, the illustrated embodiments can be understood as providing exemplary features of varying detail of certain embodiments, and therefore, unless otherwise specified, features, components, modules, and/or aspects of the illustrations can be otherwise combined, separated, interchanged, and/or rearranged without departing from the disclosed systems or methods. Additionally, the shapes and sizes of components are also exemplary and unless specified, can be altered without affecting the scope of the disclosed systems or methods of the present disclosure.

[0039] It will be understood that when an element is referred to as being “on” or “connected” or “coupled” to another element, it can be directly on or connected or coupled to the other element, or intervening elements can be present. In contrast, when an element is referred to as being “directly on” or “directly connected” or “directly coupled” to another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion, e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” “in contact with” versus “in direct contact with” etc. It will be further understood that when an element is referred to as being “in contact with” another element, the element can be directly abutting the other element such that there is no separation between the two elements, or the element can be separated from the other element by a small distance.

[0040] To address the abovementioned limitations of the prior art, in embodiments, systems and methods are provided that simulate a contaminant detector, for example, a radiation detector, and in doing so, consider a distance between the simulated detector and a surface by utilizing a proximity

detector that modifies a simulated dose rate measurement, contamination level measurement, or other data known to those of ordinary skill in the art as being useful in detecting contaminants, such as radioactive, chemical or biological agents, and the like. Accordingly, the systems and methods described herein are useful for exercising basic detection principles, for example, radiation or chemical detection principles, as well as safety concepts.

[0041] FIG. 1 is a block diagram of a conventional radiation detection simulation system **100** that simulates a radiation detector. The training system **100** comprises a control system **120**, a simulated radiation detector **130**, and a meter **140**.

[0042] The control unit **120** allows an operator or instructor to select a signal strength that represents a simulated dose rate or contamination level of a source of radiation and to transmit a signal representing a response to the simulated dose rate or contamination level to the simulated radiation detector **130** via a radio or wireless link, direct connection, internet connection, or other communication method known to those of ordinary skill in the art. The simulated radiation detector **130** in turn outputs the signal to a visual display or audio device on the meter **140**. During operational training, an operator trainee can observe readings, perform calculations, etc. based on results displayed on the meter.

[0043] However, the conventional radiation detection simulation system **100** shown in FIG. 1 may not provide an operator trainee with a “real-life experience,” since the control unit operator must change the signal provided to the display in order to compensate for changes in position of the detector **130** relative to the simulated contaminated surface. For example, in a real-life operation, a detector that is positioned 3 inches from a surface of a sample emitting beta radiation particles may receive a signal at 3 inches, but receive a different signal if the detector is positioned 4 inches from the surface. The training system **100**, on the other hand, cannot automatically adjust the simulated signal when an operator/trainee moves the detector from 3 inches to 4 inches from the surface. Instead, the control unit operator must change the simulated signal on the control unit **120** in order to compensate for this change in position of the simulated detector **130**. Thus, the control unit operator must continually monitor the location of the simulated radiation detector **130** relative to the surface, and manually change the signal on the control unit **120**, in order to account for changes in distance relative to the surface. In addition, there is no way to verify that the operator trainee is properly positioning the active face of the detector toward the sample. Further, there is no way to verify that the operator trainee is moving the detector along the surface at a constant distance from the surface, which is necessary during certain operations, for example, in performing a survey of an area containing hazardous material.

[0044] FIG. 2 is a block diagram of a contaminant detection simulation system **200** according to embodiments of the invention. In an embodiment, the detection simulation system **200** automatically emulates the response of a radiation detector to alpha or beta particle contamination. In other embodiments, the detection simulation system can emulate the response of other detectors that detect hazardous and non-hazardous matter and energy waves produced by chemicals, biological agents, gases, residues, contamination, vapors, fumes, or other hazardous or non-hazardous particles.

[0045] The detection simulation system **200** comprises a control unit **220**, a simulated detector **230**, also referred to

herein as a signal detector, a proximity detector **235**, a processing unit **245**, and a meter **240**.

[0046] The control unit **220** outputs a signal representing a response to a simulated or hypothetical dose rate or contamination level, or outputs signals representing other data known to those of ordinary skill in the art as being useful in the detection of a source of material, such as radioactive material, chemicals, biological agents, and the like. For example, the signal can simulate a contamination level of alpha radiation contamination or beta radiation contamination, or simulate a contamination level of a chemical or biological agent, or simulate a response to the abovementioned contamination levels. In an embodiment, the strength or level of the simulated source of material is selected by a human operator. In another embodiment, the strength of the simulated source of material is computer-generated, for example, a radiation pattern that is provided by a software program stored on a computer.

[0047] In an embodiment, the control unit **220** outputs a first signal that simulates a response to a maximum dose rate or contamination level. In an embodiment, the simulated maximum dose rate or contamination level applies to a dose rate or level of contamination directly on a contaminated surface. In an embodiment, the control unit **220** can receive a second signal from other elements of the system **200**, such as at least one of the detector **230** and the processing unit **245**. One such second signal includes data corresponding to a dose rate or contamination level adjusted for distance between the detector **230** and the surface.

[0048] In an embodiment, the control unit **220** is co-located with the simulated detector **230**, for example, enclosed together in a single platform. In an embodiment, the control unit **220** comprises the processing unit **245**, described below. In other embodiments, the control unit **220** is directly or indirectly connected to the simulated detector **230**. In another embodiment, the control unit **220** communicates with the simulated detector **230** by a radio link, GPS, or other wireless communication link, or internet connection. The simulated detector **230** receives the signal from the control unit **220** and upon receipt of the signal responds to the signal as if it was detecting actual contamination, such as alpha or beta radiation, vapors, chemicals, biological agents, and the like. The simulated detector **230** outputs the signal to the meter **240**, which reports the signal on a display of the meter. In an embodiment, the display is a visual display. In other embodiments, the meter **240** can include an audio and/or visual device that outputs the signal as tones, clicks, human speech, or sounds that a trained operator can comprehend. In an embodiment, the meter **240** can be an off-the-shelf meter, and include features known to those of ordinary skill in the art. In an embodiment, the meter **240** can be part of the detector **230**. In an embodiment, the meter **240** can be a commercial off-the-shelf meter that can be configured to operate in response to signals received from the detector **230** and/or the control unit **210**, or can operate with sensing devices such as probes that detect actual hazardous materials. For example, the meter **240**, in response to signals received from the control unit **210** and/or the proximity detector **230**, can be responsive to simulated alpha or beta radioactive particles or alternatively, and can provide readings corresponding to actual alpha or beta radioactive particles when the detector **230** is not in communication with the meter **240**.

[0049] In an embodiment, the simulated detector **230** receives additional data that is used to adjust the received

signal in response to the data, wherein the adjusted signal is output to at least one of the control unit **220** and the meter **240**. In an embodiment, the additional data includes detector-to-surface distance information provided by the proximity detector **235**.

[0050] In an embodiment, the simulated detector **230** is configured to operate substantially the same as an actual contaminant detector. Unlike conventional simulated detectors, the simulated detector **230** in the embodiments herein can verify if an operator trainee is holding a face of the detector, or a probe of the detector, at a proper orientation and at a proper distance from a surface simulating a contaminated surface in order to perform a survey of contamination on the surface. In addition, the simulated detector **230** in the embodiments herein can verify if an operator trainee is holding the detector at an optimum distance from a surface while attempting to locate surface contamination, noting that the instructor can determine whether the operator trainee has in fact located surface contamination by sending a signal from the control unit **220** to the probe. These features are achieved by the proximity detector **235**, which continuously provides distance-to-surface data to the processing unit **245** or the control unit **220** for the instructor to use to verify an ideal, consistent distance while the operator trainee is performing a task, such as a survey of the surface.

[0051] The proximity detector **235** transmits data related to distance from the surface simulating a contaminated surface. In an embodiment, the proximity detector **235** comprises at least one transducer comprising a transceiver that measures a distance from the surface to back-calculate the signal corresponding to the simulated or hypothetical dose rate sent to the meter display based on a maximum dose rate at contact. In other embodiments, one or more sensors can be used to measure the detector-to-surface distance. In an embodiment, the proximity detector **235** determines a distance from the simulated detector **230** to the surface and provides the detector-to-surface distance result to the processing unit **245** to the simulated detector **230**. In an embodiment, the proximity detector **235** comprises at least one piezoelectric sensor that operates at frequencies known to those of ordinary skill in the art, for example, ultrasonic frequencies. In an embodiment, the at least one piezoelectric sensor can comprise a single piezoelectric transducer. In other embodiment, the at least one piezoelectric transducer can include a first transducer comprising a transmitter that transmits signals to the surface, and a second transducer comprising a receiver that receives signals from the surface.

[0052] In an embodiment, the proximity detector **235** comprises a wireless sensing system, such as a laser sensing system or acoustic sensing system such as an ultrasonic sensing system that determines the distance between the proximity detector **235** and the surface by operating at frequency ranges known to those of ordinary skill in the art. The distance between the detector **230** and the surface is determined by outputting from the sensing system a first signal to the surface. The proximity detector **235** receives a second signal from the surface in response to the outputted first signal, and calculates the time required for the second signal to be reflected back to the sensor from the surface. In an embodiment, at least one of the first signal and second signal operates at laser frequencies. In another embodiment, at least one of the first signal and second signal operates at ultrasonic frequencies. The calculated time is converted into a distance result, which is output to the processing unit **245**.

[0053] The proximity detector **235** can determine if the distance between the detector **230** and the surface is greater than or equal to 0 inches. As described above, the control unit **220** generates a signal based on measurements taken when the detector **230** is positioned on or in contact with the surface, or when the detector **230** is proximal to or near the surface, for example, 0-1 inches from the surface. If the proximity detector **235** determines that the distance between the detector **230** and the surface is greater than 0 inches in one embodiment, or greater than 0-1 inches in another embodiment, data including the actual distance between the detector **230** and the surface is provided to the processing unit **245**, wherein the signal provided by the control unit is adjusted in response to the distance result provided by the proximity detector **235**, and the adjusted signal is output to at least one of the control unit **220** and the meter **240**.

[0054] The processing unit **245** receives the signal from the control unit **220** and the detector-to-surface distance data from the proximity detector **245** and in response generates an adjusted signal that is output to at least one of the control unit **220** and the meter **240**. For example, the initial signal output by the control unit **220** to the simulated detector **230** can represent a maximum dose rate, contamination level, or other measurements of a simulated source at a distance that is, in an embodiment, 0 inches from the surface, or another embodiment, is 0-1 inches from the surface, and is automatically modified by the detector-to-surface result to accurately represent a dose rate, contamination level, or other measurements of a simulated source adjusted based on the calculated distance between the detector and the source.

[0055] In an embodiment, as shown in FIG. 2, the processing unit **245** is separate from the simulated detector **230**, wherein the detector **230** simulates a detector, and the processing unit **245** performs the calculation. In another embodiment, the processing unit **245** is part of the detector **230**. In an embodiment, the processing unit **245** is part of the control unit **220**.

[0056] In an embodiment, the processing unit **245** recalculates the dose rate or contamination level provided by the control unit **220** based on the distance of the detector **230** from the surface. The processor can calculate the change in dose rate or contamination level adjusted for distance based on empirical relationships or theoretical principles, for example, based on the geometry of a hypothetical source at the surface and, in another example, based on energy levels of the emitted simulated radiation.

[0057] The system **200** outputs the data, for example, corresponding to the modified dose rate, or contamination level, to at least one of the meter **240** and the control unit **220**. In an embodiment, the control unit **220** and simulated detector **230** continually transmit the signals described herein in real-time. The meter **240** and control unit **220** continually update the reported data in real time to emulate the effects of moving the simulated detector **230** closer to or farther from the simulated surface contamination.

[0058] FIG. 3 is a diagram illustrating a contaminant detection simulation system **300** including a simulated monitoring detector **350** and a meter **360**, according to embodiments of the invention. FIG. 4 is a diagram illustrating a contaminant detection simulation system **400** including a simulated monitoring detector **350** and a simulated meter **460**, according to embodiments of the invention.

[0059] In FIGS. 3 and 4, a control unit **320** is controlled by an operator, for example, a training instructor, who can output

a signal via a communication path **321**, **421**, respectively, to a training detector such as a simulated monitoring detector **350** that simulates results of a dose rate, contamination level, or other measurements known to those of ordinary skill in the art of a source of material. In FIG. 3, the signal can also be output to a meter **360** that can also measure “real” contamination, also referred to as a “real” meter”. In FIG. 4, the signal can be output to a simulated meter **460**, which includes the simulated monitoring detector **350**. In an embodiment, the communication paths **321**, **421** can be direct connections, for example, a wire or cable between the control unit **320** and the simulated monitoring detector **350**. In other embodiments, the communication paths **321**, **421** can be wireless connections.

[0060] In the embodiment shown in FIG. 3, the simulated monitoring detector **350** can be positioned in a simulated monitoring probe **330** that is attached via a direct or wireless connector **322** to a “real” meter **360**. In an embodiment, the meter **360** can be a commercial off-the-shelf meter that can be configured to operate in response to signals received from the detector **350** and/or the control unit **320**, or can operate with sensing devices such as a monitoring probe that detects actual hazardous materials. In the embodiment shown in FIG. 4, a detector **350** is positioned in the simulated meter **460**. In other embodiments, the detector **350** is positioned in a different location than the meter **460**.

[0061] A conventional monitoring probe can detect radiation, gases, vapors, emissions, and the like, when the probe is placed over a source of the radiation, gases, etc., and generate a signal, for example, an analog signal, from the detected radiation, gases, etc. In FIG. 3, the detector **350** is positioned in a simulated monitoring probe **330**, wherein readings are output to the meter **360**. In FIGS. 3 and 4, the simulated monitoring detector **350** can be positioned by an operator trainee over a surface **370** and allow the trainee to take readings from the meter **460**.

[0062] In an embodiment, the simulated monitoring detector **350** comprises a proximity detector **335**, which continuously provides to a processing unit data (d) related to the distance to the surface **370**. In response to the data (d), the signal provided by the control unit **320** to the simulated detector **330** can be adjusted, and output to the control unit **320** to notify the instructor of the adjusted signal, and can be output to the simulated meter **460** (FIG. 4) or “real” meter **360** (FIG. 3) to permit the operator trainee to take accurate readings. The instructor can also verify an ideal, consistent distance while the operator trainee is performing a task, such as a survey of the surface **370**.

[0063] FIG. 5 is a flowchart of the steps used to simulate the detection of contamination on a surface in accordance with an embodiment of the present invention.

[0064] As shown in Step **510**, simulated measurements are set. In an embodiment, the simulated measurements can be set by an operator or instructor on a control unit, such as control unit **220** shown in FIG. 2 or control unit **320** shown in FIGS. 3 and 4. In another embodiment, the simulated measurements can be input to, or determined by, a computer. In an embodiment, the simulated measurements can include a dose rate, contamination level, or other parameters known to those of skill in the art as being determined by a detector and measured by an operator.

[0065] As shown in Step **520**, the simulated measurements are transmitted to a simulated detector, which responds to the simulated measurements as if it was detecting actual contamination, such as radiation, vapors, chemicals, biological

agents, and the like. The simulated detector can output the simulated measurements to a meter, which can be used by an operator trainee to take readings of the measurements.

[0066] As shown in Step **530**, the distance between the simulated detector and a surface is measured. As shown in Step **540**, the simulated measurements are adjusted in response to the measured distance between the simulated detector and the surface. In an embodiment, a processing unit recalculates the simulated measurements based on the transmitted signal from a proximity detector, where calculations are performed to adjust the simulated measurements to more accurately simulate the presence of contamination of the surface.

[0067] As shown in Step **550**, the adjusted simulated measurements are output. In an embodiment, the adjusted simulated measurements are output to the control unit, wherein an instructor can provide feedback to the operator trainee in response to the adjusted simulated measurements. In another embodiment, the adjusted simulated measurements are output to a meter so that an operator trainee can reposition the detector to be at a proper distance from the simulated contaminated surface in order to receive more appropriate readings.

[0068] The systems and methods for simulating contamination detection provide several advantages over conventional training systems. One advantage is that the systems and methods can simulate the detection of beta and alpha particles emitted from a surface containing radioactive contamination in real time and in a realistic manner. A second advantage is that the systems and methods provide an accurate calculation of a simulated dose rate or contamination level response based on a distance from a surface using an established response algorithm, thereby simulating a response based on the presence of contamination on the surface, which is actually a hypothetical contamination level as no actual contamination exists on the surface. This method of emulating the response of a radiation detector to beta or alpha particle surface contamination has wide potential application for radiation detector training simulator systems using various detector technologies. The radiation energy response of different detector technologies could then be used to modify the dose rate or contamination level response algorithm in order to allow the training system to simulate various radiation detector designs.

[0069] Accordingly, the systems and methods for simulating contamination detection described herein have wide potential application in many fields where detectors, including radiation detectors, chemical detectors, and the like are used, and where training is required on such detectors, including, but not limited to, environmental cleanup, waste monitoring, and emergency response.

[0070] While this invention has been particularly shown and described with references to preferred embodiments thereof, it will be understood to those skilled in the art that various changes in form and details may be made herein without departing from the spirit and scope of the invention as defined in the appended claims.

What is claimed is:

1. A detection simulation system comprising:
 - a control unit that generates a first signal comprising data corresponding to a simulated source of contamination;
 - a simulated detector that receives the signal from the control unit, the simulated detector positioned at a distance from a surface;

- a proximity detector that determines the distance between the simulated detector and the surface and outputs a distance result; and
- a processing unit that generates a second signal in response to the first signal and the distance result.
2. The detection simulation system of claim 1, wherein the simulated source of contamination comprises simulated alpha or beta radiation.
3. The detection simulation system of claim 1, wherein the first signal comprises data that simulates a response to a dose rate or contamination level of the source of contamination when the simulated detector is in contact with a surface.
4. The detection simulation system of claim 1, wherein the processing unit modifies the data of the first signal based on the distance result.
5. The detection simulation system of claim 1, wherein the second signal comprises data that simulates a dose rate or contamination level of the source of contamination adjusted according to the distance result.
6. The detection simulation system of claim 5, wherein the simulated dose rate or contamination level simulates a maximum dose rate or contamination level at a contaminated surface, and wherein the processing unit generates the second signal that simulates a response to an adjusted dose rate or contamination level based on the distance result.
7. The detection simulation system of claim 1 further comprising a meter that receives the second signal from the processing unit.
8. The detection simulation system of claim 7, wherein the meter, in response to the second signal, simulates a meter response to alpha or beta radiation.
9. The detection simulation system of claim 1, wherein the simulated detector comprises a training probe, wherein the proximity detector is configured to be positioned in the training probe.
10. The detection simulation system of claim 1, wherein the proximity detector provides a signal to the processing unit indicating whether the simulated detector is properly positioned over the surface.
11. The detection simulation system of claim 1, wherein the proximity detector comprises a transducer that determines the distance between the simulated detector and the surface.
12. The detection simulation system of claim 1, wherein the second signal is received by the control unit.
13. A method of simulating detection of a source of material comprising:
- generating a first signal corresponding to a simulated source of contamination;
 - positioning a simulated detector at a distance from a surface;
 - determining the distance between the simulated detector and the surface; and

generating a second signal in response to the first signal and the distance result.

14. The method of claim 13, further comprising verifying that the detector is properly positioned at a same distance between the simulated detector and the surface during a period of time.

15. The method of claim 13, wherein the simulated source of contamination comprises simulated alpha or beta radioactive particles.

16. The method of claim 13, wherein generating the first signal comprises generating data that simulates a response to dose rate or contamination level of the source of contamination when the simulated detector is in contact with a surface.

17. The method of claim 13, wherein generating the second signal comprises generating data that simulates a dose rate or contamination level of the source of contamination adjusted according to the distance result.

18. The method of claim 17, wherein the simulated dose rate or contamination level simulates a maximum dose rate or contamination level at a contaminated surface, and wherein the processing unit generates the second signal that simulates a response to an adjusted dose rate or contamination level based on the distance result.

19. The method of claim 13 further comprising determining whether the simulated detector is properly positioned over the surface.

20. A method of training an operator to detect contamination in a hazardous environment comprising:

- setting at least one simulated measurement of the detected contamination on a control unit;
- transmitting the at least one simulated measurement to a simulated detector;
- measuring a distance between the simulated detector and a surface over which the simulated detector is positioned;
- modifying the at least one simulated measurement in response to the distance between the simulated detector and the surface; and
- outputting the at least one modified simulation measurement to a display.

21. The method of claim 20, wherein the at least one simulated measurement comprises at least one of a simulated dose rate and a contamination level of at least one of alpha radiation and beta radiation.

22. The method of claim 20, wherein the display is at least one of a display of the control unit and a meter display.

23. The method of claim 20, wherein an instructor sets the at least one simulated measurement on the control unit and wherein the trainee has an instrument that receives the modified simulated measurement.

* * * * *