US 20100322042A1

(19) **United States**

(12) **Patent Application Publication**

Serletic et al.

(10) **Pub. No.: US 2010/0322042 A1**

(43) **Pub. Date: Dec. 23, 2010**

(54) **SYSTEM AND METHOD FOR GENERATING MUSICAL TRACKS WITHIN A CONTINUOUSLY LOOPING RECORDING SESSION**

(75) Inventors: **Matt Serletic**, Malibu Hills, CA (US); **Travis Robert Savo**, Valencia, CA (US); **Francesco Gerald Capodieci**, Woodland Hills, CA (US); **Reza Rassool**, Stevenson Ranch, CA (US)

Correspondence Address:
LOEB & LOEB, LLP
321 NORTH CLARK, SUITE 2300
CHICAGO, IL 60654-4746 (US)

(73) Assignee: **Music Mastermind, LLC**, Calabasas, CA (US)

(21) Appl. No.: **12/791,792**

(22) Filed: **Jun. 1, 2010**

Related U.S. Application Data

(60) Provisional application No. 61/182,982, filed on Jun. 1, 2009, provisional application No. 61/248,238, filed on Oct. 2, 2009, provisional application No. 61/266,472, filed on Dec. 3, 2009.

Publication Classification

(51) **Int. Cl.**
H04B 1/20 (2006.01)

(52) **U.S. Cl.** **369/1**

(57) **ABSTRACT**

An apparatus for creating a musical composition comprising an audio interface, an audio converter and a live looping recording session is disclosed. The audio interface operably receives audio from an input device and outputs audio to an audio output device. The audio converter module is operably connected to the audio interface to convert audio received via the audio interface into an audio track. The recording session module is configured to repeatedly playback a live loop that includes at least a portion of a first audio track, and to add at least a portion of a second audio track to the live loop during repeated playback. The first audio track may be a pre-existing track stored in a data storage medium. The recording session module may be configured to add at least a portion of a third audio track to the live loop during playback, which may be automatically generated based on one or more musical criteria of the first or second tracks. The apparatus may include a user interface coupled to the recording session module to provide a visual representation illustrating the portion of the live loop that is being played. The audio converter module may include a track partitioner to divide at least one of the first and second audio tracks into one or more partitions, a quantizer that aligns audio with a predetermined beat, and a frequency detector to identify the pitch of one or more sounds leading to their storage as a morphology. A method is also provided.




100
Audio Converter Module
140
Recording Session Live Looping Module
142
Multi-Track Auto-Compositor Module
144
Harmonizer Module
146
Track Sharer Module
148
Sound Searcher Module
150
Chord Matcher Module
154
Genre Matcher Module
152
User Interface
134
Data Storage
132
75
50
51
52
55
54

FIG. 1A



FIG. 1B

FIG. 1C





FIG. 2

Intro	Verse	Chorus	Verse	Chorus	Bridge	Verse	Chorus

FIG. 3


Track Partitioner
204
Silence Detector
402
Stop Detector
404
Manual Partitioner
406

FIG. 4


502
M+
CH2 10.0dB 50.0Hz (1.00RS/s)

FIG. 5



FIG. 6



FIG. 7



FIG. 8


900
Start
910
Play Recording?
N
Y
920
Generate Track?
Y
922
Receive Audible Input
924
Convert Into Track
926
Add Track To Recording
N
940
Modify Track?
Y
942
Receive Adjusted Parameters
944
Adjust Track
N
960
Modify Recording Setup?
Y
962
Calibrate Recording Circuit
964
Change Other Recording Parameter Settings
N
980
End Session?
N
Y
Return

FIG. 9



FIG. 10

FIG. 10B

FIG. 10A

FIG. 10A



FIG. 10B


1100
1120
1130
1140
Circuit Parameters
mic gain: 1.0
upper: 0.025
lower: 0.0050
halflife: 0.01
1110
Calibrate
system latency (s): 0.3227
1150
1160

FIG. 11

FIG. 12A



FIG. 12B



FIG. 12C



FIG. 13A



FIG. 13B



FIG. 13C





FIG. 14A



FIG. 14B



FIG. 14C


MTAC Module
144
Partition Scorer
1702
Compositor
1704

FIG. 15


start
startBonus = 1;
Set keyWeights[index];
Start loop for each key (1 to 12)
Start loop
for each
note in passage
Score = (note.duration/
passage.duration) *
keyWeights[index];
Start of
bar?
Y
Score *=
startBonus;
N
keyScore[key]
+= Score;
Next
note?
N
Next
key?
BestKey is index of
highest element in
keyScore[] array
done

FIG. 16

FIG. 17



FIG. 17A




Bonus += occurrenceBonus
Bonus += fracDuration
Is note a chord root?
Y
Bonus += rootBonus
N
Is note start of a chord bar?
Y
Bonus += startBonus
N
Sum += bonus * multiplier
End of passage?
Y
Return sum
done

FIG. 17B


Pitch = 100, Duration = 80
Pitch = 90, Duration = 90
Pitch = 85, Duration = 78.3
Pitch = 75, Duration = 65

FIG. 18


mu = 6
mu = 2
mu = 1
Step
2
1.6
1.2
0.8
0.4
0
Step Response
-0.5
1.5
3.5
Time

FIG. 19


Audio
Receive Audio
2002
Original Audio Waveform
Received Audio
Convert Audio Waveform Into Morphology Of Pitch Events
2004
Compute Difference Between Original And Constructed Waveform
2008
Morphology
Constructed Waveform
Construct Waveform With Critically Damped Pitch Changes
2006
Compute Score
2010

FIG. 20


Start
Set Configuration
2102
Record Take
2104
Partition Take
2106
Convert Partition To Morphology
2108
Guide Selection
2110
Score Partition
2112
Illustrate Scores for Partitions
2114
Another Take?
2116
Auto Composition?
2118
Receive Manually Selected Partitions
2120
Auto Select Partitions Based On Score
2122
Compose track
2124
Another Take?
2126
End

FIG. 21



FIG. 22



FIG. 23


Lead Music Source
2404
Lead Music Input
Controller
2410
Control
Transform Note Module
2402
Music Output
Accompaniment Destination
2412
Key
Chord
Accompaniment Source
2406
Accompaniment Music Input
Chord/Key Selector
2408

FIG. 24


2402
Lead Music Input
Accompaniment Music Input
Determine Note of Lead 2502
Determine Note of Accompaniment 2504
Determine Chord of Lead 2506
Determine Key of Lead 2508
Transform Note 2510
Render Note 2512
Control Consonance 2514
Lead Music Buffer 2516
Control
Consonance Metric
Filter
Music Output
Output Note
Note
Notes
Key
Chord
Key

FIG. 25



FIG. 26



FIG. 27A



FIG. 27B


2800
Mobile Device (Client Device)
2812
2813
2803
2804
2805
2811
Mobile Device (Client Device)
2809
Mobile Device (Client Device)
Wireless Network
2810
2801
Client Device
Wide Area Network/Local Area Network - (Network)
2802
Client Device
2806
2808
Music Network Device (MND)

FIG. 28


Memory 2904
RAM 2924
Music Compilation System
100
Operating System 2930
Other Apps 2938
Messenger 2934
Browser 2936
ROM 2926
BIOS 2928
2906
Power Supply 2908
Processor 2902
GPS 2924
Audio Interface 2912
User Input Handler 2916
Network Interface(s) 2910
Display Driver 2914
Illuminator 2918
Haptic Interface 2922
I/O Interface 2920

FIG. 29


3000
central processing unit
3012
3016
3022
3020
ram
operating system
cd-rom/
dvd-rom
drive
3026
3010
network
interface
unit
Data Stores
3052
input/output
interface
3024
Applications
3050
3056
Music Service
Music Matcher
3054
Rights Manager
3058
hard disk
drive
3028
Web Server
3057
video
display
adapter
3014
rom
3032
bios
3018

FIG. 30


3100
3102
3104
3106
3108
3110
3112
3114
3116
3118
3120
3122
3124
3126

FIG. 31


3102
3204
3202
3206
3208
3238
3220
3236
3234
3232
3230
3228
3226
3224
3222
3214
3210
3212
3216
3218

FIG. 32



FIG. 33



FIG. 34A



FIG. 34B



FIG. 34C


D
2
3
4
G
a
C
a

FIG. 35


3600
Intro
Verse
Chorus
3602
3604
3614
3606
3608
3610
3612

FIG. 36



FIG. 37A



FIG. 37B

SYSTEM AND METHOD FOR GENERATING MUSICAL TRACKS WITHIN A CONTINUOUSLY LOOPING RECORDING SESSION

[0001] This application claims priority from U.S. Provisional Patent Application No. 61/182,982, filed on Jun. 1, 2009; U.S. Provisional Patent Application No. 61/248,238, filed on Oct. 2, 2009; and U.S. Provisional Patent Application No. 61/266,472, filed on Dec. 3, 2009.

TECHNICAL FIELD

[0002] The present invention relates generally to the creation of music, and more particularly to a system and method for generating a musical compilation having a plurality of substantially harmonious tracks.

BACKGROUND

[0003] Music is a reputably well-known form of human self-expression. However, a person's firsthand appreciation for this artistic endeavor may be derived in different manners. Often, the person can more easily enjoy music by listening to the creations of others rather than generating it by himself or herself. For many people, the ability to hear and recognize an appealing musical composition is innate, while the ability to manually create a proper collection of notes remains out of reach. A person's ability to create new music may be inhibited by the time, money, and/or skill necessary to learn an instrument well-enough to accurately reproduce a tune at will. For most people, their own imaginations may be the source of new music, but their ability to hum or chant this same tune limits the extent to which their tunes can be formally retained and recreated for the enjoyment of others.

[0004] Recording a session musician's performance can also be a laborious process. Multiple takes of the same material are recorded and painstakingly scrutinized until a single take can be assembled with all of the imperfections ironed out. A good take often requires a talented artist under the direction of another to adjust his or her performance accordingly. In the case of an amateur recording, the best take is often the result of serendipity and consequently cannot be repeated. More often than not, amateur performers produce takes with both good and bad portions. The recording process would be much easier and more fun if a song could be constructed without having to meticulously analyze every portion of every take. Thus, it is with respect to these considerations and others that the present invention has been made.

[0005] Moreover, the music that a person desires to create may be complex. For example, an envisioned tune can have more than one instrument, which may be played concurrently with other instruments in a potential arrangement. This complexity further adds to the time, skill, and/or money required for a lone person to generate a desired combination of sounds. The physical configuration of most musical instruments also requires a person's full physical attention to manually generate notes, further requiring additional personnel to play the additional parts of a desired tune. Additionally, extra review and management may then be necessary to ensure proper interaction of the various involved instruments and elements of a desired tune.

[0006] Even for people who already enjoy creating their own music, those listeners may lack the type of expertise that enables proper composition and music creation. As a result, the music created may contain notes that are not within the same musical key or chord. In most musical styles, the presence of off-key or off-chord notes, often referred to as "inharmonious" notes, causes the music to be unpleasing and jarring. Accordingly, because of their lack of experience and training, music listeners often create music that sounds undesirable and unprofessional.

[0007] For some people, artistic inspiration is not bound by the same time and location limitations that are typically associated with the generation and recording of new music. For example, a person may not be in a production studio with a playable instrument at hand when an idea for a new tune materializes. After the moment of inspiration passes, the person may not be able to recall the complete extent of the original tune, resulting in a loss of artistic effort. Moreover, the person may become frustrated with the time and effort applied in recreating no more than an inferior and incomplete version of his or her initial musical revelation.

[0008] Professional music composing and editing software tools are currently generally available. However, these tools project an intimidating barrier to entry for a novice user. Such complex user interfaces can soon sap the enthusiasm of any beginner who dares venture their way on an artistic whim. Being tethered to a suite of pro-audio servers also cramps the style of the mobile creative, wanting to craft a tune on the move.

[0009] What is needed is a system and method of music creation that can easily interface with a user's most basic ability, yet enable the creation of music that is as complex as the user's imagination and expectations. There is also an associated need to facilitate the creation of music free from notes that are inharmonious. In addition, there is a need in the art for a music authoring system that can generate a musical compilation track by aggregating portions of multiple takes based on automated selection criteria. It is also desirable that such a system further be implemented in a manner that is not limited by the location of a user when inspiration occurs, thereby enabling capture of the first utterances of a new musical composition.

[0010] There is an associated need in the art for a system and method that can create a compilation track from multiple takes by automatically evaluating the quality of previously recorded tracks and selecting the best of the previously recorded tracks, recorded via an electronic authoring system.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Non-limiting and non-exhaustive embodiments are described in reference to the following drawings. In the drawings, like reference numerals refer to like parts through all the various figures unless otherwise specified.

[0012] For a better understanding of the present disclosure, a reference will be made to the following detailed description, which is to be read in association with the accompanying drawings, wherein:

[0013] FIGS. **1**A, **1**B, and **1**C illustrate several embodiments of a system in which aspects of the invention may be practiced;

[0014] FIG. **2** is a block diagram of one embodiment of potential components of the audio converter **140** of the system of FIG. **1**;

[0015] FIG. **3** illustrates one exemplary embodiment of a progression for a musical compilation;

[0016] FIG. **4** is a block diagram of one embodiment of potential components of the track partitioner **204** of the system of FIG. **2**;

[0017] FIG. **5** is an exemplary frequency spectrum diagram illustrating the frequency distribution of an audio input having a fundamental frequency and multiple harmonics;

[0018] FIG. **6** is an exemplary pitch versus time plot illustrating the pitch of a human voice changing between first and second pitches and subsequently settling around the second pitch;

[0019] FIG. **7** is an exemplary embodiment of a morphology plotted as pitch events over time, each having a discrete duration;

[0020] FIG. **8** is a block diagram illustrating the content of a data file in one embodiment of the invention;

[0021] FIG. **9** is a flow chart illustrating one embodiment of a method for generating musical tracks within a continuously looping recording session;

[0022] FIGS. **10**, **10**A and **10**B together form an illustration of one potential user interface for generating musical tracks within a continuously looping recording session;

[0023] FIG. **11** is an illustration of one potential user interface for calibrating a recording session;

[0024] FIGS. **12**A, **12**B, and **12**C together illustrate a second potential user interface associated with the generation of musical tracks within a continuously looping recording session at three separate periods of time;

[0025] FIGS. **13**A, **13**B, and **13**C together illustrate one potential use of the user interface to modify a musical track input into the system using the user interface of FIG. **12**;

[0026] FIGS. **14**A, **14**B and **14**C together illustrate one potential user interface for creating a rhythm track at three separate periods of time;

[0027] FIG. **15** is a block diagram of one embodiment of potential components of the MTAC module **144** of the system of FIG. **1**;

[0028] FIG. **16** is a flow diagram illustrating one potential process for determining the musical key reflected by one or more notes of audio input;

[0029] FIGS. **17**, **17**A, and **17**B together form a flow diagram illustrating one potential process for scoring a portion of a musical track based on a chord sequence constraint;

[0030] FIG. **18** illustrates one embodiment of a process for determining the centroid of a morphology;

[0031] FIG. **19** illustrates step-responses of a harmonic oscillator over time having a damped response, an over-damped response, and an under-damped response;

[0032] FIG. **20** illustrates a logical flow diagram showing one embodiment for scoring a portion of a musical input;

[0033] FIG. **21** illustrates a logical flow diagram for one embodiment of a process for composing a "best" track from multiple recorded tracks;

[0034] FIG. **22** illustrates one embodiment of an exemplary audio waveform and a graphical representation of a score showing the variance of the actual pitch from an ideal pitch;

[0035] FIG. **23** illustrates one embodiment of a new track constructed from partitions of previously recorded tracks;

[0036] FIG. **24** illustrates a data flow diagram showing one embodiment of a process for harmonizing an accompaniment musical input with a lead musical input;

[0037] FIG. **25** illustrates a data flow diagram of the processes performed by the Transform Note Module of FIG. **24**;

[0038] FIG. **26** illustrates one exemplary embodiment of a super keyboard;

[0039] FIGS. **27**A-B illustrate two exemplary embodiments of a chord wheel;

[0040] FIG. **28** illustrates one exemplary embodiment of a network configuration in which the present invention may be practiced;

[0041] FIG. **29** illustrates a block diagram of a device that supports the processes discussed herein;

[0042] FIG. **30** illustrates one embodiment of a music network device;

[0043] FIG. **31** illustrates one potential embodiment of a first interface in a game environment;

[0044] FIG. **32** illustrates one potential embodiment of an interface for creating one or more lead vocal or instrument tracks in the game environment of FIG. **31**;

[0045] FIG. **33** illustrates one potential embodiment of an interface for creating one or more percussion tracks in the game environment of FIG. **31**;

[0046] FIGS. **34**A-C illustrate potential embodiments of an interface for creating one or more accompaniment tracks in the game environment of FIG. **31**;

[0047] FIG. **35** illustrates one potential embodiment of a graphical interface that depicts the chord progression playing as accompaniment of the lead music; and

[0048] FIG. **36** illustrates one potential embodiment for selecting among different sections of a musical compilation in the game environment of FIG. **31**

[0049] FIGS. **37**A and **37**B illustrate potential embodiments of a files structure associated with musical assets that may be utilized in conjunction with the game environment of FIGS. **31**-**36**.

DETAILED DESCRIPTION

[0050] The present invention now will be described more fully hereinafter with reference to the accompanying drawings, which form a part hereof, and which show, by way of illustration, specific exemplary embodiments by which the invention may be practiced. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Among other things, the present invention may be embodied as methods or devices. Accordingly, the present invention may take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment combining software and hardware aspects. The following detailed description is, therefore, not to be taken in a limiting sense.

DEFINITIONS

[0051] Throughout the specification and claims, the following terms take the meanings explicitly associated herein, unless the context clearly dictates otherwise. The phrase "in one embodiment" as used herein does not necessarily refer to the same embodiment, although it may. Furthermore, the phrase "in another embodiment" as used herein does not necessarily refer to a different embodiment, although it may. Thus, as described below, various embodiments of the invention may be readily combined, without departing from the scope or spirit of the invention.

[0052] In addition, as used herein, the term "or" is an inclusive "or" operator, and is equivalent to the term "and/or," unless the context clearly dictates otherwise. The term "based

on" is not exclusive and allows for being based on additional factors not, described, unless the context clearly dictates otherwise. In addition, throughout the specification, the meaning of "a," "an," and "the" include plural references. The meaning of "in" includes "in" and includes plural references. The meaning of "in" includes "in" and "on."

[0053] As used herein the term "musical input," refers to any signal input that contains musical and/or control information transmitted over any of a variety of mediums, including, but not limited to air, microphones, line-in mechanisms, or the like. Musical inputs are not limited to signal input frequencies which might be heard by a human ear, and may include other frequencies outside of that which may be heard by the human ear, or in a form not readily heard by the human ear. Moreover, the use of the term "musical" is not intended to convey an inherent requirement for a beat, rhythm, or the like. Thus, for example, a musical input, may include various inputs such as a tapping, including a single tap, clicking, human inputs (such as voice (e.g do, re, mi), percussive inputs (e.g. ka, cha, da-da), or the like) as well as indirect inputs through an instrument or other amplitude and/or frequency generation mechanism via a transport including, but not limited to, a microphone input, a Line-In input, a MIDI input, a file having signal information useable to convey a musical input, or other inputs that enable a transported signal to be converted into music.

[0054] As used herein, the term "musical key" is a group of musical notes that are harmonious. Keys are usually major or minor. Musicians frequently speak of a musical composition as being "in the key of" C major, for instance, which implies a piece of music harmonically centered on the note C and making use of a major scale whose first note, or tonic, is C. A major scale is an eight note progression consisting of the perfect and major semitones (e.g. C D E F G A B or do re mi fa so la ti). With respect to a piano, for instance, middle-C (sometimes called "C4") has a frequency of 261.626 Hz, while D4 is 293.665 Hz; E4 is 329.628 Hz; F4 is 349.228 Hz; G4 is 391.995 Hz; A4 is 440.000 Hz; and B4 is 493.883 Hz. While the same notes on other musical instruments will play at the same frequencies, it is also understood that some instruments naturally play in one key or another.

[0055] As used herein, the term "inharmonious note" is a note that is not in a correct musical key or chord, where the correct musical key and the correct chord are the musical key or chord currently being played by another musician or musical source.

[0056] As used herein, the term "blue note" is a note that is not in a correct musical key or chord, but which is allowed to be played without transformation.

[0057] As used herein, the term "note of accompaniment musical input" is a note played by an accompanying musician that is associated with a note played in a corresponding lead melody.

GENERAL DESCRIPTION OF THE INVENTION

[0058] The following briefly describes various embodiments in order to provide a basic understanding of some aspects of the invention. This brief description is not intended as an extensive overview. It is not intended to identify key or critical elements, or to delineate or otherwise narrow the scope. Its purpose is merely to present some concepts in a simplified form as a prelude to the more detailed description that is presented later.

[0059] Briefly stated, various embodiments are directed toward generating a multi-track recording by looping through a set of previously recorded audio tracks and receiving a new audible input for each added audio track. In one embodiment, each of the audio tracks in the multi-track recording may be generated from an audible vocal input from an end-user. Each new audible input may be provided after the current recording is repeatedly played back, or looped, one or more times. This recording sequence, separated by loop periods during which no new track input is received may permit a user to listen to the current recording thoroughly, continuously, and without a time-related pressure of an immediately required additional input. The looped playback, independent from a loop in which an additional track is input, may also permit other actions to be performed, such as modifying a previous track or changing parameters of the recording system.

[0060] Further, at least one of the audio tracks in the multi-track recording may comprise one or more musical instrument sounds generated based on one or more different sounds provided in the audible input. Various forms of processing may be performed on the received audible input to create the audio track, including aligning and adjusting of the timing of the audible input, frequency recognition and adjustment, converting the audible input to a timbre associated with a musical instrument, adding known aural cues associated with the musical instrument, and the like. Further, each of these processes may be performed in real-time, permitting almost instantaneous playback of a generated audio track and enabling another audible input to be immediately and subsequently received for processing and overlay as an audio track onto one or more previously recorded tracks in a multi-track recording.

[0061] In one embodiment, the looped or repeated portion of the multi-track recording may comprise a single bar of music. The length of this bar may be determined by a tempo and a time signature associated with the track. In another embodiment, the number of bars, or looping point for playback of the multi-track recording, may be dynamic. That is, the repetition of a first audio track in the multi-track recording may occur at a different time than that of a second audio track in the multi-track recording. The adjustment of this dynamic looping point, for example, may be automatically determined based on the length of an audible input for subsequent tracks.

[0062] Various embodiments are also directed toward automatically producing a single, "best" take that is derived from a collection of takes. In one embodiment, multiple takes of a performance are recorded during one or more sessions onto a multi-track recorder. Each take is automatically partitioned into segments. The quality of each partition of each of the multiple takes is scored, based on selectable criteria, and a track is automatically constructed from the best quality segments of each take. In one embodiment, a best segment is defined by the segment having a highest score from within a plurality of segment scores.

[0063] Various embodiments are also further directed toward protecting a musician from playing an inharmonious note. In one embodiment, the notes of an accompaniment musical instrument are received as well as from a lead musical instrument. The notes from the accompaniment musical instrument are then modified based on the key, chord, and/or timing of the lead. In one embodiment, a virtual instrument, where the input keys of the instrument dynamically map onto safe notes, may be provided. Thus, if a player of the virtual instrument is accompanying a melody, the virtual instrument

may identify safe notes that comprise notes that are either for the current chord of the melody being accompanied or in the musical key of the melody.

[0064] Device Architecture

[0065] FIG. **1**A shows one embodiment of system **100** that may be deployed on a variety of devices **50**, which may be, for illustrative purposes, any multi-purpose computer, hand-held computing device (FIG. **1**B) and/or dedicated gaming system (FIG. **1**C). Device **50** may include many more or less components than those shown in FIG. **29**. However, it should be understood by those of ordinary skill in the art that certain components are not necessary to operate system **100**, while others, such as processor, microphone, video display, and audio speaker are important, if not necessary to practice aspects of the present invention.

[0066] As shown in FIG. **29**, device **50** includes a processor **2902**, which may be a CPU, in communication with a mass memory **2904** via a bus **2906**. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, processor **2902** could also comprise one or more general processors, digital signal processors, other specialized processors and/or ASICs, alone or in combination with one another. Device **50** also includes a power supply **2908**, one or more network interfaces **2910**, an audio interface **2912**, a display driver **2914**, a user input handler **2916**, an illuminator **2918**, an input/output interface **2920**, an optional haptic interface **2922**, and an optional global positioning systems (GPS) receiver **2924**. Device **50** may also include a camera (not shown), enabling video to be acquired and/or associated with a particular multi-track recording. Video from the camera, or other source, may also further be provided to an online social network and/or an online music community. Device **50** may also optionally communicate with a base station (not shown), or directly with another computing device. Other computing device, such as the base station, may include additional audio-related components, such as a professional audio processor, generator, amplifier, speaker, XLR connectors and/or power supply.

[0067] Continuing with FIG. **29**, power supply **2908** may comprise a rechargeable or non-rechargeable battery or may be provided by an external power source, such as an AC adapter or a powered docking cradle that could also supplement and/or recharge the battery. Network interface **2910** includes circuitry for coupling device **50** to one or more networks, and is constructed for use with one or more communication protocols and technologies including, but not limited to, global system for mobile communication (GSM), code division multiple access (CDMA), time division multiple access (TDMA), user datagram protocol (UDP), transmission control protocol/Internet protocol (TCP/IP), SMS, general packet radio service (GPRS), WAP, ultra wide band (UWB), IEEE 802.16 Worldwide Interoperability for Microwave Access (WiMax), SIP/RTP, or any of a variety of other wireless communication protocols. Accordingly, network interface **2910** may include as a transceiver, transceiving device, or network interface card (NIC).

[0068] Audio interface **2912** (FIG. **29**) is arranged to produce and receive audio signals such as the sound of a human voice. For example, as shown most clearly in FIGS. **1**A and **1**B, audio interface **2912** may be coupled to a speaker **51** and/or microphone **52** to enable music output and input into the system **100**. Display driver **2914** (FIG. **29**) is arranged to produce video signals to drive various types of displays. For example, display driver **2914** may drive video monitor display **75**, shown in FIG. **1**A, which may be a liquid crystal, gas plasma, or light emitting diode (LED) based-display, or any other type of display that may be used with a computing device. As shown in FIG. **1**B, display driver **2914** may alternatively drive a hand-held, touch sensitive screen **80**, which would also be arranged to receive input from an object such as a stylus or a digit from a human hand via user input handler **2916** (see FIG. **31**). Keypad **55** may comprise any input device (e.g. keyboard, game controller, track-ball and/or mouse) arranged to receive input from a user. For example, keypad **55** may include one or more push buttons, numeric dials, and/or keys. Keypad **55** may also include command buttons that are associated with selecting and sending images.

[0069] Device **50** also comprises input/output interface **2920** for communicating with external devices, such as a headset, a speaker **51**, or other input or output devices. Input/output interface **2920** may utilize one or more communication technologies, such as USB, infrared, Bluetooth™, or the like. The optional haptic interface **2922** is arranged to provide tactile feedback to a user of device **50**. For example, in an embodiment, such as that shown in FIG. **1**B, where the device **50** is a mobile or handheld device, the optional haptic interface **2922** may be employed to vibrate the device in a particular way such as, for example, when another user of a computing device is calling.

[0070] Optional GPS transceiver **2924** may determine the physical coordinates of device **100** on the surface of the Earth, which typically outputs a location as latitude and longitude values. GPS transceiver **2924** can also employ other geo-positioning mechanisms, including, but not limited to, triangulation, assisted GPS (AGPS), E-OTD, CI, SAI, ETA, BSS or the like, to further determine the physical location of device **50** on the surface of the Earth. In one embodiment, however, mobile device may, through other components, provide other information that may be employed to determine a physical location of the device, including for example, a MAC address, IP address, or the like.

[0071] As shown in FIG. **29**, mass memory **2904** includes a RAM **2924**, a ROM **2926**, and other storage means. Mass memory **2904** illustrates an example of computer readable storage media for storage of information such as computer readable instructions, data structures, program modules, or other data. Mass memory **2904** stores a basic input/output system ("BIOS") **2928** for controlling low-level operation of device **50**. The mass memory also stores an operating system **2930** for controlling the operation of device **50**. It will be appreciated that this component may include a general purpose operating system such as a version of MAC OS, WINDOWS, UNIX, or LINUX, or a specialized operating system such as, for example, Xbox 360 system software, Wii IOS, Windows Mobile™, or the Symbian® operating systems. The operating system may include, or interface with, a Java virtual machine module that enables control of hardware components and/or operating system operations via Java application programs.

[0072] One or more data storage modules **132** may be stored in memory **2904** of device **50**. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, a portion of the information stored in data storage modules **132** may also be stored on a disk drive or other storage medium associated with device **50**. These data storage modules **132** may store multiple track recordings, MIDI files, WAV files, samples of audio data, and a variety of other data and/or data formats or

input melody data in any of the formats discussed above. Data storage modules **132** may also store information that describes various capabilities of system **100**, which may be sent to other devices, for instance as part of a header during a communication, upon request or in response to certain events, or the like. Moreover, data storage modules **132** may also be employed to store social networking information including address books, buddy lists, aliases, user profile information, or the like.

[0073] Device **50** may store and selectively execute a number of different applications, including applications for use in accordance with system **100**. For example, application for use in accordance with system **100** may include Audio Converter Module **140**, Recording Session Live Looping (RSLL) Module **142**, Multiple Take Auto-Compositor (MTAC) Module **144**, Harmonizer Module **146**, Track Sharer Module **148**, Sound Searcher Module **150**, Genre Matcher Module **152**, and Chord Matcher Module **154**. The functions of these applications are described in more detail below.

[0074] The applications on device **50** may also include a messenger **134** and browser **136**. Messenger **132** may be configured to initiate and manage a messaging session using any of a variety of messaging communications including, but not limited to email, Short Message Service (SMS), Instant Message (IM), Multimedia Message Service (MMS), Internet relay chat (IRC), mIRC, RSS feeds, and/or the like. For example, in one embodiment, messenger **243** may be configured as an IM messaging application, such as AOL Instant Messenger, Yahoo! Messenger, .NET Messenger Server, ICQ, or the like. In another embodiment, messenger **132** may be a client application that is configured to integrate and employ a variety of messaging protocols. In one embodiment, messenger **132** may interact with browser **134** for managing messages. Browser **134** may include virtually any application configured to receive and display graphics, text, multimedia, and the like, employing virtually any web based language. In one embodiment, the browser application is enabled to employ Handheld Device Markup Language (HDML), Wireless Markup Language (WML), WMLScript, JavaScript, Standard Generalized Markup Language (SMGL), HyperText Markup Language (HTML), eXtensible Markup Language (XML), and the like, to display and send a message. However, any of a variety of other web-based languages may be employed.

[0075] Device **50** may also include other applications **138**, such as computer executable instructions which, when executed by client device **100**, transmit, receive, and/or otherwise process messages (e.g., SMS, MMS, IM, email, and/or other messages), audio, video, and enable telecommunication with another user of another client device. Other examples of application programs include calendars, search programs, email clients, IM applications, SMS applications, VoIP applications, contact managers, task managers, transcoders, database programs, word processing programs, security applications, spreadsheet programs, games, search programs, and so forth. Each of the applications described above may be embedded or, alternately, downloaded and executed on device **50**.

[0076] Of course, while the various applications discussed above are shown as being implemented on device **50**, in alternate embodiments, one or more portions of each of these applications may be implemented on one or more remote devices or servers, wherein inputs and outputs of each portion are passed between device **50** and the one or more remote devices or servers over one or more networks. Alternately, one or more of the applications may be packaged for execution on, or downloaded from a peripheral device.

[0077] Audio Converter

[0078] Audio converter **140** is configured to receive audio data and convert it to a more meaningful form for use within system **100**. One embodiment of audio converter **140** is illustrated in FIG. **2**. In this embodiment, audio converter **140** may include a variety of sub-systems including track recorder **202**, track partitioner **204**, quantizer **206**, frequency detector **208**, frequency shifter **210**, instrument converter **212**, gain control **214**, harmonics generator **216**, special effects editor **218**, and manual adjustment control **220**. The connections to and interconnections between the various sub-systems of audio converter **140** are not shown to avoid obscuring the present invention, however, these sub-systems would be electrically and/or logically connected as would be understood by those of ordinary skill in the art having the present specification, drawings, and claims before them.

[0079] Track recorder **202** enables a user to record at least one audio track from either vocal or a musical instrument. In one embodiment, the user may record the track without any accompaniment. However, track recorder **202** may also be configured to play audio, either automatically or upon a user's request, comprising a click track, a musical accompaniment, an initial tone against which a user can judge his/her pitch and timing, or even previously recorded audio. "Click track" refers to a periodic clicking noise (such as the periodic clicking noise made by a mechanical metronome) intended to assist the user to keep a consistent tempo. Track recorder **202** may also enable a user to set the length of time to record—as either a time limit (i.e. a number of minutes and seconds) or a number of musical bars. When used in conjunction with MTAC module **144**, as discussed below, track recorder **202** may also be configured to graphically indicate a score associated with various portions of a recorded track, so as to indicate, for instance, when a user is off-key, or the like.

[0080] In general, a musical compilation is comprised of multiple lyrical sections. For example, FIG. **3** illustrates a one typical progression for a pop song that begins with an intro section, followed by alternating verse and chorus sections, and a bridge section prior to the final verse. Of course, although not shown, other structures such as refrains, outros, and the like, may also be used. Thus, in one embodiment, track recorder **202** may also be configured to enable a user to select the section of a song for which the recorded audio track is to be used. These sections may then be arranged in any order (either automatically (based on a determination by the genre matcher module **152**) or as selected by the end user) to create a complete musical compilation.

[0081] Track partitioner **204** divides a recorded audio track into separate partitions that may then be addressed and potentially stored as individually addressable separate sound clips or files. The partitions are preferably chosen so that segments spliced end-to-end result in few or no audio artifacts. For example, let us assume that an audible input comprises the phrase "pum pa pum". In one embodiment, division of this audible input may identify and distinguish each syllable of this audible input into separate sounds, such as "pum," "pa," and "pum." However, it should be understood that this phrase can be delineated in other ways, and a single partition may include more than one syllable or word. Four partitions (numbered "1," "2," "3," and "4") each including more than one syllable are illustrated on display **75** in FIGS. **1**A, **1**B and **1**C.

As illustrated, partition "1" has a plurality of notes that may reflect the same plurality of syllables having been recorded by track recorder **202** using input from microphone **52** from a human or musical instrument source.

[0082] To perform the division of an audible track into separate partitions track partitioner **204** may utilize one or more processes running on the processor **2902**. In one exemplary embodiment illustrated in FIG. **4**, track partitioner **204** may include silence detector **402**, stop detector **404**, and/or manual partitioner **406**, each of which may be used to partition an audio track into N partitions aligned in time. Track partitioner **204** may use silence detector **302** to partition a track wherever silence is detected for a certain period of time. That "silence" may be defined by a volume threshold, such that when the audio volume dips below the defined threshold for a defined period of time, the location in the track is deemed silent. Both the volume threshold and the period of time may be configurable.

[0083] Stop detector **404**, on the other hand, may be configured to use speech analysis, such as formant analysis, to identify vowels and consonants in the track. For example, consonants such as T, D, P, B, G, K, and nasals are delimited by stoppages of airflow in their vocalization. The location of certain vowels or consonants may then be used to detect and identify preferably partitioning points. Similar to silence detector **402**, the types of vowels and consonants utilized by stop detector **404** for identifying partitioning points may be configurable. Manual partitioner **406** may also be provided to enable a user to manually delimit each partition. For example, a user may simply specify a time length for each partition causing the audio track to be divided into numerous partitions each of equal length. The user may also be permitted to identify a specific location in the audio track at which a partition is to be created. The identification may be performed graphically using a pointing device, such as a mouse or game controller, in conjunction with the type of graphical user interface illustrated in FIGS. **1**A, **1**B, and **1**C. The identification may also be performed by pressing a button or key on user input device, such as keyboard **55**, mouse **54** or game controller **56** during audible playback of the audio track by track recorder **202**.

[0084] Of course, although the functions of silence detector **402**, stop detector **304**, and manual partitioner **406** have been described individually, it is contemplated that track partitioner **204** may use any combination of the silence detector, stop detector, and/or manual partitioner to partition or divide an audio track into segments. It would also be understood by those of ordinary skill in the art having the present specification, drawings and claims before them that other techniques to partition or divide an audio track into segments may also be used.

[0085] Quantizer **206** is configured to quantize partitions of a received audio track, which may utilize one or more processes running on the processor **2902**. The process of quantization, as the term is used herein, refers to the time shifting of each previously created partition (and consequently the notes contained within the partition), as may be necessary in order to align the sounds within the partitions with a certain beat. Preferably, quantizer **206** is configured to align the beginning of each partition chronologically with a previously determined beat. For example, a meter may be provided where each bar may comprise four beats and alignment of a separate sound may occur relative to quarter-beat increments of time, thus providing sixteen time points in each four-beat bar to which a partition may be aligned. Of course, any number of increments for each bar (such as three beats for a waltz or polka effect, two beats for a swing effect, etc.) and beat may be used and, at any time during process, may be adjusted either manually by a user or automatically based on certain criteria such as a user selection of a certain style or genre of music (e.g. blues, jazz, polka, pop, rock, swing, or waltz).

[0086] In one embodiment, each partition may be automatically aligned by quantizer **206** with an available time increment to which it was most closely received at the time of recording. That is, if a sound begins between two time increments in the beat, then the playback timing of the sound will be shifted chronologically forward or backward to either one of these increments to which its initial starting time is closer. Alternately, each sound may be automatically shifted in time to each time increment that immediately precedes the relative time in which the sound was initially recorded. In yet another embodiment, each sound may be automatically shifted in time to each time increment that immediately follows the relative time in which the sound was initially recorded. A time shift, if any, for each separate sound may also be alternately or additionally influenced based on a genre selected for the multi-track recording, as further discussed below with regards to genre matcher **152**. In another embodiment, each sound may also be automatically time aligned with a previously recorded track in a multi-track recording, enabling a karaoke-type effect. Moreover, the length of a separate sound may be greater than one or more time increments and time shifting of quantizer **206** may be controlled to prevent separate sounds from being time shifted so that they overlap within the same audio track.

[0087] Frequency detector **208** is configured to detect and identify the pitches of the one or more separate sounds that may be contained within each partition, which may utilize one or more processes running on the processor **2902**. In one embodiment, a pitch may be determined by converting each separate sound to a frequency spectrum. Preferably, this is accomplished by using a Fast Fourier transform (FFT) algorithm, such as the FFT implementation by iZotope. However, it should be understood that any FFT implementation may be used. It is also contemplated that a Discrete Fourier Transform (DFT) algorithm may also be used to obtain the frequency spectrum.

[0088] For illustration, FIG. **5** depicts one example of a frequency spectrum that may be produced by the output of a FFT process performed on a portion of a received audio track. As can be seen, the frequency spectrum **400** includes one major peak at a single fundamental frequency (F) **502** that corresponds to the pitch, in addition to harmonics that are excited at 2F, 3F, 4F . . . nF. The additional harmonics are present in the spectrum because, when an oscillator such as the vocal cord or a violin string is excited at a single pitch, it typically vibrates at multiple frequencies.

[0089] In some instances, the identification of a pitch may be complicated due to additional noise. For example, as shown in FIG. **5**, the frequency spectrum may include noise that occurs as a result of the audio input being from a real world oscillator such as a voice or instrument, and appears as low amplitude spikes spread across the spectrum. In one embodiment, this noise may be extracted by filtering the FFT output below a certain noise threshold. Identification of the pitch may also be complicated in some instances by the presence of vibrato. Vibrato is a deliberate frequency modulation

that may be applied to a performance, and is typically between 5.5 Hz and 7.5 Hz. Like with noise, vibrato may be filtered out of the FFT output by applying a band-pass filter in the frequency domain, but filtering the vibrato may be undesirable in many situations.

[0090] In addition to the frequency domain approaches discussed above, it is contemplated that the pitch of one or more sounds in a partition could also be determined using one or more time-domain approaches. For example, in one embodiment, the pitch may be determined by measuring the distance between zero crossing points of the signal. Algorithms such as AMDF (average magnitude difference function), ASMDF (Average Squared Mean Difference Function), and other similar autocorrelation algorithms may also be used.

[0091] For judgments in pitch to be most effective, the pitched content may also be grouped into notes (of constant frequency) and glisses (of steadily increasing or decreasing frequency). However—unlike instruments with frets or keys that naturally produce steady, discrete pitches—the human voice tends to slide into notes and wavers in a continuous fashion, making conversion to discrete pitches difficult. Consequently, frequency detector **208** may also preferably utilize pitch impulse detection to identify shifts or changes in pitch between separate sounds within a partition.

[0092] Pitch impulse detection is one approach of delimiting pitch events that focuses on the ballistics of the control loop formed between the singer's voice and his perception of his voice. Generally, when a singer utters a sound, the singer hears that sound a moment later. If the singer hears that the pitch is incorrect, he immediately modifies his voice toward the intended pitch. This negative feedback loop may be modeled as damped harmonic motion driven by periodic impulses. Thus, a human voice may be considered as a single oscillator: the vocal cord. One example illustration of a pitch changing and settling for a singer's voice **602** can be seen in FIG. **6**. The tension in the vocal cord controls the pitch, and this change in pitch may be modeled by the response to a step function, such as step function **604** in FIG. **6**. Thus, the start of the new pitch event may be determined by finding the start of the damped harmonic oscillation in pitch; and observing the successive turning points of the pitch converging to a steady value.

[0093] After the pitch events within a partition of an audio track have been determined, they may be converted and/or stored into a morphology, which is a plot of pitch events over time. One example of a morphology (without partitioning) is depicted in FIG. **7**. The morphology may therefore include information identifying the onset, duration, and pitch of each sound, or any combination or subset of these values. In one embodiment, the morphology may be in the form of MIDI data, although a morphology may refer to any representation of pitch over time, and is not limited to semitones or any particular meter. For instance, other such examples of morphologies that may be used are described in "Morphological Metrics" by Larry Polansky, *Journal of New Music Research*, volume 25, pp. 289-368, ISSN: 09929-8215, which is incorporated herein by reference.

[0094] Frequency shifter **210** may be configured to shift the frequency of the audible input, which may utilize one or more processes running on the processor **2902**. For example, the frequency of one or more sounds within a partition of an audible input may be automatically raised or lowered in order to align with fundamental frequency of audible inputs or separate sounds that have been previously recorded. In one embodiment, the determination of whether to raise or lower the frequency of the audible input depends upon the closest fundamental frequency. In other words, assuming the composition was in the key of C major, if the audible frequency captured by track recorder **202** is 270.000 Hz frequency shifter **210** would shift the note down to 261.626 Hz (middle-C), whereas if the audible frequency captured by the track recorder **202** is 280.000 Hz frequency shifter **210** would shift the note up 293.665 Hz (or the D above middle-C). Even when the frequency shifter **210** primarily adjusts audible input to the closest fundamental frequency, the shifter **210** may also be further programmed to make different decisions on close calls (i.e. where the audible frequency is approximately half-way between two notes) based on the musical key, genre and/or chord. In one embodiment, the frequency shifter **210** may adjust audible inputs to other fundamental frequencies that make more musical sense based on the musical key, genre and/or chord based on controls provided by the genre matcher **260** and/or chord matcher **270**, as further discussed below. Alternately or additionally the frequency shifter **210**—in response to input from the instrument converter **212**—may also individually shift one or more portions of one or more partitions to correspond with a predetermined set of frequencies or semitones such as those typically associated with a selected musical instrument, such as a piano, guitar or other stringed instrument, woodwind, or brass.

[0095] Instrument converter **212** may be configured to perform conversion of one or more portions of the audible input into one or more sounds that have a timbre associated with a musical instrument. For example, one or more sounds in an audible input may be converted into one or more instrument sounds of one or more different types of percussion instruments, including a snare drum, cowbell, bass drum, triangle, and the like. In one embodiment, the conversion of an audible input into one or more corresponding percussion instrument sounds may comprise adapting the timing and amplitude of one or more sounds in the audible input into a corresponding track comprising one or more sounds of the percussion instrument, the percussion instrument sound comprising a same or similar timing and amplitude as the one or more audible input sounds. For other instruments enabled to play different notes, such as a trombone or other types of brass, string, woodwind instrument or the like, the instrument conversion may further correlate one or more frequencies of audible input sounds with one or more sounds with the same or similar frequencies played by the instrument. Further, each conversion may be derived and/or limited by the physical capabilities of actually playing the corresponding physical instrument. For example, the frequencies of instrument sounds generated for an alto saxophone track may be limited by the actual frequency range of a traditional alto saxophone. In one embodiment, the generated audio track may comprise a MIDI formatted representation of the converted audible input. The data for the various instruments used by instrument converter **212** would preferably be stored in memory **2904** and may be downloaded from optical or magnetic media, removable memory, or via the network.

[0096] Gain control **214** may be configured to automatically adjust the relative volume of the audible input based on the volume of other, previously recorded tracks and may utilize one or more processes running on the processor **2902**. Harmonics generator **216**, may be configured to incorporate harmonics into the audio track, which may utilize one or more processes running on the processor **2902**. For example, dif-

ferent, additional frequencies of the audible input signal may be determined and added to the generated audio track. Determining the additional frequencies may be also based on a genre from genre matcher **260** or through the use of other, predetermined parameter settings input by a user. For instance, if the selected genre were a waltz the additional frequencies may be selected from major chords harmonious to the lead music in the octave immediately below the lead, in ¾ time with an "oom-pa-pa" beat, as follows:

5 5 5 5
root 3 3, root 3 3.

Special effects editor **218** may be configured to add various effects to the audio track, such as an echo, reverberation, and the like preferably utilizing one or more processes running on the processor **2902**.

[0097] Audio Converter **140** may also include a manual adjustment control **220** to enable a user to manually alter any of the settings automatically configured by the modules discussed above. For instance, manual adjustment control **220** may enable a user to alter the frequency of an audio input, or portions thereof; enable a user to alter the onset and duration of each separate sound; increase or decrease the gain for an audio track; select a different instrument to be applied to instrument converter **212**, among other options. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, this manual adjustment control **220** may be designed for use with one or more graphical user interfaces. One particular graphical user interface will be discussed below in association with FIGS. **13**A, **13**B, and **13**C below.

[0098] FIG. **8** illustrates one embodiment of a file structure for a partition of an audio track that has been processed by audio converter **140**, or otherwise downloaded, ingested, or obtained from another source. As shown, in this embodiment, the file includes metadata associated with the file, the obtained morphology data (e.g. in MIDI format), and the raw audio (e.g. in .wav format). The metadata may include information indicating a profile associated with the creator or supplier of the audio track partition. It may also include additional information regarding the audio signature of the data, such as a key, tempo, and partitions associated with the audio. The metadata may also include information regarding the potential available pitch shifts that can be applied to each note in the partition, the amount of time shifting that can be applied to each note, and the like. For example, it is understood that, for live recorded audio, there is a possibility of distortion if a pitch is shifted by more than a semitone. Accordingly, in one embodiment, a constraint may be placed on live audio to prevent shifting more than one semitone. Of course, different settings and different constraints may also be used. In another embodiment, ranges for potential pitch shifting, time shifting, etc. may also be altered or established by a creator of an audio track partition, or any individual with substantial rights in that audio track partition, such as an administrator, a collaborating party, and the like.

[0099] Recording Session Live Looping

[0100] Recording Session Live Looping (RSLL) Module **142** implements a digital audio workstation that, in conjunction with audio converter **140**, enables recording of audible input, generation of separate audio tracks, and the creation of multi-track recordings. Thus, RSLL Module **142** may enable any recorded audio tracks, either spoken, chanted, or otherwise, to be combined with previously recorded tracks to create a multi-track recording. As further discussed below, RSLL Module **142** is also preferably configured to loop at least one bar of a previously recorded multi-track recording for repeated playback. This repeated playback may be executed while new audible inputs are being recorded or the RSLL Module **142** is otherwise receiving instructions for a recording session currently being conducted. As a result, RSLL module **142** allows a user to continue editing and composing musical tracks while playing and listening to previously recorded tracks. As will be understood from the discussion below, the continuous looping of previously recorded tracks also minimizes the user's perception of any latency that may result from the processes that are applied to an audio track that is being currently recorded by the user, as such processes are preferably completed.

[0101] FIG. **9** illustrates a logical flow diagram generally showing one embodiment of an overview process for creating a multi-track recording using RSLL Module **142** in conjunction with audio converter **140**. Overall, the operations of FIG. **9** generally represent a recording session. Such a session may be newly created and completed each time a user employs system **100**, and, for example, RSLL Module **142**. Alternately, a previous session may be continued and certain elements thereof, such as a previously recorded multi-track recording or other user-specified recording parameters, may also be loaded and applied.

[0102] In either arrangement, process **900** begins, after a start block, at decision block **910**, where a user determines whether a currently recorded multi-track recording is to be played back. The process of playing back the current multi-track recording, while enabling other actions to be performed, is generally referred to herein as "live looping." The content and duration of a portion of the multi-track recording currently being played back, without explicit repetition, is referred to as a "live loop." During playback, the multi-track recording may be accompanied by a click track, which generally comprises a separate audio track, not stored with the multi-track recording, that provides a series of equally spaced reference sounds or clicks that audibly indicate a speed and measure for a track for which the system is currently configured to record.

[0103] In an initial execution of process **900**, an audio track may not yet have been generated. In such a state, playback of the empty multi-track recording in block **910** may be simulated and the click track may provide the only sounds played back to a user. However, in one embodiment, a user may select to mute the click track, as further discussed below with respect to block **964**. Visual cues may be provided to the user during recording in conjunction with audio playback. Even when an audio track has not been recorded, and the click track is muted, indication of simulated playback and current playback position may be limited solely to those visual cues, which may include, for example, a changing display of a progress bar, pointer, or some other graphical indication (see, e.g., FIGS. **12**A, **12**B, and **12**C).

[0104] The live looped multi-track recording played back in decision block **910** may comprise one or more audio tracks that have been previously recorded. The multi-track recording may include an overall length as well as a length which is played back as a live loop. The length of a live loop may be selected to be less than the overall length of a multi-track recording, permitting a user to separately layer different bars

of the multi-track recording. The length of a live loop, relative to the overall length of a multi-track recording, may be manually selected by a user or, alternately, automatically determined based on received audible input. In at least one embodiment, the overall length of the multi-track recording and the live loop may be the same. For example, the length of the live loop and the multi-track recording may be a single bar of music.

[0105] When the multi-track recording is selected for playback at decision block **910**, additional visual cues, such as a visual representation of the one or more tracks, may be provided in synch with the audio playback of a live loop comprising at least a portion of the multi-track recording played back for the user. While the multi-track recording is played, process **900** continues at decision block **920** where a determination is made by an end-user whether an audio track for the multi-track recording is to be generated. The recording may be initiated based on the receipt of an audible input, such as a vocal audible input generated by an end-user. In one embodiment, a detected amplitude of an audible input may trigger the sampling and storage of an audible input signal received in system **100**. In an alternate embodiment, such a track generation may be initialized by a manual input received by system **100**. Further, generating a new audio track may require both a detected audible input, such as from a microphone, and a manual indication. If a new audio track is to be generated, processing continues at block **922**. If the generation of an audio track is not initiated, process **900** continues at decision block **940**.

[0106] At block **922**, an audible input is received by the track recorder **202** of audio converter **140** and the audible input is stored in memory **2904** in one or more data storage modules **132**. As used herein, "audible" refers to a property of an input to device **50** wherein, as the input is being provided, it may concurrently, naturally, and directly be heard by at least one user without amplification or other electronic processing. In one embodiment, the length of the recorded audible input may be determined based on the remaining amount of time within a live loop when the audible input is first received. That is, the recording of an audible input may be ended after a length of time at the end of a live loop, regardless if a detectable amount of audible input is still being received. For example, if the length of the loop is one bar long at four beats per bar and receipt of the audible input is first detected or triggered at the beginning of the second beat, then three beats worth of audible input may be recorded, corresponding to the second, third, and fourth beats of the bar and, thus, those second, third, and fourth beats would be looped in the multi-track recording playback continually processed in block **910**. In such an arrangement, any audible input received after the end of the single bar may be recorded and processed as a basis for another separate track for the multi-track recording. Such additional processing of the separate track may be represented as a separate iteration through at least blocks **910**, **920**, and **922**.

[0107] In at least one alternate embodiment, the length of the looped playback may be dynamically adjusted based on the length of audible input received at block **922**. That is, the audible input might automatically result in an extension of the length of the track of the multi-track recording that is currently being played in block **910**. For example, if additional audible input is received after a length of a current live loop has been played back, then this longer audible input may be further recorded and maintained for derivation as the new audio track. In such an arrangement, previous tracks of the multi-track recording may be repeated within subsequent live loops in order to match the length of the received audible input. In one embodiment, the repetition of the shorter, previous multi-track recording may be performed an integral number of times. This integral number of repetitions retains the relationship, if any, between multiple bars of the shorter multi-track recording previously recorded. In such a way, the looping point of a multi-track recording and live loop may be dynamically altered.

[0108] Similarly, the length of the received track at block **922** may be shorter than, the length of the currently playing live loop (i.e. receiving only one bar of audible input during the playback of a four bar long live loop). In such an arrangement, the end of the audible input may be detected when no additional audible input has been received after a predetermined time (e.g. a selected number of seconds) following the receipt and recording of an audible input of at least a threshold volume. In one embodiment, the detection of this silence may be based on the lack of input above the threshold volume of the current live loop. Alternately or additionally, the end of an audible input may be signaled by receipt of a manual signal. The associated length of this shorter audible input may be determined in terms of a number of bars with a same number of beats as the multi-track recording. In one embodiment, this number of bars is selected as a factor of the length of the current live loop. In each case, an audible input, once converted to a track at block **924**, may be manually or automatically selected for repetition for a number of times sufficient to match a length of the multi-track recording currently being played back.

[0109] In block **924**, the received audible input may be converted into an audio track by audio converter **140**. As discussed above, the audio conversion process may include various operations including partitioning, quantization, frequency detection and shifting, instrument conversion, gain control, harmonics generation, adding special effects, and manual adjustment. The order of each of these audio conversion operations may be altered, and may, in at least one embodiment, be configured by an end-user. Also, each of these operations may be selectively applied, enabling the audible input to be converted to an audio track with as much or as minimal additional processing as required. For example, instrument conversion may not be selected, thus permitting one or more original sounds from an audible input to be substantially included in the generated audio track with its original timbre. In block **924**, an echo cancellation process may be applied to filter out the audio of other tracks being played during live looping from the audio track being actively recorded. In one embodiment, this may be accomplished by identifying the audio signal being played during the live loop, determining any delay between the output audio signal and the input audio signal; filtering and delaying the output audio signal to resemble the input audio signal; and subtracting the output audio signal from the input audio signal. One preferred echo cancellation process that may be used is one implemented by iZotope, although other implementations may also be used. The processes of block **924** may be subsequently applied or removed as further discussed herein with respect to block **942**. After converting the audible input into a generated audio track at block **924**, process **900** continues at block **926**.

[0110] At block **926**, the generated audio track from block **924** may be added in real-time to a multi-track recording. This may be a multi-track already initiated or, alternately, a new

multi-track with the audio track included as the first track thereof. After block **926**, process **900** may begin again at decision block **910**, wherein the multi-track may be played back with the most recently generated audio track included. While the operations of **922**, **924**, and **926** are shown as being performed in series in FIG. **9**, these steps may also be performed in parallel for each received audible input, in order to further enable the real-time recording and playback of an audible input signal. During each audible input, such parallel processing may be performed, for example, for each separate sound identified from the audible input, though alternate embodiments may include other, differently sized portions of the audible input signal.

[0111] At decision block **940**, a determination is made whether one or more audio tracks in the multi-track recording are to be modified. For example, an input may be received that indicates an end-user desires to modify one or more of the previously recorded audio tracks. In one embodiment, the indication may be received through a manual input. As noted above, this modification may also be performed during playback of the currently recorded multi-track recording, permitting immediate appreciation of a current state of the multi-track recording for the end-user. In one embodiment, the indication may include one or more tracks of the multi-track recording to which an adjustment is desired to be applied. These tracks may also include one or more new tracks manually added to the multi-track recording. If indication of a track modification is received, process **900** continues at block **942**; otherwise, process **900** continues at decision block **960**.

[0112] At block **942**, the parameters of the one or more previously converted tracks are received and adjusted parameters may be input by an end-user. Parameters for modification may include any adjustments that can be done using the processes of audio converter **140**, which may include among other examples, muting or soloing a track, removal of an entire track, adjusting the strike velocity of an instrument in a track, adjusting the volume level of a track, adjusting a tempo of playback of all tracks in the live loop, adding or removing separate sounds from selected time increments of a track, adjusting the length of a live loop and/or overall length of the multi-track recording. Adjusting the length of the live loop may comprise altering start and end points of the loop with respect to the overall multi-track recording and/or may also comprise adding more bars to the tracks currently being repeated in a live loop, adding and/or appending previously recorded bars of the multi-track recording with at least a subset of the tracks previously associated with these bars, or deleting bars from the multi-track recording. The addition of a new track may require various aspects of this new track to be manually input by an end-user. Also at block **942**, a search may be conducted for an additional track through the use of sound searcher module **150** to facilitate an end-user's reuse of previously recorded audio tracks.

[0113] At block **944**, the adjusted parameters are applied to one or more tracks indicated at decision block **940**. The application may include converting the adjusted parameter into a format compatible with the adjusted one or more tracks. For example, one or more numerical parameters may be adjusted to correspond to one or more values applicable to the MIDI or other protocol format. After block **944**, process **900** may begin again at decision block **910**, wherein at least a portion of the multi-track recording that corresponds to the live loop may be played back with the one or more modified audio tracks included.

[0114] At decision block **960**, a determination is made whether a recording setup is to be modified. For example, an input may be received that indicates if a user desires to modify one or more aspects of the recording setup. This indication may also be received through a manual input. The indication may further one or more parameter settings of a recording setup that are to be adjusted. If the end user desires to modify the recording setup process **900** continues at block **962**; otherwise, process **900** continues at decision block **980**.

[0115] At block **962**, the recording system may be calibrated. Particularly, the recording circuit, comprising at least an audio input source, audio output source, and audio track processing components, may be calibrated to determine latency of system **100** in conjunction with device **50**, preferably measured in thousandths of a second, between a playback of a sound through the audio output source and receipt of an audible input through the audio input source. For example, if a recording circuit comprises a headset and a microphone, the latency may be determined by the RSLL **142** to improve receipt and conversion of an audible input, particularly a determination of a relative timing between beats of a multi-track recording being played back and a received audible input. After calibration at block **962**, if any, process **900** continues to block **964**.

[0116] At block **964**, other recording system parameters settings may be changed. For example, playback of the click track may be turned on or off. Also, default settings for new tracks or new multi-track recordings may be modified, such as a default tempo and a default set of conversions for an audible input for block **924** may be provided. The time signature of a current multi-track recording may also be changed at block **964**. Other settings associated with a digital audio workstation may also be provided so they may be modified by an end-user as would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them. After block **964**, process **900** may return to decision block **910**, wherein adjustments to the recording system may be applied to the subsequent recording and modification of audio tracks for a multi-track recording.

[0117] At block **980**, a determination is made whether the recording session is to be ended. For example, an input indicating the end of the session may be received from a manual input. Alternately, device **50** may indicate the end of the session if, for example, data storage **132** is full. If an end-of-session indication is received, the multi-track recording may be stored and/or transmitted for additional operations. For example, a multi-track recording may be stored in data storage **132** for future retrieval, review, and modification in a new session or a continuation of the session in which the multi-track recording was initially created. The multi-track recording may also be transmitted from a device **50** to another device **50** over a network for storage in at least one remote data store associated with a user account. A transmitted multi-track recording may also be shared through a network server with an online music community or shared in a game hosted by a network server.

[0118] If the recording session is not ended, process **900** returns again to decision block **910**. Such a sequence of events may represent periods in which a user is listening to a live loop while deciding which, if any, additional tracks are to be generated or other modifications, if any, are to be performed. It will be understood by those of ordinary skill in the art having the present specification, drawings and claims before them that each block of the flowchart illustration in FIG. **9**

(and otherwise), and combinations of blocks in the flowchart illustration, can be implemented by computer program instructions. These program instructions may be provided to a processor to produce a machine, such that the instructions, which execute on the processor, create means for implementing the actions specified in the flowchart block or blocks. The computer program instructions may be executed by a processor to cause a series of operational steps to be performed by the processor to produce a computer implemented process such that the instructions, which execute on the processor to provide steps for implementing the actions specified in the flowchart block or blocks. The computer program instructions may also cause at least some of the operational steps shown in the blocks of the flowchart to be performed in parallel. Moreover, some of the steps may also be performed across more than one processor, such as might arise in a multi-processor computer system. In addition, one or more blocks or combinations of blocks in the flowchart illustration may also be performed concurrently with other blocks or combinations of blocks, or even in a different sequence than illustrated without departing from the scope or spirit of the invention. Accordingly, blocks of the flowchart illustration support combinations of means for performing the specified actions, combinations of steps for performing the specified actions and program instruction means for performing the specified actions. It will also be understood that each block of the flowchart illustration, and combinations of blocks in the flowchart illustration, can be implemented by special purpose hardware-based systems, which perform the specified actions or steps, or combinations of special purpose hardware and computer instructions.

[0119] The operation of certain aspects of the invention will now be described with respect to various screen displays that may be associated with a user interface implementing audio converter **140** and RSSL module **142**. The illustrated embodiments are non-limiting, non-exhaustive example user interfaces that may be employed in association with the operations of system **100**. The various screen displays may include many more or less components than those shown. Furthermore, the arrangement of the components are not limited to that shown in these displays, and other arrangements are also envisioned, including the disposition of various components on different interfaces. However, the components shown are sufficient to disclose an illustrative embodiment for practicing the present invention.

[0120] FIGS. **10**, **10**A, and **10**B together illustrate one user interface that implements RSLL **142** and aspects of audio converter **140** to record and modify tracks of a multi-track recording. The overall display of interface **1000** may be considered a "control space". Each control displayed on interface may be operated based on a manual input from a user, such as through the use of a mouse **54**, touch screen **80**, pressure pad, or device arranged to respond to and convey a physical control. As shown, interface **1000** displays various aspects of a recording session and a multi-track recording generated as a part of this session. File menu **1010** includes options for creating a new multi-track recording or loading a previously recorded multi-track recording, as would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them.

[0121] Tempo control **1012** displays a tempo of the multi-track recording in beats per minute. Tempo control **1012** may be directly, manually modified by a user. Bar control **1014** displays a bar number for a multi-track recording. Bar control **1014** may be configured to display a current bar number during a live loop, an overall number of bars, or alternately be used to select a certain bar number of the multi-track recording for further display in the interface **1000**.

[0122] Beat control **1016** displays a beat number for a multi-track recording. Beat control **1016** may be configured to display a total number of beats for each bar, or, alternately, a current beat number during playback of the multi-track recording. Time control **1018** displays a time for the multi-track recording. This time control **1018** may be configured to display an overall time for the multi-track recording, a length of time for a currently selected live loop, an absolute or relative time during a live loop, or be used to jump to a certain absolute time of a multi-track recording. Operations of controls of interface **1000**, such as controls **1012**, **1014**, **1016**, **1018**, and **1021-1026**, may be changed in block **964** of FIG. **9**. Controls **1020** correspond to track and recording setup adjustments further discussed with respect to blocks **942** and **962** of FIG. **9**.

[0123] Add track control **1021** enables a user to manually add a track to a multi-track recording. Upon selection of control **1021**, a new track is added to the multi-track recording and the interface is updated to include additional controls **1040-1054** for the added track, the operations of which are discussed as follows. Render WAV control **1022** generates and stores a WAV file from at least a portion of a multi-track recording. The portions of the multi-track recording rendered in this WAV file, as well as other storage parameters, may be further entered by a user upon selection of Render WAV control **1022**. Further, other audio file formats, in addition to WAV, may also be available through a control such as control **1022**.

[0124] Click track control **1023** toggles playback of the click track. Armed control **1024** toggles on and off the recording component of RSLL **142** and a device's ability to record an audible input. Armed control **1024** enables an end user to speak with other users, practice a vocal input, and create other audible sounds during a recording session without having those sounds converted into an audible input that is further processed by RSLL **142**.

[0125] Circuit parameters control **1025** enables a user calibrate recording circuit parameters as is further discussed with regards to FIG. **11**. Slider **1026** enables the volume of the multi-track recording playback to be controlled. Playback control **1030** enables playback of a multi-track recording. This playback is conducted in coordination with recording parameters further displayed and controlled through controls **1012-1018**. For example, playback control **1030** may initiate playback of multi-track recording from positions indicated via controls **1014-1018** and at a tempo displayed in control **1012**. As noted above, this control **1030** also enables recording of an additional audible input for generating another audio track for a multi-track recording. Position control **1032** may also be used to control a current playback position of a multi-track recording. For example, control **1032** may cause playback to be initiated at the absolute beginning of multi-track recording or, alternately, the beginning of a current live loop.

[0126] Grid **1050** on user interface **1000** represents the playback and timing of separate sounds within one or more tracks of a multi-track recording, wherein each row represents an individual track and each column represents a time increment. Each row may, for example, include a box for each time increment in a single bar. Alternately, each row may

include enough boxes to represent time increments for an overall duration of a live loop. Boxes with a first shading or color in the grid **1050**, such as box **1052**, may represent a relative timing of where a sound is played back during a live loop, while other boxes, such as boxes **1054**, each indicate a time increment within a track where a separate sound is not played back. A track added via manual control **1021** initially includes boxes such as box **1054**. Selection of a box, such as a box **1052** or box **1054** may add or remove a sound from the track at the time increment associated with the selected box. Sounds added via manual input to a box in grid **1050** may comprise a default sound for an instrument selected for the track, or alternately, a copy of at least one sound quantized from an audible input for a track. This manual operation with grid **1050** enables an audible input to generate one or more sounds for a track, yet add copies of one or more of these sounds at manually chosen locations within the track.

[0127] A progress bar **1056** visually indicates a time increment of a current playback position of a multi-track recording. Each track in grid **1050** is associated with a set of track controls **1040**, **1042**, **1044**, **1046**, and **1048**. Remove track control **1040** enables removal of a track from multi-track recording and may be configured to selectively remove a track from one or more bars of a multi-track recording.

[0128] Instrument selection control **1042** enables selection of an instrument to which sounds of an audible input are converted in the generated audio track. As illustrated in FIG. **10**A, a plurality of instruments, including percussion or other types of non-percussion instruments, may be manually selected from a drop down menu. Alternatively, a default instrument or a default progression of instruments may be automatically selected or predetermined for each given audio track. When no instrument is selected, each sound in a generated audio track may substantially correspond to sounds of the original audible input, including with a timbre of the initial audible input. In one embodiment, an instrument may be selected based on training RSLL **142** to automatically convert particular sounds in an audible into associated instrument sounds based on, for example, a classification of frequency bands of each particular sound.

[0129] Mute/Solo control **1044** mutes an associated track or mutes all other tracks except for the track associated with the control **1044**. Velocity control **1046** enables adjustment of an initial attack or strike strength of instrument sounds generated for a converted audio track, which may influence the peak, duration, release, and overall amplitude shape of each instrument sound generated for the associated audio track. Such velocity may be manually entered or, alternately, extracted based on properties of the audible input sounds from which one or more instrument sounds are generated. Volume control **1048** enables individual control of the playback volume of each track in the multi-track recording.

[0130] FIG. **11** illustrates one embodiment of an interface **1100** for calibrating a recording circuit. Interface **1100** may represent one example of a screen display pop-up, or the like, that may appear when control **1025** (see FIG. **10**A) is selected. In one embodiment, interface **1100** comprises a microphone gain control **1110** that enables adjustment of the amplitude of a received audible input. Upper control **1120** and lower control **1130** and half-life control **1140** provide additional control and validation for identifying a received signal as being an audible input for further processing by system **100**. Calibrate circuit initiates a predetermined click track and may direct a user to replicate the click track in an audible input signal. In an alternate embodiment, the click track for calibration may be directly received as an audible input by audio input devices such as a microphone, without requiring a user to audibly replicate the click track. Based on relative timing differences between the generation of sounds in the click track and the receipt of sounds in the audible input, a system latency **1160** may be determined. This latency value may be further employed by RSLL **142** to improve quantization of an audible input and the detected relative timing between the playback of a multi-track recording and an audible input received for subsequent derivation of an additional audio track to be added to the multi-track recording.

[0131] Thus, as illustrated, interfaces **1000** and **1100** present users with a control space that is welcoming and non-threatening, powerful, and consistent, yet intuitive to learn, which is particularly important for a lay user who is not a professional musician or otherwise familiar with digital audio authoring tools.

[0132] FIGS. **12**A, **12**B, and **12**C together illustrate yet another exemplary visual display that may be used in association with the recording and modification of audio tracks in a multi-track recording. In this example, the audio frequency (actual and morphological (post frequency shift by frequency shifter **210**)), partition, quantization, and tempo information are provided graphically in order to provide the user with an even more intuitive experience. For instance, turning first to FIG. **12**A, a graphical control space **1200** for a live loop is provided. The control space includes a plurality of partition indicators **1204** that identify each of the partitions (or musical measures) in the track (in the case of FIGS. **12**A-C measures **1** through **4** are shown). In one embodiment of the graphical user interface illustrated in FIGS. **12**A-C, vertical lines **1206** illustrate the beat within each measure, with the number of vertical lines per measure preferably corresponding to the top number of a time signature. For example if a musical composition is chosen to be composed using a ¾ time signature, each measure would include three vertical lines to indicate that there are three beats in the measure or partition. In the same embodiment of the user interface illustrated in FIGS. **12**A-C, horizontal lines **1208** may also identify the fundamental frequencies associated with a selected instrument to which the audible input is to be converted. As further illustrated in the embodiment of FIGS. **12**A-C, an instrument icon **1210** may also be provided to indicate the selected instrument, such as the guitar selected in FIGS. **12**A-C.

[0133] In the embodiment illustrated in FIGS. **12**A-C, solid line **1212** represents the audio waveform of one track as recorded by an end-user, either vocally or using a musical instrument; while the plurality of horizontal bars **1214** represent the morphology of the notes that have been generated from the audio waveform by quantizer **206** and frequency shifter **210** of audio converter **140**. As depicted, each note of the generated morphology has been shifted in time to align with the beats of each partition and shifted in frequency to correspond to one of the fundamental frequencies of the selected instrument.

[0134] As depicted by comparing FIG. **12**A to FIG. **12**B to FIG. **12**C, playback bar **1216** may also be provided to identify the specific part of the live loop that is currently being played by track recorder **202** pursuant to the process of FIG. **9**. The playback bar **1216** therefore moves from left to right as the live loop is played. Upon reaching the end of the fourth measure, the playback bar returns to the beginning of measure one and repeats the loop again sequentially. The end-user may

provide additional audio input at any point within the live loop by recording additional audio at the appropriate point in the loop. Although not shown in FIGS. **12**A-C, each additional recording can be used to provide a new track (or set of notes) for depiction within the live loop. Separate tracks may be associated with a different instruments by adding additional instrument icons **1210**.

[0135] FIGS. **13**A, **13**B, and **13**C together illustrate one example of a process for manually altering a previously generated note via the interface of FIGS. **12**A-C. As shown in FIG. **13**A, an end-user can select one specific note **1302** using a pointer **1304**. As shown in FIG. **13**B, the end-user may then drag the note vertically to another horizontal line **1208** to alter the pitch of the dragged note. In this example, the note **1302** is shown as being moved to a higher fundamental frequency. It is contemplated that notes could also be moved to frequencies between fundamental frequencies of the instrument. As shown in FIG. **13**C, the timing of a note can also be altered by selecting the end of the morphologic depiction of the note and then dragging it horizontally. In FIG. **13**C, the duration of note **1304** has been lengthened. As also depicted in FIG. **13**C, the result of lengthening note **1304**, is the automatic shortening of note **1306** by quantizer **206** to maintain the beat and avoid overlapping notes being played by a single instrument. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, the same or similar methodology can be used to shorten the duration of a selected note resulting in the automatic lengthening of another adjacent note and further that the duration of a note can be changed from the beginning of the morphologic depiction in the same manner illustrated with respect to modifying the tail of that depiction. It should also be similarly understood by those of ordinary skill in the art that the same methodology may be used to delete notes from a track or copy notes for insertion at other parts of the track.

[0136] FIGS. **14**A, **14**B, and **14**C illustrate yet another exemplary visual display for use with system **100**. In this example, the visual display enables a user to record and modify a multi-track recording associated with percussion instruments. Turning first to FIG. **14**A, a control space **1400** includes a grid **1402** that represents the playback and timing of separate sounds within one or more percussion tracks. As in the illustration of FIGS. **12**A-C, partitions **1-4**, each having four beats are depicted in the example of FIG. **14**A-C. For example, in FIG. **14**A, the first row of grid **1402** represents the playback and timing of sounds associated with a first base drum, the second row of grid **1402** represents the playback and timing of sounds associated with a snare drum, the third and fourth rows of grid **1402** represents the playback and timing of sounds associated with cymbals, and the fifth row of grid **1402** represents the playback and timing of sounds associated with a floor torn. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, these particularly percussion instruments and their order on grid **1402** is meant only to illustrate the concept and should not be seen as limiting the concept to this particular example.

[0137] Each box in the grid represents the timing increments for sounds associated with the related percussion instrument, where an unshaded box indicates that no sound is to be played at that time increment, and a shaded box indicates that a sound (associated with the timbre of the related percussion instrument) is to be played at that time increment. Thus, FIG. **14**A illustrates an example where no sounds are to be played, FIG. **14**B illustrates an example where the sound of a base drum are to be played at the times indicated by the shaded boxes, and FIG. **14**C illustrates an example where the sounds of a base drum and a symbol are to be played at the times indicated by the shaded boxes. For each percussion instrument track, a sound associated with the particular percussion instrument may be added to the track for instrument in various ways. For example, as shown in FIG. **14**B or **14**C, a playback bar **1404** may be provided to visually indicate a time increment of a current playback position of a multi-track recording during live looping. Thus, in FIG. **14**B, the playback bar indicates that the first beat of the third measure is currently being played. A user may then be enabled to add a sound associated with a particular percussion instrument at a particular beat by recording a sound at the time that the playback bar **1404** is over the box associated with a particular beat. In one embodiment, the instrument track to which the sound is to be associated with may be identified manually by the user selecting or clicking on the appropriate instrument. In this case, the particular nature and pitch of the sound made by the user may not be important, although it is contemplated that the volume of the sound made by the user may affect the gain of the associated sound generated for the percussion track. Alternatively, the sound made by a user may be indicative of the percussion instrument that the sound is to be associated with. For example, a user may vocalize the sounds "boom", "tsk" or "ka" to indicate a base drum, symbol, or tom drum beat, respectively. In yet another embodiment, the user may be enabled to add or remove sounds from a track simply by clicking or selecting a box in the grid **1402**.

[0138] Multiple Take-Auto Composition Module

[0139] MTAC Module **144** (FIG. **1**A) is configured to operate in conjunction with audio converter **140**, and optionally RSLL **142**, to enable the automatic production of single, "best" take that is derived from a collection of takes. One embodiment of MTAC Module **144** is illustrated in FIG. **15**. In this embodiment, MTAC Module **144** includes a Partition Scorer **1702** to score partitions from each take of recorded audio and a Compositor **1704** to assemble the single, "best" take based on the scores identified by Partition Scorer **1702**.

[0140] Partition scorer **1702** may be configured to score partitions based on any one or more criteria, which may utilize one or more processes running on the processor **2902**. For example, a partition may be scored based on the key of the partition relative to a key selected for the overall composition. Often, a performer may sing an off-key note without knowing it. Thus, notes within a partition may also be scored based on the difference between the key of the note and the proper key for the partition.

[0141] In many cases, however, a novice end-user may not know what music key he wants to sing in. Consequently, partition scorer **1702** may also be configured to automatically identify a key, which may be referred to as "Automatic Key Detection." With "Automatic Key Detection," partition scorer **1702** may determine the key closest to that of the end-user's recorded audio performance. The system **50** may highlight any notes that are off-key from the automatically detected key and may further automatically adjust those notes to fundamental frequencies that are in the automatically determined key signature.

[0142] One illustrative process for determining the musical key is depicted in FIG. **16**. As shown in the first block, this process scores the entire track against each of the 12 musical keys (C, C#/Db, D#/Eb, E, F, F#/Gb, G, G#/Ab, A, A#/Bb, B)

with weight being given to each fundamental frequency within a key. For instance, the key weight array for some arbitrary major key may look like this [1, −1, 1, −1, 1, 1, −1, 1, −1, 1, −1, 1], which assigns a weighting to every one of the twelve notes in a scale beginning with Do and continuing with Re, etc. Assigning weights to each note (or interval from the tonic) works for any type of key. The notes that are out of the key are given a negative weight. While the magnitudes of the weights are generally less important, they can be adjusted to individual user taste or based on input from genre matcher module **152**. For instance, some tones in the key are more definitive of that key, so the magnitude of their weights could be higher. Furthermore, some tones not in the key are more common than others; they can remain negative but have smaller magnitudes. So, it would be possible for a user or system **100** (based on input, for instance, from the genre matcher module **152**) to develop a more refined key Weights array for a major key that could be [1, −1, 0.5, −0.5, 0.8, 0.9, −1, 1, −0.8, 0.9, −0.2, 0.5]. Each of the 12 major keys would be associated with a weight array. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, minor (or any other) keys could be accommodated by selecting weights for each array that account for the tones within the key with reference to any document showing the relative position of notes within a key.

[0143] As shown in the third block of FIG. **16**, the relative duration of each note to the duration of the overall passage (or partition) is multiplied by the "weight" of the note's pitch class in the key currently being analyzed for the loop to determine the score for each note in the passage. At the start of each passage, the score is zeroed out, then the scores for each note as compared against the current key are added one to another until there are no more notes in the passage and process loops back around to begin analyzing the passage with respect to the next key. The result of the main loop of the process is a single key score for each key reflecting the aggregate of all the scores for each of the notes in the passage. In the last block of the process of FIG. **16**, the key with the highest score would be selected as the BestKey (i.e. most appropriate for the passage). As would be understood by those of ordinary skill in the art different keys could tie or have sufficiently similar scores so as to be essentially tied.

[0144] In one embodiment, a note's pitch class in a key, represented by the value "index" in FIG. **17**, may be determined using the formula: index:=(note.pitch−key+12) % **12**, where note.pitch represents a numerical value associated with a specific pitch for an instrument, where the numerical values are preferably assigned in order of increasing pitch. Taking the example of a piano, which has 88 keys, each key may be associated with a numeral between 1 and 88 inclusively. For instance, key **1** may be the AO Double Pedal A, key **88** may be the C8 eighth octave, and key **40** may be middle C.

[0145] In another embodiment where the end-user knows which musical key they wish to be in, the user may identify that key in which case, the process of FIG. **16** will be started for only the one key selected by the end-user rather than the 12 keys indicated. In this manner, each of the partitions may be judged against the single predetermined key selected by the user in the manner discussed above.

[0146] In another embodiment, a partition may also be judged against a chord constraint. A chord sequence is a musical constraint that can be employed when the user wishes to record an accompaniment. Accompaniments may be typically thought of as arpeggiations of the notes in the chord track and may also include the chords themselves. It is, of course, permissible to play notes that are out of the chord, but these must typically be judged on their musical merits.

[0147] One illustrative process for scoring the quality of a partition's harmony based on a chord sequence constraint is depicted in FIGS. **17**, **17**A, and **17**B. In the process of FIG. **17**, one selected chord is scored per pass according to how well that selected chord would harmonize with a given partition (or measure) of the audio track. The chord-score for each note is the sum of a bonus and a multiplier. In the second box of process **1700**, the variables are reset to zero for each note in the passage. Then, the relationship of the pitch of the note is compared to the currently selected chord. If the note is in the selected chord, the multiplier is set to the value of chordNote-Multiplier set in the first box of process **1700**. If the note is a tritone (i.e. a musical interval that spans three whole tones) of the chord root (e.g. C is the chord root of a C major chord), then the multiplier is set to the value of tritoneMultiplier (which as is shown in FIG. **17**A is negative, thus, indicating that the note does not harmonize well with the selected chord). If the note is one or eight semitones above the root (or four semitones above the root in the case of a minor chord), then the multiplier is set to the value of a nonKeyMultiplier (which as is shown in FIG. **17**A is again negative, thus, indicating that the note does not harmonize well with the selected chord). Notes which fall into none of the foregoing categories are assigned a zero multiplier, and thus have no effect on the chord-score. As shown in FIG. **17**B, the multiplier is scaled by the fraction duration of the passage which the current note occupies. Bonuses are added to the chord-score if the note is at the beginning of the passage, or if the note is the root of the current chord selected for analysis. The chord-score with respect to the passage is the accumulation of this computation for each note. Once a first selected chord is analyzed, the system **50** may analyze other selected chords (one at a time) using the process **1700** anew. The chord-score from each pass through process **1700** may be compared to one another and the highest score would determine the chord that would be selected to accompany the passage as being the best fit with that passage. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, two or more chords may be found to have the same score with respect to a selected passage in which case system **50** could decide between those chords on the basis of various choices, including, but not limited to the genre of the musical track. It should also be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, that the scoring set forth above is to some extent a matter of design choice best upon the prevailing musical genre in Western Music. It is accordingly contemplated that the selection criteria for the multipliers could be altered for different genre of music and/or the multiplier values assigned to the various multiplier selection criteria in FIG. **17** could be changed to reflect different musical tastes without departing from the spirit of the present invention.

[0148] In another embodiment, partition scorer **1702** may also judge a partition against the collection of certain allowed pitch values, such as semitones as are typical in Western music. However, quarter tones of other musical traditions (such as those of Middle Eastern Cultures) are similarly contemplated.

[0149] In another embodiment, a partition may also be scored based on the quality of transitions between the various pitches within the partition. For example, as discussed above, changes in pitch may be identified using pitch impulse detection. In one embodiment, the same pitch impulse detection may also be used to identify the quality of the pitch transitions in a partition. In one approach, system may utilize the generally understood concept that damped harmonic oscillators generally satisfy the following equation:

$$\frac{d^2x}{dt^2} + 2\zeta\omega_0\frac{dx}{dt} + \omega_0^2 x = 0$$

[0150] where ω0 is the undamped angular frequency of the oscillator and ϵ is a system dependent constant called the damping ratio. (for a mass on a spring having a spring constant k and a damping coefficient c, $\omega_0=\sqrt{k/m}$ and $\epsilon=c/2m\omega_0$.) It is understood that the value of the damping ratio ϵ critically determines the behavior of the damped system (e.g. overdamped, critically damped (ϵ=1), or underdamped). In a critically damped system, the system returns to equilibrium as quickly as possible without oscillating. A professional singer, in general, is able to change his/her pitch with a response that is critically damped. By using pitch impulse analysis, both the true start of the pitch change event and the quality of the pitch change may be determined. In particular, the pitch change event is the deduced step function, whereas the quality of the pitch change is determined by the ϵ value. For instance, FIG. **19** depicts a step-response of a damped harmonic oscillator for three values ϵ In general, values of ϵ>1 denote poor vocal control, where the singer "hunts" for the target pitch. Thus, the larger the value of ϵ, the poorer the pitch-transition-score attributed to the partition.

[0151] Another exemplary method for scoring the quality of pitch transition is shown in FIG. **20**. In this embodiment, the scoring of a partition may comprise receiving an audio input (process **2002**), converting the audio input into a morphology of pitch events showing the true oscillations between pitch changes (process **2004**), using the morphology of pitch events to construct a waveform with critically damped pitch changes between each pitch event (process **2006**), computing the difference between the pitch in the constructed waveform with the original audio waveform (process **2008**), and computing a score based on this difference (process **2010**). In one embodiment, the score may be based on the signed root mean square error between the "filtered pitch" and the "reconstructed pitch." In simple terms, this calculation can indicated to the end-user how far they deviated from the "ideal" pitch, which in turn may be turned into a pitch-transition-score.

[0152] The scoring methods described above may be utilized to score a partition against either an explicit reference or an implicit reference. An explicit reference may be an existing or pre-recorded melody track, musical key, chord sequence, or note range. The explicit case is typically used when the performer is recording in unison with another track. The explicit case could analogized to judging Karaoke in that the music reference exists and the track is being analyzed using the previous known melody as the reference. An implicit reference, on the other hand, may be a "target" melody (i.e. the system's best guess at the notes that the performer is intending to produce) computed from multiple previously recorded takes that have been saved by track recorder **202** in data storage **132**. The implicit case is typically used when the user is recording the lead melody of a song during which no reference is available, such as an original composition or a song for which partition scorer **1702** has no knowledge.

[0153] In the case where a reference is implicit, a reference may be computed from the takes. This is typically achieved by determining the centroid of the morphologies for each of the N partitions of each previously recorded track. In one embodiment, the centroid of a set of morphologies is simply a new morphology constructed by taking the mean average pitch and duration for each event in the morphology. This is repeated for n=1 to N. The resulting centroid would then be treated as the morphology of the implicit reference track. One illustration of a centroid determined in this manner for a single note is depicted in FIG. **18**, with the dotted line depicting the resulting centroid. It is contemplated that other methods may be used to compute the centroid. For instance, the modal average value of the set of morphologies for each of the takes could be used instead of the mean average. In any approach, any outlying values can be discarded before computing the average or mean. Those of ordinary skill in the art having the present specification, drawings and claims before them, would understand that additional options for determining the centroid of the takes may be developed based on the principles set forth in the specification without having to conduct undue experimentation.

[0154] As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, any number of the foregoing independent methodologies for scoring partitions may be combined to provide an analysis of a wider set of the considerations. Each score may be given identical or different weight. If the scores are given different weights it may be based on the particular genre of the composition as determined by genre matcher module **152**. For instance, in some musical genre a higher value may be placed on one aspect of a performance over another. The selection of which scoring methodologies are applied may also be determined automatically or manually selected by a user.

[0155] As illustrated in FIG. **23**, partitions of musical performance may selected from any of a plurality of recorded tracks. Compositor **1704** is configured to combine partitions from the plurality of recorded tracks in order to create an ideal track. The selection could be manual through a graphical user interface where the user could view the scores identified for each version of a partition, audition each version of a partition, and choose one version as the 'best' track. Alternatively, or additionally, the combination of partitions may be performed automatically by selecting the version of each track partition with the highest scores based on the scoring concepts introduced above.

[0156] FIG. **21** illustrates on exemplary embodiment of a process for providing a single, "best" take from a collection of takes using MTAC module **144** in conjunction with Audio Converter **140**. In step **2102**, the user sets a configuration. For instance, the user can select whether a partition is to be scored against an explicit or an implicit reference. The user may also select one or more criteria (i.e. key, melody, chord, target, etc.) to use for scoring a partition, and/or provide rankings to identify the relevant weight or importance of each criteria. A take is then recorded in step **2104**, partitioned in step **2106**, and converted into a morphology in step **2108** using the process described above. If RSSL Module **142** is being employed then, as described above, at the end of the take, the

track may automatically loop back to the start, allowing the user to record another take. Also, during recording the user may choose to hear a click track, a previously recorded track, a MIDI version of any single track, or a MIDI version of a "target" track computed as discussed above with respect to an explicit or an implicit reference (see FIGS. **18**, **19**, **20** and **21**). This allows the user to listen to a reference against which he can produce the next (hopefully improved) take.

[0157] In one embodiment, the end-user may select the reference and/or one or more methods against which the recorded take(s) should be scored, step **2110**. For instance, the user's configuration may indicate that the partition should be scored against a key, a melody, the chords, a target morphology constructed from the centroid of one or more tracks, or any other method discussed above. The guide selection may be made manually by the user or set automatically by the system.

[0158] The partitions of a take are scored in step **2112**, and, in step **2114**, an indication of the scoring for each partition in a track may be indicated to the user. This may benefit the end user by providing them with an indication of where the end user's pitch or timing is off so that the end user can improve in future takes. One illustration of a graphical display for illustrating the score of a partition is illustrated in FIG. **22**. In particular, FIG. **22** the vertical bars depict an audio waveform as recorded from an audio source, the solid black, primarily horizontal, line depicts the ideal waveform the audio source was trying to mimic, and the arrows represent how the pitch of the audio source (e.g. a singer) varied from the ideal waveform (called the explicit reference).

[0159] In step **2116**, the end user manually determines whether to record another take. If the user desires another take, the process returns to step **2104**. Once the end user has recorded all of the multiple takes for a track, the process proceeds to step **2118**.

[0160] In step **2118**, the user may be provided a choice as to whether a "best" overall track is to be compiled from all of the takes manually or automatically. If the user selects to create a manual composition, the user may, in step **2120**, simply audition the first partition of the first take, followed by the first partition of the second take, until each of the candidate first partitions have been auditioned. One interface that be used to facilitate the auditioning and selection between the various takes of the partitions is shown in FIG. **23** wherein the end user by use a pointing device (such as a mouse) to click on each track taken for each partition to prompt the playback of that track and then subsequently the user selects one of these candidate partitions as the best performance of that partition by, for instance, double-clicking the desired track and/or clicking-and-dragging the desired track into the bottom, final compiled track **2310**. The user repeats this process for second, third and subsequent partitions, until he reaches the end of the track. The system then constructs a "best" track by splicing together the selected partitions into a single, new track in step **2124**. The user may then also decide whether to record further takes in order to improve his performance in step **2126**. If the user chose to compile the "best" track automatically, a new track is spliced together in step **2122** based on the scores for each partition in each take (preferably using the highest scored take for each partition).

[0161] One example of a virtual "best" track that is spliced together from partitions of actual recorded tracks is also illustrated in FIG. **23**. In this example, the final compiled track **2310** includes a first partition **2302** from take 1, a second partition **2304** from track **5**, a third partition **2306** from take 3 and a fourth partition **2308** taken from track **2**, with no partitions being used from track **4**.

[0162] Harmonizer

[0163] Harmonizer module **146** implements a process for harmonizing notes from an accompanying source with a musical key and/or chord of a lead source, which may be a vocal input, a musical instrument (real or virtual), or a pre-recorded melody that may be selectable by a user. One exemplary embodiment of this harmonizing process an accompanying source is described in conjunction with FIGS. **24** and **25**. Each of these figures are illustrated as a data flow diagram (DFD). These diagrams provide a graphical representation of the "flow" of data through an information system, where data items flow from an external data source or an internal data store to an internal data store or an external data sink, via an internal process. These diagrams are not intended to provide information about the timing or ordering of processes, or about whether processes will operate in sequence or in parallel. Also, control signals and processes that convert input control flows into output control flows are generally indicated by dotted lines.

[0164] FIG. **24** depicts that the harmonizer module **146** may generally include a transform note module **2402**, a lead music source **2404**, an accompaniment source **2406**, a chord/key selector **2408** and a controller **2410**. As shown, the transform note module may receive lead music input from the lead music source **2404**; and an accompaniment music input from the accompaniment source **2406**. The lead and accompaniment music may each be comprised of live audio or previously stored audio. In one embodiment the harmonizer module **146** may also be configured to generate the accompaniment music input based on a melody of the lead music input.

[0165] The transform note module **2402** may also receive a musical key and/or a selected chord from the chord/key selector **2408**. The control signal from controller **2410** indicates to transform note module **2402** whether the music output should be based on the lead music input, accompaniment music input and/or musical key or chord from the chord/key selector **2408** and how the transformation should be handled. For instance, as described above, the musical key and chord may be either derived from the lead melody or the accompaniment source or even from the manually selected key or chord indicated by chord/key selector **2408**.

[0166] Based on the control signal, the transform note module **2402** may alternatively transform the lead music input into a note consonant with the chord or the musical key, producing a harmonious output note. In one embodiment, input notes are mapped to harmonious notes using a pre-established consonance metric. In an embodiment discussed in more detail below, the control signal may also be configured to indicate whether one or more "blue-notes" may be allowed in the accompaniment music input without transformation by the transform note module **2402**.

[0167] FIG. **25** illustrates a data flow diagram generally showing more detail of the processes that may be performed by transform note module **2402** of FIG. **24** in selecting notes to "harmonize" with the lead music source **2404**. As shown, the lead musical input is received at process **2502**, where a note of the lead melody is determined. In one embodiment, a note of the lead melody may be determined using one of the techniques described, such as converting the lead musical input into a morphology that identifies its onset, duration, and

pitch, or any subset or combination thereof. Of course, as would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, other methods of determining a note from the lead melody may be used. For example, if the lead music input is already in MIDI format, determining a note may simply include extracting a note from the MIDI stream. As notes of the lead melody are determined, they are stored in a lead music buffer **2510**. Proposed accompaniment musical input is received at process **2504** from accompaniment source **2406** (as shown in FIG. **24**). Process **2504** determines a note of accompaniment and may extract the MIDI note from the MIDI stream (where available), convert the musical input into a morphology that identifies its onset, duration, and pitch, or any subset or combination thereof or use another methodology that would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them.

[0168] At process **2506**, a chord of the lead melody may be determined from the notes found in lead music buffer **2516**. The chord of the lead melody may be determined by analyzing notes in the same manner forth in association with FIG. **17** above or by using another methodology understood by those of ordinary skill in the art (such as a chord progression analysis using a Hidden Markov Model as performed by Chord Matcher **154** described below). The timing of the notes as well as the notes, themselves, may be analyzed (among other potential considerations, such as genre) to determine the current chord of the lead melody. Once that chord has been determined its notes are passed to transform note **2510** to await potential selection by the control signal from control consonance **2514**.

[0169] At process **2508** of FIG. **25**, the musical key of the lead melody may be determined. In one embodiment, the process described with reference to FIG. **16** above may be used to determine the key of the lead melody. In other embodiments, statistical techniques including the use of a Hidden Markov Model or the like may be used to determine a musical key from the notes stored in the lead music buffer. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, other methods of determining a musical key are similarly contemplated, including but not limited to combinations of process **1600** and the use of statistical techniques. The output of process **2508** is one of many inputs to transform note **2510**.

[0170] Process **2510** (FIG. **25**) "transforms" the note used as accompaniment. The transformation of the accompaniment musical note input into process **2510** is determined by the output of control consonance **2514** (discussed in some detail below). Based on the output of control consonance **2514**, the transform note process **2510** may select between (a) the note input from process **2504** (which is shown in FIG. **24** as having received the accompaniment music input from the accompaniment source **2406**); (b) one or more notes from the chord (which is shown in FIG. **24** as having been received from chord/key selector **2408**); (c) a note from the selected musical key (the identity of the key having been received from chord/key selector **2408** (as shown in FIG. **24**)); (d) one or more notes from the chord input from process **2506** (which is shown as having been based on the notes and musical key determined from the notes in the lead music buffer **2516**); or (e) the musical key determined from the notes in the lead music buffer **2516** by process **2508**.

[0171] At process **2512**, the transformed note may be rendered by modifying the note of accompaniment musical input and modifying the timing of the note of accompaniment musical input. In one embodiment, the rendered note is played audibly. Additionally or alternatively, the transformed note may also be rendered visually.

[0172] Control consonance **2514** represents a collection of decisions that the process makes based on one or more inputs from one or more sources that control the selection of notes made by transform note process **2510**. Control consonance **2514** receives a number of input control signals from controller **2410** (see FIG. **24**), which may come directly from user input (perhaps from a graphical user input or preset configuration), from harmonizer module **146**, genre matcher module **152** or another external process. Among the potential user inputs that may be considered by control consonance **2514** are user inputs that require the output note to be (a) constrained to the chord selected via chord/key selector **2408** (see FIG. **24**); (b) constrained to the key selected via chord/key selector **2408** (see FIG. **24**); (c) in harmony with the chord or key selected by **2408** (see FIG. **24**); (d) constrained to the chord determined by process **2506**; (e) constrained to the key determined by process **2508**; (f) in harmony with the chord or key determined from the lead notes; (g) constrained within a certain range of tones (e.g. below middle C, within two octaves of middle C, etc.); and/or (h) constrained within a certain selection of tones (i.e. minor, augmented, etc.).

[0173] Another input to control consonance **2514** is the consonance metric, which is essentially a feedback path from the transform note process **2510**. First, "consonance" is generally defined as sounds that make for pleasant harmony with respect to some base sound. Consonance can also be thought of as the opposite of dissonance (which includes any sounds used freely even if they are inharmonious). So, if an end user has caused control signals to be fed into control consonance **2514** via controller **2410** that constrained the output note from transform note process **2510** to the chord or key manually selected via chord/key selector **2408**, then it is possible that one or more of the output notes were inharmonious to the lead music buffer **2516**. An indication that the output note was inharmonious (i.e. the consonance metric) will be ultimately fed back to control consonance **2514**. While, control consonance **2514** is designed to force the output note track generated by transform note **2510** back into consonance with the lead music due to inherent latencies in feedback and programming systems, a number of inharmonious notes are expected to be allowed through into the music output. In fact, allowing at least some inharmonious notes and even inharmonious rifts in the music produced by the system should facilitate the system **50** making a less mechanical sounding form of musical composition, something desired by the inventors.

[0174] In one embodiment, another control signal that may also be input into control consonance **2514** indicates whether one or more "blue-notes" may be allowed in the music output. As noted above, the term "blue note" for purposes of this specification is given a broader meaning than its ordinary use in blues music as a note that is not in a correct musical key or chord, but which is allowed to be played without transformation. In addition to the harnessing the latencies of the system to provide some minimal insertion of "blue notes," one or more blues accumulators (preferably software coded rather than hard wired) may be used to provide some additional leeway for blue-notes. So, for example, one accumulator can be used to limit the number of blue-notes within a single

partition, another accumulator can be used to limit the number of blue-notes in adjacent partitions, still another accumulator can be used to limit the number of blue-notes per some predetermined time interval or total number of notes. In other words, control consonance via the consonance metric may be counting any one or more of the following: elapsing time, the number of blue-notes in the music output, the number of total notes in the music output, the number of blue-notes per partition, etc. Pre-determined, automatically determined, and real-time determined/adjusted ceilings can be programmed in real-time or as preset/predetermined values. These values may also be affected by the genre of the current composition.

[0175] In one embodiment, the system **100** may also include a super keyboard for providing an accompaniment music source. The super keyboard may be a physical hardware device, or a graphical representation that is generated and displayed by a computing device. In either embodiment, super keyboard may be thought of as the manual input for chord/key selector **2408** of FIG. **24**. The super keyboard preferably includes at least one row of input keys on a keyboard that dynamically maps to notes that are in musical key and/or that are in chord (that is, part of the chord) with respect to the existing melody. A super keyboard may also include a row of input keys that are inharmonious to the existing melody. However, inharmonious input keys pressed on the super keyboard may then be dynamically mapped to notes that are in the musical key of the existing melody, or to notes that are chord notes for the existing melody.

[0176] One embodiment of a super keyboard in accordance with the present invention is illustrated in FIG. **26**. The embodiment illustrated in FIG. **26** is shown with respect to the notes for a standard piano, although it would be understood that the super keyboard may be used for any instrument. In embodiment shown in FIG. **26**, the top row **2602** of input keys of a super keyboard maps onto standard piano notes; the middle row **2604** maps onto notes that are in a musical key for the existing melody; and the bottom row **2606** maps onto notes that are within the current chord. More particularly, the top row exposes **12** notes per octave as in a regular piano, the middle row exposes eight notes per octave, and the bottom row exposes three notes per octave. In one embodiment, the color of each input key in the middle row may depend on the current musical key of the melody. As such, when the musical key of the melody changes, the input keys that were chosen to be displayed in the middle row also change. In one embodiment, if an inharmonious musical note is entered by the user from the top row, the super keyboard may also be configure to automatically play a harmonious note instead. In this way, the player can accompany lead music in an increasingly constrained manner the lower the row he chooses. However, other arrangements are also envisioned.

[0177] FIG. **27**A illustrates one embodiment of a chord selector in accordance with the present invention. In this embodiment, the chord selector may comprise a graphical user interface of a chord wheel **2700**. The chord wheel **2700** depicts chords that are in musical key with respect to the existing melody. In one embodiment, the chord wheel **2700** displays chords derived from the currently selected musical key. In one embodiment, the currently selected musical key is determined by the melody, as discussed above. Additionally or alternatively, the outermost concentric circle of the chord wheel provides a mechanism to select a musical key. In one embodiment, a user may input a chord via chord/key selector **2408**, by selecting a chord from the chord wheel **2700**.

[0178] In one embodiment, the chord wheel **2700** depicts seven chords related to the currently selected musical key—three major chords, three minor chords, and one diminished chord. in this embodiment, the diminished chord is located at the center of the chord wheel; the three minor chords surround the diminished chord; and the three major chords surround the three minor chords. In one embodiment, a player is enabled to select a musical key using the outermost concentric circle, wherein each of the seven chords depicted by the chord wheel are determined by the selected musical key.

[0179] FIG. **27**B illustrates another potential embodiment of a chord selector in accordance with the present invention at a particular instant during operation of system **50**. In this embodiment, the chord selector may comprise a chord flower **2750**. Like chord wheel **2700**, chord flower **2750** depicts at least a sub-set of the chords that fall musically within the current musical key of the current audio track. And Chord flower **2750** also indicates the chord currently being played. In the example illustrated in FIG. **27**B, the key is C major (as can be determined from the identity of the major and minor chords included on the flower petals and in the center) and the currently played chord is indicated by the chord depicted in the center, which in the illustrated time of playback is C major. The chord flower **2750** is arranged to provide visual cues as to the probability of any depicted chord following immediately after the currently played chord. As depicted in FIG. **27**B, the most likely chord progression would be from the currently playing C major to G major, the next most likely progression would be to F major, followed in likelihood by A minor. In this sense, the likelihood that any chord will follow another is not a rigorous probability in the mathematical sense but rather a general concept of the frequency of a certain chord progressions in particular genres of music. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, when the lead track results in the calculation of a different chord, then chord flower **2750** will change. For example, lets say that the next partition of the lead musical track is actually determined to correspond to B-flat major, then the center of the flower would show an upper-case B with a flat symbol. In turn, the other chord found in the key of C major will "rotate" about the B-flat into an arrangement that indicates the relatively likelihood that any particular chord is the next in the progression.

[0180] Track Sharer Module

[0181] Returning to the diagram of system **100** in FIG. **1**A, track sharer module **148** may enable transmission and receipt of tracks or multi-track recordings for system **100**. In one embodiment, such tracks may be transferred or received from a remote device or server. The track sharer module **148** may also perform administrative operations related to the sharing of tracks, such as enabling account login and exchange of payment and billing information.

[0182] Sound Searcher Module

[0183] Sound searcher module **150**, also shown in FIG. **1**A, may implement operations related to finding a previously recorded track or multi-track recording. For example, based on an audible input, the Sound Searcher Module **150** may search for similar tracks and/or multi-track recordings that were previously recorded. This search may be performed on a particular device **50** or on other, networked devices or servers. The results of this search may then be presented via the device and a track or multi-track recording may be sub-

sequently accessed, purchased, or otherwise acquired for use on device **50** or otherwise within the system **100**.

[0184] Genre Matcher Module

[0185] Genre Matcher Module **152**, also shown in FIG. **1**A, is configured to identify chord sequences and beat profiles that are common to a genre of music. That is, a user may input or select a particular genre or an exemplary band that has an associated genre to Genre Matcher Module **152**. The processing for each recorded track may then be preformed by applying one or more traits of the indicated genre with each generated audio track. For example, if a user indicate "jazz" as the desired genre, the quantization of a recorded audible input may be applied such that the timing of beats may tend to be syncopated. Also, the resulting chords generated from the audible input may comprise be one or more chords that are that are traditionally associated with jazz music. Furthermore, the number of "blue notes" may be higher than would be allowed in lets say a classical piece.

[0186] Chord Matcher Module

[0187] Chord Matcher **154** provides pitch and chord related services. For example, Chord Matcher **154** may perform intelligent pitch correction of a monophonic track. Such a track may be derived from an audible input and pitch correction may include modifying a frequency of the input to align the pitch of the audible input with a particular, predetermined frequency. The Chord Matcher **154** may also build and refine an accompaniment to an existing melody included in a previously recorded multi-track recording.

[0188] In one embodiment, Chord Matcher **154** may also be configured to dynamically identify the probability of appropriate future chords for an audio track based on the previously played chords. In particular, Chord Matcher **142** may, in one embodiment, include a database of music. Using a Hidden Markov Model in conjunction with this database, the probabilities for a future progression of chords may then be determined based on the previous chords occurring in the audio track.

[0189] Network Environment

[0190] As discussed above, device **50** may be any device capable of performing the processes described above, and need not be networked to any other devices. Nevertheless, FIG. **28** shows components of one potential embodiment of a network environment in which the invention may be practiced. Not all the components may be required to practice the invention, and variations in the arrangement and type of the components may be made without departing from the spirit or scope of the invention.

[0191] As shown, system **2800** of FIG. **28** includes local area networks ("LANs")/wide area networks ("WANs")-(network) **2806**, wireless network **2810**, client devices **2801-2805**, Music Network Device (MND) **2808**, and peripheral input/output (I/O) devices **2811-2813**. Any one or more of client devices **2801-2805** may be comprised of a device **100** as described above. Of course, while several examples of client devices are illustrated, it should be understood that, in the context of the network disclosed in FIG. **28**, client devices **2801-2805** may include virtually any computing device capable of processing audio signals and sending audio-related data over a network, such as network **2806**, wireless network **2810**, or the like. Client devices **2803-2805** may also include devices that are configured to be portable. Thus, client devices **2803-2805** may include virtually any portable computing device capable of connecting to another computing device and receiving information. Such devices include portable devices such as, cellular telephones, smart phones, display pagers, radio frequency (RF) devices, infrared (IR) devices, Personal Digital Assistants (PDAs), handheld computers, laptop computers, wearable computers, tablet computers, integrated devices combining one or more of the preceding devices, and the like. As such, client devices **2803-2805** typically range widely in terms of capabilities and features. For example, a cell phone may have a numeric keypad and a few lines of monochrome LCD display on which only text may be displayed. In another example, a web-enabled mobile device may have a multi-touch sensitive screen, a stylus, and several lines of color LCD display in which both text and graphics may be displayed.

[0192] Client devices **2801-2805** may also include virtually any computing device capable of communicating over a network to send and receive information, including track information and social networking information, performing audibly generated track search queries, or the like. The set of such devices may include devices that typically connect using a wired or wireless communications medium such as personal computers, multiprocessor systems, microprocessor-based or programmable consumer electronics, network PCs, or the like. In one embodiment, at least some of client devices **2803-2805** may operate over wired and/or wireless network.

[0193] A web-enabled client device may also include a browser application that is configured to receive and to send web pages, web-based messages, and the like. The browser application may be configured to receive and display graphics, text, multimedia, and the like, employing virtually any web-based language, including a wireless application protocol messages (WAP), and the like. In one embodiment, the browser application is enabled to employ Handheld Device Markup Language (HDML), Wireless Markup Language (WML), WMLScript, JavaScript, Standard Generalized **25** Markup Language (SMGL), HyperText Markup Language (HTML), eXtensible Markup Language (XML), and the like, to display and send various content: In one embodiment, a user of the client device may employ the browser application to interact with a messaging client, such as a text messaging client, an email client, or the like, to send and/or receive messages.

[0194] Client devices **2801-2805** also may include at least one other client application that is configured to receive content from another computing device. The client application may include a capability to provide and receive textual content, graphical content, audio content, and the like. The client application may further provide information that identifies itself, including a type, capability, name, and the like. In one embodiment, client devices **3001-3005** may uniquely identify themselves through any of a variety of mechanisms, including a phone number, Mobile Identification Number (MIN), an electronic serial number (ESN), or other mobile device identifier. The information may also indicate a content format that the mobile device is enabled to employ. Such information may be provided in a network packet, or the like, sent to MND **108**, or other computing devices.

[0195] Client devices **2801-2805** may further be configured to include a client application that enables the end-user to log into a user account that may be managed by another computing device, such as MND **2808**, or the like. Such a user account, for example, may be configured to enable the end-user to participate in one or more social networking activities, such as submit a track or a multi-track recording, search for tracks or recordings similar to an audible input, download a

track or recording, and participate in an online music community, particularly one centered around the sharing, review, and discussion of produced tracks and multi-track recordings. However, participation in various networking activities may also be performed without logging into the user account.

[0196] In one embodiment, a musical input comprising the melody may be received by client devices **2801-2805** over network **2806** or **2810** from MND **3008**, or from any other processor-based device capable of transmitting such a musical input. The musical input containing the melody may be pre-recorded or captured live by MND **2808** or other such processor-based device. Additionally or alternatively, the melody may be captured in real-time by client devices **2801-2805**. For example, a melody generating device may generate a melody, and a microphone in communication with one of client devices **2801-2805** may capture the generated melody. If the music input is captured live, the system typically seeks at least one bar of music before the musical key and chords of the melody are calculated. This is analogous to musicians playing in a band, where an accompanying musician may typically listen to at least one bar of a melody to determine the musical key and chords being played before contributing any additional music.

[0197] In one embodiment, the musician may interact with client devices **2801-2805** in order to accompany a melody, treating a client device as a virtual instrument. Additionally or alternatively, the musician accompanying the melody may sing and/or play a musical instrument, such as user played instrument, to accompany a melody.

[0198] Wireless network **2810** is configured to couple client devices **2803-2805** and its components with network **2806**. Wireless network **2810** may include any of a variety of wireless sub-networks that may further overlay stand-alone ad-hoc networks, and the like, to provide an infrastructure-oriented connection for client devices **2803-2805**. Such sub-networks may include mesh networks, Wireless LAN (WLAN) networks, cellular networks, and the like. Wireless network **2810** may further include an autonomous system of terminals, gateways, routers, and the like connected by wireless radio links, and the like. These connectors may be configured to move freely and randomly and organize themselves arbitrarily, such that the topology of wireless network **2810** may change rapidly.

[0199] Wireless network **2810** may further employ a plurality of access technologies including 2nd (2G), 3rd (3G), 4th (4G) generation radio access for cellular systems, WLAN, Wireless Router (WR) mesh, and the like. Access technologies such as 2G, 3G, 4G and future access networks may enable wide area coverage for mobile devices, such as client devices **2803-2805** with various degrees of mobility. For example, wireless network **2810** may enable a radio connection through a radio network access such as Global System for Mobil communication (GSM), General Packet Radio Services (GPRS), Enhanced Data GSM Environment (EDGE), Wideband Code Division Multiple Access (WCDMA), and the like. In essence, wireless network **2810** may include virtually any wireless communication mechanism by which information may travel between client devices **2803-2805** and another computing device, network, and the like.

[0200] Network **2806** is configured to couple network devices with other computing devices, including, MND **2808**, client devices **2801-2802**, and through wireless network **2810** to client devices **2803-2805**. Network **2806** is enabled to employ any form of computer readable media for communicating information from one electronic device to another. Also, network **106** can include the Internet in addition to local area networks (LANs), wide area networks (WANs), direct connections, such as through a universal serial bus (USB) port, other forms of computer-readable media, or any combination thereof. On an interconnected set of LANs, including those based on differing architectures and protocols, a router acts as a link between LANs, enabling messages to be sent from one to another. In addition, communication links within LANs typically include twisted wire pair or coaxial cable, while communication links between networks may utilize analog telephone lines, full or fractional dedicated digital lines including T**1**, T**2**, T**3**, and T**4**, Integrated Services Digital Networks (ISDNs), Digital Subscriber Lines (DSLs), wireless links including satellite links, or other communications links known to those skilled in the art. Furthermore, remote computers and other related electronic devices could be remotely connected to either LANs or WANs via a modem and temporary telephone link. In essence, network **2806** includes any communication method by which information may travel between computing devices.

[0201] In one embodiment, client devices **2801-2805** may directly communicate, for example, using a peer to peer configuration.

[0202] Additionally, communication media typically embodies computer-readable instructions, data structures, program modules, or other transport mechanism and includes any information delivery media. By way of example, communication media includes wired media such as twisted pair, coaxial cable, fiber optics, wave guides, and other wired media and wireless media such as acoustic, RF, infrared, and other wireless media.

[0203] Various peripherals, including I/O devices **2811-2813** may be attached to client devices **2801-2805**. Multi-touch, pressure pad **2813** may receive physical inputs from a user and be distributed as a USB peripheral, although not limited to USB, and other interface protocols may also be used, including but not limited to ZIGBEE, BLUETOOTH, or the like. Data transported over an external and the interface protocol of pressure pad **2813** may include, for example, MIDI formatted data, though data of other formats may be conveyed over this connection as well. A similar pressure pad **2809** may alternately be bodily integrated with a client device, such as mobile device **2805**. A headset **2812** may be attached to an audio port or other wired or wireless I/O interface of a client device, providing an exemplary arrangement for a user to listen to looped playback of a recorded track, along with other audible outputs of the system. Microphone **2811** may be attached to a client device **2801-2805** via an audio input port or other connection as well. Alternately, or in addition to headset **2812** and microphone **2811**, one or more other speakers and/or microphones may be integrated into one or more of the client devices **2801-2805** or other peripheral devices **2811-2813**. Also, an external device may be connected to pressure pad **2813** and/or client devices **101-105** to provide an external source of sound samples, waveforms, signals, or other musical inputs that can be reproduced by external control. Such an external device may be a MIDI device to which a client device **2803** and/or pressure pad **2813** may route MIDI events or other data in order to trigger the playback of audio from external device **2814**. However, formats other than MIDI may be employed by such an external device.

[0204] FIG. **30** shows one embodiment of a network device **3000**, according to one embodiment. Network device **3000** may include many more or less components than those shown. The components shown, however, are sufficient to disclose an illustrative embodiment for practicing the invention. Network device **3000** may represent, for example, MND **2808** of FIG. **28**. Briefly, network device **3000** may include any computing device capable of connecting to network **2806** to enable a user to send and receive tracks and track information between different accounts. In one embodiment, such track distribution, or sharing, is also performed between different client devices, which may be managed by different users, system administrators, business entities, or the like. Additionally or alternatively, network device **3000** may enable sharing a tune, including melody and harmony, produced with client devices **2801-2805**. In one embodiment, such melody or tune distribution, or sharing, is also performed between different client devices, which may be managed by different users, system administrators, business entities, or the like. In one embodiment, network device **3000** also operates to automatically provide a similar "best" musical key and/or chord for a melody from a collection of musical keys and/or chords.

[0205] Devices that may operate as network device **3000** include various network devices, including, but not limited to personal computers, desktop computers, multiprocessor systems, microprocessor-based or programmable consumer electronics, network PCs, servers, network appliances, and the like. As shown in FIG. **30**, network device **3000** includes processing unit **3012**, video display adapter **3014**, and a mass memory, all in communication with each other via bus **3022**. The mass memory generally includes RAM **3016**, ROM **3032**, and one or more permanent mass storage devices, such as hard disk drive **3028**, tape drive, optical drive, and/or floppy disk drive. The mass memory stores operating system **3020** for controlling the operation of network device **3000**. Any general-purpose operating system may be employed. Basic input/output system ("BIOS") **3018** is also provided for controlling the low-level operation of network device **3000**. As illustrated in FIG. **30**, network device **3000** also can communicate with the Internet, or some other communications network, via network interface unit **3010**, which is constructed for use with various communication protocols including the TCP/IP protocol. Network interface unit **3010** is sometimes known as a transceiver, transceiving device, or network interface card (NIC).

[0206] The mass memory as described above illustrates another type of computer-readable media, namely'computer-readable storage media. Computer-readable storage media may include volatile, nonvolatile, removable, and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, or other data. Examples of computer readable storage media include RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by a computing device.

[0207] As shown, data stores **3052** may include a database, text, spreadsheet, folder, file, or the like, that may be configured to maintain and store user account identifiers, email addresses, IM addresses, and/or other network addresses; group identifier information; tracks or multi-track recordings associated with each user account; rules for sharing tracks and/or recordings; billing information; or the like. In one embodiment, at least some of data store **3052** might also be stored on another component of network device **3000**, including, but not limited to cd-rom/dvd-rom **3026**, hard disk drive **3028**, or the like.

[0208] The mass memory also stores program code and data. One or more applications **3050** are loaded into mass memory and run on operating system **3020**. Examples of application programs may include transcoders, schedulers, calendars, database programs, word processing programs, HTTP programs, customizable user interface programs, IPSec applications, encryption programs, security programs, SMS message servers, IM message servers, email servers, account managers, and so forth. Web server **3057** and Music Service **3056** may also be included as application programs within applications **3050**.

[0209] Web server **3057** represent any of a variety of services that are configured to provide content, including messages, over a network to another computing device. Thus, web server **3057** includes for example, a web server, a File Transfer Protocol (FTP) server, a database server, a content server, or the like. Web server **3057** may provide the content including messages over the network using any of a variety of formats, including, but not limited to WAP, HDML, WML, SMGL, HTML, XML, cHTML, xHTML, or the like. In one embodiment, web server **3057** may be configured to enable a user to access and manage user accounts and shared tracks and multi-track recordings.

[0210] Music Service **3056** may provide various functions related to enabling an online music community and may further include a Music Matcher **3054** a Rights Manager **3058**, and melody data. The Music Matcher **3054** may match similar tracks and multi-track recordings, including those stored in data stores **3052**. In one embodiment, such matching may be requested by Sound Searcher or MTAC on a client device which may, for example, provide an audible input, track, or multi-track to be matched. Rights Manager **3058** enables a user associated with an account to upload tracks and multi-track recordings. Such tracks and multi-track recordings may be stored in one or more data stores **3052**. The Rights Manager **3058** may further enable a user to provide controls for the distribution of provided tracks and multi-track recordings, such as restrictions based on a relationship or membership in the online music community, a payment, or an intended use of a track or multi-track recording. Using Rights Manager **3058**, a user may also restrict all access rights to a stored track or multi-track recording, thereby enabling an unfinished recording or other work-in-progress to be stored without community review before the user believes it to be ready.

[0211] Music Service **3056** may also host or otherwise enable single or multiplayer games to be played by and among various members of the online music community. For example, a multi-user role playing game hosted by Music Service **3056** may be set in the music recording industry. Users may select a role for their character that is typical of the industry. A game user may then progress their character through the creation of music using their client device **50** and, for example, RSLL **142**, and MTAC **144**.

[0212] Messaging server **3056** may include virtually any computing component or components configured and arranged to forward messages from message user agents,

and/or other message servers, or to deliver messages. Thus, messaging server **3056** may include a message transfer manager to communicate a message employing any of a variety of messaging protocols, including, but not limited, to SMS messages, IM, MMS, IRC, RSS feeds, mIRC, any of a variety of text messaging protocols, or any of a variety of other message types. In one embodiment, messaging server **3056** may enable users to initiate and/or otherwise conduct chat sessions, VOIP sessions, text messaging sessions, or the like.

[0213] It is noted that while network device **3000** is illustrated as a single network device, the invention is not so limited. For example, in another embodiment, a music service, or the like, of network device **3000** may reside in one network device, while an associated data store might reside in another network device. In still another embodiment, various music and/or message forwarding components might reside in one or more client devices, operate in a peer-to-peer configuration, or the like.

[0214] Gaming Environment

[0215] To further facilitate the creation and composition of music, FIGS. **31-37** illustrate an embodiment in which a gaming interface is provided as the user interface to the music compilation tools described above. In this manner, it is believed that the user interface will be less intimidating, more user-friendly so as to minimize any interference with an end user's creative musical process. As will be apparent from the following discussion, the gaming interface provides visual cues and indicia that are associated with one or more functional aspects described above in order to simplify, streamline, and incentivise the music compilation process. This enables end users (also referred to with respect to this embodiment as "players") to utilize professional quality tools to create professional quality music without requiring those users to have any expertise in music theory or the operation of music creation tools.

[0216] Turning first to FIG. **31**, one exemplary embodiment of a first display interface **3100** is provided. In this interface, the player may be provided a studio view from the perspective of a music producer sitting behind a mixing board. In the embodiment of FIG. **31**, three different studio rooms are then visualized in the background: a lead vocal/instrument room **3102**, a percussion room **3104**, and an accompaniment room **3106**. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, the number of rooms could be greater or fewer, the functionality provided in each room may be sub-divided differently and/or additional options may be provided in the rooms. Each of the three rooms depicted in FIG. **3**I may include one or more musician "avatars" that provide visual cues that illustrate the nature and/or purpose of the room, as well as to provide further cues as to the genre, style, and/or nuanced performance of music performed by the "avatars" and the variety of instruments being utilized. For example, in the embodiment illustrated in FIG. **31**, the lead vocal/instrument room **3102** includes a female pop singer, the accompaniment room **3104** includes a rock drummer, and the accompaniment room **3106** includes a country violinist, a rock bass player, and a hip-hop electric keyboard player. As will be discussed in more detail below, the selection of musician avatars, in conjunction with other aspects of the gaming environment interface, provides a visual, easy to understand, interface by which various tools described above can be readily implemented by the most novice of end users.

[0217] To begin creating music, the player may select one of these rooms. In one embodiment, the user may simply select the room directly using a mouse or other input device. Alternatively, one or more buttons may be provided that correspond to the various studio rooms. For example, in the embodiment illustrated in FIG. **31**, selection of a lead room button **3110** will transfer the player to the lead vocal/instrument room **3102**, selection of a percussion room button **3108** will transfer the player to the percussion room **3104**; and selection of an accompaniment room button **3112** will transfer the player to the accompaniment room **3106**.

[0218] Other selectable buttons may also be provided, as shown in FIG. **31**. For instance, a record button **3116** and a stop button **3118** may be provided to start and stop the recording of any music made by the end user in studio room **3100** via the recording session live looping module **142** (FIG. **1**A). A settings button **3120** may be provided to permit the player to alter various settings, such as desired genre, tempo, and rhythm, volume, etc. A search button **3122** may be provided to enable a user to initiate the sound searcher module **150**. Buttons for saving (**3124**) and deleting (**3126**) the player's musical composition may also be provided.

[0219] FIG. **32** presents one exemplary embodiment of a lead vocal/instrument room **3102**. In this embodiment, the interface for this studio room has been configured to enable an end user to create and record one or more lead vocal and/or instrument tracks for a musical compilation. The lead vocal/instrument room **3102** may include a control space **3202** similar to the one described above in conjunction with FIGS. **12-13**. Thus, as described above, the control space **3202** may include a plurality of partition indicators **3204** to identify each of the partitions (e.g. musical measures) in the track; vertical lines **3206** illustrating the beat within each measure, horizontal lines **3208** identifying the various fundamental frequencies associated with a selected instrument (such as a guitar indicated by instrument selector **3214** (shown in FIG. **32**), and a playback bar to identify the specific part of the live loop that is currently being played.

[0220] In the example illustrated in FIG. **32**, the interface illustrates the audio waveform **3210** of one track that has already been recorded, presumably earlier in the session by the player, however, the user may also pull up preexisting audio tracks particularly in conjunction with sound search module **150** (as called by search button **3122** (see FIG. **31**). In the example illustrated in FIG. **32**, the recorded audio waveform **3210** has also been converted into its morphology of the notes **3212** in correspondence to the fundamental frequencies of a guitar, as indicated by instrument selector **3214**. As should be understood, using various instrument selector icons that may be dragged onto control space **3202**, the player may be able to select one or more other instruments, which would cause the original audio waveform to be converted to a different morphology of notes corresponding to the fundamental frequencies of the newly or additionally selected instrument (s). The player may also alter the number of measures, or the number of beats per measure, which may also then cause the audio waveform to be quantized (by quantizer **206** (see FIG. **2**)) and aligned in time with the newly altered timing. It should also be understood that while the player may choose to convert the audio waveform into a morphology of notes associated with an instrument, the player need not do so, thus enabling one or more original sounds from the audible input to be substantially included in the generated audio track with its original timbre.

[0221] As shown in FIG. **32**, an avatar of a singer **3220** may also be provided in the background. In one embodiment, this avatar may provide a readily understandable visual indication of a specific genre of music that has been previously defined in genre matcher module **152**. For instance, in FIG. **32**, the singer is illustrated as a pop singer. In this case, the processing of the recorded track **3210** may be performed by applying one or more traits associated with pop music. In other examples, the singer could be illustrated as a male adult, a young male or female child, a barber-shop quartet, as opera or Broadway diva, a country-western star, a hip-hop musician, a British Invasion rocker, folk singer, etc. with the resulting pitch, rhythms, modes, musical textures, timbres, expressive qualities, harmonies, etc. that people commonly understand to be associated with each type of singer. In one embodiment, to provide additional entertainment value the singer avatar **3220** may be programmed to dance and otherwise act like the avatar is involved in a recording session perhaps even in synchronization with the musical track.

[0222] The lead vocal/instrument room interface **3102** may further include a track selector **3216**. The track selector **3216** enables a user to record or create multiple lead takes and the select one or more of those takes to be included within the musical compilation. For example, in FIG. **32**, three track windows, labeled as "1", "2", and "3" are illustrated, each of which shows a miniature representation of an audio waveform of the corresponding track in order to provide a visual cue as to the audio associated with each track. The track in each track window may represent a separately recorded audio take. However, it should also be understood that copies of an audio track may be created, in which case each track window may represent different instances of a single audio waveform. For instance, track window "1" could represent an unaltered vocal version of the audio waveform, track window "2" could represent the audio waveform as converted into a morphology of notes associated with a guitar, and track window "3" could represent the same audio waveform as converted into a morphology of notes associated with a piano. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, there need be no particular limitation on the number of tracks that may be held on track selector **3216**.

[0223] A track selection window **3218** is provided to enable the player to select one or more of the tracks to be included in the musical compilation by, for example, selecting and dragging one or more of the three track windows to the selection window **3218**. In one embodiment, the selection window **3218** may also be used to engage MTAC module **144** in order to generate a single best take from multiple takes "1" "2" and "3."

[0224] The lead vocal/instrument room interface **3102** may also include a plurality of buttons to enable one or more functions associated with the creation of a lead vocal or instrument track. For instance, a minimize button **3222** may be provided to permit a user to minimize grid **3202**; sound button **3224** may be provided to enable a user to mute or unmute the sound associated with one or more audio tracks, a solo button **3226** may be provided to mute any accompaniment audio that has been generated by the system **100** based on the audio waveform **3210** or its morphology so as to allow the player to concentrate on issues associated with the lead audio, a new track button **3228** may be provided to enable the user to begin recording a new lead track; morphology button **3230** activates the operations of frequency detector and shifter **208** and **210** on the audio waveform in the control space **3202**. A set of buttons may also be provided to enable a user to set a reference tone to aid in providing a vocal track. Thus, toggling tone button **3232** may enable and disable a reference tone, tone up button **3234** may increase the frequency of the reference tone, and tone down button **3236** may decrease the pitch of the reference tone.

[0225] FIG. **33** illustrates one exemplary embodiment of a percussion room **3104**. The interface for this room is configured to enable the player to create and record one or more percussion tracks for the musical compilation. The percussion room interface **3104** includes a control space similar to the one described above in conjunction with FIG. **14**. Thus, the control space may include a grid **3302** that represents the playback and timing of separate sounds within one or more percussion tracks, a playback bar **3304** to identify the specific part of the live loop that is currently being played, and a plurality of partitions (**1-4**) divided into multiple beats, with each box **3306** in the grid representing the timing increments for sounds associated with the related percussion instrument (where an unshaded box indicates that no sound is to be played at that time increment, and a shaded box indicates that a sound associated with the timbre of the related percussion instrument is to be played at that time increment).

[0226] A percussion segment selector **3308** may also be provided in order to enable a player to create and select multiple percussion segments. In the example illustrated in FIG. **33**, only the partitions of a single percussion segment "A" are shown. However, by selecting the percussion segment selector **3308**, additional segments may be created and identified as segments "B", "C" and so on. The player may then create different percussion sequences within each partition of each different segment. The created segments may then be arranged in any order to create a more varied percussion track for use in the musical compilation. For example, a player may desire to create different percussion tracks repetitively played in the following order: "A", "A", "B", "C", "B", although any number of segments may be created and any order may be used. To facilitate review and creation of multiple percussion segments, a segment playback indicator **3310** may be provided to visually indicate the percussion segment that is currently being played and/or edited, as well as the portion of the segment that is being played and/or edited.

[0227] As further illustrated in FIG. **33**, an avatar of a drummer **3320** may also be provided in the background. Similar to the performer avatar described in conjunction with the lead vocal/instrument room **3102**, the drummer avatar **3220** may provide a readily understandable visual indication of a specific genre of music and style of playing that corresponds to a genre that has been previously defined in genre matcher module **152**. For instance, in FIG. **33**, the drummer is illustrated as a rock drummer. In this case, the processing of the created percussion tracks may be performed for each percussion instrument by applying one or more previously defined traits of percussion instruments associated with rock music. In one embodiment, to provide additional entertainment value the drummer avatar **3320** may be programmed to dance and otherwise act like the avatar is involved in a recording session perhaps even in synchronization with the musical track.

[0228] The percussion room interface **3104** may also include a plurality of buttons to enable one or more functions associated with the creation of one or more percussion tracks. For instance, minimize button **3312** may be provided to

enable a user to minimize grid **3302**, a sound button **3314** may be provided to enable a user to mute or unmute the sound associated with one or more audio tracks, solo button **3316** may be provided to enable a user to toggle between mute and unmute to stop playback of the other audio tracks so the player can focus on the percussion track without distraction, additional percussion instrument button **3318** adds an additional sub-track corresponding to a percussion instrument that may be selected by the player, and swing button **3320** permits a user to swing (i.e. syncopate) notes.

[0229] FIGS. **34**A-C present one exemplary embodiment of an accompaniment room interface **3106**. The interface for this studio room is configured to provide the player with a musical pallet from which the user can select and create one or more accompaniment tracks for a musical compilation. For example, as shown in FIG. **34**A, the player may be provided with an instrument class selector bar **3402** to enable the player to select a class of instrument to accompany the lead vocal and/or musical tracks. In the illustrated embodiment, three classes are illustrated for selection—base **3404**, keyboard **3406**, and guitar **3408**. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, any number of instrument classes may be provided including a variety of instruments, including brass, woodwinds, and strings.

[0230] For illustration purposes, let us assume that the player has selected the bass class **3404** in FIG. **34**A. In that case, the player is then provided with an option to select among one or more musician avatars to play the accompanying instrument. For example, as shown in FIG. **34**B, the player may be provided with the option to select between a country musician **3410**, a rock musician **3412**, and a hip-hop musician **3414**, which the player may then select by clicking directly on the desired avatar. Of course, while three avatars are illustrated, the player may be permitted to select between more or less choices. Arrows **3416** may also be provided to enable the player to scroll through the avatar choices, especially where more avatars choices are provided.

[0231] After selecting a musician avatar in FIG. **34**B, the player may then be provided with an option to select a specific instrument. For example, let us now assume that the player has selected the country musician. As shown in FIG. **34**C, the player may then be given the option to select among an electric bass guitar **3418**, a standing bass **3420**, or an acoustic bass guitar **3422**, which the player may then select by clicking directly on the desired instrument. Arrows **3424** may also be provided to enable the player to scroll through the instrument choices, which as would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, may not be limited to only three types of bass instruments. Of course, while in the above sequence the instrument class is selected prior to selecting a musician avatar, it is contemplated that a player may be provided with the option to select a musician avatar before selecting a class of instrument. Similarly, it is also contemplated that a player may be provided the option to select a specific instrument before selecting a musician avatar.

[0232] After the player has selected a musician avatar, and instrument, system **100** creates an appropriate accompaniment track by generating a set of accompaniment notes based on the one or more lead tracks currently being played in the lead vocal/instrument room **3102** (even if the other rooms are muted), converting those notes to the appropriate genre, timbre, and musical style for the selected musician and instrument utilizing genre matcher module **152** and harmonizer module **146** to harmonize the one or more lead tracks. Thus, an accompaniment track for a specific instrument may have different sound, timing, harmony, blue note content, and the like depending on instrument and musician avatar chosen by the player.

[0233] The accompaniment room interface **3106** is also configured to enable the player to individually audition each of the multiple musician avatars and/or multiple instruments to aid in the selection of a preferred accompaniment track. As such, once a musical instrument and avatar have been selected by the user and the corresponding accompaniment track has been created as described above, the accompaniment track is automatically played in conjunction with other previously created tracks (lead, percussion, or accompaniment) during a live loop playback so that the player can, in virtually real time, assess whether the new accompaniment track is a good fit. The player may then choose to keep the accompanying track, select a different musician avatar for the same instrument, select a different instrument for the same musician avatar, pick an entirely new avatar and instrument, or delete the accompaniment track altogether. The player may also create multiple accompaniment tracks by repeating the steps described above.

[0234] FIG. **35** illustrates one potential embodiment of a graphical interface that depicts the chord progression playing as accompaniment of the lead music. In one embodiment, this graphical user interface may be launch by pressing the flower button shown in FIGS. **34**A, **34**B, and **34**C. In particular, this interface shows the chord progression that is generally being forced onto the multiple accompanying avatars in accompaniment room **3106** subject to any blue note allowances (due to genre and other issues discussed above in association with FIG. **25**) that the avatar may have built into its associated configuration file. Each avatar may also have certain arpeggio techniques (i.e. broken chords played in a sequence) that are associated with the avatar because of the avatar's genre or based on other attributes of the avatar. As depicted in the example of FIG. **35**, the chord progression is "G" major, "A" minor, "C" major, "A" minor, with each chord being played for the entirety of a partition in accord with the technique individually associated with each accompanying avatar in accompaniment room **3106**. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, the chord progression may change chords multiple times within a single partition or may remain the same chord over a plurality of partitions.

[0235] FIG. **36** illustrates one exemplary interface by which a player can identify the portion of a musical composition the player desires to create or edit. For instance, in the exemplary interface shown in FIG. **36**, a tabbed structure **3600** is provided in which the player can select between an intro section, a verse section, and a chorus section of a musical composition. Of course, it should be understood that other portions of a musical composition may also be available, such as a bridge, an outro, and the like. The portions that are made available for editing in a particular musical composition may be predetermined, manually selected by the player, or automatically set based on a selected genre of music. The order in which the various portions are ultimately arranged to form a musical composition may similarly be predetermined, manually selected by the player, or automatically set based on a selected genre of music. So, for instance, if a novice user choose to create a pop song, tabbed structure **3600** may be

pre-populated with the expected elements of a pop composition, which generally include an introduction, one or more versus, a chorus, a bridge and a conclusion. The end user may then be prompted to create music associated with a first aspect of this overall composition. After completing the first aspect of the overall composition, the end user may be directed to create another aspect. Each aspect individually and/or collective may be scored to warn an end user if the key of adjacent elements is different. As would be understood by those of ordinary skill in the art having the present specification, drawings and claims before them, using standard graphical user interface manipulation techniques, portions of the composition may be deleted, moved to other portions of the composition, copied and subsequently modified, and the like.

[0236] As shown in FIG. **36**, the tab for each portion of a musical compilation may also include selectable icons to enable a player to identify and edit audio tracks associated with that portion, where a first row may illustrate the lead track, the second row may illustrate the accompaniment track, and the third row may illustrate the percussion tracks. In the illustrated example, the intro section is shown as including keyboard and guitar lead tracks (**3602** and **3604**, respectively); guitar, keyboard, and bass accompaniment tracks (**3606**, **3608**, and **3610**, respectively); and a percussion track **3612**. A chord selector icon **3614** may also be provided that, when selected, provides the player with an interface (such as in FIG. **27** or FIG. **35**) that allows the player to alter the chords associated with the accompaniment tracks.

[0237] FIGS. **37**A and **37**B illustrate one embodiment of a file structure that may be provided for certain visual cues utilized in the graphical interface described above and stored in data storage **132**. Turning first, to FIG. **37**A, a file **3700**, also referred to herein as a musical asset, may be provided for each musician avatar that is player selectable within the graphical interface. For example, in FIG. **37**A, the top musical asset illustrated is for a hip-hop musician. In this embodiment, the musical asset may include visual attributes **3704** that identify the graphical look of the avatar that is to be associated with the musical asset. The musical asset may also include one or more functional attributes that are associated with the musical asset and which, upon selection of the musical asset by the player, are applied to an audio track or compilation. The functional attributes may be stored within the musical asset and/or provide a pointer or call to another file, object or process, such as genre matcher **152**. The functional attributes may be configured to affect any of the various setting or selection described above, including but not limited to the rhythm or tempo of a track, constraints on the chords or keys to be used, constraints on available instruments, the nature of the transitions between notes, the structure or progression of a musical compilation, etc. In one embodiment, these functional assets may be based on the genre of music that would be generally associated with the visual representation of the musician. In instances where the visual attributes provide a representation of a specific musician, the functional attributes may also be based on the musical style of that particular musician.

[0238] FIG. **37**B illustrates another set of musical assets **3706** that may be associated with each selectable instrument, which may be a generic type of instrument (i.e. a guitar) or a specific brand and/or model of instrument (i.e. Fender Stratocaster, Rhodes Electric Piano, Wurlitzer Organ) Similar to the musical assets **3700** corresponding to musician avatars, each musical asset **3706** for an instrument may include visual attributes **3708** that identify the graphical look of the instrument that is to be associated with the musical asset, and one or more functional attributes **3710** of that instrument. As above, the functional attributes **3710** may be configured to affect any of the various setting or selection described above. For an instrument, these may include the available fundamental frequencies, the nature of the transition between notes, etc.

[0239] Using the graphical tools and the game based dynamic illustrated in FIGS. **31-37**, novice user will be more readily able to create professional sounding musical compositions that the user will be willing to share with other user for self-enjoyment and even entertainment much the same way the player may listen to commercially produced music. The graphical paradigm provided in the context of a music authoring system in the present specification would work equally well with respect to a variety of creative projects and endeavors that are generally performed by professionals because the level of skill otherwise necessary to produce even a pedestrian product would be too high to accessible to the ordinary person. However, by simplifying the routine tasks, even a novice user can be making professional level projects with intuitive ease.

[0240] The foregoing description and drawings merely explain and illustrate the invention and the invention is not limited thereto. While the specification is described in relation to certain implementation or embodiments, many details are set forth for the purpose of illustration. Thus, the foregoing merely illustrates the principles of the invention. For example, the invention may have other specific forms without departing from its spirit or essential characteristic. The described arrangements are illustrative and not restrictive. To those skilled in the art, the invention is susceptible to additional implementations or embodiments and certain of these details described in this application may be varied considerably without departing from the basic principles of the invention. It will thus be appreciated that those skilled in the art will be able to devise various arrangements which, although not explicitly described or shown herein, embody the principles of the invention and, thus, within its scope and spirit.

What is claimed is:

1. An apparatus for creating a musical composition comprising:

an audio interface operably receiving audio from an audio input device and outputting audio to an audio output device;

an audio converter module operably connected to the audio interface to convert audio received via the audio interface into an audio track; and

a recording session module configured to repeatedly play back a live loop that includes at least a portion of a first audio track, and to add at least a portion of a second audio track to the live loop during the repeated playback.

2. The apparatus of claim **1** wherein the first audio track is a pre-existing track.

3. The apparatus of claim **2** wherein the pre-existing track is a click track.

4. The apparatus of claim **2** wherein the live loop is stored in a data storage medium, and the pre-existing track is a previously recorded live loop.

5. The apparatus of claim **1** wherein the recording session module is configured to add at least a portion of a third audio track to the live loop during playback.

6. The apparatus of claim **5** wherein the third audio track is automatically generated based on one or more musical criteria of the first or second tracks.

7. The apparatus of claim **6** wherein one of the first and second tracks is a percussion track.

8. The apparatus of claim **1** further including a data storage medium that stores at least one of the live loop, the first audio track, and the second audio track.

9. The apparatus of claim **1** further comprising a user interface coupled to the recording session module, the user interface providing a visual representation illustrating the portion of the live loop that is being played.

10. The apparatus of claim **1** wherein the audio converter module includes a track partitioner to divide at least one of the first and second audio tracks into one or more partitions, and wherein the live loop includes at least a subset of the one or more partitions.

11. The apparatus of claim **10** wherein the audio converter further includes a quantizer that is configured to align audio in the least one of the first and second audio tracks in the one or more partitions with a predetermined beat.

12. The apparatus of claim **11** wherein the audio converter further includes a frequency detector that is configured to identify a pitch of one or more sounds within each of the one or more partitions.

13. The apparatus of claim **12** wherein each of the one or more partitions are stored as a morphology having information identifying the onset, pitch, and duration of one or more sounds in the partition.

14. The apparatus of claim **13** where the audio converter module further includes a frequency converter to shift a frequency of the audio track based on one or more criteria.

15. The apparatus of claim **14** wherein the audio converter module further includes an instrument converter configured to convert the audio track into one or more sounds having a timbre associated with a musical instrument.

16. An method for creating a musical composition comprising:

identifying a first audio track;

repeatedly playing back a live loop that includes at least a portion of the first audio track; and

adding at least a portion of a second audio track to the live loop during the repeated playback.

17. The method of claim **16** wherein identifying a first audio track includes obtaining a pre-existing track.

18. The method of claim **16** wherein identifying a first audio track includes generating a click track.

19. The method of claim **16** wherein the second audio track is automatically generated based on one or more criteria of the first audio track.

20. The method of claim **16** wherein one of the first and second tracks is a percussion track.

21. The method of claim **16** further including storing at least one of the live loop, the first audio track, and the second audio track.

22. The method of claim **16** wherein identifying a first audio track includes receiving an audible input via an audio interface, and converting the audio input into an audio track

23. The method of claim **22** wherein converting the audio input includes dividing the audio track into one or more partitions.

24. The method of claim **23** wherein converting the audio input further includes quantizing the one or more partitions with a predetermined beat.

25. The method of claim **24** wherein converting the audio input further includes identifying a pitch of one or more sounds within each of the one or more partitions.

26. The method of claim **25** where converting the audio input further includes shift a frequency of the first audio track based on one or more criteria.

27. The method of claim **26** wherein converting the audio input further includes converting the first audio track into one or more sounds having a timbre associated with a musical instrument.

28. The method of claim **27** further including storing each of the one or more partitions as a morphology having information identifying the onset, pitch, and duration of one or more sounds in the partition.

* * * * *